











CONTENTS

METAL CORE DRILLING			12
Endurance Compact	22 25	Universal Automatic	34 49
DRILLING			64
Drills Rotary hammer drill Angle drills	66 74 75	Tappers Magnetic drill jigs	76 78
FASTENING			82
Drill/Driver Cordless impact wrench/driver AccuTec screw guns with mid-mounted handle	84 90 93	AccuTec baton offset screwdriver Metal screw gun	94 97
GRINDING & POLISHING			98
Angle Grinders Universal Angle Grinders Premium Die Grinders	104 110 120	Sanders Polishers	127 138
SHEET METAL WORKING			144
Nibblers Sheet metal shears	148 160	Slitting shears	164
SAWING & CUTTING			170
Chop saws Pipe Saws	172 173	Beveller Pipe milling machine	177 184
FEIN VersaMAG SYSTEM			186
FEIN VersaMAG	190	Accessories	191
WET / DRY DUST EXTRACTOR			192
Cordless dust extractor	194	Wet / dry dust extractor	196
OSCILLATING MULTI-TOOL			204
MULTIMASTER Starlock accessories MULTIMASTER Automotive	210 217 230	MULTIMASTER joint renovation 12-sided fitting accessories	237 241
BELT GRINDERS			248
GRIT GHB hand-guided belt grinder GRIT GX basic belt grinder for manual trades GRIT GX add-on modules for manual trades	250 253 255	GRIT GI basic belt grinder for industry GRIT GI add-on modules for industry GRIT GKS compact belt grinder	256 259 263
AMPShare BATTERIES & CHARGERS			274
AMPShare batteries	276	AMPShare chargers	277
ACCESSORIES			278
L-BOXX Balancers	280 282	Cordless sealant gun Cordless radio	285 288
NUMERICAL PART			290
Machines in numerical order Accessories in numerical order	292 297	Vibration and noise emission values	346









THE VISION.

As end users demand more and more of their power tools, the market is becoming increasingly more specialised and more segmented. This is why we take the view of not just one market but many attractive sub-markets.

Within the overall power tools market, our vision for the FEIN brand is to become an international leader in metalworking in the industry sectors of steel, metal and container construction, special vehicle and machine construction as well as the construction of infrastructure in selected areas, such as pipework and rail construction.

We are concentrating on being the specialist power tool supplier to end users in these sectors – not just in terms of the tools themselves, but also consumables and accessories. We also see further potential in oscillating power tool technology.

Every action the company takes is a step towards turning this vision into reality.

Through the FEIN brand, we hope to demonstrate in the long term that we can successfully achieve return on sales (ROS) far above average in order to retain our independence as a family-owned business. And we aim to do this in the highly competitive power tool market on the basis of a defined system of values and a product/market strategy derived from this.

Recognising cause and effect relationships, we are fully committed to the idea of "Total Quality Management". To this end, we entrust our employees and managers with a very high level of responsibility and decision-making authority once their personal traits and own results have demonstrated that we can trust them with such powers.



OUR SYSTEM OF VALUES IN 3 GUIDING PRINCIPLES:

- WE STRIVE TO PRODUCE THE BEST SOLUTION FOR OUR CUSTOMERS.
- WE CONSTRUCTIVELY SCRUTINISE WHAT WE HAVE ACHIEVED.
- WE CAREFULLY WEIGH UP THE CONSEQUENCES OF ANY MEASURES WE TAKE. WE ALL CONSISTENTLY SHOULDER RESPONSIBILITY FOR THEM IN OUR WORK.



With FEIN you're in good hands after making your purchase. We have designed our power tools for maximum loading and overload – even when used continuously. Should you ever need our help, we provide speedy, professional and dedicated assistance. That's something you can rely on.

ONLINE PORTAL

One log-in – and the FEIN world of service is at your fingertips. With my.FEIN, we make it easy for you to bundle services in one place and ensure that you always have them to hand. Either with the convenience of the app or online at my.FEIN.com

FEIN SPARE PART

You can easily find the right FEIN spare parts for your FEIN power tool online – using the FEIN spare part catalogue with intuitive search function and exploded views of the products.

3-YEAR FEIN PLUS WARRANTY

Quick registration – extended warranty period: We offer the 3-year FEIN PLUS warranty for all your FEIN power tools. All you need to do is register your new FEIN product at **www.fein.com/warranty** within 3 months of purchase. Here you will find which countries are covered and further information.

MORE FEIN SERVICES ONLINE

On our website, you will find lots more information and service offerings:

- + Operating instructions and brochures available to download
- + FAQ
- + Maintenance information

FEIN REPAIR SERVICE

No matter whether you contact us regarding repairs, maintenance or warranty claims – we process your orders quickly and efficiently through our FEIN authorised repair centres. They hold the right genuine FEIN spare parts in stock – even for many older tools. So you can get back to work as soon as possible.



The **website** also contains **details of services** available locally to you.



Powerful tools in the AMPShare 18 V battery system.

One interface, lots of options: More and more FEIN products can now be run with both BOSCH Professional 18 V batteries (since 2008) and AMPShare batteries. This gives you shorter charge times, more power and fewer different batteries and chargers – for greater clarity and less clutter at the point of use. You can benefit from the advantages of these tools right now. And don't worry, we are already working on more.

Keep your eyes peeled!



CORE DRILLS



ANGLE GRINDERS

DIE GRINDERS

BEVELLING MACHINES

NIBBLERS, SHEET METAL SHEARS, SLITTING SHEARS



RADIOS & EXTRACTORS

FURTHER PRODUCTS

METAL CORE DRILLING



ENDURANCE

Endurance magnetic core drills for drilling, which do not compromise on lifetime or performance.

COMPACT

22

Compact magnetic core drills with minimum dimensions for core drilling in tight and difficult-to-reach spots.



25



34

UNIVERSAL

High-performance universal magnetic core drills with very high quality standards for universal applications.

AUTOMATIC

High-performance, fully automatic auto magnetic core drills for maximum efficiency and minimum physical strain.



The most compact core drill.*

THE KBC 36 MAGFORCE.

COMPACT POWER PACK.

Powerful, long-life and the only compact core drill of its kind anywhere in the world: the brushless FEIN 1200 W high-power motor with impressive speed stability ensures a brand new level of efficiency due to its outstanding work progress.



SURPASSES ITSELF.

With forward and reverse running, electronic speed setting and cutting depths of up to 35 mm, the KBC 36 MAGFORCE is universal and can therefore be used for any project.

ATTRACTED TO CHALLENGES.

Thanks to its integrated tilt sensor, 10 000 N magnetic holding force and convenient magnetic holding force display, the KBC 36 MAGFORCE always delivers incredible results.

THE NEW SIZE.

Tiny installation height of 169 mm, an installation length of just 290 mm and a total weight of only 8.5 kg make the tightest of situations as well as mobile and flexible use your new favourite tasks.

ADDED VALUE FOR YOU



NO SPACE. NO PROBLEM.

The KBC 36 MAGFORCE turns tight and difficult-to-reach work positions into routine jobs.



DON'T WORRY ABOUT REWORK.

Need to rework holes in components or girders which are already being installed? Done in a flash.



COMPACT ALL-ROUNDER.

Whether you are core drilling, twist drilling, tapping or countersinking – the KBC 36 MAGFORCE is equipped for every requirement.




SIMPLE. SAFE.

Optimum view of the drilling point, intuitive operation and secure positioning at the point of use: with the KBC 36 MAGFORCE, you will effortlessly handle tough jobs.



TESTED QUALITY.

Extremely low wear, durable and tested for continuous use: there is a good reason why the most compact core drill in the world with forward and reverse running has our name on its housing.



NOTE: This photo shows the KBC 36 MAGFORCE in its **original size**.

The KBC 36 MAGFORCE has been singled out for a **Red Dot Award**.



reddot winner 2023

SETTING STANDARDS. INCLUDING SIZE STANDARDS.



This photo shows the KBC 36 MAGFORCE in its **original size**.

DIN A4 (297 x 210 mm)




The same size as a DIN A4 sheet of paper but simply the best when compared with competitors: the new KBC 36 MAGFORCE, the world's most compact core drill with forward and reverse running.

MODEL	INSTALLATION LENGTH	INSTALLATION HEIGHT	WIDTH ACROSS CORNERS	WEIGHT	CUTTING DEPTH
FEIN KBC 36 MAGFORCE	290 mm	169 mm	40 mm	8.5 kg	35 mm
Competitor 1	310 mm	167 mm	50 mm	10.3 kg	30 mm
Competitor 2	338 mm	180 mm	43 mm	11.0 kg	30 mm
Competitor 3	380 mm	176 mm	57 mm	9.5 kg	30 mm



Core drilling.

CORE DRILL BITS AND ACCESSORIES.



FEIN CORE DRILL BITS 3/4" WELDON











3/4"	' Weldon	FEIN HM ULTRA SPEED HM/TCT [WC-Co] + TIALSIN 1.450 HV TIALSIN (3 µm) 3.800 HV	FEIN HM ULTRA HM/TCT [WC-Co] 1.450 HV	FEIN HSS DURA HSS + TIN 64 HRC (800 HV) TIN (3 µm) 1.550 HV	FEIN HSS NOVA HSS 64 HRC (800 HV)	FEIN HSS SPECIAL HSS 64 HRC (800 HV) Multilayer geometry
<u></u>	25 mm	-	_	Ø 12–60 mm	Ø 12–60 mm	Ø 12–35 mm
b	35 mm	Ø 14–36 mm	Ø 12–60 mm	-	-	-
)	50 mm	-	Ø 12–65 mm	Ø 12–60 mm	Ø 12–60 mm	Ø 12–50 mm
	75 mm	-	Ø 18–65 mm	-	Ø 19–60 mm	-
<u> </u>	100 mm	-	-	-	Ø 21–50 mm*	-
	< 10% Si < 600 N/mm²	~ ~	~	~	~ ~	~~
	> 10% Si < 600 N/mm ²	~	-	✓	✓	~
AL	< 500 N/mm²	///	///	///	///	///
	< 750 N/mm²	///	///	///	~	~~
	< 900 N/mm²	///	///	~~	✓	~
	< 1.100 N/mm²	~ ~	~~	~	-	-
<u> </u>	< 700 N/mm²	//	~ ~	~ ~	~	~
•	> 700 N/mm²	✓	~	~	-	-
GJS	< 300 N/mm²	///	~~~	-	~	~
Sn Zn	< 500 N/mm²	~ ~	~~	-	-	-

QuickIN








Qı	uickIN	FEIN HM ULTRA HM/TCT [WC-Co] 1.450 HV	FEIN HSS DURA HSS + TIN 64 HRC (800 HV). TIN (3 μm) 1.550 HV	FEIN HSS NOVA HSS 64 HRC (800 HV)
_ ↑	25 mm	-	Ø 12–50 mm	Ø 12–50 mm
221	35 mm	Ø 12–65 mm	-	-
202	50 mm	-	Ø 12–50 mm	Ø 12–50 mm
\mathbb{Z}	75 mm	Ø 18–65 mm	-	-
AI .	< 10% Si < 600 N/mm²	✓	✓	/ /
	> 10% Si < 600 N/mm²	-	✓	✓
METAL	< 500 N/mm²	///	~ ~~	~~~
	< 750 N/mm²	///	~ ~~	/ /
	< 900 N/mm²	///	~ ~	✓
	< 1.100 N/mm²	~	✓	-
NOX	< 700 N/mm²	~	~ ~	✓
+	> 700 N/mm²	✓	~	-
GJL GJS	< 300 N/mm²	~ ~~	-	~
Cu Ni Sn Zn	< 500 N/mm²	~ ~	-	-

1 METAL CORE DRILLING



FEIN CORE DRILL BITS WELDON 32



FEIN HM ULTRA HM/ TCT [WC-Co]

	WELDON 32	1.450 HV	
	25 mm	-	
100	35 mm	-	
(88)	50 mm	Ø 50–110 mm	
	75 mm	-	
1000	<u> </u>	Ø 50-110 mm	
Al	< 10% Si < 600 N/mm²	~	
	> 10% Si < 600 N/mm²	-	
METAL	< 500 N/mm²	~ ~~	
	- < 750 N/mm²	~ ~~	
	< 900 N/mm²	> >>	
	< 1.100 N/mm²	~	
INOX	< 700 N/mm²	~	
++	> 700 N/mm²	✓	
GJL GJS	< 300 N/mm²	~~~	
Cu Ni Sn Zn	< 500 N/mm²	~ ~	

FEIN CENTRING PINS

		- Signature -					
		82 mm	100 mm	125 mm	135 mm	158 mm	184 mm
Ø x L [mm]		6.35 x 82	6.35 x 100	6.35 x 125	6.35 x 135	6.35 x 158	7.98 x 184
part number		6 31 34 998 30 0	6 31 34 998 31 0	6 31 34 998 33 0	6 31 34 998 33 5	3 02 17 366 01 0	3 02 17 362 01 0
Cutting depth	Core drill bit holder						
25	QuickIN	~					
25 mm	3/4" Weldon	~					
75	QuickIN		~				
35 mm	3/4" Weldon		/ *				
	QuickIN		~				
50 mm	3/4" Weldon		~				
	QuickIN MAX / Weldon 32			~			
75	QuickIN			~			
75 mm	3/4" Weldon			~			
	3/4" Weldon					~	
100 mm	Weldon 32						~

QuickIN > 3/4" Weldon adapter (6 39 01 021 01 4)

25 mm			~		
35 mm	3/4" Weldon output		>		
50 mm	•			~	

Weldon 32 > 3/4" Weldon adapter (6 39 01 075 01 0)

25 mm			~		
35 mm	3/4" Weldon output			~	
50 mm				~	

3/4" Weldon > QuickIN adapter (6 39 01 027 01 0)

25 mm		~			
35 mm	QuickIN output		~		
50 mm				~	

Weldon 32 > QuickIN adapter (6 39 01 045 01 0)

25 mm			~		
35 mm	QuickIN output			~	
50 mm				~	

1 ENDURANCE











KBE 32

KBE 32 QW

MAGSPEED Small and extremely lightweight single-speed endurance magnetic core drill for core drilling on the construction site.

KBE 36

KBE 36 QW MAGSPEED

Small and lightweight single-speed endurance Lightweight and magnetic core drill offering unique performance and service life even under the most challenging conditions in the workshop and on the construction site.

powerful 2-speed Endurance magnetic core drill with basic functionality for core drilling and twist drilling in the workshop and on the

KBE 50-2

						onstruction site.
PAGE		23	23	23	24	24
Core drilling in metal with a Ø up to 35 mm		++	++	++	++	++
Core drilling in metal with a Ø up to 50 mm						++
Twist drills with drill chuck (DIN 33	58)					++
Working overhead		++	++	++	++	+
Installation work		++	++	++	++	++
Workshop jobs		++	++	++	++	++
Feed handwheel can be moved from one side to the other		•	•	•	•	•
Tool-free core bit quick change sys	stem		•	•		
Input	W	1 200	1 200	1 600	1 600	1 100
Output	W	770	770	1 200	1 200	650
Motor				brushless	brushless	
Speed, full load	rpm	450	450	620	620	
Load speed in speed 1	rpm					260
Load speed in speed 2	rpm					520
Speed, no load	rpm	700	700	620	620	
Idling speed in speed 1	rpm					330
Idling speed in speed 2	rpm					650
Carbide core drill bit max. Ø	mm	32	32	36	36	50
HSS core drill max. Ø	mm	32	32	26	26	50
Core drill, drilling depth max.	mm	50	50	50	50	50
Twist drill max. Ø	mm					16
Core drill holder		3/4" Weldon				
Stroke	mm	90	90	107	107	135
Magnetic holding power	N	10,000	10,000	10,000	10,000	12,000
Magnetic foot dimensions	mm	175 x 80	175 x 80	175 x 80	175 x 80	195 x 90
Cable with plug	m	3	3	4	4	3
Weight according to EPTA	kg	10,8	11	11	11,2	12,5

⁺ suitability

⁺⁺ optimal suitability

[•] included

KBE 32



SUPPLIED

1 hand pump, 1 bottle holder, 1 lashing strap, 1 centring pin 100 mm, 1 contact guard, 1 socket head wrench 5 mm. 1 case

For accessories, see page 28

Small and extremely lightweight single-speed endurance magnetic core drill for core drilling on the construction site.

Small and extremely lightweight single-speed endurance magnetic core drill for core drilling on the construction site.

Input	W	1 200
Output	W	770
Speed, full load	rpm	450
Speed, no load	rpm	700
Carbide core drill bit max. Ø	mm	32
HSS core drill max. Ø	mm	32
Core drill, drilling depth max.	mm	50
Core drill holder		3/4" Weldon
Stroke	mm	90
Magnetic holding power	N	10,000
Magnetic foot dimensions	mm	175 x 80
Cable with plug	m	3
Weight according to EPTA	kg	10,8

Part number	7 270 94 61 00 0
EAN	4014586894539

FEIN BENEFITS

- + For tough use thanks to the outstanding quality of workmanship and the internal motor cable guide.
- Extremely durable gearbox design offering an operating time of up to 400 hours for an uncompromising service
- Lightweight with FEIN high-power motor and high torque for all core drilling tasks
- Excellent price / performance ratio.
- + Internal cooling.+ High magnetic holding force.
- + Feed handwheel can be moved from one side to the
- Good accessibility in cramped operating situations.
- Personal safety switch.

KBE 32 QW



SUPPLIED

1 hand pump, 1 bottle holder, 1 lashing strap, 1 centring pin 100 mm, 1 contact guard, 1 case

For accessories, see page 28

Input	W	1 200
Output	W	770
Speed, full load	rpm	450
Speed, no load	rpm	700
Carbide core drill bit max. Ø	mm	32
HSS core drill max. Ø	mm	32
Core drill, drilling depth max.	mm	50
Core drill holder		
Core drill holder		3/4" Weldon
Core drill holder Changing the core bit		3/4" Weldon tool-free
	mm	
Changing the core bit	mm N	tool-free
Changing the core bit Stroke		tool-free 90
Changing the core bit Stroke Magnetic holding power	N	tool-free 90 10,000

Part number	7 270 95 61 00 0
EAN	4014586894614

FEIN BENEFITS

- + For tough use thanks to the outstanding quality of workmanship and the internal motor cable guide.
- + Extremely durable gearbox design offering an operating time of up to 400 hours for an uncompromising service life.
- + Lightweight with FEIN high-power motor and high torque for all core drilling tasks
- Excellent price / performance ratio.
- Tool-free core bit quick change system.
- + Internal cooling.
- High magnetic holding force.
 Feed handwheel can be moved from one side to the
- Good accessibility in cramped operating situations.
- Personal safety switch.

KBE 36 MAGSPEED



SUPPLIED

1 coolant tank, 1 lashing strap, 1 centring pin 100 mm, 1 contact guard, 1 x 5 mm hexagon socket wrench, 1 x 5 mm hexagon socket wrench with T-handle, 1 case

For accessories, see page 28

Small and lightweight single-speed endurance magnetic core drill offering unique performance and service life even under the most challenging conditions in the workshop and on the construction site.

Input	W	1 600
Output	W	1 200
Motor		brushless
Speed, full load	rpm	620
Speed, no load	rpm	620
Carbide core drill bit max. Ø	mm	36
HSS core drill max. Ø	mm	26
Core drill, drilling depth max.	mm	50
Core drill holder		3/4" Weldon
Stroke	mm	107
Magnetic holding power	N	10,000
Magnetic foot dimensions	mm	175 x 80
Cable with plug	m	4
Weight according to EPTA	kg	11

Part number	7 273 24 61 00 0
FAN	4014586898551

FEIN BENEFITS

- + Twice the productivity combined with the perfect result: drilling times are halved, the work process is sped up. Thanks to rapid work progress, you can drill up to 60 holes rather than the 30 that used to be possible in the same time.
- Outstanding cutting performance that has never been seen before thanks to stable speed and torque curve with cutting speeds of up to 70 m/min - ideal for carbide core drill bits.
- Unique durability for up to 240 000 holes thanks to the extremely low-wear machine concept with brushless 1600 W high-power motor and internal drill motor cable routing!
- + Intuitive operating concept translates into good accessibility in tight spots.
- Convenient magnetic holding force display.

 Tilt sensor stops the drill motor when the tool slips
- or tilts.
- Integrated coolant tank.
- Feed handwheel can be moved from one side to the other without any tools.
- Slot for 5 mm hexagon socket wrench on the tool itself.
- + Personal safety switch.

1 ENDURANCE

KBE 36 QW MAGSPEED

Small and lightweight single-speed endurance magnetic core drill offering unique performance and service life even under the most challenging conditions in the workshop and on the construction site.



SUPPLIED

1 coolant tank, 1 lashing strap, 1 centring pin 100 mm, 1 contact guard, 1 case

For accessories, see page 28

Input	W	1 600
Output W		1 200
Motor		brushless
Speed, full load	rpm	620
Speed, no load	rpm	620
Carbide core drill bit max. Ø m		36
HSS core drill max. Ø	mm	26
Core drill, drilling depth max.	mm	50
Core drill holder		3/4" Weldon
Changing the core bit		tool-free
Stroke	mm	107
Magnetic holding power	N	10,000
Magnetic foot dimensions	mm	175 x 80
Cable with plug	m	4
Weight according to EPTA	kg	11,2

Part number	7 273 28 61 00 0
EAN	4014586899794

FEIN BENEFITS

- + Twice the productivity combined with the perfect result: drilling times are halved, the work process is sped up. Thanks to rapid work progress, you can drill up to 60 holes rather than the 30 that used to be possible in the same time.
- Outstanding cutting performance that has never been seen before thanks to speed and torque curve with cutting speeds of up to 70 m/min, ideal for HM ULTRA and HM ULTRA SPEED core drill bits.
- Unique durability for up to 240 000 holes thanks to the extremely low-wear machine concept with brushless 1 600 W high-power motor and internal drill motor cable routing.
- + Good accessibility in cramped operating situations.
- + Convenient magnetic holding force display.
- + Tilt sensor stops the drill motor when the tool slips or tilts.
- + Integrated coolant tank.
- + Feed handwheel can be moved from one side to the other without any tools.
- Personal safety switch.

KBE 36 QW MAGSPEED FABRICATION SET



SUPPLIED

1 magnetic core drill, 1 coolant tank, 1 lashing strap, 1 centring pin 100 mm, 1 contact guard, 1 case, 6 HM ULTRA SPEED 35 core drill bits, 3 m cutting depth (diameter 2x 14 / 16 / 18 / 20 / 22 mm), 2 x 100 mm centring pins

For accessories, see page 28

Input	W	1 600
Output	W	1 200
Motor		brushless
Speed, full load	rpm	620
Speed, no load	rpm	620
Carbide core drill bit max. Ø	mm	36
Core drill, drilling depth max.	mm	50
Core drill holder		3/4" Weldon
Changing the core bit		tool-free
Weight according to EPTA	kg	11,2

Part number	7 273 28 62 00 0
EAN	4014586899664

FEIN BENEFITS

- Twice the productivity combined with the perfect result: drilling times are halved, the work process is sped up. Thanks to rapid work progress, you can drill up to 60 holes rather than the 30 that used to be possible in the same time.
- Outstanding cutting performance that has never been seen before thanks to speed and torque curve with cutting speeds of up to 70 m/min, ideal for HM ULTRA and HM ULTRA SPEED core drill bits.
- Unique durability for up to 240 000 holes thanks to the extremely low-wear machine concept with brushless 1 600 W high-power motor and internal drill motor cable routing.

HM ULTRA SPEED 35: carbide core drill bit with TiAlSiN surface coating for unique cutting performance and maximum work progress with an extremely long service life.

KBE 50-2



SUPPLIED

1 coolant tank, 1 lashing strap, 1 centring pin 100 mm, 1 contact guard, 2 x 5 and 6 mm hexagon socket wrench

For accessories, see page 28

Lightweight and powerful 2-speed Endurance magnetic core drill with basic functionality for core drilling and twist drilling in the workshop and on the construction site.

The KBE 36 QW MAGSPEED endurance core drill with unique performance coupled with TiAlSiN-coated HM ULTRA SPEED 35

core drill bit – for maximum cutting performance and outstanding work progress. Perfect for serial high-impact use in steel

Input	W	1 100
Output	W	650
Load speed in speed 1	rpm	260
Load speed in speed 2	rpm	520
Idling speed in speed 1	rpm	330
Idling speed in speed 2	rpm	650
Carbide core drill bit max. Ø	mm	50
HSS core drill max. Ø	mm	50
Core drill, drilling depth max.	mm	50
Twist drill max. Ø	mm	16
Core drill holder	ore drill holder	
Stroke	mm	135
Total stroke range	mm	260
Magnetic holding power	N	12,000
Magnetic foot dimensions	mm	195 x 90
Cable with plug	m	3
Weight according to EPTA	kg	12,5

Part number	7 270 51 60 00 0
EAN	4014586881645

FEIN BENEFITS

- + For tough use thanks to the outstanding quality of workmanship
- FEIN high-power motor with high torque and large stroke range for core and twist drilling.
- + Uncompromising with regard to service life and work progress coupled with outstanding value for money.
- + Mechanical 2-speed gearbox.
- + Integrated coolant tank.
- + High magnetic holding force.
- + Optimum power-to-weight ratio.
- + Feed handwheel can be moved from one side to the other with hex hub.
- + Integrated Allen wrench holder.
- + Personal safety switch.



KBC 36 MAGFORCE (230 V)

Extremely small and light single-speed compact magnetic core drill with minimum dimensions for use in tight spaces in the workshop and on the construction site.

PAGE		26
Core drilling in metal with a Ø up to 35	nm	++
Working overhead		++
Installation work		++
Input	W	1 200
Output	W	680
Speed, full load	rpm	130 - 610
Speed, no load	rpm	130 - 660
Carbide core drill bit max. Ø	mm	36
HSS core drill max. Ø	mm	36
Core drill, drilling depth max.	mm	35
Twist drill max. Ø	mm	16
Tapping		M 12
Core drill holder		3/4" Weldon
Width across corners	mm	40
Height	mm	169
Length	mm	290
Stroke	mm	46
Magnetic holding power	N	10 000
Magnetic foot dimensions	mm	175 x 80
Cable with plug	m	3
Weight according to EPTA	kg	8,50

⁺⁺ optimal suitability

1 COMPACT

KBC 36 MAGFORCE (230 V)



SUPPLIED

 $1\times1/2"$ ratchet, $1\times1/2"$ socket wrench extension, $1\times$ coolant pump, 1 lashing strap, 1 swarf hook, 1×82 mm centring pin, 1 contact guard, 1 additional handle, 1×5 mm hexagon socket wrench, 1×5 mm hexagon socket wrench with T-handle, 1 plastic tool case (L-BOXX 238)

For accessories, see page 28

Extremely small and light single-speed compact magnetic core drill with minimum dimensions for use in tight spaces in the workshop and on the construction site.

Input	W	1 200
Output	W	680
Speed, full load	rpm	130 - 610
Speed, no load	rpm	130 - 660
Carbide core drill bit max. Ø	mm	36
HSS core drill max. Ø	mm	36
Core drill, drilling depth max.	mm	35
Twist drill max. Ø	mm	16
Tapping		M 12
Countersinking max. Ø	mm	32
Core drill holder		3/4" Weldon
Core drill holder Width across corners	mm	3/4" Weldon 40
	mm mm	
Width across corners		40
Width across corners Height	mm	40 169
Width across corners Height Length	mm mm	40 169 290
Width across corners Height Length Stroke	mm mm mm	40 169 290 46
Width across corners Height Length Stroke Magnetic holding power	mm mm mm N	40 169 290 46 10,000
Width across corners Height Length Stroke Magnetic holding power Magnetic foot dimensions	mm mm mm N	40 169 290 46 10,000 175 x 80

Part number 7 273 23 62 00 0 EAN 4014586897356

FEIN BENEFITS

- Extremely small and light for working in tight and difficult-to-reach spots – including vertically and overhead – thanks to height of 169 mm, a length of 290 mm and a weight of 8.5 kg.
- Extremely low wear and long-life tool design with spindle sleeve feed without clearance for accurate drilling results in tough use in industry and manual trades.
- Very powerful and maintenance-free brushless 1200 W high-power motor with high speed stability for continuously fast work progress as well as forward / reverse running and electronic speed setting for all drilling applications, such as core drilling, twist drilling and tapping and countersinking.
- High gearbox positioning for optimum view of the drilling point.
- + Large installation space under the drill spindle with a stroke range of 46 mm.
- + Space-saving operation on both sides with ratchet.
- + Combined drive shaft, 1/2" square and 8 mm hexagon socket.
- Intuitive operating concept avoids mix-ups and can be clearly seen by the user.
- + Convenient magnetic holding force display.
- + Tilt sensor stops the drill motor when the tool slips or tilts.
- + Integrated handle.
- + Speed saving "memory function".
- + Slot for 5 mm hexagon socket wrench on the tool itself.
- + Internal cooling lubrication by means of hand pump.
- + Personal safety switch.
- Ideally equipped for every job. Mobile working with the L-BOXX system.

KBC 36 MAGFORCE STRUCTURAL STEEL-SET 3/4" WELDON / HSS NOVA 25



SUPPLIED

1 magnetic core drill, 1 x 1/2" ratchet, 1 x 1/2" socket wrench extension, 1 x coolant pump, 1 lashing strap, 1 swarf hook, 1 x 82 mm centring pin, 1 contact guard, 1 additional handle, 1 x 5 mm hexagon socket wrench, 1 x 5 mm hexagon socket wrench with T-handle, 1 plastic tool case (L-BOXX 238), HSS twist drills, 35 mm cutting depth (3 each of diameter 10 mm and 12 mm), HSS NOVA 25 core drill bits, 25 mm cutting depth (3 each of diameter 14 / 16 / 18 / 20 / 22 mm), 2 x 82 mm centring pin, 1 cutting paste, 1 L-BOXX 136 for accessories

For accessories, see page 28

The smallest core drill in the world with forward and reverse running coupled with a large number of HSS NOVA 25 core drilling accessories. Perfect for steel and bridge construction.

Input	W	1 200
Output	W	680
Speed, full load	rpm	130 - 610
Speed, no load	rpm	130 - 660
Carbide core drill bit max. Ø	mm	36
HSS core drill max. Ø	mm	36
Core drill, drilling depth max.	mm	35
Twist drill max. Ø	mm	16
Tapping		M 12
Countersinking max. Ø	mm	32
Core drill holder		3/4" Weldon
Width across corners	mm	40
Height	mm	169
Length	mm	290
Stroke	mm	46
Magnetic holding power	N	10,000
Magnetic foot dimensions	mm	175 x 80
Cable with plug	m	3
Weight according to EPTA	kg	8,50

Part number 7 273 23 64 00 0 EAN 4014586897462

FEIN BENEFITS

- Extremely small and light for working in tight and difficult-to-reach spots – including vertically and overhead – thanks to height of 169 mm, a length of 290 mm and a weight of 8.5 kg.
- Extremely low wear and long-life tool design with spindle sleeve feed without clearance for accurate drilling results in tough use in industry and manual trades.
- + Very powerful and maintenance-free brushless 1200 W high-power motor with high speed stability for continuously fast work progress as well as forward / reverse running and electronic speed setting for all drilling applications, such as core drilling, twist drilling and tapping and countersinking.

HSS NOVA 25 core drill bit: Long service life and particularly resistant to shock and impact: thanks to its tough cutting edges and outstanding HSS steel with a hardness of 64 HRC, the core drill bit is perfectly designed for tough use in steel construction and installation work.

L-BOXX system: Keep things stowed clearly, tidily and safely. Thanks to the tray for small parts, there is room for all accessories and the L-BOXXs can also be joined together and stacked with ease.

KBC 36 MAGFORCE MACHINERY-SET 3/4" WELDON (230 V)



SUPPLIED

1 magnetic core drill, 1 x 1/2" ratchet, 1 x 1/2" socket wrench extension, 1 x coolant pump, 1 lashing strap, 1 swarf hook, 1 x 82 mm centring pin, 1 contact guard, 1 additional handle, 1 x 5 mm hexagon socket wrench, 1 x 5 mm hexagon socket wrench with T-handle, 1 plastic tool case (L-BOXX 238), Tapping drills (2 each of M6, M8, M10, M12 (DIN 352 / ISO 13)), HSS twist drills, 35 mm cutting depth (1 each of diameter 5.0 / 6.8 / 8.5 / 10.2 mm), 4 x HSS 90° countersink bits, diameter 16.5 mm, 1 cutting paste, 1 L-BOXX 136 for accessories

For accessories, see page 28

The smallest core drill in the world with forward and reverse running coupled with a large number of tapping accessories. Perfect for the construction of machines and machine tools.

Input	W	1 200
Output	W	680
Speed, full load	rpm	130 - 610
Speed, no load	rpm	130 - 660
Carbide core drill bit max. Ø	mm	36
HSS core drill max. Ø	mm	36
Core drill, drilling depth max.	mm	35
Twist drill max. Ø	mm	16
Tapping		M 12
Countersinking max. Ø	mm	32
Core drill holder		3/4" Weldon
Width across corners	mm	40
Height	mm	169
Length	mm	290
Stroke	mm	46
Magnetic holding power	N	10,000
Magnetic foot dimensions	mm	175 x 80
Cable with plug	m	3
Weight according to EPTA	kg	8,50

Part number	7 273 23 63 00 0
EAN	4014586897424

FEIN BENEFITS

- Extremely small and light for working in tight and difficult-to-reach spots – including vertically and overhead – thanks to height of 169 mm, a length of 290 mm and a weight of 8.5 kg.
- Extremely low wear and long-life tool design with spindle sleeve feed without clearance for accurate drilling results in tough use in industry and manual trades
- + Very powerful and maintenance-free brushless 1200 W high-power motor with high speed stability for continuously fast work progress as well as forward / reverse running and electronic speed setting for all drelling applications, such as core drilling, twist drilling and tapping and countersinking.

Tapping drill: Ideal for when things get tight. The M6, M8, M10, M12 tapping drills are perfectly suited to through threads in particularly tight spots.

Twist drills and countersink bits: With this set you can have everything you need for core drilling and blind holes readily to hand.

L-BOXX system: Keep things stowed clearly, tidily and safely. Thanks to the tray for small parts, there is room for all accessories and the L-BOXXs can also be joined together and stacked with ease.

KBC 36 MAGFORCE TRUCKFRAME-SET 3/4" WELDON / HSS SPECIAL 25



SUPPLIED

1 magnetic core drill, $1 \times 1/2^*$ ratchet, $1 \times 1/2^*$ socket wrench extension, $1 \times$ coolant pump, 1 lashing strap, $1 \times$ swarf hook, $1 \times$ 82 mm centring pin, $1 \times$ 5 mm hexagon socket wrench, $1 \times$ 5 mm hexagon socket wrench with T-handle, $1 \times$ 1 plastic tool case (L-BOXX 238), HSS SPECIAL 25 core drill bits, $2 \times$ 15 mm cutting depth (2 each of diameter 12/14/16/18/20/22/24/26 mm), HSS twist drills, $3 \times$ 5 mm cutting depth (2 each of diameter 8 mm and $1 \times$ 0 mm), $1 \times$ 2 × 82 mm centring pin, $1 \times$ 1 cutting paste, $1 \times$ 1 -BOXX $1 \times$ 6 for accessories

For accessories, see page 28

The smallest core drill in the world with forward and reverse running coupled with a large number of HSS SPECIAL core drilling accessories. Perfect for the construction of frames for vehicles and special vehicles.

rpm rpm mm	680 130 - 610 130 - 660
rpm	130 - 660
mm	
	36
mm	36
mm	35
mm	16
	M 12
mm	32
	3/4" Weldon
mm	40
mm	169
mm	290
mm	46
N	10,000
mm	175 x 80
m	3
kg	8,50
	mm

Part number 7 273 23 65 00 0 EAN 4014586897509

FEIN BENEFITS

- Extremely small and light for working in tight and difficult-to-reach spots – including vertically and overhead – thanks to height of 169 mm, a length of 290 mm and a weight of 8.5 kg.
- Extremely low wear and long-life tool design with spindle sleeve feed without clearance for accurate drilling results in tough use in industry and manual trades.
- + Very powerful and maintenance-free brushless 1200 W high-power motor with high speed stability for continuously fast work progress as well as forward / reverse running and electronic speed setting for all drilling applications, such as core drilling, twist drilling and tapping and countersinking.

HSS SPECIAL 25 core drill bit: Thanks to its special cutting geometry, the core is cut from the inside out and materials of multiple layers can therefore be drilled in a single process.

Hole diameters and consumables: Always have key accessories to hand, everything from the most common drill bit diameters to cutting paste for cooling lubrication.

L-BOXX system: Keep things stowed clearly, tidily and safely. Thanks to the tray for small parts, there is room for all accessories and the L-BOXXs can also be joined together and stacked with ease.

BEST OF CORE DRILLING HSS ACCESSORY SET



BEST OF CORE BITS 3/4" WELDON

Industrial standard. Metric dimensions, cutting depth 25 mm. Set version, consisting of 4 core bits, 2 x 14 mm diameter, 2 x 18 mm diameter, (cutting depth 25 mm) and 1 centring pin (80 mm) in plastic case.

Part number 6 31 34 999 06 2



BEST OF CORE BITS 3/4" WELDON

Industrial standard. Metric dimensions, cutting depth 50 mm. Set version, consisting of 4 core bits, 2x 14 mm diameter, 2x 18 mm diameter, (cutting depth 50 mm) and 1 centring pin (100 mm) in plastic case.

Part number 6 31 34 999 06 4



BEST OF CORE BITS 3/4" WELDON

Industrial standard. Metric dimensions, cutting depth 25 mm. Set version, consisting of 6 core bits with diameters of 12, 14, 16, 18, 20 and 22 mm (cutting depth 25 mm) and 2 centring pins (80 mm) in plastic case.

Part number

6 31 34 999 06 1



BEST OF CORE BITS 3/4" WELDON

Industrial standard. Metric dimensions, cutting depth 50 mm. Set version, consisting of 6 core bits with diameters of 12, 14, 16, 18, 20 and 22 mm (cutting depth 50 mm) and 2 centring pins (100 mm) in plastic case.

Part number 6 31 34 999 06 3

BEST OF CORE DRILLING CARBIDE ACCESSORY SET



BEST OF CORE BITS 3/4" WELDON

Very long service life and outstanding cutting performance. Metric dimensions, cutting depth 35 mm. Set version, consisting of 6 core bits with diameters of 12, 14, 16, 18, 20 and 22 mm (cutting depth 35 mm) and 2 centring pins (100 mm) in plastic case.

Part number

6 31 27 714 02 0



BEST OF CORE BITS 3/4" WELDON

Very long service life and outstanding cutting performance. Metric dimensions, cutting depth 50 mm. Set version, consisting of 6 core bits with diameters of 12, 14, 16, 18, 20 and 22 mm (cutting depth 35 mm) and 2 centring pins (100 mm) in plastic case.

Part number 6 31 27 276 02 0



ACCESSORY SET FOR BEST OF CORE DRILLING CARBIDE COATED 3/4" WELDON

TiAlSiN surface coating for unique cutting performance and maximum work progress with an extremely long service life. Metric dimensions, cutting depth 35 mm. Set model, consisting of 6 core drill bits with diameters of 2x 14 / 16 / 18 / 20 / 22 mm (cutting depth 35 mm) and 2 centring pins (100 mm) in plastic case.

Part number 6 31 27 838 11 0

CARBIDE CORE DRILL



TCT ULTRA 35 CORE BIT WITH 3/4" WELDON HOLDER

Very long service life and outstanding cutting performance. Metric dimensions, cutting depth $35\ \mathrm{mm}$.

35 12 63127714010 35 13 63127715010 35 14 63127717010 35 15 63127717010 35 16 63127719010 35 17 63127719010 35 18 63127721010 35 19 63127721010 35 20 63127722010 35 21 63127723010 35 22 63127723010 35 22 63127725010 35 22 63127725010 35 22 63127725010 35 24 63127725010 35 25 63127727010 35 26 63127727010 35 27 63127729010 35 28 63127729010 35 28 63127730010 35 29 63127730010 35 32 63127730010 35 32 63127733010 <th< th=""><th>Cutting depth mm</th><th>Bore Ø mm</th><th>Part number</th></th<>	Cutting depth mm	Bore Ø mm	Part number
35 13 63127715010 35 14 63127716010 35 15 63127717010 35 16 63127718010 35 17 63127720010 35 18 63127720101 35 19 6312772010 35 20 63127723010 35 21 63127723010 35 22 63127724010 35 23 63127725010 35 23 63127725010 35 24 63127725010 35 25 63127726010 35 26 63127726010 35 27 63127729010 35 28 63127729010 35 29 63127730010 35 29 63127730010 35 30 63127732010 35 32 63127730010 35 32 63127730010 35 33 63127735010			
35 14 63127716010 35 15 63127717010 35 16 63127718010 35 17 63127719010 35 18 63127720010 35 19 63127722010 35 20 63127722010 35 21 63127723010 35 22 63127724010 35 22 63127724010 35 23 63127724010 35 24 63127726010 35 25 63127727010 35 26 63127727010 35 26 63127728010 35 27 63127729010 35 28 63127730010 35 29 6312773010 35 30 63127732010 35 31 63127733010 35 32 63127733010 35 32 63127733010 35 32 63127733010 35 33 63127733010 35 34 63127736010<			
35 15 63127717010 35 16 63127718010 35 17 63127719010 35 18 63127720010 35 19 63127722010 35 20 63127722010 35 21 63127723010 35 22 63127724010 35 23 63127725010 35 24 63127725010 35 25 63127727010 35 25 63127727010 35 26 63127728010 35 27 63127729010 35 28 63127730010 35 29 63127730010 35 30 63127730010 35 32 63127730010 35 32 63127730010 35 32 63127730010 35 32 63127730010 35 33 63127730010 35 34 63127730010 <td< td=""><td></td><td>14</td><td></td></td<>		14	
35 16 63127718010 35 17 63127719010 35 18 63127720010 35 19 63127722010 35 20 63127722010 35 21 63127722010 35 22 63127724010 35 23 63127725010 35 24 63127726010 35 25 63127728010 35 25 63127728010 35 26 63127728010 35 27 63127729010 35 28 63127730010 35 29 63127732010 35 30 63127732010 35 32 63127733010 35 32 63127734010 35 33 63127735010 35 34 63127735010 35 35 35 35 35 36 35 37 63127739010 35 38 63127734010 35 39 63127740010	35	15	
35 17 63127719010 35 18 63127720010 35 19 63127722010 35 20 63127722010 35 21 63127723010 35 22 63127724010 35 22 63127725010 35 24 63127726010 35 25 63127722010 35 26 63127722010 35 27 63127722010 35 28 63127732010 35 29 63127732010 35 30 63127732010 35 32 63127732010 35 32 63127734010 35 32 63127735010 35 34 63127735010 35 35 36 35 35 36 35 37 63127735010 35 38 63127739010 35 37 63127739010 35 39 63127740010 35 40 63127740010	35	16	
35 18 63127720010 35 19 63127721010 35 20 63127722010 35 21 63127723010 35 22 63127724010 35 23 63127725010 35 24 63127726010 35 25 63127727010 35 26 63127728010 35 27 63127729010 35 28 63127730010 35 29 63127730010 35 30 63127732010 35 31 63127732010 35 32 63127732010 35 32 63127734010 35 32 63127735010 35 34 63127736010 35 35 36 35 37 63127739010 35 38 63127739010 35 39 63127739010 35 39 63127740010 35 39 63127740010 35 40 63127740010	35	17	
35 20 63127722010 35 21 63127723010 35 22 63127724010 35 23 63127725010 35 24 63127726010 35 25 63127727010 35 26 63127728010 35 27 63127729010 35 28 63127730010 35 29 63127731010 35 30 63127732010 35 32 63127733010 35 32 63127735010 35 32 63127736010 35 34 63127736010 35 35 63127738010 35 35 63127739010 35 36 63127739010 35 36 63127739010 35 37 63127739010 35 38 63127740010 35 39 63127740010 35 40 63127740010 35 41 63127740010 35 42 63127740010			
35 21 6 31 27 723 01 0 35 22 6 31 27 724 01 0 35 23 6 31 27 725 01 0 35 24 6 31 27 726 01 0 35 25 6 31 27 727 01 0 35 26 6 31 27 728 01 0 35 27 6 31 27 729 01 0 35 28 6 31 27 730 01 0 35 29 6 31 27 732 01 0 35 30 6 31 27 732 01 0 35 32 6 31 27 734 01 0 35 32 6 31 27 735 01 0 35 34 6 31 27 736 01 0 35 35 36 6 31 27 736 01 0 35 35 6 31 27 736 01 0 35 36 6 31 27 739 01 0 35 36 6 31 27 739 01 0 35 36 6 31 27 730 01 0 35 37 6 31 27 730 01 0 35 38 6 31 27 740 01 0 35 39 6 31 27 740 01 0 35 40 6 31 27 740 01 0 35 42 6 31 27 745 01 0	35	19	6 31 27 721 01 0
35 22 6 31 27 724 01 0 35 23 6 31 27 725 01 0 35 24 6 31 27 726 01 0 35 25 6 31 27 728 01 0 35 26 6 31 27 729 01 0 35 27 6 31 27 729 01 0 35 28 6 31 27 730 01 0 35 29 6 31 27 732 01 0 35 30 6 31 27 732 01 0 35 31 6 31 27 733 01 0 35 32 6 31 27 734 01 0 35 33 6 31 27 736 01 0 35 34 6 31 27 736 01 0 35 35 6 31 27 736 01 0 35 36 6 31 27 736 01 0 35 36 6 31 27 736 01 0 35 37 6 31 27 736 01 0 35 38 6 31 27 740 01 0 35 39 6 31 27 740 01 0 35 40 6 31 27 740 01 0 35 42 6 31 27 745 01 0 35 42 6 31 27 745 01 0 35 43 6 31 27 746 01 0 35	35	20	6 31 27 722 01 0
35 23 6 31 27 725 01 0 35 24 6 31 27 726 01 0 35 25 6 31 27 727 01 0 35 26 6 31 27 728 01 0 35 27 6 31 27 729 01 0 35 28 6 31 27 730 01 0 35 29 6 31 27 731 01 0 35 30 6 31 27 732 01 0 35 31 6 31 27 732 01 0 35 32 6 31 27 734 01 0 35 33 6 31 27 735 01 0 35 34 6 31 27 736 01 0 35 35 6 31 27 736 01 0 35 35 6 31 27 736 01 0 35 35 6 31 27 736 01 0 35 35 6 31 27 736 01 0 35 36 6 31 27 739 01 0 35 36 6 31 27 739 01 0 35 37 6 31 27 740 01 0 35 38 6 31 27 740 01 0 35 40 6 31 27 740 01 0 35 42 6 31 27 745 01 0 35 43 6 31 27 746 01 0 35	35	21	6 31 27 723 01 0
35 24 6 31 27 726 01 0 35 25 6 31 27 727 01 0 35 26 6 31 27 728 01 0 35 27 6 31 27 730 01 0 35 28 6 31 27 730 01 0 35 29 6 31 27 732 01 0 35 30 6 31 27 732 01 0 35 31 6 31 27 734 01 0 35 32 6 31 27 734 01 0 35 33 6 31 27 735 01 0 35 34 6 31 27 736 01 0 35 35 35 35 35 6 31 27 736 01 0 35 35 6 31 27 736 01 0 35 35 6 31 27 730 01 0 35 36 6 31 27 730 01 0 35 36 6 31 27 730 01 0 35 36 6 31 27 730 01 0 35 37 6 31 27 740 01 0 35 38 6 31 27 740 01 0 35 40 6 31 27 745 01 0 35 41 6 31 27 745 01 0 35 42 6 31 27 745 01 0 35 45	35	22	6 31 27 724 01 0
35 25 6 31 27 727 01 0 35 26 6 31 27 728 01 0 35 27 6 31 27 730 01 0 35 28 6 31 27 730 01 0 35 29 6 31 27 732 01 0 35 30 6 31 27 732 01 0 35 31 6 31 27 734 01 0 35 32 6 31 27 734 01 0 35 33 6 31 27 735 01 0 35 34 6 31 27 736 01 0 35 35 6 31 27 736 01 0 35 35 6 31 27 730 01 0 35 36 6 31 27 739 01 0 35 37 6 31 27 739 01 0 35 38 6 31 27 740 01 0 35 39 6 31 27 740 01 0 35 40 6 31 27 743 01 0 35 41 6 31 27 745 01 0 35 42 6 31 27 745 01 0 35 43 6 31 27 746 01 0 35 45 6 31 27 745 01 0 35 46 6 31 27 740 01 0 35 46 6 31 27 740 01 0 35	35	23	6 31 27 725 01 0
35 26 6 31 27 728 01 0 35 27 6 31 27 729 01 0 35 28 6 31 27 730 01 0 35 29 6 31 27 732 01 0 35 30 6 31 27 732 01 0 35 31 6 31 27 734 01 0 35 32 6 31 27 734 01 0 35 33 6 31 27 735 01 0 35 34 6 31 27 736 01 0 35 35 6 31 27 736 01 0 35 35 6 31 27 730 01 0 35 36 6 31 27 739 01 0 35 37 6 31 27 739 01 0 35 38 6 31 27 740 01 0 35 39 6 31 27 740 01 0 35 40 6 31 27 742 01 0 35 41 6 31 27 745 01 0 35 42 6 31 27 745 01 0 35 43 6 31 27 746 01 0 35 45 6 31 27 749 01 0 35 45 6 31 27 749 01 0 35 46 6 31 27 749 01 0 35 46 6 31 27 750 01 0 35	35	24	6 31 27 726 01 0
35 27 6 31 27 729 01 0 35 28 6 31 27 730 01 0 35 29 6 31 27 731 01 0 35 30 6 31 27 732 01 0 35 31 6 31 27 733 01 0 35 32 6 31 27 734 01 0 35 33 6 31 27 735 01 0 35 34 6 31 27 736 01 0 35 35 6 31 27 736 01 0 35 36 6 31 27 739 01 0 35 36 6 31 27 739 01 0 35 37 6 31 27 740 01 0 35 38 6 31 27 740 01 0 35 39 6 31 27 740 01 0 35 40 6 31 27 742 01 0 35 41 6 31 27 743 01 0 35 42 6 31 27 745 01 0 35 43 6 31 27 745 01 0 35 45 6 31 27 746 01 0 35 46 6 31 27 749 01 0 35 46 6 31 27 749 01 0 35 46 6 31 27 750 01 0 35 48 6 31 27 750 01 0 35	35	25	6 31 27 727 01 0
35 28 6 31 27 730 01 0 35 29 6 31 27 731 01 0 35 30 6 31 27 732 01 0 35 31 6 31 27 734 01 0 35 32 6 31 27 734 01 0 35 33 6 31 27 735 01 0 35 34 6 31 27 736 01 0 35 35 6 31 27 737 01 0 35 36 6 31 27 739 01 0 35 37 6 31 27 739 01 0 35 38 6 31 27 740 01 0 35 39 6 31 27 741 01 0 35 40 6 31 27 742 01 0 35 41 6 31 27 743 01 0 35 42 6 31 27 744 01 0 35 43 6 31 27 745 01 0 35 44 6 31 27 746 01 0 35 45 6 31 27 746 01 0 35 46 6 31 27 749 01 0 35 46 6 31 27 750 01 0 35 48 6 31 27 750 01 0 35 49 6 31 27 751 01 0	35	26	6 31 27 728 01 0
35 29 6 31 27 731 01 0 35 30 6 31 27 732 01 0 35 31 6 31 27 733 01 0 35 32 6 31 27 734 01 0 35 33 6 31 27 735 01 0 35 34 6 31 27 736 01 0 35 35 6 31 27 737 01 0 35 36 6 31 27 738 01 0 35 37 6 31 27 739 01 0 35 38 6 31 27 740 01 0 35 39 6 31 27 741 01 0 35 40 6 31 27 742 01 0 35 41 6 31 27 743 01 0 35 42 6 31 27 745 01 0 35 43 6 31 27 745 01 0 35 44 6 31 27 746 01 0 35 45 6 31 27 747 01 0 35 46 6 31 27 749 01 0 35 46 6 31 27 750 01 0 35 48 6 31 27 750 01 0 35 49 6 31 27 751 01 0	35	27	6 31 27 729 01 0
35 30 6 31 27 732 01 0 35 31 6 31 27 733 01 0 35 32 6 31 27 735 01 0 35 33 6 31 27 735 01 0 35 34 6 31 27 736 01 0 35 35 35 6 31 27 737 01 0 35 36 6 31 27 738 01 0 35 37 6 31 27 739 01 0 35 38 6 31 27 740 01 0 35 39 6 31 27 741 01 0 35 40 6 31 27 742 01 0 35 41 6 31 27 743 01 0 35 42 6 31 27 744 01 0 35 42 6 31 27 745 01 0 35 43 6 31 27 746 01 0 35 44 6 31 27 746 01 0 35 45 6 31 27 748 01 0 35 46 6 31 27 749 01 0 35 48 6 31 27 750 01 0 35 49 6 31 27 751 01 0	35	28	6 31 27 730 01 0
35 31 6 31 27 733 01 0 35 32 6 31 27 734 01 0 35 33 6 31 27 735 01 0 35 34 6 31 27 736 01 0 35 35 6 31 27 737 01 0 35 36 6 31 27 738 01 0 35 36 6 31 27 739 01 0 35 37 6 31 27 740 01 0 35 38 6 31 27 740 01 0 35 39 6 31 27 741 01 0 35 40 6 31 27 742 01 0 35 41 6 31 27 743 01 0 35 42 6 31 27 745 01 0 35 43 6 31 27 745 01 0 35 44 6 31 27 746 01 0 35 45 6 31 27 747 01 0 35 46 6 31 27 749 01 0 35 47 6 31 27 749 01 0 35 48 6 31 27 750 01 0 35 49 6 31 27 751 01 0	35	29	6 31 27 731 01 0
35 32 6 31 27 734 01 0 35 33 6 31 27 735 01 0 35 34 6 31 27 736 01 0 35 35 6 31 27 737 01 0 35 36 6 31 27 738 01 0 35 37 6 31 27 739 01 0 35 38 6 31 27 740 01 0 35 39 6 31 27 741 01 0 35 40 6 31 27 742 01 0 35 41 6 31 27 743 01 0 35 42 6 31 27 745 01 0 35 43 6 31 27 745 01 0 35 44 6 31 27 746 01 0 35 45 6 31 27 747 01 0 35 46 6 31 27 748 01 0 35 46 6 31 27 749 01 0 35 48 6 31 27 750 01 0 35 48 6 31 27 750 01 0 35 49 6 31 27 751 01 0	35	30	6 31 27 732 01 0
35 33 6 31 27 735 01 0 35 34 6 31 27 736 01 0 35 35 6 31 27 737 01 0 35 36 6 31 27 738 01 0 35 37 6 31 27 739 01 0 35 38 6 31 27 740 01 0 35 39 6 31 27 741 01 0 35 40 6 31 27 742 01 0 35 41 6 31 27 743 01 0 35 42 6 31 27 744 01 0 35 43 6 31 27 745 01 0 35 44 6 31 27 746 01 0 35 45 6 31 27 747 01 0 35 46 6 31 27 748 01 0 35 47 6 31 27 749 01 0 35 48 6 31 27 750 01 0 35 49 6 31 27 751 01 0	35	31	6 31 27 733 01 0
35 34 6 31 27 736 01 0 35 35 6 31 27 737 01 0 35 36 6 31 27 738 01 0 35 37 6 31 27 739 01 0 35 38 6 31 27 740 01 0 35 39 6 31 27 741 01 0 35 40 6 31 27 742 01 0 35 41 6 31 27 743 01 0 35 42 6 31 27 744 01 0 35 43 6 31 27 745 01 0 35 44 6 31 27 746 01 0 35 45 6 31 27 747 01 0 35 46 6 31 27 748 01 0 35 47 6 31 27 749 01 0 35 48 6 31 27 750 01 0 35 49 6 31 27 751 01 0	35	32	6 31 27 734 01 0
35 35 6 31 27 737 01 0 35 36 6 31 27 738 01 0 35 37 6 31 27 739 01 0 35 38 6 31 27 740 01 0 35 39 6 31 27 741 01 0 35 40 6 31 27 742 01 0 35 41 6 31 27 743 01 0 35 42 6 31 27 744 01 0 35 43 6 31 27 745 01 0 35 44 6 31 27 746 01 0 35 45 6 31 27 747 01 0 35 46 6 31 27 748 01 0 35 47 6 31 27 749 01 0 35 48 6 31 27 750 01 0 35 49 6 31 27 751 01 0	35	33	6 31 27 735 01 0
35 36 6 31 27 738 01 0 35 37 6 31 27 739 01 0 35 38 6 31 27 740 01 0 35 39 6 31 27 741 01 0 35 40 6 31 27 742 01 0 35 41 6 31 27 743 01 0 35 42 6 31 27 744 01 0 35 43 6 31 27 745 01 0 35 44 6 31 27 746 01 0 35 45 6 31 27 747 01 0 35 46 6 31 27 748 01 0 35 47 6 31 27 749 01 0 35 48 6 31 27 750 01 0 35 49 6 31 27 751 01 0	35	34	6 31 27 736 01 0
35 37 6 31 27 739 01 0 35 38 6 31 27 740 01 0 35 39 6 31 27 742 01 0 35 40 6 31 27 742 01 0 35 41 6 31 27 743 01 0 35 42 6 31 27 744 01 0 35 43 6 31 27 745 01 0 35 44 6 31 27 746 01 0 35 45 6 31 27 747 01 0 35 46 6 31 27 748 01 0 35 47 6 31 27 749 01 0 35 48 6 31 27 750 01 0 35 49 6 31 27 751 01 0	35	35	6 31 27 737 01 0
35 38 6 31 27 740 01 0 35 39 6 31 27 742 01 0 35 40 6 31 27 742 01 0 35 41 6 31 27 743 01 0 35 42 6 31 27 744 01 0 35 43 6 31 27 745 01 0 35 44 6 31 27 746 01 0 35 45 6 31 27 747 01 0 35 46 6 31 27 748 01 0 35 47 6 31 27 749 01 0 35 48 6 31 27 750 01 0 35 49 6 31 27 751 01 0	35	36	6 31 27 738 01 0
35 39 63127741010 35 40 63127742010 35 41 63127743010 35 42 63127744010 35 43 63127745010 35 44 63127746010 35 45 63127747010 35 46 63127748010 35 47 63127749010 35 48 63127750010 35 49 63127751010	35	37	6 31 27 739 01 0
35 40 6 31 27 742 01 0 35 41 6 31 27 743 01 0 35 42 6 31 27 744 01 0 35 43 6 31 27 745 01 0 35 44 6 31 27 746 01 0 35 45 6 31 27 747 01 0 35 46 6 31 27 748 01 0 35 47 6 31 27 749 01 0 35 48 6 31 27 750 01 0 35 49 6 31 27 751 01 0	35	38	6 31 27 740 01 0
35 41 6 31 27 743 01 0 35 42 6 31 27 744 01 0 35 43 6 31 27 745 01 0 35 44 6 31 27 746 01 0 35 45 6 31 27 747 01 0 35 46 6 31 27 748 01 0 35 47 6 31 27 749 01 0 35 48 6 31 27 750 01 0 35 49 6 31 27 751 01 0	35	39	6 31 27 741 01 0
35 42 6 31 27 744 01 0 35 43 6 31 27 745 01 0 35 44 6 31 27 746 01 0 35 45 6 31 27 747 01 0 35 46 6 31 27 748 01 0 35 47 6 31 27 749 01 0 35 48 6 31 27 750 01 0 35 49 6 31 27 751 01 0	35	40	6 31 27 742 01 0
35 43 6 31 27 745 01 0 35 44 6 31 27 746 01 0 35 45 6 31 27 747 01 0 35 46 6 31 27 748 01 0 35 47 6 31 27 749 01 0 35 48 6 31 27 750 01 0 35 49 6 31 27 751 01 0	35	41	6 31 27 743 01 0
35 44 6 31 27 746 01 0 35 45 6 31 27 747 01 0 35 46 6 31 27 748 01 0 35 47 6 31 27 749 01 0 35 48 6 31 27 750 01 0 35 49 6 31 27 751 01 0	35	42	6 31 27 744 01 0
35 45 6 31 27 747 01 0 35 46 6 31 27 748 01 0 35 47 6 31 27 749 01 0 35 48 6 31 27 750 01 0 35 49 6 31 27 751 01 0	35	43	6 31 27 745 01 0
35 46 6 31 27 748 01 0 35 47 6 31 27 749 01 0 35 48 6 31 27 750 01 0 35 49 6 31 27 751 01 0	35	44	6 31 27 746 01 0
35 47 6 31 27 749 01 0 35 48 6 31 27 750 01 0 35 49 6 31 27 751 01 0	35	45	6 31 27 747 01 0
35 48 6 31 27 750 01 0 35 49 6 31 27 751 01 0	35	46	6 31 27 748 01 0
35 49 6 31 27 751 01 0	35	47	6 31 27 749 01 0
	35	48	6 31 27 750 01 0
35 50 6 31 27 752 01 0	35	49	6 31 27 751 01 0
	35	50	6 31 27 752 01 0



TCT ULTRA 50 CORE BIT WITH 3/4" WELDON HOLDER

Very long service life and outstanding cutting performance. Metric dimensions, cutting depth 50 mm.

Cutting depth	Bore Ø	
mm	mm	Part number
50	12	6 31 27 276 01 0
50	13	6 31 27 277 01 0
50	14	6 31 27 278 01 0
50	15	6 31 27 279 01 0
50	15,5	6 31 27 828 01 0
50	16	6 31 27 280 01 0
50	17	6 31 27 281 01 0
50	17,5	6 31 27 829 01 0
50	18	6 31 27 282 01 0
50	19	6 31 27 283 01 0
50	19,5	6 31 27 830 01 0
50	20	6 31 27 284 01 0
50	21	6 31 27 285 01 0
50	22	6 31 27 286 01 0
50	23	6 31 27 287 01 0
50	24	6 31 27 288 01 0
50	25	6 31 27 289 01 0

1

Cutting depth	Bore ∅	5
mm	mm	Part number
50	26	6 31 27 290 01 0
50	26,5	6 31 27 831 01 0
50	27	6 31 27 291 01 0
50	28	6 31 27 292 01 0
50	29	6 31 27 293 01 0
50	30	6 31 27 294 01 0
50	31	6 31 27 295 01 0
50	32	6 31 27 296 01 0
50	33	6 31 27 297 01 0
50	34	6 31 27 298 01 0
50	35	6 31 27 299 01 0
50	36	6 31 27 300 01 0
50	37	6 31 27 301 01 0
50	38	6 31 27 302 01 0
50	39	6 31 27 303 01 0
50	40	6 31 27 304 01 0
50	41	6 31 27 305 01 0
50	42	6 31 27 306 01 0
50	43	6 31 27 307 01 0
50	44	6 31 27 308 01 0
50	45	6 31 27 309 01 0
50	46	6 31 27 310 01 0
50	47	6 31 27 311 01 0
50	48	6 31 27 312 01 0
50	49	6 31 27 313 01 0
50	50	6 31 27 314 01 0

CARBIDE CORE DRILL COATED



TCT ULTRA 35 CORE BIT WITH 3/4" WELDON HOLDER

TiAlSiN surface coating for unique cutting performance and maximum work progress with an extremely long service life. Metric dimensions, cutting depth 35 mm.

Cutting depth	Bore Ø	
mm	mm	Part number
35	14	6 31 27 838 00 3
35	16	6 31 27 838 00 4
35	17,5	6 31 27 838 00 5
35	18	6 31 27 838 00 6
35	20	6 31 27 838 00 7
35	21	6 31 27 838 00 8
35	22	6 31 27 838 00 9
35	24	6 31 27 838 01 1
35	25	6 31 27 838 01 2
35	26	6 31 27 838 01 3
35	26,5	6 31 27 838 01 4
35	28	6 31 27 838 01 5
35	30	6 31 27 838 01 6
35	32	6 31 27 838 01 7
35	33	6 31 27 838 01 8
35	34	6 31 27 838 01 9
35	35	6 31 27 838 02 0
35	36	6 31 27 838 02 1

HSS CORE DRILL



HSS NOVA 25 CORE BIT WITH 3/4" WELDON HOLDER

Industrial standard. Metric dimensions, cutting depth 25 mm.

Cutting depth mm	Bore Ø mm	Part number
25	12	6 31 34 120 05 1
25	13	6 31 34 130 05 1
25	14	6 31 34 140 05 1
25	15	6 31 34 150 05 1
25	16	6 31 34 160 05 1
25	17	6 31 34 170 05 1
25	18	6 31 34 180 05 1
25	19	6 31 34 190 05 1
25	20	6 31 34 200 05 1
25	21	6 31 34 210 05 1
25	22	6 31 34 220 05 1
25	23	6 31 34 230 05 1
25	24	6 31 34 240 05 1
25	25	6 31 34 250 05 1
25	26	6 31 34 260 05 1
25	27	6 31 34 270 05 1
25	28	6 31 34 280 05 1
25	29	6 31 34 290 05 1
25	30	6 31 34 300 05 1
25	31	6 31 34 310 05 1
25	32	6 31 34 320 05 1
25	33	6 31 34 330 05 1
25	34	6 31 34 340 05 1
25	35	6 31 34 350 05 1
25	36	6 31 34 360 05 1
25	37	6 31 34 370 05 1
25	38	6 31 34 380 05 1
25	39	6 31 34 390 05 1
25	40	6 31 34 400 05 1
25	41	6 31 34 410 05 1
25	42	6 31 34 420 05 1
25	43	6 31 34 430 05 1
25	44	6 31 34 440 05 1
25	45	6 31 34 450 05 1
25	46	6 31 34 460 05 1
25	47	6 31 34 470 05 1
25	48	6 31 34 480 05 1
25	49	6 31 34 490 05 1
25	50	6 31 34 500 05 1



HSS NOVA 50 CORE BIT WITH 3/4" WELDON HOLDER

Industrial standard. Metric dimensions, cutting depth 50 mm.

Cutting depth mm	Bore Ø mm	Part number
50	12	6 31 34 120 05 2
50	13	6 31 34 130 05 2
50	14	6 31 34 140 05 2
50	15	6 31 34 150 05 2
50	16	6 31 34 160 05 2
50	17	6 31 34 170 05 2
50	18	6 31 34 180 05 2
50	19	6 31 34 190 05 2
50	20	6 31 34 200 05 2
50	21	6 31 34 210 05 2
50	22	6 31 34 220 05 2
50	23	6 31 34 230 05 2
50	24	6 31 34 240 05 2
50	25	6 31 34 250 05 2
50	26	6 31 34 260 05 2
50	27	6 31 34 270 05 2
50	28	6 31 34 280 05 2
50	29	6 31 34 290 05 2
50	30	6 31 34 300 05 2
50	31	6 31 34 310 05 2
50	32	6 31 34 320 05 2
50	33	6 31 34 330 05 2
50	34	6 31 34 340 05 2
50	35	6 31 34 350 05 2
50	36	6 31 34 360 05 2
50	37	6 31 34 370 05 2
50	38	6 31 34 380 05 2
50	39	6 31 34 390 05 2
50	40	6 31 34 400 05 2
50	41	6 31 34 410 05 2
50	42	6 31 34 420 05 2
50	43	6 31 34 430 05 2
50	44	6 31 34 440 05 2
50	45	6 31 34 450 05 2
50	46	6 31 34 460 05 2
50	47	6 31 34 470 05 2
50	48	6 31 34 480 05 2
50	49	6 31 34 490 05 2
50	50	6 31 34 500 05 2

HSS CORE DRILL SPECIAL



HSS SPECIAL 25 CORE BIT WITH 3/4" WELDON FITTING Long service life. For drilling multi-layered materials in a single process, cutting depth 25 mm.

Cutting depth	Bore Ø	
mm	mm	Part number
25	12	6 31 34 120 30 1
25	13	6 31 34 130 30 1
25	14	6 31 34 140 30 1
25	14,3	6 31 34 143 30 1
25	15	6 31 34 150 30 1
25	16	6 31 34 160 30 1
25	17	6 31 34 170 30 1
25	18	6 31 34 180 30 1
25	20	6 31 34 200 30 1
25	22	6 31 34 220 30 1
25	24	6 31 34 240 30 1
25	26	6 31 34 260 30 1
25	28	6 31 34 280 30 1
25	30	6 31 34 300 30 1
25	32	6 31 34 320 30 1
25	35	6 31 34 350 30 1



HSS SPECIAL 50 CORE DRILL BIT WITH 3/4" WELDON FITTING

Long service life. For drilling multi-layered materials in a single operation. Metric dimensions, cutting depth 50 mm.

Cutting depth mm	Bore Ø mm	Part number
50	12	6 31 34 120 30 2
50	13	6 31 34 130 30 2
50	14	6 31 34 140 30 2
50	15	6 31 34 150 30 2
50	16	6 31 34 160 30 2
50	17	6 31 34 170 30 2
50	18	6 31 34 180 30 2
50	20	6 31 34 200 30 2
50	22	6 31 34 220 30 2
50	24	6 31 34 240 30 2
50	26	6 31 34 260 30 2
50	28	6 31 34 280 30 2
50	30	6 31 34 300 30 2
50	32	6 31 34 320 30 2
50	35	6 31 34 350 30 2
50	36	6 31 34 360 30 2
50	40	6 31 34 400 30 2
50	45	6 31 34 450 30 2
50	50	6 31 34 500 30 2

HSS CORE DRILL COATED



HSS DURA 25 CORE BIT WITH 3/4" WELDON HOLDER

TiN surface coating for outstanding service lives and the best glide properties.

Metric dimensions, cutting depth 25 mm.

Cutting depth mm	Bore Ø mm	Part number
25	12	6 31 34 120 07 5
25	13	6 31 34 130 07 5
25	14	6 31 34 140 07 5
25	15	6 31 34 150 07 5
25	16	6 31 34 160 07 5
25	17	6 31 34 170 07 5
25	18	6 31 34 180 07 5
25	19	6 31 34 190 07 5
25	20	6 31 34 200 07 5
25	21	6 31 34 210 07 5
25	22	6 31 34 220 07 5
25	23	6 31 34 230 07 5
25	24	6 31 34 240 07 5
25	25	6 31 34 250 07 5
25	26	6 31 34 260 07 5
25	27	6 31 34 270 07 5
25	28	6 31 34 280 07 5
25	29	6 31 34 290 07 5
25	30	6 31 34 300 07 5
25	31	6 31 34 310 07 5
25	32	6 31 34 320 07 5
25	33	6 31 34 330 07 5
25	34	6 31 34 340 07 5
25	35	6 31 34 350 07 5
25	36	6 31 34 360 07 5
25	37	6 31 34 370 07 5
25	38	6 31 34 380 07 5
25	39	6 31 34 390 07 5
25	40	6 31 34 400 07 5
25	41	6 31 34 410 07 5
25	42	6 31 34 420 07 5
25	43	6 31 34 430 07 5
25	44	6 31 34 440 07 5
25	45	6 31 34 450 07 5
25	46	6 31 34 460 07 5
25	47	6 31 34 470 07 5
25	48	6 31 34 480 07 5
25	49	6 31 34 490 07 5
25	50	6 31 34 500 07 5



HSS DURA 50 CORE BIT WITH 3/4" WELDON HOLDER

TiN surface coating for outstanding service lives and the best glide properties. Metric dimensions, cutting depth 50 mm.

Cutting depth mm	Bore Ø mm	Part number
50	12	6 31 34 120 07 6
50	13	6 31 34 130 07 6
50	14	6 31 34 140 07 6
50	15	6 31 34 150 07 6
50	16	6 31 34 160 07 6
50	17	6 31 34 170 07 6
50	18	6 31 34 180 07 6
50	19	6 31 34 190 07 6
50	20	6 31 34 200 07 6
50	21	6 31 34 210 07 6
50	22	6 31 34 220 07 6
50	23	6 31 34 230 07 6
50	24	6 31 34 240 07 6
50	25	6 31 34 250 07 6

50 26 6 31 34 260 07 6 50 27 6 31 34 270 07 6 50 28 6 31 34 280 07 6 50 29 6 31 34 300 07 6 50 30 6 31 34 310 07 6 50 31 6 31 34 320 07 6 50 32 6 31 34 330 07 6 50 34 6 31 34 350 07 6 50 35 6 31 34 350 07 6 50 35 6 31 34 350 07 6 50 36 6 31 34 350 07 6 50 36 6 31 34 350 07 6 50 36 6 31 34 350 07 6 50 37 6 31 34 370 07 6 50 38 6 31 34 390 07 6 50 39 6 31 34 400 07 6 50 40 6 31 34 400 07 6 50 41 6 31 34 420 07 6 50 42 6 31 34 420 07 6 50 43 6 31 34 420 07 6 50 43 6 31 34 420 07 6 50 45 6 31 34 450 07 6 <th>Cutting depth</th> <th>Bore Ø mm</th> <th>Part number</th>	Cutting depth	Bore Ø mm	Part number
50 27 6 31 34 270 07 6 50 28 6 31 34 280 07 6 50 29 6 31 34 290 07 6 50 30 6 31 34 300 07 6 50 31 6 31 34 310 07 6 50 32 6 31 34 320 07 6 50 33 6 31 34 330 07 6 50 34 6 31 34 350 07 6 50 35 6 31 34 350 07 6 50 36 6 31 34 350 07 6 50 36 6 31 34 350 07 6 50 37 6 31 34 370 07 6 50 38 6 31 34 390 07 6 50 39 6 31 34 490 07 6 50 40 6 31 34 400 07 6 50 41 6 31 34 400 07 6 50 42 6 31 34 420 07 6 50 43 6 31 34 430 07 6 50 43 6 31 34 440 07 6 50 45 6 31 34 450 07 6 50 45 6 31 34 450 07 6 50 45 6 31 34 450 07 6 50 46 6 31 34 470 07 6 50			
50 28 6 31 34 280 07 6 50 29 6 31 34 290 07 6 50 30 6 31 34 300 07 6 50 31 6 31 34 310 07 6 50 32 6 31 34 320 07 6 50 33 6 31 34 330 07 6 50 34 6 31 34 350 07 6 50 35 6 31 34 350 07 6 50 36 6 31 34 350 07 6 50 37 6 31 34 370 07 6 50 38 6 31 34 380 07 6 50 39 6 31 34 490 07 6 50 40 6 31 34 400 07 6 50 41 6 31 34 400 07 6 50 42 6 31 34 420 07 6 50 43 6 31 34 430 07 6 50 43 6 31 34 440 07 6 50 44 6 31 34 440 07 6 50 45 6 31 34 450 07 6 50 45 6 31 34 450 07 6 50 46 6 31 34 470 07 6 50 46 6 31 34 470 07 6 50 46 6 31 34 480 07 6 50			
50 30 6 31 34 300 07 6 50 31 6 31 34 310 07 6 50 32 6 31 34 320 07 6 50 33 6 31 34 330 07 6 50 34 6 31 34 350 07 6 50 35 6 31 34 350 07 6 50 36 6 31 34 370 07 6 50 37 6 31 34 370 07 6 50 38 6 31 34 380 07 6 50 39 6 31 34 490 07 6 50 40 6 31 34 400 07 6 50 41 6 31 34 410 07 6 50 42 6 31 34 420 07 6 50 43 6 31 34 430 07 6 50 43 6 31 34 440 07 6 50 44 6 31 34 440 07 6 50 45 6 31 34 450 07 6 50 45 6 31 34 450 07 6 50 46 6 31 34 450 07 6 50 46 6 31 34 450 07 6 50 46 6 31 34 450 07 6 50 46 6 31 34 450 07 6 50 48 6 31 34 480 07 6 50			
50 31 6 31 34 310 07 6 50 32 6 31 34 320 07 6 50 33 6 31 34 330 07 6 50 34 6 31 34 350 07 6 50 35 6 31 34 350 07 6 50 36 6 31 34 370 07 6 50 37 6 31 34 380 07 6 50 38 6 31 34 390 07 6 50 39 6 31 34 490 07 6 50 40 6 31 34 400 07 6 50 41 6 31 34 410 07 6 50 42 6 31 34 420 07 6 50 43 6 31 34 430 07 6 50 43 6 31 34 440 07 6 50 44 6 31 34 450 07 6 50 45 6 31 34 450 07 6 50 45 6 31 34 450 07 6 50 46 6 31 34 470 07 6 50 47 6 31 34 470 07 6 50 48 6 31 34 480 07 6 50 49 6 31 34 490 07 6	50	29	6 31 34 290 07 6
50 32 6 31 34 320 07 6 50 33 6 31 34 330 07 6 50 34 6 31 34 350 07 6 50 35 6 31 34 350 07 6 50 36 6 31 34 360 07 6 50 37 6 31 34 370 07 6 50 38 6 31 34 380 07 6 50 39 6 31 34 490 07 6 50 40 6 31 34 400 07 6 50 41 6 31 34 410 07 6 50 42 6 31 34 420 07 6 50 42 6 31 34 420 07 6 50 43 6 31 34 430 07 6 50 44 6 31 34 450 07 6 50 45 6 31 34 450 07 6 50 46 6 31 34 460 07 6 50 47 6 31 34 470 07 6 50 48 6 31 34 480 07 6 50 48 6 31 34 490 07 6	50	30	6 31 34 300 07 6
50 33 6 31 34 330 07 6 50 34 6 31 34 340 07 6 50 35 6 31 34 350 07 6 50 36 6 31 34 370 07 6 50 37 6 31 34 380 07 6 50 38 6 31 34 380 07 6 50 39 6 31 34 490 07 6 50 40 6 31 34 400 07 6 50 41 6 31 34 410 07 6 50 42 6 31 34 420 07 6 50 43 6 31 34 430 07 6 50 44 6 31 34 450 07 6 50 45 6 31 34 450 07 6 50 46 6 31 34 470 07 6 50 46 6 31 34 470 07 6 50 47 6 31 34 480 07 6 50 48 6 31 34 480 07 6 50 48 6 31 34 490 07 6	50	31	6 31 34 310 07 6
50 34 6 31 34 3400 76 50 35 6 31 34 350 07 6 50 36 6 31 34 360 07 6 50 37 6 31 34 370 07 6 50 38 6 31 34 380 07 6 50 39 6 31 34 490 07 6 50 40 6 31 34 400 07 6 50 41 6 31 34 410 07 6 50 42 6 31 34 420 07 6 50 43 6 31 34 430 07 6 50 44 6 31 34 440 07 6 50 45 6 31 34 450 07 6 50 46 6 31 34 460 07 6 50 46 6 31 34 470 07 6 50 47 6 31 34 480 07 6 50 48 6 31 34 480 07 6 50 48 6 31 34 490 07 6	50	32	6 31 34 320 07 6
50 35 6 31 34 350 07 6 50 36 6 31 34 360 07 6 50 37 6 31 34 370 07 6 50 38 6 31 34 380 07 6 50 39 6 31 34 490 07 6 50 40 6 31 34 410 07 6 50 41 6 31 34 420 07 6 50 42 6 31 34 420 07 6 50 43 6 31 34 430 07 6 50 44 6 31 34 440 07 6 50 45 6 31 34 450 07 6 50 46 6 31 34 460 07 6 50 47 6 31 34 470 07 6 50 48 6 31 34 480 07 6 50 48 6 31 34 490 07 6	50	33	6 31 34 330 07 6
50 36 6 31 34 360 07 6 50 37 6 31 34 370 07 6 50 38 6 31 34 380 07 6 50 39 6 31 34 400 07 6 50 40 6 31 34 410 07 6 50 41 6 31 34 420 07 6 50 42 6 31 34 420 07 6 50 43 6 31 34 430 07 6 50 44 6 31 34 450 07 6 50 45 6 31 34 450 07 6 50 46 6 31 34 470 07 6 50 47 6 31 34 470 07 6 50 48 6 31 34 480 07 6 50 49 6 31 34 490 07 6	50	34	6 31 34 340 07 6
50 37 6 31 34 370 07 6 50 38 6 31 34 380 07 6 50 39 6 31 34 400 07 6 50 40 6 31 34 410 07 6 50 41 6 31 34 420 07 6 50 42 6 31 34 420 07 6 50 43 6 31 34 430 07 6 50 44 6 31 34 440 07 6 50 45 6 31 34 450 07 6 50 46 6 31 34 460 07 6 50 47 6 31 34 470 07 6 50 48 6 31 34 480 07 6 50 49 6 31 34 490 07 6	50	35	6 31 34 350 07 6
50 38 6 31 34 380 07 6 50 39 6 31 34 400 07 6 50 40 6 31 34 410 07 6 50 41 6 31 34 410 07 6 50 42 6 31 34 420 07 6 50 43 6 31 34 430 07 6 50 44 6 31 34 440 07 6 50 45 6 31 34 450 07 6 50 46 6 31 34 460 07 6 50 47 6 31 34 470 07 6 50 48 6 31 34 480 07 6 50 49 6 31 34 490 07 6	50	36	6 31 34 360 07 6
50 39 6 31 34 390 07 6 50 40 6 31 34 400 07 6 50 41 6 31 34 410 07 6 50 42 6 31 34 420 07 6 50 43 6 31 34 430 07 6 50 44 6 31 34 440 07 6 50 45 6 31 34 450 07 6 50 46 6 31 34 460 07 6 50 47 6 31 34 470 07 6 50 48 6 31 34 480 07 6 50 49 6 31 34 490 07 6	50	37	6 31 34 370 07 6
50 40 6 31 34 400 07 6 50 41 6 31 34 410 07 6 50 42 6 31 34 420 07 6 50 43 6 31 34 430 07 6 50 44 6 31 34 440 07 6 50 45 6 31 34 450 07 6 50 46 6 31 34 460 07 6 50 47 6 31 34 470 07 6 50 48 6 31 34 480 07 6 50 49 6 31 34 490 07 6	50	38	6 31 34 380 07 6
50 41 6 31 34 410 07 6 50 42 6 31 34 420 07 6 50 43 6 31 34 430 07 6 50 44 6 31 34 440 07 6 50 45 6 31 34 450 07 6 50 46 6 31 34 460 07 6 50 47 6 31 34 470 07 6 50 48 6 31 34 480 07 6 50 49 6 31 34 490 07 6	50	39	6 31 34 390 07 6
50 42 6 31 34 420 07 6 50 43 6 31 34 430 07 6 50 44 6 31 34 440 07 6 50 45 6 31 34 450 07 6 50 46 6 31 34 460 07 6 50 47 6 31 34 470 07 6 50 48 6 31 34 480 07 6 50 49 6 31 34 490 07 6	50	40	6 31 34 400 07 6
50 43 6 31 34 430 07 6 50 44 6 31 34 440 07 6 50 45 6 31 34 450 07 6 50 46 6 31 34 460 07 6 50 47 6 31 34 470 07 6 50 48 6 31 34 480 07 6 50 49 6 31 34 490 07 6	50	41	6 31 34 410 07 6
50 44 6 31 34 440 07 6 50 45 6 31 34 450 07 6 50 46 6 31 34 460 07 6 50 47 6 31 34 470 07 6 50 48 6 31 34 480 07 6 50 49 6 31 34 490 07 6	50	42	6 31 34 420 07 6
50 45 6 31 34 450 07 6 50 46 6 31 34 460 07 6 50 47 6 31 34 470 07 6 50 48 6 31 34 480 07 6 50 49 6 31 34 490 07 6	50	43	6 31 34 430 07 6
50 46 6 31 34 460 07 6 50 47 6 31 34 470 07 6 50 48 6 31 34 480 07 6 50 49 6 31 34 490 07 6	50	44	6 31 34 440 07 6
50 47 6 31 34 470 07 6 50 48 6 31 34 480 07 6 50 49 6 31 34 490 07 6	50	45	6 31 34 450 07 6
50 48 6 31 34 480 07 6 50 49 6 31 34 490 07 6	50	46	6 31 34 460 07 6
50 49 6 31 34 490 07 6	50	47	6 31 34 470 07 6
	50	48	6 31 34 480 07 6
50 50 6 31 34 500 07 6	50	49	6 31 34 490 07 6
	50	50	6 31 34 500 07 6

CENTERING PINS

CENTERING PIN		
Ø	L	
mm	mm	Part number
6,35	82	6 31 34 998 30 0
6,35	100	6 31 34 998 31 0

ADAPTER/DRILL CHUCK



HSS TWIST DRILL WITH 3/4" WELDON FITTING

Cutting depth 35 mm

Part number
6 31 11 036 01 0
6 31 11 018 01 0
6 31 11 034 01 0
6 31 11 019 01 0
6 31 11 020 01 0
6 31 11 035 01 0
6 31 11 021 01 0
6 31 11 022 01 0
6 31 11 037 01 0
6 31 11 023 01 0
6 31 11 024 01 0
6 31 11 025 01 0
6 31 11 026 01 0
6 31 11 027 01 0
6 31 11 028 01 0



HSS TWIST DRILL SET WITH 3/4" WELDON FITTING

Comprising 6 HSS twist drills (diameters of 6, 8, 10, 12, 14 and 16 mm) in a handy plastic storage box. Cutting depth 35 mm

Part number
6 31 11 018 02 0

TAPPING



ADAPTER WITH 3/4" WELDON FITTING

1/4" hexagonal output in accordance with DIN 3126/ISO 1173 – C 6.3

Part number
6 32 06 148 01 0



ADAPTER WITH 3/4" WELDON FITTING

6~mm round shank output for M5-M8 in accordance with DIN 352/ISO 13

Ø	Square	
mm	mm	Part number
6	4,9	6 32 06 146 01 0



ADAPTER WITH 3/4" WELDON FITTING

7 mm round shank output for M10 in accordance with DIN 352/ISO 13

Ø	Square	
mm	mm	Part number
7	5,5	6 32 06 147 01 0



ADAPTER WITH 3/4" WELDON FITTING

9 mm round shank output for M12 in accordance with DIN 352/ISO 13 $\,$

Ø	Square	
mm	mm	Part number
9	7	6 32 06 149 01 0



TAPPING DRILL FOR THROUGH HOLES WITH ADAPTER WITH 3/4" WELDON FITTING

Short version in accordance with DIN 352/ISO 13.

Thread	Part number
M 6	6 31 10 019 03 0
M 8	6 31 10 020 03 0
M 10	6 31 10 021 03 0
M 12	6 31 10 022 03 0



TAPPING DRILL FOR THROUGH HOLES

Short version in accordance with DIN 352/ISO 13.

-				
	L	Ø	Square	
Thread	mm	mm	mm	Part number
M 6	56	6	4,9	6 31 10 019 01 0
M 8	63	6	4,9	6 31 10 020 01 0
M 10	70	7	5,5	6 31 10 021 01 0
M 12	75	9	7	6 31 10 022 01 0



HSS 90° COUNTERSINK BIT

With 1/4" hexagon in accordance with DIN 3126/ISO 1173 – C 6.3

Ø	
mm	Part number
16.5	6 31 11 038 01 0



HSS 90° COUNTERSINK BIT WITH ADAPTER WITH 3/4" WELDON FITTING

Ø	
mm	Part number
16,5	6 31 11 038 02 0



TAPPING DRILL SET FOR THROUGH HOLES

Comprising 1 x M6 threading drill in accordance with DIN 352/ISO 13 with 3/4" Weldon adapter, $1 \times$ HSS twist drill, 5 mm in diameter, with 3/4" Weldon fitting and $1 \times$ HSS 90° countersink bit, 16.5 mm in diameter, with 3/4" Weldon adapter and $1 \times$ hexagon socket wrench in a handy plastic storage box

Thread	Part number
M 6	6 31 10 019 02 0



TAPPING DRILL SET FOR THROUGH HOLES

Comprising 1 x M8 threading drill in accordance with DIN 352/ISO 13 with 3/4" Weldon adapter, 1 x HSS twist drill, 6.8 mm in diameter, with 3/4" Weldon fitting and 1 x HSS 90° countersink bit, 16.5 mm in diameter, with 3/4" Weldon adapter and 1 x hexagon socket wrench in a handy plastic storage box.

Thread	Part number
M 8	6 31 10 020 02 0



TAPPING DRILL SET FOR THROUGH HOLES

Comprising 1 x M10 threading drill in accordance with DIN 352/ISO 13 with 3/4" Weldon adapter, 1 x HSS twist drill, 8.5 mm in diameter, with 3/4" Weldon fitting and 1 x HSS 90° countersink bit, 16.5 mm in diameter, with 3/4" Weldon adapter and 1 x hexagon socket wrench in a handy plastic storage box.

Thread	Part number
M 10	6 31 10 021 02 0



TAPPING DRILL SET FOR THROUGH HOLES

Comprising 1 x M12 threading drill in accordance with DIN 352/ISO 13 with 3/4" Weldon adapter, 1 x HSS twist drill, 10.2 mm in diameter, with 3/4" Weldon fitting and 1 x HSS 90° countersink bit, 16.5 mm in diameter, with 3/4" Weldon adapter and 1 x hexagon socket wrench in a handy plastic storage box.

Thread	Part number
M 12	6 31 10 022 02 0

CLAMPING FIXTURES



VACUUM PLATE

for anti-magnetic materials and structured bases (corrugated sheet, stud plate etc.) Vacuum plate $396 \times 200 \times 95$ mm

Part number 9 26 02 057 01 7



VACUUM PUMP

Vacuum pump 230 V 50 Hz, 92 W, suction volume $0.015 \, \text{m}^3$ /min, - $0.8 \, \text{bar}$, weight 2.5 kg, incl. suction hose, degree of protection: IP 30, protection class: I, switch-on duration: 15-min operation / 10-min pause (interval)

Part number
9 26 01 022 01 3



SUCTION PLATE

for anti-magnetic materials, 250 x 330 x 110 mm

Part number 9 26 02 054 01 6



PIPE DRILLING DEVICE

incl. clamping strap, for positioning bores on pipes with pipe Ø of 60 to 300 mm, 220 x 130 mm.

Part number 9 26 02 055 01 0

COOLING



PUMP

Capacity approx. 450 ml.

Part number 3 21 32 022 00 7

REPLACEMENT HOSE

for hand pump 3 21 32 022 00 7.

Part number 3 14 14 054 00 8



CUTTING PASTE

Lubricating agents for working on sheet metals.

Part number 3 21 32 046 00 0



COOLANT TANK

Capacity approx. $500 \, \text{ml}$. Scope for regulating the flow rate. Suitable for KBE 32 and KBE 32 QW.

Part number 3 21 31 038 02 0

OTHER ACCESSORIES



MAGBRUSH

Practical tool with high magnetic force for quick and easy collection of magnetic metal swarf.

Part number 6 42 01 005 01 0

ACCESSORY SETS



STRUCTURAL STEEL-SET 3/4" WELDON / HSS NOVA 25

- + User set of HSS core drill bits in an L-BOXX.
- + The most common HSS core drill bit diameters in one set.

 Perfect for steel and bridge construction.
- Perfect for steel and bridge construction.

 + HSS NOVA 25 core drill bit: Long service life and particularly resistant to shock and impact: thanks to its tough cutting edges and outstanding HSS steel with a hardness of 64 HRC, the core drill bit is perfectly designed for tough use in steel construction and installation work.
- + Twist drills and countersink bits: With this set you can have everything you need for core drilling and blind holes readily to hand.
- + L-BOXX system: Keep things stowed clearly, tidily and safely. Thanks to the tray for small parts, there is room for all accessories and the L-BOXXs can also be joined together and stacked with ease.
- + HSS twist drills, 35 mm cutting depth (3 each of diameter 10 mm and 12 mm)
- + HSS NOVA 25 core drill bits, 25 mm cutting depth (3 each of diameter 14 / 16 / 18 / 20 / 22 mm)
- + 2 x 82 mm centring pin
- + 1 cutting paste
- + 1 L-BOXX 136 for accessories

Part number

3 39 01 680 42 0



MACHINERY-SET 3/4" WELDON

- + User set comprising a large number of tapping accessories in an L-BOXX
- + The most common tapping drills for through holes in one set. Perfect for the construction of machines and machine tools.
- + Twist drills and countersink bits: With this set you can have everything you need for core drilling and blind holes readily to hand.
- + L-BOXX system: Keep things stowed clearly, tidily and safely. Thanks to the tray for small parts, there is room for all accessories and the L-BOXXs can also be joined together and stacked with ease.
- + Tapping drills (2 each of M6, M8, M10, M12 (DIN 352 / ISO 13))
- + HSS twist drills, 35 mm cutting depth (1 each of diameter 5.0 / 6.8 / 8.5 / 10.2 mm)
- + 4 x HSS 90° countersink bits, diameter 16.5 mm
- + 1 cutting paste
- + 1 L-BOXX 136 for accessories

Part number

3 39 01 680 41 0



KBC 36 MAGFORCE TRUCKFRAME-SET 3/4" WELDON / HSS SPECIAL 25

- + User set of HSS core drill bits in an L-BOXX
- + The most common HSS SPECIAL core drill bit diameters in one set. Perfect for the construction of frames for vehicles and special vehicles.
- + HSS SPECIAL 25 core drill bit: Thanks to its special cutting geometry, the core is cut from the inside out and materials of multiple layers can therefore be drilled in a single process.
- + Twist drills and countersink bits: With this set you can have everything you need for core drilling and blind holes readily to hand
- + L-BOXX system: Keep things stowed clearly, tidily and safely. Thanks to the tray for small parts, there is room for all accessories and the L-BOXXs can also be joined together and stacked with ease.
- + HSS twist drills, 35 mm cutting depth (2 each of diameter 8 mm and 10 mm) $\,$
- + HSS SPECIAL 25 core drill bits, 25 mm cutting depth (2 each of diameter 12/14/16/18/20/22/24/26 mm)
- + 2 x 82 mm centring pin
- + 1 cutting paste
- + 1 L-BOXX 136 for accessories

Part number

3 39 01 680 43 0

1 UNIVERSAL











AKBU 35 PMQW AS

AKBU 35 PMQ AS

Small and powerful singlespeed cordless universal magnetic core drill with forward/reverse running, MT2 tool mounting, permanent magnet and maximum functionality for mobile working on the construction site.

KBU 35 QW KBU 35 Q

Small and powerful single-speed universal magnetic core drill with clockwise/ anti-clockwise operation

KBU 35 PQW KBU 35 PQ

Small and powerful single-speed universal magnetic core drill with clockwise/ anti-clockwise operation, and maximum functionality permanent magnet and for flexible working on the construction site. permanent magnet and maximum functionality for very safe and for very safe and flexible working on the construction site.

KBU 35 MQW KBU 35 MQ

Small and powerful single-speed universal magnetic core drill with clockwise/anti-clockwise operation, MT2 tool mounting and maximum functionality for flexible working on the construction site.

	con	construction site.		ruction site. const	construction site.	
PAGE		36 / 36	40 / 40	42 / 42	43 / 43	
Core drilling in metal with a Ø up to 35 n	mm	++	++	++	++	
Core drilling in metal with a Ø up to 50 r	mm					
Core drilling in metal with a Ø up to 65 n	mm					
Core drilling in metal with a Ø up to 110 r	mm					
Twist drills with drill chuck (DIN 338)		+	+	+	+	
Twist drills with MK fitting (DIN 345)		++			++	
Tapping		++	++	++	++	
Countersinking		++	++	++	++	
Reaming		++	++	++	++	
Working overhead		++	++	++	++	
Installation work		++	++	++	++	
Workshop jobs		++	++	++	++	
Electronic magnetic holding force						
Magnetic holding force display		•	•	•	•	
Reversible rotation		•	•	•	•	
Variable speed control		•	•	•	•	
Memory function		•	•	•	•	
Speed-controlled electronics (tacho)		•	•	•	•	
Torque slipping clutch						
Tilt sensor		•	•	•	•	
Input	W		1 100	1 010	1 100	
Output	W		550	550	550	
Battery voltage	V	18				
Speed, full load	rpm	130 - 520	130 - 520	130-520	130 - 520	
Load speed in speed 1	rpm					
Load speed in speed 2	rpm					
Load speed in speed 3	rpm					
Load speed in speed 4	rpm					
Tool Holder		MT 2			MT 2	
Carbide core drill bit max. Ø	mm	35	35	35	35	
HSS core drill max. Ø	mm	35	35	35	35	
Core drill holder $QW = 3/4$ " Weldo $Q = Quick!N$	n	3/4" Weldon QuickIN	3/4" Weldon QuickIN	3/4" Weldon QuickIN	3/4" Weldon QuickIN	
Stroke	mm	135	135	135	135	
Total stroke range	mm	260	260	260	260	
Adjustment range for drill jigs	mm					
Swivel range for drill jigs						
Magnetic holding power	N	9,000	10,000	9,000	10,000	
Magnetic foot dimensions	mm	195 x 70	175 x 80	175 x 80	175 x 80	
Weight according to EPTA	kg		10,7	12,5	10,7	
Weight without storage battery	kg	12,2				

⁺ suitability

⁺⁺ optimal suitability

[•] included











KBU 35-2 QW

KBU 35-2 Q

Small and powerful 2-speed universal magnetic core drill with clockwise/anti-clockwise operation and high speed for efficient twist drilling on the construction site.

KBM 50 Q

Lightweight and powerful 2-speed universal magnetic core drill with clockwise/anti-clockwise operation and maximum functionality for flexible working in the workshop and on the construction

KBM 50 UQW

KBM 50 U

Lightweight and powerful 2-speed universal magnetic core drill with clockwise/anti-clockwise operation, MT3 tool mounting and maximum functionality for flexible working in the workshop and on the construction

KBM 65 UQW

KBM 65 U

Powerful and very high-performance 2-speed universal magnetic core drill with clockwise/ anti-clockwise operation, MT3 tool mounting, fine adjustment and maximum functionality for flexible working in the workshop.

KBU 110-4 M

High-performance and powerful 4-speed universal magnetic core drill with forward/reverse running, MT4 tool mounting and maximum functionality for the toughest drilling jobs in the workshop.

est drilling jobs in the nop.	functionality for flexible working in the workshop.	working in the workshop and on the construction site.	and on the construction site.	on the construction site.
48	47 / 47	46 / 46	45	44 / 44
++	++	++	++	++
++	++	++	++	
++	++			
++				
++	+	+	+	++
++	++	++		
++	++	++	++	++
++	++	++	++	++
++	++	++	++	++
- 1	+	+	+	++
4	++	++	++	++
++	++	++	++	++
	•	•	•	
•	•	•	•	•
•	•	•	•	•
•	•	•	•	•
	•	•	•	•
	•	•	•	•
				•
1 700	1 300	1 200	1 200	1 100
850	730	610	640	550
000	730	010	040	550
60 / 120	120 - 240	130 - 260	130 - 260	130 - 520
90 / 170	260 - 520	260 - 520	260 - 520	400 - 1,600
150 / 300				
230 / 430				
MK 4	MK 3	MK 3		
110	65	50	50	35
80	45	40	40	35
Weldon 32	3/4" Weldon QuickIN	3/4" Weldon QuickIN	QuickIN	3/4" Weldon QuickIN
280	145	145	145	135
400	315	315	315	260
	6			
	7°			
23 000	14 000	12 500	12 500	9 500
240 x 120	205 x 95	195 x 90	195 x 90	186 x 70
35,00	15,70	14,00	14,00	11,10

AKBU 35 PMQ AS

AKBU 35 PMQW AS







 $Small\ and\ powerful\ single-speed\ cordless\ universal\ magnetic\ core\ drill\ with\ forward/reverse\ running,\ MT2\ tool\ mounting,$ and maximum functionality for mobile working on the construction site

		permanent magnet and maximum functionality for mobile w	vorking on the construction site.
Battery voltage	V	18	18
Battery compatibility		Li-ion/ProCORE Li-ion**	Li-ion/ProCORE Li-ion**
Battery interface		18 V AMPShare	18 V AMPShare
Motor		brushless	brushless
Speed, full load	rpm	130 - 520	130 - 520
Tool Holder		MT 2	MT 2
Carbide core drill bit max. Ø	mm	35	35
HSS core drill max. Ø	mm	35	35
Core drill, drilling depth max.	mm	50(75)*	50(75)*
Twist drill max. Ø	mm	18	18
Tapping		M 14	M 14
Countersinking max. Ø	mm	30	30
Reaming max. Ø	mm	18	18
Core drill holder		QuickIN	3/4" Weldon
Changing the core bit		tool-free	tool-free
Stroke	mm	135	135
Total stroke range	mm	260	260
Magnetic holding power	N	9,000	9,000
Magnetic foot dimensions	mm	195 x 70	195 x 70
Weight without storage battery	kg	12,2	12,2

FEIN BENEFITS

- + Extremely wear-resistant and durable tool concept thanks to brushless motor as well as high material quality and workmanship. Designed for up to 60,000 holes during a 300 h usage period.
- $Small\ and\ light\ tool\ with\ increased\ work\ progress\ of\ up\ to\ 25\ \%,\ offering\ unique\ productivity\ and\ battery\ life\ compared\ with\ progress\ of\ up\ to\ 25\ \%,\ offering\ unique\ productivity\ and\ battery\ life\ compared\ with\ progress\ of\ up\ to\ 25\ \%,\ offering\ unique\ productivity\ and\ battery\ life\ compared\ with\ progress\ of\ up\ to\ 25\ \%,\ offering\ unique\ productivity\ and\ battery\ life\ compared\ with\ progress\ of\ up\ to\ 25\ \%,\ offering\ unique\ productivity\ and\ battery\ life\ compared\ with\ progress\ of\ up\ to\ 25\ \%,\ offering\ unique\ productivity\ and\ battery\ life\ compared\ with\ progress\ of\ up\ to\ 25\ \%,\ offering\ unique\ productivity\ and\ battery\ life\ progress\ of\ up\ to\ 25\ \%,\ offering\ unique\ productivity\ and\ battery\ life\ progress\ of\ up\ to\ 25\ \%,\ offering\ unique\ productivity\ and\ battery\ life\ progress\ of\ up\ to\ 25\ \%,\ offering\ unique\ productivity\ and\ battery\ life\ progress\ of\ up\ to\ 25\ \%,\ offering\ unique\ productivity\ and\ battery\ life\ progress\ of\ up\ to\ 25\ \%,\ offering\ unique\ productivity\ and\ battery\ life\ progress\ of\ up\ to\ 25\ \%,\ offering\ unique\ productivity\ and\ battery\ life\ progress\ up\ unique\ productivity\ up\ unique\ productivity\ life\ progress\ up\ unique\ productivity\ up\ unique\ up\ unique\ unique\ unique\ up\ unique\ unique\ unique\ unique\ unique\ unique\$ the competition. Using 18 V 12 Ah AMPShare ProCORE batteries, up to 48 holes can be drilled per battery charge (carbide core drill bit, diameter 18 mm, S235 12 mm).
- Weighing 12.2 kg, it's the lightest cordless universal core drill in the world. Maximum flexibility for all mobile drilling work, such as core drilling, twist drilling, tapping, countersinking and reaming thanks to forward/reverse running, electronic speed setting and a 260 mm stroke range.
- Intuitive operating concept avoids mix-ups and can be clearly seen by the user. Convenient magnetic holding force display.
- Tilt sensor stops the drill motor when the tool slips or tilts.
- MT2 tool mounting.
- Secure positioning thanks to extra narrow permanent magnet with magnetic bias for convenient and simple alignment.
- Speed saving "memory function". Compatible with Bosch Professional 18 V batteries (available since 2008) and AMPShare batteries.
- COOLPACK 2.0 technology delivers a 135 % longer battery life and therefore makes longer operating times possible.
- State-of-the-art cell technology and intelligent battery management deliver 87 % more power than with conventional batteries
- ProCORE Li-Ion battery with high-power cells, charge status indicator and "Electronic Cell Protection" (ECP). ECP protects against overload, overheating and total discharge.
- Also available with accessories.
- ** Outstanding performance with AMPShare ProCORE 18 V 8.0 Ah / 12.0 Ah

SUPPLIED

1 cordless magnetic core drill, 1 x coolant pump, 1 lashing strap, 1 swarf hook, 1 centring pin 100 mm, 1 contact guard,

Part number	7 170 03 61 00 0	7 170 04 61 00 0
FAN	4014586898285	4014586898292

AKBU 35 PMQW 18 V AS Battery set containing 12 Ah ProCORE battery. Perfect for mobile working on the construction site.

SET 1X 12 AH



AMP Share

SUPPLIED

1 cordless magnetic core drill, 1 x coolant pump, 1 lashing strap, 1 swarf hook, 1 centring pin 100 mm, 1 contact guard, 1 drift key, 1 ProCORE 18 V / 12.0 Ah Li-Ion battery, 1 x GAL18 V-160 AS rapid charger, 1 plastic carrying case

For accessories, see page 51

Battery voltage	V	18
Battery compatibility		Li-ion/ProCORE Li-ion**
Battery interface		18 V AMPShare
Motor		brushless
Speed, full load	rpm	130 - 520
Tool Holder		MT 2
Carbide core drill bit max. Ø	mm	35
HSS core drill max. Ø	mm	35
Core drill, drilling depth max.	mm	50(75)*
Twist drill max. Ø	mm	18
Tapping		M 14
Countersinking max. Ø	mm	31
Reaming max. Ø	mm	18
Core drill holder		3/4" Weldon
Changing the core bit		tool-free
Stroke	mm	135
Total stroke range	mm	260
Magnetic holding power	N	9,000
Magnetic foot dimensions	mm	195 x 70
Weight without storage battery	kg	12,2

Part number	7 170 04 63 00 0
EAN	4014586899602

FEIN BENEFITS

- + Extremely wear-resistant and durable tool concent thanks to brushless motor as well as high material quality and workmanship. Designed for up to 60,000 holes during a 300 h usage period.
- + Small and light tool with increased work progress of up to 25 %, offering unique productivity and battery life compared with the competition. Using 18 V 12 Ah AMPShare ProCORE batteries, up to 48 holes can be drilled per battery charge (carbide core drill bit, diameter 18 mm, S235 12 mm).
- Weighing 12.2 kg, it's the lightest cordless universal core drill in the world. Maximum flexibility for all mobile drilling work, such as core drilling, twist drilling, tapping, countersinking and reaming thanks to forward/reverse running, electronic speed setting and a 260 mm stroke range.
- + Intuitive operating concept avoids mix-ups and can be clearly seen by the user.
- Convenient magnetic holding force display.
- Tilt sensor stops the drill motor when the tool slips or tilts.
- MT2 tool mounting.
- Secure positioning thanks to extra narrow permanent magnet with magnetic bias for convenient and simple alignment.
- Speed saving "memory function".
- Compatible with Bosch Professional 18 V batteries (available since 2008) and AMPShare batteries.
 COOLPACK 2.0 technology delivers a 135 % longer
- battery life and therefore makes longer operating times possible.
- State-of-the-art cell technology and intelligent battery management deliver 87 % more power than with conventional batteries.
- ProCORE Li-Ion battery with high-power cells, charge status indicator and "Electronic Cell Protection" (ECP) ECP protects against overload, overheating and total discharge.
- Also available with accessories.
- Outstanding performance with AMPShare ProCORE 18 V 8.0 Ah / 12.0 Ah

AKBU 35 PMQW 18 V AS Battery set containing 2 x 8 Ah ProCORE batteries. Perfect for mobile working on the construction site.

SET 2X 8 AH



SUPPLIED

1 cordless magnetic core drill, 1 x coolant pump, 1 lashing strap, 1 swarf hook, 1 centring pin 100 mm. 1 contact guard, 1 drift key, 2 ProCORE 18 V / 8.0 Ah Li-Ion batteries, 1 x GAL18 V-160 AS rapid charger, 1 plastic carrying case

For accessories, see page 51

Battery voltage	V	18
Battery compatibility		Li-ion/ProCORE Li-ion**
Battery interface		18 V AMPShare
Motor		brushless
Speed, full load	rpm	130 - 520
Tool Holder		MT 2
Carbide core drill bit max. Ø	mm	35
HSS core drill max. Ø	mm	35
Core drill, drilling depth max.	mm	50(75)*
Twist drill max. Ø	mm	18
Tapping		M 14
Tapping Countersinking max. Ø	mm	M 14
	mm mm	
Countersinking max. Ø		31
Countersinking max. Ø Reaming max. Ø		31 18
Countersinking max. Ø Reaming max. Ø Core drill holder		31 18 3/4" Weldon
Countersinking max. Ø Reaming max. Ø Core drill holder Changing the core bit	mm	31 18 3/4" Weldon tool-free
Countersinking max. Ø Reaming max. Ø Core drill holder Changing the core bit Stroke	mm	31 18 3/4" Weldon tool-free 135
Countersinking max. Ø Reaming max. Ø Core drill holder Changing the core bit Stroke Total stroke range	mm mm	31 18 3/4" Weldon tool-free 135 260

Part number	7 170 04 64 00 0
EAN	4014586899633

- + Extremely wear-resistant and durable tool concept thanks to brushless motor as well as high material quality and workmanship. Designed for up to 60,000 holes during a 300 h usage period.
- Small and light tool with increased work progress of up to 25 %, offering unique productivity and battery life compared with the competition. Using 18 V 8 Ah AMPShare ProCORE batteries, up to 31 holes can be drilled per battery charge (carbide core drill bit,
- diameter 18 mm, S235 12 mm).

 + Weighing 12.2 kg, it's the lightest cordless universal core drill in the world. Maximum flexibility for all mobile drilling work, such as core drilling, twist drilling, tapping, countersinking and reaming thanks to forward/reverse running, electronic speed setting and a 260 mm stroke range.
- Intuitive operating concept avoids mix-ups and can be clearly seen by the user.
- Convenient magnetic holding force display.

 Tilt sensor stops the drill motor when the tool slips or

- MT2 tool mounting.
 Secure positioning thanks to extra narrow permanent magnet with magnetic bias for convenient and simple alignment.
- Speed saving "memory function".
- Compatible with Bosch Professional 18 V batteries (available since 2008) and AMPShare batteries.
- COOLPACK 2.0 technology delivers a 135 % longer battery life and therefore makes longer operating times possible.
- State-of-the-art cell technology and intelligent battery management deliver 87 % more power than with conventional batteries
- ProCORE Li-Ion battery with high-power cells, charge status indicator and "Electronic Cell Protection" (ECP) ECP protects against overload, overheating and total discharge.
- Also available with accessories.
- Outstanding performance with AMPShare ProCORE 18 V 8.0 Ah / 12.0 Ah

AKBU 35 PMQW AS CONSTRUCTION SITE SET 3/4" WELDON / HSS NOVA 50



SUPPLIED

1 cordless magnetic core drill, 1 x coolant pump, 1 lashing strap, 1 swarf hook, 1 centring pin 100 mm, 1 contact guard, 1 drift key, 1 plastic carrying case, 1 set of twist drills, 6 parts, 1 SUPRA-SK quick-clamp drill chuck, 1–13 mm with 3/4" Weldon, 1 HSS twist drill, 35 mm cutting depth (diameter 10 mm), 6 HSS NOVA 50 core drill bits, 50 mm cutting depth (diameter 12 / 14 / 16 / 18 / 20 / 22 mm), 2 x 100 mm centring pins, 1 cutting paste, 1 L-BOXX 136 for accessories

For accessories, see page 51

AKBU 35 PMQW AS, an extremely versatile cordless core drill coupled with extensive HSS core drilling accessories and HSS cobalt 5 % twist drilling accessories. Perfect for steel and bridge construction.

Battery voltage	V	18
Battery compatibility		Li-ion/ProCORE Li-ion**
Battery interface		18 V AMPShare
Motor		brushless
Speed, full load	rpm	130 - 520
Tool Holder		MT 2
Carbide core drill bit max. Ø	mm	35
HSS core drill max. Ø	mm	35
Core drill, drilling depth max.	mm	50(75)*
Twist drill max. Ø	mm	18
Tapping		M 14
Countersinking max. Ø	mm	30
Reaming max. Ø	mm	18
Core drill holder		3/4" Weldon
Changing the core bit		tool-free
Stroke	mm	135
Total stroke range	mm	260
Total stroke range Magnetic holding power	mm N	260 9 000
Magnetic holding power	N	9 000

Part number	7 170 04 62 00 0
EAN	4014586899596

FEIN BENEFITS

- Extremely wear-resistant and durable tool concept thanks to brushless motor as well as high material quality and workmanship. Designed for up to 60,000 holes during a 300 h usage period.
- + Small and light tool with increased work progress of up to 25 %, offering unique productivity and battery life compared with the competition. Using 18 V 12 Ah AMPShare ProCORE batteries, up to 48 holes can be drilled per battery charge (carbide core drill bit, diameter 18 mm, \$235 12 mm).
- Weighing 12.2 kg, it's the lightest cordless universal core drill in the world. Maximum flexibility for all mobile drilling work, such as core drilling, twist drilling, tapping, countersinking and reaming thanks to forward/reverse running, electronic speed setting and a 260 mm stroke range.
- a 260 mm stroke range. **HSS NOVA 50 core drill bit:** Extremely resistant to shock and impact, perfectly designed for tough use in steel construction and installation work. Thanks to its tough cutting edges and outstanding HSS steel with a hardness of 64 HRC, the core drill bit also delivers an impressively long service life.
- HSS cobalt 5 % twist drill set: HSS cobalt alloy twist drills, diameter 2 / 3 / 4 / 5 / 6 / 8 mm. Particularly suitable for working with stainless and alloyed steels.
- SUPRA SK quick-clamp drill chuck: metal quickclamping drill chuck with a clamping range of 1–13 mm. Simple, rapid and tool-free clamping for maximum convenience. Automatically self-tightening clamping jaws for precisely axial drilling tool concentricity.
- **L-BOXX system:** Keep things stowed clearly, tidily and safely. Thanks to the tray for small parts, there is room for all accessories and the L-BOXXs can also be joined together and stacked with ease.
- * Also available with accessories.
- ** Outstanding performance with AMPShare ProCORE 18 V 8.0 Ah / 12.0 Ah

AKBU 35 PMQW 18 V AS CONSTRUCTION SITE 1X 12 AH SET 3/4" WELDON / HSS NOVA 50



SUPPLIED

1 cordless magnetic core drill, 1 x coolant pump, 1 lashing strap, 1 swarf hook, 1 centring pin 100 mm, 1 contact guard, 1 drift key, 1 plastic carrying case, 1 ProCORE 18 V / 12.0 Ah Li-Ion battery, 1 x GAL18 V-160 AS rapid charger, 1 set of twist drills, 6 parts, 1 SUPRA-SK quick-clamp drill chuck, 1–13 mm with $3/4^\circ$ Weldon, 1 HSS twist drill, 35 mm cutting depth (diameter 10 mm), 6 HSS NOVA 50 core drill bits, 50 mm cutting depth (diameter 12 / 14 / 16 / 18 / 20 / 22 mm), 2 x 100 mm centring pins, 1 cutting paste, 1 L-BOXX 136 for accessories

For accessories, see page 51

AKBU 35 PMQW 18 V ASAKBU 35 PMQW 18 V / 12 Ah AS, an extremely versatile cordless core drill coupled with extensive HSS core drilling accessories and HSS cobalt 5 % twist drilling accessories. Perfect for steel and bridge construction.

Battery voltage	V	18
Battery compatibility		Li-ion/ProCORE Li-ion**
Battery interface		18 V AMPShare
Motor		brushless
Speed, full load	rpm	130 - 520
Tool Holder		MT 2
Carbide core drill bit max. Ø	mm	35
HSS core drill max. Ø	mm	35
Core drill, drilling depth max.	mm	50(75)*
Twist drill max. Ø	mm	18
Tapping		M 14
Countersinking max. Ø	mm	30
Reaming max. Ø	mm	18
Core drill holder		3/4" Weldon
Changing the core bit		tool-free
Stroke	mm	135
Total stroke range	mm	260
Magnetic holding power	N	9,000
Magnetic foot dimensions	mm	195 x 70
Weight without storage battery	kg	12,2

Part number	7 170 04 65 00 0
EAN	4014586899688

- Extremely wear-resistant and durable tool concept thanks to brushless motor as well as high material quality and workmanship. Designed for up to 60,000 holes during a 300 h usage period.
- + Small and light tool with increased work progress of up to 25 %, offering unique productivity and battery life compared with the competition. Using 18 V 12 Ah AMPShare ProCORE batteries, up to 48 holes can be drilled per battery charge (carbide core drill bit, diameter 18 mm, S235 12 mm).
- + Weighing 12.2 kg, it's the lightest cordless universal core drill in the world. Maximum flexibility for all mobile drilling work, such as core drilling, twist drilling, tapping, countersinking and reaming thanks to forward/reverse running, electronic speed setting and a 260 mm stroke range.
- COOLPACK 2.0 technology delivers a 135 % longer battery life and therefore makes longer operating times possible.
- State-of-the-art cell technology and intelligent battery management deliver 87 % more power than with conventional batteries.
- ProCORE Li-lon battery with high-power cells, charge status indicator and "Electronic Cell Protection" (ECP). ECP protects against overload, overheating and total discharge.
- HSS NOVA 50 core drill bit: Extremely resistant to shock and impact, perfectly designed for tough use in steel construction and installation work. Thanks to its tough cutting edges and outstanding HSS steel with a hardness of 64 HRC, the core drill bit also delivers an impressively long service life.
- **HSS cobalt 5 % twist drill set:** HSS cobalt alloy twist drills, diameter 2 / 3 / 4 / 5 / 6 / 8 mm. Particularly suitable for working with stainless and alloyed steels.
- SUPRA SK quick-clamp drill chuck: metal quickclamping drill chuck with a clamping range of 1–13 mm. Simple, rapid and tool-free clamping for maximum convenience. Automatically self-tightening clamping iaws for precisely axial drilling tool concentricity.
- jaws for precisely axial drilling tool concentricity. **L-BOXX system:** Keep things stowed clearly, tidily and safely. Thanks to the tray for small parts, there is room for all accessories and the L-BOXXs can also be joined together and stacked with ease.
- * Also available with accessories
- ** Outstanding performance with AMPShare ProCORE 18 V 8.0 Ah / 12.0 Ah

AKBU 35 PMQW 18 V AS CONSTRUCTION SITE 2X 8 AH SET 3/4" WELDON / HSS NOVA 50



SUPPLIED

1 cordless magnetic core drill,
1 x coolant pump, 1 lashing strap,
1 swarf hook, 1 centring pin 100 mm,
1 contact guard, 1 drift key,
2 ProCORE 18 V / 8.0 Ah Li-lon
batteries, 1 x GAL18 V-160 AS rapid
charger, 1 plastic carrying case,
1 set of twist drills, 6 parts,
1 SUPRA-SK quick-clamp drill chuck,
1–13 mm with 3/4" Weldon,
1 HSS twist drill, 35 mm cutting depth
(diameter 10 mm), 6 HSS NOVA 50
core drill bits, 50 mm cutting depth
(diameter 12 / 14 / 16 / 18 / 20 /
22 mm), 2 x 100 mm centring pins,
1 cutting paste, 1 L-BOXX 136 for
accessories

For accessories, see page 51

AKBU 35 PMQW 18 V ASAKBU 35 PMQW 18 V / 8 Ah AS, an extremely versatile cordless core drill coupled with extensive HSS core drilling accessories and HSS cobalt 5 % twist drilling accessories. Perfect for steel and bridge construction.

Battery voltage	V	18
Battery compatibility		Li-ion/ProCORE Li-ion**
Battery interface		18 V AMPShare
Motor		brushless
Speed, full load	rpm	130 - 520
Tool Holder		MT 2
Carbide core drill bit max. Ø	mm	35
HSS core drill max. Ø	mm	35
Core drill, drilling depth max.	mm	50(75)*
Twist drill max. Ø	mm	18
Tapping		M 14
Countersinking max. Ø		70
Counterstriking max. Ø	mm	30
Reaming max. Ø	mm	18
Reaming max. Ø		18
Reaming max. Ø Core drill holder		18 3/4" Weldon
Reaming max. Ø Core drill holder Changing the core bit	mm	18 3/4" Weldon tool-free
Reaming max. Ø Core drill holder Changing the core bit Stroke	mm	18 3/4" Weldon tool-free 135
Reaming max. Ø Core drill holder Changing the core bit Stroke Total stroke range	mm mm mm	18 3/4" Weldon tool-free 135 260
Reaming max. Ø Core drill holder Changing the core bit Stroke Total stroke range Magnetic holding power	mm mm mm	18 3/4" Weldon tool-free 135 260 9,000

Part number	7 170 04 66 00 0
EAN	4014586899718

- Extremely wear-resistant and durable tool concept thanks to brushless motor as well as high material quality and workmanship. Designed for up to 60,000 holes during a 300 h usage period.
- + Small and light tool with increased work progress of up to 25 %, offering unique productivity and battery life compared with the competition. Using 18 V 8 Ah AMPShare ProCORE batteries, up to 31 holes can be drilled per battery charge (carbide core drill bit, diameter 18 mm, S235 12 mm).
- diameter 18 mm, S235 12 mm).

 + Weighing 12.2 kg, it's the lightest cordless universal core drill in the world. Maximum flexibility for all mobile drilling work, such as core drilling, twist drilling, tapping, countersinking and reaming thanks to forward/reverse running, electronic speed setting and a 260 mm stroke range.
- a 260 mm stroke range.

 + COOLPACK 2.0 technology delivers a 135 % longer battery life and therefore makes longer operating times possible.
- State-of-the-art cell technology and intelligent battery management deliver 87 % more power than with conventional batteries.
- ProCORE Li-lon battery with high-power cells, charge status indicator and "Electronic Cell Protection" (ECP). ECP protects against overload, overheating and total discharge.
- discharge.

 HSS NOVA 50 core drill bit: Extremely resistant to shock and impact, perfectly designed for tough use in steel construction and installation work. Thanks to its tough cutting edges and outstanding HSS steel with a hardness of 64 HRC, the core drill bit also delivers an impressively long service life.
- HSS cobalt 5 % twist drill set: HSS cobalt alloy twist drills, diameter 2 / 3 / 4 / 5 / 6 / 8 mm. Particularly suitable for working with stainless and alloyed steels.
- working with stainless and alloyed steels.

 SUPRA SK quick-clamp drill chuck: metal quick-clamping drill chuck with a clamping range of 1–13 mm.

 Simple, rapid and tool-free clamping for maximum convenience. Automatically self-tightening clamping jaws for precisely axial drilling tool concentricity.
- L-BOXX system: Keep things stowed clearly, tidily and safely. Thanks to the tray for small parts, there is room for all accessories and the L-BOXXs can also be joined together and stacked with ease.
- together and stacked with ease.

 * Also available with accessories.
- ** Outstanding performance with AMPShare ProCORE 18 V 8.0 Ah / 12.0 Ah

KBU 35 Q







 $Small\ and\ powerful\ single-speed\ universal\ magnetic\ core\ drill\ with\ clockwise/anti-clockwise\ operation\ and\ maximum\ functionality\ for\ flexible\ working\ on\ the\ construction\ site.$

Input	W	1 100	1 100
Output	W	550	550
Speed, full load	rpm	130 - 520	130 - 520
Carbide core drill bit max. Ø	mm	35	35
HSS core drill max. Ø	mm	35	35
Core drill, drilling depth max.	mm	50	50
Twist drill max. Ø	mm	16	16
Tapping		M 14	M 14
Countersinking max. Ø	mm	31	31
Reaming max. Ø	mm	16	16
Core drill holder		QuickIN	3/4" Weldon
Changing the core bit		tool-free	tool-free
Stroke	mm	135	135
Total stroke range	mm	260	260
Magnetic holding power	N	10,000	10,000
Magnetic foot dimensions	mm	175 x 80	175 x 80
Cable with plug	m	4	4
Weight according to EPTA	kg	10,7	10,7

FEIN BENEFITS

- + Extremely low-wear tool design with swivel-mounted motor cable protection hose for tough use in industry and manual
- trades. Perfect power-to-weight ratio thanks to compact, weight-optimised design and FEIN 1100 W high-power motor with tacho electronics for high speed stability for reliable and economical working.
- + With clockwise/anti-clockwise operation, electronic speed setting and a 260 mm stroke range, this is a universal tool for core drilling, twist drilling, tapping, countersinking and reaming.
- Small and lightweight.
 Simple operating concept avoids mix-ups and can be clearly seen by the user.
 Convenient magnetic holding force display.
- High magnetic holding force.
- Tilt sensor.

- Additional magnetic switch in the drill jig.
 Integrated coolant tank.
 Feed handwheel can be moved from one side to the other.
- Speed saving "memory function".
- + Personal safety switch.

SUPPLIED

 $1\, coolant\, tank, 1\, lashing\, strap, 1\, swarf\, hook, 1\, centering\, pin, 1\, contact\, guard, 1\, case$

Part number	7 270 53 61 00 0	7 270 54 61 00 0
EAN	4014586886039	4014586886763

KBU 35 QW FABRICATOR M12 TAPPING-SET 3/4" WELDON



SUPPLIED

1 magnetic core drill, 1 coolant tank, 1 lashing strap, 1 swarf hook, 1 centring pin 100 mm, 1 contact guard, 1 plastic carrying case, 2 x 100 mm centring pin, 1 x size 2 tapping quick-change chuck, Tapping collet with safety clutch (1 each of M8 / M10 [DIN 371], M12 [DIN 374/376]), HSS machine taps for through holes, 1 each of M8 / M10 [DIN 371B], M12 [DIN 376B], HSS machine taps for blind holes (1 each of M8 / M10 [DIN 371C], M12 [DIN 376C]), HSS twist drills, 35 mm cutting depth (1 each of diameter 6.8 / 8.5 / 10.2 mm). 1 x HSS 90° countersink bit, diameter 16.5 mm, 1 cutting paste, 1 L-BOXX 136 for accessories

For accessories, see page 51

KBU 35 QW - the extremely versatile core drill coupled with a large number of tapping accessories. Perfect for metal and machine construction.

Input	W	1 100
Output	W	550
Speed, full load	rpm	130 - 520
Carbide core drill bit max. Ø	mm	35
HSS core drill max. Ø	mm	35
Core drill, drilling depth max.	mm	50
Twist drill max. Ø	mm	16
Tapping		M 14
Countersinking max. Ø	mm	31
Reaming max. Ø	mm	16
Core drill holder		3/4" Weldon
Changing the core bit		tool-free
Stroke	mm	135
Magnetic holding power	N	10,000
Magnetic foot dimensions	mm	175 x 80
Cable with plug	m	4
Weight according to EPTA	kg	10,6

Part number	7 270 54 64 00 0
EAN	4014586897325

FEIN BENEFITS

- + Extremely low-wear tool design with swivel-mounted motor cable protection hose for tough use in industry and manual trades.
- Perfect power-to-weight ratio thanks to compact, weight-optimised design and FEIN 1 100 W highpower motor with tacho electronics for high speed stability for reliable and economical working.
- With clockwise/anti-clockwise operation, electronic speed setting and a 260 mm stroke range, this is a universal tool for core drilling, twist drilling, tapping, countersinking and reaming.

countersinking and reaming. **Tapping quick change chuck:** Can be used with all core drills with reverse running and make your tapping even more precise and more efficient.

Tapping inserts and tool tapping drills: All from one source, in one set for M8, M10, M12 tapped bores in through holes and blind holes.

L-BOXX system: Keep things stowed clearly, tidily and safely. Thanks to the tray for small parts, there is room for all accessories and the L-BOXXs can also be joined together and stacked with ease.

KBU 35 QW STRUCTURAL STEEL-SET 3/4" WELDON



SUPPLIED

1 magnetic core drill, 1 coolant tank, 1 lashing strap, 1 swarf hook, 1 centring pin 100 mm, 1 contact guard, 1 plastic carrying case, HSS NOVA 50 core drill bits, 50 mm cutting depth (1 each of diameter 12 / 14 / 16 / 18 / 20 / 22 mm), HM ULTRA 50 core drill bits, 50 mm cutting depth (1 each of diameter 12 / 14 / 16 / 18 / 20 / 22 mm), 2 x 100 mm centring pin, 1 cutting paste, 1 L-BOXX 136 for accessories

For accessories, see page 51

KBU 35 QW - the extremely versatile core drill coupled with a large number of HM and HSS core drilling accessories. Perfect for steel and bridge construction.

Input	W	1 100
Output	W	550
Speed, full load	rpm	130 - 520
Carbide core drill bit max. Ø	mm	35
HSS core drill max. Ø	mm	35
Core drill, drilling depth max.	mm	50
Twist drill max. Ø	mm	16
Tapping		M 14
Countersinking max. Ø	mm	31
Reaming max. Ø	mm	16
Core drill holder		3/4" Weldon
Changing the core bit		tool-free
Stroke	mm	135
Magnetic holding power	N	10,000
Magnetic foot dimensions	mm	175 x 80
Cable with plug	m	4
Weight according to EPTA	kg	10,6

Part number	7 270 54 63 00 0
EAN	4014586897295

FEIN BENEFITS

- + Extremely low-wear tool design with swivel-mounted motor cable protection hose for tough use in industry and manual trades.
- Perfect power-to-weight ratio thanks to compact, weight-optimised design and FEIN 1 100 W highpower motor with tacho electronics for high speed stability for reliable and economical working.
- With clockwise/anti-clockwise operation, electronic speed setting and a 260 mm stroke range, this is a universal tool for core drilling, twist drilling, tapping, countersinking and reaming.

HSS NOVA 50 core drill bit: Extremely resistant to shock and impact, perfectly designed for tough use in steel construction and installation work. Thanks to its tough cutting edges and outstanding HSS steel with a hardness of 64 HRC, the core drill bit also delivers an impressively long service life.

HM ULTRA 50 core drill bit: Thanks to its high-quality carbide cutting teeth with a hardness of 1450 HV, the core drill bit wins customers over with it outstanding cutting performance and very long service life in all metals.

L-BOXX system: Keep things stowed clearly, tidily and safely. Thanks to the tray for small parts, there is room for all accessories and the L-BOXXs can also be joined together and stacked with ease.

KBU 35 PQ







Small and powerful single-speed universal magnetic core drill with clockwise/anti-clockwise operation, permanent magnet and maximum functionality for very safe and flexible working on the construction site.

Input	W	1 010	1 010
Output	W	550	550
Speed, full load	rpm	130-520	130-520
Carbide core drill bit max. Ø	mm	35	35
HSS core drill max. Ø	mm	35	35
Core drill, drilling depth max.	mm	50	50
Twist drill max. Ø	mm	16	16
Tapping		M 14	M 14
Countersinking max. Ø	mm	31	31
Reaming max. Ø	mm	16	16
Core drill holder		QuickIN	3/4" Weldon
Changing the core bit		tool-free	tool-free
Stroke	mm	135	135
Total stroke range	mm	260	260
Magnetic holding power	Ν	9,000	9,000
Magnetic foot dimensions	mm	195 x 70	195 x 70
Cable with plug	m	4	4
Weight according to EPTA	kg	12,5	12,5

FEIN BENEFITS

- + Permanent magnet for very safe working at height, swivel-mounted motor cable protective hose and good quality of
- workmanship for tough use. Compact and lightweight tool with high torque for continuously good work progress thanks to FEIN high-power motor with tacho electronics.
- Tool with extra large stroke range for all drilling work, such as core, twist and tap drilling, countersinking and reaming.
- Extra narrow permanent magnet with magnetic bias.
- Tilt sensor.
 Simple operating concept avoids mix-ups and can be clearly seen by the user.
 Convenient magnetic holding force display.
- Reversible.
- Integrated coolant tank.
- Speed saving "memory function".
- Feed handwheel can be moved from one side to the other.
- + Personal safety switch.

SUPPLIED $1\ coolant\ tank,\ 1\ lashing\ strap,\ 1\ swarf\ hook,\ 1\ centring\ pin,\ diameter\ of\ 6.35\ x\ 100\ mm,\ 1\ contact\ guard,\ 1\ case$

Part number	7 270 71 61 00 0	7 270 72 61 00 0
EAN	4014586890524	4014586890548

KBU 35 MQ

KBU 35 MQW





 $1\, coolant\, tank, 1\, lashing\, strap, 1\, swarf\, hook, 1\, centering\, pin,$

1 contact guard, 1 case

Small and powerful single-speed universal magnetic core drill with clockwise/anti-clockwise operation, MT2 tool mounting and maximum functionality for flexible working on the construction site.

Input	W	1 100	1100
Output	W	550	550
Speed, full load	rpm	130 - 520	130 - 520
Tool Holder		MT 2	MT 2
Carbide core drill bit max. Ø	mm	35	35
HSS core drill max. Ø	mm	35	35
Core drill, drilling depth max.	mm	50(75)*	50(75)*
Twist drill max. Ø	mm	18	18
Tapping		M 14	M 14
Countersinking max. Ø	mm	31	31
Reaming max. Ø	mm	18	18
Core drill holder		QuickIN	3/4" Weldon
Changing the core bit		tool-free	tool-free
Stroke	mm	135	135
Total stroke range	mm	260	260
Magnetic holding power	N	10,000	10,000
Magnetic foot dimensions	mm	175 x 80	175 x 80
Cable with plug	m	4	4
Weight according to EPTA	kg	10,7	10,7
FEIN BENEFITS		+ Extremely low-wear tool design with swivel-mounted mot	tor cable protection hose for tough use in industry and manual

SUPPLIED

EAN

- emely low-wear tool design with swivel-mounted motor cable protection hose for tough use in industry and manual trades.
- Perfect power-to-weight ratio thanks to compact, weight-optimised design and FEIN 1100 W high-power motor with tacho electronics for high speed stability for reliable and economical working.
- With clockwise/anti-clockwise operation, electronic speed setting and a 260 mm stroke range, this is a universal tool for core drilling, twist drilling, tapping, countersinking and reaming.
- Small with MT2 tool mounting.
 Simple operating concept avoids mix-ups and can be clearly seen by the user.
 Convenient magnetic holding force display.
- High magnetic holding force.
- Tilt sensor.
- $\label{eq:Additional magnetic switch in the drill jig.} Additional magnetic switch in the drill jig.$
- Integrated coolant tank.
 Feed handwheel can be moved from one side to the other.

1 coolant tank, 1 lashing strap, 1 swarf hook, 1 centering pin, 1 contact guard, 1 drift key, 1 case

- Speed saving "memory function".
- Personal safety switch.
- Also available with accessories.

Part number	7 270 55 61 00 0	7 270 56 61 00 0

4014586886053

For accessories, see page 51

4014586886770

KBU 35-2 Q







Small and powerful 2-speed universal magnetic core drill with clockwise/anti-clockwise operation and high speed for efficient twist drilling on the construction site.

Input	W	1 100	1 100
Output	W	550	550
Load speed in speed 1	rpm	130 - 520	130 - 520
Load speed in speed 2	rpm	400 - 1,600	400 - 1,600
Carbide core drill bit max. Ø	mm	35	35
HSS core drill max. Ø	mm	35	35
Core drill, drilling depth max.	mm	50	50
Twist drill max. Ø	mm	16	16
Tapping		M 14	M 14
Countersinking max. Ø	mm	31	31
Reaming max. Ø	mm	16	16
Core drill holder		QuickIN	3/4" Weldon
Changing the core bit		tool-free	tool-free
Stroke	mm	135	135
Total stroke range	mm	260	260
Magnetic holding power	N	9,500	9,500
Magnetic foot dimensions	mm	186 x 70	186 x 70
Cable with plug	m	4	4
Weight according to EPTA	kg	11,10	11,10

FEIN BENEFITS

- + Extremely low-wear tool design with swivel-mounted motor cable protection hose for tough use in industry and manual trades.
- + Extremely resilient construction thanks to sturdy machine design with swivel-mounted motor cable protection hose. Designed for tough use in industry and manual trades.
- + Perfect power-to-weight ratio thanks to compact, weight-optimised design and FEIN 1 100 W high-power motor with
- tacho electronics for high speed stability for reliable and economical working.
 With clockwise/anti-clockwise operation, electronic speed setting and a 260 mm stroke range, this is a universal tool for core drilling, twist drilling, tapping, countersinking and reaming.
 Small with mechanical 2-speed gearbox for twist drilling.
- Simple operating concept avoids mix-ups and can be clearly seen by the user.
- Convenient magnetic holding force display.
- High magnetic holding force thanks to 2-coil magnet, just 70 mm wide.
- Tilt sensor.
 Additional magnetic switch in the drill jig.
- Integrated coolant tank.
- Feed handwheel can be moved from one side to the other.
- Speed saving "memory function". Personal safety switch.

SUPPLIED

1 coolant tank, 1 lashing strap, 1 swarf hook, 1 centering pin, 1 contact guard, 1 case

Part number	7 270 57 61 00 0	7 270 58 61 00 0
EAN	4014586886077	4014586886787

KBM 50 Q



SUPPLIED

1 coolant tank, 1 lashing strap, 1 swarf hook, 1 centering pin, 1 contact guard, 1 case

For accessories, see page 51

Lightweight and powerful 2-speed universal magnetic core drill with clockwise/anti-clockwise operation and maximum functionality for flexible working in the workshop and on the construction site.

Input	W	1 200
Output	W	640
Load speed in speed 1	rpm	130 - 260
Load speed in speed 2	rpm	260 - 520
Carbide core drill bit max. Ø	mm	50
HSS core drill max. Ø	mm	40
Core drill, drilling depth max.	mm	50
Twist drill max. Ø	mm	16
Tapping		M 16
Countersinking max. Ø	mm	31
Reaming max. Ø	mm	16
Core drill holder		QuickIN
Changing the core bit		tool-free
Stroke	mm	145
Total stroke range	mm	315
Magnetic holding power	N	12,500
Magnetic foot dimensions	mm	195 x 90
Cable with plug	m	4
Weight according to EPTA	kg	14,00

Part number	7 270 41 61 00 0
EAN	4014586872834

- + Extremely low-wear tool design with swivel-mounted motor cable protection hose for tough use in industry and manual trades.
- Perfect power-to-weight ratio thanks to compact, weight-optimised design and FEIN 1,200 W high-power motor with tacho electronics for high speed stability for reliable and economical working.
- + With clockwise/anti-clockwise operation, electronic speed setting and a 315 mm stroke range, this is a universal tool for core drilling, twist drilling, tapping,
- a universal cortor core drating, twist drating, apping, countersinking and reaming.
 + Simple operating concept avoids mix-ups and can be clearly seen by the user.
 + Convenient magnetic holding force display.
 + High magnetic holding force.

- Integrated coolant tank.
- + Feed handwheel can be moved from one side to the other.
- + Speed saving "memory function". + Personal safety switch.

KBM 50 U







Lightweight and powerful 2-speed universal magnetic core drill with clockwise/anti-clockwise operation, MT3 tool mounting and maximum functionality for flexible working in the workshop and on the construction site.

FEIN BENEFITS + Extremely low-wear tool design with swivel-mounted motor cable protection hose for tough use in industry and m trades.			·
Weight according to EPTA	kg	14,00	14,00
Cable with plug	m	4	4
Magnetic foot dimensions	mm	195 x 90	195 x 90
Magnetic holding power	N	12,500	12,500
Total stroke range	mm	315	315
Stroke	mm	145	145
Changing the core bit		tool-free	tool-free
Core drill holder		QuickIN	3/4" Weldon
Reaming max. Ø	mm	23	23
Countersinking max. Ø	mm	50	50
Tapping		M 16	M 16
Twist drill max. Ø	mm	23	23
Core drill, drilling depth max.	mm	50(75)*	50(75)*
HSS core drill max. Ø	mm	40	40
Carbide core drill bit max. Ø	mm	50	50
Tool Holder		MK 3	MK 3
Load speed in speed 2	rpm	260 - 520	260 - 520
Load speed in speed 1	rpm	130 - 260	130 - 260
Output	W	610	610
Input	W	1 200	1 200

- tacho electronics for high speed stability for reliable and economical working.

 + With clockwise/anti-clockwise operation, electronic speed setting and a 315 mm stroke range, this is a universal tool for core drilling, twist drilling, tapping, countersinking and reaming.
- + MT3 tool mounting.
 + Simple operating concept avoids mix-ups and can be clearly seen by the user.
 + Convenient magnetic holding force display.
- High magnetic holding force.
- Integrated coolant tank.
- Feed handwheel can be moved from one side to the other.

 Speed saving "memory function".

 Personal safety switch.

 Also available with accessories.

SUPPLIED 1 coolant tank, 1 lashing strap, 1 swarf hook, 1 centering pin, 1 contact guard, 1 drift key, 1 case	SUPPLIED	1 coolant tank, 1 lashing strap, 1 swarf hook, 1 ce	entering pin, 1 contact guard, 1 drift key, 1 case
--	----------	---	--

Part number	7 270 40 61 00 0	7 273 25 61 00 0
EAN	4014586872995	4014586897608

KBM 65 U

KBM 65 UQW





Powerful and very high-performance 2-speed universal magnetic core drill with clockwise/anti-clockwise operation, MT3 tool mounting, fine adjustment and maximum functionality for flexible working in the workshop.

Input	W	1 300	1 300
Output	W	730	730
Load speed in speed 1	rpm	120 - 240	120 - 240
Load speed in speed 2	rpm	260 - 520	260 - 520
Tool Holder		MK 3	MK 3
Carbide core drill bit max. Ø	mm	65	65
HSS core drill max. Ø	mm	45	45
Core drill, drilling depth max.	mm	50(75)*	50(75)*
Twist drill max. Ø	mm	25	25
Tapping		M 20	M 20
Countersinking max. Ø	mm	50	50
Reaming max. Ø	mm	25	25
Core drill holder		QuickIN	3/4" Weldon
Changing the core bit		tool-free	tool-free
Stroke	mm	145	145
Total stroke range	mm	315	315
Adjustment range for drill jigs	mm	6	6
Swivel range for drill jigs		7°	7°
Magnetic holding power	N	14,000	14,000
Magnetic foot dimensions	mm	205 x 95	205 x 95
Cable with plug	m	4	4
Weight according to EPTA	kg	15,70	15,70
EFIN RENFEITS		+ Extremely low-wear tool design with swivel-mounted mo	stor cable protection hose for tough use in industry and manual

FEIN BENEFITS

- + Extremely low-wear tool design with swivel-mounted motor cable protection hose for tough use in industry and manual
- trades.

 Perfect power-to-weight ratio thanks to compact, weight-optimised design and FEIN 1,300 W high-power motor with tacho electronics for high speed stability for reliable and economical working.

 With clockwise/anti-clockwise operation, electronic speed setting and a 315 mm stroke range, this is a universal tool for
- core drilling, twist drilling, tapping, countersinking and reaming.
- Fine adjustment of the drill spindle for convenient tool alignment.
- MT3 tool mounting.
 Simple operating concept avoids mix-ups and can be clearly seen by the user.
- Convenient magnetic holding force display.
- High magnetic holding force.
- Integrated coolant tank.
- Feed handwheel can be moved from one side to the other. Speed saving "memory function". Personal safety switch.

- Also available with accessories.

SUPPLIED

 $1\, coolant\, tank,\, 1\, lashing\, strap,\, 1\, swarf\, hook,\, 1\, centering\, pin,\, 1\, contact\, guard,\, 1\, drift\, key,\, 1\, case$

Part number	7 270 43 61 00 0	7 273 26 61 00 0
EAN	4014586872902	4014586897622

KBU 110-4 M



SUPPLIED

1 coolant tank, 1 safety strap with ratchet, 1 swarf hook, 2 centring pins, diameter of 6.35 x 125 mm and diameter of 7.98 x 184 mm, 1 contact guard, 1 drift key, 2 x 5 and 6 mm hexagon socket wrench, 1 additional handle, 1 case

For accessories, see page 51

High-performance and powerful 4-speed universal magnetic core drill with forward/reverse running, MT4 tool mounting and maximum functionality for the toughest drilling jobs in the workshop.

Input	W	1700
Output	W	850
Load speed in speed 1	rpm	60 / 120
Load speed in speed 2	rpm	90 / 170
Load speed in speed 3	rpm	150 / 300
Load speed in speed 4	rpm	230 / 430
Idling speed in speed 1	rpm	100 / 190
Idling speed in speed 2	rpm	160 / 290
Idling speed in speed 3	rpm	270 / 500
Idling speed in speed 4	rpm	420 / 750
Tool Holder		MK 4
Carbide core drill bit max. Ø	mm	110
HSS core drill max. Ø	mm	80
Core drill, drilling depth max.	mm	100
Twist drill max. Ø	mm	40
Tapping		M 36
Countersinking max. Ø	mm	60
Reaming max. Ø	mm	36
Core drill holder		Weldon 32
Stroke	mm	280
Total stroke range	mm	400
Magnetic holding power	N	23,000
Magnetic foot dimensions	mm	240 x 120
Cable with plug	m	4
Weight according to EPTA	kg	35

Part number	7 270 60 61 00 0
EAN	4014586889740

- + FEIN 1700 W high-power motor with high torque for heavy-duty drilling work.
- + For tough use thanks to outstanding quality of workmanship and swivel-mounted motor cable protective hose.
- Tool with extra large stroke range for all drilling work, such as core, twist and tap drilling, countersinking and
- Mechanical 4-speed gearbox.
- + High magnetic holding force.
- Torque support for high stability.
- Tilt sensor.
- Slipping clutch torque.
- Convenient magnetic holding force display.
- Speed reduction.
- Reversible.
- MT4 tool mounting.
- Integrated coolant tank.
 Personal safety switch.





KBM 50 AUTO	KBM 50 AUTO QW
Lightweight, powerful and ingenious 2-speed auto mag minimum physical strain for core drilling in the worksho	

PAGE		50	50
Core drilling in metal with a Ø up to 3	35 mm	++	++
Core drilling in metal with a Ø up to 5	50 mm	++	++
Twist drills with drill chuck (DIN 338)		+	+
Twist drills with MK fitting (DIN 345)		++	++
Tapping		++	++
Countersinking		++	++
Reaming		++	++
Fully-automatic drilling		++	++
Working overhead		+	+
Installation work		++	++
Workshop jobs		++	++
Electronic magnetic holding force		•	•
Magnetic holding force display		•	•
Automatic drill feed		•	•
Reversible rotation		•	•
Variable speed control		•	•
Memory function		•	•
Speed-controlled electronics (tacho)		•	•
Tilt sensor		•	•
Input	W	1 200	1 200
Output	W	610	610
Load speed in speed 1	rpm	130 - 260	130 - 260
Load speed in speed 2	rpm	260 - 520	260 - 520
Tool Holder		MK 3	МК 3
Carbide core drill bit max. Ø	mm	50	50
HSS core drill max. Ø	mm	40	40
Core drill, drilling depth max.	mm	50(75)*	50(75)*
Twist drill max. Ø	mm	18/23**	18/23**
Tapping		M 16**	M 16**
Countersinking max. Ø	mm	50**	50**
Reaming max. Ø	mm	23**	23**
Core drill holder		QuickIN	3/4" Weldon
Stroke	mm	145	145
Total stroke range	mm	315	315
Magnetic holding power	N	12,500	12,500
Magnetic foot dimensions	mm	195 x 90	195 x 90
Cable with plug	m	4	4
Weight according to EPTA	kg	16,20	16,20

⁺ suitability ++ optimal suitability

[•] included *Also available with accessories.

^{**} In manual tool mode only

1 AUTOMATIC

KBM 50 AUTO



KBM 50 AUTO QW



Lightweight, powerful and ingenious 2-speed auto magnetic core drill offering maximum efficiency and minimum physical strain for core drilling in the workshop and on the construction site.

		strain for core untiling in the workshop and off the construction	11 31.C.
Input	W	1 200	1 200
Output	W	610	610
Load speed in speed 1	rpm	130 - 260 min ⁻¹	130 - 260 min ⁻¹
Load speed in speed 2	rpm	260 - 520 min ⁻¹	260 - 520 min ⁻¹
Tool Holder		MK 3	MK 3
Carbide core drill bit max. Ø	mm	50	50
HSS core drill max. Ø	mm	40	40
Core drill, drilling depth max.	mm	50(75)*	50(75)*
Twist drill max. Ø	mm	18/23**	18/23**
Tapping		M 16**	M 16**
Countersinking max. Ø	mm	50**	50**
Reaming max. Ø	mm	23**	23**
Core drill holder		QuickIN	3/4" Weldon
Changing the core bit		tool-free	tool-free
Stroke	mm	145	145
Total stroke range	mm	315	315
Magnetic holding power	N	12,500	12,500
Magnetic foot dimensions	mm	195 x 90	195 x 90
Cable with plug	m	4	4
Weight according to EPTA	kg	16,20	16,20

FEIN BENEFITS

- + Extremely low-wear tool design with swivel-mounted motor cable protection hose for tough use in industry and manual
- trades.
 Saves time and money when producing a large number of holes thanks to the digitally controlled drill feed.
 With clockwise/anti-clockwise operation, electronic speed setting and a 315 mm stroke range, this is a universal tool for core drilling, twist drilling, tapping, countersinking and reaming.
- Thanks to reproducible and timed drilling times, working hours for commissioned and serial work can be planned.
- MT3 tool mounting. FEIN high-power motor with stable speed.
- Simple operating concept avoids mix-ups and can be clearly seen by the user.
- High magnetic holding force.
- Convenient magnetic holding force display.
- Integrated coolant tank.
- Tilt sensor.
 Speed saving "memory function".
- Personal safety switch.
- Also available with accessories.
- ** In manual tool mode only

SUPPLIED

 $1\, {\rm coolant\, tank}, 1\, {\rm lashing\, strap}, 1\, {\rm swarf\, hook}, 1\, {\rm centering\, pin}, 1\, {\rm drift\, key}, 1\, {\rm contact\, guard}, 1\, {\rm case}$

Part number	7 270 42 61 00 0	7 273 27 61 00 0
FAN	4014586874272	4014586897646

BEST OF CORE DRILLING CARBIDE ACCESSORY SET



BEST OF CORE BITS QUICKIN

Very long service life and outstanding cutting performance. Metric dimensions, cutting depth 35 mm.

Set version, consisting of 6 core bits with diameters of 12, 14, 16, 18, 20 and 22 mm (cutting depth 35 mm) and 2 centring pins (100 mm) in plastic case.

> Part number 6 31 27 086 04 0



BEST OF CORE BITS 3/4" WELDON

Very long service life and outstanding cutting performance. Metric dimensions, cutting depth 35 mm.

Set version, consisting of 6 core bits with diameters of 12, 14, 16, 18, 20 and 22 mm (cutting depth 35 mm) and 2 centring pins (100 mm) in plastic case.

> Part number 6 31 27 714 02 0



BEST OF CORE BITS 3/4" WELDON

Very long service life and outstanding cutting performance.

Metric dimensions, cutting depth 50 mm. Set version, consisting of 6 core bits with diameters of 12, 14, 16, 18, 20 and 22 mm (cutting depth 35 mm) and 2 centring pins (100 mm) in plastic case.

> Part number 6 31 27 276 02 0



ACCESSORY SET FOR BEST OF CORE DRILLING CARBIDE COATED 3/4" WELDON

TiAlSiN surface coating for unique cutting performance and maximum work progress with an extremely long service life. Metric dimensions, cutting depth 35 mm. Set model, consisting of 6 core drill bits with diameters of 2x 14 / 16 / 18 / 20 / 22 mm (cutting depth 35 mm) and 2 centring pins (100 mm) in plastic case.

> Part number 6 31 27 838 11 0

CARBIDE CORE DRILL



TCT ULTRA 35 CORE BIT WITH QUICKIN HOLDER

Very long service life and outstanding cutting performance. Metric dimensions, cutting depth 35 mm.

Cutting depth	Bore Ø	
mm	mm	Part number
35	12	6 31 27 086 01 9
35	13	6 31 27 087 01 3
35	14	6 31 27 088 01 1
35	15	6 31 27 089 01 5
35	15,5	6 31 27 238 01 1
35	16	6 31 27 090 01 7
35	17	6 31 27 091 01 6
35	17,5	6 31 27 239 01 5
35	18	6 31 27 092 01 9
35	19	6 31 27 093 01 3
35	19,5	6 31 27 240 01 7
35	20	6 31 27 094 01 1
35	21	6 31 27 095 01 5
35	22	6 31 27 096 01 8
35	23	6 31 27 097 01 2
35	24	6 31 27 098 01 0
35	25	6 31 27 099 01 4
35	26	6 31 27 100 01 5
35	26,5	6 31 27 241 01 6
35	27	6 31 27 101 01 4
35	28	6 31 27 102 01 7
35	29	6 31 27 103 01 1
35	30	6 31 27 104 01 9
35	31	6 31 27 105 01 3
35	32	6 31 27 106 01 6

Cutting depth mm	Bore Ø mm	Part number
35	33	6 31 27 107 01 0
35	34	6 31 27 108 01 8
35	35	6 31 27 109 01 2
35	36	6 31 27 110 01 4
35	37	6 31 27 111 01 3
35	38	6 31 27 112 01 6
35	39	6 31 27 113 01 0
35	40	6 31 27 114 01 8
35	41	6 31 27 115 01 2
35	42	6 31 27 116 01 5
35	43	6 31 27 117 01 9
35	44	6 31 27 118 01 7
35	45	6 31 27 119 01 1
35	46	6 31 27 120 01 3
35	47	6 31 27 121 01 2
35	48	6 31 27 122 01 5
35	49	6 31 27 123 01 9
35	50	6 31 27 124 01 7
35	51	6 31 27 125 01 1
35	52	6 31 27 126 01 4
35	53	6 31 27 127 01 8
35	54	6 31 27 128 01 6
35	55	6 31 27 129 01 0
35	56	6 31 27 130 01 2
35	57	6 31 27 131 01 1
35	58	6 31 27 132 01 4
35	59	6 31 27 133 01 8
35	60	6 31 27 134 01 6
35	61	6 31 27 135 01 0
35	62	6 31 27 136 01 3
35	63	6 31 27 137 01 7
35	64	6 31 27 138 01 5
35	65	6 31 27 139 01 9



TCT ULTRA 75 CORE BIT WITH QUICKIN HOLDER

Very long service life and outstanding cutting performance. Metric dimensions, cutting depth 75 mm.

Cutting depth	Bore Ø	
mm	mm	Part number
75	18	6 31 27 763 01 0
75	19	6 31 27 764 01 0
75	20	6 31 27 765 01 0
75	21	6 31 27 766 01 0
75	22	6 31 27 767 01 0
75	23	6 31 27 768 01 0
75	24	6 31 27 769 01 0
75	25	6 31 27 770 01 0
75	26	6 31 27 771 01 0
75	27	6 31 27 772 01 0
75	28	6 31 27 773 01 0
75	29	6 31 27 774 01 0
75	30	6 31 27 775 01 0
75	32	6 31 27 776 01 0
75	35	6 31 27 777 01 0
75	36	6 31 27 778 01 0
75	40	6 31 27 779 01 0
75	45	6 31 27 780 01 0
75	50	6 31 27 781 01 0
75	55	6 31 27 782 01 0
75	60	6 31 27 783 01 0
75	65	6 31 27 784 01 0



TCT ULTRA 35 CORE BIT WITH 3/4" WELDON HOLDER

Very long service life and outstanding cutting performance. Metric dimensions, cutting depth 35 mm.

Cutting depth mm	Bore Ø mm	Part number
35	12	6 31 27 714 01 0
35	13	6 31 27 715 01 0
35	14	6 31 27 716 01 0
35	15	6 31 27 717 01 0
35	16	6 31 27 718 01 0
35	17	
		6 31 27 719 01 0
35	18	6 31 27 720 01 0
35	19	6 31 27 721 01 0
35	20	6 31 27 722 01 0
35	21	6 31 27 723 01 0
35	22	6 31 27 724 01 0
35	23	6 31 27 725 01 0
35	24	6 31 27 726 01 0
35	25	6 31 27 727 01 0
35	26	6 31 27 728 01 0
35	27	6 31 27 729 01 0
35	28	6 31 27 730 01 0
35	29	6 31 27 731 01 0
35	30	6 31 27 732 01 0
35	31	6 31 27 733 01 0
35	32	6 31 27 734 01 0
35	33	6 31 27 735 01 0
35	34	6 31 27 736 01 0
35	35	6 31 27 737 01 0
35	36	6 31 27 738 01 0
35	37	6 31 27 739 01 0
35	38	6 31 27 740 01 0
35	39	6 31 27 741 01 0
35	40	
		6 31 27 742 01 0
35	41	6 31 27 743 01 0
35	42	6 31 27 744 01 0
35	43	6 31 27 745 01 0
35	44	6 31 27 746 01 0
35	45	6 31 27 747 01 0
35	46	6 31 27 748 01 0
35	47	6 31 27 749 01 0
35	48	6 31 27 750 01 0
35	49	6 31 27 751 01 0
35	50	6 31 27 752 01 0
35	51	6 31 27 753 01 0
35	52	6 31 27 754 01 0
35	53	6 31 27 755 01 0
35	54	6 31 27 756 01 0
35	55	6 31 27 757 01 0
35	56	6 31 27 758 01 0
35	57	6 31 27 759 01 0
35	58	6 31 27 760 01 0
35		
-	59	6 31 27 761 01 0
35	60	6 31 27 762 01 0



TCT ULTRA 50 CORE BIT WITH 3/4" WELDON HOLDER Very long service life and outstanding cutting performance. Metric dimensions, cutting depth 50 mm.

4 OU CHE		
Cutting depth	Bore Ø	
mm	mm	Part number
50	12	6 31 27 276 01 0
50	13	6 31 27 277 01 0
50	14	6 31 27 278 01 0
50	15	6 31 27 279 01 0
50	15,5	6 31 27 828 01 0
50	16	6 31 27 280 01 0
50	17	6 31 27 281 01 0
50	17,5	6 31 27 829 01 0
-		
50	18	6 31 27 282 01 0
50	19	6 31 27 283 01 0
50	19,5	6 31 27 830 01 0
50	20	6 31 27 284 01 0
50	21	6 31 27 285 01 0
50	22	6 31 27 286 01 0
50	23	6 31 27 287 01 0
50	24	6 31 27 288 01 0
50	25	6 31 27 289 01 0
50	26	6 31 27 290 01 0
50	26,5	6 31 27 831 01 0
50	27	6 31 27 291 01 0
50	28	6 31 27 292 01 0
50	29	6 31 27 293 01 0
50	30	6 31 27 294 01 0
50	31	6 31 27 295 01 0
50	32	6 31 27 296 01 0
50	33	6 31 27 297 01 0
50	34	6 31 27 298 01 0
50	35	6 31 27 299 01 0
50	36	6 31 27 300 01 0
		6 31 27 300 01 0
50	37	
50	38	6 31 27 302 01 0
50	39	6 31 27 303 01 0
50	40	6 31 27 304 01 0
50	41	6 31 27 305 01 0
50	42	6 31 27 306 01 0
50	43	6 31 27 307 01 0
50	44	6 31 27 308 01 0
50	45	6 31 27 309 01 0
50	46	6 31 27 310 01 0
50	47	6 31 27 311 01 0
50	48	6 31 27 312 01 0
50	49	6 31 27 313 01 0
50	50	6 31 27 314 01 0
50	51	6 31 27 315 01 0
50	52	6 31 27 316 01 0
50	53	6 31 27 317 01 0
50	54	6 31 27 318 01 0
50	55	6 31 27 319 01 0
50	56	6 31 27 320 01 0
50	57	6 31 27 321 01 0
50	58	6 31 27 322 01 0
50	59	6 31 27 323 01 0
50	60	6 31 27 324 01 0
50	61	6 31 27 325 01 0
50	62	6 31 27 326 01 0
50	63	6 31 27 327 01 0
50	64	6 31 27 328 01 0
50	65	6 31 27 329 01 0



TCT ULTRA 75 CORE BIT WITH 3/4" WELDON HOLDER

Very long service life and outstanding cutting performance. Metric dimensions, cutting depth 75 mm.

Cutting depth	Bore Ø	
mm	mm	Part number
75	18	6 31 27 785 01 0
75	19	6 31 27 786 01 0
75	20	6 31 27 787 01 0
75	21	6 31 27 788 01 0
75	22	6 31 27 789 01 0
75	23	6 31 27 790 01 0
75	24	6 31 27 791 01 0
75	25	6 31 27 792 01 0
75	26	6 31 27 793 01 0
75	27	6 31 27 794 01 0
75	28	6 31 27 795 01 0
75	29	6 31 27 796 01 0
75	30	6 31 27 797 01 0
75	32	6 31 27 798 01 0
75	35	6 31 27 799 01 0
75	36	6 31 27 800 01 0
75	40	6 31 27 801 01 0
75	45	6 31 27 802 01 0
75	50	6 31 27 803 01 0
75	55	6 31 27 804 01 0
75	60	6 31 27 805 01 0
75	65	6 31 27 806 01 0



TCT ULTRA 50 CORE BIT WITH FEIN THREAD M 18 X 6 P 1.5

Very long service life and outstanding cutting performance. Metric dimensions, cutting depth 50 mm.

Cutting depth	Bore Ø	
mm	mm	Part number
50	12	6 31 27 042 01 4
50	13	6 31 27 043 01 8
50	14	6 31 27 044 01 6
50	15	6 31 27 045 01 0
50	16	6 31 27 046 01 3
50	17	6 31 27 047 01 7
50	18	6 31 27 001 01 5
50	19	6 31 27 019 01 2
50	20	6 31 27 002 01 8
50	21	6 31 27 020 01 4
50	22	6 31 27 003 01 2
50	23	6 31 27 021 01 3
50	24	6 31 27 022 01 6
50	25	6 31 27 004 01 0
50	26	6 31 27 005 01 4
50	27	6 31 27 023 01 0
50	28	6 31 27 006 01 7
50	29	6 31 27 024 01 8
50	30	6 31 27 007 01 1
50	31	6 31 27 025 01 2
50	32	6 31 27 008 01 9
50	33	6 31 27 026 01 5
50	34	6 31 27 009 01 3
50	35	6 31 27 010 01 5
50	36	6 31 27 027 01 9
50	37	6 31 27 028 01 7
50	38	6 31 27 011 01 4
50	39	6 31 27 029 01 1
50	40	6 31 27 012 01 7
50	41	6 31 27 030 01 3
50	42	6 31 27 013 01 1
50	43	6 31 27 014 01 9
50	44	6 31 27 031 01 2
50	45	6 31 27 015 01 3

Cutting depth mm	Bore ∅ mm	Part number
50	46	6 31 27 032 01 5
50	47	6 31 27 033 01 9
50	48	6 31 27 016 01 6
50	49	6 31 27 034 01 7
50	50	6 31 27 017 01 0
50	51	6 31 27 035 01 1
50	52	6 31 27 018 01 8
50	53	6 31 27 036 01 4
50	54	6 31 27 037 01 8
50	55	6 31 27 038 01 6
50	56	6 31 27 039 01 0
50	57	6 31 27 040 01 2
50	58	6 31 27 041 01 1
50	59	6 31 27 049 01 9
50	60	6 31 27 050 01 1
50	61	6 31 27 051 01 0
50	62	6 31 27 052 01 3
50	63	6 31 27 053 01 7
50	64	6 31 27 054 01 5
50	65	6 31 27 055 01 9



HM ULTRA 50 CORE DRILL BIT WITH QUICKIN MAX/ **WELDON 32 FITTING**

Very long service life and outstanding cutting performance. Metric dimensions, cutting depth 50 mm.

Cutting depth	Bore Ø	5
mm	mm	Part number
50	50	6 31 27 330 01 0
50	51	6 31 27 331 01 0
50	52	6 31 27 332 01 0
50	53	6 31 27 333 01 0
50	54	6 31 27 334 01 0
50	55	6 31 27 335 01 0
50	56	6 31 27 336 01 0
50	57	6 31 27 337 01 0
50	58	6 31 27 338 01 0
50	59	6 31 27 339 01 0
50	60	6 31 27 340 01 0
50	61	6 31 27 341 01 0
50	62	6 31 27 342 01 0
50	63	6 31 27 343 01 0
50	64	6 31 27 344 01 0
50	65	6 31 27 345 01 0
50	66	6 31 27 346 01 0
50	67	6 31 27 347 01 0
50	68	6 31 27 348 01 0
50	69	6 31 27 349 01 0
50	70	6 31 27 350 01 0
50	71	6 31 27 351 01 0
50	72	6 31 27 352 01 0
50	73	6 31 27 353 01 0
50	74	6 31 27 354 01 0
50	75	6 31 27 355 01 0
50	76	6 31 27 456 01 0
50	77	6 31 27 457 01 0
50	78	6 31 27 458 01 0
50	79	6 31 27 459 01 0
50	80	6 31 27 460 01 0
50	85	6 31 27 807 01 0
50	90	6 31 27 808 01 0
50	95	6 31 27 809 01 0
50	100	6 31 27 810 01 0
50	105	6 31 27 822 01 0
50	110	6 31 27 823 01 0



HM ULTRA 100 CORE DRILL BIT WITH WELDON 32 FITTING

Very long service life and outstanding cutting performance. Metric dimensions, cutting depth 100 mm. Internal hole 8 mm.

Cutting depth mm	Bore Ø mm	Part number
100	50	6 31 27 811 01 0
100	55	6 31 27 812 01 0
100	60	6 31 27 813 01 0
100	65	6 31 27 814 01 0
100	70	6 31 27 815 01 0
100	74	6 31 27 826 01 0
100	75	6 31 27 816 01 0
100	80	6 31 27 817 01 0
100	82	6 31 27 827 01 0
100	85	6 31 27 818 01 0
100	90	6 31 27 819 01 0
100	95	6 31 27 820 01 0
100	100	6 31 27 821 01 0
100	105	6 31 27 824 01 0
100	110	6 31 27 825 01 0

BEST OF CORE BITS 3/4" WELDON

Industrial standard. Metric dimensions, cutting depth 25 mm. Set version, consisting of 6 core bits with diameters of 12, 14, 16, 18, 20 and 22 mm (cutting depth 25 mm) and 2 centring pins (80 mm) in plastic case.

Tarthamber
6 31 34 999 06 1



BEST OF CORE BITS 3/4" WELDON

Industrial standard. Metric dimensions, cutting depth 25 mm. Set version, consisting of 4 core bits, 2 x 14 mm diameter, 2 x 18 mm diameter, (cutting depth 25 mm) and 1 centring pin (80 mm) in plastic case.

	-	Part	t nui	nbe	er
6	31	34	999	06	2

Part number



BEST OF CORE BITS 3/4" WELDON

Industrial standard. Metric dimensions, cutting depth 50 mm. Set version, consisting of 6 core bits with diameters of 12, 14, 16, 18, 20 and 22 mm (cutting depth 50 mm) and 2 centring pins (100 mm) in plastic case.

> Part number 6 31 34 999 06 3



BEST OF CORE BITS 3/4" WELDON

Industrial standard. Metric dimensions, cutting depth 50 mm. Set version, consisting of 4 core bits, 2x 14 mm diameter, $2x\,18$ mm diameter, (cutting depth 50 mm) and 1 centring pin (100 mm) in plastic case.



Part number

6 31 34 999 06 4

CARBIDE CORE DRILL COATED



TCT ULTRA 35 CORE BIT WITH 3/4" WELDON HOLDER

TiAlSiN surface coating for unique cutting performance and maximum work progress with an extremely long service life. Metric dimensions, cutting depth 35 mm.

Cutting depth	Bore Ø	
mm	mm	Part number
35	14	6 31 27 838 00 3
35	16	6 31 27 838 00 4
35	17,5	6 31 27 838 00 5
35	18	6 31 27 838 00 6
35	20	6 31 27 838 00 7
35	21	6 31 27 838 00 8
35	22	6 31 27 838 00 9
35	24	6 31 27 838 01 1
35	25	6 31 27 838 01 2
35	26	6 31 27 838 01 3
35	26,5	6 31 27 838 01 4
35	28	6 31 27 838 01 5
35	30	6 31 27 838 01 6
35	32	6 31 27 838 01 7
35	33	6 31 27 838 01 8
35	34	6 31 27 838 01 9
35	35	6 31 27 838 02 0
35	36	6 31 27 838 02 1

HSS CORE DRILL



HSS NOVA 25 CORE BIT WITH QUICKIN HOLDER Industrial standard. Metric dimensions, cutting depth 25 mm.

Cutting depth	Bore Ø	
mm	mm	Part number
25	12	6 31 33 119 05 1
25	13	6 31 33 129 05 1
25	14	6 31 33 140 05 1
25	15	6 31 33 150 05 1
25	16	6 31 33 159 05 1
25	17	6 31 33 170 05 1
25	18	6 31 33 180 05 1
25	19	6 31 33 189 05 1
25	20	6 31 33 199 06 3
25	21	6 31 33 210 05 1
25	22	6 31 33 219 05 1
25	23	6 31 33 229 05 1
25	24	6 31 33 240 05 1
25	25	6 31 33 250 05 1
25	26	6 31 33 259 05 1
25	27	6 31 33 270 05 1
25	28	6 31 33 279 05 1
25	29	6 31 33 289 05 1
25	30	6 31 33 299 05 1
25	31	6 31 33 309 05 1

Para M

BEST OF CORE DRILLING HSS ACCESSORY SET



BEST OF CORE BITS QUICKIN

Industrial standard. Metric dimensions, cutting depth 50 mm. Set version, consisting of 6 core bits with diameters of 12, 14, 16, 18, 20 and 22 mm (cutting depth 50 mm) and 2 centring pins (100 mm) in plastic case.

Part number
6 31 33 999 01 0

Cutting depth mm	Bore Ø mm	Part number
25	32	6 31 33 319 05 1
25	33	6 31 33 329 05 1
25	34	6 31 33 339 05 1
25	35	6 31 33 350 05 1
25	36	6 31 33 359 05 1
25	37	6 31 33 369 05 1
25	38	6 31 33 379 05 1
25	39	6 31 33 389 05 1
25	40	6 31 33 399 05 1
25	41	6 31 33 409 05 1
25	42	6 31 33 420 05 1
25	43	6 31 33 429 05 1
25	44	6 31 33 439 05 1
25	45	6 31 33 449 05 1
25	46	6 31 33 459 05 1
25	47	6 31 33 469 05 1
25	48	6 31 33 479 05 1
25	49	6 31 33 489 05 1
25	50	6 31 33 499 05 1



HSS NOVA 50 CORE BIT WITH QUICKIN HOLDER Industrial standard. Metric dimensions, cutting depth 50 mm.

Cutting depth	Bore Ø	
mm	mm	Part number
50	12	6 31 33 119 05 2
50	13	6 31 33 129 05 2
50	14	6 31 33 140 05 2
50	15	6 31 33 150 05 2
50	16	6 31 33 159 05 2
50	17	6 31 33 170 05 2
50	18	6 31 33 180 05 2
50	19	6 31 33 189 05 2
50	20	6 31 33 199 05 2
50	21	6 31 33 210 05 2
50	22	6 31 33 219 05 2
50	23	6 31 33 229 05 2
50	24	6 31 33 240 05 2
50	25	6 31 33 250 05 2
50	26	6 31 33 259 05 2
50	27	6 31 33 270 05 2
50	28	6 31 33 279 05 2
50	29	6 31 33 289 05 2
50	30	6 31 33 299 05 2
50	31	6 31 33 309 05 2
50	32	6 31 33 319 05 2
50	33	6 31 33 329 05 2
50	34	6 31 33 339 05 2
50	35	6 31 33 350 05 2
50	36	6 31 33 359 05 2
50	37	6 31 33 369 05 2
50	38	6 31 33 379 05 2
50	39	6 31 33 389 05 2
50	40	6 31 33 399 05 2
50	41	6 31 33 409 05 2
50	42	6 31 33 420 05 2
50	43	6 31 33 429 05 2
50	44	6 31 33 439 05 2
50	45	6 31 33 449 05 2
50	46	6 31 33 459 05 2
50	47	6 31 33 469 05 2
50	48	6 31 33 479 05 2
50	49	6 31 33 489 05 2
50	50	6 31 33 499 05 2



HSS NOVA 25 CORE BIT WITH 3/4" WELDON HOLDER

Industrial standard. Metric dimensions, cutting depth 25 mm.

Cutting depth mm	Bore Ø mm	Part number
	12	
25 25	13	6 31 34 120 05 1 6 31 34 130 05 1
25	14	6 31 34 140 05 1
25	15	6 31 34 150 05 1
25	16	6 31 34 160 05 1
25	17	6 31 34 170 05 1
25	18	6 31 34 180 05 1
25	19	6 31 34 190 05 1
25	20	6 31 34 200 05 1
25	21	6 31 34 210 05 1
25	22	6 31 34 220 05 1
25	23	6 31 34 230 05 1
25	24	6 31 34 240 05 1
25	25	6 31 34 250 05 1
25	26	6 31 34 260 05 1
25	27	6 31 34 270 05 1
25	28	6 31 34 280 05 1
25	29	6 31 34 290 05 1
25	30	6 31 34 300 05 1
25	31	6 31 34 310 05 1
25	32	6 31 34 320 05 1
25	33	6 31 34 330 05 1
25	34	6 31 34 340 05 1
25	35	6 31 34 350 05 1
25	36	6 31 34 360 05 1
25	37	6 31 34 370 05 1
25	38	6 31 34 380 05 1
25	39	6 31 34 390 05 1
25	40	6 31 34 400 05 1
25	41	6 31 34 410 05 1
25	42	6 31 34 420 05 1
25	43	6 31 34 430 05 1
25	44	6 31 34 440 05 1
25	45	6 31 34 450 05 1
25	46	6 31 34 460 05 1
25	47	6 31 34 470 05 1
25	48	6 31 34 480 05 1
25	49	6 31 34 490 05 1
25	50	6 31 34 500 05 1
25	51	6 31 34 510 05 1
25	52	6 31 34 520 05 1
25	53	6 31 34 530 05 1
25	54	6 31 34 540 05 1
25	55	6 31 34 550 05 1
25	56	6 31 34 560 05 1
25	57	6 31 34 570 05 1
25	58	6 31 34 580 05 1
25	59	6 31 34 590 05 1
25	60	6 31 34 600 05 1



HSS NOVA 50 CORE BIT WITH 3/4" WELDON HOLDER

Industrial standard. Metric dimensions, cutting depth 50 mm.

Cutting depth	Bore Ø	
mm	mm	Part number
50	12	6 31 34 120 05 2
50	13	6 31 34 130 05 2
50	14	6 31 34 140 05 2
50	15	6 31 34 150 05 2
50	16	6 31 34 160 05 2
50	17	6 31 34 170 05 2
50	18	6 31 34 180 05 2
50	19	6 31 34 190 05 2
50	20	6 31 34 200 05 2
50	21	6 31 34 210 05 2
50	22	6 31 34 220 05 2
50	23	6 31 34 230 05 2
50	24	6 31 34 240 05 2
50	25	6 31 34 250 05 2
50	26	6 31 34 260 05 2
50	27	6 31 34 270 05 2
50	28	6 31 34 280 05 2
50	29	6 31 34 290 05 2
50	30	6 31 34 300 05 2
50	31	6 31 34 310 05 2
50	32	6 31 34 320 05 2
50	33	6 31 34 330 05 2
50	34	6 31 34 340 05 2
50	35	6 31 34 350 05 2
50	36	6 31 34 360 05 2
50	37	6 31 34 370 05 2
50	38	6 31 34 380 05 2
50	39	6 31 34 390 05 2
50	40	6 31 34 400 05 2
50	41	6 31 34 410 05 2
50	42	6 31 34 420 05 2
50	43	6 31 34 430 05 2
50	44	6 31 34 440 05 2
50	45	6 31 34 450 05 2
50	46	6 31 34 460 05 2
50	47	6 31 34 470 05 2
50	48	6 31 34 480 05 2
50	49	6 31 34 490 05 2
50	50	6 31 34 500 05 2
50	51	6 31 34 510 05 2
50	52	6 31 34 520 05 2
50	53	6 31 34 530 05 2
50	54	6 31 34 540 05 2
50	55	6 31 34 550 05 2
		6 31 34 560 05 2
50	56	
50	57	6 31 34 570 05 2
50	58	6 31 34 580 05 2
50	59	6 31 34 590 05 2
50	60	6 31 34 600 05 2



HSS NOVA 75 CORE BIT WITH 3/4" WELDON HOLDER Industrial standard. Metric dimensions, cutting depth 75 mm.

Cutting depth mm	Bore Ø mm	Part number
75	19	6 31 34 190 05 3
75	20	6 31 34 200 05 3
75	21	6 31 34 210 05 3
75	22	6 31 34 220 05 3
75	23	6 31 34 230 05 3
75	24	6 31 34 240 05 3

Cutting depth	Bore Ø	
mm	mm	Part number
75	25	6 31 34 250 05 3
75	26	6 31 34 260 05 3
75	27	6 31 34 270 05 3
75	28	6 31 34 280 05 3
75	29	6 31 34 290 05 3
75	30	6 31 34 300 05 3
75	32	6 31 34 320 05 3
75	35	6 31 34 350 05 3
75	36	6 31 34 360 05 3
75	40	6 31 34 400 05 3
75	45	6 31 34 450 05 3
75	50	6 31 34 500 05 3
75	60	6 31 34 600 05 3



HSS NOVA 100 CORE DRILL BIT WITH 3/4" WELDON FITTING

Long service life. Metric dimensions, cutting depth 100 mm. Not suitable for overlapping drilling.

Cutting depth	Bore Ø	D
mm	mm	Part number
100	21	6 31 34 210 05 4
100	22	6 31 34 220 05 4
100	23	6 31 34 230 05 4
100	24	6 31 34 240 05 4
100	25	6 31 34 250 05 4
100	26	6 31 34 260 05 4
100	27	6 31 34 270 05 4
100	28	6 31 34 280 05 4
100	29	6 31 34 290 05 4
100	30	6 31 34 300 05 4
100	32	6 31 34 320 05 4
100	35	6 31 34 350 05 4
100	36	6 31 34 360 05 4
100	40	6 31 34 400 05 4
100	45	6 31 34 450 05 4
100	50	6 31 34 500 05 4

HSS CORE DRILL SPECIAL



HSS SPECIAL 25 CORE BIT WITH 3/4" WELDON FITTING

Long service life. For drilling multi-layered materials in a single process, cutting depth 25 mm.

Cutting depth	Bore Ø	
mm	mm	Part number
25	12	6 31 34 120 30 1
25	13	6 31 34 130 30 1
25	14	6 31 34 140 30 1
25	14,3	6 31 34 143 30 1
25	15	6 31 34 150 30 1
25	16	6 31 34 160 30 1
25	17	6 31 34 170 30 1
25	18	6 31 34 180 30 1
25	20	6 31 34 200 30 1
25	22	6 31 34 220 30 1
25	24	6 31 34 240 30 1
25	26	6 31 34 260 30 1
25	28	6 31 34 280 30 1
25	30	6 31 34 300 30 1
25	32	6 31 34 320 30 1
25	35	6 31 34 350 30 1



HSS SPECIAL 50 CORE DRILL BIT WITH 3/4" WELDON

Long service life. For drilling multi-layered materials in a single operation. Metric dimensions, cutting depth 50 mm.

Cutting depth	Bore Ø	
mm	mm	Part number
50	12	6 31 34 120 30 2
50	13	6 31 34 130 30 2
50	14	6 31 34 140 30 2
50	15	6 31 34 150 30 2
50	16	6 31 34 160 30 2
50	17	6 31 34 170 30 2
50	18	6 31 34 180 30 2
50	20	6 31 34 200 30 2
50	22	6 31 34 220 30 2
50	24	6 31 34 240 30 2
50	26	6 31 34 260 30 2
50	28	6 31 34 280 30 2
50	30	6 31 34 300 30 2
50	32	6 31 34 320 30 2
50	35	6 31 34 350 30 2
50	36	6 31 34 360 30 2
50	40	6 31 34 400 30 2
50	45	6 31 34 450 30 2
50	50	6 31 34 500 30 2

HSS CORE DRILL COATED



HSS DURA 25 CORE BIT WITH QUICKIN HOLDER

TiN surface coating for outstanding service lives and the best glide properties. Metric dimensions, cutting depth 25 mm.

Cutting depth	Bore Ø	
mm	mm	Part number
25	12	6 31 33 120 06 7
25	13	6 31 33 130 06 7
25	14	6 31 33 140 06 7
25	15	6 31 33 150 06 7
25	16	6 31 33 160 06 7
25	17	6 31 33 170 06 7
25	18	6 31 33 180 06 7
25	19	6 31 33 190 06 7
25	20	6 31 33 200 06 7
25	21	6 31 33 210 06 7
25	22	6 31 33 220 06 7
25	23	6 31 33 230 06 7
25	24	6 31 33 240 06 7
25	25	6 31 33 250 06 7
25	26	6 31 33 260 06 7
25	27	6 31 33 270 06 7
25	28	6 31 33 280 06 7
25	29	6 31 33 290 06 7
25	30	6 31 33 300 06 7
25	31	6 31 33 310 06 7
25	32	6 31 33 320 06 7
25	34	6 31 33 340 06 7
25	37	6 31 33 370 06 7
25	43	6 31 33 430 06 7
25	44	6 31 33 440 06 7
25	45	6 31 33 450 06 7
25	46	6 31 33 460 06 7
25	47	6 31 33 470 06 7
25	48	6 31 33 480 06 7
25	49	6 31 33 490 06 7
25	50	6 31 33 500 06 7



HSS DURA 50 CORE BIT WITH QUICKIN HOLDER

TiN surface coating for outstanding service lives and the best glide properties.

Metric dimensions, cutting depth 50 mm.

Cutting depth mm	Bore Ø mm	Part number
50	12	6 31 33 120 06 8
50	13	6 31 33 130 06 8
50	14	6 31 33 140 06 8
50	15	6 31 33 150 06 8
50	16	6 31 33 160 06 8
50	17	6 31 33 170 06 8
50	18	6 31 33 180 06 8
50	19	6 31 33 190 06 8
50	20	6 31 33 200 06 8
50	21	6 31 33 210 06 8
50	22	6 31 33 220 06 8
50	23	6 31 33 230 06 8
50	24	6 31 33 240 06 8
50	25	6 31 33 250 06 8
50	26	6 31 33 260 06 8
50	27	6 31 33 270 06 8
50	28	6 31 33 280 06 8
50	29	6 31 33 290 06 8
50	30	6 31 33 300 06 8
50	31	6 31 33 310 06 8
50	32	6 31 33 320 06 8
50	33	6 31 33 330 06 8
50	34	6 31 33 340 06 8
50	35	6 31 33 350 06 8
50	36	6 31 33 360 06 8
50	37	6 31 33 370 06 8
50	38	6 31 33 380 06 8
50	39	6 31 33 390 06 8
50	40	6 31 33 400 06 8
50	41	6 31 33 410 06 8
50	42	6 31 33 420 06 8
50	43	6 31 33 430 06 8
50	44	6 31 33 440 06 8
50	45	6 31 33 450 06 8
50	46	6 31 33 460 06 8
50	47	6 31 33 470 06 8
50	48	6 31 33 480 06 8
50	49	6 31 33 490 06 8
50	50	6 31 33 500 06 8



HSS DURA 25 CORE BIT WITH 3/4" WELDON HOLDER TiN surface coating for outstanding service lives and the best glide properties. Metric dimensions, cutting depth 25 mm.

Cutting depth	Bore Ø	
mm	mm	Part number
25	12	6 31 34 120 07 5
25	13	6 31 34 130 07 5
25	14	6 31 34 140 07 5
25	15	6 31 34 150 07 5
25	16	6 31 34 160 07 5
25	17	6 31 34 170 07 5
25	18	6 31 34 180 07 5
25	19	6 31 34 190 07 5
25	20	6 31 34 200 07 5
25	21	6 31 34 210 07 5
25	22	6 31 34 220 07 5
25	23	6 31 34 230 07 5
25	24	6 31 34 240 07 5
25	25	6 31 34 250 07 5
25	26	6 31 34 260 07 5
25	27	6 31 34 270 07 5
25	28	6 31 34 280 07 5

Cutting depth mm	Bore Ø mm	Part number
25	29	6 31 34 290 07 5
25	30	6 31 34 300 07 5
25	31	6 31 34 310 07 5
25	32	6 31 34 320 07 5
25	33	6 31 34 330 07 5
25	34	6 31 34 340 07 5
25	35	6 31 34 350 07 5
25	36	6 31 34 360 07 5
25	37	6 31 34 370 07 5
25	38	6 31 34 380 07 5
25	39	6 31 34 390 07 5
25	40	6 31 34 400 07 5
25	41	6 31 34 410 07 5
25	42	6 31 34 420 07 5
25	43	6 31 34 430 07 5
25	44	6 31 34 440 07 5
25	45	6 31 34 450 07 5
25	46	6 31 34 460 07 5
25	47	6 31 34 470 07 5
25	48	6 31 34 480 07 5
25	49	6 31 34 490 07 5
25	50	6 31 34 500 07 5
25	51	6 31 34 510 07 5
25	52	6 31 34 520 07 5
25	53	6 31 34 530 07 5
25	54	6 31 34 540 07 5
25	55	6 31 34 550 07 5
25	56	6 31 34 560 07 5
25	57	6 31 34 570 07 5
25	58	6 31 34 580 07 5
25	59	6 31 34 590 07 5
25	60	6 31 34 600 07 5



HSS DURA 50 CORE BIT WITH 3/4" WELDON HOLDER TIN surface coating for outstanding service lives and the best

glide properties.

Metric dimensions, cutting depth 50 mm.

Cutting depth	Bore Ø	
mm	mm	Part number
50	12	6 31 34 120 07 6
50	13	6 31 34 130 07 6
50	14	6 31 34 140 07 6
50	15	6 31 34 150 07 6
50	16	6 31 34 160 07 6
50	17	6 31 34 170 07 6
50	18	6 31 34 180 07 6
50	19	6 31 34 190 07 6
50	20	6 31 34 200 07 6
50	21	6 31 34 210 07 6
50	22	6 31 34 220 07 6
50	23	6 31 34 230 07 6
50	24	6 31 34 240 07 6
50	25	6 31 34 250 07 6
50	26	6 31 34 260 07 6
50	27	6 31 34 270 07 6
50	28	6 31 34 280 07 6
50	29	6 31 34 290 07 6
50	30	6 31 34 300 07 6
50	31	6 31 34 310 07 6
50	32	6 31 34 320 07 6
50	33	6 31 34 330 07 6
50	34	6 31 34 340 07 6
50	35	6 31 34 350 07 6
50	36	6 31 34 360 07 6
50	37	6 31 34 370 07 6
50	38	6 31 34 380 07 6

Cutting depth	Bore ∅	
mm	mm	Part number
50	39	6 31 34 390 07 6
50	40	6 31 34 400 07 6
50	41	6 31 34 410 07 6
50	42	6 31 34 420 07 6
50	43	6 31 34 430 07 6
50	44	6 31 34 440 07 6
50	45	6 31 34 450 07 6
50	46	6 31 34 460 07 6
50	47	6 31 34 470 07 6
50	48	6 31 34 480 07 6
50	49	6 31 34 490 07 6
50	50	6 31 34 500 07 6
50	51	6 31 34 510 07 6
50	52	6 31 34 520 07 6
50	53	6 31 34 530 07 6
50	54	6 31 34 540 07 6
50	55	6 31 34 550 07 6
50	56	6 31 34 560 07 6
50	57	6 31 34 570 07 6
50	58	6 31 34 580 07 6
50	59	6 31 34 590 07 6
50	60	6 31 34 600 07 6

CENTERING PINS



Ø	L	
mm	mm	Part number
6,35	82	6 31 34 998 30 0
6,35	100	6 31 34 998 31 0
6,35	125	6 31 34 998 33 0
6,35	135	6 31 34 998 33 5



Ø	L	
mm	mm	Part number
6,35	158	3 02 17 366 01 0
7,98	184	3 02 17 362 01 0

ADAPTER/DRILL CHUCK



QUICKIN-ADAPTOR Output M18 x 6 P 1.5

Part number
6 39 01 020 00 6



QUICKIN-ADAPTOR Output 3/4" Weldon

> Part number 6 39 01 021 01 4



 $\begin{tabular}{ll} \bf QUICKIN-ADAPTOR \\ Special Weldon output. Specially designed for core bits from other manufacturers that have an internal hole of > 6.4 mm. \\ \end{tabular}$

Part number
6 39 01 024 01 9



QUICKIN-ADAPTOR Output 1/2" - 20 UNF

Part number 6 39 01 022 00 8



QUICKIN-ADAPTOR

Output B 16

Part number
6 39 01 023 00 2



ADAPTER WITH 3/4" WELDON FITTING

for converting competitor products to the QuickIN system.

Part number 6 39 01 027 01 0



ADAPTER 3/4" WELDON ON B16

Output B 16

Part number 6 39 01 061 00 0



ADAPTER WITH 3/4" WELDON FITTING

Output 1/2" - 20 UNF

Part numbe
6 39 01 070 00 (



ADAPTER WITH QUICKIN MAX / WELDON 32 FITTING

QuickIN output

Part number 6 39 01 045 01 0



ADAPTER WITH QUICKIN MAX / WELDON 32 FITTING

Output 3/4" Weldon

Part number 6 39 01 076 01 0



ADAPTER WITH WELDON 32 FITTING

Output 3/4" Weldon

Part number
6 39 01 075 01 0



EXTENSION

for use on confined, deep, or layered surfaces, through holes possible as of Ø 36 mm. QuickIN fitting, length 100 mm, including centring pin.

Part number 6 31 06 016 01 0



EXTENSION

For use on confined, deep, or layered surfaces, through holes possible from a diameter of 34 mm. 3/4" Weldon fitting, length . 100 mm.

Length mm	Part number
100	6 31 06 022 98 0



KEY-TYPE DRILL CHUCK WITH QUICKIN HOLDER

Chuck opening	
mm	Part number
1.5 - 13	6 39 01 023 02 0
1 - 16	6 39 01 023 01 1



KEY-TYPE DRILL CHUCK WITH 3/4" WELDON FITTING

All and the second seco	
Chuck opening	
mm	Part number
1.5 - 13	6 39 01 061 02 0



QUICK-CLAMPING DRILL CHUCK AND CHUCKING FORCE **SAFETY DEVICE WITH 3/4" WELDON FITTING**

Chuck opening	
mm	Part number
1 - 13	6 32 04 037 01 0



MORSE TAPER ARBORS

for drilling machines with morse taper arbor

Mount	Part number
MT 3/B 16	6 33 01 012 00 5
MT 3/B 22	6 33 01 014 00 7



REDUCING SLEEVES

for M.T. sockets

Mount	Part number
MT 4/MT 3	6 33 02 004 00 2



ENLARGEMENT TAPERS

for M.T. sockets

Mount	Part number
MT 3/MT 3	6 33 04 005 00 0

SPIRALBOHRER



HSS SPIRAL DRILL WITH QUICKIN FITTING

Cutting depth 35 mm

Bore Ø	
mm	Part number
10	6 31 11 009 01 0
10,2	6 31 11 010 01 0
11	6 31 11 011 01 0
12	6 31 11 012 01 0
13	6 31 11 013 01 0
14	6 31 11 014 01 0
15	6 31 11 015 01 0
15,5	6 31 11 016 01 0



HSS TWIST DRILL WITH 3/4" WELDON FITTING

Cutting depth 35 mm

bore Ø	
mm	Part number
5	6 31 11 036 01 0
6	6 31 11 018 01 0
6,8	6 31 11 034 01 0
7	6 31 11 019 01 0
8	6 31 11 020 01 0
8,5	6 31 11 035 01 0
9	6 31 11 021 01 0
10	6 31 11 022 01 0
10,2	6 31 11 037 01 0
11	6 31 11 023 01 0
12	6 31 11 024 01 0
13	6 31 11 025 01 0
14	6 31 11 026 01 0
15	6 31 11 027 01 0
16	6 31 11 028 01 0



HSS TWIST DRILL SET WITH 3/4" WELDON FITTING

Comprising 6 HSS twist drills (diameters of 6, 8, 10, 12, 14 and 16 mm) in a handy plastic storage box. Cutting depth $35\ \text{mm}$

		Pa	ar	t nui	mb	ei
6	71	1	1	Λ1 Ω	02	^

DRIVE ARBORS



QUICKIN-ADAPTORS

With internal cooling lubricant supply. Tool-free core drill bit changes.

Cutting depth mm Taper		Bore Ø mm	Part number	
50	MT 2	12 - 35	6 39 01 065 02 0	
75	MT 2	12 - 35	6 39 01 066 02 0	
50	MK 3	12 - 65	6 39 01 048 02 0	
75	МК 3	12 - 65	6 39 01 049 02 0	



3/4" WELDON MOUNTING SHAFT

With internal cooling lubricant supply. Tool-free core drill bit changes.

Cutting depth		Bore ∅		
mm	Taper	mm	Part number	
50	MT 2	12 - 35	3 34 01 121 02 0	
75	MT 2	12 - 35	3 34 01 120 02 0	
50	MK 3	12 - 35	3 34 01 119 02 0	
75	MK 3	12 - 35	3 34 01 118 02 0	



3/4" WELDON MOUNTING SHAFT

With internal cooling lubricant supply.

Cutting depth Bore ∅				
mm	Taper	mm	Part number	
50	MK 3	12 - 65	6 39 01 074 02 0	
75	MK 3	12 - 65	6 39 01 073 02 0	



WELDON 32 MOUNTING SHAFT

With internal cooling lubricant supply.

Cutting depth		Bore Ø		
mm Taper		mm	Part number	
50	MT 4	50 - 100	6 39 01 072 02 0	



QUICKIN-ADAPTORS

for using FEIN core drills on bench and column drilling machines and all other core drilling units with MT fitting. With internal cooling lubricant supply. Tool-free core drill bit changes.

Cutting depth mm Taper		Bore Ø mm	Part number	
50	MK 3	12 - 65	6 39 01 019 01 3	
50	MT 2	12 - 35	6 39 01 018 01 9	
75	MK 3	12 - 65	6 39 01 055 02 0	
75	MT 2	12 - 35	6 39 01 057 02 0	



3/4" WELDON MOUNTING SHAFT

for using FEIN core drills on bench and column drilling machines and all other core drilling units with MT fitting. With internal cooling lubricant supply. Tool-free core drill bit changes.

Cutting depth		Bore Ø		
mm	Taper	mm	Part number	
75	MT 2	12 - 35	3 34 01 116 02 0	
75	MK 3	12 - 65	3 34 01 117 02 0	

TAPPING



SIZE 2 TAPPING QUICK-CHANGE CHUCK WITH 3/4" WELDON FITTING

Can only be used for magnetic core drills with reverse running function. For tapping drills in accordance with DIN 371 and 374/376, in conjunction with tapping inserts with or without M6 - M20 safety clutch.

Part number
9 26 02 089 01 0



SIZE 2 TAPPING QUICK-CHANGE CHUCK WITH QUICKIN FITTING

Can only be used for magnetic core drills with reverse running function. For tapping drills in accordance with DIN 371 and 374/376, in conjunction with tapping inserts with or without M6 - M20 safety clutch.

Part number
9 26 02 079 01 0



TAPPING INSERTS

for thread drills in accordance with DIN 371 $\,$

	Ø	Square		
Thread	mm	mm	Part number	
M 6	6	4,9	6 32 06 095 01 1	
M 8	8	6,2	6 32 06 138 01 0	
M 10	10	8	6 32 06 139 01 0	



TAPPING INSERTS

for thread drills in accordance with DIN 374/376

Thread	Ø mm	Square mm	Part number
M 6	4,5	3,4	6 32 06 117 01 5
M 10	7	5,5	6 32 06 096 01 4
M 12	9	7	6 32 06 097 01 8
M 14	11	9	6 32 06 098 01 6
M 16	12	9	6 32 06 099 01 0
M 18	14	11	6 32 06 100 01 1
M 20	16	12	6 32 06 101 01 0



TAPPING INSERTS

with safety coupling for blind holes. for thread drills in accordance with DIN 371

	Ø	Square	
Thread	mm	mm	Part number
M 6	6	4,9	6 32 06 118 01 3
M 8	8	6,2	6 32 06 140 01 0
M 10	10	8	6 32 06 141 01 0



TAPPING INSERTS

with safety coupling for blind holes. for thread drills in accordance with DIN 374/376

Thread	Ø mm	Square mm	Part number
M 8	6	4,9	6 32 06 102 01 3
M 10	7	5,5	6 32 06 103 01 7
M 12	9	7	6 32 06 104 01 5
M 14	11	9	6 32 06 105 01 9
M 16	12	9	6 32 06 106 01 2
M 18	14	11	6 32 06 107 01 6
M 20	16	12	6 32 06 108 01 4



TAPPING DRILL FOR THROUGH HOLES

Thread	L mm	Ø mm	Square mm	Part number
M 8	90	8	6,2	6 31 10 023 01 0
M 10	100	10	8	6 31 10 024 01 0
M 12	110	9	7	6 31 10 025 01 0



TAPPERS FOR BLIND HOLES

T	L	Ø	Square	D
Thread	mm	mm	mm	Part number
M 8	90	8	6,2	6 31 10 023 02 0
M 10	100	10	8	6 31 10 024 02 0
M 12	110	9	7	6 31 10 025 02 0



SIZE 3 TAPPING QUICK-CHANGE CHUCK WITH QUICKIN MAX/WELDON 32 FITTING

Can only be used for magnetic core drills with reverse running function. For tapping drills in accordance with DIN 374/376, in conjunction with tapping inserts with or without M22 - M36 $\,$ safety clutch.

	Part number
450,00	9 26 02 082 01 0



TAPPING INSERTS

for thread drills in accordance with DIN 374/376

	Ø	Square	
Thread	mm	mm	Part number
M22/M24	18	14,5	6 32 06 119 01 0
M 27	20	16	6 32 06 120 01 0
M 30	22	18	6 32 06 121 01 0
M 33	25	20	6 32 06 157 01 0
M 36	28	22	6 32 06 158 01 0



TAPPING INSERTS

with safety coupling for blind holes. for thread drills in accordance with DIN 374/376

	Ø	Square		
Thread	mm	mm	Part number	
M22/M24	18	14,5	6 32 06 122 01 0	
M 27	20	16	6 32 06 123 01 0	
M 30	22	18	6 32 06 124 01 0	
M 33	25	20	6 32 06 155 01 0	
M 36	28	22	6 32 06 156 01 0	



INTERCHANGEABLE REDUCING INSERT (SIZE 3 TO SIZE 2)

Reducing insert for holding size 2 tapping inserts (M6-M20) in size 3 tapping quick change chuck (9 26 02 082 01 0).

> Part number 6 32 06 125 01 0



TAPPING DRILL FOR THROUGH HOLES WITH ADAPTER WITH 3/4" WELDON FITTING

Short version in accordance with DIN 352/ISO 13.

Thread	Part number
M 6	6 31 10 019 03 0
M 8	6 31 10 020 03 0
M 10	6 31 10 021 03 0
M 12	6 31 10 022 03 0



TAPPING DRILL FOR THROUGH HOLES

Short version in accordance with DIN 352/ISO 13.

	L	Ø	Square	
Thread	mm	mm	mm	Part number
M 6	56	6	4,9	6 31 10 019 01 0
M 8	63	6	4,9	6 31 10 020 01 0
M 10	70	7	5,5	6 31 10 021 01 0
M 12	75	9	7	6 31 10 022 01 0



ADAPTER WITH 3/4" WELDON FITTING

1/4" hexagonal output in accordance with DIN 3126/ISO 1173 - C 6.3

Part number
6 32 06 148 01 0



ADAPTER WITH 3/4" WELDON FITTING

6 mm round shank output for M5-M8 in accordance with DIN 352/ISO 13

Ø	Square	
mm	mm	Part number
6	4,9	6 32 06 146 01 0



ADAPTER WITH 3/4" WELDON FITTING

7 mm round shank output for M10 in accordance with DIN 352/ISO 13

Ø	Square	
mm	mm	Part number
7	5,5	6 32 06 147 01 0



ADAPTER WITH 3/4" WELDON FITTING

9 mm round shank output for M12 in accordance with DIN 352/ISO 13

Ø	Square	
mm	mm	Part number
9	7	6 32 06 149 01 0



HSS 90° COUNTERSINK BIT

With 1/4" hexagon in accordance with DIN 3126/ISO 1173 - C 6.3

Ø	
mm	Part number
16,5	6 31 11 038 01 0



HSS 90° COUNTERSINK BIT WITH ADAPTER WITH 3/4" WELDON FITTING

 Ø mm
 Part number

 16,5
 6 31 11 038 02 0



TAPPING DRILL SET FOR THROUGH HOLES

Comprising 1 x M6 threading drill in accordance with DIN 352/ISO 13 with 3/4" Weldon adapter, 1 x HSS twist drill, 5 mm in diameter, with 3/4" Weldon fitting and 1 x HSS 90° countersink bit, 16.5 mm in diameter, with 3/4" Weldon adapter and 1 x hexagon socket wrench in a handy plastic storage box.

Thread	Part number
M 6	6 31 10 019 02 0



TAPPING DRILL SET FOR THROUGH HOLES

Comprising 1 x M8 threading drill in accordance with DIN 352/ISO 13 with 3/4" Weldon adapter, 1 x HSS twist drill, 6.8 mm in diameter, with 3/4" Weldon fitting and 1 x HSS 90° countersink bit, 16.5 mm in diameter, with 3/4" Weldon adapter and 1 x hexagon socket wrench in a handy plastic storage box.

Thread	Part number
M 8	6 31 10 020 02 0



TAPPING DRILL SET FOR THROUGH HOLES

Comprising 1 x M10 threading drill in accordance with DIN 352/ISO 13 with 3/4" Weldon adapter, $1 \times 10^{-1} \times 10^{-1}$ x HSS twist drill, 8.5 mm in diameter, with 3/4" Weldon fitting and $1 \times 10^{-1} \times 10^{-1}$ weldon adapter and $1 \times 10^{-1} \times 10^{-1}$ weldon adapter and $1 \times 10^{-1} \times 10^{-1}$ x hexagon socket wrench in a handy plastic storage box.

Thread	Part number
M 10	6 31 10 021 02 0



TAPPING DRILL SET FOR THROUGH HOLES

Comprising 1 x M12 threading drill in accordance with DIN 352/ISO 13 with 3/4" Weldon adapter, 1 x HSS twist drill, 10.2 mm in diameter, with 3/4" Weldon fitting and 1 x HSS 90° countersink bit, 16.5 mm in diameter, with 3/4" Weldon adapter and 1 x hexagon socket wrench in a handy plastic storage box.

Thread	Part number
M 12	6 31 10 022 02 0

CLAMPING FIXTURES



VACUUM PLATE

for anti-magnetic materials and structured bases (corrugated sheet, stud plate etc.) Vacuum plate $396 \times 200 \times 95$ mm

Part number 9 26 02 057 01 7



VACUUM PLATE

for anti-magnetic materials and structured bases (corrugated sheet, stud plate etc.) Vacuum plate $396 \times 350 \times 95$ mm

Part number 9 26 02 085 01 0



VACUUM PUMP

Vacuum pump 230 V 50 Hz, 92 W, suction volume $0.015\,\text{m}^3/\text{min}$, $-0.8\,\text{bar}$, weight 2.5 kg, incl. suction hose, degree of protection: IP 30, protection class: I, switch-on duration: 15-min operation / 10-min pause (interval)

Part number 9 26 01 022 01 3



SUCTION PLATE

for anti-magnetic materials, 250 x 330 x 110 mm

Part number 9 26 02 054 01 6



PIPE DRILLING DEVICE

incl. clamping strap, for positioning bores on pipes with pipe \varnothing of 60 to 300 mm, 220 x 130 mm.

Part number 9 26 02 055 01 0

COOLING



PUMP

Capacity approx. 450 ml.

	Part numbe
	3 21 32 022 00 7

REPLACEMENT HOSE

for hand pump 3 21 32 022 00 7.

Part number 3 14 14 054 00 8



FLEX-JOINTED HOSE

For applications using twist drills.

 mm
 Part number

 340
 3 14 14 070 01 0

 500
 3 14 14 078 01 0



CUTTING PASTE

Lubricating agents for working on sheet metals.

Part number 3 21 32 046 00 0

OTHER ACCESSORIES



MAGBRUSH

Practical tool with high magnetic force for quick and easy collection of magnetic metal swarf.

Part number 6 42 01 005 01 0

ACCESSORY SETS



CONSTRUCTION SITE SET 3/4" WELDON / HSS NOVA 50

- + User set of HM and HSS core drill bits in an L-BOXX
 - + HSS NOVA 50 core drill bit: Extremely resistant to shock and impact, perfectly designed for tough use in steel construction and installation work. Thanks to its tough cutting edges and outstanding HSS steel with a hardness of 64 HRC, the core drill bit also delivers an impressively long service life.
 - HISS cobalt 5 % twist drill set: HSS cobalt alloy twist drills, diameter 2 / 3 / 4 / 5 / 6 / 8 mm. Particularly suitable for working with stainless and alloyed steels.

 + SUPRA SK quick-clamp drill chuck: metal quick-clamping
 - drill chuck with a clamping range of 1–13 mm. Simple, rapid and tool-free clamping for maximum convenience. Automatically self-tightening clamping jaws for precisely axial drilling tool concentricity.
 - + L-BOXX system: Keep things stowed clearly, tidily and safely. Thanks to the tray for small parts, there is room for all accessories and the L-BOXXs can also be joined together and stacked with ease.
 - + 1 set of twist drills, 6 parts
 - + 1 SUPRA-SK quick-clamp drill chuck, 1–13 mm with 3/4" Weldon
 - + HSS twist drills, 35 mm cutting depth (2 each of diameter 8 mm and 10 mm)
 - + 6 HSS NOVA 50 core drill bits, 50 mm cutting depth (diameter 12 / 14 / 16 / 18 / 20 / 22 mm)
 - + 2 x 100 mm centring pins
 - + 1 cutting paste
 - + 1 L-BOXX 136 for accessories

Part number

3 39 01 680 52 0



STRUCTURAL STEEL-SET 3/4" WELDON / HSS NOVA 50 — HM ULTRA 50

- + User set of HM and HSS core drill bits in an L-BOXX
- + HSS NOVA 50 core drill bit: Extremely resistant to shock and impact, perfectly designed for tough use in steel construction and installation work. Thanks to its tough cutting edges and outstanding HSS steel with a hardness of 64 HRC, the core drill bit also delivers an impressively long service life.
- + HM ULTRA 50 core drill bit: Thanks to its high-quality carbide cutting teeth with a hardness of 1450 HV, the core drill bit wins customers over with it outstanding cutting performance and very long service life in all metals.
- + L-BOXX system: Keep things stowed clearly, tidily and safely. Thanks to the tray for small parts, there is room for all accessories and the L-BOXXs can also be joined together and stacked with ease.
- + HSS NOVA 50 core drill bits, 50 mm cutting depth (1 each of diameter 12 / 14 / 16 / 18 / 20 / 22 mm)
- + HM ULTRA 50 core drill bits, 50 mm cutting depth (1 each of diameter 12 / 14 / 16 / 18 / 20 / 22 mm)
- + 2 x 100 mm centring pins
- + 1 cutting paste
- + 1 L-BOXX 136 for accessories

Part number

3 39 01 680 39 0



STRUCTURAL STEEL-SET 3/4" WELDON / HSS NOVA 25

- + User set of HSS core drill bits in an L-BOXX.
- + The most common HSS core drill bit diameters in one set.
- Perfect for steel and bridge construction.

 + HSS NOVA 25 core drill bit: Long service life and particularly resistant to shock and impact: thanks to its tough cutting edges and outstanding HSS steel with a hardness of 64 HRC, the core drill bit is perfectly designed for tough use in steel construction and installation work.

 + Twist drills and countersink bits: With this set you can have
- everything you need for core drilling and blind holes readily
- + L-BOXX system: Keep things stowed clearly, tidily and safely. Thanks to the tray for small parts, there is room for all accessories and the L-BOXXs can also be joined together and stacked with ease.
- + HSS twist drills, 35 mm cutting depth (3 each of diameter
- 10 mm and 12 mm) + HSS NOVA 25 core drill bits, 25 mm cutting depth (3 each of diameter 14 / 16 / 18 / 20 / 22 mm)
- + 2 x 82 mm centring pin
- + 1 cutting paste
- + 1 L-BOXX 136 for accessories

Part number

3 39 01 680 42 0



MACHINERY-SET 3/4" WELDON

- + User set comprising a large number of tapping accessories in an L-BOXX
- + The most common tapping drills for through holes in one set. Perfect for the construction of machines and machine
- + Twist drills and countersink bits: With this set you can have everything you need for core drilling and blind holes readily to hand.
- + L-BOXX system: Keep things stowed clearly, tidily and safely. Thanks to the tray for small parts, there is room for all accessories and the L-BOXXs can also be joined together and stacked with ease. + Tapping drills (2 each of M6, M8, M10, M12 (DIN 352 / ISO 13))
- + HSS twist drills, 35 mm cutting depth (1 each of diameter 5.0 / 6.8 / 8.5 / 10.2 mm)
- + 4 x HSS 90° countersink bits, diameter 16.5 mm
- + 1 cutting paste
- + 1 L-BOXX 136 for accessories

Part number

3 39 01 680 41 0



KBC 36 MAGFORCE TRUCKFRAME-SET 3/4" WELDON / HSS SPECIAL 25

- + User set of HSS core drill bits in an L-BOXX
- + The most common HSS SPECIAL core drill bit diameters in one set. Perfect for the construction of frames for vehicles and special vehicles.
- + HSS SPECIAL 25 core drill bit: Thanks to its special cutting geometry, the core is cut from the inside out and materials of multiple layers can therefore be drilled in a single process.
- + Twist drills and countersink bits: With this set you can have everything you need for core drilling and blind holes readily to hand.
- + L-BOXX system: Keep things stowed clearly, tidily and safely. Thanks to the tray for small parts, there is room for all accessories and the L-BOXXs can also be joined together and stacked with ease
- + HSS twist drills, 35 mm cutting depth (2 each of diameter 8 mm and 10 mm)
- + HSS SPECIAL 25 core drill bits, 25 mm cutting depth (2 each of diameter 12/ 14 / 16 / 18 / 20 / 22 /24 / 26 mm)
- + 2 x 82 mm centring pin
- + 1 cutting paste
- + 1 L-BOXX 136 for accessories

Part number

699.00 3 39 01 680 43 0



FABRICATOR M12 TAPPING-SET 3/4" WELDON

- + User set comprising a large number of tapping accessories in
- The most common tapping drills for through holes and blind holes in one set. Perfect for metal and machine construction
- Tapping quick change chuck: Can be used with all core drills with reverse running and make your tapping even more precise and more efficient.
- + Tapping inserts and tool tapping drills: All from one source, in one set for M8, M10, M12 tapped bores in through holes and blind holes
- + L-BOXX system: Keep things stowed clearly, tidily and safely. Thanks to the tray for small parts, there is room for all accessories and the L-BOXXs can also be joined together and stacked with ease
- + 1 x size 2 tapping quick-change chuck + Tapping collet with safety clutch (1 each of M8 / M10 [DIN 371], M12 [DIN 374/376])
- + HSS machine taps for through holes, 1 each of M8 / M10 [DIN 371B], M12 [DIN 376B]
- + HSS machine taps for blind holes (1 each of M8 / M10 [DIN 371C], M12 [DIN 376C])
- + HSS twist drills, 35 mm cutting depth (1 each of diameter 6.8 / 8.5 / 10.2 mm)
- + 1 x HSS 90° countersink bit, diameter 16.5 mm
- + 1 cutting paste
- + 1 L-BOXX 136 for accessories

Part number

3 39 01 680 40 0





DRILLS

66

Perfectly suited to the job.
Precise, powerful, easy to use.



ROTARY HAMMER DRILL 74

Unbeatable in stone, concrete and masonry. Universal suitability for a very wide range of applications.

ANGLE DRILLS

75

Makes easy work of drilling round corners. Compact, versatile and powerful, for difficult or narrow locations.

TAPPERS

76

Efficient, precise and reliable.
The alternative to working by hand.




MAGNETIC DRILL JIGS 7

Horizontal, vertical or overhead working: easy to use and flexible, on site or in the workshop.



2 DRILLS



⁶⁶

BOP 6



BOP 6 SET



Fast-running single-speed drill with good speed stability, up to 6 mm in steel in metal construction.

		rast raining single speed and with good speed stability, ap	to o minimi steet in metat construction.	
Input	W	500	500	
Output	W	270	270	
Speed, full load	rpm	0 - 2,700	0 - 2,700	
Speed, no load	rpm	0 - 4,000	0 - 4,000	
Torque at max. output power	Nm	3,5	3,5	
Stall torque	Nm	9	9	
Drill chuck clamping width	mm	0.5 - 10	0.5 - 10	
Capacity in steel Ø	mm	6	6	
capacity in Ø stainless steel	mm	6	6	
Capacity in alu Ø	mm	10	10	
Capacity in wood Ø	mm	20	20	
Thread of spindle		1/2"-20 UNF	1/2"-20 UNF	
Collar Ø	mm	43	43	
Width across corners	mm	23	23	
Cable with plug	m	5	5	
Weight according to EPTA	kg	1,7	1,7	
FEIN BENEFITS		 + Optimum speed for lower diameters and therefore econc + FEIN high-power motor with good speed stability for con + Metal gear head and distortion-free barrel-type motor ho + Reversible. + High-precision metal drill chuck. + High concentricity. + Self-tightening drill chuck clamping jaws. + FEIN Sensitive Handle. + Variable speed control. + 5 metre cable. + 43 mm diameter collar for use in the drill jig. 	stant drilling progress in almost any application	
SUPPLIED		1 SUPRA SKE single sheath metal quick clamping drill chuck, 1 additional handle	1 SUPRA SKE single sheath metal quick cla 1 additional handle, 1 plastic carrying case	
Part number		7 205 52 60 00	0	7 205 52 61 00 0

 Part number
 7 205 52 60 00 0
 7 205 52 61 00 0

 EAN
 4014586882413
 4014586881973

2 DRILLS

BOP 10




BOP 10 SET



 $Compact single-speed drill with speed stability, up to 10 \ mm in steel for on-site installation work.$

		compact single speed and with speed stability, up to 10 m	THE SECRET OF SHE HIS GREAT WORK	
Input	W	500	500	
Output	W	270	270	
Speed, full load	rpm	0 - 900	0 - 900	
Speed, no load	rpm	0 - 1,500	0 - 1,500	
Torque at max. output power	Nm	9	9	
Stall torque	Nm	24	24	
Drill chuck clamping width	mm	1.5 - 13	1.5 - 13	
Capacity in steel Ø	mm	10	10	
capacity in Ø stainless steel	mm	10	10	
Capacity in alu Ø	mm	15	15	
Capacity in wood Ø	mm	30	30	
Tapping		M 6	M 6	
Thread of spindle		1/2"-20 UNF	1/2"-20 UNF	
Collar Ø	mm	43	43	
Width across corners	mm	23	23	
Cable with plug	m	5	5	
Weight according to EPTA	kg	1,8	1,8	
FEIN BENEFITS		 Particularly flat and slim design with excellent width acr FEIN high-power motor with good speed stability for co Metal gear head and distortion-free barrel-type motor h Reversible. High-precision metal drill chuck. High-precision metal drill chuck. High concentricity. Self-tightening drill chuck clamping jaws. FEIN Sensitive Handle. Variable speed control. 5 metre cable. 43 mm diameter collar for use in the drill jig. 	nstant drilling progress in almost any applic	
SUPPLIED		1 SUPRA SKE single sheath metal quick clamping drill chuc 1 additional handle	k, 1 SUPRA SKE single sheath metal quici 1 additional handle, 1 plastic carrying of	
Part number		7 205 53 60 0	00 0	7 205 53 61 00 0
EAN		4014586882	468	4014586881980

BOP 10-2







Universal two-speed drill, up to 10 mm with ideal speed range for steel and stainless steel.

		oniversat two speed anti, up to 10 min with the	acat speed range	for steet and stanitess steet.	
Input	W	500		500	
Output	W	270		270	
Speed, full load	rpm	0 - 460 / 0 - 1,350		0 - 460 / 0 - 1,350	
Speed, no load	rpm	0 - 700 / 0 - 2,250		0 - 700 / 0 - 2,250	
Torque at max. output power	Nm	20 / 7		20 / 7	
Stall torque	Nm	50 / 16		50 / 16	
Drill chuck clamping width	mm	1.5 - 13		1.5 - 13	
Capacity in steel Ø	mm	10		10	
capacity in Ø stainless steel	mm	10		10	
Capacity in alu Ø	mm	16		16	
Capacity in wood Ø	mm	35		35	
Tapping		M 10		M 10	
Thread of spindle		1/2"-20 UNF		1/2"-20 UNF	
Collar Ø	mm	43		43	
Width across corners	mm	23		23	
Cable with plug	m	5		5	
Weight according to EPTA	kg	2		2	
FEIN BENEFITS		 + Mechanical two-speed gearbox for optimu + FEIN high-power motor with good speed s + Metal gear head and distortion-free barrel- + Reversible. + High-precision metal drill chuck. + High concentricity. + Self-tightening drill chuck clamping jaws. + FEIN Sensitive Handle. + Variable speed control. + 5 metre cable. + 43 mm diameter collar for use in the drill jig 	itability for consta type motor hous	ant drilling progress in almost any applicatio	n.
SUPPLIED		1 SUPRA SKE single sheath metal quick clamp 1 additional handle	ing drill chuck,	1 SUPRA SKE single sheath metal quick cla 1 additional handle, 1 plastic carrying case	
Part number			7 205 54 60 00 0		7 205 54 61 00 0
EAN			4014586882512		4014586881997

2 DRILLS

BOP 13-2







Universal two-speed drill, up to 13 mm with ideal speed range for steel and stainless steel.

			_		
Input	W	550		550	
Output	W	300		300	
Speed, full load	rpm	0 - 440 / 0 - 1,300		0 - 440 / 0 - 1,300	
Speed, no load	rpm	0 - 680 / 0 - 2,200		0 - 680 / 0 - 2,200	
Torque at max. output power	Nm	20 / 7		20 / 7	
Stall torque	Nm	50 / 16		50 / 16	
Drill chuck clamping width	mm	1.5 - 13		1.5 - 13	
Capacity in steel Ø	mm	13		13	
capacity in Ø stainless steel	mm	13		13	
Capacity in alu Ø	mm	16		16	
Capacity in wood Ø	mm	37		37	
Tapping		M 10		M 10	
Thread of spindle		1/2"-20 UNF		1/2"-20 UNF	
Collar Ø	mm	43		43	
Width across corners	mm	23		23	
Cable with plug	m	5		5	
Weight according to EPTA	kg	2		2	
FEIN BENEFITS		 + Mechanical two-speed gearbox for optimum spee + FEIN high-power motor with good speed stability in Metal gear head and distortion-free barrel-type metal Reversible. + High-precision metal drill chuck. + High-precision metal drill chuck. + High concentricity. + Self-tightening drill chuck clamping jaws. + FEIN Sensitive Handle. + Variable speed control. + 5 metre cable. + 43 mm diameter collar for use in the drill jig. 	for consta	ant drilling progress in almost any applicatior	n.
SUPPLIED		1 SUPRA SKE single sheath metal quick clamping drill 1 additional handle	chuck,	1 SUPRA SKE single sheath metal quick claid additional handle, 1 plastic carrying case	
Part number		7 205 5	5 60 00 0		7 205 55 61 00 0
EAN		401458	6882567		4014586882017

BOS 16

BOS 16-2





		Powerful drill with speed setting for flexible use in metal construction.	Powerful two-speed drill with speed setting in metal construction.	g for flexible use
Input	W	1 200	1 200	
Output	W	680	680	
Speed, full load	rpm	0 - 520	0 - 520 / 0 - 1,600	
Speed, no load	rpm	0 - 520	0 - 520 / 0 - 1,600	
Torque at max. output power	Nm	50	50 / 16	
Stall torque	Nm	50 **	50 / 16 **	
Drill chuck clamping width	mm	3 - 16	3 - 16	
Capacity in steel Ø	mm	16	16	
capacity in Ø stainless steel	mm	16	16	
Capacity in alu Ø	mm	20	20	
Capacity in wood Ø	mm	50	50	
Drilling diameter in steel, hole saws	mm	80	80	
Tapping		M 12	M 12	
Countersinking max. Ø	mm	31	31	
Thread of spindle		1/2"-20 UNF	1/2"-20 UNF	
Width across corners	mm	27	27	
Cable with plug	m	4	4	
Weight according to EPTA	kg	3,5	3,7	
FEIN BENEFITS	+ + + + + + + +	+ Optimum speed for large diameters and therefore cost-effective working with efficient use of the tool. + FEIN high-power motor with good speed stability for constant drilling progress in almost any application. + Metal gear head and distortion-free barrel-type motor housing for superb service life. + Forward/reverse running and electronic speed preselection. - Speed-controlled tacho electronics. + High-precision metal drill chuck. + High concentricity. - Self-tightening drill chuck clamping jaws. - Spaed handle for optimum power transfer. - Variable speed control. - Torque slipping clutch.		
SUPPLIED	15	SUPRA SKE single sheath metal quick clamping drill chuck, 1 a	dditional handle	
Part number		7 205 47 60 00 0		7 205 49 60 00 0
EAN		4014586874463		4014586876443

For accessories, see page 73

2 DRILLS

BOZ 32-4 M



SUPPLIED

1 additional handle, 1 drift key

For accessories, see page 73

Universal four-speed drill with forward/reverse running, speed setting, MT3 tool mounting for heavy-duty drilling.

Input	W	1 800
Output	W	1 100
Load speed in speed 1	rpm	60 - 140
Load speed in speed 2	rpm	95 - 220
Load speed in speed 3	rpm	135 - 310
Load speed in speed 4	rpm	210 - 480
Torque at max. output power	Nm	75 / 48 / 34 / 22
Idling speed in speed 1	rpm	60 - 140
Idling speed in speed 2	rpm	95 - 220
Idling speed in speed 3	rpm	135 - 310
Idling speed in speed 4	rpm	210 - 480
Stall torque	Nm	75 / 48 / 34 / 22 **
Tool Holder		MK 3
Capacity in steel Ø	mm	32
capacity in Ø stainless steel	mm	20
Capacity in alu Ø	mm	60
Capacity in wood Ø	mm	70
Tapping		M 24
Countersinking max. Ø	mm	50
Reaming max. Ø	mm	30
Collar Ø	mm	65
Width across corners	mm	38
Cable with plug	m	3,1
Weight according to EPTA	kg	7,5

Part number	7 202 51 60 00 0
EAN	4014586889849

FEIN BENEFITS

- + FEIN 1800 W high-power motor and mechanical 4-speed gearbox for high torque in heavy-duty drilling work.
- + Tool with forward/reverse running and electronic speed reduction for all drilling work, such as twist drilling, tap drilling, countersinking and reaming.

 Extremely durable design for tough use thanks to highest quality materials and workmanship.

 HT3 tool mounting.

- Electronic torque shut-off.
- Speed-controlled tacho electronics.

- Able to handle extreme loads.
 Metal gear head.
 Cross handle.
 For optimum use on FEIN magnetic drill jigs.
- Wide range of accessories.
- + Wide range of accesso.
 ** Torque slipping clutch.

ACCESSORIES FOR BOP 6, BOP 10, BOP 10-2, **BOP 13-2**



QUICK-ACTION CHUCKS

Single sheath metal SUPRA SKE quick clamping drill chuck with locking force safety device, drill chuck holder 1/2" - 20 UNF

mm	Part number
0.5 - 10	6 32 05 036 01 0



QUICK-ACTION CHUCKS

Single sheath metal SUPRA SKE quick clamping drill chuck with locking force safety device, drill chuck holder 1/2" - 20 UNF

Chuck opening	D
mm	Part number
1.5-13	6 32 05 035 01 0

JAW SPANNER SW17

Part number
6 29 03 002 00 9

SUSPENSION DEVICE

for hooking onto a balancer vertical

Part number
3 02 32 046 00 8



SUSPENSION DEVICE

for hooking onto a balancer horizontal and vertical

Part number
3 21 25 050 00 7



Part number
3 21 27 005 00 6

ACCESSORIES FOR BOS 16, BOS 16-2



Part number
6 39 02 002 01 3



QUICK-ACTION CHUCKS

Single sheath metal SUPRA SKE quick clamping drill chuck with locking force safety device, drill chuck holder 1/2" - 20 UNF

Chuck opening mm	Part number
3-16	6 32 05 038 01 0

QUICK-ACTION CHUCKS

Drill chuck holder 1/2" - 20 UNF form R tip

Chuck opening	
mm	Part number
1-13	6 32 05 033 01 0



KEY-TYPE DRILL CHUCKS

Drill chuck holder 1/2" - 20 UNF

Chuck opening	
mm	Part number
1-10	6 32 03 034 01 0
1.5-13	6 32 03 041 01 4

ACCESSORIES FOR BOZ 32-4 M, DSKE 672, DDSK 672-1, DDSK 672



QUICK-ACTION CHUCKS

Drill chuck holder B 16 form R tip

Chuck opening	
mm	Part number
3-16	6 32 04 025 00 3



QUICK-ACTION CHUCKS

Drill chuck holder B 16 R shaped tip with locking force safety device

Chuck opening	
mm	Part number
L-13	6 32 04 032 00 6



KEY-TYPE DRILL CHUCKS

Drill chuck holder B 16

mm	Part number
1.5-13	6 32 02 030 01 5
3-16	6 32 02 037 01 0



MORSE TAPER ARBORS

for drilling machines with morse taper arbor

Mount	Part number
MT 3/B 16	6 33 01 012 00 5
MT 3/B 22	6 33 01 014 00 7



REDUCING SLEEVES

for M.T. sockets

		6 33 02 003 00) 4
•	DRIFT KEYS		



Mount	mm	Part number
MT 1/MT 2	140	6 33 05 003 00 3
MT 3/MT 4	190	6 33 05 004 00 1

ACCESSORIES FOR ASQ 672-1



MORSE TAPER ARBORS

For tools with Morse taper.

Mount	Part number
MT 4/B 22	6 33 01 016 00 4



REDUCING SLEEVES

for M.T. sockets

Mount	Part number
MT 4/MT 3	6 33 02 004 00 2

Part number

2 ROTARY HAMMER DRILL

ABH 18



SUPPLIED

1 handle, 1 depth stop, 1 plastic carrying case

For accessories, see page 77

Battery voltage	V	18
Battery compatibility		Li-ion/HighPower Li-ion
Battery interface		18 V
Motor		brushless
Speed, no load	rpm	0 - 1,200
Impacts	rpm	0 - 4,400
Impact energy	J	2
Tool Holder		SDS-plus
Hole diameter, concrete	mm	20
Hole diameter, masonry	mm	68
Capacity in steel Ø	mm	13
Capacity in wood Ø	mm	22
Weight without storage battery	kg	2,3

Part number	7 140 01 64 00 0
EAN	4014586889214

FEIN BENEFITS

Extremely compact and powerful cordless rotary hammer drill with an impact energy of 2 J for drilling up to 20 mm in concrete.

- + Rapid work progress thanks to brushless motor with high impact energy.
 + Fatigue-free working thanks to compact design and
- few vibrations.
- + Protection for the user and tool by means of safety
- Protection for the user and tool by finears of safety clutch and overload protection.
 Combination hammer with three functions: hammer drilling, drilling and chiselling.
 Brushless motor with 30 % higher efficiency and long
- service life.
- + 100 screw connections (10 x 75 mm in concrete) with one battery charge (6 Ah).
- + Producing 68 mm socket holes with drill bit in
- masonry.

 + The optional drilling dust nozzle means that little dust is produced.
- + Low-vibration working at just 12 m/s².
- + FEIN SafetyCell technology. Protects the battery and tool from overload, overheating and total discharge.
- + The battery charge can be read off the battery.

WBP 10



SUPPLIED

1 3-jaw chuck up to Ø 10 mm, 1 drill chuck key

For accessories, see page 77

Extremely small angle drill for working in difficult-to-reach spots.

Input	W	500
Output	W	270
Speed, full load	rpm	0 - 1,030
Speed, no load	rpm	0 - 1,830
Torque at max. output power	Nm	8
Stall torque	Nm	21
Drill chuck clamping width	mm	0.8 - 10
Capacity in steel Ø	mm	10
capacity in Ø stainless steel	mm	10
Capacity in alu Ø	mm	15
Capacity in wood Ø	mm	25
Tapping		M 6
Cone at drill shaft	,	B 10
Width across corners	mm	17
Gearbox head height		96
Cable with plug	m	5
Weight according to EPTA	kg	1,5

Part number	7 205 51 60 00 0
EAN	4014586878843

FEIN BENEFITS

- FEIN high-power motor with good speed stability for constant drilling progress in almost any application.
 Particularly flat and slim design with 17 mm width
- across corners and 96 mm gearbox head height for work in tight spaces and corners.
- Flexible and universal use thanks to clockwise and reverse running for thread cuts up to M6.
 Metal gear head.
 Tapered drill shaft.
- + High-precision metal drill chuck.
- High processor mean unit critics.
 High concentricity.
 Distortion-free barrel-type motor housing.
 FEIN Sensitive Handle.
 5 metre cable.

2 TAPPERS

GWP 10



SUPPLIED

 $1\, {\rm additional}\, {\rm handle}, \textbf{Threaded}\, \textbf{chuck}$ not included

For accessories, see page 77

Fast, accurate thread drill with reversing gear for shorter working times.

Input	W	450
Output	W	250
Idling speed in reverse running	rpm	0 - 1,000
Load speed when cutting	rpm	0 - 450
Load speed in reverse running	rpm	0 - 680
Torque at max. output power	Nm	21
Stall torque	Nm	53
Thread in steel up to		M 10
Thread in stainless steel		M 10
Cone at drill shaft		B 12
Collar Ø	mm	43
Width across corners	mm	23
Cable with plug	m	5
Weight according to EPTA	kg	1,6

Part number	7 209 38 60 00 0
EAN	4014586881256

FEIN BENEFITS

- + Unique speed thanks to reversing gear for automatic reversal of rotation direction when retracting drill spindle from threaded hole. Rapid return action at 680 rpm for shorter cycle times.
- Outstanding precision due to clearance-free connection of drill shaft and threaded chuck with B12 taper mounting for high concentricity. Positive fit of thread drill in chuck for the best results.
- + FEIN sensitive handle for applying feed force in the direct drilling axis while ensuring an ideal position in the guiding hand.

- FEIN high-power motor with stable speed.
 Small width across corners of 23 mm.
 Metal gear head.
 Distortion-free barrel-type motor housing.

GENERAL ACCESSORIES



KEY-TYPE DRILL CHUCKS

Drill chuck holder B 10

mm	Part number
0.8-10	6 32 02 044 01 8
0.5-8	6 32 02 043 01 0



DRILLING DUST NOZZLE

Drilling dust nozzle for wet/dry dust extractor. For drilling in all standard wall and ceiling surfaces and producing little dust. For suction hose with 35 mm diameter.

Part number
9 26 02 101 01 0



COLLET CHUCK

with collets 3,5/4,5/6 mm

Part number
6 32 06 063 01 2



FLOATING COLLET CHUCK

with collets 3,5/4,5/6 mm

Part number
6 32 06 076 02 2



COLLETS

for collet chucks and floating collet chucks and tapping adapters.

M2 (DIN 352, DIN 371), M4 (DIN 357, DIN 376)

Ø	Square	
mm	mm	Part number
2,8	2,1	6 32 06 077 00 1



COLLETS

for collet chucks and floating collet chucks and tapping adapters

M3 (DIN 352, DIN 371), M5 (DIN 357, DIN 376)

Ø	Square	
mm	mm	Part number
3,5	2,7	6 32 06 064 00 1



for collet chucks and floating collet chucks and tapping

M4 (DIN 352, DIN 371), M6 (DIN 357, DIN 376)

Ø	Square	
mm	mm	Part number
4,5	3,4	6 32 06 065 00 5



COLLETS

for collet chucks and floating collet chucks and tapping

M5 (DIN 352, DIN 371), M6 (DIN 352), M7 (DIN 352), M8 (DIN 352, DIN 357, DIN 376)

Ø	Square	are
mm	mm	Part number
6	4,9	6 32 06 066 00 8



COLLETS

for collet chucks and floating collet chucks and tapping

M7 (DIN 371), M9 (DIN 352) M 10 (DIN 352, DIN 357, DIN 376)

Ø	Square	
mm	mm	Part number
7	5,5	6 32 06 070 00 6



COLLETS

for collet chucks and floating collet chucks and tapping

adapters. M8 (DIN 371), M11 (DIN 352)

Ø	Square	
mm	mm	Part number
8	6,2	6 32 06 078 00 9



COLLETS

for collet chucks and floating collet chucks and tapping

M10 (DIN 371)

Ø	Square	
mm	mm	Part number
10	8	6 32 06 079 00 3



COLLETS

for collet chucks and floating collet chucks and tapping adapters.

M12 (DIN 357, DIN 371, DIN 376)

Ø	Square	
mm	mm	Part number
9	7	6 32 06 075 00 4



JAW CHUCK

for tapping drill direct adaptor clamping range 2.8 - 9.0 mm,

with key wrench

Part number 6 32 06 019 00 9



FLOATING JAW CHUCK

for tapping drill direct adaptor clamping range 2.8 - 9.0 mm, with key wrench

Part number 6 32 06 041 00 8



DRIFTS

for drill chuck up to B12, length 125 mm, pack of 2

	Length	
Mount	mm	Part number
B 12	125	6 33 05 009 01 3



DEPTH STOP

Part number
3 21 27 005 00 6

ACCESSORIES FOR GWP 10



SUSPENSION DEVICE

for hooking onto a balancer horizontal and vertical

Part number
3 21 25 050 00 7

2 MAGNETIC DRILL JIGS









					1
		IBS 16	MBS 16 X	MBS 25 F	MBS 32 F
		Industrial drill jig for drills with drilling capacity of up to 16 mm.	Flexible magnetic drill jig for rotary drills with up to 16 mm drill capacity.	Flexible magnetic drill jig with fine adjustment for rotary drills with up to 23 mm drill capacity.	Flexible magnetic drill jig with fine adjustment for rotary drills with up to 32 mm drill capacity.
PAGE		79	79	80	80
Input	W		100	100	130
Socket max.	Α		16	16	16
For collar Ø	mm	53	43	53	63 / 65
Twist drill max. Ø	mm	16	16	25	32
Tapping		M 12	M 12	M 20	M 24
Countersinking max. Ø	mm	50	50	50	60
Reaming max. Ø	mm	16	16	25	40
Stroke	mm	145	145	145	178
Swivel range for drill jigs				7°	350°
Total stroke range	mm	295	325	290	365
Adjustment range for drill jigs	mm			6	10
Magnetic holding power	N		12 500	14 000	18 000
Magnetic foot dimensions	mm		195 x 90	205 x 95	220 x 100
Cable with plug	m		4	4	4
Weight according to EPTA	kg	8	9	12,5	21,8

IBS 16



Industrial drill jig for drills with drilling capacity of up to 16 mm.

For collar Ø	mm	53
Twist drill max. Ø	mm	16
Tapping		M 12
Countersinking max. Ø	mm	50
Reaming max. Ø	mm	16
Stroke	mm	145
Total stroke range	mm	295
Weight according to EPTA	kg	8

Part number	9 03 20 223 00 0
EAN	4014586878515

FEIN BENEFITS

- + Lightweight, compact industrial drill jig with aluminium base plate for universal use, including drilling, tapping, reaming and countersinking.
- Double drill motor guide for use with very large drilling tools.
- Base plate with hole pattern for Demmeler and Siegmund System 28 welding tables.
 Integrated coolant tank with flexible jointed hose.
- + Feed handwheel can be moved from one side to the
- Carriage height adjustable without tools.

1 coolant tank, 1 flex-jointed hose, 1 reducing ring, diameter 43 mm

For accessories, see page 81

MBS 16 X



SUPPLIED

1 coolant tank, 1 lashing strap, 1 contact quard

For accessories, see page 81

Input	W	100
Socket max.	А	16
For collar Ø	mm	43
Twist drill max. Ø	mm	16
Tapping		M 12
Countersinking max. Ø	mm	50
Reaming max. Ø	mm	16
Stroke	mm	145
Total stroke range	mm	325
Magnetic holding power	N	12,500
Magnetic foot dimensions	mm	195 x 90

Flexible magnetic drill jig for rotary drills with up to 16 mm drill capacity.

Part number	9 03 21 223 00 0
EAN	4014586895475

kg

4

9

Cable with plug

Weight according to EPTA

FEIN BENEFITS

- + Lightweight, compact magnetic drill jig for universal use, including drilling, tapping, reaming and counter-
- + Double drill motor guide for use with very large drilling
- tools.
 High magnetic holding power and safety circuit guarantee safe working in any position.
 Integrated coolant tank with flexible jointed hose.
- Feed handwheel can be moved from one side to the other.
- + Carriage height adjustable without tools.

2 MAGNETIC DRILL JIGS

MBS 25 F



SUPPLIED

1 coolant tank, 1 lashing strap, 1 contact guard, 1 reducing ring, diameter 43 mm

For accessories, see page 81

Flexible magnetic drill jig with fine adjustment for rotary drills with up to 23 mm drill capacity.

Socket max. A 16 For collar Ø mm 53 Twist drill max. Ø mm 25 Tapping M 20 Countersinking max. Ø mm 50 Reaming max. Ø mm 25 Stroke mm 145 Total stroke range mm 290 Magnetic holding power N 14,000 Adjustment range for drill jigs mm 6 Swivel range for drill jigs 7° Magnetic foot dimensions mm 205 x 95	Input	W	100
Twist drill max. Ø mm 25 Tapping M 20 Countersinking max. Ø mm 50 Reaming max. Ø mm 25 Stroke mm 145 Total stroke range mm 290 Magnetic holding power N 14,000 Adjustment range for drill jigs mm 6 Swivel range for drill jigs 7° Magnetic foot dimensions mm 205 x 95	Socket max.	Α	16
Tapping M 20 Countersinking max. Ø mm 50 Reaming max. Ø mm 25 Stroke mm 145 Total stroke range mm 290 Magnetic holding power N 14,000 Adjustment range for drill jigs mm 6 Swivel range for drill jigs 7° Magnetic foot dimensions mm 205 x 95	For collar Ø	mm	53
Countersinking max. Ø mm 50 Reaming max. Ø mm 25 Stroke mm 145 Total stroke range mm 290 Magnetic holding power N 14,000 Adjustment range for drill jigs mm 6 Swivel range for drill jigs 7° Magnetic foot dimensions mm 205 x 95	Twist drill max. Ø	mm	25
Reaming max. Ø mm 25 Stroke mm 145 Total stroke range mm 290 Magnetic holding power N 14,000 Adjustment range for drill jigs mm 6 Swivel range for drill jigs 7° Magnetic foot dimensions mm 205 x 95	Tapping		M 20
Stroke mm 145 Total stroke range mm 290 Magnetic holding power N 14,000 Adjustment range for drill jigs mm 6 Swivel range for drill jigs 7° Magnetic foot dimensions mm 205 x 95	Countersinking max. Ø	mm	50
Total stroke range mm 290 Magnetic holding power N 14,000 Adjustment range for drill jigs mm 6 Swivel range for drill jigs 7° Magnetic foot dimensions mm 205 x 95	Reaming max. Ø	mm	25
Magnetic holding power N 14,000 Adjustment range for drill jigs mm 6 Swivel range for drill jigs 7° Magnetic foot dimensions mm 205 x 95	Stroke	mm	145
Adjustment range for drill jigs mm 6 Swivel range for drill jigs 7° Magnetic foot dimensions mm 205 x 95	Total stroke range	mm	290
Swivel range for drill jigs 7° Magnetic foot dimensions mm 205 x 95	Magnetic holding power	N	14,000
Magnetic foot dimensions mm 205 x 95	Adjustment range for drill jigs	mm	6
	Swivel range for drill jigs		7°
	Magnetic foot dimensions	mm	205 x 95
Cable with plug m 4	Cable with plug	m	4
Weight according to EPTA kg 12,5	Weight according to EPTA	kg	12,5

Part number	9 03 22 223 00 0
EAN	4014586895482

FEIN BENEFITS

- + Universal suitability for drilling, tapping, reaming and countersinking.
- + Fine adjustment of the drill spindle for convenient tool alignment.
- + Double drill motor guide for use with very large drilling tools.
- + Feed handwheel can be moved from one side to the other.
- + Integrated coolant tank with flexible jointed hose.
- High magnetic holding force.
- + Carriage height adjustable without tools.

MBS 32 F



SUPPLIED

1 clamping strap, 1 swarf hook, 1 swarf guard, 2 keys

For accessories, see page 81

Flexible magnetic drill jig with fine adjustment for rotary drills with up to 32 mm drill capacity.

Input	W	130
Socket max.	Α	16
For collar Ø	mm	63 / 65
Twist drill max. ∅	mm	32
Tapping		M 24
Countersinking max. Ø	mm	60
Reaming max. Ø	mm	40
Stroke	mm	178
Total stroke range	mm	365
Magnetic holding power	N	18,000
Adjustment range for drill jigs	mm	10
Swivel range for drill jigs		350°
Magnetic foot dimensions	mm	220 x 100
Cable with plug	m	4
Weight according to EPTA	kg	21,8

Part number	9 03 16 223 00 8
EAN	4014586847924

FEIN BENEFITS

- + Universal suitability for drilling, tapping, reaming and countersinking.
- Fine adjustment of drill spindle for easy alignment of machine without constantly removing and refitting the magnet.
- High magnetic holding power and safety circuit guarantee safe working in any position.
 Infinitely variable stroke range setting.
- + Compact design.
- Optimum power-to-weight ratio.
- Robust and accurate dual dove-tail guide
- Universal use for drive machines with clamping collar.

ACCESSORIES FOR IBS 16



REDUCING RINGS for attaching machines with collar Ø 43 mm FEIN BOS, KBH

Ø	
mm	Part number
53 / 43	3 26 23 014 01 0

ACCESSORIES FOR MBS 16 X



REDUCING RINGS for attaching machines with collar Ø 33 mm.

Part number
3 26 23 012 01 9



REDUCING RINGS for attaching machines with collar \varnothing 38 mm

Ø	
mm	Part number
43 / 38	3 26 23 013 00 4

ACCESSORIES FOR MBS 25 F



REDUCING RINGS for attaching machines with collar Ø 38 mm

Ø		
mm	Part number	
53 / 38	3 26 23 010 00 8	



for attaching machines with collar Ø 43 mm

Ø	
mm	Part number
53 / 43	3 26 23 009 00 6



REDUCING RINGS for attaching machines with collar ∅ 43 mm FEIN BOS, KBH

Ø	
mm	Part number
53 / 43	3 26 23 014 01 0

ACCESSORIES FOR MBS 16 X, MBS 25 F, MBS 32 F



SUCTION PLATE

for anti-magnetic materials, 250 x 330 x 110 mm

Part number
9 26 02 054 01 6



VACUUM PLATE

for anti-magnetic materials and structured bases (corrugated sheet, stud plate etc.) Vacuum plate $396 \times 200 \times 95$ mm

Part number
9 26 02 057 01 7



PIPE DRILLING DEVICE

incl. clamping strap, for positioning bores on pipes with pipe \varnothing of 60 to 300 mm, 220 x 130 mm.

Part number
9 26 02 055 01 0



VACUUM PUMP

Vacuum pump 230 V 50 Hz, 92 W, suction volume 0.015 m³/min, - 0.8 bar, weight 2.5 kg, incl. suction hose, degree of protection: IP 30, protection class: I, switch-on duration: 15-min operation / 10-min pause (interval)

Part number
9 26 01 022 01 3



DRILL/DRIVER

84

The optimum combination of flexibility, power and reliability. Designed for drilling, tapping and screwdriving in metal.



93

CORDLESS IMPACT WRENCH/DRIVER

90

Unbeatably efficient and always reliable. Wide ranges of use and can withstand permanent loads.



ACCUTEC SCREW GUNS WITH MID-MOUNTED HANDLE

Long-life precision cordless drill/driver for soft and hard sCrew connections in industrial volume production.



97

ACCUTEC BATON OFFSET SCREWDRIVER

Long-life precision cordless drill/driver for soft and hard screw connections in industrial volume production.



METAL SCREW GUN

For safe, consistent working with self-drilling and threadmoulding screws in roof and facade construction as well as heating, air conditioning and ventilation.





3 DRILL/DRIVER









ASCM 18 QM SELECT

4-speed cordless drill/ driver with brushless motor and QuickIN MAX interface. No compromise on performance for drilling and tapping up to 12 mm and drilling with carbide hole saws.

Small and light 4-speed cordless drill/driver with brushless motor and QuickIN interface. Perfectly suited to universal drilling and screwdriving up to 8 mm.

ASCM 18 QSW SELECT

2-speed cordless drill/ driver with brushless motor and QuicklN interface. Perfectly suited to drilling and tapping up to 10 mm.

2-speed cordless combi drill with brushless motor and QuicklN interface. Perfectly suited to drilling up to 10 mm in metal, stone and masonry.

		carbide hole saws.	3 1		
PAGE		85	85	86	86
Removable drill chuck		•	•	•	•
Electronic torque shut-off		•			
Battery voltage	V	18	18	18	18
Battery compatibility		Li-ion/HighPower Li-ion	Li-ion/HighPower Li-ion	Li-ion/HighPower Li-ion	Li-ion/HighPower Li-ion
Battery interface		18 V	MultiVolt	MultiVolt	MultiVolt
Motor		brushless	brushless	brushless	brushless
Gearbox		4-speed	4-speed	2-speed	2-speed
Accessory interface		QuickIN MAX	QuickIN	QuickIN	QuickIN
Speed, no load	rpm	400 / 800 / 1,950 / 3,850	400 / 700 / 1,400 / 2,500	450 / 2,000	450 / 2,000
Impacts	rpm				7,360 / 32,000
Max. torque (hard/soft)	Nm	90 / 45	40 / 20	60 / 32	60 / 32
Torque levels		15 + 1	20 + 1	22 + 1	22 + 1
Drill chuck clamping width	mm	1.5 - 13	1.5 - 13	1.5 - 13	1.5 - 13
Fastening	mm	10 x 400	8 x 200	8 x 300	8 x 300
Capacity in steel Ø	mm	25	13	13	13
Capacity in wood Ø	mm	50	40	50	50
Capacity in stone Ø	mm				13
Tapping		M 12	M 8	M 10	M 10
Weight without storage battery	kg	1,5	1,2	1,3	1,3

[•] included

ASCM 18 QM SELECT



SUPPLIED

1 QuickIN drill chuck (120 Nm), 1 belt clip, 1 magnetic bit storage, 1 handle, 1 plastic carrying case

For accessories, see page 87

4-speed cordless drill/driver with brushless motor and QuickIN MAX interface. No compromise on performance for drilling and tapping up to 12 mm and drilling with carbide hole saws.

Battery voltage	V	18
Battery compatibility		Li-ion/HighPower Li-ion
Battery interface		18 V
Motor		brushless
Gearbox		4-speed
Accessory interface		QuickIN MAX
Speed, no load	rpm	400 / 800 / 1,950 / 3,850
Max. torque (hard/soft)	Nm	90 / 45
Torque levels		15 + 1
Drill chuck clamping width	mm	1.5 - 13
Fastening	mm	10 x 400
Capacity in steel Ø	mm	25
Capacity in wood Ø	mm	50
Tapping		M 12
Weight without storage battery	kg	1,5

Part number	7 116 11 64 00 0
EAN	4014586887340

FEIN BENEFITS

- + Brushless FEIN PowerDrive motor, fully encapsulated and dust-protected with 30 % higher efficiency and long service life.
- 4-speed solid metal gearbox. Optimum cutting speeds for drilling in metal and self-drilling screwdriving.
- $\operatorname{\mathsf{QuickIN}}\nolimits\operatorname{\mathsf{MAX}}\nolimits\operatorname{\mathsf{accessory}}\nolimits\operatorname{\mathsf{interface}}\nolimits\operatorname{\mathsf{for}}\nolimits\operatorname{\mathsf{all}}\nolimits\operatorname{\mathsf{QuickIN}}\nolimits\operatorname{\mathsf{and}}\nolimits$ QuickIN MAX accessories. Quick change between applications.
- + High torques up to 90 Nm.
- + Including QuickIN solid metal drill chuck (120 Nm) with carbide-tipped clamping jaws and high clamping forces.
- + In speed 4, optimum speeds (3850 rpm) for small diameters
- + In speed 3, optimum speeds (1950 rpm) for 8 mm diameters.
- Speed 1 for powerful thread cutting.
- Electronic torque setting.
- Fixes 10 x 400 mm screws without pre-drilling.
- + 2,500 screw connections (5 x 40 mm in wood) with one battery charge (6 Ah)
- One charger for all FEIN Li-ion batteries of all voltage classes.
- The battery charge can be read off the battery.
- FEIN SafetyCell technology. Protects the battery and tool from overload, overheating and total discharge.
- Extensive user protection features include restart protection, electronic overload protection and brake.

ASCM 18 QSW SELECT



SUPPLIED

1 QuickIN drill chuck (120 Nm), 1 belt clip, 1 magnetic bit storage, 1 plastic carrying case

For accessories, see page 87

Small and light 4-speed cordless drill/driver with brushless motor and QuickIN interface. Perfectly suited to universal drilling and screwdriving up to 8 mm.

Battery voltage	V	18
Battery compatibility		Li-ion/HighPower Li-ion
Battery interface		MultiVolt
Motor		brushless
Gearbox		4-speed
Accessory interface		QuickIN
Speed, no load	rpm	400 / 700 / 1,400 / 2,500
Max. torque (hard/soft)	Nm	40 / 20
Torque levels		20 + 1
Drill chuck clamping width	mm	1.5 - 13
Fastening	mm	8 x 200
Capacity in steel Ø	mm	13
Capacity in wood Ø	mm	40
Tapping		M 8

Part number	7 116 12 64 00 0
EAN	4014586889900

Weight without storage battery kg

FEIN BENEFITS

- + Brushless FEIN PowerDrive motor with 30 % higher
- efficiency and long service life.
 4-speed solid metal gearbox. Optimum cutting speeds for drilling in metal and self-drilling screwdriving.
- QuickIN accessory interface for all QuickIN accessories. Quick change between applications.
- + Flexibility with the FEIN MultiVolt interface. Tool can be operated with all FEIN Li-ion batteries (12 to 18V).
- + High torques up to 40 Nm.
 + In speed 4, optimum speeds (2500 rpm) for diameters of up to 6 mm.
- Mechanical torque setting.
- Compact, lightweight design
- 550 screw connections (5 \bar{x} 40 mm in wood) with one battery charge (3 Ah).
- Including QuickIN solid metal drill chuck (120 Nm) with carbide-tipped clamping jaws and high clamping forces.
- One charger for all FEIN Li-ion batteries of all voltage classes.
- The battery charge can be read off the battery.
- FEIN SafetyCell technology. Protects the battery and tool from overload, overheating and total discharge.
- Extensive user protection features include restart protection, electronic overload protection and brake.

Determine the tool speed based on cutting speed and hole diameter.

4-speed cordless drill/driver ASCM 18 QM

Hole diameter	Cutting speed (m/min)			
mm	15	30	40	50
2	3. Speed	4. Speed	4. Speed	4. Speed
4	2. Speed	3. Speed	4. Speed	4. Speed
6	2. Speed	3. Speed	3. Speed	3. Speed
8	1. Speed	2. Speed	3. Speed	3. Speed
10	1. Speed	2. Speed	2. Speed	3. Speed
12	1. Speed	2. Speed	2. Speed	2. Speed

4-speed cordless drill/driver ASCM 18 QSW

Hole diameter	Cutting speed (m/min)			
mm	15	30	40	50
2	4. Speed	4. Speed	4. Speed	4. Speed
4	3. Speed	4. Speed	4. Speed	4. Speed
6	2. Speed	3. Speed	4. Speed	4. Speed
8	1. Speed	3. Speed	3. Speed	3. Speed
10	-	_	-	_
12	-	_	_	_

ABS 18 Q SELECT



ASB 18 Q SELECT



2-speed cordless drill/driver with brushless motor and	
QuickIN interface. Perfectly suited to drilling and tapping	
up to 10 mm.	

2-speed cordless combi drill with brushless motor and QuickIN interface. Perfectly suited to drilling up to 10 mm

		up to 10 mm.	in metal, stone and masonry.
Battery voltage	V	18	18
Battery compatibility		Li-ion/HighPower Li-ion	Li-ion/HighPower Li-ion
Battery interface		MultiVolt	MultiVolt
Motor		brushless	brushless
Gearbox		2-speed	2-speed
Accessory interface		QuickIN	QuickIN
Speed, no load	rpm	450 / 2,000	450 / 2,000
Impacts	rpm		7,360 / 32,000
Max. torque (hard/soft)	Nm	60 / 32	60 / 32
Torque levels		22 + 1	22 + 1
Drill chuck clamping width	mm	1.5 - 13	1.5 - 13
Fastening	mm	8 x 300	8 x 300
Capacity in steel Ø	mm	13	13
Capacity in wood Ø	mm	50	50
Capacity in stone Ø	mm		13
Tapping		M 10	M 10
Weight without storage battery	kg	1,3	1,3

FEIN BENEFITS

- Brushless FEIN PowerDrive motor with 30 % higher efficiency and long service life.
 QuickIN accessory interface for all QuickIN accessories. Quick change between applications.
 MultiVolt interface. Cordless tool can be operated with all FEIN Li-ion batteries (12-18 V).
- + 2-speed solid metal gearbox with switchable striking 2-speed solid metal gearbox for drilling in metal and selfdrilling screwdriving. mechanism for drilling in metal, stone and masonry. Including QuickIN solid metal drill chuck (120 Nm) with carbide-tipped clamping jaws and high clamping forces. Mechanical torque setting.

- Compact design.
- 900 screw connections (5 x 40 mm in wood) with one battery charge (3 Ah).
- One charger for all FEIN Li-ion batteries of all voltage classes.
- The battery charge can be read off the battery.
 FEIN SafetyCell technology. Protects the battery and tool from overload, overheating and total discharge.
 Extensive user protection features include restart protection, electronic overload protection and brake.

SUPPLIED

1 QuickIN drill chuck (120 Nm), 1 belt clip, 1 magnetic bit storage, 1 plastic carrying case

Part number	7 113 22 64 00 0	7 113 23 64 00 0
EAN	4014586887203	4014586887265

For accessories, see page 87

QUICKIN ACCESSORIES



DRILL CHUCK

Small solid metal drill chuck from Röhm, maximum torque

Compatible with all FEIN cordless drill/drivers with QuickIN/ QuickIN MAX interface

Accessory interface	Part number
QuickIN	6 32 08 002 01 0



DRILL CHUCK

Solid metal drill chuck from Röhm with carbide-tipped clamping jaws and high clamping forces. Screwdriver bit may remain in the drive shaft, the drill chuck moves above the bit. Maximum torque 120 Nm.

Compatible with all FEIN cordless drill/drivers with QuickIN/ QuickIN MAX interface.

Accessory interface	Part number
QuickIN	6 32 08 005 01 0



Solid metal drill chuck from Röhm with flat jaws and automatic re-tensioning. Prevents twist drills and threading drills from slipping. Clamping range of 1.5 - 13 mm. High concentricity of up to 0.35 mm for precise working. Compatible with all FEIN cordless drill/drivers with QuickIN / QuickIN MAX interface.

Accessory interface	Part number
QuickIN	6 42 03 006 01 0



BIT HOLDER

1/4" hexagon socket bit holder with convenient one-handed operation and powerful neodymium magnet. Use of the bit holder makes the screwdriver lighter and shorter. Compatible with all FEIN cordless drill/drivers with QuickIN/ QuickIN MAX interface

Accessory interface	Part number
QuickIN	6 05 10 222 01 0



SOCKET ADAPTER

Socket adapter to hold sockets with 1/2" square holder. Compatible with all FEIN cordless drill/drivers with QuickIN/ QuickIN MAX interface.

Accessory interface	Part number
QuickIN	6 42 03 002 01 0



Metal angled head for drilling, tapping and screwdriving in confined spaces. All FEIN QuickIN accessories such as drill chucks, bit holders or socket adapters can be attached to the angled head. Compatible with all FEIN cordless drill/drivers with QuickIN/QuickIN MAX interface.

Accessory interface	Part number
QuickIN	6 42 03 008 01 0



TAPPING ADAPTER

Tapping adapter with 2 collets for shank diameter of 4.5 mm and 6 mm to cut thread sizes M4 / M5 / M6 / M8. Reliable thread drill hold on the square, preventing slipping.
Compatible with all FEIN cordless drill/drivers with QuickIN/ QuickIN MAX interface.

Accessory interface	Part number
QuickIN	6 42 03 003 01 0



TAPPING ADAPTER

Reliable thread drill hold on the square, preventing slipping. Compatible with all FEIN collets and all FEIN cordless drill/ drivers with QuickIN/QuickIN MAX interface.

Accessory interface	Part number
QuickIN	6 42 03 003 02 0



TAPPING COLLET

Efficient thread tapping through reliable tapping drill hold on the square, preventing slipping. The tapping drill bit can be easily changed without the need for any tools. Supplied without tapping drill. Compatible with all FEIN cordless drill/ drivers with QuickIN/QuickIN MAX interface.

	Ø	Square	
Accessory interface	mm	mm	Part number
QuickIN	3,5	2,7	6 42 03 009 01 0
QuickIN	4,5	3,4	6 42 03 010 01 0
QuickIN	6	4,9	6 42 03 011 01 0
QuickIN	7	5,5	6 42 03 012 01 0
QuickIN	8	6,2	6 42 03 013 01 0
QuickIN	9	7	6 42 03 014 01 0
QuickIN	10	8	6 42 03 015 01 0
QuickIN	11	9	6 42 03 016 01 0



QUICKIN SET OF ACCESSORIES FOR METAL

QuickIN set of accessories for cordless drill/drivers for efficient metalworking. Comprising bit holder (1/4"), socket adapter (1/2") and tapping adapter with 2 collects for shank diameters of 4.5 and 6 mm

Compatible with all FEIN cordless drill/drivers with QuickIN/ QuickIN MAX interface.

Accessory interface	Part number
QuickIN	6 42 03 017 02 0



HOLE SAW ADAPTER

To drill large holes in metal. Suitable for all FEIN carbide hole saws and core drills with QuickIN PLUS holder. Perfectly suited to diameters of up to 40 mm. Supplied with centring bit, without hole saw. Compatible with all FEIN cordless drill/ drivers with QuickIN / QuickIN MAX interface.

Accessory interface	Part number
QuickIN	6 42 03 007 01 0

OTHER ACCESSORIES



COLLETS

for collet chucks and floating collet chucks and tapping adapters.

M2 (DIN 352, DIN 371), M4 (DIN 357, DIN 376)

Ø	Square		
mm	mm	Part number	
2.8	2.1	6 32 06 077 00 1	



COLLETS

for collet chucks and floating collet chucks and tapping adapters

M3 (DIN 352, DIN 371), M5 (DIN 357, DIN 376)

Ø	Square	
mm	mm	Part number
3,5	2,7	6 32 06 064 00 1



for collet chucks and floating collet chucks and tapping

M4 (DIN 352, DIN 371), M6 (DIN 357, DIN 376)

Part number
raitifullibei
6 32 06 065 00 5



COLLETS

for collet chucks and floating collet chucks and tapping adapters.

M5 (DIN 352, DIN 371), M6 (DIN 352), M7 (DIN 352), M8 (DIN 352, DIN 357, DIN 376)

Ø	Square	
mm	mm	Part number
6	4,9	6 32 06 066 00 8

3 DRILL/DRIVER



COLLETS

for collet chucks and floating collet chucks and tapping

adapters. M7 (DIN 371), M9 (DIN 352) M 10 (DIN 352, DIN 357, DIN 376)

Ø	Square	
mm	mm	Part number
7	5,5	6 32 06 070 00 6



COLLETS

for collet chucks and floating collet chucks and tapping adapters.

M8 (DIN 371), M11 (DIN 352)

Ø	Square	
mm	mm	Part number
8	6,2	6 32 06 078 00 9



COLLETS

for collet chucks and floating collet chucks and tapping adapters.

M12 (DIN 357, DIN 371, DIN 376)

Ø	Square	
mm	mm	Part number
9	7	6 32 06 075 00 4



COLLETS

for collet chucks and floating collet chucks and tapping adapters. $% \label{eq:collection}%$

M10 (DIN 371)

Ø	Square	
mm	mm	Part number
10	8	6 32 06 079 00 3



CARBIDE HOLE SAW WITH QUICKIN PLUS HOLDER

Carbide cutting tips for optimum service life for efficient drilling in sheet metal plate up to 4 mm thick. Metric dimensions, cutting depth 4 mm.

Cutting depth	Bore Ø	
mm	mm	Part number
4	14	6 31 31 014 01 0
4	15	6 31 31 015 01 0
4	16	6 31 31 016 01 0
4	17	6 31 31 017 01 0
4	18	6 31 31 018 01 0
4	19	6 31 31 019 01 0
4	20	6 31 31 020 01 0
4	21	6 31 31 021 01 0
4	22	6 31 31 022 01 0
4	23	6 31 31 023 01 0
4	24	6 31 31 024 01 0
4	25	6 31 31 025 01 0
4	26	6 31 31 026 01 0
4	27	6 31 31 027 01 0
4	28	6 31 31 028 01 0
4	29	6 31 31 029 01 0
4	30	6 31 31 030 01 0
4	31	6 31 31 031 01 0
4	32	6 31 31 032 01 0
4	33	6 31 31 033 01 0
4	34	6 31 31 034 01 0
4	35	6 31 31 035 01 0
4	36	6 31 31 036 01 0
4	37	6 31 31 037 01 0
4	38	6 31 31 038 01 0
4	39	6 31 31 039 01 0

	Bore ∅	Cutting depth
Part numbe	mm	mm
6 31 31 040 01 0	40	4
6 31 31 041 01 (41	4
6 31 31 042 01 (42	4
6 31 31 043 01 (43	4
6 31 31 044 01 (44	4
6 31 31 045 01 (45	4
6 31 31 046 01 (46	4
6 31 31 047 01 (47	4
6 31 31 048 01 (48	4
6 31 31 049 01 (49	4
6 31 31 050 01 (50	4
6 31 31 051 01 (51	4
6 31 31 052 01 (52	4
6 31 31 053 01 (53	4
6 31 31 054 01 (54	4
6 31 31 055 01 (55	4
6 31 31 056 01 (56	4
6 31 31 057 01 (57	4
6 31 31 058 01 (58	4
6 31 31 059 01 (59	4
6 31 31 060 01 (60	4
6 31 31 065 01 (65	4
6 31 31 068 01 (68	4
6 31 31 070 01 (70	4
6 31 31 075 01 (75	4
6 31 31 080 01 (80	4



CARBIDE HOLE SAW FOR PIPES WITH QUICKIN PLUS HOLDER

Carbide cutting tips for optimum service life for use with pipe material and curved surfaces with wall thicknesses of up to 4 mm

Metric dimensions, cutting depth 4 mm.

Cutting depth	Bore Ø	
mm	mm	Part number
4	21	6 31 31 421 01 0
4	22	6 31 31 422 01 0
4	23	6 31 31 423 01 0
4	24	6 31 31 424 01 0
4	25	6 31 31 425 01 0
4	26	6 31 31 426 01 0
4	27	6 31 31 427 01 0
4	28	6 31 31 428 01 0
4	29	6 31 31 429 01 0
4	30	6 31 31 430 01 0
4	31	6 31 31 431 01 0
4	32	6 31 31 432 01 0
4	33	6 31 31 433 01 0
4	34	6 31 31 434 01 0
4	35	6 31 31 435 01 0
4	36	6 31 31 436 01 0
4	37	6 31 31 437 01 0
4	38	6 31 31 438 01 0
4	39	6 31 31 439 01 0
4	40	6 31 31 440 01 0
4	41	6 31 31 441 01 0
4	42	6 31 31 442 01 0
4	43	6 31 31 443 01 0
4	44	6 31 31 444 01 0

Cutting depth	Bore Ø	
mm	mm	Part number
4	45	6 31 31 445 01 0
4	46	6 31 31 446 01 0
4	47	6 31 31 447 01 0
4	48	6 31 31 448 01 0
4	49	6 31 31 449 01 0
4	50	6 31 31 450 01 0
4	51	6 31 31 451 01 0
4	52	6 31 31 452 01 0
4	53	6 31 31 453 01 0
4	54	6 31 31 454 01 0
4	55	6 31 31 455 01 0
4	56	6 31 31 456 01 0
4	57	6 31 31 457 01 0
4	58	6 31 31 458 01 0
4	59	6 31 31 459 01 0
4	60	6 31 31 460 01 0
4	65	6 31 31 465 01 0
4	68	6 31 31 468 01 0



CARBIDE CORE DRILL BIT WITH QUICKIN PLUS HOLDEROutstanding cutting performance in all common metals.
Metric dimensions, cutting depth 20 mm, drilling diameter in steel up to 25 mm, drilling diameter in aluminium up to 30 mm.

Cutting depth	Bore Ø	
mm	mm	Part number
20	14	6 31 30 014 01 0
20	15	6 31 30 015 01 0
20	16	6 31 30 016 01 0
20	17	6 31 30 017 01 0
20	18	6 31 30 018 01 0
20	19	6 31 30 019 01 0
20	20	6 31 30 020 01 0
20	21	6 31 30 021 01 0
20	22	6 31 30 022 01 0
20	23	6 31 30 023 01 0
20	24	6 31 30 024 01 0
20	25	6 31 30 025 01 0
20	26	6 31 30 026 01 0
20	27	6 31 30 027 01 0
20	28	6 31 30 028 01 0
20	29	6 31 30 029 01 0
20	30	6 31 30 030 01 0



No. in pack

pcs	Part number
1	6 31 14 038 01 0
5	6 31 14 038 02 0

3 CORDLESS IMPACT WRENCH/DRIVER







A3CD 10-1000 W34 SELECT
Cordless impact wrench/driver with
brushless motor and 6-stage torque
setting. For metric screw connections
un to M27

Cordless impact wrench/driver with brushless motor and 6-stage torque setting. For metric screwdriving applications up to M18.

Impact wrench/driver with brushless motor and 6-stage torque setting. For universal screwdriving applications including self-drilling screwdriving

	up to M27.		applications up to M18.		including self-drilling screwdriving.
PAGE		91		91	91
Battery voltage	V	18		18	18
Battery compatibility		Li-ion/HighPower Li-ion	Li-ion/HighPower L	i-ion	Li-ion/HighPower Li-ion
Battery interface		MultiVolt	Mult	tiVolt	MultiVolt
Motor		brushless	brusł	nless	brushless
Speed, no load	rpm	0 - 1,800	0 - 1	L,700	0 - 1,500
Impacts	rpm	0 - 2,200	0 - 3	,400	0 - 3,000
Max. torque	Nm	1,050		290	210
Max. metric screw		M27 (8.8)	M18	(8.8)	
Torque levels		6		6	6
Tool Holder		3/4" Outer square	1/2" Outer sq	uare	1/4" hexagon socket
Weight without storage battery	kg	3		1	1

ASCD 18-1000 W34 SELECT



SUPPLIED

1 plastic carrying case

For accessories, see page 92

Cordless impact wrench/driver with brushless motor and 6-stage torque setting. For metric screw connections up to M27.

Battery voltage		18
Battery compatibility		Li-ion/HighPower Li-ion
Battery interface		MultiVolt
Motor		brushless
Speed, no load	rpm	0 - 1,800
Impacts	rpm	0 - 2,200
Max. torque	Nm	1,050
Torque levels		6
Tool Holder		3/4" Outer square
Max. metric screw		M27 (8.8)
Wood screw Ø	mm	12 x 600
Weight without storage battery	kg	3

Part number	7 115 08 64 00 0
EAN	4014586891651

FEIN BENEFITS

- + Electronic 6-stage torque setting prevents screw heads from being torn off.
- + High torque of up to 1050 Nm for tightening and loosening screws of up to M27.
- Brushless FEIN PowerDrive motor with 30 % higher efficiency and long service life.
- + Maximum release torque of 1500 Nm in reverse
- running.
 Secure socket connection on square drive thanks to force fit and positive fit.
- 3/4" square head for holding sockets.
- Robust solid metal impact gear.
- MultiVolt interface. Cordless tool can be operated with all FEIN Li-ion batteries (12-18 V).
- 130 screw connections (M27) with one battery charge (6 Ah).
- One charger for all FEIN Li-ion batteries of all voltage classes.
- The battery charge can be read off the battery.
- ${\sf FEIN SafetyCell\ technology}.\ {\sf Protects\ the\ battery\ and}$ tool from overload, overheating and total discharge.
- Extensive user protection features include restart protection, electronic overload protection and brake.

ASCD 18-300 W2 SELECT



Cordless impact wrench/driver with brushless motor and 6-stage torque setting. For metric screwdriving applications up to M18.

ASCD 18-200 W4 SELECT



Impact wrench/driver with brushless motor and 6-stage torque setting. For universal screwdriving applications including self-drilling screwdriving.

Battery voltage	V	18	18
Battery compatibility		Li-ion/HighPower Li-ion	Li-ion/HighPower Li-ion
Battery interface		MultiVolt	MultiVolt
Motor		brushless	brushless
Speed, no load	rpm	0 - 1,700	0 - 1,500
Impacts	rpm	0 - 3,400	0 - 3,000
Max. torque	Nm	290	210
Torque levels		6	6
Tool Holder		1/2" Outer square	1/4" hexagon socket
Max. metric screw		M18 (8.8)	
Wood screw Ø	mm	8 x 300	8 x 200
Weight without storage battery	kg	1	1

FEIN BENEFITS

- Brushless FEIN PowerDrive motor with 30 % higher efficiency and long service life.
- Electronic 6-stage torque setting prevents screw heads from being torn off.
- 10 % more torque in reverse running to loosen screws which are extremely tight. MultiVolt interface. Cordless tool can be operated with all FEIN Li-ion batteries (12-18 V).
- 1/2" square for holding sockets. 1/4" hexagon socket for holding bits and socket wrench
- Robust solid metal impact gear.
- Contact guard on gearbox head.
- Compact design.
- 600 screw connections (M18) with one battery charge (6 Ah).
- One charger for all FEIN Li-ion batteries of all voltage classes.
- The battery charge can be read off the battery.
- FEIN SafetyCell technology. Protects the battery and tool from overload, overheating and total discharge.

inserts

- Extensive user protection features include restart protection, electronic overload protection and brake. Metric screws up to M18 (8.8).

SUPPLIED

1 belt clip, 1 magnetic bit storage, 1 plastic carrying case

Part number	7 115 06 64 00 0	7 115 07 64 00 0
EAN	4014586887425	4014586887449

For accessories, see page 92

3 CORDLESS IMPACT WRENCH/DRIVER

GENERAL ACCESSORIES



REDUCTION ADAPTER

3/4" to 1/2" adapter

Part number 6 24 15 002 01 0



IMPACT SOCKET Long, hexagonal, 3/4" fitting.

wrench size		Length		
mm	Thread	mm	Part number	
24	M16 (DIN/ISO)	95	6 24 05 323 01 0	
27	M18 (DIN/ISO)	95	6 24 05 324 01 0	
30	M20 (DIN/ISO)	95	6 24 05 325 01 0	
32	M22 (DIN/ISO)	95	6 24 05 326 01 0	
34	M24 (ISO)	95	6 24 05 327 01 0	
36	M24 (DIN/ISO)	95	6 24 05 328 01 0	
41	M27 (DIN/ISO)	95	6 24 05 329 01 0	



SET OF IMPACT SOCKETS

Long, hexagonal, 3/4" fitting, content: widths across flats of 27, 30, 32, 36 and 41.

Length	
mm	Part number
95	6 24 05 323 02 0



SECURING PIN

For 3/4" impact socket, diameter 4 mm, length 36 mm.

Part number 3 02 40 395 00 0



CIRCLIP

For 3/4" impact socket, diameter 38 mm.

Part number
3 02 40 396 00 0



LOCKING SET

For 3/4" impact socket comprising 3 circlips (diameter 38 mm) and 3 locking pins (diameter 4 mm, length 36 mm).

Part number
3 02 40 396 01 0

ACCUTEC SCREWDRIVERS 3

ASM 18-3 PC









Parameterisable cordless screwdriver with mechanical shut-off clutch for industrial use.

Battery voltage	٧	18	18	18	
Battery interface		MultiVolt	MultiVolt	MultiVolt	
Torque range	Nm	0.5 - 3	1 - 8	3 - 12	
Speed, no load	rpm	110 - 1,200	110 - 1,200	80 - 900	
Tool Holder		1/4" hexagon socket	1/4" hexagon socket	1/4" hexagon socket	
Weight without storage battery	kg	0,8	0,8	0,8	
FEIN BENEFITS		+ Process-capable according to ISO 5393, VDI/VDE 2647, achieves CMK value > 1.67 at ± 10 % (refers to 6 Sigma). + For soft and hard screwed connections. + Programmable parameters (up to 5 steps); speed, direction of rotation, angle of rotation, torque threshold, time			

- - Error criteria settings can prevent manipulation of the screwdriving process.

- Infinitely variable speed adjustment.
 Parameters can be set for forwards or reverse running.
 Brushless motor with 30 % higher efficiency and long service life.
- High speed stability for constant work progress.
- Can be fully loaded up to maximum output torque during continuous operation.
- Extra short design for use in tight spaces.
- Fatigue-free working thanks to narrow grip dimensions and good balance. Optimised air guide: air isn't blown onto the user's hand or into his or her face. Extra large and bright signal unit (OK / not OK).
- Optimum illumination of the screwdriving site.
- Wear-free acceleration switch.

- Tools can be colour-coded using coding rings.

 Scope for attaching suspension bracket (balancer).

 Integrated fastening counter means that a maintenance interval can be set.

 Adjustable battery charge state display on tool.
- MultiVolt interface. Cordless tool can be operated with all FEIN Li-ion batteries (12-18 V).

SUPPLIED

Supplied without battery, charger or torque wrench.

Part number	7 112 77 60 00 0	7 112 78 60 00 0	7 112 79 60 00 0
EAN	4014586891422	4014586891446	4014586891460

For accessories, see page 95

3 ACCUTEC SCREWDRIVERS

ASW 18-6 PC

ASW 18-12 PC

ASW 18-18 PC







Parameterisable cordless screwdriver with mechanical shut-off clutch for industrial use.

Battery voltage	V	18	18	18
Battery interface		MultiVolt	MultiVolt	MultiVolt
Torque range	Nm	1.2 - 6	3 - 12	6 - 18
Speed, no load	rpm	100 - 1,340	75 - 1,020	65 - 900
Weight without storage battery	kg	1	1	1,2

FEIN BENEFITS

- + Process-capable according to ISO 5393, VDI/VDE 2647, achieves CMK value > 1.67 at ± 10 % (refers to 6 Sigma).
- For soft and hard screwed connections.

 Programmable parameters (up to 5 steps): speed, direction of rotation, angle of rotation, torque threshold, time.

 Error criteria settings can prevent manipulation of the screwdriving process.
- Infinitely variable speed adjustment.
- Parameters can be set for forwards or reverse running.
- Brushless FEIN PowerDrive motor with 30 % higher efficiency and long service life.

- High speed stability for constant work progress.

 Can be fully loaded up to maximum output torque during continuous operation.

 Fatigue-free working thanks to narrow grip dimensions and good balance.
- Optimised air guide: air isn't blown onto the user's hand or into his or her face.
- Extra large and bright signal unit (OK / not OK).
- Optimum illumination of the screwdriving site.
- Wear-free acceleration switch.
- Tools can be colour-coded using coding rings.
- Scope for attaching suspension bracket (balancer).
- Integrated fastening counter means that a maintenance interval can be set.
- Adjustable battery charge state display on tool.
- MultiVolt interface. Cordless tool can be operated with all FEIN Li-ion batteries (12-18 V).

 Infinitely adjustable angle head alignment.

 | + Angled head can be set in 30° steps.

SUPPLIED

Supplied without battery, charger, angled head or torque wrench.

Part number	7 112 66 60 00 0	7 112 68 60 00 0	7 112 70 60 00 0
EAN	4014586887920	4014586887968	4014586888002

For accessories, see page 95

ASW 18-30 PC

ASW 18-45 PC

ASW 18-60 PC







Parameterisable cordless screwdriver with mechanical shut-off clutch for industrial use.

Battery voltage	V	18	18	18
Battery interface		MultiVolt	MultiVolt	MultiVolt
Torque range	Nm	12 - 30	20 - 45	25 - 60
Speed, no load	rpm	30 - 420	25 - 310	20 - 230
Weight without storage battery	kg	1,5	1,5	1,65

FEIN BENEFITS

- Process-capable according to ISO 5393, VDI/VDE 2647, achieves CMK value > 1.67 at ± 10 % (refers to 6 Sigma).
- For soft and hard screwed connections.
- Programmable parameters (up to 5 steps): speed, direction of rotation, angle of rotation, torque threshold, time.
- Error criteria settings can prevent manipulation of the screwdriving process.
- Infinitely variable speed adjustment.
- Parameters can be set for forwards or reverse running.
- Brushless FEIN PowerDrive motor with 30 % higher efficiency and long service life.
- High speed stability for constant work progress.

- Can be fully loaded up to maximum output torque during continuous operation. Fatigue-free working thanks to narrow grip dimensions and good balance. Optimised air guide: air isn't blown onto the user's hand or into his or her face.
- Extra large and bright signal unit (OK / not OK).
- Optimum illumination of the screwdriving site.
- Wear-free acceleration switch.
- Tools can be colour-coded using coding rings.
 Scope for attaching suspension bracket (balancer).
- Integrated fastening counter means that a maintenance interval can be set.
- Adjustable battery charge state display on tool.
- MultiVolt interface. Cordless tool can be operated with all FEIN Li-ion batteries (14.4-18 V). Angled head can be set in 30° steps.

+ Angled head can be set in 60° steps.

SUPPLIED

Supplied without battery, charger, angled head or torque wrench.

Part number

Part number	7 112 62 60 00 0	7 112 63 60 00 0	7 112 64 60 00 0
EAN	4014586883830	4014586883847	4014586883854

For accessories, see page 95

GENERAL ACCESSORIES

ADJUSTMENT SPANNER - TORQUE

Part number 3 21 23 002 00 6



TOOL HOLDER

Tool storage for all FEIN AccuTec models.

3 21 26 012 01 0



CODING SLEEVES

for colour IDs of different models For all ASM, ASW 18-6 PC, ASW 18-12 PC.

	No. in pack	
Colour	pcs	Part number
Colour mix	7	3 05 01 352 02 0
blue	10	3 05 01 355 01 0
red	10	3 05 01 356 01 0
orange	10	3 05 01 357 01 0
yellow	10	3 05 01 358 01 0
grey	10	3 05 01 353 01 0
green	10	3 05 01 354 01 0
black	10	3 05 01 352 01 0

ASM ACCESSORIES



PROTECTION FOR ACCUTEC ASM

for protecting the work piece surface from mechanical damages

Model	Part number
ASM 18	3 21 74 028 01 0

ASW ACCESSORIES



ACCUTEC ASW PROTECTIVE COVER

for protecting the work piece surface from mechanical damages

Model	Part number
ASW 18	3 21 74 024 01 0



ANGLED HEAD UP TO 14 NM

3/8" angle head (square head) (DIN 3121-E10) with width across corners of 40 mm and a weight of 0.15 kg. For ASW 18-6 (PC), ASW 18-12 (PC), ASW 14-6 (PC), 14-10 (PC), 14-14 (PC), ASW 10-X and ASW 9-10.

Tool Holder	Part number
3/8" Outer square	9 01 02 018 02 0

3 ACCUTEC SCREWDRIVERS



ANGLED HEAD UP TO 14 NM

1/4" angle head (square head) (DIN 3121-E6,3) with width across corners of 36 mm and a weight of 0.15 kg. For ASW 18-6 (PC), ASW 18-12 (PC), ASW 14-6 (PC), 14-10 (PC), 14-14 (PC), ASW 10-X and ASW 9-10.

Tool Holder	Part number
1/4" Outer square	9 01 02 019 02 0



ANGLED HEAD UP TO 14 NM

1/4" angle head (hexagon socket) (DIN ISO 1173-D6,3) with width across corners of 30 mm and a weight of 0.14 kg. For ASW 18-6 (PC), ASW 18-12 (PC), ASW 14-6 (PC), 14-10 (PC), 14-14 (PC), ASW 10-X and ASW 9-10.

Tool Holder	Part number
1/4" hexagon socket	9 01 02 020 02 0



ANGLED HEAD UP TO 14 NM

1/4" angle head (QuickIN hexagon socket) (DIN ISO 1173-F6,3) with width across corners of 47 mm and a weight of 0.16 kg. For ASW 18-6 (PC), ASW 18-12 (PC), ASW 14-6 (PC), 14-10 (PC), 14-14 (PC), ASW 10-X and ASW 9-10.

Tool Holder	Part number
QuickIN 1/4" Hexagon socket	9 01 02 021 02 0



ANGLED HEAD UP TO 18 NM

ASW 18-18 PC

Tool Holder	Part number
3/8" Outer square	9 01 02 017 02 0



ANGLED HEAD UP TO 45 NM

ASW 18-30 PC, ASW 18-45 PC

Tool Holder	Part number
3/8" Outer square	9 01 02 015 02 0



ANGLED HEAD UP TO 60 NM

ASW 18-60 PC

Tool Holder	Part number
1/2" Outer square	9 01 02 016 02 0



STRAIGHT OUTPUT

ASW 14-6 (PC), ASW 14-10 (PC), ASW 14-14 (PC), ASW 18-6 (PC), ASW 18-12 (PC) Can be used between 1.1 - 9.9 Nm.

Tool Holder	Part number
QuickIN 1/4" Hexagon socket	9 01 06 001 02 0
3/8" Outer square	9 01 06 002 02 0



PLASTIC COVER

for protecting the work piece surface from mechanical damages

Model	Part number
<14 Nm	3 21 74 023 01 0



PLASTIC COVER

for protecting the work piece surface from mechanical damages $% \left(1\right) =\left(1\right) \left(1\right$

Model	Part number	
<45 Nm	3 21 74 022 01 0	



PLASTIC COVER

for protecting the work piece surface from mechanical damages

Model	Part number
<60 Nm	3 21 74 021 01 0



EXTENSION

To reduce the reaction torque and for better accessibility. 100 mm, for ASW18-30 PC, ASW18-45 PC and ASW18-60 PC.

Part number
6 42 03 005 01 0



HANDLI

For ASW14-30 PC, ASW18-30 PC, ASW18-45 PC and ASW18-60 PC.

Part number
3 21 19 150 01 0



SICKLE SPANNER

For securing the angled head on ASW 18-18 (PC), ASW 18-30/45/60 PC.

Part number
6 29 08 014 00 0



SUSPENSION DEVICE

for hooking onto a balancer horizontal and vertical

Part number
3 21 25 050 00 7

ACCESSORIES FOR PARAMETERCONTROL MODELS



PROGRAMMING ADAPTER

For all AccuTec ParameterControl models. Supplied: Software on USB card incl. instructions, adapter and connection cable.

Part number
9 26 04 163 02 0

For more information about the FEIN AccuTec range and to download the Parameter Control PC software, please visit **www.fein.com.**



ASCS 6.3 SELECT



SUPPLIED

- 1 hook, 1 depth stop, 1 insert for hexagon bolts SW 8, 1 plastic carrying case
- For accessories, see page 97

Speed-optimised cordless drill/driver for screw connections in metal up to a diameter of 6.3mm.

V	18
	Li-ion/HighPower Li-ion
	18 V
rpm	0 - 1,500
rpm	0 - 1,700
Nm	30 / 10
mm	6,3
	1/4"
kg	1,1
	rpm rpm Nm mm

Part number	7 113 11 63 00 0
EAN	4014586881461

FEIN BENEFITS

- + 180 screw connections (in steel sheet metal) with one battery charge (6 Ah).
- + Electronic torque shut-off for precise results even without a depth stop.
- Brushless FEIN PowerDrive motor, fully encapsulated and dust-protected with 30 % higher efficiency and long service life.

 + Tested for more than 1 million screw connections.
- + More than 1,000 charge cycles per battery pack.
- + Extremely light weight.
- + Optimum ergonomics with gun handle for high
- contact pressure.
 Powerful up to 30 Nm.
 FEIN SafetyCell technology. Protects the battery and tool from overload, overheating and total discharge.
 Extensive user protection features include restart
- protection, electronic overload protection and brake.

GENERAL ACCESSORIES



TOOL HOLDER 1/4" EXTERNAL HEXAGON

1/4" Drive-Hex Socket with quick-change chuck

mm	mm	Part number
15	51	6 05 10 011 00 9



TOOL HOLDER 1/4" EXTERNAL HEXAGON

1/4" Drive-Hex Socket with spring washer, magnetic

Ø	L	
mm	mm	Part number
10,6	45	6 05 10 215 00 3

GRINDING & POLISHING



ANGLE GRINDERS

Angle Grinders Universal

Powerful, for regular use in the workshop and on the construction site.





Angle Grinders Premium

104

Outstanding runtime, value for money and safety. For seriously challenging jobs.





120 **DIE GRINDERS**

The specialist tools for use in metal working, for grinding, brushing, deburring and polishing.



STAINLESS STEEL

127

Specifically designed for grinding and polishing stainless steel workpieces and surfaces.



The first of its class to include a brushless FEIN PowerDrive Motor and fully enclosed

LASTS MUCH LONGER, BUT COSTS **MUCH LESS!**



A LIGHTWEIGHT TOOL CAN BE POWERFUL TOO.

The best power-to-weight ratio; weighing 2.2 kg and with an output power of 1050 W. Considerably more efficient than an angle grinder with a 1700 W nominal rated input.

ABLE TO WORK WELL UNDER PRESSURE.

The electronic overload protection kicks in when required. A flashing LED indicates when you are working in the overload range. This protects the tool and results in less downtime.

60% LONGER SERVICE LIFE*

PREPARED FOR EVERYTHING.

The infinitely variable electronic speed is ideal for a whole host of grinding materials and applications.



HIGHER SAFETY LEVELS.

Health and safety is significantly improved through the efficient brake (≤ 2 s), soft start, restart protection, kick-back check and jam monitoring. Also available with optional AutoStop and fall arrestor.





PERFECT PROTECTION.


The fully enclosed brushless FEIN PowerDrive Motor and the motor electronics, which are fitted separately and have dust protection, mean that the CG 15 product line lasts much longer than products with universal motors. The concept is rounded off by the optimised cool air supply and temperature monitoring.

BOOK A DEMONSTRATION TODAY AT FEIN.COM

IT'S BEST TO TRY IT FOR YOURSELF.

In addition to its cost-effectiveness and long service life, the EC technology also offers huge benefits that you'll notice as soon as you start using it. The motors are extremely quiet and low-vibration. You will be impressed by its great efficiency in all speed ranges. The whole thing is packaged in a highly ergonomic housing with an optimised low weight.

We guarantee that you'll be bowled over by the difference.



ADDED VALUE FOR YOU



SAFETY IS A PRIORITY.

Almost a third of all reportable accidents at work falling into the category of manually-operated power tools are caused by angle grinders.** FEIN angle grinders of the CG 15 product line with extensive user protection minimise risks for the user. This keeps staff safe and allows you to plan processes. Costs and work loads can be calculated.



THE EASY WAY TO GRIND WITHOUT BREAKS.

A weight of 2.2 kg with an output power of 1050 W produce an excellent power-to-weight ratio. Narrow grip dimensions, the compact design and a good balance ensure the most fatigue-free working possible in tough everyday professional use.




TAKES THE PLACE OF 1.5 UNIVERSAL ANGLE GRINDERS.

The fully enclosed brushless FEIN PowerDrive motor provides the perfect protection from aggressive ceramic and mineral dusts. Sooner or later, these dusts will destroy universal motors. The new innovative FEIN motor concept reliably prevents this from happening and thereby extends the tool's life by more than 60%.



PAYS OFF.

The technology in the FEIN PowerDrive motor manages without carbon brushes. This translates into few wearing parts, longer service intervals and lower maintenance costs. The extremely efficient 1500 W motor consumes 200 W less power and yet is more effective than a 1700 W universal motor, which cuts energy costs.



The new FEIN cordless angle grinder with AMPShare battery technology.

PROTAGO. EXCEPTIONALLY SAFE.

The new FEIN cordless angle grinder. A unique operating concept almost fully eliminates the risks associated with improper operation. FEIN – one thing less to worry about.

→ For more information, visit
https://fein.com/en_uk/protago

NON-REMOVABLE SAFETY HOOD

TOOL-FREE QUICK CLAMPING SYSTEM

USER PROTECTION

thanks to kick-back monitoring, soft start, restart protection, electronic overload protection and braking function.



ADDED VALUE FOR YOU



GUARANTEED PROTECTION AND SAFETY!

Ultimately, as the employer, you are also responsible for the health and safety of your employees. Protect your employees from harm and potentially lifelong negative consequences.

FULLY ENCLOSED MOTOR HOUSING

protects the motor from aggressive ceramic and mineral dusts.

FATIGUE-FREE WORKING

thanks to narrow grip dimensions, compact design and a well-balanced low weight.











SAFE GUIDANCE

thanks to a non-removable additional handle, which can be adjusted into 6 positions.

TWO-HANDED OPERATION

provided by integrated dead man's switch ("AutoStop") and permanently fitted additional handle.



MINIMISE RISK!

Depending on the severity of an accident at work, a company may face huge costs. Now you can finally get this incalculable risk under control.



REDUCE ADMINISTRATIVE WORK!

No accidents means: no administrative work, no disputes with employers' liability insurance associations and health insurance companies or lengthy legal battles.



IMPROVE PLANNING CERTAINTY!

Your projects can be planned with greater reliability. Downtimes caused by accidents become a thing of the past. Qualified and available staff are a key factor in completing projects on time.

4 ANGLE GRINDERS UNIVERSAL





AMP Share





CCG 18-125-7 AS

Compact and easy-to-use cordless angle grinder for light-duty grinding and cutting work.

CCG 18-125-15 AS

Powerful cordless angle grinder with the same output as a corresponding corded 1500 W device, for effective dividing, grinding and deburring tasks.

WSG 7-125 WSG 7-115

Ergonomic 700 W compact angle grinder for light-duty sanding and cutting.

and deburring tasks.						
PAGE		106	106	107	107	
Roughing-down			++	+	+	
Deburring		++	++	+	+	
Dividing		++	++	+	+	
Brushing		+	+			
Satin-finishing						
Polishing						
Soft start		•	•			
Restart protection		•	•	•	•	
Blockage monitoring						
Electronic overload protection		•	•			
Electronic speed preselection			•			
Kick-back check						
Brake			•			
Battery voltage	V	18	18			
Input	W			750	760	
Speed, no load	rpm	11,000	3,400 - 9,800	12,000	12,500	
Grinding disc Ø	mm	125	125	125	115	
Elast. Backing pad Ø	mm	125	125	125	115	
Weight without storage battery	kg	1,6	2,3			

⁺ suitability

⁺⁺ optimal suitability

[•] included











CG 10-125 Ergonomic 1 000 W compact angle grinder for deburring, sanding and cutting.

CG 13-125 V angle grinder with variable speed for effective grinding and cutting work.

CG 17-125 Ergonomic 1300 W compact Ergonomic 1700 W compact angle grinder with high power reserve for effective sanding and cutting.

CG 17-125 INOX Ergonomic 1700 W compact angle grinder with variable speed and high power reserve for stainless steel processing.

CG 17-150 Ergonomic 1700 W compact angle grinder with high power reserve for effective sanding and cutting.

			3	
107	108	108	109	109
+	++	++	++	++
++	+	+	+	+
++	+	++	+	++
+	+	++	+	++
	++		++	
	++		++	
•	•	•	•	•
•	•	•	•	•
	•	•	•	•
	•	•	•	•
	•		•	
	•	•	•	•
1 000	1 300	1 700	1 700	1 700
11,000	2,800 - 11,500	11,500	2,200 - 7,500	9,300
125	125	125	125	150
125	125	125	125	150

4 ANGLE GRINDERS UNIVERSAL

CCG 18-125-7 AS

Compact and easy-to-use cordless angle grinder for light-duty grinding and cutting work.



SUPPLIED

1 Tool-free quick-clamping nut, 1 Inner flange, 1 wheel guard, 1 anti-vibration handle, 1 safety hood for cutter, 1 tool case (L-BOXX 136)

For accessories, see page 118

Battery voltage	V	18
Battery compatibility		Li-ion/ProCORE Li-ion
Battery interface		18 V AMPShare
Motor		brushless
Speed, no load	rpm	11,000
Grinding disc Ø	mm	125
Elast. Backing pad Ø	mm	125
Flange		M 14
Weight without storage battery	kg	1,6

Part number	7 122 07 61 00 0
EAN	4014586897202

FEIN BENEFITS

- High power, mobile use: The brushless high-power motor delivers the same power as a comparable corded 700 W tool for light-duty grinding and cutting work.
- + Optimum user protection features include restart protection, soft start and electronic overload protection.
- + Slimline handle and balanced design for perfect ergonomics.
- + Secure hold for all applications thanks to non-slip handle.
- + Safety hood, which can be adjusted without the use of tools, and quick-clamping nuts make for short setup times.
- Compatible with all 18 V AMPShare ProCORE batteries and chargers for even more power and flexibility. Also suitable for 18 V Bosch Professional cordless devices.
- COOLPACK 2.0 technology delivers a 135 % longer battery life and therefore makes longer operating times possible.
- State-of-the-art cell technology and intelligent battery management deliver 87 % more power than with conventional batteries.
- ProCORE Li-Ion battery with high-power cells, charge status indicator and "Electronic Cell Protection" (ECP). ECP protects against overload, overheating and total discharge.
- + Ideally equipped for every form of use. Mobile working with the L-BOXX system.

CCG 18-125-15 AS

Powerful cordless angle grinder with the same output as a corresponding corded 1500 W device, for effective dividing, grinding and deburring tasks.



SUPPLIED

1 Tool-free quick-clamping nut, 1 Inner flange, 1 wheel guard, 1 anti-vibration handle, 1 safety hood for cutter, 1 plastic tool case (L-BOXX 238)

For accessories, see page 118

Battery voltage	V	18
Battery compatibility		Li-ion/ProCORE Li-ion
Battery interface		18 V AMPShare
Motor		brushless
Speed, no load	rpm	3,400 - 9,800
Grinding disc Ø	mm	125
Elast. Backing pad Ø	mm	125
Flange		M 14
Weight without storage battery	kg	2,3
3		

Part number	7 122 09 61 00 0
EAN	4014586897226

FEIN BENEFITS

- Powerful cordless angle grinder with brushless motor, which can handle very tough requirements and industrial applications, especially in combination with the ProCORE 18 V battery technology.
- + Extensive user protection features include soft start, restart protection, kickback monitoring, electronic overload protection, fall monitoring and brake.
- It's got the knack: manual speed settings via the intuitive control panel allow the speeds to be adapted perfectly to a large range of materials and grinding materials.
- + Secure hold for all applications thanks to non-slip handle.
- Safety hood, which can be adjusted without the use of tools, and quick-clamping nuts make for short setup times.
- + Compatible with all 18 V AMPShare ProCORE batteries and chargers for even more power and flexibility. Also suitable for 18 V Bosch Professional cordless devices.
- COOLPACK 2.0 technology delivers a 135 % longer battery life and therefore makes longer operating times possible.
- State-of-the-art cell technology and intelligent battery management deliver 87 % more power than with conventional batteries.
- ProCORE Li-lon battery with high-power cells, charge status indicator and "Electronic Cell Protection" (ECP).
 ECP protects against overload, overheating and total discharge.
- + Ideally equipped for every form of use. Mobile working with the L-BOXX system.

WSG 7-115

WSG 7-125



Ergonomic 700 W compact angle grinder for light-duty sanding and cutting.

Input	W	760	750
Output	W	420	440
Speed, no load	rpm	12,500	12,000
Grinding disc Ø	mm	115	125
Elast. Backing pad Ø	mm	115	125
Flange		M 14	M 14
Cable with plug	m	2,5	4
Weight according to EPTA	kg	1,7	1,8

FEIN BENEFITS

- Perfect ergonomics thanks to lateral slide switch and small grip dimension.
 Fatigue-free working thanks to low weight.
 Solid metal gearbox head can be turned in 90° steps for maximum robustness and service life and very good access to difficult-to-reach spots.
- + Enhanced safety through integrated restart protection.

SUPPLIED

1 wheel guard, 1 pair of flanges, 1 additional handle, 1 key

Part number	7 221 98 60 00 0	7 222 65 60 00 0
EAN	4014586885506	4014586891477

For accessories, see page 118

CG 10-125



SUPPLIED

1 wheel guard, 1 Tool-free quick-clamping nut, 1 handle, 1 key

For accessories, see page 118

Ergonomic 1	000 W	compact	angle	arinder	for	deburring	sanding	and	cutting

Input	W	1 000
Output	W	630
Speed, no load	rpm	11,000
Grinding disc Ø	mm	125
Elast. Backing pad Ø	mm	125
Flange		M 14
Cable with plug	m	4
Weight according to EPTA	kg	2,1

Part number	7 222 79 60 00 0
EANI	1011506001000

- Robust motor for daily use.
- Compact and easy to use thanks to slim motor housing.
- + Gearbox head can be rotated 90° for high versatility.
- + Good ability to cope with overload thanks to direct motor cooling.
- + Abrasive materials can be changed at speed and without the need for any tools: quick-clamping nut included in scope of supply as standard.
- + Rapid work progress thanks to powerful motor.
- + Enhanced safety through integrated restart protection.

ANGLE GRINDERS UNIVERSAL

CG 13-125 V



SUPPLIED

1 wheel guard, 1 Tool-free guickclamping nut, 1 anti-vibration handle,

For accessories, see page 118

Ergonomic 1300 W compact angle grinder with variable speed for effective grinding and cutting work.

Input	W	1 300
Output	W	700
Speed, no load	rpm	2,800 - 11,500
Grinding disc Ø	mm	125
Elast. Backing pad Ø	mm	125
Flange		M 14
Cable with plug	m	4
Weight according to EPTA	kg	2,3

Part number	7 222 80 60 00 0
EAN	4014586895000

FEIN BENEFITS

- + Robust motor for daily use.+ Long-life thanks to overload protection and long carbon brush service life.
- Versatile due to variable speed.
- Extensive user protection provided by kick-back monitoring, restart protection, soft start and antivibration handle.
- Gearbox head can be rotated 90° for high versatility.
- Abrasive materials can be changed at speed and without the need for any tools: quick-clamping nut included in scope of supply as standard.
- Rapid work progress thanks to powerful motor.
- Good ability to cope with overload thanks to direct motor cooling.
- Industrial cable H07, length 4m.

CG 17-125



SUPPLIED

1 wheel guard, 1 Tool-free quickclamping nut, 1 anti-vibration handle,

For accessories, see page 118

Ergonomic 1700 W compact angle grinder with high power reserve for effective sanding and cutting.

Input	W	1700
Output	W	1 010
Speed, no load	rpm	11,500
Grinding disc Ø	mm	125
Elast. Backing pad Ø	mm	125
Flange	· · · · · · · · · · · · · · · · · · ·	M 14
Cable with plug	m	4
Weight according to EPTA	kg	2,4

Part number	7 222 81 60 00 0
EAN	4014586895017

- Robust motor for daily use.
- Long-life thanks to overload protection and long carbon brush service life.
- Rapid work progress thanks to powerful motor.
- Extensive user protection provided by kick-back monitoring, restart protection, soft start and antivibration handle.
- + Gearbox head can be rotated 90° for high versatility.
- Abrasive materials can be changed at speed and without the need for any tools: quick-clamping nut included in scope of supply as standard.
- Good ability to cope with overload thanks to direct motor cooling. Industrial cable H07, length 4m.

CG 17-125 INOX



SUPPLIED

1 wheel guard, 1 Tool-free quickclamping nut, 1 anti-vibration handle,

For accessories, see page 118

Ergonomic 1700 W compact angle grinder with variable speed and high power reserve for stainless steel processing.

Ergonomic 1700 W compact angle grinder with high power reserve for effective sanding and cutting.

2,5

Input	W	1700
Output	W	1 010
Speed, no load	rpm	2,200 - 7,500
Grinding disc Ø	mm	125
Elast. Backing pad Ø	mm	125
Flange		M 14
Cable with plug	m	4
Weight according to EPTA	kg	2,4

Part number	7 222 82 60 00 0
EAN	4014586895024

FEIN BENEFITS

- + Robust motor for daily use.+ Long-life thanks to overload protection and long carbon brush service life.
- Versatile due to variable speed.
- Extensive user protection provided by kick-back monitoring, restart protection, soft start and antivibration handle.
- Gearbox head can be rotated 90° for high versatility.
- + Abrasive materials can be changed at speed and without the need for any tools: quick-clamping nut included in scope of supply as standard.
- Rapid work progress thanks to powerful motor.
- Good ability to cope with overload thanks to direct motor cooling.
 - Industrial cable H07, length 4m.

CG 17-150



SUPPLIED

1 wheel guard, 1 Tool-free quickclamping nut, 1 anti-vibration handle, 1 key

For accessories, see page 118

Input	W	1 700	
Output	W	1 010	
Speed, no load	rpm	9,300	
Grinding disc Ø	mm	150	
Elast. Backing pad Ø	mm	150	
Flange		M 14	
Cable with plug	m	4	

Part number	7 222 83 60 00 0
EAN	4014586895031

kg

Weight according to EPTA

- Robust motor for daily use.
- Long-life thanks to overload protection and long carbon brush service life.
- Rapid work progress thanks to powerful motor. Extensive user protection provided by kick-back monitoring, restart protection, soft start and antivibration handle.
- Gearbox head can be rotated 90° for high versatility.
- Abrasive materials can be changed at speed and without the need for any tools: quick-clamping nut included in scope of supply as standard.
 Good ability to cope with overload thanks to direct
- motor cooling.
- Industrial cable H07, length 4m.

4 ANGLE GRINDERS PREMIUM









AMP Share





CCG 18-115-10 PD-SEC AS

Powerful cordless angle grinder with

unique operating concept for particularly safe working.

CCG 18-125-10 PD-SEC AS

CCG 18-115-10 AS

Dust-resistant and powerful, compact cordless angle grinder for effective cutting, grinding and deburring work in assembly jobs.

CCG 18-115-10 PD AS

Dust-resistant and powerful, compact cordless angle grinder with dead man's switch for effective cutting, grinding and deburring work in assembly jobs.

CCG 18-125-10 AS

Dust-resistant and powerful, compact cordless angle grinder for effective cutting, grinding and deburring work in assembly jobs.

CCG 18-125-10 PD AS

Dust-resistant and powerful, compact cordless angle grinder with dead man's switch for effective cutting, grinding and deburring work in assembly jobs.

PAGE		112	113	114	114	115	115	
Roughing-down		+	+	+	+	+	+	
Deburring		+	++	++	++	++	++	
Dividing		+	++	++	++	++	++	
Brushing		+	+	+	+	+	+	
Satin-finishing		++	++	++	++	++	++	
Soft start		•	•	•	•	•	•	
Restart protection				•	•	•	•	
Blockage monitoring		•	•	•	•	•	•	
Electronic overload protection		•	•	•	•	•	•	
Electronic speed preselection		•	•	•	•	•	•	
AutoStop dead man's switch		•	•		•		•	
Kick-back check								
Brake		•	•	•	•	•	•	
Battery voltage	V	18	18	18	18	18	18	
Input	W							
Speed, no load	rpm	2,500 - 8,500	2,500 - 8,500	2,500 - 8,500	2,500 - 8,500	2,500 - 8,500	2,500 - 8,500	
Grinding disc Ø	mm	115	125	115	115	125	125	
Elast. Backing pad Ø	mm	115	125	115	115	125	125	
Weight without storage battery	kg	2,3	2,3	2	2	2	2	

⁺ suitability

⁺⁺ optimal suitability

included



3,800 - 9,000

125

125









CG 15-150 BL

Dust-resistant,

powerful, low-maintenance and

long-life compact

angle grinder with

effective cutting,

deburring work in

grinding and

tough working environments.

2,800 - 7,000

125

125

brushless FEIN
PowerDrive motor for



CG 15-125 BLP

Dust-resistant,

powerful, low-maintenance and

long-life compact

angle grinder with

dead man's switch and brushless FEIN

effective cutting,

grinding and deburring work in tough working environments.

117

+

++

++

954

1 500

150

150

2,800 - 7,000

PowerDrive motor for

117

++

+

++

++

• • • •

•

1 500

125

125

3,800 - 9,000

CG 15-125 BL	CG 15-150 BLP	CG 15-125 BL INOX	CG 15-125 BLP INOX
Dust-resistant, powerful, low-maintenance and long-life compact angle grinder with brushless FEIN PowerDrive motor for effective cutting, grinding and deburring work in tough working environments.	Dust-resistant, powerful, low-maintenance and long-life compact angle grinder with dead man's switch and brushless FEIN PowerDrive motor for effective cutting, grinding and deburring work in tough working environments.	Dust-resistant, powerful, low-maintenance and long-life compact angle grinder with brushless FEIN PowerDrive motor for effective cutting, grinding and deburring work in tough working environments for stainless steel processing.	Dust-resistant, powerful, low-maintenance and long-life compact angle grinder with dead man's switch and brushless FEIN PowerDrive motor for effective cutting, grinding and deburring work in tough working environments for stainless steel processing.
116	116	116	117
++	++	++	++
+	+	+	+
++	++	+	+
++	++	+	+
•	•	•	•
•	•	•	•
•	•	•	•
•	•	•	•
954	•	954	•
•	•	•	•
•	•	•	•
1 500	1 500	1 500	1 500

2,800 - 7,000

150

150

2,800 - 7,000

125

125

ANGLE GRINDERS PREMIUM

CCG 18-115-10 PD-SEC AS

CCG 18-115-10 PD-SEC SET **8 AH ProCORE AS**







Powerful cordless angle grinder with unique operating concept for particularly safe working.

AMP Share

Battery voltage	V	18	18
Battery compatibility	-	Li-ion/ProCORE Li-ion	Li-ion/ProCORE Li-ion
Battery interface		18 V AMPShare	18 V AMPShare
Motor		brushless	brushless
Speed, no load	rpm	2,500 - 8,500	2,500 - 8,500
Grinding disc Ø	mm	115	115
Elast. Backing pad Ø	mm	115	115
Flange		M 14	M 14
Weight with battery	kg		3,3
Weight without storage battery	kg	2,3	2,3

FFIN RENEFITS

- Maximum user protection thanks to the combination of a number of safety features. Fewer accidents of the type frequently caused by improper use or negligence.
- Optimum performance, safe handling, perfect ergonomics and simple operation in all work situations.
- Extensive user protection provided by two-handed operation with AutoStop (dead man's switch) and permanently fitted $additional\ handle,\ non-removable\ safety\ hood\ as\ well\ as\ kick-back\ monitoring,\ soft\ start,\ restart\ protection,\ electronic$ overload protection and braking function.
- Safe guidance in all work situations thanks to the additional handle, which can be adjusted into 6 positions.
- Short setup times thanks to the options of tool-free installation and setting, such as those for setting the safety hood, installing the protective cover for cutting work or changing consumables using quick-clamping nuts.
- Fatigue-free working thanks to narrow grip dimensions, compact design and a well-balanced low weight.
- The tried and tested, highly reliable brushless FEIN PowerDrive motors guarantee a very long service life.
- Totally closed motor housing protects the motor from aggressive ceramic and mineral dusts. Separate motor electronics with dust guard in handle area.

 Powerful. 30 % more efficiency than comparable universal motors with a rated output of 1080 W.
- Maintenance-free motor with innovative cooling ribs for optimum heat dissipation, including monitoring of temperature.
- Very smooth running and low-vibration working thanks to motor being decoupled from the housing and mounted separately and four additional vibration dampers.
- Ideal for every application. Optimum speeds, matched to a large number of abrasive materials and other materials using the infinitely variable, electronic speed preselection.
- Delivers the same power as an equivalent corded 1080 W angle grinder
- Ideally equipped for every form of use. Mobile working with the L-BOXX system.

 Compatible with all 18 V AMPShare ProCORE batteries and chargers for even more power and flexibility. Also suitable for 18 V Bosch Professional cordless devices.
- COOLPACK 2.0 technology delivers a 135 % longer battery life and therefore makes longer operating times possible.
- State-of-the-art cell technology and intelligent battery management deliver 87 % more power than with conventional batteries.
- ProCORE Li-Ion battery with high-power cells, charge status indicator and "Electronic Cell Protection" (ECP). ECP protects against overload, overheating and total discharge.

CII	DD	1	FD
วบ	P٢	L	Eυ

1 Tool-free quick-clamping nut, 1 key, 1 plastic tool case (L-BOXX 238), 1 x protective cover for cutting work

1 Tool-free quick-clamping nut, 1 key, 1 x protective cover for cutting work, 2 ProCORE 18 V 8.0 Ah battery pack, 1 x GAL18 V-160 AS rapid charger, 1 plastic tool case (I-ROXX 238)

Part number	7 122 06 61 00 0	7 122 06 62 00 0
FAN	4014586897059	4014586897073

CCG 18-125-10 PD-SEC AS

CCG 18-125-10 PD-SEC SET **8 AH ProCORE AS**







Powerful cordless angle grinder with unique operating concept for particularly safe working.

Battery voltage	V	18	18
Battery compatibility		Li-ion/ProCORE Li-ion	Li-ion/ProCORE Li-ion
Battery interface		18 V AMPShare	18 V AMPShare
Motor		brushless	brushless
Speed, no load	rpm	2,500 - 8,500	2,500 - 8,500
Grinding disc Ø	mm	125	125
Elast. Backing pad Ø	mm	125	125
Flange		M 14	M 14
Weight with battery	kg		3,3
Weight without storage battery	kg	2,3	2,3

FEIN BENEFITS

- Maximum user protection thanks to the combination of a number of safety features. Fewer accidents of the type frequently caused by improper use or negligence.
- Optimum performance, safe handling, perfect ergonomics and simple operation in all work situations.
- Delivers the same power as an equivalent corded 1080 W angle grinder.
- Safe guidance in all work situations thanks to the additional handle, which can be adjusted into 6 positions.

 Extensive user protection provided by two-handed operation with AutoStop (dead man's switch) and permanently fitted additional handle, non-removable safety hood as well as kick-back monitoring, soft start, restart protection, electronic overload protection and braking function.
- Short setup times thanks to the options of tool-free installation and setting, such as those for setting the safety hood, installing the protective cover for cutting work or changing consumables using quick-clamping nuts.
- The tried and tested, highly reliable brushless FEIN PowerDrive motors guarantee a very long service life.
- Totally closed motor housing protects the motor from aggressive ceramic and mineral dusts. Separate motor electronics with dust guard in handle area.
- Ideal for every application. Optimum speeds, matched to a large number of abrasive materials and other materials using the infinitely variable, electronic speed preselection.
- Powerful. 30 % more efficiency than comparable universal motors with a rated output of 1080 W.

 Maintenance-free motor with innovative cooling ribs for optimum heat dissipation, including monitoring of temperature.
- Very smooth running and low-vibration working thanks to motor being decoupled from the housing and mounted separately and four additional vibration dampers.
- Fatigue-free working thanks to narrow grip dimensions, compact design and a well-balanced low weight. Ideally equipped for every form of use. Mobile working with the L-BOXX system.
- Compatible with all 18 V AMPShare ProCORE batteries and chargers for even more power and flexibility. Also suitable for 18 V Bosch Professional cordless devices. COOLPACK 2.0 technology delivers a 135 % longer battery life and therefore makes longer operating times possible.
- State-of-the-art cell technology and intelligent battery management deliver 87 % more power than with conventional
- ProCORE Li-lon battery with high-power cells, charge status indicator and "Electronic Cell Protection" (ECP). ECP protects against overload, overheating and total discharge.

SUPPLIED

1 Tool-free quick-clamping nut, 1 key, 1 plastic tool case (L-BOXX 238), 1 x protective cover for cutting work

1 Tool-free quick-clamping nut, 1 key, 1 x protective cover for cutting work, 2 ProCORE 18 V 8.0 Ah battery pack, 1 x GAL18 V-160 AS rapid charger, 1 plastic tool case (L-BOXX 238)

Part number	7 122 05 61 00 0	7 122 05 62 00 0
EAN	4014586896991	4014586897011

ANGLE GRINDERS PREMIUM

CCG 18-115-10 AS

Dust-resistant and powerful, compact cordless angle grinder for effective cutting, grinding and deburring work in assembly jobs.



SUPPLIED

1 wheel guard, 1 Tool-free quickclamping nut, 1 anti-vibration handle, 1 key, 1 plastic tool case (L-BOXX 238)

For accessories, see page 118

Battery voltage	V	18
Battery compatibility		Li-ion/ProCORE Li-ion
Battery interface		18 V AMPShare
Motor		brushless
Speed, no load	rpm	2,500 - 8,500
Grinding disc Ø	mm	115
Elast. Backing pad Ø	mm	115
Flange		M 14
Weight without storage battery	kg	2

Part number	7 122 01 61 00 0
EAN	4014586898155

FEIN BENEFITS

- Guarantees very long life with the next generation of brushless FEIN PowerDrive motors. Totally closed motor housing protects the motor from aggressive ceramic and mineral dusts
- Ideal for every application. Optimum speeds, matched to a large number of abrasive materials and other materials using the infinitely variable, electronic speed preselection.
- Powerful. 30 % more efficiency than comparable universal motors with a rated output of 1080 W.
- Delivers the same power as an equivalent corded 1080 W angle grinder.
- Maintenance-free motor with innovative cooling ribs for optimum heat dissipation, including monitoring of temperature.
- COOLPACK 2.0 technology delivers a 135 % longer battery life and therefore makes longer operating times possible.
- State-of-the-art cell technology and intelligent battery management deliver 87 % more power than with conventional batteries.
- ProCORE Li-lon battery with high-power cells, charge status indicator and "Electronic Cell Protection" (ECP). ECP protects against overload, overheating and total discharge.
- Very smooth running and low-vibration working thanks to motor being decoupled from the housing and mounted separately and four additional vibration dampers
- Extensive user protection features include soft start, restart protection, electronic overload protection and brake.
- Fatigue-free working thanks to narrow grip dimensions, compact design and a well-balanced low weight.
- Separate motor electronics with dust guard in handle area.
- Compatible with all 18 V AMPShare ProCORE batteries and chargers for even more power and flexibility. Also suitable for 18 V Bosch Professional cordless devices.
- Safety hood, which can be adjusted without the use of tools, and quick-clamping nuts make for short setup
- Bright working area thanks to integrated LED light.
- Ideally equipped for every form of use. Mobile working with the L-BOXX system.

CCG 18-115-10 PD AS

Dust-resistant and powerful, compact cordless angle grinder with dead man's switch for effective cutting, grinding and deburring work in assembly jobs



SUPPLIED

1 wheel guard, 1 Tool-free quickclamping nut, 1 anti-vibration handle, 1 key, 1 plastic tool case (L-BOXX 238)

For accessories, see page 118

Battery voltage	V	18
Battery compatibility		Li-ion/ProCORE Li-ion
Battery interface		18 V AMPShare
Motor		brushless
Speed, no load	rpm	2,500 - 8,500
Grinding disc Ø	mm	115
Elast. Backing pad Ø	mm	115
Flange		M 14
Weight without storage battery	kg	2

Part number	7 122 03 61 00 0
EAN	4014586898179

- Guarantees very long life with the next generation of brushless FEIN PowerDrive motors. Totally closed motor housing protects the motor from aggressive ceramic and mineral dusts.
- Ideal for every application. Optimum speeds, matched to a large number of abrasive materials and other materials using the infinitely variable, electronic speed preselection.
- Powerful. 30 % more efficiency than comparable
- universal motors with a rated output of 1080 W. Delivers the same power as an equivalent corded 1080 W angle grinder.
- Maintenance-free motor with innovative cooling ribs for optimum heat dissipation, including monitoring of
- COOLPACK 2.0 technology delivers a 135 % longer battery life and therefore makes longer operating times possible.
- State-of-the-art cell technology and intelligent battery management deliver 87 % more power than with conventional batteries.
- ProCORE Li-lon battery with high-power cells, charge status indicator and "Electronic Cell Protection" (ECP). ECP protects against overload, overheating and total discharge.
- Very smooth running and low-vibration working thanks to motor being decoupled from the housing and mounted separately and four additional vibration dampers. Extensive user protection features include soft start,
- restart protection, electronic overload protection and brake
- Fatigue-free working thanks to narrow grip dimensions, compact design and a well-balanced low weight.
- Separate motor electronics with dust guard in handle area. Compatible with all 18 V AMPShare ProCORE batteries
- and chargers for even more power and flexibility. Also suitable for 18 V Bosch Professional cordless devices.
- Safety hood, which can be adjusted without the use of tools, and quick-clamping nuts make for short setup times.
- Bright working area thanks to integrated LED light
- Ideally equipped for every form of use. Mobile working with the L-BOXX system.

CCG 18-125-10 AS

Dust-resistant and powerful, compact cordless angle grinder for effective cutting, grinding and deburring work in assembly jobs.



SUPPLIED

1 wheel guard, 1 Tool-free quickclamping nut, 1 anti-vibration handle, 1 key, 1 plastic tool case (L-BOXX 238)

For accessories, see page 118

Battery voltage	V	18
Battery compatibility		Li-ion/ProCORE Li-ion
Battery interface		18 V AMPShare
Motor		brushless
Speed, no load	rpm	2,500 - 8,500
Grinding disc Ø	mm	125
Elast. Backing pad Ø	mm	125
Flange		M 14
Weight without storage battery	kg	2
Speed, no load Grinding disc Ø Elast. Backing pad Ø Flange	mm	2,500 - 8,500 125 125 M 14

Part number	7 122 02 61 00 0
EAN	4014586898162

FEIN BENEFITS

- + Guarantees very long life with the next generation of brushless FEIN PowerDrive motors. Totally closed motor housing protects the motor from aggressive ceramic and mineral dusts.
- Ideal for every application. Optimum speeds, matched to a large number of abrasive materials and other materials using the infinitely variable, electronic speed preselection.
- + Powerful. 30 % more efficiency than comparable universal motors with a rated output of 1080 W.
- + Delivers the same power as an equivalent corded 1080 W angle grinder.
- Maintenance-free motor with innovative cooling ribs for optimum heat dissipation, including monitoring of temperature.
- COOLPACK 2.0 technology delivers a 135 % longer battery life and therefore makes longer operating times possible.
- State-of-the-art cell technology and intelligent battery management deliver 87 % more power than with conventional batteries.
- ProCORE Li-lon battery with high-power cells, charge status indicator and "Electronic Cell Protection" (ECP). ECP protects against overload, overheating and total discharge.
- Very smooth running and low-vibration working thanks to motor being decoupled from the housing and mounted separately and four additional vibration dampers.
- + Extensive user protection features include soft start, restart protection, electronic overload protection and brake.
- + Fatigue-free working thanks to narrow grip dimensions, compact design and a well-balanced low weight.
- + Separate motor electronics with dust guard in handle area.
- Compatible with all 18 V AMPShare ProCORE batteries and chargers for even more power and flexibility. Also suitable for 18 V Bosch Professional cordless devices.
- Safety hood, which can be adjusted without the use of tools, and quick-clamping nuts make for short setup times.
- + Bright working area thanks to integrated LED light
- Ideally equipped for every form of use. Mobile working with the L-BOXX system.

CCG 18-125-10 PD AS

Dust-resistant and powerful, compact cordless angle grinder with dead man's switch for effective cutting, grinding and deburring work in assembly jobs.



SUPPLIED

1 wheel guard, 1 Tool-free quickclamping nut, 1 anti-vibration handle, 1 key, 1 plastic tool case (L-BOXX 238)

For accessories, see page 118

Battery voltage	V	18
Battery compatibility		Li-ion/ProCORE Li-ion
Battery interface		18 V AMPShare
Motor		brushless
Speed, no load	rpm	2,500 - 8,500
Grinding disc Ø	mm	125
Elast. Backing pad Ø	mm	125
Flange		M 14
Weight without storage battery	kg	2

Part number	7 122 04 61 00 0
EAN	4014586898186

- + Guarantees very long life with the next generation of brushless FEIN PowerDrive motors. Totally closed motor housing protects the motor from aggressive ceramic and mineral dusts.
- Ideal for every application. Optimum speeds, matched to a large number of abrasive materials and other materials using the infinitely variable, electronic speed preselection.
- + Powerful. 30 % more efficiency than comparable universal motors with a rated output of 1080 W.
- Delivers the same power as an equivalent corded 1080 W angle grinder.
- Maintenance-free motor with innovative cooling ribs for optimum heat dissipation, including monitoring of temperature.
- COOLPACK 2.0 technology delivers a 135 % longer battery life and therefore makes longer operating times possible.
- State-of-the-art cell technology and intelligent battery management deliver 87 % more power than with conventional batteries.
- ProCORE Li-lon battery with high-power cells, charge status indicator and "Electronic Cell Protection" (ECP). ECP protects against overload, overheating and total discharge.
- Very smooth running and low-vibration working thanks to motor being decoupled from the housing and mounted separately and four additional vibration dampers.
 Extensive user protection features include soft start,
- Extensive user protection features include soft start, restart protection, electronic overload protection and brake.
- + Fatigue-free working thanks to narrow grip dimensions, compact design and a well-balanced low weight.
- + Separate motor electronics with dust guard in handle area.
- Compatible with all 18 V AMPShare ProCORE batteries and chargers for even more power and flexibility. Also suitable for 18 V Bosch Professional cordless devices.
- + Safety hood, which can be adjusted without the use of tools, and quick-clamping nuts make for short setup times.
- + Bright working area thanks to integrated LED light
- Ideally equipped for every form of use. Mobile working with the L-BOXX system.

ANGLE GRINDERS PREMIUM

CG 15-125 BL



SUPPLIED

1 wheel guard, 1 Tool-free quickclamping nut, 1 anti-vibration handle, 1 key, 1 x protective cover for cutting

For accessories, see page 118

Dust-resistant, powerful, low-maintenance and long-life compact angle grinder with brushless FEIN PowerDrive motor for effective cutting, grinding and deburring work in tough working environments.

Input	W	1 500
Output	W	1 050
Speed, no load	rpm	3,800 - 9,000
Grinding disc Ø	mm	125
Elast. Backing pad Ø	mm	125
Flange		M 14
Cable with plug	m	4
Weight according to EPTA	kg	2,2

Part number	7 222 67 60 00 0
EAN	4014586895802

FEIN BENEFITS

- Outstanding service life thanks to brushless FEIN PowerDrive motor with fully enclosed motor housing and motor electronics fitted separately.
- Optimum protection for the motor from aggressive ceramic and mineral dusts and therefore reduction in downtimes and maintenance costs.
- Comprehensive user protection provided by soft start, restart protection, blockage monitoring, electronic overload protection, speed preselection, kick-back monitoring, anti-vibration handle and brake.
- Optimum cooling and temperature monitoring
- Weighs just 2.2 kg with an output power of 1 050 W for an excellent power-to-weight ratio.
- Quick-clamping nut included in scope of supply for changing grinding materials in a matter of seconds and without the need for any tools.
- Fatigue-free working thanks to narrow grip dimensions, compact design and a well-balanced low weight. Industrial cable H07, length 4m.

CG 15-150 BLP



SUPPLIED

1 wheel guard, 1 Tool-free quickclamping nut, 1 anti-vibration handle, 1 key, 1 x protective cover for cutting

For accessories, see page 118


Dust-resistant, powerful, low-maintenance and long-life compact angle grinder with dead man's switch and brushless

Input	W	1 500
Output	W	1 050
Speed, no load	rpm	2,800 - 7,000
Grinding disc Ø	mm	150
Elast. Backing pad Ø	mm	150
Flange		M 14
Cable with plug	m	4
Weight according to EPTA	kg	2,4

Part number	7 222 77 60 00 0
FΔN	4014586895956

- Outstanding service life thanks to brushless FEIN PowerDrive motor with fully enclosed motor housing and motor electronics fitted separately.
- Optimum protection for the motor from aggressive ceramic and mineral dusts and therefore reduction in downtimes and maintenance costs.
- Comprehensive user protection provided by soft start. restart protection, blockage monitoring, electronic overload protection, speed preselection, kick-back monitoring, anti-vibration handle and brake.
- Optimum cooling and temperature monitoring.
- Eye for carabiner to secure the angle grinder and prevent it falling off when working at height. Weighs just 2.4 kg with an output power of 1 050 W for
- an excellent power-to-weight ratio.
- Quick-clamping nut included in scope of supply for changing grinding materials in a matter of seconds and without the need for any tools.
- Fatigue-free working thanks to narrow grip dimensions, compact design and a well-balanced low weight.
- Industrial cable H07, length 4m.

CG 15-125 BL INOX





SUPPLIED

1 wheel guard, 1 Tool-free guickclamping nut, 1 anti-vibration handle, 1 key, 1 x protective cover for cutting work

For accessories, see page 118

Input	W	1 500
Output	W	1 050
Speed, no load	rpm	2,800 - 7,000
Grinding disc Ø	mm	125
Elast. Backing pad Ø	mm	125
Flange		M 14
Cable with plug	m	4
Weight according to EPTA	kg	2,3

Part number	7 222 86 60 00 0
EAN	4014586896137

- Outstanding service life thanks to brushless FEIN PowerDrive motor with fully enclosed motor housing and motor electronics fitted separately.
- Optimum protection for the motor from aggressive ceramic and mineral dusts and therefore reduction in downtimes and maintenance costs.
- Comprehensive user protection provided by soft start, restart protection, blockage monitoring, electronic overload protection, speed preselection, kick-back monitoring, anti-vibration handle and brake.
- Optimum cooling and temperature monitoring
- Weighs just 2.3 kg with an output power of 1 050 W for an excellent power-to-weight ratio.
- Quick-clamping nut included in scope of supply for changing grinding materials in a matter of seconds and without the need for any tools.
- Fatigue-free working thanks to narrow grip dimensions, compact design and a well-balanced low weight.
- Industrial cable H07, length 4m.

CG 15-125 BLP INOX

Dust-resistant, powerful, low-maintenance and long-life compact angle grinder with dead man's switch and brushless FEIN PowerDrive motor for effective cutting, grinding and deburring work in tough working environments for stainless steel processing.



SUPPLIED

1 wheel guard, $1\, \text{Tool-free}$ quick-clamping nut, $1\, \text{anti-vibration}$ handle, $1\, \text{key}, 1\, \text{x}$ protective cover for cutting work

For accessories, see page 118

Input	W	1 500
Output	W	1 050
Speed, no load	rpm	2,800 - 7,000
Grinding disc Ø	mm	125
Elast. Backing pad Ø	mm	125
Flange		M 14
Cable with plug	m	4
Weight according to EPTA	kg	2,3

Part number	7 222 85 60 00 0
EAN	4014586896076

FEIN BENEFITS

- Outstanding service life thanks to brushless FEIN
 PowerDrive motor with fully enclosed motor housing
 and motor electronics fitted separately.
- + Optimum protection for the motor from aggressive ceramic and mineral dusts and therefore reduction in downtimes and maintenance costs.
- Comprehensive user protection provided by soft start, restart protection, blockage monitoring, electronic overload protection, speed preselection, kick-back monitoring, anti-vibration handle and brake.
- + Optimum cooling and temperature monitoring.
- Eye for carabiner to secure the angle grinder and prevent it falling off when working at height.
- + Weighs just 2.3 kg with an output power of 1 050 W for an excellent power-to-weight ratio.
- Quick-clamping nut included in scope of supply for changing grinding materials in a matter of seconds and without the need for any tools.
- Fatigue-free working thanks to narrow grip dimensions, compact design and a well-balanced low weight.
- + Industrial cable H07, length 4m.

CG 15-150 BL



SUPPLIED

1 wheel guard, 1 Tool-free quick-clamping nut, 1 anti-vibration handle, 1 key, 1 x protective cover for cutting work

For accessories, see page 118

Dust-resistant, powerful, low-maintenance and long-life compact angle grinder with brushless FEIN PowerDrive motor for effective cutting, grinding and deburring work in tough working environments.

Input	W	1 500
Output	W	1 050
Speed, no load	rpm	2,800 - 7,000
Grinding disc Ø	mm	150
Elast. Backing pad Ø	mm	150
Flange		M 14
Cable with plug	m	4
Weight according to EPTA	kg	2,4

Part number	7 222 78 60 00 0
EAN	4014586896014

FEIN BENEFITS

- Outstanding service life thanks to brushless FEIN
 PowerDrive motor with fully enclosed motor housing
 and motor electronics fitted separately.
- Optimum protection for the motor from aggressive ceramic and mineral dusts and therefore reduction in downtimes and maintenance costs.
- Comprehensive user protection provided by soft start, restart protection, blockage monitoring, electronic overload protection, speed preselection, kick-back monitoring, anti-vibration handle and brake.
- + Optimum cooling and temperature monitoring
- + Weighs just 2.4 kg with an output power of 1 050 W for an excellent power-to-weight ratio.
- + Quick-clamping nut included in scope of supply for changing grinding materials in a matter of seconds and without the need for any tools.
- + Fatigue-free working thanks to narrow grip dimensions, compact design and a well-balanced low weight.
- + Industrial cable H07, length 4m.

CG 15-125 BLP



SUPPLIED

1 wheel guard, 1 Tool-free quickclamping nut, 1 anti-vibration handle, 1 key, 1 x protective cover for cutting work

For accessories, see page 118

Dust-resistant, powerful, low-maintenance and long-life compact angle grinder with dead man's switch and brushless FEIN PowerDrive motor for effective cutting, grinding and deburring work in tough working environments.

Input	W	1 500
Output	W	1 050
Speed, no load	rpm	3,800 - 9,000
Grinding disc Ø	mm	125
Elast. Backing pad Ø	mm	125
Flange		M 14
Cable with plug	m	4
Weight according to EPTA	kg	2,2

Part number	7 222 76 60 00 0
EAN	4014586895895

- Outstanding service life thanks to brushless FEIN PowerDrive motor with fully enclosed motor housing and motor electronics fitted separately.
- Optimum protection for the motor from aggressive ceramic and mineral dusts and therefore reduction in downtimes and maintenance costs.
- Comprehensive user protection provided by soft start, restart protection, blockage monitoring, electronic overload protection, speed preselection, kick-back monitoring, anti-vibration handle and brake.
- + Optimum cooling and temperature monitoring.+ Eye for carabiner to secure the angle grinder and
- Eye for carabiner to secure the angle grinder ar prevent it falling off when working at height.
- + Weighs just 2.2 kg with an output power of 1 050 W for an excellent power-to-weight ratio.
- Quick-clamping nut included in scope of supply for changing grinding materials in a matter of seconds and without the need for any tools.
- + Fatigue-free working thanks to narrow grip dimensions, compact design and a well-balanced low weight.
- + Industrial cable H07, length 4m.

ANGLE GRINDERS PREMIUM

CG 15-125 BL SET HEAVY DUTY



SUPPLIED

1 CG 15-125 BL. 1 Tool-free quickclamping nut, 1 anti-vibration handle, 1 key, 1 x protective cover for cutting work, 1 sanding pad Ø 125 mm, 1 K36 serrated sanding discs, pack size: 10, 1 6.0 mm grinding discs, pack size: 10, 1 K36 fibre sanding discs, pack size: 25

For accessories, see page 118

Dust-resistant, powerful, low-maintenance and long-life compact angle grinder with brushless FEIN PowerDrive motor for effective cutting, grinding and deburring work in tough working environments.

Input	W	1 500
Output	W	1 050
Speed, no load	rpm	3,800 - 9,000
Grinding disc Ø	mm	125
Elast. Backing pad Ø	mm	125
Flange		M 14
Cable with plug	m	4
Weight according to EPTA	kg	2,2

Part number	7 222 67 62 00 0
EAN	4014586898308

FEIN BENEFITS

- Outstanding service life thanks to brushless FEIN PowerDrive motor with fully enclosed motor housing and motor electronics fitted separately.
- Optimum protection for the motor from aggressive ceramic and mineral dusts and therefore reduction in downtimes and maintenance costs.
- Comprehensive user protection provided by soft start, restart protection, blockage monitoring, electronic overload protection, speed preselection, kick-back monitoring, anti-vibration handle and brake
- No need to stress about finding the right consumables - you have everything to hand in a flash!
- The key grinding materials for the most relevant grinding applications.
- Optimum cooling and temperature monitoring.
- Weighs just 2.2 kg with an output power of 1 050 W for an excellent power-to-weight ratio. Quick-clamping nut included in scope of supply for
- changing grinding materials in a matter of seconds and without the need for any tools.
- Fatigue-free working thanks to narrow grip dimensions, compact design and a well-balanced low weight.
- Industrial cable H07, length 4m.

GENERAL ACCESSORIES



ANTI-VIBRATION HANDLE

M 8, vibration absorbing, to reduce the vibrations during longer jobs.

Part number

3 21 19 124 01 0



QUICK-CLAMPING NUT

M14, to change discs without need for tool, low height of just 8 mm

> Part number 6 38 02 191 01 0



INNER FLANGE

Part number 6 38 01 182 01 0



THREADED FLANGE

M 14, for flexible grinding/cutting discs, fan-pattern grinding wheels and round brush

Part number 6 38 02 052 00 0



THREADED FLANGE

M 14, for elastic backing pad and for twisted steel wire brush

Part number 6 38 01 154 00 7



ELASTIC BACKING PAD

with flange M 14, for fibre sanding sheets Ø 125 mm

Ø Part number mm 125 6 38 06 087 01 3



GRINDING DISC

For coarse sanding and machining a welded seam with a good service life. Can be used universally in steel and stainless steel. Stepped shape, inner diameter of 22.23 mm, maximum speed of 12 250 rpm, maximum working speed of 80 m/s.

Ø Thickness		No. in pack	
mm	mm	pcs	Part number
125	6	10	6 37 03 005 01 0



Perfect for dividing thin sheet metal, pipes and profiles. Precise and rapid cut with minimum effort and excellent service life. No rework or thermal discolouration on the workpiece. Can be used universally in steel and stainless steel. Straight shape, inner diameter of 22.23 mm, maximum speed of 12 250 rpm, maximum working speed of 80 m/s.

Ø	Thickness	No. in pack	Part number
mm	mm	pcs	
125	1	25	6 37 09 013 01 0



CUTTING DISC

For dividing sheet metal, pipes and profiles with good dividing speed and good service life. Can be used universally in steel and stainless steel. Stepped shape, inner diameter of 22.23 mm, maximum speed of 12 250 rpm, maximum working speed of 80 m/s.

Ø	Thickness	No. in pack	
mm	mm	pcs	Part number
125	2,5	25	6 37 09 014 01 0



FLAP WHEEL

Abrasive material made from zirconium corundum for excellent surface results with good sanding capacity, offering simple handling and few vibrations. Ideal for machining edges. Long service life with consistent quality of work. Can be used universally in steel and stainless steel. Conical shape, inner diameter of 22.23 mm, maximum speed of 12 250 rpm, maximum working speed of 80 m/s.

	Ø	No. in pack	
Grain	mm	pcs	Part number
40	125	10	6 37 30 022 01 0
60	125	10	6 37 30 023 01 0
80	125	10	6 37 30 024 01 0



FIBRE SANDING DISC

High-performance abrasive material made from zirconium corundum with a very good sanding capacity and service life.

Can be used universally in steel and stainless steel.

	Ø	No. in pack	
Grain	mm	pcs	Part number
36	125	25	6 37 17 301 01 0
60	125	25	6 37 17 302 01 0
80	125	25	6 37 17 303 01 0

ACCESSORIES FOR CCG 18/CG 15



WHEEL GUARD

for serrated and roughing discs

Ø	
mm	Part number
115	3 18 10 299 00 0
125	3 18 10 300 00 0
150	3 18 10 301 00 0



SAFETY HOOD FOR CUTTING WORK

for safe working with cutting wheels

Ø	
mm	Part number
115	6 38 11 016 01 0
125	6 38 11 017 01 0
150	6 38 11 018 01 0



SAFETY HOOD FOR CUTTING WORK

for safe working with cutting wheels

Ø	
mm	Part number
125	3 18 10 319 00 0
150	3 18 10 320 00 0

ACCESSORIES FOR THE WSG 7



WHEEL GUARD

for serrated and roughing discs

Ø	
mm	Part number
115	3 13 48 073 01 0
125	3 13 48 134 01 0



SAFETY HOOD FOR CUTTING WORK

for safe working with cutting wheels

Ø	
mm	Part number
125	3 13 48 135 01 0

ACCESSORIES FOR CG 10/13/17/18



ANTI-VIBRATION HANDLE

M 10, vibration absorbing, to reduce the vibrations during longer jobs.

Part number
3 13 24 000 11 1



WHEEL GUARD

for serrated and roughing discs

0	
mm	Part number
125	3 13 24 000 10 1
150	3 13 24 000 10 2



SAFETY HOOD FOR CUTTING WORK

for safe working with cutting wheels

Ø	
mm	Part number
125	3 13 24 000 14 2
150	3 13 24 000 14 3




DUST PROTECTION FILTER

Suitable for CG 13-125 V, CG 17-125, CG 17-125 Inox and CG 17-150.

Part number
3 13 24 000 14 4

4 DIE GRINDERS



1,77

1,77

battery

Weight without storage

kg

1,35

⁺ suitability

⁺⁺ optimal suitability

[•] included













GSZ 8-280 P	GSZ 8-280 PE	GSZ 8-280 PEL	GSZ 8-90 PEL	GSZ 11-320 PERL	GSZ 11-90 PERL
	die grinder for grinding and to-reach spots; also suitable for	Ergonomic, powerful die grinder with high plunge depth for grinding and deburring in difficult-to- reach spots.	Ergonomic, powerful die grinder for stainless steel processing with high plunge depth for grinding and polishing in especially difficult-to-reach spots.	Ergonomic, extremely powerful die grinder with high plunge depth for heavy-duty grinding and deburring in difficult-to- reach spots.	Ergonomic, extremely powerful die grinder for stainless steel processing with high plunge depth for heavy-duty grinding and polishing.
	124 124	125	125	126	126
	++ ++	++		++	
	++	++		++	
	++ ++	++	++	++	++
	+	+		+	
	+	+		+	
			++		++
			++		++
		•	•	•	•
	750 750	750	710	1 010	1 010
28	8,000 8,500 - 28,000	8,500 - 28,000	2,500 - 9,000	9,500 - 32,500	2,900 - 9,900
 <u> </u>	45 50	50	50	45	50
	8 8	8	8	8	8
	1,4 1,4	1,8	1,8	2,1	2,2

4 DIE GRINDERS

AGSZ 18-280 BL AS AGSZ 18-280 LBL AS AGSZ 18-90 LBL AS AMP Share AMP Share Dust-resistant and powerful, compact Dust-resistant and powerful, compact Dust-resistant and powerful, compact cordless die grinder for effective cutting, cordless die grinder with large plunge cordless die grinder with large plunge grinding, deburring and milling work depth for effective cutting, grinding, depth for grinding and polishing work. deburring and milling work. Battery voltage V 18 18 18 Li-ion/ProCORE Li-ion Li-ion/ProCORE Li-ion Battery compatibility Li-ion/ProCORE Li-ion 18 V AMPShare 18 V AMPShare Battery interface 18 V AMPShare Motor brushless brushless brushless 9,000 - 28,000 9,000 - 28,000 Speed, no load rpm 2,900 - 9,000 Polishing disc Ø mm 80 Grinding wheel for max. Ø mm 50 50 50 Collet for max. Ø 8 8 8 Max. cutter diameter 12 12 12 Weight without storage battery 1,35 1,77 1,77 kg **FEIN BENEFITS** + Guarantees very long life with the next generation of brushless FEIN PowerDrive motors. Totally closed motor housing protects the motor from aggressive ceramic and mineral dusts. Ideal for every application. Optimum speeds, matched to a large number of abrasive materials and other materials using the infinitely variable, electronic speed preselection. Powerful. 30 % more efficiency than comparable universal motors with a rated output of 1 100 W. COOLPACK 2.0 technology delivers a 135 % longer battery life and therefore makes longer operating times possible. State-of-the-art cell technology and intelligent battery management deliver 87 % more power than with conventional batteries ProCORE Li-Ion battery with high-power cells, charge status indicator and "Electronic Cell Protection" (ECP). ECP protects against overload, overheating and total discharge. Very smooth running and low-vibration working thanks to motor being decoupled from the housing and mounted separately and four additional vibration dampers. Extensive user protection features include soft start, restart protection and electronic overload protection. Innovative collets with all-round flange to protect the workpiece and prevent the wrench sliding off during tool changes. Fatigue-free working thanks to narrow grip dimensions, compact design and a well-balanced low weight. Separate motor electronics with dust guard in handle area. Compatible with all 18 V AMPShare ProCORE batteries and chargers for even more power and flexibility. Also suitable for 18 V Bosch Professional cordless devices. Bright working area thanks to integrated LED light. Ideally equipped for every job. Mobile | + Ideally equipped for every job. Mobile working with the XL-BOXX system. working with the L-BOXX system. Long, narrow neck allows tool to plunge a long way into workpieces (e.g. grinding inside pipes).+ Removable rubber collar bearing cover. **SUPPLIED** 1 collet Ø 6 mm, Jaw spanner SW13, 1 collet Ø 6 mm, Jaw spanner SW13, Jaw spanner SW17, 1 tool case (XL-Boxx) Jaw spanner SW17, 1 plastic tool case (L-BOXX 238)

7 123 04 61 00 0

4014586897158

7 123 05 61 00 0

4014586897165

7 123 06 61 00 0

4014586897172

For accessories, see page 126

Part number

EAN

GSZ 4-280 EL

GSZ 4-90 EL





		Extremely ergonomic die grinder with high plunge depth for light grinding and deburring in especially difficult-to-reach spots.	Extremely ergonomic die grinder for stainless steel processing with high plunge depth for light grinding and polishing in especially difficult-to-reach spots.	
Input	W	350	350	
Output	W	170	170	
Speed, no load	rpm	13,000 - 28,000	3,500 - 8,500	
Polishing disc Ø	mm		50	
Grinding wheel for max. Ø	mm	20	20	
Collet for max. Ø	mm	6	6	
Collar Ø	mm	43		
Max. cutter diameter	mm	12	12	
Cable with plug	m	5	5	
Weight according to EPTA	kg	1,5	1,5	
FEIN BENEFITS		inside pipes).	variative collets with all-round flange to protect the workpiece and prevent the wrench sliding off during tool changes. ole speed allows different tools to be used. r and electronics protected against metal dust.	
SUPPLIED		1 collet Ø 6 mm, Jaw spanner SW13, Jaw spanner SW17	Jaw spanner SW17, 1 collet Ø 6 mm, Jaw spanner SW13	

 Part number
 7 223 24 60 00 0
 7 223 25 60 00 0

 EAN
 4014586880594
 4014586880648

4 DIE GRINDERS

GSZ 8-280 P

GSZ 8-280 PE






Ergonomic, powerful die grinder for grinding and deburring in difficult-to-reach spots; also suitable for semi-stationary use.

Input	W	750	750	
Output	W	400	400	
Speed, no load	rpm	28,000	8,500 - 28,000	
Grinding wheel for max. Ø	mm	45	50	
Collet for max. Ø	mm	8	8	
Collar Ø	mm	43	43	
Max. cutter diameter	mm	12	12	
Cable with plug	m	4	4	
Weight according to EPTA	kg	1,4	1,4	
FEIN BENEFITS		as profile miller). + User protection features include blockage monitoring, res + Innovative collets with all-round flange to protect the worl	otection features include blockage monitoring, restart protection, soft start and electronic overload protection. ive collets with all-round flange to protect the workpiece and prevent the wrench sliding off during tool changes. Attronic tachoelectronics for enormous power, power reserve and exceptional speed stability under load.	

SUPPLIED 1 collet Ø 6 mm, Jaw spanner SW13, Jaw spanner SW17

Part number	7 223 16 60 00 0	7 223 17 60 00 0
EAN	4014586879505	4014586879437

GSZ 8-280 PEL







Ergonomic, powerful die grinder with high plunge depth for grinding and deburring in difficult-to-reach spots.

Ergonomic, powerful die grinder for stainless steel processing with high plunge depth for grinding and polishing in especially difficult-to-reach spots

			difficult-to-reach spots.
Input	W	750	710
Output	W	410	410
Speed, no load	rpm	8,500 - 28,000	2,500 - 9,000
Grinding wheel for max. Ø	mm	50	50
Collet for max. Ø	mm	8	8
Collar Ø	mm	43	43
Max. cutter diameter	mm	12	12
Cable with plug	m	4	4
Weight according to EPTA	kg	1,8	1,8

FEIN BENEFITS

- Long narrow neck allows tool to plunge a long way into workpieces (e.g. grinding inside pipes).
- User protection features include blockage monitoring, restart protection, soft start and electronic overload protection. Innovative collets with all-round flange to protect the workpiece and prevent the wrench sliding off during tool changes. POWERtronic tachoelectronics for enormous power, power reserve and exceptional speed stability under load. Removable rubber collar bearing cover.

- Motor and electronics protected against metal dust.
- Variable speed allows different tools to be used.

SUPPLIED

1 collet Ø 6 mm, Jaw spanner SW13, Jaw spanner SW17

Part number	7 223 19 60 00 0	7 223 20 60 00 0
EAN	4014586879444	4014586879451

4 DIE GRINDERS

GSZ 11-320 PERL

GSZ 11-90 PERL





Ergonomic, extremely powerful die grinder with high plunge depth for heavy-duty grinding and deburring in difficult-to-

 $\label{prop:continuous} \mbox{Ergonomic, extremely powerful die grinder for stainless steel}$ processing with high plunge depth for heavy-duty grinding and polishing.

		reach spots.	and potisining.
Input	W	1 010	1 010
Output	W	620	620
Speed, no load	rpm	9,500 - 32,500	2,900 - 9,900
Polishing disc Ø	mm		80
Grinding wheel for max. Ø	mm	45	50
Collet for max. Ø	mm	8	8
Collar Ø	mm	43	43
Max. cutter diameter	mm	12	12
Cable with plug	m	4	4
Weight according to EPTA	kg	2,1	2,2

FEIN BENEFITS

- Long narrow neck allows tool to plunge a long way into workpieces (e.g. grinding inside pipes).
 User protection features include blockage monitoring, restart protection, soft start and electronic overload protection.
- Innovative collets with all-round flange to protect the workpiece and prevent the wrench sliding off during tool changes.
- POWER tronic tachoelectronics for enormous power, power reserve and exceptional speed stability under load.
- Removable rubber collar bearing cover.

 Motor and electronics protected against metal dust.

 Variable speed allows different tools to be used.

SUPPLIED

1 collet Ø 8 mm, Jaw spanner SW13, Jaw spanner SW17

Part number	7 223 22 60 00 0	7 223 23 60 00 0
EAN	4014586880501	4014586880525

For accessories, see page 126

COLLETS FOR AGSZ 18, GSZ 4, GSZ 8, GSZ 11



With all-round flange to protect the workpiece and prevent the wrench sliding off during tool changes.

Ø	Part number
3 mm	6 32 07 130 00 0
6 mm	6 32 07 128 00 0
8 mm	6 32 07 129 00 0
1/4"	6 32 07 131 00 0



COLLETS INOX

Stainless steel model, with all-round flange to protect the workpiece and prevent the wrench sliding off during tool

Ø	Part number
3 mm	6 32 07 132 00 0
6 mm	6 32 07 133 00 0
8 mm	6 32 07 134 00 0
1/4"	6 32 07 135 00 0



⁺ suitability ++ optimal suitability • included

SANDERS

WPO 14-25 E



SUPPLIED

1 anti-vibration handle

For accessories, see page 130

Extremely powerful sander/polisher for cool machining of stainless steel surfaces.

Input	W	1 200
Output	W	750
Sanding pad Ø	mm	230
Speed, no load	rpm	900 - 2,500
Polishing disc Ø	mm	230
Mounting thread		M 14
Cable with plug	m	4
Weight according to EPTA	kg	2,5

Part number	7 221 49 00 23 0
EAN	4014586862729

FEIN BENEFITS

- + Extremely powerful even at low speeds thanks to mechanical gear reduction and FEIN high power
- Infinitely variable speed, ideal for sanding, satin finishing, brushing and high-gloss polishing of stainless steel
- Universal suitability as fully-functional sander, polisher and satin-finisher.
- Excellent handling
- Spindle lock.
- Right or left-handed operation.
- Restart protection.
- Soft start.
- H 07 industrial cable.
- Dustproof ball bearing.
- Carbon brushes with self cut-off function.
- Comprehensive range of accessories available.

WPO 14-25 E -**STAINLESS STEEL START SET**



SUPPLIED

1 holder, rotating, safety guard, 1 work arbour, 1 corrugated sanding fleece, 1 supporting plate with velcro adhesion section (Ø 115 mm, M14), 10 sanding fleeces with velcro (Ø 115 mm, fine), 1 elastic sanding roller (100 x 100 mm, grain 60), 1 lamella fleece cylinder (100 x 100 mm, grain 180), 2 keys, 1 anti-vibration handle, 1 plastic carrying case

For accessories, see page 130

Stainless steel starter set for standard applications in surface machining.

Input	W	1 200
Output	W	750
Sanding pad Ø	mm	230
Speed, no load	rpm	900 - 2,500
Polishing disc Ø	mm	230
Mounting thread		M 14
Cable with plug	m	4
Weight according to EPTA	kg	2,5

Part number	7 221 49 50 01 0
EAN	4014586862743

FEIN BENEFITS

- + Extremely powerful even at low speeds thanks to mechanical gear reduction and FEIN high power motor.
- Infinitely variable speed, ideal for sanding, satin finishing, brushing and high-gloss polishing of stainless steel.
- Universal suitability as fully-functional sander, polisher and satin-finisher. Excellent handling.
- Spindle lock.
- Right or left-handed operation.
- Restart protection.
- Soft start.
- H 07 industrial cable.
- Dustproof ball bearing.
- Carbon brushes with self cut-off function.
- Wide range of accessories.

RS 17-70 E



For accessories, see page 130

Pipe sander with extremely high sanding capacity for stainless steel pipes and pipe bends up to 80 mm in diameter.

Input	W	1700
Output	W	1000
Speed, no load	rpm	2,700 - 8,500
Minimum wall clearance	mm	50
Belt speed	m/sec	9 - 27
Pipes up to ∅	mm	8 - 80
Belt size	mm	20/40 x 815
Cable with plug	m	4
Weight according to EPTA	kg	4,3

Part number	7 222 75 60 00 0
EAN	4014586895864

- + Effective sanding of welded seams thanks to optimum cutting speeds of the sanding belts.
- Infinitely variable speed, ideal for sanding, satin finishing, brushing and high-gloss polishing of stainless steel.
- Flexible sanding belts optimally adapt to even narrow pipe bends, creating surfaces without awkward transitions.
- 360° peripheral sanding in just 2 steps.
- Optional guide pulleys for narrow distances from the wall.
- Restart lock.
- Dustproof ball bearing.
- Wide range of accessories.

RS 17-70 E SET



SUPPLIED

2 x 10 pcs. polishing belts, 20 x 815 mm P120/P180, 2 x 10 pcs. polishing belts, 40 x 815 mm P120/ P180, 5 fleece belts 20 x 820 mm very fine, 1 plastic carrying case

For accessories, see page 130

Pipe sander with extremely high sanding capacity for stainless steel pipes and pipe bends up to 80 mm in diameter.

Input	W	1 700
Output	W	1 000
Speed, no load	rpm	2,700 - 8,500
Minimum wall clearance	mm	50
Belt speed	m/sec	9 - 27
Pipes up to Ø	mm	8 - 80
Belt size	mm	20/40 x 815
Cable with plug	m	4
Weight according to EPTA	kg	4,3
		-

Part number	7 222 75 61 00 0
EAN	4014586895871

FEIN BENEFITS

- + Effective sanding of welded seams thanks to optimum cutting speeds of the sanding belts.
- + Infinitely variable speed, ideal for sanding, satin finishing, brushing and high-gloss polishing of stainless
- + Flexible sanding belts optimally adapt to even narrow pipe bends, creating surfaces without awkward transitions.
- 360° peripheral sanding in just 2 steps.
- Optional guide pulleys for narrow distances from the wall.
- + Restart lock.
- Dustproof ball bearing.
- Wide range of accessories.

KS 10-38 E SET



SUPPLIED

1 anti-vibration handle, Medium fleece discs, diameter 150 mm, one 3 mm thick and one 6 mm thick. Fine fleece discs, diameter 150 mm, one 3 mm thick and one 6 mm thick, Profiling stone for profiling the fleece discs, 1 plastic carrying case

For accessories, see page 130

Fillet weld grinder for difficult-to-reach spots in metal constructions.

Input	W	800
Output	W	550
Speed, no load	rpm	1,350 - 3,750
Peripheral speed	m/sec	29,5
Tool diameter	mm	150
Cable with plug	m	4
Weight according to EPTA	kg	3,2

Part number	7 221 67 60 00 0
EAN	4014586868936

FEIN BENEFITS

- + Flexible use thanks to drive head that can be swivelled without the need for tools.
- Flat design for corners, angles and difficult-to-reach spots.
- Long belt drive service life thanks to zero-maintenance tensioning system.
 Spindle brake for quick tool changes.
- Spark hood can be adjusted and removed without the need for tools.
- Electronic speed setting.
- Made in Germany quality.
- H 07 industrial cable.
- + Soft start
- + Restart protection.

BF 10-280 E



SUPPLIED

1 stepped grinding arm 3/6 mm (6 38 100 26 01 0)

For accessories, see page 130

Extremely powerful belt file for corners and edges in stainless steel machining.

Input	W	800
Output	W	550
Speed, no load	rpm	10,000 - 28,000
Belt speed	m/sec	12 - 32
Belt size	mm	520 x 3/6/20
Cable with plug	m	4
Weight according to EPTA	kg	2,1

David as such as	7 222 05 50 00 0
Part number	7 228 05 50 00 0
FAN	4014586867250

- + FEIN high-power motor for highly effective material removal and constant speed even at high loads.
- Optimum belt speeds for effective use of various grinding, fleece and polishing belts.
- Extremely easy to handle tool-free, grinding arm can be swivelled 180°, tool-free belt installation and adjustment.
- Perfect belt guidance.
- Belt widths of between 3 and 20 mm.
- Infinitely variable speed, ideal for protecting sensitive surfaces.
- Stepped and straight grinding arms for a variety of applications.
- Soft start.
- + Restart protection.
- H 07 industrial cable.
- Comprehensive range of accessories available.

4 SANDERS

BF 10-280 E START-SET Start set belt file for corners and edges in stainless steel machining.



SUPPLIED

3 grinding arms (1 each of 3/6 mm stepped, 6 mm straight, 20 mm straight), 10 grinding belts, 3 mm (grit 120), 10 grinding belts, 6 mm (grit 120), 10 grinding belts, 20 mm (grit 120), 5 fleece belts, 6 mm (medium), 1 plastic carrying case

For accessories, see page 130

Input	W	800
Output	W	550
Speed, no load	rpm	10,000 - 28,000
Belt speed	m/sec	12 - 32
Belt size	mm	520 x 3/6/20
Cable with plug	m	4
Weight according to EPTA	kg	2,1

Part number	7 228 05 51 00 0
EAN	4014586867267

FEIN BENEFITS

- + FEIN high-power motor for highly effective material removal and constant speed even at high loads.
- Extremely easy to handle tool-free, grinding arm can be swivelled 180°, tool-free belt installation and adjustment.
- + Start set with stepped and straight grinding arms for a variety of applications, ceramic grinding belts for effective machining of welded seams and fleece belts for finishing work in various widths.
- + Optimum belt speeds.
- + Perfect belt guidance.
- + Belt widths of between 3 and 20 mm.
- + Infinitely variable speed, ideal for protecting sensitive surfaces.
- + Soft start.
- + Restart protection.
- + H 07 industrial cable.
- + Comprehensive range of accessories available.

GENERAL ACCESSORIES



ANTI-VIBRATION HANDLE

M 8, vibration absorbing, to reduce the vibrations during longer jobs.

Part number 3 21 19 124 01 0



MICROFIBRE CLOTH

Fine weave quality for cleaning polishing residue. Hem-free version means no scratches and no lint

Part number 6 37 33 003 01 0

Part number

6 37 14 050 02 1



STAINLESS STEEL MASKING TAPE

To protect stainless steel surfaces from scratches when sanding. Perfect for use with grinding of mitre joints on welded stainless steel profiles. The covered side is protected by masking tape when sanding, satin-finishing or matting.

 L
 m
 Part number

 5
 6 37 33 010 01 0

5 fleece belts, 20 x 820 mm, very fine 280

ACCESSORIES FOR RS 12-70 E / RS 17-70 E

BASIC PIPE SANDER SET

GRINDING BELTS

Highly flexible sanding belts, ideal for sanding pipe bends $20\,\mathrm{x}$ 815 mm

	No. in pack	
Grain	pcs	Part number
120	10	6 37 14 050 01 5
180	10	6 37 14 051 01 4
320	10	6 37 14 052 01 7
400	10	6 37 14 053 01 1



GRINDING BELTS

Highly flexible sanding belts, ideal for sanding pipe bends $40\,\mathrm{x}\,815\,\mathrm{mm}$

	No. in pack	
Grain	pcs	Part number
120	10	6 37 14 054 01 9
180	10	6 37 14 055 01 3



FLEECE STRIPS

Very soft version for smooth surfaces, even with tight pipe bends $20 \times 815 \text{ mm}$

	No. in pack	
Grain	pcs	Part number
80	5	6 37 14 056 01 6
120	5	6 37 14 057 01 0
280	5	6 37 14 058 01 8



POLISHING BELTS

 $20\,x\,815$ mm, very soft version, for smooth mirror polish even with tight pipe bends

Part number 6 37 26 010 01 8



CERAMIC SANDING BELTS

Maximum material removal and very long service life. Also suitable for removing fine welded seams

Cleaning off dirt, removing scratches and achieving a perfect

satin finish. Consisting of: 2 x 10 grinding belts, 20 x 815 mm,

P 120/P180; 2 x 10 grinding belts, 40 x 815 mm, P120/P180;

	Dimensions	No. in pack		
Grain	mm	pcs	Part number	
80	20 x 815	10	6 37 14 130 01 0	
80	40 x 815	10	6 37 14 131 01 0	



ROTATING ROLLER

For narrow spaces (distance from wall 50 mm)

Part number
3 13 35 017 01 1

ACCESSORIES FOR BF 10-280 E



STRAIGHT GRINDING ARM

Belt width	
mm	Part number
6	6 38 10 027 01 0
20	6 38 10 030 01 0



CERAMIC GRINDING BELT

Maximum material removal and very long service life. Also suitable for removing fine welded seams Pack of 10, 520 mm long.

	Width	
Grain	mm	Part number
80	3	6 37 14 061 01 0
120	3	6 37 14 062 01 0
180	3	6 37 14 063 01 0
80	6	6 37 14 068 01 0
120	6	6 37 14 069 01 0
180	6	6 37 14 070 01 0
80	20	6 37 14 089 01 0
120	20	6 37 14 090 01 0
180	20	6 37 14 091 01 0



FLEECE BELT

Soft version for smooth surfaces. Pack of 5, 520 mm long.

Width		
mm	Model	Part number
6	coarse	6 37 14 114 01 0
6	medium	6 37 14 115 01 0
6	fine	6 37 14 116 01 0
20	coarse	6 37 14 123 01 0
20	medium	6 37 14 124 01 0
20	fine	6 37 14 125 01 0



POLISHING BELT

Soft version, for a smooth mirror polish in conjunction with polishing pastes.
Pack of 3, 520 mm long.

mm	Part number
6	6 37 26 016 01 0
20	6 37 26 019 01 0

ACCESSORIES FOR CG 17-125 INOX



QUICK-CLAMPING NUT

M14, to change discs without need for tool, low height of just 8 mm

Part number 6 38 02 191 01 0



WHEEL GUARD

for serrated and roughing discs

3	
nm	Part number
.25	3 18 10 300 00 0



SAFETY HOOD FOR CUTTING WORK

for safe working with cutting wheels





INNER FLANGE

Part number 6 38 01 182 01 0



THREADED FLANGE

M 14, for flexible grinding/cutting discs, fan-pattern grinding wheels and round brush

Part number 6 38 02 052 00 0



THREADED FLANGE

M 14, for elastic backing pad and for twisted steel wire brush

Part number 6 38 01 154 00 7



ELASTIC BACKING PAD

with flange M 14, for fibre sanding sheets Ø 125 mm

 Ø mm
 Part number

 125
 6 38 06 087 01 3



GRINDING DISC

For coarse sanding and machining a welded seam with a good service life. Can be used universally in steel and stainless steel. Stepped shape, inner diameter of 22.23 mm, maximum speed of 12 250 rpm, maximum working speed of 80 m/s.

Ø	Thickness	No. in pack		
mm	mm	pcs	Part number	
125	6	10	6 37 03 005 01 0	



CUTTING DISC

Perfect for dividing thin sheet metal, pipes and profiles. Precise and rapid cut with minimum effort and excellent service life. No rework or thermal discolouration on the workpiece. Can be used universally in steel and stainless steel. Straight shape, inner diameter of 22.23 mm, maximum speed of 12 250 rpm, maximum working speed of 80 m/s.

Ø	Thickness	No. in pack	
mm	mm	pcs	Part number
125	1	25	6 37 09 013 01 0

4 SANDERS



CUTTING DISC

For dividing sheet metal, pipes and profiles with good dividing speed and good service life. Can be used universally in steel and stainless steel. Stepped shape, inner diameter of 22.23 mm, maximum speed of 12 250 rpm, maximum working speed of 80 m/s

Ø	Thickness	No. in pack		
mm	mm	pcs	Part number	
125	2,5	25	6 37 09 014 01 0	



FLAP WHEEL

Abrasive material made from zirconium corundum for excellent surface results with good sanding capacity, offering simple handling and few vibrations. Ideal for machining edges. Long service life with consistent quality of work. Can be used universally in steel and stainless steel. Conical shape, inner diameter of 22.23 mm, maximum speed of 12 250 rpm, maximum working speed of 80 m/s.

	Ø	No. in pack	
Grain	mm	pcs	Part number
40	125	10	6 37 30 022 01 0
60	125	10	6 37 30 023 01 0
80	125	10	6 37 30 024 01 0



FIBRE SANDING DISC

High-performance abrasive material made from zirconium corundum with a very good sanding capacity and service life. Can be used universally in steel and stainless steel.

	Ø	No. in pack	
Grain	mm	pcs	Part number
36	125	25	6 37 17 301 01 0
60	125	25	6 37 17 302 01 0
80	125	25	6 37 17 303 01 0



BACKING PAD

M 14, \varnothing 125 mm, with Velcro attachment, for sanding sheets with Velcro rapid attachment

Ø	
mm	Part number
115	6 38 06 168 01 2



BACKING PAD

with Velcro attachment, for working with sanding fleece, M 14

Ø	
mm	Part number
115	6 38 06 172 01 0



FLEECE SANDING DISCS

 \emptyset 115 mm, with Velcro attachment, for use with support plate 6 38 06 172 01 0

M 1.1	No. in pack	D
Model	pcs	Part number
coarse	10	6 37 32 001 01 8
medium	10	6 37 32 002 01 1
fine	10	6 37 32 003 01 5



COOL SANDING PAD

Rear-ventilated backing pad, ideal for Pyramix sanding discs

Ø	
mm	Part number
115	6 38 06 193 01 0



COOL SANDING PAD

Rear-ventilated backing pad, ideal for Pyramix sanding discs for use when the outer edge of the sanding discs has been removed.

Ø	
mm	Part number
75	6 38 06 196 01 0



SANDING SHEETS

Ø 115 mm, for removing very deep scratches and fine welded

	No. in pack	
Grain	pcs	Part number
80	25	6 37 28 135 01 0



PYRAMIX SANDING SHEET

The Pyramix hook and loop sanding disc features a new perforation pattern which means it can now also be used after the first edge has been worn away. \emptyset 115 mm. For removing deep scratches

	No. in pack	
Grain	pcs	Part number
280	5	6 37 17 239 01 0
280	25	6 37 17 239 02 0



PYRAMIX SANDING SHEET

The Pyramix hook and loop sanding disc features a new perforation pattern which means it can now also be used after the first edge has been worn away. Ø 115 mm. For removing minor scratches, creating sanding pattern, reducing roughness depth

	No. in pack	
Grain	pcs	Part number
400	5	6 37 17 240 01 0
400	25	6 37 17 240 02 0



PYRAMIX SANDING SHEET

The Pyramix hook and loop sanding disc features a new perforation pattern which means it can now also be used after the first edge has been worn away. Ø 115 mm. For removing very minor scratches, creating sanding pattern, reducing roughness depth

	No. in pack	
Grain	pcs	Part number
800	5	6 37 17 241 01 0
800	25	6 37 17 241 02 0



PYRAMIX SANDING SHEET

The Pyramix hook and loop sanding disc features a new perforation pattern which means it can now also be used after the first edge has been worn away. Ø 115 mm. Reducing roughness depth, optimum preconditions for subsequent polishing

	No. in pack	
Grain	pcs	Part number
1 400	5	6 37 17 242 01 0
1 400	25	6 37 17 242 02 0



FLAP WHEEL

diameter 125 mm, M 14

	Width	
Grain	mm	Part number
120	20	6 37 21 052 01 0



FINISHING DISC

Ø 125 mm, for final finish

Part number 6 37 32 005 01 0



FLAP WHEEL

Ideal for stainless steel processing and removing welded seams and finishing in one step. A combination of rapid material removal and perfect surface quality.

Ø		No. in pack	
mm	Model	pcs	Part number
125	soft	5	6 37 30 019 01 0
125	medium	5	6 37 30 021 01 0
125	coarse	5	6 37 30 020 01 0



STAINLESS STEEL SET – PREPARING TO POLISH SURFACES / PIPES / PROFILES

Quickly and effectively removes scratches; optimum preparation for polishing with matched sanding pattern; when preparing for polishing: effective material removal in little time. Consisting of: 5 Pyramix sanding sheets, grit 280 (6 37 17 239 01 0), 5 Pyramix sanding sheets, grit 400 (6 37 17 240 01 0), 5 sanding sheets, grit 800 (6 37 17 241 01 0), 5 Pyramix sanding sheets, grit 1400 (6 37 17 242 01 0), 1 cooling backing pad, Ø 75 mm (6 38 06 196 01 0), 25 sanding sheets, grit 80 (6 37 28 135 01 0), 1 cooling backing pad, Ø 115 mm (6 38 06 193 01 0)

Part number 6 38 06 193 04 0



FELT SERRATED DISC

For polishing and pre-polishing stainless steel. Because of the lamella, the felt doesn't "burn" and polishing without streaks is possible. Only use with polishing paste (pre-polishing = pre-polishing paste, high-gloss polishing = colouring paste).

Ø mm	Model	Part number
125	soft	6 37 23 037 01 0
125	medium	6 37 23 038 01 0

ACCESSORIES FOR KS 10-38 E



FLEECE DISC

Very high sanding capacity for sanding, descaling and satin-finishing fillet welds.

Ø	Thickness		
mm	mm	Model	Part number
150	7	very course	6 37 34 008 01 0



FLEECE DISC

With a high sanding capacity for sanding, descaling and satin-finishing fillet welds.

Ø	Thickness		
mm	mm	Model	Part number
150	3	coarse	6 37 34 001 01 0
150	6	coarse	6 37 34 002 01 0



FLEECE DISC

For sanding, levelling, descaling and fine satin-finishing of fillet welds. Removes scratches on profiles and surfaces with ease.

Ø	Thickness		
mm	mm	Model	Part number
150	3	medium	6 37 34 003 01 0
150	6	hard	6 37 34 004 01 0



FLEECE DISC

Removes tarnishing and minor scratches, ideal for preparing to polish fillet welds.

Ø	Thickness		
mm	mm	Model	Part number
150	3	fine	6 37 34 005 01 0
150	6	fine	6 37 34 006 01 0



FLEECE DISC

For pre-polishing surfaces of fillet welds. Quickly removes tarnishing without wearing away the welded seam.

Ø	Thickness		
mm	mm	Model	Part number
150	6	very fine	6 37 34 007 01 0



FELT DISC

For polishing fillet welds to a mirror polish in conjunction with FEIN polishing paste.

Ø	Thickness	
mm	mm	Part number
150	6	6 37 18 011 01 0



PROFILING STONE

For sanding the fleece discs for even fillet weld profiles.

Part number
6 37 19 011 01 0

ACCESSORY RS 10-70 E



GRINDING BELTS

Highly flexible sanding belts, ideal for sanding pipe bends No. in pack 10, 30×533 mm.

Grain	Part number
80	6 37 14 136 01 0
120	6 37 14 137 01 0
180	6 37 14 138 01 0
320	6 37 14 139 01 0
400	6 37 14 140 01 0



FLEECE STRIPS

Very soft version for smooth surfaces, even with tight pipe hends

No. in pack 5, 30 x 533 mm.

Model	Part number
fine	6 37 14 143 01 0



POLISHING BELTS

Very soft version for smooth mirror polish, even with tight pipe bends.

No. in pack 3, 30 x 533 mm.

Part number
6 37 14 144 01 0

4 SANDERS

ACCESSORIES FOR ROT 14-200 E



PROTECT.SUCTION HOOD

Part number
3 18 10 264 01 0

PROTECT.SUCTION HOOD

Part number 3 18 10 240 01 4



CONNECTING PIECE

Universal device to connect power tools and accessories with dust extraction to vacuum cleaner. Flexible rubber sleeve, length 70 mm, inner diameter 31.5 mm.

Part number 3 13 22 771 00 9



SANDING SHEETS

perforated, \oslash 150 mm, with Velcro rapid attachment Application: Wood, metal, car bodies, welds. Quality: fully synthetic-resin bonded, corundum. Features: high sanding capacity.

	No. in pack		
Grain	pcs	Part number	
60	50	6 37 28 022 01 7	



SANDING PAD

Ø 150 mm, with holes, with hook and loop fastener

Model	Part number
hard	6 38 06 116 02 1
extra soft	6 38 06 166 02 6



SANDING PAD

Ø 200 mm, with holes, with hook and loop fastener

Model	Part number
hard	6 38 06 102 02 3
medium	6 38 06 095 02 1
extra soft	6 38 06 118 02 3



LAMBSKIN

with Velcro rapid attachment.

mm	Part number
150	6 37 23 009 00 4
200	6 37 23 010 00 6

ACCESSORIES FOR MSF 636-1

HOOK AND LOOP FASTENER

Ø 150 mm

Ø	
mm	Part number
150	3 14 26 030 00 5

SANDING PAD

Ø 115 mm, without holes, with hook and loop fastener, hard

Part number
6 38 06 167 02 0



SANDING SHEETS

 $\ensuremath{\mathcal{O}}$ 115 mm, for removing very deep scratches and fine welded seams

	No. in pack		
Grain	pcs	Part number	
80	50	6 37 28 096 01 9	



SANDING PAD

Ø 125 mm, perforated, with hook and loop fastening

Connector thread		
backing pad	Model	Part number
5/16"-24 UNF	hard	6 38 06 103 02 7
5/16"-24 UNF	medium	6 38 06 088 02 7
5/16"-24 UNF	soft	6 38 06 117 02 5



SANDING PAD

Ø 150 mm, with holes, with hook and loop fastener

Connector thread backing pad	Model	Part number
5/16"-24 UNF	hard	6 38 06 101 02 0
5/16"-24 UNF	medium	6 38 06 090 02 3
5/16"-24 UNF	soft	6 38 06 114 02 4



ECCENTRIC HEAD

Ø 150 mm

Part number
3 12 07 103 01 3



SANDING SHEETS

perforated, Ø 150 mm, with Velcro rapid attachment Application: Metal, car bodies, soldered points, welds, fibreglass. Quality: high-performance emery canvas, fully synthetic-resin bonded, corundum. Features: highly stable, high sanding capacity.

	No. in pack	
Grain	pcs	Part number
40	50	6 37 28 009 01 4
60	50	6 37 28 010 01 6
80	50	6 37 28 056 01 3
100	50	6 37 28 054 01 6



SANDING SHEETS

perforated, Ø 150 mm, with Velcro rapid attachment Application: wood, paint, automotive paints, filler, fibreglass, plastics.Quality: fully synthetic-resin bonded, corundum. Feature: greatly reduces glazing, flexible.

Grain	No. in pack	
	pcs	Part number
80	50	6 37 28 074 01 4
120	50	6 37 28 084 01 3
150	50	6 37 28 012 01 8
180	50	6 37 28 013 01 2
240	50	6 37 28 015 01 4



SANDING SHEETS

perforated, \oslash 150 mm, with Velcro rapid attachment Application: Wood, metal, car bodies, welds. Quality: fully synthetic-resin bonded, light bond, corundum. Features: high sanding capacity.

	No. in pack	
Grain	pcs	Part number
60	50	6 37 28 073 01 6



LAMBSKIN with Velcro rapid attachment.



ELASTIC SANDING CYLINDER Bore 19 mm 100 x 50 mm

V				
mm	Part number	Grain	Model	Part number
125	6 37 23 008 00 0	60	medium	6 37 21 054 01 0
150	6 37 23 009 00 4	180	fine	6 37 21 055 01 0

ACCESSORIES FOR WPO 14-25 E



STANDARD STAINLESS STEEL SET FOR SURFACES

Set for standard applications in surface machining: cleaning off dirt with corrugated fleece, removing tarnishing and achieving a high-quality satin finish. Consisting of: 1 elastic sanding cylinder, grit 60 (6 37 21 006 01 2), 1 lamella fleece cylinder (6 37 21 009 01 8), 1 corrugated sanding fleece (6 37 23 021 01 3), 1 fine fleece sanding disc, pack of 10 (6 37 32 003 01 5), 1 support plate (6 38 06 172 01 0), 1 work arbour (6 38 03 066 02 4), 1 pin-type face spanner (6 29 10 022 00 2), 1 open-ended spanner 19 x 22 (6 29 04 003 00 0)

Part number 6 37 21 006 04 0



STAINLESS STEEL SET FOR GRINDING SURFACES

Effective material removal for surfaces. Consisting of: 1 expansion cylinder (6 38 06 192 01 0), 5 sanding sleeves, grit 60 (6 37 14 132 01 0), 5 sanding sleeves, grit 80 (6 37 14 133 01 0), 5 sanding sleeves, grit 120 (6 37 14 134 01 0)

Part number 6 38 06 192 02 0



STAINLESS STEEL SET FOR SATIN-FINISHING SURFACES

Perfect smooth satin finish. Very low build-up of heat during machining. Consisting of: 1 medium elastic sanding cylinder, grit 60 (6 37 21 006 01 2), 1 fine elastic sanding cylinder, grit 180 (6 37 21 007 01 6), 1 fine sine fleece sanding cylinder, grit 180 (6 37 21 051 01 0)

Part number 6 37 21 050 02 0



STANDARD STAINLESS STEEL SET FOR PIPES

Set for standard applications in the machining of straight pipes. Cleaning off dirt, removing tarnishing and achieving a high-quality satin finish. Consisting of: 1 grinding belt roller (6 38 06 181 01 6), 1 grinding belt, grit 60, pack of 10 (6 37 14 044 01 0), 1 grinding belt, grit 120, pack of 10 (6 37 14 045 01 4), 1 medium fleece belt (6 37 14 048 01 9), 1 fine fleece belt (6 37 14 049 01 3), 1 adhesive strip (6 38 09 004 01 9)

Part number 6 38 06 181 03 0



STAINLESS STEEL SET - SATIN-FINISHING PROFILES

Satin-finishing of profiles for a perfect sanding pattern. Consisting of: 1 elastic cylinder, grit 60, medium (6 37 21 054 01 0), 1 elastic cylinder, grit 180, fine (6 37 21 055 01 0), 1 sine fleece sanding cylinder, fine (6 37 21 056 01 0), 1 work arbour (6 38 03 071 02 0)

Part number 6 37 21 054 02 0



ELASTIC SANDING CYLINDER Bore 19 mm

100 x 100 mm

Grain	Model	Part number
60	medium	6 37 21 006 01 2
180	fine	6 37 21 007 01 6



SINE FLEECE SANDING CYLINDER

Bore 19 mm

Ø 100 x 50 mm, with sine wave, for smooth satin finish

Grain	Model	Part number
180	fine	6 37 21 056 01 0



SINE FLEECE SANDING CYLINDER

Bore 19 mm

Ø 100 x 100 mm, with sine wave, for smooth satin finish

Grain	Model	Part number
180	fine	6 37 21 051 01 0



FLAP WHEEL

diameter 150 mm, bore 14 mm For remedying minor mistakes and scratches

Part number
6 37 21 003 01 7



FLAP WHEEL

diameter 150 mm, bore 14 mm for medium brush applications

Part number 6 37 21 004 01 5



FLAP WHEEL

diameter 150 mm, bore 14 mm For for fine brush strokes, satin finish.

Part number 6 37 21 005 01 9



LAMELLA FLEECE CYLINDER 100 x 100 mm

100 x 100 mm

Part number 6 37 21 015 01 0



LAMELLA FLEECE CYLINDER diameter 100 x 100 mm, bore 19 mm

For medium satin finish

Grain	Model	Part number
100	medium	6 37 21 008 01 4

SANDERS



LAMELLA FLEECE CYLINDER

diameter 100 x 100 mm, bore 19 mm For fine satin finish

Grain	Model	Part number
180	fine	6 37 21 009 01 8



LAMELLA FLEECE CYLINDER

diameter 100 x 100 mm, bore 19 mm For very fine satin finish

Grain	Model	Part number
280	very fine	6 37 21 010 01 0



FELT LAMELLA ROLLER

For polishing and pre-polishing stainless steel. Because of the lamella, the felt doesn't "burn" and polishing without streaks is possible. Only use with polishing paste (pre-polishing = pre-polishing paste, high-gloss polishing = colouring paste).

Model	Part number
soft	6 37 21 057 01 0
medium	6 37 21 058 01 0



SANDING FLEECE

with corrugated folds, width approx. 30 mm, bore hole 14 mm, for light finishing work, derusting, polishing, and decorative work

Ø	
mm	Part number
150	6 37 23 021 01 3
200	6 37 23 022 01 6



FLEECE SANDING DISCS

Ø 115 mm, with Velcro attachment, for use with support plate 6 38 06 172 01 0

	No. in pack	
Model	pcs	Part number
coarse	10	6 37 32 001 01 8
medium	10	6 37 32 002 01 1
fine	10	6 37 32 003 01 5



BACKING PAD

with Velcro attachment, for working with sanding fleece, M 14

Ø	
mm	Part number
115	6 38 06 172 01 0



SANDING STRIP ROLL

Bore 19 mm 100 x 70 mm

Part numbe
6 38 06 181 01 6



GRINDING BELTS

600 x 30 mm

	No. in pack	
Grain	pcs	Part number
60	10	6 37 14 044 01 0
120	10	6 37 14 045 01 4
240	10	6 37 14 046 01 7

ADHESIVE STRIP

For re-fastening grinding belts in closed pipe systems, 50 m

Part number
6 38 09 004 01 9



FLEECE STRIPS

With button closure for refastening, ideal for closed pipe systems, 600 x 30 mm

Model	Part number
coarse	6 37 14 047 01 1
medium	6 37 14 048 01 9
fine	6 37 14 049 01 3



POLISHING RINGS, SISAL, CLOTH

- fine finishing/brushing and levelling of non-ferrous metals following preliminary sanding with grain 240-280 using polishing paste.
- fine finishing/brushing and levelling of iron/steel, and stainless steel following preliminary sanding with grain 280-320 using polishing paste.
- matt-shining/brushing non-ferrous metals, iron/steel, and stainless steel using polishing paste.
 Preliminary polishing of iron/steel and stainless steel with
- preliminary polishing paste width about 30 mm, 14 mm bore.

mm	Part number
150	6 37 23 011 01 4
200	6 37 23 012 01 7



POLISHING RINGS, HARD CLOTH

Width approx. 15 mm, bore hole 14 mm, for preliminary polishing and polishing of non-ferrous metals, iron/steel, stainless steel with preliminary polishing paste.

Ø	
mm	Part number
150	6 37 23 013 01 1
200	6 37 23 015 01 3



POLISHING RINGS, SOFT CLOTH

Width approx. 15 mm, bore hole 14 mm, for high-gloss polishing of non-ferrous metals, iron/steel, stainless steel and chrome with final polishing paste.

Ø	
mm	Part number
150	6 37 23 014 01 9
200	6 37 23 016 01 6

POLISHING RINGS, FLEECE, EXTRA SOFT

Width approx. 15 mm, bore hole 14 mm, for final polishing of non-ferrous metals, iron/steel, stainless steel and many plastics with final polishing paste.

Ø	
mm	Part number
150	6 37 23 019 01 2
200	6 37 23 020 01 4



POLISHING WHEEL

diameter 150 mm, width 60 mm, elastic, bore 14 mm for brush polishing, grain 16 (coarse), soft, "green"

Part number
6 37 13 013 01 8



POLISHING WHEEL

diameter 150 mm, width 60 mm, elastic, bore 14 mm for delicate surfaces, grit 24 (medium), soft, "blue"



Part number

Part number

Part number 6 37 33 006 01 0

Part number 6 38 03 027 03 8

6 37 21 001 00 1

WHEEL ARBOR

With wheel flange M 14, for lamella sanding discs, buffing and polishing discs, holding range $15-50\,$ mm, tool mounting diameter 14 mm

Part number

6 38 03 066 02 4

6 37 13 015 01 0

POLISHING WHEEL

diameter 150 mm, width 60 mm, elastic, bore 14 mm for fine polishing, grit 46, soft, "brown"



SAFETY GUARD as hand guard

> Part number 3 02 29 216 00 5

Part number 6 37 13 016 01 3



mm

FLAP WHEEL

Width 50 mm, for polishing rust-resistant steel, bore 14 mm



EXPANSION ROLLER

Bore 19 mm \emptyset 100 x 100 mm, for vibration-free, secure holding of sanding sleeves



Part number

6 38 06 192 01 0



HOLDER

for side handle, 360° rotatable

SANDING SLEEVE

For removing small welded seams and very deep scratches and mill scale



Grain	pcs	Part number
60	5	6 37 14 132 01 0



WHEEL ARBOR

WHEEL ARBOR

15-35 mm

For satin-finishing tools (cylinders and rollers), tool holder Ø 19 mm

with clamping flange M 14, for polishing rings, clamping range

Length	
mm	Part number
50	6 38 03 071 02 0
100	6 38 03 067 02 8



SANDING SLEEVE

For removing deep scratches



	No. in pack	
Grain	pcs	Part number
30	5	6 37 14 133 01 0



SANDING SLEEVE

For removing scratches, stage prior to satin-finishing



	No. in pack	
Grain	pcs	Part number
120	5	6 37 14 134 01 0



PYRAMIX SANDING SLEEVE

For removing scratches, stage prior to satin-finishing

	No. in pack	
Grain	pcs	Part number
280	5	6 37 14 145 01 0
400	5	6 37 14 146 01 0
600	5	6 37 14 147 01 0
1 400	5	6 37 14 148 01 0

4 POLISHERS



⁺ suitability

⁺⁺ optimal suitability

included

WPO 14-15 E



SUPPLIED

1 Grip hood, 1 additional handle

For accessories, see page 142

Extremely powerful angle polisher for vehicle and boat repairs.

Input	W	1 200
Output	W	750
Speed, no load	rpm	500 - 1,500
Polishing disc Ø	mm	230
Mounting thread		M 14
Cable with plug	m	4
Weight according to EPTA	kg	2,5

Part number	7 221 48 00 23 0
EAN	4014586862699

FEIN BENEFITS

- Ideal speed range with infinitely variable speed control for professional surface processing on vehicles and
- Maximum speed stability at any load over the full setting range thanks to mechanical gear reduction in conjunction with the FEIN high-power motor.
- Special system accessories for the efficient refurbishment of used car paintwork, new car paintwork and highly scratch-resistant paints, and for cleaning, sanding and polishing boat surfaces and gelcoat layers.
- Convenient speed adjustment.
- Does not heat up in continuous use.
- Handle cover for excellent ergonomics.
- Spindle lock.
- Right or left-handed operation.
- Restart protection.
- Soft start.
- Carbon brushes with self cut-off function.
- Can be converted to rotary sander with extractor hood and backing pad.

WPO 14-15 E SET



SUPPLIED

1 anti-vibration handle, 1 Grip hood. 1 Support plate with Velcro attachment, Ø 150 mm, 1 Polishing sponge, Ø 150 mm, medium

For accessories, see page 142

Extremely powerful angle polisher for vehicle and boat repairs.

W	1 200
W	750
rpm	500 - 1,500
mm	230
	M 14
m	4
kg	2,5
	W rpm mm

Part number	7 221 48 51 01 0
EAN	4014586867069

FEIN BENEFITS

- + Ideal speed range with infinitely variable speed control for professional surface processing on vehicles and hoats
- + Maximum speed stability at any load over the full setting range thanks to mechanical gear reduction in conjunction with the FEIN high-power motor.
- Special system accessories for the efficient refurbishment of used car paintwork, new car paintwork and highly scratch-resistant paints, and for cleaning, sanding and polishing boat surfaces and gelcoat layers.
- Convenient speed adjustment.
- Does not heat up in continuous use.
- Handle cover for excellent ergonomics.
- Spindle lock.
- Right or left-handed operation.
- Restart protection.
- Soft start.
- Carbon brushes with self cut-off function.
- Can be converted to rotary sander with extractor hood and backing pad.
- Tool also available without accessories (7 221 48).

WPO 14-15 E MARINE POLISHING SET



SUPPLIED

1 anti-vibration handle, 1 Grip hood, 1 support plate with hook and loop fastening, Ø 170 mm, 1 polishing pad, Ø 195 mm, 1 plastic carrying case

For accessories, see page 142

Polishing set for boat repairs.

Input	W	1 200
Output	W	750
Speed, no load	rpm	500 - 1,500
Polishing disc Ø	mm	230
Mounting thread		M 14
Cable with plug	m	4
Weight according to EPTA	kg	2,5

Part number	7 221 48 60 00 0
EAN	4014586872216

- + Ideal speed range with infinitely variable speed control for professional surface machining on boats.
- Maximum speed stability at any load over the full setting range thanks to mechanical gear reduction in conjunction with the FEIN high-power motor.
- Special system accessories for the efficient refurbishment of used car paintwork, new car paintwork and highly scratch-resistant paints, and for cleaning, sanding and polishing boat surfaces and gelcoat layers.
- Convenient speed adjustment.
- Does not heat up in continuous use.
- Handle cover for excellent ergonomics. Spindle lock.
- Right or left-handed operation.
- Restart protection.
- Soft start.
- Carbon brushes with self cut-off function.
- Can be converted to rotary sander with extractor hood and backing pad.
- Wide range of accessories.
- Tool also available without accessories (7 221 48).

4 POLISHERS

WPO 14-15 E MARINE POLISHING SET



SUPPLIED

1 anti-vibration handle, 1 Grip hood, 1 support plate with hook and loop fastening, Ø 170 mm, 1 polishing pad, Ø 195 mm, 1 lamb's wool, dome shape, Ø 235 mm, 1 Extractor hood, 1 sanding pad Ø 150 mm, 2 sanding fleeces for antifoul, 1 bristle fleece, 2 of each sanding sheet, Ø 150 mm, perforated, (G 80, 150, 180), 1 plastic carrying case

For accessories, see page 142

Polishing set for boat repairs.

Input	W	1 200
Output	W	750
Speed, no load	rpm	500 - 1,500
Polishing disc Ø	mm	230
Mounting thread		M 14
Cable with plug	m	4
Weight according to EPTA	kg	2,5

Part number	7 221 48 50 01 0
EAN	4014586862712

FEIN BENEFITS

- Ideal speed range with infinitely variable speed control for professional surface machining on boats.
- Maximum speed stability at any load over the full setting range thanks to mechanical gear reduction in conjunction with the FEIN high-power motor.
- Special system accessories for the efficient refurbishment of used car paintwork, new car paintwork and highly scratch-resistant paints, and for cleaning, sanding and polishing boat surfaces and gelcoat layers.
- Convenient speed adjustment.
- Does not heat up in continuous use.
- Handle cover for excellent ergonomics.
- Spindle lock.
- Right or left-handed operation.
- Restart protection.
- Soft start.
- Carbon brushes with self cut-off function.
- Can be converted to rotary sander with extractor hood and backing pad.
- Wide range of accessories.
- Tool also available without accessories (7 221 48).

WPO 14-25 E



SUPPLIED

1 anti-vibration handle, 1 Grip hood, 1 Support plate with Velcro attachment, Ø 150 mm, 1 Polishing sponge, Ø 150 mm, medium

For accessories, see page 142

Extremely powerful angle polisher for refurbishing paintwork.

Input	W	1 200
Output	W	750
Speed, no load	rpm	900 - 2,500
Polishing disc Ø	mm	230
Mounting thread		M 14
Cable with plug	m	4
Weight according to EPTA	kg	2,5

Part number	7 221 49 51 01 0
EAN	4014586867113

- Ideal speed range with infinitely variable speed control for professional surface processing on vehicles and boats.
- Special system accessories for the efficient refurbishment of used car paintwork, new car paintwork and highly scratch-resistant paints, and for cleaning, sanding and polishing boat surfaces and gelcoat layers.
- Maximum speed stability at any load over the full setting range thanks to mechanical gear reduction in conjunction with the FEIN high-power motor. Excellent handling.
- Spindle lock.
- Right or left-handed operation.
- Restart protection.
 - Soft start.
- H 07 industrial cable.
- Dustproof ball bearing.
- Carbon brushes with self cut-off function.
- Comprehensive range of accessories available.
- Tool also available without accessories (7 221 49).

WPO 10-25 E



SUPPLIED

1 additional handle, 1 Grip hood

For accessories, see page 142

Powerful easy-to-use angle polisher for refurbishing paintwork.

Input	W	800
Output	W	550
Speed, no load	rpm	900 - 2,500
Polishing disc Ø	mm	150
Mounting thread		M 14
Cable with plug	m	4
Weight according to EPTA	kg	2,2

Part number	7 221 63 00 23 0
EAN	4014586866055

FEIN BENEFITS

- + Ideal speed range with infinitely variable speed control for professional surface machining on vehicles.
- + Maximum speed stability at any load over the full setting range thanks to mechanical gear reduction in conjunction with the FEIN high-power motor.
- + Special system accessories for effective refurbishing of new and used cars and highly scratch-resistant paintwork.
 Convenient speed adjustment.
- Does not heat up in continuous use.
- Handle cover for excellent ergonomics.
- Spindle lock.
- Right or left-handed operation. Restart protection.
- Soft start.
- + Carbon brushes with self cut-off function.

WPO 10-25 E SET



SUPPLIED

1 anti-vibration handle, 1 Grip hood, 1 Support plate with Velcro attachment, Ø 150 mm, 1 Polishing sponge, Ø 150 mm, medium

For accessories, see page 142

Powerful easy-to-use angle polisher for refurbishing paintwork.

Input	W	800
Output	W	550
Speed, no load	rpm	900 - 2,500
Polishing disc Ø	mm	150
Mounting thread		M 14
Cable with plug	m	4
Weight according to EPTA	kg	2,2

Part number	7 221 63 51 01 0
EAN	4014586867199

- Ideal speed range with infinitely variable speed control for professional surface machining on vehicles.
- + Maximum speed stability at any load over the full setting range thanks to mechanical gear reduction in conjunction with the FEIN high-power motor. Special system accessories for effective refurbishing
- of new and used cars and highly scratch-resistant paintwork.
- Convenient speed adjustment.
- Does not heat up in continuous use.
- Handle cover for excellent ergonomics.
- Spindle lock.
- Right or left-handed operation.
- Restart protection.
- Soft start.
- Carbon brushes with self cut-off function.
- + Tool also available without accessories (7 221 63).

4 POLISHERS

ACCESSORIES FOR WPO 10-25 E, WPO 14-15 E, WPO 14-15 XE, WPO 14-25 E



MICROFIBRE CLOTH

Fine weave quality for cleaning polishing residue. Hem-free version means no scratches and no lint

> Part number 6 37 33 003 01 0



SANDING DISC

Micro-fine self-adhesive sandpaper, 2800 grain, for treating lacquer faults such as lacquer inclusions. 1 sheet of 53 sanding discs, Ø 30 mm. Fits on hand sanding block 6 37 33 002 01 0

> Part number 6 37 17 221 01 0

> > 6 37 33 002 01 0



HUMIDIFICATION SPONGE

Easy-to-use foam cube for hygienic moisturizing the sanding discs.

> Part number 6 37 33 001 01 0



SANDING BLOCK

Easy-to-use sanding block for holding self-adhesive sanding discs on both sides.

Part number



BACKING PAD

with Velcro attachment, M 14

Ø	
mm	Part number
80	6 38 06 179 01 5
125	6 38 06 169 01 6
130	6 38 06 178 01 1
150	6 38 06 170 01 8



BACKING PAD

for lamb's fleece with tensioning cord, rubber coated, M 14

Ø	
mm	Part number
120	6 38 06 012 00 8



POLISHING SPONGE

For polishing painted surfaces. Various hardness grades: soft for new paintwork, medium for slightly weathered paintwork and applying wax, hard for severely weathered paintwork. Quick hook and loop fastening, height 40 mm.

Model	Part number
soft	6 37 23 024 01 8
hard	6 37 23 023 01 0
medium	6 37 23 017 01 0
	hard



POLISHING SPONGE ORANGE 150 MM

Polishing sponge with fine pores, medium hard for new and old lacquers Ø 150 mm

> Part number 6 37 23 028 01 0



WAFFLED SPONGE

Extremely fine and soft polishing sponge for removing holograms on dark lacquers. Ø 150 mm

> Part number 6 37 23 029 01 0



LAMBSKIN

with tensioning cord





LAMBSKIN

with Velcro rapid attachment.



Ø	
mm	Part number
125	6 37 23 008 00 0
150	6 37 23 009 00 4

ACCESSORIES FOR WPO 14-15 E



mm

170

BACKING PAD

with Velcro attachment, M 14



POLISHING SPONGE

Ø 195 mm for backing pads with a Ø of 170 mm, 6 38 06 187 01 0, M 14 with hook and loop fastening system. Recommended working speed 500-1 000 rpm.

Part number

6 38 06 187 01 0

0	
mm	Part number
195	6 37 23 034 01 0



Bristle fleece for cleaning or polishing boat hulls and decks, with a \varnothing of 195 mm for backing pads with a \varnothing of 170 mm, 6 38 06 187 01 0, M 14 with hook and loop fastening system. For fibreglass anti-slip structures. Recommended working speed: approx. 500 rpm.

0	
mm	Part number
195	6 37 23 033 01 0



LAMB'S WOOL, DOME SHAPE

Diameter approx. 230 mm for backing pads with a \emptyset of 170 mm, 6 38 06 187 01 0, M 14 with hook and loop fastening system. Recommended working speed 500-1,200 rpm. Quality TOPWOOL, fleece polishing wheel. Lamb's wool/synthetic blend, washable.

0	
mm	Part number
230	6 37 23 035 01 0



SANDING PAD

With hook and loop fastening, \emptyset 150 mm with M 14 suction hole. Hole circle suitable for FEIN and other sanding materials.

mm

SANDING SHEETS

perforated, Ø 150 mm, with Velcro rapid attachment Application: Metal, car bodies, soldered points, welds, fibreglass. Quality: high-performance emery canvas, fully synthetic-resin bonded, corundum. Features: highly stable, high sanding capacity.

	No. in pack	
Grain	pcs	Part number
60	50	6 37 28 010 01 6



SANDING SHEETS

perforated, Ø 150 mm, with Velcro rapid attachment Application: wood, paint, automotive paints, filler, fibreglass, plastics.Quality: fully synthetic-resin bonded, corundum. Feature: greatly reduces glazing, flexible.

	No. in pack	
Grain	pcs	Part number
80	50	6 37 28 074 01 4
120	50	6 37 28 084 01 3
150	50	6 37 28 012 01 8
180	50	6 37 28 013 01 2
240	50	6 37 28 015 01 4



SANDING FLEECE FOR ANTIFOUL

Sanding fleece for light sanding and sanding down of coats of antifoul product. Produces a stunning sanding pattern without choking the sanding fleece. Very long service life.

Ø	No. in pack		
mm	pcs	Part number	
150	5	6 37 32 004 01 0	



PROTECT.SUCTION HOOD

Part number 3 18 10 264 01 0



CONNECTING PIECE

Universal device to connect power tools and accessories with dust extraction to vacuum cleaner. Flexible rubber sleeve, length 70 mm, inner diameter 31.5 mm.

Part number
3 13 22 771 00 9

ACCESSORIES FOR WPO 14-15 E, WPO 14-25 E



NYLON BARREL BRUSH

Ø 125 mm, grain 46, M 14, for brushing after removal by caustics, cleaning roof beams, restoration of antique furniture, roughing paint for new coats, deburring, and light derusting of metal parts

Part number

47,20 6 37 22 048 01 4

ACCESSORIES FOR WPO 14-15 E, WPO 14-15 XE



Part number

6 38 06 188 01 0

BACKING PAD

with Velcro attachment, M 14

mm	Part number
200	6 38 06 171 01 7



BACKING PAD

for lamb's fleece with tensioning cord, rubber coated, M 14

Ø	
mm	Part number
170	6 38 06 030 00 4



POLISHING SPONGE

For polishing painted surfaces. Various hardness grades: soft for new paintwork, medium for slightly weathered paintwork and applying wax, hard for severely weathered paintwork. Quick hook and loop fastening, height 40 mm.

Ø		
mm	Model	Part number
160	soft	6 37 23 026 01 5
160	hard	6 37 23 025 01 2



LAMBSKIN

with tensioning cord

Ø	
mm	Part number
170	6 37 23 003 00 3



LAMBSKIN

with Velcro rapid attachment.

Ø	
mm	Part number
200	6 37 23 010 00 6

SHEET METAL WORKING



NIBBLERS

148

Extremely versatile and curve-compatible, particularly suited for trapezoid sheet metals, corrugated sheet metals, profiles and curved single rolled sheets.



SHEET METAL SHEARS

160

The right choice for everyone who values the highest cutting performance in sheet metal and stainless steel.



SLITTING SHEARS 164

Clean, distortion-free cutting of sheet metals, profiles and pipes - with just one continuous cut.





DOES THIS SOUND FAMILIAR?



VERTICAL CUTS

can only be produced with a lot of effort?

Is the sheet metal that you have to cut often



THICKER THAN 3 mm?

In your workplace, are



SPARKS NOT PERMITTED?

Are you



UNABLE TO FIND SUITABLE TOOL ACCESSORIES

for machining stainless steel or aluminium?

When machining rounded sections, is the



SPEED OF YOUR TOOL TOO FAST FOR YOU?


Our most powerful nibbler.

THE NEW BLK 5.0 E



SIMPLE WAY TO CHANGE DIRECTION.

With tool-free adjustment in four 90-degree steps – ideal for guiding vertically from top to bottom with little effort or for cutting when working backwards.







MAXIMUM SAFETY.

Thanks to restart protection, blocking protection, overload protection and soft start.

EXCELLENTLY BALANCED.

All you need for improved ergonomics: a slim grip size, compact design, low weight.



ADDED VALUE FOR YOU



MISSION SAFETY.

Fully focused on protecting the user.



SPARK-FREE WORKING.

Suitable for use under conditions requiring greater fire prevention, e.g. tank decommissioning.



TIME SAVINGS.

During use thanks to simple changes in direction and adjustment of the working speed.



COST-EFFECTIVENESS.

Machine various material types and shapes – with just one long-life tool.

5 NIBBLERS









ABLK 18 1.3 CSE AS

Compact and curve-compatible nibbler for roof and façade construction. Precise cuts in corrugated sheet metal up to 1.3 mm.

Compact and curve-compatible nibbler for roof and façade construction. Precise cuts in trapezoid and corrugated sheet

Compact and rapid nibbler for corrugated sheet metals. Compact and rapid nibbler for the for the formula of the

	3	sheet metal up to 1.3 mm.	and corrugated sheet metals and profiles.			
PAGE		150	151	152	153	
Containers and tanks			+			
Single rolled sheets		++	++	++	++	
Channels		+	+	+	+	
Trapezoid sheet metal up to 85 mm deep channels		0	++	0	++	
Trapezoid sheet metal up to 160 mm deep channels			0			
Corrugated sheet metal		++	++	++	0	
Notches		++	++	++	++	
Coil sections		+	+	+	+	
Interior cut-outs		++	++	++	++	
Curve cuts		++	++	++	++	
Profile sections		++	++	++	++	
Adjustable stroke		•	•	•	•	
QuickIN		•	•	•	•	
Rotating round punch		•	•	•	•	
Cutting direction		8 x 45°	8 x 45°	8 x 45°	8 x 45°	
Additional handle						
Input	W			350	350	
Output	W			210	210	
Battery voltage	V	18	18			
Battery compatibility		Li-ion/ProCORE Li-ion	Li-ion/ProCORE Li-ion			
Battery interface		18 V AMPShare	18 V AMPShare			
Strokes	rpm	1 000 - 1 600	850 - 1 350	1,000 - 1,800	1,000 - 1,800	
Cutting speed	m/min	1,9	1,5	2,3	2,3	
Steel up to 400 N/mm²	mm	1,3	1,6	1,3	1,3	
Steel up to 600 N/mm²	mm	0,8	1	0,8	0,8	
Steel up to 800 N/mm²	mm	0,6	0,7	0,6	0,6	
Non-ferrous metals up to 250 N/mm²	mm	2	2,5	2	2	
Cutting width	mm	4	5	4	4	
Immersion Ø with die	mm	19	22	19	19	
Rad. of smallest curve (inside/outside)	mm	15 / 20	30 / 35	15 / 20	25 / 30	
Cable with plug	m			5	5	
Weight according to EPTA	kg			1,8	1,8	
Weight without storage battery	kg	1,68	1,71			

⁺ suitability

⁺⁺ optimal suitability

o optional

included











DLK 1.0 E
Universal nibbler for sheets,
profiles, trapezoid and
corrugated sheet metals.

DLK 1.0 LE
Compact nibbler for deep
channel trapezoidal sheet
metals in roof and façade
construction.

BLK 3.5 E Compact nibbler with unlimited curve precision for corners and edges.

Powerful nibbler with unlimited curve-compatibility for grooves and cut-outs.

Powerful nibbler for heavy dismantling and cutting applications.

BLK 5.0 E

corrugated sheet metals.	metals in roof and façade construction.	edges.	and cut-outs.	applications.
154	155	5 156	157	157
+				++
++				++
+				+
++				
0	++	+		
++		++		
++	++	+ ++	++	++
+				
++	+-	++	+	+
++	4	++	++	+
++	+-	++	++	++
•		•	•	•
•		•	•	•
•				
8 x 45°	8 x 45	° 8 x 45°	3 x 90°	4 x 90°
			•	•
350				1 700
210	210	210	1 000	1 000
800 - 1,500	800 - 1,500	500 - 1,000	820	820
1,9	2,7	7 1	1,5	1,5
1,6	1,6	5 2	3,5	5
1	1	1,5	2,3	3,3
0,7	0,7	7 1	1,8	2,5
2,5	2,5	5 2,5	3,5	7
5		5 8	14	8
22	24	4 18	30	43
 30 / 35	65 / 70	0 4/0	7	90
5		5 5		4
1,8	1,9	1,8	3,6	3,8

ABLK 18 1.3 CSE ABLK 18 1.3 CSE ABLK 18 1.3 CSE ABLK 18 1.3 CSE AS SET 1X 5 AH AS SET 2X 5 AH **AS SET**



Compact and curvecompatible nibbler for roof and façade construction. Precise cuts in corrugated sheet metal up to 1.3 mm.



Compact and curvecompatible nibbler for roof and façade construction. Precise cuts in corrugated sheet metal up to 1.3 mm. Includes additional punch and die set, permanent marker, painter's tape and metre rule.



Compact and curvecompatible nibbler for roof and façade construction. Precise cuts in trapezoid and corrugated sheet metals and profiles. Includes battery charger GAL 1880 CV AS 1x Li-ion storage batteries GBA 18 V 5.0 Ah AS. additional punch and die set. permanent marker, painter's tape and metre rule



Compact and curvecompatible nibbler for roof and façade construction. Precise cuts in corrugated sheet metal up to 1.3 mm. Includes battery charger GAL 1880 CV AS, 2x Li-ion storage batteries GBA 18 V 5.0 Ah AS. additional punch and die set. permanent marker, painter's tape and metre rule

				tape and metre rule.	tape and metre rute.
Battery voltage	٧	18	18	18	18
Battery compatibility		Li-ion/ProCORE Li-ion	Li-ion/ProCORE Li-ion	Li-ion/ProCORE Li-ion	Li-ion/ProCORE Li-ion
Battery interface		18 V AMPShare	18 V AMPShare	18 V AMPShare	18 V AMPShare
Strokes	rpm	1 000 - 1 600	1000 - 1600	1 000 - 1 600	1000 - 1600
Cutting speed	m/min	1,9	1,9	1,9	1,9
Steel up to 400 N/mm ²	mm	1,3	1,3	1,3	1,3
Steel up to 600 N/mm²	mm	0,8	0,8	0,8	0,8
Steel up to 800 N/mm²	mm	0,6	0,6	0,6	0,6
Non-ferrous metals up to 250 N/mm ²	mm	2	2	2	2
Cutting width	mm	4	4	4	4
Immersion Ø with die	mm	19	19	19	19
Rad. of smallest curve (inside/outside)	mm	15 / 20	15 / 20	15 / 20	15 / 20
Weight without storage battery	kg	1,68	1,68	1,68	1,68

FEIN BENEFITS

- 66 m cutting capacity (in 0.8 mm sheet metal) with one battery charge (5 Ah).
- Cutting direction setting can be changed in 45° steps up to 360° using tool-free pivoting cutting head. Optimum handling due to extremely slim gearbox head.
- 1.9 m/min cutting speed for excellent work progress.
- Variable cutting speed due to electronically adjustable speed control.
- Brief overlapping area up to 2.6 mm.
- Rotating punch for a service life which is now up to 30 % longer.
- Proven MULTIMASTER motor with outstanding performance and stability.
- QuickIN quick change system for die and punch.
- Low operating costs. Punch and die are replaced independently of one another.
- Compatible with AMPShare/Bosch Professional 18 V batteries.
- Maximum work progress with AMPShare 18 V storage batteries: COOLPACK 1.0 technology ensures a longer storage battery life compared with batteries without COOLPACK technology and therefore makes longer operating periods possible. ECP protects the storage battery against overload, overheating and total discharge.
- Ideally equipped for every job. Mobile working with the L-BOXX system.

State-of-the-art cell technology and intelligent battery management deliver 87% more power than with conventional batteries

SUPPLIED

1 die for corrugated sheet metal (30109169009) fitted, 1 punch (6 36 02 050 00 0), 1 tool case (L-BOXX 136)

1 die for corrugated sheet metal (30109169009) fitted, 1 punch (6 36 02 050 00 0), 1 punch and die set (30109169030), 1 permanent marker (32133037000), 1 painter's tape (32133038000), 1 metre rule (18750283000), 1 tool case (I-ROXX 136)

1 die for corrugated sheet metal (30109169009) fitted, 1 punch (6 36 02 050 00 0), 1 punch and die set (30109169030), 1 permanent marker (32133037000), 1 painter's tape (32133038000) 1 metre rule (18750283000), 1 Li-lon storage battery GBA 18 V 5.0 Ah AS (92604346020), 1 rapid charger GAL 1880 CV AS (92604335010), 1 tool case (L-BOXX 136)

1 die for corrugated sheet metal (30109169009) fitted, 1 punch (6 36 02 050 00 0), 1 punch and die set (30109169030), 1 permanent marker (32133037000), 1 painter's tape (32133038000), 1 metre rule (18750283000), 2 Li-lon storage battery GBA 28 V 5.0 Ah AS (92604346020), 1 rapid charger GAL 1880 CV AS (92604335010), 1 tool case (L-BOXX 136)

Part number	7 132 10 61 00 0	7 132 10 62 00 0	7 132 10 63 00 0	7 132 10 64 00 0
EAN	4014586898612	4014586899220	4014586899237	4014586899244

ABLK 18 1.6 E AS

SET 1X 5 AH

ABLK 18 1.6 E AS ABLK 18 1.6 E AS ABLK 18 1.6 E AS SET 2X 5 AH



Compact and curvecompatible nibbler for roof and façade construction. Precise cuts in trapezoid and corrugated sheet metals and profiles.



Maximum work progress with AMPShare 18 V storage batteries: COOLPACK 1.0 technology ensures a longer storage battery life compared with batteries without COOLPACK technology and therefore makes longer operating periods possible. ECP protects the storage battery against overload, overheating and total



Compact and curvecompatible nibbler for roof and façade construction. Precise cuts in trapezoid and corrugated sheet metals and profiles. Includes battery charger GAL 1880 CV AS 1x Li-ion storage batteries GBA 18 V 5.0 Ah AS, additional punch and die set, permanent marker, painter's tape and metre rule.



Compact and curvecompatible nibbler for roof and façade construction. Precise cuts in trapezoid and corrugated sheet metals and profiles. Includes battery . charger GAL 1880 CV AS, 2x Li-ion storage batteries GBA 18 V 5.0 Ah AS, additional punch and die set, permanent marker, painter's tape and metre rule.

			discharge.		
Battery voltage	V	18	18	18	18
Battery compatibility		Li-ion/ProCORE Li-ion	Li-ion/ProCORE Li-ion	Li-ion/ProCORE Li-ion	Li-ion/ProCORE Li-ion
Battery interface		18 V AMPShare	18 V AMPShare	18 V AMPShare	18 V AMPShare
Strokes	rpm	850 - 1 350	850 - 1 350	850 - 1 350	850 - 1 350
Cutting speed	m/min	1,5	1,5	1,5	1,5
Steel up to 400 N/mm²	mm	1,6	1,6	1,6	1,6
Steel up to 600 N/mm²	mm	1	1	1	1
Steel up to 800 N/mm²	mm	0,7	0,7	0,7	0,7
Non-ferrous metals up to 250 N/mm²	mm	2,5	2,5	2,5	2,5
Cutting width	mm	5	5	5	5
Immersion Ø with die	mm	22	22	22	22
Rad. of smallest curve (inside/outside)	mm	30 / 35	30 / 35	30 / 35	30 / 35
Weight without storage battery	kg	1,71	1,71	1,71	1,71

FEIN BENEFITS

- 66 m cutting capacity (in 0.8 mm sheet metal) with one battery charge (5 Ah).
- Cutting direction setting can be changed in 45° steps up to 360° using tool-free pivoting cutting head.
- Optimum handling due to extremely slim gearbox head.
- 1.5 m/min cutting speed for excellent work progress. Variable cutting speed due to electronically adjustable speed control.
- Brief overlapping area up to 2.6 mm.
- Rotating punch for a service life which is now up to 30 % longer.
- Proven MULTIMASTER motor with outstanding performance and stability.
- Compatible with AMPShare/Bosch Professional 18 V batteries.
- Maximum work progress with AMPShare 18 V storage batteries: COOLPACK 1.0 technology ensures a longer storage battery life compared with batteries without COOLPACK technology and therefore makes longer operating periods possible. ECP protects the storage battery against overload, overheating and total discharge.
- Low operating costs. Punch and die are replaced independently of one another.
- QuickIN quick change system for die and punch.
- Ideally equipped for every job. Mobile working with the L-BOXX system

+ State-of-the-art cell technology and intelligent battery management deliver 87% more power than with conventional batteries.

SUPPLIED

1 die (30109141003) fitted, 1 punch (63602048004) fitted, 1 cutting head (30109154007) mounted. 1 socket head wrench 6 mm. 1 tool case (L-BOXX 136)

1 die (30109141003) fitted, 1 punch (6 36 02 050 00 0), 1 cutting head (30109154007) mounted, 1 socket head wrench 6 mm. 1 punch and die set (30109169030), 1 permanent marker (32133037000), 1 painter's tane (32133038000) 1 metre rule (18750283000), 1 tool case (L-BOXX 136)

1 die (30109141003) fitted, 1 punch (6 36 02 050 00 0) 1 cutting head (30109154007) mounted, 1 socket head wrench 6 mm, 1 punch and die set (30109169030), 1 permanent marker (32133037000), 1 painter's tape (32133038000), 1 metre rule (18750283000), 1 Li-lon storage battery GBA 18 V 5.0 Ah AS (92604346020), 1 rapid charger GAL 1880 CV AS (92604335010), 1 tool case (L-BOXX 136)

1 die (30109141003) fitted, 1 punch (6 36 02 050 00 0), 1 cutting head (30109154007) mounted, 1 socket head wrench 6 mm, 1 punch and die set (30109169030), 1 permanent marker (32133037000), 1 painter's tape (32133038000). 1 metre rule (18750283000), 2 Li-Ion storage battery GBA 28 V 5.0 Ah AS (92604346020), 1 rapid charger GAL 1880 CV AS (92604335010), 1 tool case (L-BOXX 136)

Part number	7 132 11 61 00 0	7 132 11 62 00 0	7 132 11 63 00 0	7 132 11 64 00 0
EAN	4014586898568	4014586899251	4014586899268	4014586899275

BLK 1.3 CSE



BLK 1.3 CSE SET



Compact and rapid nibbler for corrugated sheet metals.

Compact and rapid nibbler for corrugated sheet metals. Includes additional punch and die set for corrugated sheet metal, permanent marker, painter's tape and metre rule.

			metat, permanent marker, painter 3 tape and metre rate.
Input	W	350	350
Output	W	210	210
Strokes	rpm	1,000 - 1,800	1,000 - 1,800
Cutting speed	m/min	2,3	2,3
Steel up to 400 N/mm²	mm	1,3	1,3
Steel up to 600 N/mm²	mm	0,8	0,8
Steel up to 800 N/mm²	mm	0,6	0,6
Non-ferrous metals up to 250 N/mm²	mm	2	2
Cutting width	mm	4	4
Immersion Ø with die	mm	19	19
Rad. of smallest curve (inside/outside)	mm	15 / 20	15 / 20
Cable with plug	m	5	5
Weight according to EPTA	kg	1,8	1,8

FEIN BENEFITS

- + Cutting direction setting can be changed in 45° steps up to 360° using tool-free pivoting cutting head.
- 2.3 m/min cutting speed for excellent work progress.

 Optimum ergonomics with a handle up to 20 % slimmer because of its extremely thin drive head.

- Chip protection mesh on vent slots.
 Low operating costs due to long tool life of punch and die.
 Rotating punch for a service life which is now up to 30 % longer.
- QuickIN clamping system. Stainless steel up to 0.6 mm.
- Motor with outstanding performance and stability.
- 5 metre cable.


SUPPLIED

1 die for corrugated sheet metal (30109169009) fitted, 1 punch (6 36 02 050 00 0)

1 die for corrugated sheet metal (30109169009) fitted, 1 punch (6 36 02 050 00 0), 1 punch and die set (30109169030), 1 permanent marker (32133037000), 1 painter's tape (32133038000), 1 metre rule (18750283000), 1 tool case (L-BOXX 136)

Part number	7 232 42 60 00 0	7 232 42 61 00 0
EAN	4014586870137	4014586900070

BLK 1.3 TE







Compact and rapid nibbler for trapezoid sheet metals.

Compact and rapid nibbler for trapezoid sheet metals. Includes additional punch and die set for trapezoid sheet metals, permanent marker, painter's tape and metre rule.

Input	W	350	350
Output	W	210	210
Strokes	rpm	1,000 - 1,800	1,000 - 1,800
Cutting speed	m/min	2,3	2,3
Steel up to 400 N/mm²	mm	1,3	1,3
Steel up to 600 N/mm²	mm	0,8	0,8
Steel up to 800 N/mm²	mm	0,6	0,6
Non-ferrous metals up to 250 N/mm ²	mm	2	2
Cutting width	mm	4	4
Immersion Ø with die	mm	19	19
Rad. of smallest curve (inside/outside)	mm	25 / 30	25 / 30
Cable with plug	m	5	5
Weight according to EPTA	kg	1,8	1,8
FEIN BENEFITS		L. Cutting disaction actting can be abanged in AES stans up	to 760° using tool free piveting putting bood

FEIN BENEFITS

- Cutting direction setting can be changed in 45° steps up to 360° using tool-free pivoting cutting head.
 2.3 m/min cutting speed for excellent work progress.
- Optimum ergonomics with a handle up to 20 % slimmer because of its extremely thin drive head.

- Chip protection mesh on vent slots.

 Low operating costs due to long tool life of punch and die.

 Brief overlapping area up to 2.6 mm.

 Rotating punch for a service life which is now up to 30 % longer.
- QuickIN clamping system.
- Stainless steel up to 0.6 mm.
- Motor with outstanding performance and stability.
- 5 metre cable.

SUPPLIED

1 die for trapezoid sheet metal (30109170001) fitted, 1 punch (6 36 02 050 00 0)

1 die for trapezoid sheet metal (30109170001) fitted, 1 punch (6 36 02 050 00 0), 1 punch and die set (30109170030), 1 permanent marker (32133037000), 1 painter's tape (32133038000), 1 metre rule (18750283000), 1 tool case (L-BOXX 136)

Part number	7 232 41 60 00 0	7 232 41 61 00 0
EAN	4014586870069	4014586900063

BLK 1.6 E



Universal nibbler for sheets, profiles, trapezoid and corrugated sheet metals.

BLK 1.6 E SET



Universal nibbler for roof and façade construction. Precise cuts in sheet metals, profiles, trapezoid and corrugated sheet metals up to 1.6 mm. Includes additional punch and die set for trapezoid and corrugated sheet metals, permanent marker, painter's tape and metre rule.

			permanent marker, painter's tape and metre rute.
Input	W	350	350
Output	W	210	210
Strokes	rpm	800 - 1,500	800 - 1,500
Cutting speed	m/min	1,9	1,9
Steel up to 400 N/mm²	mm	1,6	1,6
Steel up to 600 N/mm²	mm	1	1
Steel up to 800 N/mm²	mm	0,7	0,7
Non-ferrous metals up to 250 N/mm²	mm	2,5	2,5
Cutting width	mm	5	5
Immersion Ø with die	mm	22	22
Rad. of smallest curve (inside/outside)	mm	30 / 35	30 / 35
Cable with plug	m	5	5
Weight according to EPTA	kg	1,8	1,8

FEIN BENEFITS

SU

- Almost indestructible. Ideal for flexible and universal use with sheet thickness up to 1.6 mm.. Optimum ergonomics with a handle up to 20 % slimmer because of its extremely thin drive head. Cutting direction setting can be changed in 45° steps up to 360° using tool-free pivoting cutting head.
- QuickIN clamping system.
- High cutting speed.
- Rotating punch for a service life which is now up to 30 % longer.
- Low operating costs due to long tool life of punch and die. Motor with outstanding performance and stability. Chip protection mesh on vent slots.

- 5 metre cable.
- Stainless steel up to 0.7 mm.
- Retrofittable trapezoid profile set up to 160 mm deep channels.

PPLIED	1 die (30109141003) fitted, 1 punch (63602048004) fitted,
--------	---

1 socket head wrench 6 mm

1 die (30109141003) fitted, 1 punch (63602048004) fitted, 1 socket head wrench 6 mm, 1 cutting head (30109154007) mounted, 1 punch and die set (63602048013), 1 permanent marker (32133037000), 1 painter's tape (32133038000), 1 metre rule (18750283000), 1 tool case (L-BOXX 136)

Part number	7 232 38 60 00 0	7 232 38 61 00 0
EAN	4014586869858	4014586900049

BLK 1.6 LE



SUPPLIED

1 die for trapezoid sheet metal (31309122005) fitted, 1 punch (63602049008) fitted, 1 wearing plate fitted

For accessories, see page 158

Compact nibbler for deep-channel trapezoidal sheet metals in roof and façade construction.

Input	W	350
Output	W	210
Strokes	rpm	800 - 1,500
Cutting speed	m/min	2,7
Steel up to 400 N/mm²	mm	1,6
Steel up to 600 N/mm²	mm	1
Steel up to 800 N/mm²	mm	0,7
Non-ferrous metals up to 250 N/mm²	mm	2,5
Cutting width	mm	5
Immersion Ø with die	mm	24
Rad. of smallest curve (inside/outside)	mm	65 / 70
Cable with plug	m	5
Weight according to EPTA	kg	1,9

Part number	7 232 39 60 00 0
EAN	4014586869926

FEIN BENEFITS

- + The specialist when it comes to zero compromise work on trapezoidal sheet metals with deep channels of up to 160 mm.
- + Optimum ergonomics with a handle up to 20 %
- Optimum ergonomics with a handle up to 20 % slimmer because of its extremely thin drive head.
 Cutting direction setting can be changed in 45° steps up to 360° using tool-free pivoting cutting head.
 QuicklN clamping system.
 High cutting speed.
 Motor with outstanding performance and stability.
 Chip protection mesh on vent slots.
 5 metre cable.

- 5 metre cable.
- + Stainless steel up to 0.7 mm.

BLK 2.0 E



BLK 2.0 E SET



Compact nibbler with unlimited curve precision for corners and edges.

Compact nibbler with unlimited curve compatibility for recesses and cut-outs in material thicknesses of up to 2 mm. Includes additional punch and die set, permanent marker, painter's tape and metre rule.

			marker, painter's tape and metre rute.
Input	W	350	350
Output	W	210	210
Strokes	rpm	500 - 1,000	500 - 1,000
Cutting speed	m/min	1	1
Steel up to 400 N/mm²	mm	2	2
Steel up to 600 N/mm²	mm	1,5	1,5
Steel up to 800 N/mm²	mm	1	1
Non-ferrous metals up to 250 N/mm²	mm	2,5	2,5
Cutting width	mm	8	8
Immersion Ø with die	mm	18	18
Rad. of smallest curve (inside/outside)	mm	4/0	4/0
Cable with plug	m	5	5
Weight according to EPTA	kg	1,8	1,8

FEIN BENEFITS

SUPPLIED

- + High curve precision due to special cutting head geometry. Nibbler can turn on the spot.
- Especially well-suited for cutting edged sheet metals with a minimum bend radius of 3 mm.

 Cutting direction setting can be changed in 45° steps up to 360° using tool-free pivoting cutting head.

 QuickIN clamping system.

 Optimal ergonomics.

- Motor with outstanding performance and stability.

1 die (3 13 09 040 00 2), 1 punch (6 36 02 051 00 9)

- Ideal for cut-outs.
- Optimally suited for template cuts.
- Chip protection mesh on vent slots. 5 metre cable.
 Stainless steel up to 1.0 mm.

1 die (3 13 09 040 00 2), 1 punch (6 36 02 051 00 9),

1 punch and die set (63602051018), 1 permanent marker (32133037000), 1 painter's tape (32133038000), 1 metre rule (18750283000), 1 tool case (L-BOXX 136)

Part number	7 232 40 60 00 0	7 232 40 61 00 0
EAN	4014586869995	4014586900056

BLK 3.5 E



SUPPLIED

1 die, steel (31309093003) fitted, 1 punch, steel (31309097002) fitted, 1 additional handle fitted, 1 spacer sleeve (31309100014), 1 plastic tool case (L-BOXX 238)

For accessories, see page 158

Powerful nibbler with unlimited curve-compatibility for grooves and cut-outs.

Input	W	1700
Output	W	1 000
Strokes	rpm	820
Cutting speed	m/min	1,5
Steel up to 400 N/mm²	mm	3,5
Steel up to 600 N/mm²	mm	2,3
Steel up to 800 N/mm²	mm	1,8
Non-ferrous metals up to 250 N/mm²	mm	3,5
Cutting width	mm	14
Immersion Ø with die	mm	30
Rad. of smallest curve (inside/outside)	mm	7
Cable with plug	m	4
Weight according to EPTA	kg	3,6

Part number	7 232 46 61 00 0
EAN	4014586897677

FEIN BENEFITS

- + Good curve precision allows the tool to be rotated into position. Making it ideally suited to recesses and cuts, e.g. templates in sheet metal.
- Warp-free cutting of flat and bent sheet metal.
- + Extensive user protection: restart protection, blocking protection, overload protection, soft start.
- Cutting direction: 3 x 90°, can be adjusted without the need for tools.
- Powerful 1700 W motor.
- Variable stroke.
- Tool-free quick change system for die and punch.
- Ergonomic handle suited to guiding in all directions. Chip protection mesh on vent slots.
- Wide range of accessories.

BLK 5.0 E



SUPPLIED

1 die 5, steel (31309107000) fitted, 1 punch 5/P5 steel (31309141000) fitted, 1 additional handle fitted, 1 plastic tool case (L-BOXX 238)

For accessories, see page 158

Powerful nibbler for heavy dismantling and cutting applications.

Input	W	1,700
Output	W	1 000
Strokes	rpm	820
Cutting speed	m/min	1,5
Steel up to 400 N/mm²	mm	5
Steel up to 600 N/mm²	mm	3,3
Steel up to 800 N/mm²	mm	2,5
Non-ferrous metals up to 250 N/mm ²	mm	7
Cutting width	mm	8
Immersion Ø with die	mm	43
Rad. of smallest curve (inside/outside)	mm	90
Cable with plug	m	4
Weight according to EPTA	kg	3,8
	Output Strokes Cutting speed Steel up to 400 N/mm² Steel up to 600 N/mm² Steel up to 800 N/mm² Non-ferrous metals up to 250 N/mm² Cutting width Immersion Ø with die Rad. of smallest curve (inside/outside) Cable with plug	Output W Strokes rpm Cutting speed m/min Steel up to 400 N/mm² mm Steel up to 600 N/mm² mm Steel up to 800 N/mm² mm Non-ferrous metals up to 250 N/mm² mm Cutting width mm Immersion Ø with die mm Rad. of smallest curve (inside/outside) mm Cable with plug m

Part number	7 232 47 61 00 0
EAN	4014586897714

FEIN BENEFITS

- + Suited to cuts over 90° edges, for example on guard rails or during tank decommissioning.

 + Incredible power delivered by the 1700 W motor while
- also offering outstanding ergonomics and optimum power-to-weight ratio.
- Extensive user protection: restart protection, blocking protection, overload protection, soft start.

 + Cutting direction: 4 x 90°, can be adjusted without the
- need for tools.
- Variable stroke.
- Tool-free quick change system for die and punch.
- Ergonomic handle suited to guiding in all directions.
- Chip protection mesh in fan area.

NIBBLERS

GENERAL ACCESSORIES



CUTTING PASTE

Lubricating agents for working on sheet metals.

Part number 3 21 32 046 00 0



MAGBRUSH

Practical tool with high magnetic force for quick and easy collection of magnetic metal swarf.

Part number 6 42 01 005 01 0

ACCESSORIES FOR (A)BLK 1.3 CSE



PUNCHES AND DIES IN A SET

consisting of 5 x punches 6 36 02 050 00 0 and 1 x die 3 01 09 169 00 9.

Part number 3 01 09 169 03 0



PUNCH

for steel sheet up to 400 N/mm²

Plate thickness	No. in pack	
mm	pcs	Part number
1,3	1	6 36 02 050 00 0
1,3	5	6 36 02 050 03 0
1,3	10	6 36 02 050 01 0



for corrugated sheet metal

No. in pack	
pcs	Part number
1	3 01 09 169 00 9
2	3 01 09 169 04 0

ACCESSORIES FOR BLK 1.3 TE



PUNCHES AND DIES IN A SET

consisting of 5 x punches 6 36 02 050 00 0 and 1 x die 3 01 09 170 00 1.

Part number 3 01 09 170 03 0



PUNCH

for steel sheet up to 400 N/mm²

Plate thickness	No. in pack			
mm	pcs	Part number		
1,3	1	6 36 02 050 00 0		
1,3	5	6 36 02 050 03 0		
1,3	10	6 36 02 050 01 0		



for trapezoidal sheet metal

No. in pack

pcs	Part number
1	3 01 09 170 00 1
2	3 01 09 170 04 0

ACCESSORIES FOR (A)BLK 1.6 E



PUNCH

No. in pack	
pcs	Part number
1	6 36 02 048 00 4
5	6 36 02 048 04 0
10	6 36 02 048 05 0



DIE

No. in pack	
pcs	Part number
1	3 01 09 141 00 3
2	3 01 09 141 02 0
5	3 01 09 141 03 0



PUNCHES AND DIES

In set, each consisting of 1x punch 6 36 02 048 00 4 and 1x die 3 01 09 141 00 3.

Part number 6 36 02 048 01 3



DIE HOLDER

for trapezoidal sheet metal and corrugated sheet metal

Part number 3 01 09 154 00 7



PROFILE SET 160

For deep-channel trapezoidal sheet metals (85-160 mm), incl. 1 punch, die and wearing plate.

Part number 9 26 02 071 01 9

ACCESSORIES FOR BLK 1.6 LE



PUNCHES AND DIES

In the set, for profile set 160, including wear plate, screws and key. Profile set 160

Part number
6 36 02 049 01 7

PUNCH No in nack

pcs	Part number
1	6 36 02 049 00 8
2	6 36 02 049 04 0
5	6 36 02 049 05 0



DIE

No. in pack	
pcs	Part number
1	3 13 09 122 00 5
2	3 13 09 122 02 0
5	3 13 09 122 03 0



WEARING PLATEProfile set 160

Part	t nur	nber
3 13 09	121	00 2

ACCESSORIES FOR BLK 2.0 E



PUNCHES AND DIES IN A SETConsisting of: 1 die 6 36 02 051 00 9 and 1 punch 3 13 09 040 00 2

Part number
6 36 02 051 01 8



PUNCH

Part number 6 36 02 051 00 9



DIE

Part number
3 13 09 040 00 2

ACCESSORIES FOR BLK 3.5 E



PUNCH for steel sheet up to 400 N/mm²

Part number 3 13 09 097 00 2



PUNCH for stainless steel up to 800 N/mm²

Part number 3 13 09 098 00 0



DIE

for steel sheet up to 400 N/mm²

Part number
3 13 09 093 00 3



DIE

for stainless steel up to 800 N/mm²

Part number 3 13 09 094 00 1



SPACER SLEEVE

To reduce the gap between cutting head and die. This prevents the material on thinner sheet metal from being damaged.

Part number

3 13 09 100 01 4

ACCESSORIES FOR BLK 5.0 E



PUNCHES AND DIES IN A SET

Up to 5.0 mm steel plate (400 N/mm²), consisting of: 1 punch 3 13 09 141 00 0 and 1 die 3 13 09 107 00 0.

Part number 3 13 09 141 01 0



PUNCHES AND DIES IN A SET

Up to 3.0 mm stainless steel plate (600 N/mm²), consisting of: 1 punch 3 13 09 142 00 0 and 1 die 3 13 09 108 00 8.

Part number 3 13 09 142 01 0



PUNCH

Up to 7.0 mm aluminium steel plate (250 $\mbox{N/mm}^2)$ up to 5.0 mm steel sheet (400 $\mbox{N/mm}^2).$

Part number 3 13 09 141 00 0



PUNCH

Up to 3.0 mm stainless steel plate (600 N/mm²).

Part number 3 13 09 142 00 0



DIE

for steel sheet up to 5 mm thickness

Part number 3 13 09 107 00 0



DIEUp to 3.0 mm stainless steel plate (600 N/mm²).

Part number 3 13 09 108 00 8



DIE

Up to 7.0 mm aluminium steel plate (250 $\mbox{N/mm}^2)$ up to 5.0 mm steel sheet (400 $\mbox{N/mm}^2).$

Part number 3 13 09 109 00 2

5 SHEET METAL SHEARS







ABLS 18 1.6 E AS

Ergonomic, curve-compatible cordless sheet metal shears for

BLS 1.6 E

BLS 2.5 E Easy-to-use, curve-compatible sheet metal shears for cutting and trimming thin sheats.

		cutting and trimming thin sheets.	thin sheets.		stainless steel.	
PAGE		161		162		163
Containers and tanks						+
Single rolled sheets		++		++		++
Notches		+		+		+
Coil sections		++		++		++
Interior cut-outs		+		+		+
Curve cuts		++		++		+
Adjustable stroke		•		•		•
Reversing blade		4x		4x		4x
Hand guard		•		•		•
Input	W			350		350
Output	W			210		210
Battery voltage	V	18				
Battery compatibility		Li-ion/ProCORE Li-ion				
Battery interface		18 V AMPShare				
Strokes	rpm	2 200 - 3 500		2,300 - 4,800		800 - 1,700
Cutting speed	m/min	6 - 9		8 - 12		3 - 6
Steel up to 400 N/mm²	mm	1,6		1,6		2,5
Steel up to 600 N/mm²	mm	1,2		1,2		2
Steel up to 800 N/mm²	mm	1		1		1,6
Non-ferrous metals up to 250 N/mm²	mm	2		2		3
Rad. of smallest curve	mm	15		15		20
Cable with plug	m			5		5
Weight according to EPTA	kg			1,7		2,1
Weight without storage battery	kg	1,44				

⁺ suitability

⁺⁺ optimal suitability

included

ABLS 18 1.6 E AS ABLS 18 1.6 E AS

ABLS 18 1.6 E AS SET 1X 5 AH

ABLS 18 1.6 E AS SET 2X 5 AH



Ergonomic, curve-compatible cordless sheet metal shears for cutting and trimming thin sheets.



Handy, curve-compatible cordless sheet metal shears for cutting and trimming thin sheet metal. Includes second plunger blade and fixed blade, permanent marker, painter's tape and metre rule.



Handy, curve-compatible cordless sheet metal shears for cutting and trimming thin sheet metal. Includes GAL 1880 CV AS charger, 1x GBA 18 V 5.0 Ah AS Li-ion storage battery, second plunger blade and fixed blade, permanent marker, painter's tape and metre rule.



Handy, curve-compatible cordless sheet metal shears for cutting and trimming thin sheet metal. Includes GAL 1880 CV AS charger, 2x GBA 18 V 5.0 Ah AS Li-ion storage battery, second plunger blade and fixed blade, permanent marker, painter's tape and metre rule

				painter 3 tape and metre rate.	painter 3 tape and metre rate.
Battery voltage	V	18	18	18	18
Battery compatibility		Li-ion/ProCORE Li-ion	Li-ion/ProCORE Li-ion	Li-ion/ProCORE Li-ion	Li-ion/ProCORE Li-ion
Battery interface		18 V AMPShare	18 V AMPShare	18 V AMPShare	18 V AMPShare
Strokes	rpm	2 200 - 3 500	2 200 - 3 500	2 200 - 3 500	2 200 - 3 500
Cutting speed	m/min	6 - 9	6 - 9	6 - 9	6 - 9
Steel up to 400 N/mm²	mm	1,6	1,6	1,6	1,6
Steel up to 600 N/mm²	mm	1,2	1,2	1,2	1,2
Steel up to 800 N/mm²	mm	1	1	1	1
Non-ferrous metals up to 250 N/mm ²	mm	2	2	2	2
Rad. of smallest curve	mm	15	15	15	15
Weight without storage battery	kg	1,44	1,44	1,44	1,44
FEIN BENEFITS		. 221	0.0	la attaur a la ausa (F. Ala)	

FEIN BENEFITS

- 221 m cutting capacity (in 0.8 mm sheet metal) with one battery charge (5 Ah).
- Outstanding ergonomics through compact and simple construction for optimal mobility of the shears. Four-fold reversing blade for clean and burr-free cutting with low operating costs.
- Good curve precision with low sheet-metal distortion.
- Perfect for trimming and cutting.
- Unrestricted view of the cutting line.
 Proven MULTIMASTER motor with outstanding performance and stability.
- Compatible with AMPShare/Bosch Professional 18 V batteries.
- Maximum work progress with AMPShare 18 V storage batteries: COOLPACK 1.0 technology ensures a longer storage battery life compared with batteries without COOLPACK technology and therefore makes longer operating periods possible. ECP protects the storage battery against overload, overheating and total discharge.
- Ideally equipped for every job. Mobile working with the L-BOXX system.

State-of-the-art cell technology and intelligent battery management deliver 87% more power than with conventional batteries.

SUPPLIED

1 plunger blade and bench blade (31308072000) fitted. 1 socket head wrench 2 mm, 1 x 3 mm socket head wrench, 1 hand guard, 1 tool case (L-BOXX 136)

2 plunger blade and bench blade (31308072000) fitted. 1 socket head wrench 2 mm, 1 x 3 mm socket head wrench, 1 hand guard, 1 permanent marker (32133037000), 1 painter's tape (32133038000), 1 metre rule (18750283000), 1 tool case (L-BOXX 136)

2 plunger blade and bench blade (31308072000) fitted. 1 socket head wrench 2 mm, 1 x 3 mm socket head wrench, 1 hand guard, 1 permanent marker (32133037000), 1 painter's tape (32133038000), 1 metre rule (18750283000), 1 Li-lon storage battery GBA 18 V 5.0 Ah AS (92604346020), 1 rapid charger GAL 1880 CV AS (92604335010), 1 tool case (I-BOXX 136)

2 plunger blade and bench blade (31308072000) fitted. 1 socket head wrench 2 mm, 1 x 3 mm socket head wrench, 1 hand guard, 1 permanent marker (32133037000), 1 painter's tape (32133038000), 1 metre rule (18750283000), 2 Li-lon storage battery GBA 28 V 5.0 Ah AS (92604346020), 1 rapid charger GAL 1880 CV AS (92604335010), 1 tool case (I-BOXX 136)

Part number	7 130 06 61 00 0	7 130 06 62 00 0	7 130 06 63 00 0	7 130 06 64 00 0
EAN	4014586898605	4014586899190	4014586899206	4014586899213

BLS 1.6 E



BLS 1.6 E SET



Easy-to-use, curve-compatible sheet metal shears for cutting and trimming thin sheets. Easy-to-use, curve-compatible sheet metal shears for cutting and trimming thin sheets. Includes second plunger blade and bench blade permanent marker, painter's tape and metre rule

350
210
2,300 - 4,800
8 - 12
1,6
1,2
1
2
15
5
1,7

FEIN BENEFITS

- Outstanding ergonomics through compact and simple construction for optimal mobility of the shears.
- Good curve precision with low sheet-metal distortion.

 Four-fold reversing blade for clean and burr-free cutting with low operating costs.

 Perfect for trimming and cutting.

 Unrestricted view of the cutting line.

- Motor with outstanding performance and stability.
- 5 metre cable.
- Stainless steel up to 1.0 mm.

SUPPLIED

- 1 plunger blade and bench blade (31308072000) fitted, 1 hand guard, fitted, 1 socket head wrench $2\ mm,$ 1 x $3\ mm$ socket head wrench

2 plunger blade and bench blade (31308072000) fitted, 1 hand guard, fitted, 1 socket head wrench 2 mm, 1 x 3 mm socket head wrench, 1 permanent marker (32133037000), 1 painter's tape (32133038000), 1 metre rule (18750283000),

1 tool case (L-BOXX 136)

Part number	7 230 34 61 00 0	7 230 34 62 00 0
EAN	4014586874876	4014586900025

BLS 2.5 E



Easy-to-use, curve-compatible sheet metal shears for working with stainless steel.

BLS 2.5 E SET



Easy-to-use, curve-compatible sheet metal shears for stainless steel processing and sheet metals. Includes second plunger blade and bench blade permanent marker, painter's tape and metre rule.

EEIN DENEEITS		+ High performance and powerful motor for the most difficu	It tacks
Weight according to EPTA	kg	2,1	2,1
Cable with plug	m	5	5
Rad. of smallest curve	mm	20	20
Non-ferrous metals up to 250 N/mm ²	mm	3	3
Steel up to 800 N/mm²	mm	1,6	1,6
Steel up to 600 N/mm²	mm	2	2
Steel up to 400 N/mm²	mm	2,5	2,5
Cutting speed	m/min	3 - 6	3 - 6
Strokes	rpm	800 - 1,700	800 - 1,700
Output	W	210	210
Input	W	350	350
			The state of the s

FEIN BENEFITS

- High performance and powerful motor for the most difficult tasks. Unrestricted view of the cutting line makes faster work progress possible.
- Four-fold reversing blade for clean and burr-free cutting with low operating costs.

- Perfect for trimming and cutting.
 Unrestricted view of the cutting line.
 Good curve precision with low sheet-metal distortion.
- 5 metre cable.
- Stainless steel up to 1.6 mm.

SUPPLIED

1 plunger blade and bench blade (63601101009) fitted, 1 hand guard, fitted, 1 socket head wrench 2,5 mm, 1 x 4 mm socket head wrench

 $2\,x$ plunger blade and bench blade (63601101009), 1 fitted, 1 hand guard, fitted, 1 socket head wrench 2,5 mm, 1 x 4 mm socket head wrench, 1 permanent marker (32133037000),

1 painter's tape (32133038000), 1 metre rule (18750283000),

1 tool case (L-BOXX 136)

Part number	7 230 35 61 00 0	7 230 35 62 00 0
EAN	4014586874944	4014586900032

For accessories, see page 163

ACCESSORIES FOR (A)BLS 1.6 E



PLUNGER BLADE AND FIXED BLADE

for steel sheet up to 800 N/mm²

mm	Part number
1	3 13 08 072 00 0

ACCESSORIES FOR BLS 2.5 E



PLUNGER BLADE AND FIXED BLADE

for steel sheet up to 800 N/mm²

Plate thickness	
mm	Part number
1,6	6 36 01 101 00 9

5 SLITTING SHEARS











ABSS 18 1.6 E AS

Easy-to-use, curvecompatible cordless slitting shears for distortion-free cuts and cut-outs in sheet

BSS 1.6 E BSS 1.6 CE Easy-to-use and curve-

Easy-to-use and curvecompatible slitting shears compatible slitting shears for distortion-free cutting.

Powerful slitting shears for stainless steel processing,

with integrated chip clipper. spiral seam pipes and profiles. metal up to 1.6 mm. 168 PAGE 165 166 167 Containers and tanks Single rolled sheets ++ ++ ++ ++ ++ ++ Trapezoid sheet metal up to 85 mm + + + + deep channels + Corrugated sheet metal + + + Folded spiral-seam pipes ++ ++ ++

rotueu spirat-seam pipes		++	++	++	++
Notches		++	++	++	++
Coil sections		++	++	++	++
Interior cut-outs		++	++	++	++
Curve cuts		+	+	+	
Profile sections		+	+	+	++
Adjustable stroke		•	•	•	•
Open cutting head		•	•	•	
QuickIN		•	•	•	
Chip clipper				•	
Input	W		350	350	350
Battery voltage	V	18			
Battery compatibility		Li-ion/ProCORE Li-ion			
Battery interface		18 V AMPShare			
Strokes	rpm	2,200 - 3,500	2,100 - 4,500	2,100 - 4,500	1,300 - 2,600
Cutting speed	m/min	5 - 8	6 - 10	6 - 10	2 - 4
Steel up to 400 N/mm²	mm	1,6	1,6	1,6	2
Steel up to 600 N/mm²	mm	1,2	1,2	1,2	1,5
Steel up to 800 N/mm²	mm	0,8	1	1	1,3
Non-ferrous metals up to 250 N/mm²	mm	2	2	2	3
Cutting width	mm	5	5	5	5
Rad. of smallest curve	mm	48	90 (30) ¹	90 (30) ¹	245
Immersion Ø	mm	15	15 (8) ¹	15 (8) ¹	12
Cable with plug	m		5	5	5

⁺ suitability

Weight according to EPTA

Weight without storage battery

kg

kg

1,5

1,5

1,7

⁺⁺ optimal suitability

included

^{1,24} ¹ with blade for curves

ABSS 18 1.6 E AS

Easy-to-use, curve-

up to 1.6 mm.

compatible cordless slitting

and cut-outs in sheet metal

AMP Share

ABSS 18 1.6 E AS



Handy, curve-compatible cordless slitting shears for shears for distortion-free cuts distortion-free cutting off and cutting out of sheet metal up to 1.6 mm. Includes additional blade for curves, permanent marker, painter's tape and

metre rule.

ABSS 18 1.6 E AS SET 1X 5 AH



Handy, curve-compatible cordless slitting shears for distortion-free cutting off and cutting out of sheet metal up to 1.6 mm. Includes GAL 1880 CV AS charger, 1x GBA 18 V 5.0 Ah AS Li-ion storage battery, additional blade for curves, permanent marker, painter's tape and



ABSS 18 1.6 E AS

Handy, curve-compatible cordless slitting shears for distortion-free cutting off and cutting out of sheet metal up to 1.6 mm. Includes GAL 1880 CV AS charger, 2x GBA 18 V 5.0 Ah AS Li-ion storage battery, additional blade for curves, permanent marker, painter's tape and

				metre rute.	mederate.
Battery voltage	V	18	18	18	18
Battery compatibility		Li-ion/ProCORE Li-ion	Li-ion / CORE Li-ions	Li-ion / CORE Li-ions	Li-ion / CORE Li-ions
Battery interface		18 V AMPShare	18 V AMPShare	18 V AMPShare	18 V AMPShare
Strokes	rpm	2,200 - 3,500	2,200 - 3,500	2,200 - 3,500	2,200 - 3,500
Cutting speed	m/min	5 - 8	5 - 8	5 - 8	5 - 8
Steel up to 400 N/mm²	mm	1,6	1,6	1,6	1,6
Steel up to 600 N/mm²	mm	1,2	1,2	1,2	1,2
Steel up to 800 N/mm²	mm	0,8	0,8	0,8	0,8
Non-ferrous metals up to 250 N/mm ²	mm	2	2	2	2
Cutting width	mm	5	5	5	5
Rad. of smallest curve	mm	48	48	48	48
Immersion Ø	mm	15	15	15	15
Weight without storage battery	kg	1,24	1,24	1,24	1,24

FEIN BENEFITS

- 180 m cutting capacity (in 0.8 mm sheet metal) with one battery charge (5 Ah).
- Rapid work progress due to excellent view of the cutting line through the open-fronted cutting head.
- Left and right curve cuts and distortion-free cutting possible with just one continuous chip.
- QuickIN for rapid toolfree blade changing, with no further adjustment required.
- Excellent ergonomics and low weight.
- Cutting blade with excellent tool life.
- Proven MULTIMASTER motor with outstanding performance and stability.
- Compatible with AMPShare/Bosch Professional 18 V batteries.
- Maximum work progress with AMPShare 18 V storage batteries: COOLPACK 1.0 technology ensures a longer storage battery life compared with batteries without COOLPACK technology and therefore makes longer operating periods possible. ECP protects the storage battery against overload, overheating and total discharge. Ideally equipped for every form of use. Mobile working with the L-BOXX system.
- - State-of-the-art cell technology and intelligent battery management deliver 87% more power than with conventional batteries

SUPPLIED

1 cutter blade (31308150009) fitted, 1 pair of cutting jaws (31308153014) fitted, 1 socket head wrench 2,5 mm, 1 tool case (L-BOXX 136)

1 cutter blade (31308150009) fitted, 1 pair of cutting jaws (31308153014) fitted, 1 socket head wrench 2.5 mm, 1 blade for curves (31308151008), 1 permanent marker (32133037000), 1 painter's tape (32133038000), 1 metre rule (18750283000), 1 tool case (L-BOXX 136)

1 cutter blade (31308150009) fitted, 1 pair of cutting jaws (31308153014) fitted, 1 socket head wrench 2.5 mm, 1 blade for curves (31308151008), 1 permanent marker . (32133037000), 1 painter's tape (32133038000), 1 metre rule (18750283000), 1 Li-lon storage battery GBA 18 V 5.0 Ah AS (92604346020), 1 rapid charger GAL 1880 CV AS (92604335010), 1 tool case (L-BOXX 136)

1 cutter blade (31308150009) fitted, 1 pair of cutting jaws (31308153014) fitted, 1 socket head wrench 2,5 mm, 1 blade for curves (31308151008), 1 permanent marker . (32133037000), 1 painter's tape (32133038000). 1 metre rule (18750283000), 2 Li-lon storage battery GBA 28 V 5.0 Ah AS (92604346020), 1 rapid charger GAL 1880 CV AS (92604335010), 1 tool case (L-BOXX 136)

Part number	7 130 05 61 00 0	7 130 05 62 00 0	7 130 05 63 00 0	7 130 05 64 00 0
EAN	4014586898599	4014586899169	4014586899176	4014586899183

BSS 1.6 E



Easy-to-use and curve-compatible slitting shears for distortion-free cutting.

BSS 1.6 E SET



Easy-to-use, curve-compatible slitting shears for distortion-free cut-offs and cut-outs in sheet metal up to 1.6 mm. Includes additional curved blade, permanent marker, painter's tape and metre rule.

Input	W	350	350
Output	W	210	210
Strokes	rpm	2,100 - 4,500	2,100 - 4,500
Cutting speed	m/min	6 - 10	6 - 10
Steel up to 400 N/mm²	mm	1,6	1,6
Steel up to 600 N/mm²	mm	1,2	1,2
Steel up to 800 N/mm²	mm	1	1
Non-ferrous metals up to 250 N/mm²	mm	2	2
Cutting width	mm	5	5
Rad. of smallest curve	mm	90 (30) ¹	90 (30)1
Immersion Ø	mm	15 (8) ¹	15 (8) ¹
Cable with plug	m	5	5
Weight according to EPTA	kg	1,5	1,5
		5 11 1 1 1 1 1 1 1 1 1 1 1	

FEIN BENEFITS

- + Rapid work progress due to excellent view of the cutting line through the open-fronted cutting head.
- Left and right curve cuts and distortion-free cutting possible with just one continuous chip. QuickIN for rapid toolfree blade changing, with no further adjustment required.

- Excellent ergonomics and low weight.

 Motor with outstanding performance and stability.

 Cutting blade with excellent tool life.
- 5 metre cable.
- Clean swarf removal prevents injuries or scratches on workpieces.
- Stainless steel up to 1.2 mm.
- Wide range of accessories. with blade for curves

SUPPLIED

1 cutter blade, straight (31308150009) fitted, up to 1.6 mm, 1 pair of cutting jaws (31308153014) fitted, 1 socket head wrench 2,5 mm

1 cutter blade, straight (31308150009) fitted, up to 1.6 mm, 1 pair of cutting jaws (31308153004) fitted, up to 1.6 mm, 1 pair of cutting jaws (31308153014) fitted, 1 socket head wrench 2,5 mm, 1 blade for curves (31308151008), 1 permanent marker (32133037000), 1 painter's tape (32133038000), 1 metre rule (18750283000), 1 tool case (L-BOXX 136)

Part number	7 230 31 61 00 0	7 230 31 62 00 0
EAN	4014586874661	4014586899992

BSS 1.6 CE



BSS 1.6 CE SET



Easy-to-use and curve-compatible slitting shears with integrated chip clipper.

Easy-to-use and curve-compatible slitting shears with integrated chip clipper. Includes additional curved blade, permanent marker, painter's tape and metre rule.

Input	W	350	350
Output	W	210	210
Strokes	rpm	2,100 - 4,500	2,100 - 4,500
Cutting speed	m/min	6 - 10	6 - 10
Steel up to 400 N/mm²	mm	1,6	1,6
Steel up to 600 N/mm²	mm	1,2	1,2
Steel up to 800 N/mm²	mm	1	1
Non-ferrous metals up to 250 N/mm ²	mm	2	2
Cutting width	mm	5	5
Rad. of smallest curve	mm	90 (30)1	90 (30)1
Immersion Ø	mm	15 (8) ¹	15 (8) ¹
Cable with plug	m	5	5
Weight according to EPTA	kg	1,5	1,5

FEIN BENEFITS

- Chip clipper for clipping off the cut chip at any point.
 Left and right curve cuts and distortion-free cutting possible with just one continuous chip.
- Rapid work progress due to excellent view of the cutting line through the open-fronted cutting head.
- Excellent ergonomics and low weight.

 Motor with outstanding performance and stability.

 Cutting blade with excellent tool life.
- 5 metre cable.
- Clean swarf removal prevents injuries or scratches on workpieces.
- Stainless steel up to 1.2 mm.
- Wide range of accessories. with blade for curves

SUPPLIED

1 cutter blade, straight (31308150009) fitted, up to 1.6 mm, 1 pair of cutting jaws (31308153020) fitted, 1 socket head wrench 2,5 mm

1 cutter blade, straight (31308150009) fitted, up to 1.6 mm, 1 pair of cutting jaws (31308153020) fitted, 1 socket head wrench 2,5 mm, 1 blade for curves (31308151008), 1 permanent marker (32133037000), 1 painter's tape (32133038000), 1 metre rule (18750283000), 1 tool case (L-BOXX 136)

Part number	7 230 32 61 00 0	7 230 32 62 00 0
EAN	4014586874739	4014586900001

BSS 2.0 E



BSS 2.0 E SET



Powerful slitting shears for stainless steel processing, spiral seam pipes and profiles.

Powerful slitting shears for stainless steel processing, spiral seam pipes, profiles and sheet metals. Includes additional blade, permanent marker, painter's tape and metre rule.

			blade, permanent marker, painter 3 tape and metre rate.
Input	W	350	350
Output	W	210	210
Strokes	rpm	1,300 - 2,600	1,300 - 2,600
Cutting speed	m/min	2 - 4	2 - 4
Steel up to 400 N/mm²	mm	2	2
Steel up to 600 N/mm²	mm	1,5	1,5
Steel up to 800 N/mm²	mm	1,3	1,3
Non-ferrous metals up to 250 N/mm ²	mm	3	3
Cutting width	mm	5	5
Rad. of smallest curve	mm	245	245
Immersion Ø	mm	12	12
Cable with plug	m	5	5
Weight according to EPTA	kg	1,7	1,7

FEIN BENEFITS

- + High-strength blades make it ideal for reinforcement profiles in drywall construction and cutting stainless steel.

- Robust cutting head for stationary application. Machine can be very easily clamped in a vice.
 Left and right curve cuts and distortion-free cutting possible with just one continuous chip.
 High performance and powerful motor when it comes to the most difficult tasks. Suitable for folded spiral-seam pipes with 4 x 0.75 mm connecting folds
- Ideal for trimming profiled sections.
- Best suited for trimming and cutting.

 Motor with outstanding performance and stability.

 Cutting blade with excellent tool life.
- - 5 metre cable.
- Clean swarf removal prevents injuries or scratches on workpieces.
- Stainless steel up to 1.5 mm. Wide range of accessories.

SUPPLIED

1 cutter blade (31308123008) fitted, 1 pair of cutting jaws (31308113009) fitted

1 cutter blade (31308123008) fitted, 1 pair of cutting jaws (31308113009) fitted, 1 permanent marker (32133037000), 1 painter's tape (32133038000), 1 metre rule (18750283000), 1 tool case (L-BOXX 136)

Part number	7 230 33 61 00 0	7 230 33 62 00 0
EAN	4014586874807	4014586900018

ACCESSORIES FOR (A)BSS 1.6 E, BSS 1.6 CE



CUTTING BLADE

for steel sheet up to 400 N/mm²

Plate thickness

Part number mm 1,6 3 13 08 150 00 9



BLADE FOR CURVES

for steel sheet up to 400 N/mm²

Plate thickness Part number 3 13 08 151 00 8



CUTTING BLADE

for stainless steel up to 800 N/mm²

0.0	7 17 00 152 00 1
mm	Part number
Plate thickness	

ACCESSORIES FOR (A)BSS 1.6 E



CUTTING BARS

1 pair

Part number
3 13 08 153 01 4

ACCESSORIES FOR BSS 1.6 CE



CUTTING BARS

1 pair

Part number
3 13 08 153 02 0

ACCESSORIES FOR BSS 2.0 E



CUTTING BLADE

for steel sheet up to 800 N/mm²

Plate thickness

Part number 3 13 08 123 00 8 1,3



CUTTING BARS

Pack of 2

Part number
3 13 08 113 00 9



BLADE PIN

Part number
3 13 08 111 00 2



CHOP SAWS

Saw safely with speed and precision with the chop saw for metal.



172

PIPE SAWS

Optimum cutting speed with minimal wear.



173




BEVELLER

For efficiently producing exposed and functional edges as well as rounding edges.



PIPE MILLING MACHINE

Cost-effective pipe machining with high cutting performance.



6 CHOP SAWS

MKAS 355



SUPPLIED

1 saw blade for construction steel, 1 combination wrench: 6 mm hexagon socket and PH2 cross recess, 1 socket head wrench 8 mm, 1 pair of extra carbon brushes

For accessories, see page 172

Saw safely with speed and precision with the chop saw for metal.

Current/Voltages	V	230
Input	W	1 800
Output	W	1 050
Speed, no load	rpm	1,300
Saw blade Ø	mm	355
Holder mandrel	mm	25,4
Max. cutting depth, square	mm	120
Max. cutting depth, square at 45°	mm	90
Max. cutting depth, round	mm	100
Max. cutting depth, round at 45°	mm	90
Cable with plug	m	4
Weight	kg	24,4

Part number	7 236 54 60 00 0
EAN	4014586894447

FEIN BENEFITS

- + Up to 100 % non-sparking: cold cuts for safe working without dust.
- + Fast and precise dividing: maximum work progress with minimal rework.
- A versatile all-rounder: the right saw blade for every material.
- + Angle can be set to 0–45° for mitre cuts.
 + Quick clamping device for table clamp.
- + Depth stop
- Swarf collecting vessel.
- + Dead man's switch.

GENERAL ACCESSORIES



SAW BLADE For construction steel.

Ø		Thickness	Thickness			
mm	nm Teeth		Part number			
355	66	2,2	6 35 02 301 00 0			



SAW BLADE

For aluminium, copper, brass and other non-ferrous metals.

Ø		Thickness	
mm	Teeth	mm	Part number
355	80	2,8	6 35 02 302 00 0



SAW BLADE For stainless steel.

Ø		Thickness	
mm Teeth		mm	Part number
 355	100	2,4	6 35 02 303 00 0



SAW BLADE For flat steel.

Ø		Thickness	
mm	Teeth	mm	Part number
355	90	2,4	6 35 02 304 00 0



MAGBRUSH

Practical tool with high magnetic force for quick and easy collection of magnetic metal swarf.

Part number 6 42 01 005 01 0



CUTTING PASTE

Lubricating agents for working on sheet metals.

Part number 3 21 32 046 00 0





		STS 325 R	ASTXE 649-1
		Compressed air hacksaw for pipes and profiled sections.	Powerful hacksaw for pipes and profiled sections with continuously variable speed adjustment.
PAGE		17	4 174
Electric drive			•
Pneumatic drive			•
Adjustable stroke			•
Input	W		750
Operating pressure	bar		6
Air consumption	m³/min	1,	5
Output	W	1 10	0 480
Strokes	rpm	33	0 100 - 350
Stroke of blade	mm	6	0 60
Pipes up to Ø	mm	440	* 440 *
profiles up to W x H	mm	290 x 50	0 290 x 550
Cable with plug	m		2,5
Weight according to EPTA	kg	7,	2 6,4

[•] included * With chain extension.

6 PIPE SAWS

STS 325 R



SUPPLIED

2 saw blades, 1 set of keys, 1 additional handle, 1 hose coupling

For accessories, see page 175

Compressed air hacksaw for pipes and profiled sections.

Operating pressure	bar	6
Air consumption	m³/min	1,5
Output	W	1100
Strokes	rpm	330
Stroke of blade	mm	60
Pipes up to Ø	mm	440 *
profiles up to W x H	mm	290 x 500
Weight according to EPTA	kg	7,2

Part number	7 534 08 00 00 0
EAN	4014586855639

FEIN BENEFITS

- + Ideally suited for trimming pipes and shaped section made of steel, cast-iron, autoclaved aerated concrete and plastics.
- + Clamp and feed device available for profiles and pipes from Ø 80 mm to Ø 400 mm.
- Adjustable clamping devices permit mitre cuts up to 45° as well.
- Clamp and feed device.
- + Adjustable clamping fixtures.
- * With chain extension.

ASTXE 649-1



SUPPLIED

2 saw blades, 1 additional handle, 1 set of keys

For accessories, see page 175

Input	W	750
Output	W	480
Strokes	rpm	100 - 350
Stroke of blade	mm	60
Pipes up to Ø	mm	440 *
profiles up to W x H	mm	290 x 550
Cable with plug	m	2,5
Weight according to EPTA	kg	6,4

Powerful hacksaw for pipes and profiled sections with continuously variable speed adjustment.

Part number	7 234 23 00 23 0
EAN	4014586858500

FEIN BENEFITS

- + Ideally suited for trimming pipes and shaped section made of steel, cast-iron, autoclaved aerated concrete and plastics.
- + Clamp and feed device available for profiles and pipes from Ø 80 mm to Ø 400 mm.
- Especially suitable for sandwich material and layers of different materials.
- + Variable electronic speed control for optimum cutting speed.
- Adjustable clamping devices permit mitre cuts up to 45° as well.
- * With chain extension.

SAW BLADES

	NF metals and steel 400 N/mm²	Steel above 400 N/mm² and grey cast iron	 Miscellaneous	Length mm	Tooth spacing mm	Thickness mm	Weight (net) kg	Material	Part number
	х	Х	≤ dia. 80	200	1.0	1.5	0.06	HSS	6 35 03 067 00 6
	×	х	≤ dia. 80	200	1.6	1.5	0.06	HSS	6 35 03 066 00 2
	×	х	≤ dia. 170 ¹	300	1.6	1.5	0.06	HSS	6 35 03 063 00 7
•••	×	х	≤ dia. 260 ¹	400	1.6	1.5	0.125	HSS	6 35 03 064 00 5
/	×	х	≤ dia. 350 ²	500	1.8	2.0	0.18	HSS	6 35 03 072 00 2
	×	х	≤ dia. 440 ²	600	1.8	2.0	0.21	HSS	6 35 03 073 00 6
	х	х		300	2.1	1.5	0.08	HSS	6 35 03 070 00 0
	х		*	530	2.1	1.5	0.170	HSS	6 35 03 069 00 8
	× (AL)		Plastic	200	3.2	1.5	0.06	HSS	6 35 03 065 00 9
	× (AL)		Plastic	400	3.2	1.5	0.125	HSS	6 35 03 068 00 4
			PE pipes, porous concrete	300	6.3	1.5	0.08		6 35 03 071 00 9
			PE pipes, porous concrete *	530	6.3	1.5	0.170		6 35 03 040 00 3

HD SAW BLADES

Special saw blades for working with steel and stainless steel. HD saw blades deliver impressively long service lives and rapid sawing progress. They are well worth trying out.

	NF metals and steel 400 N/mm²	Steel above 400 N/mm² and grey cast iron	Miscellaneous	Length mm	Tooth spacing mm	Thickness mm	Weight (net) kg	Material	Part number
	х	Х	≤ dia. 170 ¹	300	1.6	2.0	0.08	HSS	6 35 03 093 00 4
/	х	Х	≤ dia. 350 ²	500	1.8	2.0	0.18	HSS	6 35 03 099 00 5
	х	Х	≤ dia. 325 *	530	2.1	1.6	0.17	HSS	6 35 03 100 00 6
/	х	Х	≤ dia. 260 ¹	400	2.1	2.0	0.175	HSS	6 35 03 094 00 2
/	Х	Х	≤ dia. 260 ¹	400	3.2	2.0	0.175	HSS	6 35 03 095 00 6
	х	Х	≤ dia. 440 ²	600	1.8	2.0	0.21	HSS	6 35 03 098 00 1

TD SAW BLADES

TD saw blades are suited to wet and dry cutting.
They deliver impressively short cutting times and clean cutting results.

	For ductile cast-iron pipes, even with cement mortar lining and grey cast iron pipes.	Pipe diameter (DN) mm	Length mm	Lining length mm	Thickness mm	Weight kg	Part number
	х	80-150 ³	320	260	2.2	0.110	6 35 03 096 01 8
•••	х	80-300 ³	490	430	2.9	0.220	6 35 03 097 01 2

 $^{^{\}star}$ only with saw blade guide 9 06 06 002 00 9 1 with FEIN clamping and feed device 9 07 02 005 00 0 or clamping device 9 07 02 004 00 6 2 only with chain extension up to diameter of 440 mm, chain 3 02 31 003 00 3 and bolt 3 02 16 130 00 4 are also needed 3 can only be used with FEIN clamping and feed device 9 07 02 005 00 0

6 PIPE SAWS

GENERAL ACCESSORIES



FEIN CLAMP AND FEED DEVICE

(W x D x H) 280 x 285 x 395 mm, for pipes and circular material with an outside dia. of 80 mm to 400 mm.

> Part number 9 07 02 005 00 0



CLAMPING FIXTUREFor pipes up to Ø 159 mm and for mitre cuts.

Part number 9 07 02 001 00 1



CLAMPING FIXTURE

For pipes from \oslash 100 mm up to 325 mm, only with extension of the chain up to \oslash 440 mm, chain 3 02 31 003 00 3 and bolt 3 02 16 130 00 4 necessary.

> Part number 9 07 02 004 00 6



CLAMPING FIXTURE

For profiles up to 290 mm width at max height 550 mm.

Part number 9 07 02 003 00 8



SAW BLADE GUIDE

For pipes up to \varnothing 325 mm only with saw blade 530 mm length, guide to the centre of the pipe.

Part number 9 06 06 002 00 9

SPLITTER WEDGE

Prevents the jamming of the saw blade.

Part number 6 33 05 006 00 8

PROTECTIVE STEEL JAWS

for avoiding damage to the surface of the pipe, 4 pieces required

Part number 3 13 27 064 00 8



CLEANING BLOCK

Rhombus for cleaning the carbide tools and diamond-coated tools.

> Part number 6 37 19 007 01 0

ACCESSORY STS 325 R

HOSE COUPLING

Part number 4 11 40 004 00 7









AKFH 18-5 AS

Powerful cordless beveller for perfectly preparing subsequent coatings for flexible jobs in the workshop and on the construction site.

KFH 17-8 R

Universal beveller with booster technology for perfectly preparing welded seams and preparing subsequent coatings.

KFH 17-15 R

Universal beveller with booster and spring technology for perfectly preparing welded seams.

	the	construction site.	subsequent coatings.		
PAGE		178	179	179	
Bevel length of up to 5 mm at 45°	0	+	++	++	
Bevel length of up to 8 mm at 45	•		+	++	
Bevel length of up to 15 mm at 45	5°			+	
Installation work		++	+	+	
Workshop jobs		+	++	++	
Soft start		•	•	•	
Restart protection		•	•	•	
Blockage monitoring		•	•	•	
Electronic overload protection		•	•	•	
Speed preselection		•	•	•	
Booster technology			•	•	
Spring technology				•	
Quick-change cutter system	,		•	•	
Input	W		1 700	1 700	
Output	W		1 000	1 000	
Battery voltage	V	18			
Battery compatibility		Li-ion/ProCORE Li-ion			
Battery interface		18 V AMPShare			
Speed, no load	rpm	2,400 - 7,500	2,300 - 7,500	2,300 - 7,500	
Max. bevel length at 45°	mm	5	8	15	
Max. bevel height at 45°	mm	3,5	5,7	10,6	
Radius		1.2 / 2,5 mm	2 / 3 / 4 mm	2 / 3 / 4 mm	
Support plate diameter	mm	98	118	137	
Bevel angle		45°	30° / 37.5° / 45° / 60°	30° / 37.5° / 45° / 60°	
Milling head configuration		3x SX tip	3x KX tip	3 x 2 KX tip	
Weight according to EPTA	kg		4,6	6,4	
Weight without storage battery	kg	2,52			

⁺ suitability

⁺⁺ optimal suitability

included

AKFH 18-5 AS

AKFH 18-5 AS BASIC CHAMFER

AKFH 18-5 AS BASIC CHAMFER **SET WITH 1X 8 AH ProCORE**

AKFH 18-5 AS BASIC CHAMFER SET WITH 2X 8 AH ProCORE





AMP Share BATTERY

AMP Share



Powerful cordless beveller for perfectly preparing subsequent coatings for flexible jobs in the workshop and on the construction site.



Powerful cordless bevelling machine coupled with optimum accessories to produce a 45° chamfer. For perfectly preparing subsequent coatings for flexible working in the workshop and on the construction site.



Powerful cordless bevelling machine coupled with optimum accessories to produce a 45° chamfer. For perfectly preparing subsequent coatings for flexible working in the workshop and on the construction site. Includes a ProCORE 8 Ah AS battery and a GAL 18 V-160 AS



Powerful cordless bevelling machine coupled with optimum accessories to produce a 45° chamfer. For perfectly preparing subsequent coatings for flexible working in the workshop and on the construction site. Includes two ProCORE 8 Ah AS batteries and a GAL 18 V-160 AS charger.

				Criarger.	
Battery voltage	V	18	18	18	18
Battery compatibility		Li-ion/ProCORE Li-ion	Li-ion/ProCORE Li-ion	Li-ion/ProCORE Li-ion	Li-ion/ProCORE Li-ion
Battery interface		18 V AMPShare	18 V AMPShare	18 V AMPShare	18 V AMPShare
Speed, no load	rpm	2,400 - 7,500	2,400 - 7,500	2,400 - 7,500	2,400 - 7,500
Max. bevel length at 45°	mm	5	5	5	5
Max. bevel height at 45°	mm	3,5	3,5	3,5	3,5
Bevel angle		45°	45°	45°	45°
Radius		1.2 / 2,5 mm			
Milling head configuration		3x SX tip	3x SX tip	3x SX tip	3x SX tip
Support plate diameter	mm	98	98	98	98
Weight without storage battery	kg	2,52	2,52	2,52	2,52

FEIN BENEFITS

- + For the production of bevels and radii on flat materials, sheet metals and containers, of inner and outer edges, contour shapes and for rounding off holes
- + Unpack the tool and off you go! The set is designed to produce chamfers on flat materials, sheet metals and containers and to produce inner and outer edges as well as contours.
- High sanding capacity requiring little force and infinitely variable speed setting for different materials.
- Ergonomic thanks to low weight and compact design.
- FEIN PowerDrive motor delivers good performance and long service life.
- Extensive user protection features include soft start, restart protection, jam monitoring and electronic overload protection.
- Compatible with all 18 V AMPShare ProCORE batteries and chargers for even more power and flexibility. Also suitable for 18 V Bosch Professional cordless devices.
- ProCORE Li-Ion battery with high-power cells, charge status indicator and "Electronic Cell Protection" (ECP). ECP protects against overload, overheating and total discharge.
- COOLPACK 2.0 technology delivers a 135 % longer battery life and therefore makes longer operating times possible. Ideally equipped for every job. Mobile working with the L-BOXX system.

State-of-the-art cell technology and intelligent battery management deliver 87% more power than with conventional batteries.

SUPPLIED

1 tool incl. 45 milling head (without guide roller, without indexable tips), 3 x clamping screws SX, 1 x copper paste, 1 x 4 mm socket head wrench, 1 x TX 15 Torx screwdriver. 1 plastic tool case (L-BOXX 238)

1 AKFH 18-5 AS including 45° milling head, 3 x clamping screws SX. 1 x 4 mm socket head wrench, 1 x TX 15 Torx screwdriver, 1 cutting paste, 1 pack of 10 SX indexable tips, chamfer for universal use 1 guide roller, 21.69 mm in diameter for 45° chamfers and a radius of 2.5 mm. 1 plastic tool case (L-BOXX 238)

1 AKFH 18-5 AS including 45° milling head, 3 x clamping screws SX. 1 x 4 mm socket head wrench, 1 x TX 15 Torx screwdriver, 1 cutting paste, 1 pack of 10 SX indexable tips, chamfer for universal use 1 guide roller, 21.69 mm in diameter for 45° chamfers and a radius of 2.5 mm, 1 ProCORE 18 V 8.0 Ah battery pack, 1 x GAL18 V-160 AS rapid charger, 1 plastic tool case (L-BOXX 238)

1 AKFH 18-5 AS including 45° milling head, 3 x clamping screws SX, 1 x 4 mm socket head wrench, 1 x TX 15 Torx screwdriver, 1 cutting paste, 1 pack of 10 SX indexable tips, chamfer for universal use 1 guide roller, 21.69 mm in diameter for 45° chamfers and a radius of 2.5 mm, 2 ProCORE 18 V 8.0 Ah battery pack, 1 x GAL18 V-160 AS rapid charger, 1 plastic tool case (L-BOXX 238)

Part number	7 138 02 62 00 0	7 138 05 61 00 0	7 138 05 62 00 0	7 138 05 63 00 0
EAN	4014586898209	4014586898247	4014586898254	4014586898261

6

KFH 17-8 R



SUPPLIED

1 tool (without milling head, without guide roller, without indexable tips), 3 x clamping screws SX, 1 x copper paste, 1 socket head wrench 5 mm, 1 x TX 15 Torx screwdriver, 1 plastic carrying case

EAN

For accessories, see page 180

Universal beveller with booster technology for perfectly preparing welded seams and preparing subsequent coatings.

4014586892696

Input	W	1 700
Output	W	1 000
Speed, no load	rpm	2,300 - 7,500
Max. bevel length at 45°	mm	8
Max. bevel height at 45°	mm	5,7
Bevel angle		30° / 37.5° / 45° / 60°
Radius		2/3/4mm
Milling head configuration		3x KX tip
Support plate diameter	mm	118
Cable with plug	m	4
Weight according to EPTA	kg	4,6
Part number		7 238 16 61 00 0

FEIN BENEFITS

- + Milling performance improved by 30 80 % and vastly reduced vibrations thanks to new booster technology.
- + FEIN ErgoGrip: unique, ergonomic concept of two-handed operation for fatigue-free working (patent pending).
- + Efficient quick-change cutter system for minimal interruptions.
 + Effective material removal requiring little force.
- Extensive user protection features include soft start, restart protection, jam monitoring and electronic overload protection.

KFH 17-15 R



SUPPLIED

1 tool (without milling head, without guide roller, without indexable tips), 6 x clamping screws, 1 x copper paste, 1 socket head wrench 5 mm, 1 x TX 15 Torx screwdriver, 1 plastic carrying case

For accessories, see page 180

Universal beveller with booster and spring technology for perfectly preparing welded seams.

Input	W	1 700
Output	W	1 000
Speed, no load	rpm	2,300 - 7,500
Max. bevel length at 45°	mm	15
Max. bevel height at 45°	mm	10,6
Bevel angle		30° / 37.5° / 45° / 60°
Radius		2 / 3 / 4 mm
Milling head configuration		3 x 2 KX tip
Support plate diameter	mm	137
Cable with plug	m	4
Weight according to EPTA	kg	6,4

Part number	7 238 18 61 00 0
EAN	4014586892733

- + Milling performance improved by 30 80 % and vastly reduced vibrations thanks to new booster technology.
- Spring technology: absorption of rotational forces and therefore improved operational safety from lowvibration working.
- + FEIN ErgoGrip: unique, ergonomic concept of two-handed operation for fatigue-free working (patent pending).
- + Extensive user protection features include soft start, restart protection, jam monitoring and electronic overload protection.
- + Efficient quick-change cutter system for minimal interruptions.
- + Effective material removal requiring little force.

GET THE RIGHT ACCESSORY ONE STEP AT A TIME.

FOR KFH 17-8 (R) AND KFH 17-15 (R)





Select milling head.Which milling head? Or radius?

FOR KFH 17-8 R



FOR KFH 17-15 R
















Select indexable tip.

STEP 02

Chamfer or radius? What radius? For what material?




For non-ferrous metals (e.g. aluminium, copper, brass) and plastics.

For hard steels, fine-grained steels and high-alloy steels.






















Please note: The system of colours indicates the right accessories.


FOR AKFH 18-5



^{*} Both guide rollers are needed when using the indexable tips 16 times.



^{*} Both guide rollers are needed when using the indexable tips 16 times.



6 BEVELLER

ACCESSORY AKFH 18-5



SX INDEXABLE TIP

Bevel for universal use (steel, stainless steels which can be milled).

No. in pack

pcs	Part number
10	6 43 02 001 01 0



SX INDEXABLE TIP

Bevel for non-ferrous metals and soft materials (aluminium, copper, plastics,..).

No. in pack

pcs	Part number
10	6 43 02 007 01 0



SX INDEXABLE TIP

1.2 mm radius for universal use (steel, stainless steels which can be milled).

No. in pack

pcs	Part number
10	6 43 02 008 01 0



SX INDEXABLE TIP

1.2 mm radius for non-ferrous metals and soft materials (aluminium, copper, plastics,..).

No. in pack

pcs	Part number
10	6 43 02 009 01 0



SX INDEXABLE TIP

2.5 mm radius for universal use (steel, stainless steels which can be milled).

No. in pack

pcs	Part number
10	6 43 02 002 01 0



SX INDEXABLE TIP

2.5 mm radius for non-ferrous metals and soft materials (aluminium, copper, plastics,..).

No. in pack

pcs	Part number
10	6 43 02 010 01 0



SX CLAMPING SCREW

For SX indexable tip.

No. in pack

pcs	Part number
10	3 13 50 076 00 0



GUIDE ROLLER

19.80 mm diameter for 45° bevel and 1.2 mm radius. In order to be able to use the two radius-cutting edges in each position (8x), both guide rollers (small and large diameters) are needed so that the indexable radius cutter can then be used 16 times.

Part number 6 43 03 006 01 0



GUIDE ROLLE

26.10 mm diameter for 45° bevel and 1.2 mm radius. In order to be able to use the two radius-cutting edges in each position (8x), both guide rollers (small and large diameters) are needed so that the indexable radius cutter can then be used 16 times.

Part number 6 43 03 007 01 0



GUIDE ROLLER

21.69 mm diameter for 45° bevel and 2.5 mm radius.

Part number 6 43 03 001 01 0

ACCESSORY KFH 17-8 R



CUTTER

Tool with 3 cutters for 30° bevel.

Part number 6 43 01 002 01 0



CUTTER

Tool with 3 cutters for 45° bevel and radius.

Part number 6 43 01 001 01 0



CUTTER

Tool with 3 cutters for 60° bevel.

Part number 6 43 01 007 01 0

ACCESSORY KFH 17-15 R



CUTTER

Tool with 3 x 2 cutters for 30° bevel.

Part number 6 43 01 004 01 0



CUTTER

Tool with 3 x 2 cutters for 45° bevel and radius.

Part number 6 43 01 003 01 0



CUTTER

Tool with 3 x 2 cutters for 60° bevel.

Part number 6 43 01 008 01 0

ACCESSORY KFH 17-8 R, KFH 17-15 R



KX INDEXABLE TIP

Chamfer for high-strength steels, fine-grained steels, special steels. \\\\

No. in pac

pcs	Part number
10	6 43 02 011 01 0



KX INDEXABLE TIP

Bevel for non-ferrous metals and soft materials (aluminium, copper, plastics,..).

No. in pack		
pcs	Part number	
10	6 43 02 003 01 0	



KX INDEXABLE TIP

Bevel for universal use (steel, stainless steels which can be milled).

No. in pack	
pcs	Part number
10	6 43 02 004 01 0



KX INDEXABLE TIP

2 mm radius for high-strength steels, fine-grained steels, special steels.

No. in pack	
pcs	Part number
10	6 43 02 013 01 0



KX INDEXABLE TIP

2 mm radius for non-ferrous metals and soft materials (aluminium, copper, plastics,..).

No. in pack	
pcs	Part number
10	6 43 02 018 01 0



KX INDEXABLE TIP

2 mm radius for universal use (steel, stainless steels which can be milled).

Part number
6 43 02 012 01 0



KX INDEXABLE TIP

3 mm radius for high-strength steels, fine-grained steels, special steels.

No. in pack	
pcs	Part number
10	6 43 02 014 01 0



KX INDEXABLE TIP

 $3\ mm$ radius for non-ferrous metals and soft materials (aluminium, copper, plastics,..).

No. in pack	
pcs	Part number
10	6 43 02 005 01 0



KX INDEXABLE TIP

 $3\ \text{mm}$ radius for universal use (steel, stainless steels which can be milled).

No. in pack	
pcs	Part number
10	6 43 02 006 01 0



KX INDEXABLE TIP

 $4\ \mbox{mm}$ radius for high-strength steels, fine-grained steels, special steels.

No. in pack	
pcs	Part number
10	6 43 02 017 01 0



KX INDEXABLE TIP

 $4\ mm$ radius for non-ferrous metals and soft materials (aluminium, copper, plastics,..).

No. in pack	
pcs	Part number
10	6 43 02 016 01 0



KX INDEXABLE TIP

 $4\ mm$ radius for universal use (steel, stainless steels which can be milled).

pcs	Part number
10	6 43 02 015 01 0



KX CLAMPING SCREW

For KX indexable tip.

No. in pack	
pcs	Part number
10	3 13 50 075 00 0



GUIDE ROLLER

29.90 mm diameter for 30° and 37.5° bevel; no radius.

Part number
6 43 03 002 01 0



GUIDE ROLLER

26.30 mm diameter for 45° bevel; no radius.

Part number
6 43 03 003 01 0



GUIDE ROLLER

25.00 mm diameter for 60° bevel; no radius.

Part number
6 43 03 008 01 0



GUIDE ROLLER

26.65 mm diameter for 45° bevel and 2 mm radius. In order to be able to use the two radius-cutting edges in each position (8x), both guide rollers (small and large diameters) are needed so that the indexable radius cutter can then be used 16 times

Part number 6 43 03 009 01 0



GUIDE ROLLER

32.30 mm diameter for 45° bevel and 2 mm radius. In order to be able to use the two radius-cutting edges in each position (8x), both guide rollers (small and large diameters) are needed so that the indexable radius cutter can then be used 16 times.

Part number 6 43 03 010 01 0



GUIDE ROLLER

28.55 mm diameter for 45° bevel and 3 mm radius.

Part number
6 43 03 004 01 0



GUIDE ROLLER

27.55 mm diameter for 45° bevel and 4 mm radius.

Part number 6 43 03 011 01 0

6 PIPE MILLING MACHINE

FEIN pipe milling cutters – cost-effective pipe machining with high cutting performance.

The pipe cutting industry the world over is familiar with FEIN pipe milling machines. They can be used for everything from cutting to length before laying to cutting pipes which have already been laid. In addition, the FEIN pipe milling machines boast impressive, robust quality and

outstanding efficiency. They are ideally suited to machining cast pipes or steel pipes for oil, gas and water supplies that are used in pipelines, public supply networks, power plants, industrial systems and container construction, for example. Optimised technology ensures good cutting performance.

Tried and tested technology for perfect results.

The system comes into its own under tough conditions, e.g. pipe fractures.

Adapting to different pipe materials by selecting the right gear ratio produces ideal cutting and feed speeds, enabling the cost-effective use of HSS and carbide tools.




Key advantages at a glance:

- + Robust tool design, powerful motors and high-quality materials make the tool ideal for use under extreme conditions.
- + Electric pipe milling machines can even be used at very low sub-zero temperatures.
- + Electric pipe milling machines with feed and return (return only in load-free operation).
- + Can be used flexibly for pipes of between 250 mm and 3 000 mm.
- + Profile and separating cuts with form cutter or saw blade.
- + Precise directional stability and exact cut thanks to the two-chain system, adjustable track setting and double chain tension.
- + Crack-free pipe ends deliver perfect results when welding. Reason: perfect cutting and sawing results are achieved due to the good sanding capacity, high tool quality and the fact that there is no misalignment.
- + Easy installation thanks to optimised handling.
- + Available in two gearbox variants: different feed and speed levels guarantee a cutting speed to suit various materials (recommendation: steel pipe slow cutting speed, cast pipe fast cutting speed).
- + Precise and safe working as feed can be switched off and shut down (RSG/RDG 1 500 pipe milling cutters).
- + Tool is shut down by slipping clutch, meaning that it is protected when the gearbox is overloaded.
- + Extensive FEIN accessories range.



Overview of tools



FEIN electric pipe milling machines:

Protection class I. Protection code IP X4. In conjunction with the controlgear combination:

- + Self-start lock ensures safe operations.
- + Overload protection for the three-phase motor. Produced and tested in accordance with EN 62841.

RSG VERSION:

- + For universal use.
- + Three-phase motor with protection from explosion and moisture.

RSG EX VERSION:

- + Particularly well suited for cutting oil and gas pipes not transporting material.
- + Three-phase motor with protection from explosion and moisture with additional switch with explosion protection.

FEIN pneumatic pipe milling machines:

RDG VERSION:

- + Protection for work on water, oil and gas pipes not transporting material thanks to pneumatic drive.
- + Suitable for use in potable water applications.
- + Motor drive parts made from stainless material.
- + The compressed air motor's fins are resistant to swelling.
- + Can even run dry for brief periods.

WE ARE MORE THAN HAPPY TO PROVIDE TECHNICAL ADVICE.



FEIN VersaMAG

Compact and powerful permanent magnet with vice for clamping various components on magnetic surfaces without the need for any tools.

190 ACCESSORIES

Practical and universal accessories. And there's more as with FEIN there is virtually no end to how much the magnetic clamping force can be extended.



191

The new FEIN VersaMAG system.

A POWERFUL MOBILE CLAMPING TOOL.





The new FEIN VersaMAG system brings a new dimension of flexibility into the world of clamping. The powerful permanent magnet is the foundation of the FEIN VersaMAG system.

Thanks to the permanent magnet with vice, vices are no longer shackled to the workbench, but can be used precisely in those places where rapid clamping used to be major challenge: on construction sites and in workshops, on vertical levels – and most importantly if you "just need to quickly do something".

Simple, mobile, flexible. And it offers the perfect solution so you no longer have to choose between a secure hold and rapid success.

FLEXIBLE.

Can be used flexibly and at speed in a wide variety of areas thanks to the magnet.

SITS, FITS, NO WOBBLING.

30% magnetic bias for precise alignment of the magnetic vice.



WHO HASN'T BEEN THERE?



DANGEROUS

Staff swiftly machine materials by hand.



INFLEXIBLE

Your vice is permanently affixed and taking up space on the work bench.



LOST TIME

Your vice is usually located somewhere you don't need it.









PROBLEM-SOLVER.

Safe and clean working on construction sites and in workshops. Work accidents are reduced thanks to the VersaMAG.

PRODUCTIVITY.

Suitable for any workplace. Results-oriented working.



MODULAR.

Clamping system can be extended to master any challenge.

HOLDS SIMPLY AND SECURELY.

Up to 7800 N holding force (as of 12 mm) for reliable clamping on all magnetic surfaces thanks to an innovative 2-rotor system – even when working with thin sheet metals.

ADDED VALUE FOR YOU



RISK OF INJURY IS MINIMISED!

Safe and simple clamping of the components. Work accidents are minimised.



TIME SAVINGS!

Mobile and flexible use enables materials to be changed directly on site.



INCREASED PRODUCTIVITY!

Setup times are reduced thanks to the VersaMAG.



SIMPLE OPERATION!

The worker pays more attention to securing the workpiece thanks to the simple clamping principle.



QUALITY!

Workpieces are always securely fixed in all locations. Professional-quality machining can be achieved at all times.



INDIVIDUAL WORKING STATION SYSTEM

Compatible accessories for versatile

7 FEIN VersaMAG

FEIN VersaMAG



SUPPLIED

1 x permanent magnet, 1 x mounting plate, 1 lashing strap

For accessories, see page 191

The powerful permanent magnet is the foundation of the FEIN VersaMAG system. With an integrated mounting plate, the permanent magnet guarantees success in every application.

Magnetic holding power	Ν	7,800
Magnetic foot dimensions	mm	212 x 70
Weight according to EPTA	kg	3,75
Part number		7 21 72 050 02 0

raitifiumber	3 21 /2 050 02 0
EAN	4014586461311

FEIN BENEFITS

- Mobile, flexible and swift use. Adapts to every workstation thanks to the compact design and extranarrow permanent magnet.
- Optimises every workstation: clean and reliable working with versatile application options.
- Modular system: the unique modular system ensures a secure hold in a very wide range of work situations and the right accessories can be added at any time.
- Up to 7800 N holding force for reliable clamping on all magnetic surfaces thanks to an innovative 2-rotor system – evren when working with thin sheet metals (from a thickness of 4 mm).
- Clamping in tight sports or on vertical levels? Not a problem with the compact design and extra-narrow permanent magnet.
- + 30 % magnetic bias for precise alignment of the permanent magnet.

FEIN VersaMAG VISE SET



SUPPLIED

 $1\,x$ permanent magnet, $1\,x$ mounting plate, $1\,x$ vice, $1\,x$ 3 mm socket head wrench, 1 lashing strap

For accessories, see page 191

Compact and powerful permanent magnet with vice for clamping various components on magnetic surfaces without the need for any tools.

Jaw height	mm	40
Jaw width	mm	100
Magnetic holding power	N	7,800
Magnetic foot dimensions	mm	212 x 70
Weight according to EPTA	kg	7,25

Part number	9 07 01 003 02 0
EAN	4014586896564

FEIN BENEFITS

- Mobile, flexible and swift use. Adapts to every workstation thanks to the compact design and extranarrow permanent magnet.
- + Optimises every workstation: clean and reliable working with versatile application options.
- Modular system: the unique modular system ensures a secure hold in a very wide range of work situations and the right accessories can be added at any time.
- + The vice has a clamping range of 108 mm and a jaw width of 100 mm.
- Interchangeable clamping jaws of various heights for clamping larger materials such as sheet metal and pines
- Up to 7800 N holding force for reliable clamping on all magnetic surfaces thanks to an innovative 2-rotor system – even when working with thin sheet metals (from a thickness of 4 mm).
- Clamping in tight sports or on vertical levels? Not a problem with the compact design and extra-narrow permanent magnet.
- + 30 % magnetic bias for precise alignment of the permanent magnet.
- Secure clamping of components for further machining with various power tools, e.g. angle grinders, drill/ drivers, saws, MULTIMASTER etc.

FEIN VersaMAG CORE DRILLING SET MK3



SUPPLIED

 $1\,x$ permanent magnet, $1\,x$ mounting plate, $1\,x$ vice, $1\,x$ 3 mm socket head wrench, 1 lashing strap, 1 best of core drilling set (6x core drills, HSS diameters of 12, 14, 16, 18, 20, 22 mm), $2\,x$ 100 mm centring pins, $1\,x$ coolant pump, $1\,x$ 3/4 in Weldon mounting shaft MK3 (Ø 12 - 65 mm), 1 plastic tool case (L-BOXX 238)

For accessories, see page 191

The FEIN VersaMAG core drilling set is the perfect combination of the fastest core drilling result and tool-free flexible clamping with the FEIN VersaMAG vice. Perfectly suited to working on table / box column drills.

Jaw height	mm	40
Jaw width	mm	100
Magnetic holding power	N	7,800
Magnetic foot dimensions	mm	212 x 70
Weight according to EPTA	kg	12,85

Bestellnummer	9 07 01 007 00 0
EAN	4014586899749
Preis Euro zzgl. MwSt. [PK01]	799,00
Preis Euro inkl. MwSt. [PK01]	950,81

FEIN BENEFITS

Core drilling set: Produce large holes at speed and with ease. Cut working times by up to 40 % compared with conventional twist drilling. In combination with the FEIN VersaMAG vice, materials can be clamped on table / box column drills flexibly, intuitively and without the need for tools.

- + Mobile, flexible and swift use. Adapts to every workstation thanks to the compact design and extranarrow permanent magnet.
- + Optimises every workstation: clean and reliable working with versatile application options.
- + Modular system: the unique modular system ensures a secure hold in a very wide range of work situations and the right accessories can be added at any time.
- + 30 % magnetic bias for precise alignment of the permanent magnet.
- + The vice has a clamping range of 108 mm and a jaw width of 100 mm.
- **L-BOXX system:** Keep things stowed clearly, tidily and safely. Thanks to the tray for small parts, there is room for all accessories and the L-BOXXs can also be joined together and stacked with ease.

GENERAL ACCESSORIES



WELDING PLATE, DIAMETER 16 MM (FEIN VersaMAG)

Long-life welding plate with a hole diameter of 16 mm on a 250 x 250 mm plate. Plasmatised product for good surface protection, also features a prefabricated drill pattern for Demmeler and Siegmund elements.

Part number

9 07 01 005 02 0



60 MM OVERSIZE JAWS (VersaMAG)

Perfect for machining larger flat and round materials with a diameter of up to 100 mm.

Part number

3 24 22 420 01 0



FEIN VICE (VersaMAG)

The mobile vice can be fitted on the FEIN VersaMAG permanent magnet in a flash and brings a whole new dimension of flexibility to the world of clamping forces.

Part number

9 07 01 003 01 0





8 CORDLESS DUST EXTRACTOR

ASBS 18-10 AS

Light and compact, dust class L cordless dust extractor with high suction force for mobile use.



Battery voltage	V	18
Battery compatibility		Li-ion/ProCORE Li-ion
Battery interface		18 V AMPShare
Tank volume	l	10
Weight without storage battery	kg	4,7

Part number	9 26 04 203 01 0
EAN	4014586895734

FEIN BENEFITS

- + The rotary air flow ensures a powerful, constant suction power and therefore low dust levels and a clean working environment at all times.
- Different accessories and working without a dust bag make various wet and dry applications possible and help achieve perfect results
- help achieve perfect results.

 + The compact design and low weight make it easy to transport the device, therefore enabling use in a wide range of working environments.

 + Compatible with AMPShare/Bosch Professional
- Compatible with AMPShare/Bosch Professional 18 V batteries.

SUPPLIED

1 tool adapter, 1 floor nozzle, 1 groove nozzle, 1 hose, 1 distributor pipe, 1 set of suction pipes, 3 parts, 1 PES flat fold filter, 1 set of rollers, 4 parts

For accessories, see page 195

GENERAL ACCESSORIES



TOOL ADAPTER

Tool adapter with suction force regulation for 35 mm diameter hose, power tool connection (diameter 27 mm).

Part number

3 13 24 000 18 7



SUCTION HOSE

1.6 m suction hose for connecting to ASBS 18-10 cordless vacuum cleaner.

Part number

3 13 24 000 18 8



ELBOW

Suction pipe elbow for connecting to suction hose of ASBS 18-10 cordless vacuum cleaner.

Part number

3 13 24 000 18 9



SUCTION TUBE

 $3\mbox{-part}$ set of suction pipes for use with ASBS 18-10 cordless vacuum cleaner.

Part number

3 13 24 000 19 0



CREVICE NOZZLE

Crevice nozzle for difficult-to-reach spots, ideal for corners and grooves.

Part number

3 13 24 000 19 1



FLUTED FILTER

Filter for ASBS 18-10 cordless vacuum cleaner.

Part number

3 13 24 000 19 2



FLOOR NOZZLE

Floor nozzle for even dust extraction from floors.

Part number

3 13 24 000 19 3



SET OF ROLLERS

4-part set of rollers for ASBS 18-10 cordless vacuum cleaner.

Part number

3 13 24 000 19 4

8 WET / DRY DUST EXTRACTOR









FEIN DUSTEX 35 MX AC

Powerful, professional wet/ dry dust extractor of dust class M with fully automatic filter cleaning for attachment of various case systems including extensive including extensive accesso- accessories.

Powerful, professional

FEIN DUSTEX 35 LX AC Powerful, professional wet/ dry dust extractor of dust class L with fully automatic filter cleaning for attachment of various case systems including extensive including extensive

Powerful, professional

	ries.		accessori	es.		
PAGE		198	198	199	199	
Automatic start/stop		•	•	•	•	
Soft start		•	•	•	•	
Automatic filter cleaning		•		•		
Anti-static function		•	•	0	0	
Case storage		•	•	•	•	
Dust class		М	М	L	L	
Maximum power input	W	1 380	1 380	1 380	1 380	
Air flow	l/min	4,320	4,320	4,320	4,320	
Max. vacuum	hPa	254	254	254	254	
Tank volume	l	35	35	35	35	
Cable with plug	m	7,5	7,5	7,5	7,5	
Weight according to EPTA	kg	14,1	13,5	14,1	13,5	

o optional

included



FEIN DUSTEX 35 L SET

Powerful wet and dry dust extractor for connecting to power tools when working in the workshop and for assembly work, with large accessory set.



FEIN DUSTEX 35 L

Powerful wet and dry dust extractor for connecting power tools when working in the workshop and for assembly work.



FEIN DUSTEX 25 L SET

Compact, powerful wet and dry dust extractor for connecting to power tools when working in the workshop and for assembly work, with large accessory



FEIN DUSTEX 25 L

Compact, powerful wet and dry dust extractor for connecting to power tools when working in the workshop and for assembly

	9	set.	
200	200	201	201
•	•	•	•
•	•	•	•
0	0	0	0
L	L	L	L
1 380	1 380	1 380	1 380
4,320	4,320	4,320	4,320
253	253	253	253
32	32	22	22
7,5	7,5	7,5	7,5
9	9	8	8

WET / DRY DUST EXTRACTOR

FEIN DUSTEX 35 MX AC Powerful, professional wet/dry dust extractor of dust class M with fully automatic filter cleaning for attachment of various case systems including extensive accessories.



Maximum power input	W	1 380	
Air flow	l/min	4,320	
Max. vacuum	hPa	254	
Tank volume	l	35	
Cable with plug	m	7,5	
Sound pressure level	dB	67	
Weight according to EPTA	kg	14,1	

Part number	9 20 32 060 00 0
EAN	4014586883069

FEIN BENEFITS

- Approved for holding hazardous dusts of class M.
- Tool cases of various systems can be simply positioned on the extraction head and secured.
- Fully automatic filter cleaning (AC) makes the flat fold filter last longer for uninterrupted working.
- Ergonomic transport of the complete unit, including power tool and extractor, thanks to push bar and case and accessory attachment.
- Reliable suction of different types of dirt from liquids to fine dusts.
- With PES flat fold filter and electronic shut-off for outstanding wet extraction performance
- Auto start socket with switch-on delay to avoid power surges
- Infinitely variable suction force regulation on the extractor.
- The 7.5 m mains cable and 4 m hose provide a large working radius.
- + Anti-static function for preventing static charging during work - electrostatically discharging.

SUPPLIED

1 push bar, 1 PES flat fold filter, 1 disposal bag, 1x 4 m ES suction hose, diameter 35 mm, 1 tool collar with suction force regulation, 1 stepped collar, 2 suction pipes (metal), 1 combi nozzle with interchangeable inserts, 1 crevice nozzle, 1 suction brush, 1 elbow

For accessories, see page 202

FEIN DUSTEX 35 MX

Powerful, professional wet/dry dust extractor of dust class M for attachment of various case systems including extensive



W	1 380
l/min	4,320
hPa	254
l	35
m	7,5
dB	67
kg	13,5
	l/min hPa l m dB

Part number	9 20 31 060 00 0
EAN	4014586883052

FFIN RENEFITS


- + Approved for holding hazardous dusts of class M.
- Tool cases of various systems can be simply positioned on the extraction head and secured.
- Ergonomic transport of the complete unit, including power tool and extractor, thanks to push bar and case and accessory attachment.
- + Reliable suction of different types of dirt from liquids to fine dusts
- With PES flat fold filter and electronic shut-off for outstanding wet extraction performance.
- Auto start socket with switch-on delay to avoid power surges.
- Infinitely variable suction force regulation on the extractor.
- The 7.5 m mains cable and 4 m hose provide a large working radius.
- Anti-static function for preventing static charging during work - electrostatically discharging.

SUPPLIED

1 push bar, 1 PES flat fold filter, 1 premium fleece filter bag, 1x 4 mES suction hose, diameter 35 mm, 1 tool collar with suction force regulation, 1 stepped collar, 2 suction pipes (metal), 1 combi nozzle with interchangeable inserts, 1 crevice nozzle, 1 suction brush, 1 elbow

For accessories, see page 202

FEIN DUSTEX 35 LX AC



systems including extensive accessories.

Part number	9 20 30 060 00 0
EAN	4014586882994

FEIN BENEFITS

Powerful, professional wet/dry dust extractor of dust class L with fully automatic filter cleaning for attachment of various case

+	Tool cas	es or va	rious s	system	is car	ı be	simp	วเร	pos	IUOI	nec
	on the e	xtractio	n head	d and s	secur	ed.					
	_										


- Ergonomic transport of the complete unit, including power tool and extractor, thanks to push bar and case and accessory attachment.
- + Fully automatic filter cleaning (AC) makes the flat fold filter last longer for uninterrupted working.
- Reliable suction of different types of dirt from liquids to fine dusts.
- Approval for dust class L.
- With PES flat fold filter and electronic shut-off for outstanding wet extraction performance
- + Auto start socket with switch-on delay to avoid power surges.
- + Infinitely variable suction force regulation on the extractor.
- The 7.5 m mains cable and 4 m hose provide a large working radius.
- + Anti-static function for preventing static charging during work - electrostatically discharging thanks to optional suction hose 3 13 45 120 01 0.

SUPPLIED

1 push bar, 1 PES flat fold filter, 1 disposal bag, 1x 4 m suction hose, diameter 35 mm, 1 tool collar with suction force regulation, 1 stepped collar, 2 suction pipes (metal), 1 combi nozzle with interchangeable inserts, 1 crevice nozzle, 1 suction brush, 1 elbow

For accessories, see page 202

FEIN DUSTEX 35 LX





Maximum power input	W	1 380
Air flow	l/min	4,320
Max. vacuum	hPa	254
Tank volume	l	35
Cable with plug	m	7,5
Sound pressure level	dB	67
Weight according to EPTA	kg	13,5

Part number	9 20 29 060 00 0
EAN	4014586882956

FFIN RENEFITS

- + Tool cases of various systems can be simply positioned on the extraction head and secured.
- Ergonomic transport of the complete unit, including power tool and extractor, thanks to push bar and case and accessory attachment.
- + Reliable suction of different types of dirt from liquids to fine dusts.
- Approval for dust class L.
- With PES flat fold filter and electronic shut-off for outstanding wet extraction performance.
- Auto start socket with switch-on delay to avoid power surges.
- + Infinitely variable suction force regulation on the extractor.
- The 7.5 m mains cable and 4 m hose provide a large working radius.
- Anti-static function for preventing static charging during work - electrostatically discharging thanks to optional suction hose 3 13 45 120 01 0.

SUPPLIED

1 push bar 1 PES flat fold filter 1 premium fleece filter bag, 1x 4 m suction hose, diameter 35 mm, 1 tool collar with suction force regulation, 1 stepped collar, 2 suction pipes (metal). 1 combi nozzle with interchangeable inserts, 1 crevice nozzle, 1 suction brush, 1 elbow

For accessories, see page 202

WET / DRY DUST EXTRACTOR

FEIN DUSTEX 35 L SET



SUPPLIED

1 tool collar with suction force regulation, 1 combi nozzle with interchangeable inserts, 1x 4 m suction hose, diameter 35 mm, 1 suction brush, 1 elbow, 2 suction pipes (metal), 1 groove nozzle, 1 Flat-fold filter, 1 Fleece filter bag

For accessories, see page 202

Powerful wet and dry dust extractor for connecting to power tools when working in the workshop and for assembly work,

W	1 380
l/min	4,320
hPa	253
l	32
m	7,5
kg	9
	l/min hPa l m


Part number	9 20 36 060 00 0
EAN	4014586891903

FEIN BENEFITS

- Powerful turbine for 72 l/s volumetric flow and 253 mbar vacuum (240 V).
- Low noise level of 67 dB (A).
- The 7.5 m mains cable and 4 m hose provide a large working radius.
- + Anti-static function for preventing static charging during work - electrostatically discharging thanks to optional suction hose 3 13 45 120 01 0 and tool collar 3 13 45 300 01 0.
- Large, 360° rotating castors for optimum manoeuvrability even in tight spaces.

 + Tool collar with suction force regulation to set the
- suction power with ease.
- Auto start socket with switch-on delay to avoid power surges.
- Practical storage area with edge.
- Approval for dust class L.

FEIN DUSTEX 35 L





SUPPLIED

1x 4 m suction hose, diameter $35\ \text{mm}$, $1\ \text{tool}$ collar with suction force regulation, 1 Fleece filter bag, 1 Flat-fold filter

For accessories, see page 202

Maximum power input	W	1 380
Air flow	l/min	4,320
Max. vacuum	hPa	253
Tank volume	l	32
Cable with plug	m	7,5
Weight according to EPTA	kg	9

Part number	9 20 36 223 00 0
EAN	4014586891941

- Powerful turbine for 72 l/s volumetric flow and 253 mbar vacuum (240 V).
- Low noise level of 67 dB (A).
- The 7.5 m mains cable and 4 m hose provide a large working radius.
- Anti-static function for preventing static charging during work electrostatically discharging thanks to optional suction hose 3 13 45 120 01 0 and tool collar 3 13 45 300 01 0.
- Large, 360° rotating castors for optimum manoeuvrability even in tight spaces.
- Auto start socket with switch-on delay to avoid power surges.
- Approval for dust class L.
- Practical storage area with edge.
- Tool collar with suction force regulation to set the suction power with ease.

FEIN DUSTEX 25 L SET



SUPPLIED

1x 4 m suction hose, diameter 35 mm, 1 tool collar with suction force regulation, 1 Fleece filter bag, 1 Flat-fold filter, 2 suction pipes (metal), 1 combi nozzle with interchangeable inserts, 1 groove nozzle, 1 suction brush, 1 elbow

For accessories, see page 202

Compact, powerful wet and dry dust extractor for connecting to power tools when working in the workshop and for assembly work, with large accessory set.

W	1 380
l/min	4,320
hPa	253
l	22
m	7,5
kg	8
	l/min hPa l m

Part number	9 20 35 060 00 0
EAN	4014586891828

FEIN BENEFITS

- + Powerful turbine for 72 l/s volumetric flow and 253 mbar vacuum (240 V).
- Low noise level of 67 dB (A).
- The 7.5 m mains cable and 4 m hose provide a large working radius.
- + Anti-static function for preventing static charging during work - electrostatically discharging thanks to optional suction hose 3 13 45 120 01 0 and tool collar 3 13 45 300 01 0.
- + Large, 360° rotating castors for optimum manoeuvrability even in tight spaces.

 + Tool collar with suction force regulation to set the
- suction power with ease.
- + Auto start socket with switch-on delay to avoid power surges.
- Practical storage area with edge.
- + Approval for dust class L.

FEIN DUSTEX 25 L



SUPPLIED

1x 4 m suction hose, diameter 35 mm, 1 tool collar with suction force regulation, 1 Fleece filter bag, 1 Flat-fold filter

For accessories, see page 202

Compact, powerful wet and dry dust extractor for connecting to power tools when working in the workshop and for assembly work.

Maximum power input	W	1 380
Air flow	l/min	4,320
Max. vacuum	hPa	253
Tank volume	l	22
Cable with plug	m	7,5
Weight according to EPTA	kg	8

Part number	9 20 35 223 00 0
EAN	4014586891866

- Powerful turbine for 72 l/s volumetric flow and 253 mbar vacuum (240 V).
- Low noise level of 67 dB (A).
- The 7.5 m mains cable and 4 m hose provide a large working radius.
- Anti-static function for preventing static charging during work - electrostatically discharging thanks to optional suction hose 3 13 45 120 01 0 and tool collar 3 13 45 300 01 0.
- + Large, 360° rotating castors for optimum manoeuvra-
- bility even in tight spaces.

 + Tool collar with suction force regulation to set the suction power with ease.
- Auto start socket with switch-on delay to avoid power
- + Practical storage area with edge.
- + Approval for dust class L

8 WET / DRY DUST EXTRACTOR

GENERAL ACCESSORIES WET / DRY DUST EXTRACTOR



FLAT-FOLD FILTER

Cellulose, M dust class certification

Part number 3 13 45 012 01 0



FLAT-FOLD FILTER

PES, M dust class certification, superior filter

Part number 3 13 45 059 01 0



FLAT-FOLD FILTER

HEPA

Part number 3 13 45 060 01 0



SUCTION HOSE

mm	m	Part number
27	4	3 13 45 065 01 0
35	4	3 13 45 066 01 0



ANTISTATIC SUCTION HOSE

Electrostatically discharging, orange-black.

Ø	L	
mm	m	Part number
27	4	3 13 45 121 01 0
35	4	3 13 45 120 01 0



EXTENSION HOSE

Ø	L		
mm	m	Part number	
27	2,5	3 13 45 067 01 0	
35	2,5	3 13 45 068 01 0	



REPAIR SET

Suitable for 35 mm diameter suction hose

Part number
3 13 45 069 01 0



ELBOW

Part numbe
3 13 45 070 01



ELBOW

with leak air aperture.

Part number
3 13 45 263 01 0



SUCTION TUBE

Metal version, pack of 2

Part number 3 13 45 071 01 0



FLOOR NOZZLE

Reversible, with stainless steel sliding surface and all-round bristles. Suitable for hard floors and textile floor coverings

Part number
3 13 45 072 01 0



COMBINATION NOZZLE

For wet and dry work with interchangeable inserts, rubber lips

Part number
3 13 45 073 01 0



CREVICE NOZZLE

Part number 3 13 45 074 01 0



UPHOLSTERY NOZZLE

With brush strips

Part number
3 13 45 075 01 0



SUCTION BRUSH,

can be rotated, with natural bristles, 70 x 45 mm bristle area

Part number
3 13 45 076 01 0



INTAKE BRUSH

Natural bristles, 120 x 45 mm bristle area

Part number
3 13 45 077 01 0



ANTISTATIC TOOL COLLAR

Electrically conducting, with suction force regulation, for hose diameter 35 mm, power tool connection (diameter 38 mm).

Part number 3 13 45 123 01 0



ANTISTATIC TOOL COLLAR

Electrically conducting, with suction force regulation, for hose diameter 35 mm, power tool connection (diameter 27 mm).

Part number 3 13 45 300 01 0



STEPPED COLLAR

4 levels

-	
	Part number
	3 13 45 079 01 0



CABLE HOLDER

to guide cable on suction hose, suitable for suction hose diameter of 27-35 mm

No. in pack	
pcs	Part number
5	3 13 45 119 01 0



ACCESSORY SET

2 suction pipes (metal), 1 combi nozzle with interchangeable inserts, 1 crevice nozzle, 1 suction brush, 1 elbow

	Part number
	3 13 45 071 02 0
	-



ACCESSORY SET

1 suction hose, 2 suction pipes (metal), 1 combi nozzle with interchangeable inserts, 1 crevice nozzle, 1 suction brush,

Fait number
3 13 45 133 02 0

ACCESSORIES FOR DUSTEX 35 LX / MX



DISPOSAL BAG

Open, recommended for AC models only

pcs	Part number
5	3 13 45 063 01 0



PREMIUM FLEECE FILTER BAG

Particularly strong, tear-resistant fleece with seams with additional reinforcement for fine, abrasive dusts. 2–3times greater effective capacity than paper filter bags.

	No. in pack	
Model	pcs	Part number
Dustex 35 L	5	3 13 45 251 01 0

ACCESSORIES FOR FEIN DUSTEX 35 L



FLEECE FILTER BAG

Particularly tear-resistant fleece. 2-3times greater effective capacity than paper filter bags.

Model Dustex 35 I	pcs 5	Part number
Dustex 35 L	5	3 13 45 062 01 0



PREMIUM FLEECE FILTER BAG

Particularly strong, tear-resistant fleece with seams with additional reinforcement for fine, abrasive dusts. 2–3times greater effective capacity than paper filter bags.

	No. in pack	
Model	pcs	Part number
Dustex 35 L	5	3 13 45 251 01 0



PERMANENT FILTER

Replaces the fleece filter bag

Part number
3 13 45 064 01 0



HEPA FILTER BAG

No. in pack	
pcs	Part number
3	3 13 45 130 01 0

ACCESSORIES FOR FEIN DUSTEX 25 L



FLEECE FILTER BAG

Particularly tear-resistant fleece. 2–3times greater effective capacity than paper filter bags.

	No. in pack	
Model	pcs	Part number
Dustex 25 I	5	3 13 45 061 01 0



PREMIUM FLEECE FILTER BAG

Particularly strong, tear-resistant fleece with seams with additional reinforcement for fine, abrasive dusts. 2-3times greater effective capacity than paper filter bags.

	No. in pack	
Model	pcs	Part number
Dustex 25 L	5	3 13 45 273 01 0



PERMANENT FILTER

Replaces the fleece filter bag

Part number
3 13 45 064 01 0



MULTIMASTER

210

The universal system for interior work and renovation.



STARLOCK ACCESSORIES

217

MULTIMASTER AUTOMOTIVE

230

The most powerful system for vehicle repairs.





MULTIMASTER 237 **JOINT RENOVATION**

12-SIDED FITTING **ACCESSORIES**

241







THE BEST SYSTEM. MULTIMASTER AND ACCESSORIES.

Select the model, which fits your demands and tasks perfectly. Here we provide an overview of the most important features and differences.



Please refer to pages 276 and 277 for more information about the batteries





ADDED VALUE FOR YOU



PERFORMANCE

3 performance classes, each delivering impressive in a mains-powered or battery-operated accessories on the market.



HANDLING

Optimum handling. From rapid, tool-free tool changes using QuickIN and Starlock to outstanding ergonomics – we simplify your work for you.



SAFETY

reduced noise emissions and effective removal of dust - FEIN MULTIMASTERS provide the user with when used for long periods.

















MULTIMASTER 700

Our best tool for the toughest requirements:

Our best multitool for the fastest work progress in interior work and renovation.

Cordless / mains-powered

18 V AMP Share / 450 W



Anti-vibration system

2 x 2.0°

StarlockMax

MULTIMASTER 500

The benchmark amongst oscillators:

The powerful multitool for rapid work progress in interior work and renovation.

Cordless / mains-powered

18 V AMP Share / 350 W

Powered by BOSCH

2 x 1.7°

Anti-vibration system

StarlockPlus

MULTIMASTER 300

Your best route into the professional class:

The effective multitool for interior work and renovation.

Mains

250 W

2 x 1.6°

StarlockPlus



Versatility thanks to more than 180 accessories



Versatility thanks to around 100 accessories

Versatility thanks to around 100 accessories



COST-EFFECTIVENESS

One universal tool for all scenarios rather than lots of different special tools. Complete flexibility thanks to one open battery platform spanning all



EXPERTISE


Benefit from the experience of the inventor. For more than 50 years, professionals around the globe have performance and reliability of the original.



RELIABILITY

"MADE IN GERMANY". AIL FEIN MULTIMASTERS are designed for the toughest requirements encountered in daily use in industry and manual trades. Of course, that applies to the range of FEIN accessories too.

FEIN MULTIMASTER. 1 SYSTEM - 1000 POSSIBILITIES.













SAW BLADES



HSS, BIM | METAL & WOOD










Felt polishing pad

Grit 240-500

Corundum, grit 40-240







AMM 700

AMM 500

AMP Share







AMP Share





CORDLESS MULTIMASTER AMM 700 MAX TOP 4.0 AH AS

Our best Multitool for the most rapid work progress in interior work and renovation with 60 accessories – from sawing in wood, metal and plastics, to cutting out tiles, cutting silicone joints and carpets, removing adhesive residues and tile adhesive.

CORDLESS MULTIMASTER AMM 700 MAX AS

Our best cordless Multitool for the most rapid work progress in interior work and renovation in the variant without battery or charger – with a bimetal saw blade for wood, metal and plastics.

CORDLESS MULTIMASTER AMM 500 PLUS TOP 4.0 AH AS

The powerful cordless Multitool for rapid work progress (in interior work and renovation) with more than 30 accessories – for sawing in wood and metal, sanding, removing tiles and much more.

CORDLESS MULTIMASTER AMM 500 PLUS AS

The powerful cordless Multitool for rapid work progress (in interior work and renovation) in the variant without battery or charger – with a bimetal saw blade for wood, metal and plastics.

		residues and the adhesive.				
PAGE		212	213	213	214	
Mechanical interface		•	•	•	•	
Input	W					
Battery voltage	V	18	18	18	18	
Battery compatibility		Li-ion/ProCORE Li-ion	Li-ion/ProCORE Li-ion	Li-ion/ProCORE Li-ion	Li-ion/ProCORE Li-ion	
Battery interface		18 V AMPShare	18 V AMPShare	18 V AMPShare	18 V AMPShare	
Oscillations	rpm	10,000 - 19,500	10,000 - 19,500	11,000 - 18,500	11,000 - 18,500	
Tool Holder		StarlockMax	StarlockMax	StarlockPlus	StarlockPlus	
Tool change		QuickIN	QuickIN	QuickIN	QuickIN	
Amplitude		2 x 2,0°	2 x 2,0°	2 x 1,7°	2 x 1,7°	
Weight according to EPTA	kg					
Weight without storage battery	kg	1,1	1,1	1,3	1,3	

[•] included

2 x 1,6°

1,4

MM 700 MM 500 MM 300 MULTIMASTER MULTIMASTER MULTIMASTER MULTIMASTER MULTIMASTER MM 700 MAX TOP MM 500 PLUS TOP MM 300 PLUS START **MM 700 MAX** MM 500 PLUS Our best Multitool for the most Our best Multitool for the most The powerful Multitool for rapid The powerful Multitool for rapid The effective Multitool for work progress (in interior work and renovation) with more than 30 accessories for sawing in rapid work progress in interior rapid work progress in interior work progress (in interior work interior work and renovation work and renovation with 60 accessories – from sawing work and renovation with and renovation) with a bimetal saw blade for wood, metal and with basic accessories for sawing in wood, metal, a bimetal saw blade for wood, in wood, metal and plastics, to metal and plastics. wood and metal, sanding, plasterboard and plastics. cutting out tiles, cutting silicone removing tiles and much more. joints and carpets, removing adhesive residues and tile adhesive. 215 215 216 216 216 . 450 450 350 350 250 10,000 - 19,500 10,000 - 19,500 10,000 - 19,500 10,000 - 19,500 11,000 - 20,000 StarlockMax StarlockMax StarlockPlus StarlockPlus StarlockPlus QuickIN QuickIN QuickIN QuickIN QuickIN

2 x 1,7°

1,4

2 x 1,7°

1,4

2 x 2,0°

1,6

2 x 2,0°

1,6

9 MULTIMASTER

CORDLESS MULTIMASTER AMM 700 MAX TOP 4.0 AH AS AMP#Share



SUPPLIED

2 E-Cut standard saw blades curved (35 mm), 2 E-Cut standard saw blades curved (65 mm), 1 E-Cut precision saw blade (35 mm), 1 E-Cut precision saw blade (65 mm), 1 E-Cut long-life saw blade (10 mm), 2 E-Cut long-life saw blades (35 mm), 1 E-Cut long-life saw blade (32 mm), 1 E-Cut long-life saw blade (42 mm), 1 E-Cut carbide Pro saw blade (32 mm), 1 segmented saw blade (Ø 85 mm), 1 HSS segment saw blade, 1 HM rasp (triangular), 1 Stopper knife, 1 Cutter blade, mushroom shaped 6 390 31 28 01 2, 1 Multi-function knife, 1 Sanding plate with holes, Sanding sheets perforated (10 each of grit 60, 80, 120, 180), 1 dust extraction device, 1 rapid charger GAL 1880 CV AS, 2 Li-ion battery packs (18 V / 4 Ah), 1 tool case (L-BOXX 136)

For accessories, see page 217

Our best Multitool for the most rapid work progress in interior work and renovation with 60 accessories – from sawing in wood, metal and plastics, to cutting out tiles, cutting silicone joints and carpets, removing adhesive residues and tile adhesive.

Battery voltage	V	18
Battery capacity	Ah	4
Battery compatibility		Li-ion/ProCORE Li-ion
Battery interface		18 V AMPShare
Oscillations	rpm	10,000 - 19,500
Tool Holder		StarlockMax
Tool change		QuickIN
Amplitude		2 x 2,0°
Weight without storage battery	kg	1,1

Part number	7 129 36 61 00 0
EAN	4014586895277

FEIN BENEFITS

- + Anti-vibration system: continuously safe and pleasant working thanks to minimal vibrations and outstanding noise insulation.
- StarlockMax tool mounting: more work progress and greater precision thanks to 100 % power transmission without losses.
- + QuickIN: tool changes in less than 3 seconds thanks to the patented tool-free FEIN rapid clamping system.
- With the StarlockMax tool mounting, you can access around 180 FEIN accessories from the Starlock, Starlock Plus and StarlockMax performance classes.
- 18 V FEIN PowerDrive motor: very powerful and virtually wear-free, brushless motor offering great efficiency, ability to handle extreme loads and a long service life.
- + Tacho generator: constant speeds even under load and infinitely variable electronic speed control.
- Metal gearbox: ability to withstand high loading and outstanding service life because all the gearbox parts are made from metal.
- + Mechanical interface: for stationary operation in the table or drill jig holder or for securing the depth stop.
- + Electronic Cell Protection (ECP): ECP protects against overload, overheating and total discharge.
- The COOLPACK technology ensures a longer battery life and therefore makes long operating periods possible.
- The battery charge can be read off the battery.
- Compatible with AMPShare/Bosch Professional 18 V batteries.
- + Ideally equipped for every job. Mobile working with the L-BOXX system.
- + Electronic safety cut-off user protection should the saw blade lock, for example.

CORDLESS MULTIMASTER AMM 700 MAX TOP AS



SUPPLIED

2 E-Cut standard saw blades curved (35 mm), 2 E-Cut standard saw blades curved (65 mm), 1 E-Cut precision saw blade (35 mm), 1 E-Cut precision saw blade (65 mm), 1 E-Cut long-life saw blade (10 mm), 2 E-Cut long-life saw blades (35 mm), 1 E-Cut long-life saw blade (32 mm), 1 E-Cut long-life saw blade (42 mm), 1 E-Cut carbide Pro saw blade (32 mm), 1 segmented saw blade (Ø 85 mm), 1 HSS segment saw blade, 1 HM rasp (triangular), 1 Stopper knife, 1 Cutter blade, mushroom shaped 6 390 31 28 01 2, 1 Multi-function knife, 1 Sanding plate with holes, Sanding sheets perforated (10 each of grit 60, 80, 120, 180), 1 dust extraction device, 1 tool case (L-BOXX 136)

For accessories, see page 217

Our best Multitool for the most rapid work progress in interior work and renovation with 60 accessories – from sawing in wood, metal and plastics, to cutting out tiles, cutting silicone joints and carpets, removing adhesive residues and tile adhesive.

Battery voltage	V	18
Battery capacity	Ah	4
Battery compatibility		Li-ion/ProCORE Li-ion
Battery interface		18 V AMPShare
Oscillations	rpm	10,000 - 19,500
Tool Holder		StarlockMax
Tool change		QuickIN
Amplitude		2 x 2,0°
Weight without storage battery	kg	1,1

Part number	7 129 36 63 00 0
EAN	4014586895291

- Anti-vibration system: continuously safe and pleasant working thanks to minimal vibrations and outstanding noise insulation.
- + StarlockMax tool mounting: more work progress and greater precision thanks to 100 % power transmission without losses.
- + QuickIN: tool changes in less than 3 seconds thanks to the patented tool-free FEIN rapid clamping system.
- With the StarlockMax tool mounting, you can access around 180 FEIN accessories from the Starlock, Starlock Plus and StarlockMax performance classes.
- + 18 V FEIN PowerDrive motor: very powerful and virtually wear-free, brushless motor offering great efficiency, ability to handle extreme loads and a long service life.
- + Tacho generator: constant speeds even under load and infinitely variable electronic speed control.
 + Metal gearbox: ability to withstand high loading and
- Metal gearbox: ability to withstand high loading and outstanding service life because all the gearbox parts are made from metal.
- + Mechanical interface: for stationary operation in the table or drill jig holder or for securing the depth stop.
- Electronic Cell Protection (ECP): ECP protects against overload, overheating and total discharge.
 The COOLPACK technology ensures a longer battery
- The COOLPACK technology ensures a longer battery life and therefore makes long operating periods possible.
- + The battery charge can be read off the battery.
- + Compatible with AMPShare/Bosch Professional 18 V batteries.
- + Ideally equipped for every job. Mobile working with the L-BOXX system.
- Electronic safety cut-off user protection should the saw blade lock, for example.

CORDLESS MULTIMASTER AMM 700 MAX AS

AMP Share



SUPPLIED

1 Universal E-Cut saw blade (44 mm), 1 tool case (L-BOXX 136)

For accessories, see page 217

Our best cordless Multitool for the most rapid work progress in interior work and renovation in the variant without battery or charger -with a bimetal saw blade for wood, metal and plastics.

V	18
	Li-ion/ProCORE Li-ion
	18 V AMPShare
rpm	10,000 - 19,500
	StarlockMax
	QuickIN
	2 x 2,0°
kg	1,1
	rpm

Part number	7 129 36 62 00 0
EAN	4014586895284

FEIN BENEFITS

- + Anti-vibration system: continuously safe and pleasant working thanks to minimal vibrations and outstanding noise insulation.
- StarlockMax tool mounting: more work progress and greater precision thanks to 100 % power transmission without losses.
- QuickIN: tool changes in less than 3 seconds thanks to the patented tool-free FEIN rapid clamping system
- With the StarlockMax tool mounting, you can access around 180 FEIN accessories from the Starlock, Starlock Plus and StarlockMax performance classes.
- + 18 V FEIN PowerDrive motor: very powerful and virtually wear-free, brushless motor offering great efficiency, ability to handle extreme loads and a long
- Tacho generator: constant speeds even under load and infinitely variable electronic speed control.
- Metal gearbox: ability to withstand high loading and outstanding service life because all the gearbox parts are made from metal.
- Mechanical interface: for stationary operation in the table or drill jig holder or for securing the depth stop.
- Electronic Cell Protection (ECP): ECP protects against overload, overheating and total discharge.
- The COOLPACK technology ensures a longer battery life and therefore makes long operating periods possible
- The battery charge can be read off the battery.
- Compatible with AMPShare/Bosch Professional 18 V batteries.
- Ideally equipped for every job. Mobile working with the L-BOXX system.
- + Electronic safety cut-off user protection should the saw blade lock, for example.

CORDLESS MULTIMASTER AMM 500 PLUS TOP 4.0 AH AS AMP Share



SUPPLIED

1 E-Cut long-life saw blade (10 mm), 2 E-Cut long-life saw blades (35 mm), 2 E-Cut long-life saw blades (65 mm), 1 E-Cut carbide Pro saw blade (32 mm), 1 carbide saw blade (diameter 75 mm), 1 HM rasp (triangular), 1 Stopper knife, 1 Sanding plate with holes, with 5 sanding sheets, with holes for each of grit sizes 60, 80, 120, 180, 1 dust extraction device, 1 rapid charger GAL 1880 CV AS, 2 Li-ion battery packs (18 V / 4 Ah), 1 tool case (L-BOXX 136)

For accessories, see page 217

The powerful cordless Multitool for rapid work progress (in interior work and renovation) with more than 30 accessories - for sawing in wood and metal, sanding, removing tiles and much more.

Battery voltage	V	18
Battery capacity	Ah	4
Battery compatibility		Li-ion/ProCORE Li-ion
Battery interface		18 V AMPShare
Oscillations	rpm	11,000 - 18,500
Tool Holder		StarlockPlus
Tool change		QuickIN
Amplitude		2 x 1,7°
Weight without storage battery	kg	1,3

Part number	7 129 38 61 00 0
EAN	4014586895321

- + Anti-vibration system: continuously safe and pleasant working thanks to minimal vibrations and outstanding noise insulation.
- StarlockPlus tool mounting: more work progress and greater precision thanks to 100 % power transmission without losses
- QuickIN: tool changes in less than 3 seconds thanks to the patented tool-free FEIN rapid clamping system.
- With the StarlockPlus tool mounting, you can access around 100 FEIN accessories from the Starlock and StarlockPlus performance classes.
- DC motor: effective and powerful motor technology offering virtually the same power as the mains-powered
- Tacho generator: constant speeds even under load and infinitely variable electronic speed control.
- Metal gearbox: ability to withstand high loading and outstanding service life because all the gearbox parts are made from metal.
- Mechanical interface: for stationary operation in the table or drill jig holder or for securing the depth stop.

 + Electronic Cell Protection (ECP): ECP protects against
- overload, overheating and total discharge.
 The COOLPACK technology ensures a longer battery
- life and therefore makes long operating periods possible.
- The battery charge can be read off the battery.
- Compatible with AMPShare/Bosch Professional 18 V batteries
- Ideally equipped for every job. Mobile working with the L-BOXX system.

9 MULTIMASTER

CORDLESS MULTIMASTER AMM 500 PLUS TOP AS



SUPPLIED

1 E-Cut long-life saw blade (10 mm), 2 E-Cut long-life saw blades (35 mm), 2 E-Cut long-life saw blades (65 mm), 1 E-Cut carbide Pro saw blade (32 mm), 1 carbide saw blade (diameter 75 mm), 1 HM rasp (triangular), 1 Stopper knife, 1 Sanding plate with holes, with 5 sanding sheets, with holes for each of grit sizes 60, 80, 120, 180, 1 dust extraction device, 1 tool case (L-BOXX 136)

For accessories, see page 217

The powerful cordless Multitool for rapid work progress (in interior work and renovation) with more than 30 accessories – for sawing in wood and metal, sanding, removing tiles and much more.

V	18
	Li-ion/ProCORE Li-ion
	18 V AMPShare
rpm	11,000 - 18,500
	StarlockPlus
	QuickIN
	2 x 1,7°
kg	1,3
	rpm

Part number	7 129 38 63 00 0
EAN	4014586895345

FEIN BENEFITS

- Anti-vibration system: continuously safe and pleasant working thanks to minimal vibrations and outstanding noise insulation.
- StarlockPlus tool mounting: more work progress and greater precision thanks to 100 % power transmission without losses.
- + QuicklN: tool changes in less than 3 seconds thanks to the patented tool-free FEIN rapid clamping system.
- With the StarlockPlus tool mounting, you can access around 100 FEIN accessories from the Starlock and StarlockPlus performance classes.
- DC motor: effective and powerful motor technology offering virtually the same power as the mainspowered version.
- + Tacho generator: constant speeds even under load and infinitely variable electronic speed control.
- + Metal gearbox: ability to withstand high loading and outstanding service life because all the gearbox parts are made from metal.
- + Mechanical interface: for stationary operation in the table or drill jig holder or for securing the depth stop.
- Electronic Cell Protection (ECP): ECP protects against overload, overheating and total discharge.
- The COOLPACK technology ensures a longer battery life and therefore makes long operating periods possible.
- + The battery charge can be read off the battery.
- + Compatible with AMPShare/Bosch Professional 18 V batteries.
- + Ideally equipped for every job. Mobile working with the L-BOXX system.

CORDLESS MULTIMASTER AMM 500 PLUS AS



SUPPLIED

1 Universal E-Cut saw blade (44 mm), 1 tool case (L-BOXX 136)

For accessories, see page 217

The powerful cordless Multitool for rapid work progress (in interior work and renovation) in the variant without battery or charger – with a bimetal saw blade for wood, metal and plastics.

Battery voltage	V	18
Battery compatibility		Li-ion/ProCORE Li-ion
Battery interface		18 V AMPShare
Oscillations	rpm	11,000 - 18,500
Tool Holder		StarlockPlus
Tool change		QuickIN
Amplitude		2 x 1,7°
Weight without storage battery	kg	1,3

Part number	7 129 38 62 00 0
FAN	4014586895338

- Anti-vibration system: continuously safe and pleasant working thanks to minimal vibrations and outstanding noise insulation.
- + StarlockPlus tool mounting: more work progress and greater precision thanks to 100 % power transmission without losses.
- + QuickIN: tool changes in less than 3 seconds thanks to the patented tool-free FEIN rapid clamping system.
- With the StarlockPlus tool mounting, you can access around 100 FEIN accessories from the Starlock and StarlockPlus performance classes.
- + DC motor: effective and powerful motor technology offering virtually the same power as the mains-powered version.
- + Tacho generator: constant speeds even under load and infinitely variable electronic speed control.
- Metal gearbox: ability to withstand high loading and outstanding service life because all the gearbox parts are made from metal.
- + Mechanical interface: for stationary operation in the table or drill jig holder or for securing the depth stop.
- + Electronic Cell Protection (ECP): ECP protects against overload, overheating and total discharge.
- The COOLPACK technology ensures a longer battery life and therefore makes long operating periods possible.
- + The battery charge can be read off the battery.
- + Compatible with AMPShare/Bosch Professional 18 V batteries.
- Ideally equipped for every job. Mobile working with the L-BOXX system.

MULTIMASTER MM 700 MAX TOP



SUPPLIED

2 E-Cut standard saw blades curved (35 mm), 2 E-Cut standard saw blades curved (65 mm), 1 E-Cut Precision BIM saw blade (35 mm), 1 E-Cut Precision BIM saw blade (65 mm), 1 E-Cut long-life saw blade (10 mm), 2 E-Cut long-life saw blades (35 mm), 1 E-Cut long-life saw blade (32 mm), 1 E-Cut long-life saw blade (42 mm), 1 E-Cut carbide Pro saw blade (32 mm), 1 segmented saw blade (Ø 85 mm), 1 carbide saw blade (diameter 75 mm), 1 HM rasp (triangular), 1 Stopper knife, 1 Cutter blade, mushroom shaped 6 390 31 28 01 2, 1 Multi-function knife, 1 Sanding plate with holes, Sanding sheets, perforated (10 each of grit 60, 80, 120, 180), 1 dust extraction device, 1 tool case (L-BOXX 136)

For accessories, see page 217

Our best Multitool for the most rapid work progress in interior work and renovation with 60 accessories – from sawing in wood, metal and plastics, to cutting out tiles, cutting silicone joints and carpets, removing adhesive residues and tile adhesive.

W	450
W	250
rpm	10,000 - 19,500
	StarlockMax
	QuickIN
	2 x 2,0°
m	5
kg	1,6
	W rpm

Part number	7 229 68 64 00 0
EAN	4014586897912

FEIN BENEFITS

- + Anti-vibration system: continuously safe and pleasant working thanks to minimal vibrations and outstanding noise insulation.
- StarlockMax tool mounting: more work progress and greater precision thanks to 100 % power transmission without losses.
- QuickIN: tool changes in less than 3 seconds thanks to the patented tool-free FEIN rapid clamping system
- With the StarlockMax tool mounting, you can access around 180 FEIN accessories from the Starlock, Starlock Plus and StarlockMax performance classes.
- + 450 W FEIN high-power motor; high-power motor with a high copper content, which is suited to continuous use and overload for maximum cutting speed and the most rapid work progress.
- Tacho generator: constant speeds even under load and infinitely variable electronic speed control.
- + Metal gearbox: ability to withstand high loading and outstanding service life because all the gearbox parts are made from metal.
- Mechanical interface: for stationary operation in the table or drill jig holder or for securing the depth stop.
- Industrial cable: large working radius thanks to finely stranded 5 metre rubber cable of industrial quality.
- + Electronic safety cut-off user protection should the saw blade lock, for example,
- Ideally equipped for every job. Mobile working with the L-BOXX system.

MULTIMASTER MM 700 MAX



SUPPLIED

1 Universal E-Cut saw blade (44 mm), 1 tool case (L-BOXX 136)

For accessories, see page 217

Our best Multitool for the most rapid work progress in interior work and renovation with a bimetal saw blade for wood, metal and plastics.

Input	W	450
Output	W	250
Oscillations	rpm	10,000 - 19,500
Tool Holder		StarlockMax
Tool change		QuickIN
Amplitude		2 x 2,0°
Cable with plug	m	5
Weight according to EPTA	kg	1,6

Part number	7 229 68 63 00 0
EAN	4014586897868

- Anti-vibration system: continuously safe and pleasant working thanks to minimal vibrations and outstanding noise insulation.
- StarlockMax tool mounting: more work progress and greater precision thanks to 100 % power transmission
- QuickIN: tool changes in less than 3 seconds thanks to the patented tool-free FEIN rapid clamping system.
- With the StarlockMax tool mounting, you can access around 180 FEIN accessories from the Starlock, Starlock Plus and StarlockMax performance classes.
- 450 W FEIN high-power motor: high-power motor with a high copper content, which is suited to continuous use and overload for maximum cutting speed and the most rapid work progress.
- Tacho generator: constant speeds even under load and infinitely variable electronic speed control.
- Metal gearbox: ability to withstand high loading and outstanding service life because all the gearbox parts are made from metal.
- Mechanical interface: for stationary operation in the table or drill jig holder or for securing the depth stop.
- + Industrial cable: large working radius thanks to finely stranded 5 metre rubber cable of industrial quality.
- Electronic safety cut-off user protection should the saw blade lock, for example.
- Ideally equipped for every job. Mobile working with the L-BOXX system.

9 MULTIMASTER

MULTIMASTER MM 500 PLUS TOP



SUPPLIED

1 E-Cut long-life saw blade (10 mm), 2 E-Cut long-life saw blades (35 mm), 2 E-Cut long-life saw blades (65 mm), 1 E-Cut carbide Pro saw blade (32 mm), 1 carbide saw blade (diameter 75 mm), 1 HM rasp (triangular), 1 Stopper knife, 1 Sanding plate with holes, with 5 sanding sheets, with holes for each of grit sizes 60, 80, 120, 180, 1 dust extraction device, 1 tool case (L-BOXX 136)

For accessories, see page 217

The powerful Multitool for rapid work progress (in interior work and renovation) with more than 30 accessories for sawing in wood and metal, sanding, removing tiles and much more.

Input	W	350
Oscillations	rpm	10,000 - 19,500
Tool Holder		StarlockPlus
Tool change		QuickIN
Amplitude		2 x 1,7°
Cable with plug	m	5
Weight according to EPTA	kg	1,4

Part number	7 229 67 70 00 0
EAN	4014586897813

FEIN BENEFITS

- Anti-vibration system: continuously safe and pleasant working thanks to minimal vibrations and outstanding noise insulation.
- StarlockPlus tool mounting: more work progress and greater precision thanks to 100 % power transmission without losses.
- + QuickIN: tool changes in less than 3 seconds thanks to the patented tool-free FEIN rapid clamping system.
- With the StarlockPlus tool mounting, you can access around 100 FEIN accessories from the Starlock and StarlockPlus performance classes.
- + 350 W FEIN motor. Powerful motor with a high copper content, which is suited to overload for a higher cutting speed and faster work progress.
- + Tacho generator: constant speeds even under load and infinitely variable electronic speed control.
- Metal gearbox: ability to withstand high loading and outstanding service life because all the gearbox parts are made from metal.
- Mechanical interface: for stationary operation in the table or drill jig holder or for securing the depth stop.
- Industrial cable: large working radius thanks to finely stranded 5 metre rubber cable of industrial quality.
- + Ideally equipped for every form of use. Mobile working with the L-BOXX system.

MULTIMASTER MM 500 PLUS



SUPPLIED

1 Universal E-Cut saw blade (44 mm), 1 tool case (L-BOXX 136)

For accessories, see page 217

The powerful Multitool for rapid work progress (in interior work and renovation) with a bimetal saw blade for wood, metal and plastics.

Input	W	350
Oscillations	rpm	10,000 - 19,500
Tool Holder		StarlockPlus
Tool change		QuickIN
Amplitude		2 x 1,7°
Cable with plug	m	5
Weight according to EPTA	kg	1,4

Part number	7 229 67 69 00 0
EAN	4014586897769

FEIN BENEFITS

- Anti-vibration system: continuously safe and pleasant working thanks to minimal vibrations and outstanding noise insulation.
- + StarlockPlus tool mounting: more work progress and greater precision thanks to 100 % power transmission without losses.
- + QuickIN: tool changes in less than 3 seconds thanks to the patented tool-free FEIN rapid clamping system.
- With the StarlockPlus tool mounting, you can access around 100 FEIN accessories from the Starlock and StarlockPlus performance classes.
- + 350 W FEIN motor. Powerful motor with a high copper content, which is suited to overload for a higher cutting speed and faster work progress.
- + Tacho generator: constant speeds even under load and infinitely variable electronic speed control.
- + Metal gearbox: ability to withstand high loading and outstanding service life because all the gearbox parts are made from metal.
- + Mechanical interface: for stationary operation in the table or drill jig holder or for securing the depth stop.
- + Industrial cable: large working radius thanks to finely stranded 5 metre rubber cable of industrial quality.
- + Ideally equipped for every form of use. Mobile working with the L-BOXX system.

MULTIMASTER MM 300 PLUS START



SUPPLIED

- 1 E-Cut long-life saw blade (35 mm), 1 E-Cut long-life saw blade (65 mm), 1 Universal E-Cut saw blade (44 mm),
- 1 Universal E-Cut saw blade (44 mm 1 tool case (L-BOXX 136)
- For accessories, see page 217

The effective Multitool for interior work and renovation with basic accessories for sawing in wood, metal, plasterboard and plastics.

Input	W	250
Oscillations	rpm	11,000 - 20,000
Tool Holder		StarlockPlus
Tool change		QuickIN
Amplitude		2 x 1,6°
Cable with plug	m	5
Weight according to EPTA	kg	1,4

Part number	7 229 72 64 00 0
EAN	4014586898094

- + StarlockPlus tool mounting: more work progress and greater precision thanks to 100 % power transmission without losses.
- + QuickIN: tool changes in less than 3 seconds thanks to the patented tool-free FEIN rapid clamping system.
- With the StarlockPlus tool mounting, you can access around 100 FEIN accessories from the Starlock and StarlockPlus performance classes.
- 250 W FEIN motor: motor with a high copper content, which is suited to overload for more power and effective working.
- + Infinitely variable electronic speed setting.
- Metal gearbox: ability to withstand high loading and outstanding service life because all the gearbox parts are made from metal.
- + Barrel-type design for maximum stability.
- Industrial cable: large working radius thanks to finely stranded 5 metre rubber cable of industrial quality.
- + Ideally equipped for every form of use. Mobile working with the L-BOXX system.

For more than 50 years, the range of FEIN accessories for our MultiTools has grown to meet your changing requirements.



FEIN BENEFITS

- + More than 180 different accessories for thousands of professional and special applications.
- + 14 accessory kits perfectly put together for varied applications.
- + Made by FEIN: Each accessory is developed, manufactured and checked by FEIN.
- + Made in Germany: All FEIN saw blades are produced in Germany.
- + Outstanding cost-effectiveness thanks to fast work progress and a long service life.

Select the Starlock accessories to suit your tool:

	you can see at a gla power tool, which a	nce which tool holder you have on ccessories fit it.	STARLOCK	STARLOCK PLUS	STARLOCK MAX
FIMASTER		STARLOCK MAX e.g. MULTIMASTER (A)MM 700, FSC 500 QSL AFSC 18 QSL	~	~	~
FEIN MULT		STARLOCK PLUS e.g. MULTIMASTER MM 300 and (A)MM 500 FMM 350 QSL & FMT 250 QSL	~	~	-
Others		STARLOCK Bosch, Festool, Würth, Makita	~	~ *	~ *
Ö		OTHER MANUFACTURERS e.g. AEG Rigid Skil Einhell and many others.	~	-	-

ALWAYS FITS

* Depends on power tool.

9 STARLOCK ACCESSORIES

SAWING



SAW BLADE

For all soft materials.

Segmented, ideal for working in corners and on edges without overcutting.

Ø mm	Mount	Part number
85	SL	6 35 02 113 21 0



HSS SAW BLADE

Solid HSS saw blade with metal teeth for sheet metal up to approx. 1 mm. Also for plastics, fibreglass-reinforced plastic, wood, putty and copper/copper alloys. Outstanding cutting speed. Clean, thin cutting line.

Circular	shape	delivers	good	cost-effectiveness.	

Mount		
Mount	pcs	Part number
SL	1	6 35 02 097 21 0
SL	2	6 35 02 097 22 0
SL	5	6 35 02 097 23 0
	SL SL SL	SL 1 SL 2 SL 5



Segmented, ideal for working in corners and on edges without overcutting.

Ø		No. in pack	
mm	Mount	pcs	Part number
85	SL	1	6 35 02 106 21 0
85	SL	2	6 35 02 106 22 0
85	SI	5	6 35 02 106 23 0



HSS SAW BLADE

Bimetal for long tool life. Metal teeth for sheet metal up to approx. 1 mm. Also for plastics, fibreglass-reinforced plastic, wood, putty and copper/copper alloys. Work flush with the surface.

Circular shape delivers good cost-effectiveness.

Ø		No. in pack	
mm	Mount	pcs	Part number
85	SL	1	6 35 02 174 21 0
85	SL	5	6 35 02 174 23 0



Circular shape and extra large diameter deliver optimum cost-effectiveness.

Ø		No. in pack	
mm	Mount	pcs	Part number
100	SLP	1	6 35 02 175 21 0
100	SLP	5	6 35 02 175 23 0



Segmented, ideal for working in corners and on edges without overcutting.

Ø		No. in pack	
mm	Mount	pcs	Part number
100	SL	1	6 35 02 196 21 0
100	SL	5	6 35 02 196 23 0



HSS SAW BLADE

Birnetal for long tool life. Set wood teeth. Outstanding tool life, high cutting quality and speed. As "mini circular saw", ideal for long, straight cuts and for making cut-outs in laid parquet, laminate and wall panelling.

Ø		No. in pack	
mm	Mount	pcs	Part number
100	SLP	1	6 35 02 176 21 0



HSS SAW BLADE SET

Bimetal for long tool life. Set wood teeth. Outstanding tool life, high cutting quality and speed. As "mini circular saw", ideal for long, straight cuts and for making cut-outs in laid parquet, laminate and wall panelling. The depth stop can also be used with many other FEIN accessories. For accurate working at depth. StarlockPlus fitting, suitable for all popular multi-function tools with StarlockPlus and StarlockMax fitting and for all FEIN MultiTalent and MULTIMASTER tools up until 04/16. Scope of supply: 1 HSS saw blade, 1 depth stop (suitable for (A) MM 500 / 700)

mm	Mount	Part number
100	SLP	3 52 22 952 01 0



CONTACT GUARD

Spare contact guard for HSS saw blade 6 35 02 176 21 0.

Part number 3 43 00 000 00 1



DEPTH STOP

Depth stop for all saw blades. For accurate working at depth. Effective protection for blade and workpiece. Contents: 1 adapter for attachment to the machine. 1 depth stop, 1 depth-adjustable guide block.
Can only be used with (A)MM 500 / 700.

Part number 3 21 27 069 01 0



BEST OF E-CUT STARLOCK WOOD & METAL

6 E-Cut plunge-cut saw blades for sawing in wood and metal. Suitable for all FEIN Multitools and all other common Multitools on the market. Available as a set, offering significant savings over purchasing the items individually. Content: E-Cut long-life saw blades (2 each of 50 x 35 mm, 50 x 65 mm), E-Cut universal saw blade (1 each of 55 x 28 mm, 55 x 44 mm).

Mount	Part number
SL	3 52 22 967 01 0



BEST OF E-CUT STARLOCKPLUS WOOD & METAL

6 E-Cut plunge-cut saw blades for sawing in wood and metal. Suitable for all FEIN Multitools and all other common Multitools with Starlock-Plus and StarlockMax mounting. Available as a set, offering significant savings over purchasing the items individually. Content: E-Cut long-life saw blades (2 each of $50 \times 35 \,$ mm, $50 \times 65 \,$ mm), E-Cut universal saw blade (1 each of $60 \times 28 \,$ mm, $60 \times 44 \,$ mm).

Mount	Part number
SLP	3 52 22 967 03 0



BEST OF E-CUT STARLOCKMAX WOOD & METAL

6 extra long E-Cut plunge-cut saw blades for large plunge depths and effective working in wood and metal. Suitable for FEIN Multitools with StarlockMax mounting and all other common Multitools with StarlockMax mounting. Available as a set, offering significant savings over purchasing the items individually. Content: E-Cut long-life saw blades (2 each of 78 x 32 mm, 78 x 42 mm), 2 E-Cut long-life saw blades (90 x 32 mm).

Mount	Part number
SLM	3 52 22 967 05 0



STARLOCK WOOD & METAL E-CUT COMBO

3 E-Cut plunge-cut saw blades for sawing in wood and metal. Suitable for all FEIN Multitools and all other common Multitools with Starlock mounting. Available as a set, offering significant savings over purchasing the items individually. Content: 2 E-Cut long-life saw blades (50 x 35 mm, 50 x 65 mm), 1 E-Cut universal saw blade (55 x 44 mm).

Mount	Part number
SL	3 52 22 967 10 0



STARLOCK WOOD E-CUT COMBO

3 E-Cut plunge-cut saw blades for precise sawing in wooden materials. Suitable for all FEIN Multitools and all other common Multitools with Starlock mounting. Available as a set, offering significant savings over purchasing the items individually. Content: 1 E-Cut standard saw blade, curved (50 x 50 mm), E-Cut precision BIM saw blade (1 each of 50 x 35 mm, 50 x 65 mm).

Mount	Part number
SL	3 52 22 967 08 0



STARLOCK MINI CUT COMBO

3 accessories, ideal for cutting smaller recesses and working in tight spots, e.g. for numerous installation jobs, switch installation, model-building and more. Suitable for all FEIN Multitools and all other common Multitools with Starlock mounting. Available as a set, offering significant savings over purchasing the items individually. Content: E-Cut long-life saw blades (2 of 30 x 10 mm, 35 x 20 mm), 1 carbide file (30 x 10 mm).

Mount	Part number
SL	3 52 22 967 09 0



E-CUT LONG-LIFE SAW BLADE

Bimetal with set wood teeth for all wood, plasterboard and plastic materials. Outstanding tool life, high cutting quality and speed. Extremely robust, not affected by nails (up to diameter of approx. 4 mm) in wood, masonry etc.

Short, very narrow shape for the smallest of recesses.

Width mm	Length mm	Mount	No. in pack pcs	Part number
10	30	SL	1	6 35 02 184 21 0
10	30	SL	3	6 35 02 184 22 0
10	30	SL	5	6 35 02 184 23 0
10	30	SL	10	6 35 02 184 24 0
10	30	SL	50	6 35 02 184 25 0



Short, very narrow shape for the smallest of recesses.

Width mm	Length mm	Mount	No. in pack pcs	Part number
20	34	SL	1	6 35 02 183 21 0
20	34	SL	3	6 35 02 183 22 0
20	34	SL	5	6 35 02 183 23 0
20	34	SL	10	6 35 02 183 24 0
20	34	SL	50	6 35 02 183 25 0



Medium width, with waist for optimum cutting speed and good swarf removal. $% \label{eq:cutting} % A = \frac{1}{2} \left(\frac{1}{2$

Width mm	Length mm	Mount	No. in pack pcs	Part number
35	50	SL	1	6 35 02 160 21 0
35	50	SL	3	6 35 02 160 22 0
35	50	SL	5	6 35 02 160 23 0
35	50	SL	10	6 35 02 160 24 0
35	50	SL	50	6 35 02 160 25 0



Wide shape for maximum cutting performance and long, straight cuts.

Width	Length		No. in pack	
mm	mm	Mount	pcs	Part number
50	50	SL	1	6 35 02 221 21 0
50	50	SL	3	6 35 02 221 22 0
50	50	SL	5	6 35 02 221 23 0
50	50	SL	10	6 35 02 221 24 0
50	50	SL	50	6 35 02 221 25 0



Wide shape for maximum cutting performance and long, straight cuts.

Width Length			No. in pack	
mm	mm	Mount	pcs	Part number
65	50	SL	1	6 35 02 228 21 0
65	50	SL	3	6 35 02 228 22 0
65	50	SL	5	6 35 02 228 23 0
65	50	SL	10	6 35 02 228 24 0
65	50	SL	50	6 35 02 228 25 0



Extra wide shape for maximum cutting performance and long, straight cuts.

Width	Length		No. in pack	
mm	mm	Mount	pcs	Part number
65	50	SLP	1	6 35 02 161 21 0
65	50	SLP	3	6 35 02 161 22 0
65	50	SLP	5	6 35 02 161 23 0
65	50	SLP	10	6 35 02 161 24 0
65	50	SLP	50	6 35 02 161 25 0



Long, narrow shape for large plunge depths. With waist for optimum cutting speed and good swarf removal.

Width mm	Length mm	Mount	No. in pack pcs	Part number
32	78	SLM	1	6 35 02 201 21 0
32	78	SLM	3	6 35 02 201 22 0
32	78	SLM	5	6 35 02 201 23 0
32	78	SLM	10	6 35 02 201 24 0
32	78	SLM	50	6 35 02 201 25 0



Long, wide shape for large plunge depths and effective working. With waist for optimum cutting speed and good swarf removal.

Width mm	Length mm	Mount	No. in pack pcs	Part number
42	78	SLM	1	6 35 02 203 21 0
42	78	SLM	3	6 35 02 203 22 0
42	78	SLM	5	6 35 02 203 23 0
42	78	SLM	10	6 35 02 203 24 0
42	78	SLM	50	6 35 02 203 25 0



XXL length for very large plunge depths and special application solutions, such as replacing windows. With waist for optimum cutting speed and good swarf removal.

Width mm	Length mm	Mount	No. in pack pcs	Part number
32	90	SLM	1	6 35 02 224 21 0
32	90	SLM	3	6 35 02 224 22 0
32	90	SLM	5	6 35 02 224 23 0
32	90	SLM	10	6 35 02 224 24 0
32	90	SLM	50	6 35 02 224 25 0

9 STARLOCK ACCESSORIES



E-CUT STANDARD SAW BLADE

Set teeth for all wood, plasterboard and plastic materials, high cutting quality and speed.

Medium width, with waist for optimum cutting speed and good swarf removal.

Width mm	Length mm	Mount	No. in pack pcs	Part number
35	50	SL	1	6 35 02 133 21 0
35	50	SL	3	6 35 02 133 22 0
35	50	SL	5	6 35 02 133 23 0
35	50	SL	10	6 35 02 133 24 0
35	50	SL	50	6 35 02 133 25 0



Wide shape for maximum cutting performance and long, straight cuts.

Width mm	Length mm	Mount	No. in pack pcs	Part number
65	50	SLP	1	6 35 02 134 21 0
65	50	SLP	3	6 35 02 134 22 0
65	50	SLP	5	6 35 02 134 23 0
65	50	SLP	10	6 35 02 134 24 0
65	50	SLP	50	6 35 02 134 25 0



Long, narrow shape for large plunge depths. With waist for optimum cutting speed and good swarf removal.

Width mm	Length mm	Mount	No. in pack pcs	Part number
32	78	SLM	1	6 35 02 200 21 0
32	78	SLM	3	6 35 02 200 22 0
32	78	SLM	5	6 35 02 200 23 0
32	78	SLM	10	6 35 02 200 24 0
32	78	SLM	50	6 35 02 200 25 0



Long, wide shape for large plunge depths and effective working. With waist for optimum cutting speed and good swarf removal.

Width mm	Length mm	Mount	No. in pack pcs	Part number
42	78	SLM	1	6 35 02 202 21 0
42	78	SLM	3	6 35 02 202 22 0
42	78	SLM	5	6 35 02 202 23 0
42	78	SLM	10	6 35 02 202 24 0
42	78	SLM	50	6 35 02 202 25 0



E-CUT STANDARD SAW BLADE CURVED

Set teeth for all wood, plasterboard and plastic materials, high cutting quality and speed. Curved cutting geometry for optimum plunging and clean precise cut edges, especially on smooth surfaces.

Narrow, with waist for optimum cutting speed and good swarf removal.

Width mm	Length mm	Mount	No. in pack pcs	Part number
35	55	SL	1	6 35 02 227 21 0
35	55	SL	3	6 35 02 227 22 0
35	55	SL	5	6 35 02 227 23 0
35	55	SL	10	6 35 02 227 24 0
35	55	SL	50	6 35 02 227 25 0



Medium width for various uses.

Width mm	Length mm	Mount	No. in pack pcs	Part number
50	50	SL	1	6 35 02 226 21 0
50	50	SL	3	6 35 02 226 22 0
50	50	SL	5	6 35 02 226 23 0
50	50	SL	10	6 35 02 226 24 0
50	50	SL	50	6 35 02 226 25 0



Wide shape for maximum cutting performance and long, straight cuts.

Length	Marriet	No. in pack	Doub would be
mm	Mount	pcs	Part number
50	SL	1	6 35 02 225 21 0
50	SL	3	6 35 02 225 22 0
50	SL	5	6 35 02 225 23 0
50	SL	10	6 35 02 225 24 0
50	SL	50	6 35 02 225 25 0
	50 50 50 50	mm Mount 50 SL 50 SL 50 SL 50 SL 50 SL	mm Mount pcs 50 SL 1 50 SL 3 50 SL 5 50 SL 10



E-CUT PRECISION BIM SAW BLADE

Bimetal with double-row Japan teeth for all wooden materials, plasterboard and soft plastics. Improved tool life and robustness. The fastest cutting speed and maximum precision. Narrow, with waist for optimum cutting speed and good swarf removal.

Width mm	Length mm	Mount	No. in pack pcs	Part number
35	50	SL	1	6 35 02 205 21 0
35	50	SL	3	6 35 02 205 22 0
35	50	SL	5	6 35 02 205 23 0
35	50	SL	10	6 35 02 205 24 0
35	50	SL	50	6 35 02 205 25 0



Medium width for various uses.

Width	Length		No. in pack		
mm	mm	Mount	pcs	Part number	
50	50	SL	1	6 35 02 232 21 0	
50	50	SL	3	6 35 02 232 22 0	
50	50	SL	5	6 35 02 232 23 0	
50	50	SL	10	6 35 02 232 24 0	
50	50	SL	50	6 35 02 232 25 0	



Extra wide shape for maximum cutting performance and long, straight cuts.

Width Length			No. in pack		
mm	mm	Mount	pcs	Part number	
65	50	SL	1	6 35 02 229 21 0	
65	50	SL	3	6 35 02 229 22 0	
65	50	SL	5	6 35 02 229 23 0	
65	50	SL	10	6 35 02 229 24 0	
65	50	SL	50	6 35 02 229 25 0	



Extra wide shape for maximum cutting performance and long, straight cuts.

Length		No. in pack		
mm	Mount	pcs	Part number	
50	SLP	1	6 35 02 208 21 0	
50	SLP	3	6 35 02 208 22 0	
50	SLP	5	6 35 02 208 23 0	
50	SLP	10	6 35 02 208 24 0	
50	SLP	50	6 35 02 208 25 0	
	50 50 50 50	mm Mount 50 SLP 50 SLP 50 SLP 50 SLP 50 SLP	mm Mount pcs 50 SLP 1 50 SLP 3 50 SLP 5 50 SLP 10	



E-CUT PRECISION SAW BLADE

Double-row Japan teeth for all wooden materials, plasterboard and soft plastics. The fastest cutting speed and maximum precision.

Narrow, with waist for optimum cutting speed and good swarf removal.

Width	Length		No. in pack		
mm	mm	Mount	pcs	Part number	
35	50	SL	1	6 35 02 126 21 0	
35	50	SL	3	6 35 02 126 22 0	
35	50	SL	5	6 35 02 126 23 0	
35	50	SL	10	6 35 02 126 24 0	
35	50	SL	50	6 35 02 126 25 0	



Medium width for various uses.

Width Length			No. in pack		
mm	mm	Mount	pcs	Part number	
50	50	SL	1	6 35 02 233 21 0	
50	50	SL	3	6 35 02 233 22 0	
50	50	SL	5	6 35 02 233 23 0	
50	50	SL	10	6 35 02 233 24 0	
50	50	SL	50	6 35 02 233 25 0	



Extra wide shape for maximum cutting performance and long, straight cuts.

Width mm	Length mm	Mount	No. in pack pcs	Part number
65	50	SL	1	6 35 02 230 21 0
65	50	SL	3	6 35 02 230 22 0
65	50	SL	5	6 35 02 230 23 0
65	50	SL	10	6 35 02 230 24 0
65	50	SL	50	6 35 02 230 25 0



Extra wide shape for maximum cutting performance and long, straight cuts.

Width mm	Length mm	Mount	No. in pack pcs	Part number
65	50	SLP	1	6 35 02 127 21 0
65	50	SLP	3	6 35 02 127 22 0
65	50	SLP	5	6 35 02 127 23 0
65	50	SLP	10	6 35 02 127 24 0
65	50	SLP	50	6 35 02 127 25 0



E-CUT UNIVERSAL SAW BLADE

Bimetal with corrugated universal teeth. Wide range of applications for sheet metal up to 2 mm, aluminium profiles, copper pipes, wood, plasterboard and plastics. Narrow, with waist for optimum cutting speed and good swarf

removal.

Width mm	Length mm	Mount	No. in pack pcs	Part number
28	55	SL	1	6 35 02 222 21 0
28	55	SL	3	6 35 02 222 22 0
28	55	SL	5	6 35 02 222 23 0
28	55	SL	10	6 35 02 222 24 0
28	55	SL	50	6 35 02 222 25 0



Narrow, with waist for optimum cutting speed and good swarf removal.

147 111			NI 1	
Width	Length		No. in pack	
mm	mm	Mount	pcs	Part number
28	60	SLP	1	6 35 02 151 21 0
28	60	SLP	3	6 35 02 151 22 0
28	60	SLP	5	6 35 02 151 23 0
28	60	SLP	10	6 35 02 151 24 0
28	60	SLP	50	6 35 02 151 25 0



Medium width, with waist for optimum cutting speed and good swarf removal.

Width	Length		No. in pack	
mm	mm	Mount	pcs	Part number
44	55	SL	1	6 35 02 223 21 0
44	55	SL	3	6 35 02 223 22 0
44	55	SL	5	6 35 02 223 23 0
44	55	SL	10	6 35 02 223 24 0
44	55	SL	50	6 35 02 223 25 0



Medium width, with waist for optimum cutting speed and good swarf removal.

Length		No. in pack	
mm	Mount	pcs	Part number
60	SLP	1	6 35 02 152 21 0
60	SLP	3	6 35 02 152 22 0
60	SLP	5	6 35 02 152 23 0
60	SLP	10	6 35 02 152 24 0
60	SLP	50	6 35 02 152 25 0
	60 60 60 60	mm Mount 60 SLP 60 SLP 60 SLP 60 SLP	mm Mount pcs 60 SLP 1 60 SLP 3 60 SLP 5 60 SLP 10



E-CUT FINE SAW BLADE

Bimetal with fine teeth for sheet metal up to 2 mm, aluminium profiles, copper pipes. Also for fibreglass-reinforced plastic and other hard plastics. Extremely precise cuts which are very easy to control with particularly thin cutting line.

Narrow, with waist for optimum cutting speed and good swarf removal.

Width mm	Length mm	Mount	No. in pack pcs	Part number
30	50	SL	1	6 35 02 157 21 0
30	50	SL	3	6 35 02 157 22 0
30	50	SL	5	6 35 02 157 23 0
30	50	SL	10	6 35 02 157 24 0
30	50	SL	50	6 35 02 157 25 0



E-CUT CARBIDE PRO

TiN-coated carbide plunge-cut saw blade with extremely good resistance to wear. Lasts 100 % longer than uncoated carbide saw blades. Lasts 30 times longer than HSS saw blades. The right choice for tough materials, such as ferrous metals, stainless steel or copper pipes. Can even be used for hardened screws (Spax) and high-strength machine screws. But also ideally suited to abrasive materials, such as bricks, masonry or fibre cement boards as well as laminate, carbon fibre-reinforced plastic and fibreglass-reinforced plastic. Good cutting results and cutting quality in all timber materials, such as hardwood or chipboard.

Narrow, with waist for optimum cutting speed and good swarf removal.

Width mm	Length mm	Mount	No. in pack pcs	Part number
32	40	SL	1	6 35 02 236 21 0
32	40	SL	3	6 35 02 236 22 0
32	40	SL	5	6 35 02 236 23 0
32	40	SL	10	6 35 02 236 24 0
32	40	SL	50	6 35 02 236 25 0



Narrow, with waist for optimum cutting speed and good swarf removal

Width mm	Length mm	Mount	No. in pack pcs	Part number
32	60	SLP	1	6 35 02 237 21 0
32	60	SLP	3	6 35 02 237 22 0
32	60	SLP	5	6 35 02 237 23 0
32	60	SLP	10	6 35 02 237 24 0
32	60	SLP	50	6 35 02 237 25 0



Narrow, with waist for optimum cutting speed and good swarf removal

Width	Length		No. in pack	
mm	mm	Mount	pcs	Part number
32	75	SLM	1	6 35 02 238 21 0
32	75	SLM	3	6 35 02 238 22 0
32	75	SLM	5	6 35 02 238 23 0
32	75	SLM	10	6 35 02 238 24 0

9 STARLOCK ACCESSORIES



CARBIDE SAW BLADE

Open teeth for perfect, clean cut edges in carbon fibrereinforced plastic/fibreglass-reinforced plastic materials without delamination. Distortion-free, long, straight cuts at high cutting speed and with precision.

Extra thin version. Cutting width approx. 1.2 mm. Segmented, ideal for working in corners and on edges without overcutting.

mm	Mount	Part number
90	SLP	6 35 02 187 21 0



Diamond coating for outstanding service life. Extra thin version. Cutting width approx. 1.2 mm. Segmented, ideal for working in corners and on edges without overcutting.

0		
mm	Mount	Part number
90	SLP	6 35 02 188 21 0



Diamond coating for outstanding service life. Extra thin version. Cutting width approx. 1.2 mm.

mm	Mount	Part number
105	SLM	6 35 02 220 21 0



E-CUT CARBIDE SAW BLADE

Gentle sawing with perfect, clean cut edges in carbon fibrereinforced plastic/fibreglass-reinforced plastic materials without delamination. Particularly well suited to precise cut-outs and short cuts. Precise working into the corners and on edges.

Width	Length			
mm	mm	Mount	Part number	
35	50	SLP	6 35 02 191 21 0	



E-CUT DIAMOND SAW BLADE

Diamond coating for outstanding service life. Gentle sawing with perfect, clean cut edges in carbon fibre-reinforced plastic/fibreglass-reinforced plastic materials without delamination. Particularly well suited to precise cut-outs and short cuts. Precise working into the corners and on edges.

Width mm	Length mm	Mount	Part number
44	60	SLM	6 35 02 204 21 0
35	50	SLP	6 35 02 193 21 0



SEGMENT SAW BLADE

For cutting out putty-mounted isolation glass.

	No. in pack	
Mount	pcs	Part number
SLM	2	6 39 03 244 22 0



BEST OF STARLOCK RENOVATION

Accessory kit containing 26 parts for upcoming renovation work. Suitable for all FEIN Multitools and all other common Multitools with Starlock mounting. Available as a set, offering significant savings over purchasing the items individually. Content: 6 E-Cut long-life saw blades (2 each of 50×35 mm, 50×50 mm, 50×65 mm), 1 carbide rasp (80 mm), 1 carbide segment saw blade (diameter 75 mm, 2.2 mm), 1 rigid stopper knife, 1 cutter blade, (mushroom–shaped), 1 sanding pad, unperforated (80 mm), sanding sheets (5 each of grif 60, 80, 120).

Mount	Part number
SL	3 52 22 967 06 0



BEST OF STARLOCK METAL

6 saw blades, especially for machining hardened and non-hardened metals. Suitable for all FEIN Multitools and all other common Multitools with Starlock mounting. Available as a set, offering significant savings over purchasing the items individually. Content: $1\,\text{E-Cut}$ CarbidePRO saw blade (40 x 32 mm), E-Cut long-life saw blades (1 each of 50 x 35 mm and 50 x 50 mm), $1\,\text{E-Cut}$ universal saw blade (55 x 44 mm), $1\,\text{E-Cut}$ fine saw blade (50 x 30 mm), $1\,\text{complete}$ HSS segment saw blade (diameter 85 mm).

Mount	Part number
SL	3 52 22 967 02 0



STARLOCKMAX INTERIOR WORK PROFESSIONAL SET

Accessory kit containing 45 parts with extensive range of saw blades for fast, precise sawing in all kinds of installation work. Suitable for FEIN Multitools with StarlockMax mounting and all other common Multitools with StarlockMax mounting. Available as a set, offering significant savings over purchasing the items individually. Content: 8 E-Cut long-life saw blades (1 set of 34 x 20 mm, 2 each of 50 x 35 mm and 50 x 65 mm, 1 each of 78 x 32 mm, 78 x 42 mm and 90 x 32 mm), E-Cut precision BIM saw blade (1 each of 50 x 35 mm, 50 x 65 mm), 1 HSS circular saw blade (diameter 100 mm), 1 depth stop, 1 rigid stopper knife, long, 1 extraction device, anti-static, 1 sanding pad, perforated (80 mm), sanding sheets, perforated (10 each of grit 60, 80, 120).

Mount	Part number
SLM	3 52 22 967 12 0



STARLOCK RENOVATION COMBO

3 accessories, especially for renovation work on flooring. Suitable for all FEIN Multitools and all other common Multitools with Starlock mounting. Available as a set, offering significant savings over purchasing the items individually. Content: 1 carbide segment saw blade (diameter 85 mm), 1 E-Cut long-life saw blade (50 x 35 mm), 1 rigid stopper knife.

Mount	Part number
SI	3 52 22 967 11 0



PROFESSIONAL MARINE SET

7-part accessory set for use in the marine sector for interior work, maintenance and repairs to yachts. Suitable for all Multitools with a StarlockPlus or StarlockMax fitting. Available as a set, offering significant savings over purchasing the items individually.

Mount	Part number
SLP	3 52 22 967 26 0

GRINDING & POLISHING



BEST OF STARLOCK SANDING

Accessory kit containing 63 parts for sanding in corners and on edges. Suitable for all FEIN Multitools and all other common Multitools with Starlock mounting. Available as a set, offering significant savings over purchasing the items individually. Content: 2 sanding pads, unperforated (80 mm), 1 sanding finger, sanding sheets (10 each of grit 60, 80, 120) for sanding pad and sanding finger.

Mount	Part number
SL	3 52 22 967 04 0



SANDING PAD SET, UNPERFORATED

Standard version. Plastic carrier plate for preventing damage and marks on the workpiece.

Triangular shape, hook and loop fastening.

Edge length		No. in pack	
mm	Mount	pcs	Part number
80	SL	2	6 38 06 129 22 0



SANDING PAD SET, FLAT

For very narrow, flat openings (e.g. slats on cupboards, window shutters). Plastic carrier plate for preventing damage and marks on the workpiece.

Triangular shape, flat version, hook and loop fastening.

Edge length		No. in pack	
mm	Mount	pcs	Part number
80	SL	2	6 38 06 142 22 0



SUPERSOFT SANDING PAD

For special areas of application such as touching up aluminium rims and paint repairs. Plastic carrier plate for preventing damage and marks on the workpiece. Only use with "Sanding sheets, super-soft".

Triangular shape, super-soft version, hook and loop fastening

80	SL	2	6 38 06 141 22 0
mm	Mount	pcs	Part number
Edge length		No. in pack	



SET OF SANDING SHEETS

50 sanding sheets of various grits for the universal use of coarse to fine sanding on virtually all materials. High sanding capacity, little clogging and long service life guaranteed thanks to corundum abrasive grit and full bonding with artificial resins. Content: sanding sheets, 10 each of grit 60, 80, 120, 180 and 240, non-perforated, with hook and loop fastening. Better value than buying items separately.

Edge length mm Part number 6 37 17 082 03 3 80



SANDING SHEETS

High sanding capacity, little clogging and long service life guaranteed thanks to corundum abrasive grit and full bonding with artificial resins. For universal use on virtually all materials. Non-perforated, hook and loop fastening.

	Edge length	No. in pack	
Grain	mm	pcs	Part number
36	80	5	6 37 17 086 04 8
40	80	5	6 37 17 081 04 6
60	80	5	6 37 17 082 04 9
80	80	5	6 37 17 083 04 3
100	80	5	6 37 17 084 04 1
120	80	5	6 37 17 085 04 5
150	80	5	6 37 17 087 04 2
180	80	5	6 37 17 088 04 0
220	80	5	6 37 17 089 04 4
240	80	5	6 37 17 090 04 6
36	80	50	6 37 17 086 01 0
40	80	50	6 37 17 081 01 8
60	80	50	6 37 17 082 01 1
80	80	50	6 37 17 083 01 5
100	80	50	6 37 17 084 01 3
120	80	50	6 37 17 085 01 7
150	80	50	6 37 17 087 01 4
180	80	50	6 37 17 088 01 2
220	80	50	6 37 17 089 01 6
240	80	50	6 37 17 090 01 8



SANDING SHEETS, ZIRCONIUM

Excellent sanding capacity on extremely hard surfaces such as varnish (e.g. parquet paint) or metal. The sanding sheet for all floor covering work. Extremely sturdy paper quality thanks to extremely tough full bonding with artificial resins and highquality zirconium corundum coating. Non-perforated, hook and loop fastening.

	Edge length	No. in pack	
Grain	mm	pcs	Part number
40	80	35	6 37 17 243 01 0
60	80	35	6 37 17 244 01 0
80	80	35	6 37 17 245 01 0



SUPERSOFT SANDING SHEETS

Special sanding sheets for machining aluminium rims, performing touch-up work on dust inclusions, dealing with paint runs, overspray on wood, plastic, metal, etc. Only to be used in conjunction with the sanding pad 6 38~06~141~22~0. Non-perforated, hook and loop fastening.

Grain	Edge length mm	No. in pack pcs	Part number
240	80	50	6 37 17 126 01 5
320	80	50	6 37 17 127 01 9
400	80	50	6 37 17 128 01 7
500	80	50	6 37 17 179 01 6

9 STARLOCK ACCESSORIES



STONE SANDING SHEETS

Specially for working with natural and artificial stone. Available up to grit 800 for a perfect surface finish in fine sanding. Non-perforated, hook and loop fastening.

	Edge length	No. in pack	
Grain	mm	pcs	Part number
40	80	50	6 37 17 120 01 4
80	80	50	6 37 17 121 01 3
120	80	50	6 37 17 122 01 6
220	80	50	6 37 17 123 01 0
320	80	50	6 37 17 124 01 8
400	80	50	6 37 17 125 01 2
600	80	50	6 37 17 175 01 7



SANDING FINGER

For use in very narrow and deep places, in channels, grooves, openings and folds. Also in mould-making, on concave forms and in convex forms. Plastic carrier plate for preventing damage and marks on the workpiece.

Finger shape, hook and loop fastening.

	No. in pack		
Mount	pcs	Part number	
SL	2	6 38 06 159 22 0	



SANDING SHEETS FOR SANDING FINGERS

With Velcro rapid attachment, fully bonded with artificial resin, high sanding capacity, corundum. For use on: wood, metal, soldered joints, fibreglass, plastic, paint, filler, leather. Pack of

	No. in pack	
Grain	pcs	Part number
40	20	6 37 17 184 01 2
60	20	6 37 17 185 01 6
80	20	6 37 17 186 01 9
100	20	6 37 17 187 01 3
120	20	6 37 17 188 01 1
150	20	6 37 17 189 01 5
180	20	6 37 17 190 01 7
220	20	6 37 17 191 01 6
240	20	6 37 17 192 01 9



PROFILE SANDING SET

22-part set for sanding in grooves and on outside radii. Contents: 1 holder with 6 different profile inserts. 1 x V-form for 90° angle, 1 x trapezium form for tongue-and-groove connections, 1 x straight form for profiles, 1 x convex form (large), 1 x concave and 1 x convex form (small) and sanding sheets, 5 each of 80, 120 and 180 grit.

Mount	Part number
SLP	6 38 10 031 01 0



SANDPAPER FOR PROFILE SANDING SET

High sanding capacity, little clogging and long service life guaranteed thanks to corundum abrasive grit and full bonding with artificial resins. For universal use on virtually all materials, non-perforated.

	No. in pack	
Grain	pcs	Part number
80	25	6 37 17 217 01 6
120	25	6 37 17 218 01 4
180	25	6 37 17 219 01 8



SANDING PAD SET, PERFORATED

Standard version for sanding with dust extraction. Plastic carrier plate for preventing damage and marks on the workpiece.

Triangular shape, perforated version, hook and loop fastening.

Edge length		No. in pack	
mm Mount		pcs	Part number
80	SL	2	6 38 06 136 22 0



SET OF SANDING SHEETS

50 sanding sheets of various grits for the universal use of coarse to fine sanding on virtually all materials. High sanding capacity, little clogging and long service life guaranteed thanks to corundum abrasive grit and full bonding with artificial resins. Content: sanding sheets, 10 each of grit 60, 80, 120, 180, 240, perforated, for use with perforated sanding pad and dust extraction, hook and loop fastening. Better value than buying items separately.

Edge length	
mm	Part number
80	6 37 17 109 03 5



SANDING SHEETS, PERFORATED

High sanding capacity, little clogging and long service life guaranteed thanks to corundum abrasive grit and full bonding with artificial resins. For universal use on virtually all materials. Perforated, for use with perforated sanding pad and dust extraction, hook and loop fastening.

	Edge length	No. in pack	
Grain	mm	pcs	Part number
36	80	5	6 37 17 107 04 9
40	80	5	6 37 17 108 04 7
60	80	5	6 37 17 109 04 1
80	80	5	6 37 17 110 04 3
100	80	5	6 37 17 111 04 2
120	80	5	6 37 17 112 04 5
150	80	5	6 37 17 113 04 9
180	80	5	6 37 17 114 04 7
220	80	5	6 37 17 115 04 1
240	80	5	6 37 17 116 04 4
36	80	50	6 37 17 107 01 1
40	80	50	6 37 17 108 01 9
60	80	50	6 37 17 109 01 3
80	80	50	6 37 17 110 01 5
100	80	50	6 37 17 111 01 4
120	80	50	6 37 17 112 01 7
150	80	50	6 37 17 113 01 1
180	80	50	6 37 17 114 01 9
220	80	50	6 37 17 115 01 3
240	80	50	6 37 17 116 01 6



SANDING SHEETS, ZIRCONIUM

Excellent sanding capacity on extremely hard surfaces such as varnish (e.g. parquet paint) or metal. The sanding sheet for all floor covering work. Extremely sturdy paper quality thanks to extremely tough full bonding with artificial resins and high-quality zirconium corundum coating. Perforated, for use with perforated sanding pad and dust extraction, hook and loop fastering.

Grain	Edge length mm	No. in pack pcs	Part number
40	80	35	6 37 17 236 01 0
60	80	35	6 37 17 237 01 0
80	80	35	6 37 17 238 01 0



SANDING SET

For the efficient sanding of edge and corner areas and mediumsized surfaces. The alternative to eccentric or random sanders No kick-back effect at edges. Easy to use, very good sanding capacity. Plastic carrier plate prevents damage and marks on the workpiece.

Scope of supply: 1 large perforated triangular sanding pad (edge length 130 mm), with perforated sanding sheets, 2 each of grit 60, 80, 180.

Edge length		
mm	Mount	Part number
130	SLP	6 38 06 204 21 0



SANDING SHEETS, PERFORATED

Compatible with large triangular sanding pad with 130 mm edge length.

High sanding capacity, little clogging and long service life guaranteed thanks to corundum abrasive grit and full bonding with artificial resins. For universal use on virtually all materials. Perforated, for use with perforated sanding pad and dust extraction, hook and loop fastening.

	Edge length	No. in pack	
Grain	mm	pcs	Part number
60	130	16	6 37 17 293 02 0
80	130	16	6 37 17 294 02 0
120	130	16	6 37 17 295 02 0
180	130	16	6 37 17 296 02 0
240	130	16	6 37 17 297 02 0



SET OF SANDING SHEETS

16 sanding sheets of various grits for the universal use of coarse to fine sanding on virtually all materials. High sanding capacity, little clogging and long service life guaranteed thanks to corundum abrasive grit and full bonding with artificial resins. Content: sanding sheets for large triangular sanding pad (edge length 130 mm), 4 each of grit 60, 80, 120, 180, perforated, for use with and without dust extraction, hook and loop fastening. Better value than buying items separately.

Edge length	
mm	Part number
130	3 52 22 952 10 0



SANDING SHEETS, ZIRCONIUM

Compatible with large triangular sanding pad with 130 mm edge length. $\,$

Excellent sanding capacity on extremely hard surfaces such as varnish (e.g. parquet paint) or metal. The sanding sheet for all floor covering work. Extremely sturdy paper quality thanks to extremely tough full bonding with artificial resins and high-quality zirconium corundum coating. Perforated, for use with perforated sanding pad and dust extraction, hook and loop fastening.

	Edge length	No. in pack	
Grain	mm	pcs	Part number
40	130	12	6 37 17 298 01 0
60	130	12	6 37 17 299 01 0
80	130	12	6 37 17 300 01 0



SANDING SET

For quickly and cost-effectively sanding medium-sized surfaces. The alternative to eccentric or random sanders. No kick-back effect at edges. Easy to use, very good sanding capacity. Can be used with or without dust extraction. Plastic carrier plate for preventing damage and marks on the workpiece.

Round shape, perforated version, hook and loop fastening Scope of supply: 1 backing pad diameter 115 mm, with perforated sanding sheets, 2 each of grit 60, 80, 180.

Ø mm	Mount	Part number
115	SLP	6 38 06 195 21 0



SET OF SANDING SHEETS

16 sanding sheets of various grits for the universal use of coarse to fine sanding on virtually all materials. High sanding capacity, little clogging and long service life guaranteed thanks to corundum abrasive grit and full bonding with artificial resins. Content: sanding sheets, 4 each of grit 60, 80, 120, 180, 115 mm diameter, perforated, for use with and without dust extraction, hook and loop fastening. Better value than buying items separately.

Part number
6 37 17 227 01 0



SANDING SHEETS

High sanding capacity, little clogging and long service life guaranteed thanks to corundum abrasive grit and full bonding with artificial resins. For universal use on virtually all materials. 115 mm diameter, perforated, for use with and without dust extraction, hook and loop fastening.

	No. in pack	
Grain	pcs	Part number
40	16	6 37 17 230 02 0
60	16	6 37 17 227 02 0
80	16	6 37 17 228 02 0
120	16	6 37 17 229 01 0
180	16	6 37 17 231 02 0
240	16	6 37 17 232 01 0



SANDING SHEETS, ZIRCONIUM

Excellent sanding capacity on extremely hard surfaces such as varnish (e.g. parquet paint) or metal. The sanding sheet for all floor covering work. Extremely sturdy paper quality thanks to extremely tough full bonding with artificial resins and high-quality zirconium corundum coating. 115 mm diameter, perforated, for use with and without dust extraction, hook and loop fastening.

	No. in pack	
Grain	pcs	Part number
40	12	6 37 17 233 01 0
60	12	6 37 17 234 01 0
80	12	6 37 17 235 01 0



SANDING SHEET SET, ZIRCONIUM

12 sanding sheets with excellent sanding capacity on extremely hard surfaces such as varnish (e.g. parquet paint) or metal. The sanding sheet for all floor covering work. Extremely sturdy paper quality thanks to extremely tough full bonding with artificial resins and high-quality zirconium corundum coating. Content: sanding sheets, 4 each of grit 40, 60, 80, 115 mm diameter, perforated, for use with and without dust extraction, hook and loop fastening. Better value than buying items separately.

Part number 6 37 17 233 02 0



BRISTLE FLEECE

Bristle fleece for cleaning boat decks or cleaning/polishing anti-slip structures.

Edge length	No. in pack	
mm	pcs	Part number
80	2	6 37 23 031 01 0



FELT POLISHING PAD

For polishing up metal parts, and for polishing and decorative polishing of stone and stone products. Can also be used to work with gelcoats on boats. Plastic carrier plate for preventing damage and marks on the workpiece.

Burnishing compounds for the respective material are available from specialist retailers.

Edge length		No. in pack	
mm	Mount	pcs	Part number
80	SL	2	6 38 06 140 22 0

9 STARLOCK ACCESSORIES



FELT POLISHING PAD

Felt polishing pad for polishing boat decks (gelcoat), chrome, stainless steel, aluminium, copper and copper alloys.

Edge length	No. in pack	
mm	pcs	Part number
80	5	6 37 23 032 01 0



FELT POLISHING PAD

Diameter 115 mm, with hook and loop fastening. Versatile in use, for polishing chrome, stainless steel, polycarbonate materials and gelcoat boat decks, for polishing up scratched paint and removing tempering colours on exhaust systems.

No.	in	pack	

pcs	Part number
5	6 37 23 036 01 0



SANDING SHEETS, FOAM BACKING

for removing scratches from paintwork, gelcoat, acrylic and polycarbonate glazing, lacquers, wood with a clear lacquer, furniture etc. For the best surface quality. 115 mm diameter with foam lamination, hook and loop fastening. Perfect as stage prior to polishing with felt polishing pad and FEIN EXTRA polish.

	No. in pack	
Grain	pcs	Part number
500	5	6 37 17 246 01 0
1000	5	6 37 17 247 01 0

CUTTING, FILING



CARBIDE SAW BLADE

For cutting out damaged tile joints. Also for cutting slots in plaster, porous concrete and similar building materials and for cleaning and reworking deck joints. Not suited to very hard epoxy resin or cement joints. The cost-effective alternative to diamond tools.

Segmented, ideal for working in corners and on edges without overcutting. Cutting width approx. 2.2 mm.

Ø		No. in pack	
mm	Mount	pcs	Part number
75	SL	1	6 35 02 118 21 0
75	SL	5	6 35 02 118 23 0



Segmented, ideal for working in corners and on edges without overcutting. Cutting width approx. 2.2 mm.

Ø		No. in pack	
mm	Mount	pcs	Part number
90	SLP	1	6 35 02 169 21 0
90	SLP	5	6 35 02 169 23 0



Extra thin version. Cutting width approx. 1.2 mm. Segmented, ideal for working in corners and on edges without overcutting.

Ø		No. in pack	
mm	Mount	pcs	Part number
75	SL	1	6 35 02 125 21 0
75	SL	5	6 35 02 125 23 0



Extra thin version. Cutting width approx. 1.2 mm. Segmented, ideal for working in corners and on edges without overcutting.

Ø		No. in pack	
mm	Mount	pcs	Part number
90	SLP	1	6 35 02 170 21 0
90	SLP	5	6 35 02 170 23 0



CARBIDE SAW BLADE

For cutting out very narrow marble, epoxy resin and trass joints. Not suited to very hard epoxy resin or cement joints. The cost-effective alternative to diamond tools. Extra thin version. Cutting width approx. 1.2 mm. Segmented, ideal for working in corners and on edges without overcutting.

	No. in pack	
Mount	pcs	Part number
SLM	1	6 39 03 240 21 0
SLM	5	6 39 03 240 23 0



CARBIDE SAW BLADE

For cutting out marble, epoxy resin and trass joints. Not suited to very hard epoxy resin or cement joints. The cost-effective alternative to diamond tools.

Segmented, ideal for working in corners and on edges without overcutting. Cutting width approx. 2.2 mm.

	No. In pack		
Mount	pcs	Part number	
SLM	1	6 39 03 241 21 0	
SLM	5	6 39 03 241 23 0	



DIAMOND-COATED SAW BLADE

For cutting out marble, epoxy resin and trass joints. Excellent service life. Also suited to very hard epoxy resin or cement joints. The right choice for frequent use and challenging jobs. Extra thin version. Cutting width approx. 1.2 mm. Segmented, ideal for working in corners and on edges without overcutting.

Ø		No. in pack	
mm	Mount	pcs	Part number
75	SL	1	6 35 02 216 21 0
75	SL	5	6 35 02 216 23 0



Extra thin version. Cutting width approx. 1.2 mm. Segmented, ideal for working in corners and on edges without overcutting

Ø		No. in pack	
mm	Mount	pcs	Part number
90	SLP	1	6 35 02 217 21 0
90	SLP	5	6 35 02 217 23 0



Segmented, ideal for working in corners and on edges without overcutting. Cutting width approx. 2.2 mm.

Ø		No. in pack	
mm	Mount	pcs	Part number
75	SL	1	6 35 02 114 21 0
75	SL	5	6 35 02 114 23 0



DIAMOND-COATED SAW BLADE

For cutting out marble, epoxy resin and trass joints. Excellent service life. Also suited to very hard epoxy resin or cement joints. The right choice for frequent use and challenging jobs. Segmented, ideal for working in corners and on edges without overcutting. Cutting width approx. 2.2 mm.

Ø		No. in pack	
mm	Mount	pcs	Part number
90	SL	1	6 35 02 166 21 0
90	SL	5	6 35 02 166 23 0



Extra thin version. Cutting width approx. 1.2 mm. Segmented, ideal for working in corners and on edges without overcutting.

	No. in pack	
Mount	pcs	Part number
SLM	1	6 39 03 242 21 0
SLM	5	6 39 03 242 23 0



Segmented, ideal for working in corners and on edges without overcutting. Cutting width approx. 2.2 mm.

	No. in pack	
Mount	pcs	Part number
SLM	1	6 39 03 243 21 0
SLM	5	6 39 03 243 23 0



CARBIDE RASP

For rough sanding of fillers, tile adhesive, concrete, stone and wood.

Triangular shape, edge length of 80 mm, perforated, can also be used with dust extraction.

Edge length mm	Mount	Part number
80	SL	6 37 31 001 21 0



CARBIDE RASP

For rough sanding of fillers, tile adhesive, concrete, stone and wood. For use in very narrow and deep places, in channels, grooves, openings and folds. Also in mould-making, on concave forms and in convex forms and for artistic work. Finger shape, coating on both sides.

Mount	Part number
SLP	6 37 31 002 21 0



CARBIDE RASP

For rough sanding of fillers, tile adhesive, concrete, stone and wood. For particularly good cutting speed and efficient machining of several square metres.

Triangular shape, large version, edge length of 110 mm, perforated, can also be used with dust extraction.

Edge length mm	Mount	Part number
110	SLM	6 37 31 006 21 0



TILE JOINT CLEANER

For quickly and cost-effectively cleaning very dirty tile joints. The alternative to a costly, complete renovation. Suitable for all widths of tile joint.

	No. in pack	
Mount	pcs	Part number
SLP	2	6 37 19 011 22 0



CLEANING BLOCK

Rhombus for cleaning the carbide tools and diamond-coated

Part number
6 37 19 007 01 0



CARBIDE FILE

For deburring and filing on CFRP, fibreglass-reinforced plastic, plastics and wood. Especially suitable for cutting out small

Width	Length		
mm	mm	Mount	Part number
10	30	SL	6 37 06 019 21 0



DIAMOND CLEANING KNIFE

For cleaning mortar flanks before filling them in again. Straight. Width 31 mm, cutting depth 60 mm.

	No. in pack	
Mount	pcs	Part number
SLM	1	6 39 03 237 21 0
SLM	5	6 39 03 237 23 0



STARLOCK TILE WORKING COMBO

3 accessories, especially for renovation and repair jobs in sanitary facilities. When undertaking partial repairs on individual tiles, tile joints can be cut out quickly and cleanly, getting right into the corners and edges without overcutting. Suitable for all FEIN Multitools and all other common Multitools with Starlock mounting. Available as a set, offering significant savings over purchasing the items individually. Content: 1 E-Cut universal saw blade (55 x 28 mm), 1 carbide rasp (80 mm), 1 carbide segment saw blade (diameter 75 mm, 2.2 mm).

Mount	Part number
SL	3 52 22 967 07 0



STARLOCKMAX HEATING/SANITARY PROFESSIONAL SET

Accessory kit containing 8 parts with extensive range of accessories, especially for key applications in sanitary repairs. Suitable for FEIN Multitools with StarlockMax mounting and all other common Multitools with StarlockMax mounting. Available as a set, offering significant savings over purchasing the items individually. Content: 2 E-Cut universal saw blades (60 x 28 mm, 60 x 44 mm), 1 cutter blade (mushroom-shaped), 1 rigid stopper knife, carbide rasp (1 each of 80 mm, 110 mm), 1 carbide segment saw blade (diameter 90 x 2.2 mm), 1 carbide saw blade (2.2 mm).

Mount	Part number
SLM	3 52 22 967 14 0

CUTTING, SCRAPING



MULTI-FUNCTION KNIFE

For cutting carpet, PVC floors, cardboard, bitumen shingles and roofing fabric. With three cutting surfaces.

	No. in pack	
Mount	pcs	Part number
SL	1	6 39 03 251 21 0
SL	5	6 39 03 251 23 0



FLEXIBLE SCRAPER BLADE

Short version. For removing silicone or acrylic joints in bathrooms and removing stickers.

Mount	Part number
SI	6 39 03 165 21 0



FIXED SCRAPER BLADE

Short version. For removing stubborn old paint, adhesive residues, carpets, tile adhesives and coats of underseal.

Mount	Part number
SL	6 39 03 226 21 0

9 STARLOCK ACCESSORIES



FIXED SCRAPER BLADE

Long version. For removing stubborn old paint, adhesive residues, carpets, tile adhesives and coats of underseal.

Mount	Part number
SLP	6 39 03 234 21 0



CUTTING BLADE

Mushroom-shaped, for cutting silicone and soft putty material and for separating insulation glass units.

	No. in pack	
Mount	pcs	Part number
SL	5	6 39 03 245 23 0



CUTTING BLADE

For cutting away panelled deck sealant materials quickly and safely. Also ideal for difficult areas such as cabins, rails, qunwales, cleats, and curves.

Blade width mm	Mount	Part number
3	SLP	6 39 03 200 21 0
4	SLP	6 39 03 201 21 0
5	SLP	6 39 03 202 21 0



CUTTING BLADE

Universal blade for virtually all expansion joints. Straight. Width 30 mm, cutting depth 60 mm.

	No. in pack	
Mount	pcs	Part number
SLM	5	6 39 03 236 23 0



CUTTING BLADE

Straight, long shape, for deep joints.

Cutting depth		No. in pack	
mm	Mount	pcs	Part number
65	SLM	5	6 39 03 239 23 0



CUTTING BLADE

Straight, very long shape, for very deep joints.

Cutting depth		No. in pack		
mm	Mount	pcs	Part number	
69	SLM	1	6 39 03 238 21 0	



STARLOCKMAX GROUT RENEWAL PROFESSIONAL SET

Set of 7 blades for professional renovation of expansion joints down to a depth of 90 mm. Suitable for FEIN Multitools with StarlockMax mounting and all other common Multitools with StarlockMax mounting. Available as a set, offering significant savings over purchasing the items individually. Content: 1 cutter blade, straight (65 mm), 1 cutter blade, straight, very long shape (69 mm), 5 universal cutter blades, straight (60 x 30 mm).

Mount	Part number
SLM	3 52 22 967 13 0

ACCESSORY SETS



BEST OF E-CUT STARLOCK WOOD & METAL

6 E-Cut plunge-cut saw blades for sawing in wood and metal. Suitable for all FEIN Multitools and all other common Multitools on the market. Available as a set, offering significant savings over purchasing the items individually. Content: E-Cut long-life saw blades (2 each of 50 x 35 mm, 50 x 65 mm), E-Cut universal saw blade (1 each of 55 x 28 mm, 55 x 44 mm).

Mount	Part number
SL	3 52 22 967 01 0



BEST OF STARLOCK SANDING

Accessory kit containing 63 parts for sanding in corners and on edges. Suitable for all FEIN Multitools and all other common Multitools with Starlock mounting. Available as a set, offering significant savings over purchasing the items individually. Content: 2 sanding pads, unperforated (80 mm), 1 sanding finger, sanding sheets (10 each of grit 60, 80, 120) for sanding pad and sanding finger.

Mount	Part number
SL	3 52 22 967 04 0



BEST OF STARLOCK METAL

6 saw blades, especially for machining hardened and nonhardened metals. Suitable for all FEIN Multitools and all other common Multitools with Starlock mounting. Available as a set, offering significant savings over purchasing the items individually. Content: 1 E-Cut CarbidePRO saw blade (40 x 32 mm), E-Cut long-life saw blades (1 each of 50 x 35 mm and 50 x 50 mm), 1 E-Cut universal saw blade (55 x 44 mm), 1 E-Cut fine saw blade (50 x 30 mm), 1 complete HSS segment saw blade (diameter 85 mm).

Mount	Part number
SL	3 52 22 967 02 0



BEST OF STARLOCK RENOVATION

Accessory kit containing 26 parts for upcoming renovation work. Suitable for all FEIN Multitools and all other common Multitools with Starlock mounting. Available as a set, offering significant savings over purchasing the items individually. Content: 6 E-Cut long-life saw blades (2 each of 50×35 mm, 50×50 mm, 50×65 mm), 1 carbide rasp (80 mm), 1 carbide segment saw blade (diameter 75 mm, 2.2 mm), 1 rigid stopper knife, 1 cutter blade, (mushroom-shaped), 1 sanding pad, unperforated (80 mm), sanding sheets (5 each of grit 60, 80, 120).

Mount	Part number
SL	3 52 22 967 06 0



STARLOCK TILE WORKING COMBO

3 accessories, especially for renovation and repair jobs in sanitary facilities. When undertaking partial repairs on individual tiles, tile joints can be cut out quickly and cleanly, getting right into the corners and edges without overcutting. Suitable for all FEIN Multitools and all other common Multitools with Starlock mounting. Available as a set, offering significant savings over purchasing the items individually. Content: $1\,\text{E-Cut}$ universal saw blade (55 x 28 mm), 1 carbide rasp (80 mm), 1 carbide segment saw blade (diameter 75 mm, 2.2 mm).

Mount	Part number
SL	3 52 22 967 07 0



STARLOCK RENOVATION COMBO

3 accessories, especially for renovation work on flooring. Suitable for all FEIN Multitools and all other common Multitools with Starlock mounting. Available as a set, offering significant savings over purchasing the items individually. Content: 1 carbide segment saw blade (diameter 85 mm), 1 E-Cut long-life saw blade (50 x 35 mm), 1 rigid stopper knife.

Mount	Part number
SL	3 52 22 967 11 0



STARLOCK MINI CUT COMBO

3 accessories, ideal for cutting smaller recesses and working in tight spots, e.g. for numerous installation jobs, switch installation, model-building and more. Suitable for all FEIN Multitools and all other common Multitools with Starlock mounting. Available as a set, offering significant savings over purchasing the items individually. Content: E-Cut long-life saw blades (2 of 30 x 10 mm, 35 x 20 mm), 1 carbide file (30 x 10 mm).

Mount	Part number
SL	3 52 22 967 09 0



STARLOCK WOOD & METAL E-CUT COMBO

3 E-Cut plunge-cut saw blades for sawing in wood and metal. Suitable for all FEIN Multitools and all other common Multitools with Starlock mounting. Available as a set, offering significant savings over purchasing the items individually. Content: 2 E-Cut long-life saw blades (50 \times 35 mm, 50 \times 65 mm), 1 E-Cut universal saw blade (55 \times 44 mm).

Mount	Part number
SL	3 52 22 967 10 0



STARLOCK WOOD E-CUT COMBO

3 E-Cut plunge-cut saw blades for precise sawing in wooden materials. Suitable for all FEIN Multitools and all other common Multitools with Starlock mounting. Available as a set, offering significant savings over purchasing the items individually. Content: 1 E-Cut standard saw blade, curved (50 x 50 mm), E-Cut precision BIM saw blade (1 each of 50 x 35 mm, 50×65 mm).

Mount	Part number
SL	3 52 22 967 08 0



BEST OF E-CUT STARLOCKPLUS WOOD & METAL

6 E-Cut plunge-cut saw blades for sawing in wood and metal. Suitable for all FEIN Multitools and all other common Multitools with Starlock-Plus and StarlockMax mounting. Available as a set, offering significant savings over purchasing the items individually. Content: E-Cut long-life saw blades (2 each of 50 x 35 mm, 50 x 65 mm), E-Cut universal saw blade (1 each of 60 x 28 mm, 60 x 44 mm).

Mount	Part number
SLP	3 52 22 967 03 0



BEST OF E-CUT STARLOCKMAX WOOD & METAL

6 extra long E-Cut plunge-cut saw blades for large plunge depths and effective working in wood and metal. Suitable for FEIN Multitools with StarlockMax mounting and all other common Multitools with StarlockMax mounting. Available as a set, offering significant savings over purchasing the items individually. Content: E-Cut long-life saw blades (2 each of 78 x 32 mm, 78 x 42 mm), 2 E-Cut long-life saw blades (90 x 32 mm).

Mount	Part number
SLM	3 52 22 967 05 0



STARLOCKMAX HEATING/SANITARY PROFESSIONAL SET

Accessory kit containing 8 parts with extensive range of accessories, especially for key applications in sanitary repairs. Suitable for FEIN Multitools with StarlockMax mounting and all other common Multitools with StarlockMax mounting. Available as a set, offering significant savings over purchasing the items individually. Content: 2 E-Cut universal saw blades (60 x 28 mm, 60 x 44 mm), 1 cutter blade (mushroom-shaped), 1 rigid stopper knife, carbide rasp (1 each of 80 mm, 110 mm), 1 carbide segment saw blade (diameter 90 x 2.2 mm), 1 carbide saw blade (2.2 mm).

Mount	Part number
SLM	3 52 22 967 14 0



STARLOCKMAX INTERIOR WORK PROFESSIONAL SET

Accessory kit containing 45 parts with extensive range of saw blades for fast, precise sawing in all kinds of installation work. Suitable for FEIN Multitools with StarlockMax mounting and all other common Multitools with StarlockMax mounting. Available as a set, offering significant savings over purchasing the items individually. Content: 8 E-Cut long-life saw blades (1 set of 34×20 mm, 2 each of 50×35 mm and 50×65 mm, 1 each of 78×32 mm, 78×42 mm and 90×32 mm), E-Cut precision BIM saw blade (1 each of 50×35 mm, 50×65 mm), 1 HSS circular saw blade (diameter 100 mm), 1 depth stop, 1 rigid stopper knife, long, 1 extraction device, anti-static, 1 sanding pad, perforated (80 mm), sanding sheets, perforated (10 each of grit 60, 80, 120).

Mount	Part number
SLM	3 52 22 967 12 0



PROFESSIONAL MARINE SET

7-part accessory set for use in the marine sector for interior work, maintenance and repairs to yachts. Suitable for all Multitools with a StarlockPlus or StarlockMax fitting. Available as a set, offering significant savings over purchasing the items individually.

Mount	Part number
SLP	3 52 22 967 26 0

GENERAL ACCESSORIES



TABLE-TOP AND DRILL JIGS SUPPORT

Perfect for precision cut-outs: the power tool can be clamped to a table or workbench and the workpiece can be guided safely to the tool. It is also possible to clamp the tool in commercially available drill jigs with a 43 mm collar diameter – the tool can be delivered via the mechanism with millimetre precision. Suited to FEIN MULTIMASTER and FEIN SuperCut. Suitable for FEIN MULTIMASTER (A)MM 700 und (A)MM 500.

Part number 9 26 02 083 01 0



DUST EXTRACTION SET

For effective removal of dust combined with maximum flexibility. Permanent connection to the tool for a secure hold in all work situations. Suction hose can be rotated freely on the tool so it can be adapted perfectly to the work situation. Antistatic – in combination with FEIN Dustex dust extractors and anti-static suction hose (optional). 35 mm diameter suction hose, standard for the most common vacuum cleaner systems. Scope of supply: 1 extraction unit, 2 perforated sanding pads (edge length 80 mm), corundum sanding sheets, perforated (60, 80 and 120 grit, 5 each). Suitable for FEIN MULTIMASTER (A)MM 700 und (A)MM 500.

Part number 9 26 02 102 00 0



ADDITIONAL HANDLE

Suitable for FEIN MULTIMASTER (A)MM 700-1.7.

Part number 3 21 19 148 02 0

9 MULTIMASTER AUTOMOTIVE











189

Our best oscillating cordless MULTIMASTER for the automotive sector including an extensive set of accessories extensive for cutting out windows and work on the

CORDLESS MULTIMASTER AMM 700 1.7 Q AUTOGLAS AS AMM 700 1.7 Q AS MULTIMASTER MM 700 1.7 BASIC

Our best oscillating cordless MULTIMASTER for the automotive sector.

Our best oscillating MULTIMASTER for the automotive sector with extra flat gearbox head for working in tight spots.

MULTIMASTER MM 700 1.7 Q BASIC

Our best oscillating MULTIMASTER for the automotive sector.

	Co	ir body.				
PAGE		232	232	235	235	
Input	W			450	450	
Battery voltage	V	18	18			
Battery compatibility		Li-ion/ProCORE Li-ion	Li-ion/ProCORE Li-ion			
Battery interface		18 V AMPShare	18 V AMPShare			
Oscillations	rpm	10,000 - 19,500	10,000 - 19,500	10,000 - 19,500	10,000 - 19,500	
Tool Holder		12-sided	12-sided	12-sided	12-sided	
Tool change		QuickIN	QuickIN	Manual with screw, hexagon socket	Manual with screw, hexagon socket	
Amplitude		2 x 1,7°	2 x 1,7°	2 x 1,7°	2 x 1,7°	
Weight according to EPTA	kg			1,45	1,45	
Weight without storage batt	ery kg	1,1	1,1			







236

MULTIMASTER MULTIMASTER MM 700 1.7 Q BUS & TRUCK MM 700 1.7 Q AUTOGLAS

Our best oscillating
MULTIMASTER including an
extensive set of accessories for
work on cars and commercial

Our best oscillating
MULTIMASTER for the
automotive sector including an
extensive set of accessories vehicles.

234

extensive for cutting out windows and work on the car

MOTLX 6-25

234

The powerful pneumatic oscillator for cargo.

450	450	
10 000 - 19 500	10 000 - 19 500	20,000

20,000	10,000 - 19,500	10,000 - 19,500
Hexagon	12-sided	12-sided
Manual with screw, hexagon socket	QuickIN	QuickIN
2 x 1,6°	2 x 1,7°	2 x 1,7°
0,9	1,65	1,65

9 MULTIMASTER AUTOMOTIVE

CORDLESS MULTIMASTER AMM 700 1.7 Q AUTOGLAS AS



SUPPLIED

1 protective cover for tool changes, 1 Straight cutter blade, Z-bend, toothed (form 081), 1 each U-shaped cutter blade, reinforced design (forms 157 and 111), 1 L-shaped cutter blade, toothed (form 209), 2 L-shaped cutter blades, toothed (form 208), 2 U-shaped cutter blades, reinforced design, toothed (form 212), 3 L-shaped cutter blades, toothed (form 207), 1 Straight cutter blade, Z-bend, with adjustable roller stop (form 143), 1 sharpening stone (63719010014), 1 rapid charger GAL 1880 CV AS, 2 Li-ion battery packs (18 V / 5 Ah), 1 tool case (L-BOXX 136)

For accessories, see page 241

Our best oscillating cordless MULTIMASTER for the automotive sector including an extensive set of accessories extensive for cutting out windows and work on the car body.

Battery voltage	V	18
Battery capacity	Ah	5
Battery compatibility		Li-ion/ProCORE Li-ion
Battery interface		18 V AMPShare
Oscillations	rpm	10,000 - 19,500
Tool Holder		12-sided
Tool change		QuickIN
Amplitude		2 x 1,7°
Weight without storage battery	kg	1,1
·		

Part number	7 129 37 62 00 0
EAN	4014586895314

FEIN BENEFITS

- + Designed for cutting out windows and work on the car body.
- + Anti-vibration system: continuously safe and pleasant working thanks to minimal vibrations and outstanding noise insulation.
- + QuickIN: tool changes in less than 3 seconds thanks to the patented tool-free FEIN rapid clamping system.
- the patented tool-free FEIN rapid clamping system.+ Hexagonal tool holder for optimum torque transfer.
- + 18 V FEIN PowerDrive motor: very powerful and virtually wear-free, brushless motor offering great efficiency, ability to handle extreme loads and a long service life.
- + Tacho generator: constant speeds even under load and infinitely variable electronic speed control.
- Metal gearbox: ability to withstand high loading and outstanding service life because all the gearbox parts are made from metal.
- Electronic Cell Protection (ECP): ECP protects against overload, overheating and total discharge.
- The COOLPACK technology ensures a longer battery life and therefore makes long operating periods possible.
- The battery charge can be read off the battery.
- Compatible with AMPShare/Bosch Professional 18 V batteries.
- Ideally equipped for every job. Mobile working with the L-BOXX system.

CORDLESS MULTIMASTER AMM 700 1.7 Q AS



SUPPLIED

1 protective cover for tool changes 1 sharpening stone (63719010014), 1 tool case (L-BOXX 136)

For accessories, see page 241

Our best oscillating cordless MULTIMASTER for the automotive sector.

Battery voltage	V	18
Battery compatibility		Li-ion/ProCORE Li-ion
Battery interface		18 V AMPShare
Oscillations	rpm	10,000 - 19,500
Tool Holder		12-sided
Tool change		QuickIN
Amplitude		2 x 1,7°
Weight without storage battery	kg	1,1

Part number	7 129 37 61 00 0
EAN	4014586895307

- + Designed for cutting out windows and work on the car body.
- Anti-vibration system: continuously safe and pleasant working thanks to minimal vibrations and outstanding noise insulation.
- + QuickIN: tool changes in less than 3 seconds thanks to the patented tool-free FEIN rapid clamping system.
- Hexagonal tool holder for optimum torque transfer.
- + 18 V FEIN PowerDrive motor: very powerful and virtually wear-free, brushless motor offering great efficiency, ability to handle extreme loads and a long service life.
- + Tacho generator: constant speeds even under load and infinitely variable electronic speed control.
- + Metal gearbox: ability to withstand high loading and outstanding service life because all the gearbox parts are made from metal.
- + Electronic Cell Protection (ECP): ECP protects against overload, overheating and total discharge.
- + The COOLPACK technology ensures a longer battery life and therefore makes long operating periods possible.
- + The battery charge can be read off the battery.
- + Compatible with AMPShare/Bosch Professional 18 V batteries.
- Ideally equipped for every job. Mobile working with the L-BOXX system.

VEHICLE GLAZIERS

AKP 18-600 AS SET FOR The perfect set for vehicle glaziers. Our powerful and flexible cordless sealant gun coupled with our best oscillating cordless MULTIMASTER for the automotive sector including an extensive set of accessories extensive for cutting out windows and work on the car body in a jumbo pack



battery voltage	v	10
Battery compatibility		Li-ion/ProCORE Li-ion
Battery interface		18 V AMPShare

10

Part number	7 190 24 60 00 0
EAN	4014586898681

For technical data relating to the cordless MULTIMASTER AMM 700 1.7 Q AS, see page 232

Pattonyvoltago

FEIN BENEFITS

+ Unbeatable saving on set compared with buying separately

Cordless sealant gun AKP 18-600 AS:

- With a maximum compressive force of 3500 N and a no-load feed of up to 7 mm/s, the powerful motor guarantees rapid work progress - even when working with particularly viscous materials.
- It's never been so easy to work accurately: thanks to 9 speed settings, a manual trigger and a continuously variable ejection speed, the material flow can be regulated ideally in no time at all.
- The automatic return function (no drip function) allows the pressure to drop when the trigger is released and the gear rack to retract, thereby preventing the used material from dripping or escaping.

CORDLESS MULTIMASTER AMM 700 1.7 Q AUTOGLAS AS:

- Designed for cutting out windows and work on the car bodv.
- + Anti-vibration system: continuously safe and pleasant working thanks to minimal vibrations and outstanding noise insulation.
- QuickIN: tool changes in less than 3 seconds thanks to the patented tool-free FEIN rapid clamping system.

SUPPLIED

1 cordless MULTIMASTER AMM 700 1.7 Q AS, 1 cordless sealant gun AKP 18-600 AS, 2 vehicle glazing accessory sets, 1 protective cover for tool changes

For accessories, see page 241

AKP 18-600 AS TOP SET The perfect set for vehicle glaziers. Our powerful and flexible cordless sealant gun coupled with our best oscillating cordless MULTIMASTER for the automotive sector including an extensive set of accessories extensive for cutting out windows and work on the car body in a jumbo pack. The batteries and charger included mean you can get started straight away.



Battery voltage	V	18
Battery capacity	Ah	4
Battery compatibility		Li-ion/ProCORE Li-ion
Battery interface		18 V AMPShare

Part number	7 190 25 60 00 0
EAN	4014586898698

For technical data relating to the cordless MULTIMASTER AMM 700 1.7 Q AS, see page 232

SUPPLIED

1 cordless MULTIMASTER AMM 700 1.7 Q AS, 1 cordless sealant gun AKP 18-600 AS, 2 battery pack GBA 18 V 4.0 AH AS, 1 rapid charger GAL 1880 CV AS, 2 vehicle glazing accessory sets, 1 protective cover for tool changes

For accessories, see page 241

FEIN BENEFITS

 Unbeatable saving on set compared with buying separately.

Cordless sealant gun AKP 18-600 AS:

- With a maximum compressive force of 3500 N and a no-load feed of up to 7 mm/s, the powerful motor guarantees rapid work progress - even when working with particularly viscous materials.
- It's never been so easy to work accurately: thanks to 9 speed settings, a manual trigger and a continuously variable ejection speed, the material flow can be regulated ideally in no time at all.
- The automatic return function (no drip function) allows the pressure to drop when the trigger is released and the gear rack to retract, thereby preventing the used material from dripping or escaping.

CORDLESS MULTIMASTER AMM 700 1.7 Q AUTOGLAS AS:

- + Designed for cutting out windows and work on the car body.
- + Anti-vibration system: continuously safe and pleasant working thanks to minimal vibrations and outstanding noise insulation.
- QuickIN: tool changes in less than 3 seconds thanks to the patented tool-free FEIN rapid clamping system.

9 MULTIMASTER AUTOMOTIVE

MULTIMASTER MM 700 1.7 Q AUTOGLAS



SUPPLIED

3 L-shaped cutter blades, toothed (form 207), 2 L-shaped cutter blades, toothed (form 208), 1 L-shaped cutter blade, toothed (form 209), 1 each U-shaped cutter blade, reinforced design (forms 157 and 111), 2 U-shaped cutter blades, reinforced design, toothed (form 212), 1 Straight cutter blade, Z-bend, with adjustable roller stop (form 143), 1 Straight cutter blade, Z-bend, toothed (form 081), 1 protective cover for tool changes, 1 sharpening stone (63719010014), 1 tool case (L-BOXX 136)

For accessories, see page 241

Our best oscillating MULTIMASTER for the automotive sector including an extensive set of accessories extensive for cutting out windows and work on the car body.

Input	W	450
Output	W	250
Oscillations	rpm	10,000 - 19,500
Tool Holder		12-sided
Tool change		QuickIN
Amplitude		2 x 1,7°
Cable with plug	m	5
Weight according to EPTA	kg	1,65

Part number	7 229 70 65 00 0
EAN	4014586898063

FEIN BENEFITS

- + Anti-vibration system: continuously safe and pleasant working thanks to minimal vibrations and outstanding noise insulation.
- + QuickIN: tool changes in less than 3 seconds thanks to the patented tool-free FEIN rapid clamping system.
- + Hexagonal tool holder for optimum torque transfer.
- 450 W FEIN high-power motor: high-power motor with a high copper content, which is suited to continuous use and overload for maximum cutting speed and the most rapid work progress.
- + Tacho generator: constant speeds even under load and infinitely variable electronic speed control.
- Metal gearbox: ability to withstand high loading and outstanding service life because all the gearbox parts are made from metal.
- + Industrial cable: large working radius thanks to finely stranded 5 metre rubber cable of industrial quality.
- + Ideally equipped for every job. Mobile working with the L-BOXX system.

MULTIMASTER MM 700 1.7 Q BUS & TRUCK



SUPPLIED

1 Hook-shaped cutter blade, toothed (form 217), 1 Spade-shaped scraper knife, with scratch-protective coating (form 105), 2 L-shaped cutter blades, toothed (form 207), 2 Straight cutter blades, toothed (form 073), 1 Straight cutter blades, curved shape, Z-bend (form 072), 1 U-shaped cutter blade, toothed (form 212), 2 straight cutter blades, Z-bend, toothed (form 081), 1 L-shaped cutter blade, toothed (form 209), 1 protective cover for tool changes, 1 traction cable with fastening, 1 sharpening stone (63719010014), 1 tool case (L-BOXX 136)

For accessories, see page 241

Our best oscillating MULTIMASTER including an extensive set of accessories for work on cars and commercial vehicles.

Input	W	450
Output	W	250
Oscillations	rpm	10,000 - 19,500
Tool Holder		12-sided
Tool change		QuickIN
Amplitude		2 x 1,7°
Cable with plug	m	5
Weight according to EPTA	kg	1,65

Part number	7 229 70 64 00 0
EAN	4014586898049

- Anti-vibration system: continuously safe and pleasant working thanks to minimal vibrations and outstanding noise insulation.
- HolickIN: tool changes in less than 3 seconds thanks to the patented tool-free FEIN rapid clamping system.
- + Hexagonal tool holder for optimum torque transfer.
- + 450 W FEIN high-power motor: high-power motor with a high copper content, which is suited to continuous use and overload for maximum cutting speed and the most rapid work progress.
- + Tacho generator: constant speeds even under load and infinitely variable electronic speed control.
- + Metal gearbox: ability to withstand high loading and outstanding service life because all the gearbox parts are made from metal.
- Industrial cable: large working radius thanks to finely stranded 5 metre rubber cable of industrial quality.
- Ideally equipped for every job. Mobile working with the L-BOXX system.

MULTIMASTER **MM 700 1.7 BASIC**



SUPPLIED

1 key, 1 sharpening stone (63719010014), 1 Mounting bolt (3 30 01 039 01 7), 1 protective cover for tool changes, 1 tool case (L-BOXX 136)

For accessories, see page 241

Our best oscillating MULTIMASTER for the automotive sector with extra flat gearbox head for working in tight spots.

Input	W	450
Output	W	250
Oscillations	rpm	10,000 - 19,500
Tool Holder		12-sided
Tool change		Manual with screw, hexagon socket
Amplitude		2 x 1,7°
Cable with plug	m	5
Weight according to EPTA	kg	1,45

Part number	7 229 69 62 00 0
EAN	4014586897967

FEIN BENEFITS

- + Designed for cutting out windows and work on the car
- + Anti-vibration system: continuously safe and pleasant working thanks to minimal vibrations and outstanding noise insulation.
- $\label{thm:lemma:lemma:def} \mbox{Hexagonal tool holder for optimum torque transfer.}$
- 450 W FEIN high-power motor: high-power motor with a high copper content, which is suited to continuous use and overload for maximum cutting speed and the most rapid work progress.
- Tacho generator: constant speeds even under load and infinitely variable electronic speed control.
- Metal gearbox: ability to withstand high loading and outstanding service life because all the gearbox parts are made from metal.
- Industrial cable: large working radius thanks to finely stranded 5 metre rubber cable of industrial quality.
- Ideally equipped for every job. Mobile working with the L-BOXX system.

MULTIMASTER MM 700 1.7 Q BASIC



SUPPLIED

1 protective cover for tool changes, 1 sharpening stone (63719010014), 1 tool case (L-BOXX 136)

For accessories, see page 241

Our best oscillating MULTIMASTER for the automotive sector.

Input	W	450
Output	W	250
Oscillations	rpm	10,000 - 19,500
Tool Holder		12-sided
Tool change		Manual with screw, hexagon socket
Amplitude		2 x 1,7°
Cable with plug	m	5
Weight according to EPTA	kg	1,45

Part number	7 229 69 63 00 0
EAN	4014586897998

- Designed for cutting out windows and work on the car body. Anti-vibration system: continuously safe and pleasant
- working thanks to minimal vibrations and outstanding noise insulation.
- QuickIN: tool changes in less than 3 seconds thanks to the patented tool-free FEIN rapid clamping system.
- Hexagonal tool holder for optimum torque transfer.
- 450 W FEIN high-power motor: high-power motor with a high copper content, which is suited to continuous use and overload for maximum cutting speed and the most rapid work progress.
- Tacho generator: constant speeds even under load and infinitely variable electronic speed control.
- Metal gearbox: ability to withstand high loading and outstanding service life because all the gearbox parts are made from metal.
- Industrial cable: large working radius thanks to finely stranded 5 metre rubber cable of industrial quality.
- Ideally equipped for every job. Mobile working with the L-BOXX system.

9 MULTIMASTER AUTOMOTIVE

MOTLX 6-25



SUPPLIED

2 keys, 1 plastic carrying case

For accessories, see page 241

The powerful pneumatic oscillator for cargo.

Operating pressure	bar	6,3
Air consumption	m³/min	0,6
Oscillations	rpm	20,000
Hose size Ø	mm	8
Tool Holder		Hexagon
Tool change		Manual with screw, hexagon socket
Amplitude		2 x 1,6°
Weight according to EPTA	kg	0,9

Part number	7 536 03 00 01 0
EAN	4014586861906

- + Available with a comprehensive range of accessories for professional use in many industry sectors.
 + Powerful oscillating motion with amplitude of 2 x 1.6 degrees for maximum work progress.
 + Ideal for removing bonded panes from lorries, buses and rail vehicles.
 + Small size.
 + Supplied with inlet and outlet air hose.
 + No air leaks, no oil misting in working area.
 + Hexagonal tool mounting.







MULTIMASTER
AMM 700 1.7 Q JOINT RENOVATION

MULTIMASTER
AMM 700 1.7 Q JOINT RENOVATION

MULTIMASTER MM 700 1.7 Q GROUTING RENEWAL

Our best Multitool specially for grouting renewal with durable 12-star receptacle and 7 blades for cutting out elastic joints.

Our best Multitool specially for grouting renewal with durable 12-star receptacle and 7 blades for cutting out elastic joints.

			anu / b	lades for cutting out elastic joints.
PAGE		238	238	240
Input	W			450
Battery voltage	V	18	18	
Battery compatibility		Li-ion/ProCORE Li-ion	Li-ion/ProCORE Li-ion	
Battery interface		18 V AMPShare	18 V AMPShare	
Oscillations	rpm	10,000 - 19,500	10,000 - 19,500	10,000 - 19,500
Tool Holder		12-sided	12-sided	12-sided
Tool change		QuickIN	QuickIN	QuickIN
Amplitude		2 x 1,7°	2 x 1,7°	2 x 1,7°
Weight according to EPTA	kg			1,65
Weight without storage bat	tery kg	1,3	1,1	

MULTIMASTER JOINT RENOVATION

MULTIMASTER AMM 700 1.7 Q JOINT RENOVATION



SUPPLIED

5 Cutter blades, straight (form 117) 6 390 31 17 01 5, 1 Cutter blade, straight, long (form 116) 6 390 31 16 01 1, 1 Cutter blade, mushroom shaped 6 390 31 28 01 2, 1 handle, 1 protective cover for tool changes, 1 sharpening stone (63719010014), 1 rapid charger GAL 1880 CV AS, 2 Li-ion battery packs (18 V / 5 Ah), 1 plastic tool case (L-BOXX 238)

For accessories, see page 241

Our best Multitool specially for grouting renewal with durable 12-star receptacle and 7 blades for cutting out elastic joints.

Battery voltage	V	18
Battery capacity	Ah	5
Battery compatibility		Li-ion/ProCORE Li-ion
Battery interface		18 V AMPShare
Oscillations	rpm	10,000 - 19,500
Tool Holder		12-sided
Tool change		QuickIN
Amplitude		2 x 1,7°
Weight without storage battery	kg	1,3
	kg	•

Part number	7 129 37 63 00 0
EAN	4014586898926

FEIN BENEFITS

- Precision Multitools get into hard-to-reach places. Thanks to vibration damping, they work quietly and
- blade lengths up to 98 mm allow even Versatility very deep joints to be cut. The diamond-coated cleaning blade cleans mortar flanks before you fill them in again.
- Safety and simplicity Multitools work precisely and safely in the joint. Blades don't break and the power tool is protected against overload and overheating. Misuse is almost impossible.
- Anti-vibration system: continuously safe and pleasant working thanks to minimal vibrations and outstanding noise insulation.
- QuickIN: tool changes in less than 3 seconds thanks to the patented tool-free FEIN rapid clamping system.
- 12-sided holder for optimum torque transfer
- 18 V FEIN PowerDrive motor: very powerful and virtually wear-free, brushless motor offering great efficiency, ability to handle extreme loads and a long service life.
- Tacho generator: constant speeds even under load and infinitely variable electronic speed control.
- Metal gearbox: ability to withstand high loading and outstanding service life because all the gearbox parts are made from metal.
- + Electronic Cell Protection (ECP): ECP protects against overload, overheating and total discharge.

 The COOLPACK technology ensures a longer battery
- life and therefore makes long operating periods possible.
- The battery charge can be read off the battery.
- Compatible with AMPShare/Bosch Professional 18 V batteries
- Ideally equipped for every job. Mobile working with the L-BOXX system.

MULTIMASTER AMM 700 1.7 Q JOINT RENOVATION



SUPPLIED

5 Cutter blades, straight (form 117) 6 390 31 17 01 5, 1 Cutter blade, straight, long (form 116) 6 390 31 16 01 1, 1 Cutter blade, mushroom shaped 6 390 31 28 01 2, 1 handle, 1 protective cover for tool changes, 1 sharpening stone (63719010014), 1 plastic tool case (L-BOXX 238)

For accessories, see page 241

Our best Multitool specially for grouting renewal with durable 12-star receptacle and 7 blades for cutting out elastic joints.

Battery voltage	V	18
Battery compatibility		Li-ion/ProCORE Li-ion
Battery interface		18 V AMPShare
Oscillations	rpm	10,000 - 19,500
Tool Holder		12-sided
Tool change		QuickIN
Amplitude		2 x 1,7°
Weight without storage battery	kg	1,1

Part number	7 129 37 64 00 0
EAN	4014586898933

- + Precision Multitools get into hard-to-reach places. Thanks to vibration damping, they work quietly and
- Versatility blade lengths up to 98 mm allow even very deep joints to be cut. The diamond-coated cleaning blade cleans mortar flanks before you fill them in again.
- Safety and simplicity Multitools work precisely and safely in the joint. Blades don't break and the power tool is protected against overload and overheating. Misuse is almost impossible.
- Anti-vibration system: continuously safe and pleasant working thanks to minimal vibrations and outstanding noise insulation.
- QuickIN: tool changes in less than 3 seconds thanks to the patented tool-free FEIN rapid clamping system.
- 12-sided holder for optimum torque transfer.
- 18 V FEIN PowerDrive motor: very powerful and virtually wear-free, brushless motor offering great efficiency, ability to handle extreme loads and a long service life.
- Tacho generator: constant speeds even under load and infinitely variable electronic speed control.
- Metal gearbox: ability to withstand high loading and outstanding service life because all the gearbox parts are made from metal.
- Electronic Cell Protection (ECP): ECP protects against overload, overheating and total discharge.
- The COOLPACK technology ensures a longer battery life and therefore makes long operating periods
- The battery charge can be read off the battery. Compatible with AMPShare/Bosch Professional 18 V batteries.
- Ideally equipped for every job. Mobile working with the L-BOXX system.

GROUTING RENEWERS

AKP 18-600 AS SET FOR The perfect set for grouting renewers. Our powerful and flexible cordless sealant gun coupled with our best oscillating cordless MULTIMASTER together with a jumbo pack of universal cutter blades for virtually all expansion joints.



Battery voltage	V	18
Battery compatibility		Li-ion/ProCORE Li-ion
Battery interface		18 V AMPShare

Part number	7 190 22 60 00 0
EAN	4014586898636

For technical data relating to the cordless MULTIMASTER AMM 700 1.7 Q AS, see page 232

FEIN BENEFITS

- 50 universal cutter blades with straight shape for virtually all expansion joints
- Unbeatable saving on set compared with buying separately.

Cordless sealant gun AKP 18-600 AS:

- + With a maximum compressive force of 3500 N and a no-load feed of up to 7 mm/s, the powerful motor guarantees rapid work progress - even when working with particularly viscous materials.
- It's never been so easy to work accurately: thanks to 9 speed settings, a manual trigger and a continuously variable ejection speed, the material flow can be regulated ideally in no time at all.
- The automatic return function (no drip function) allows the pressure to drop when the trigger is released and the gear rack to retract, thereby preventing the used material from dripping or escaping.

 Cordless MULTIMASTER AMM 700 1.7 Q AS:

- Designed for cutting out windows and work on the car body.
- Anti-vibration system: continuously safe and pleasant working thanks to minimal vibrations and outstanding noise insulation.
- QuickIN: tool changes in less than 3 seconds thanks to the patented tool-free FEIN rapid clamping system.

SUPPLIED

1 cordless MULTIMASTER AMM 700 1.7 Q AS, 1 cordless sealant gun AKP 18-600 AS, 50 cutter blades, 1 protective cover for tool changes

For accessories, see page 241

FOR GROUTING RENEWERS





18
4
Li-ion/ProCORE Li-ion
18 V AMPShare

Part number	7 190 23 60 00 0
EAN	4014586898643

For technical data relating to the cordless MULTIMASTER AMM 700 1.7 Q AS, see page 232

FEIN BENEFITS

- 50 universal cutter blades with straight shape for virtually all expansion joints.
- Unbeatable saving on set compared with buying separately.

Cordless sealant gun AKP 18-600 AS:

- With a maximum compressive force of 3500 N and a no-load feed of up to 7 mm/s, the powerful motor quarantees rapid work progress - even when working with particularly viscous materials.
- It's never been so easy to work accurately: thanks to 9 speed settings, a manual trigger and a continuously variable ejection speed, the material flow can be regulated ideally in no time at all.
- The automatic return function (no drip function) allows the pressure to drop when the trigger is released and the gear rack to retract, thereby preventing the used material from dripping or escaping

Cordless MULTIMASTER AMM 700 1.7 Q AS:

- Designed for cutting out windows and work on the car body.
- + Anti-vibration system: continuously safe and pleasant working thanks to minimal vibrations and outstanding noise insulation.
- QuickIN: tool changes in less than 3 seconds thanks to the patented tool-free FEIN rapid clamping system.

SUPPLIED

1 cordless MULTIMASTER AMM 700 1.7 Q AS, 1 cordless sealant gun AKP 18-600 AS, 2 battery pack GBA 18 V 4.0 AH AS, 1 rapid charger GAL 1880 CV AS, 50 cutter blades, 1 protective cover for tool changes

For accessories, see page 241

MULTIMASTER JOINT RENOVATION

MULTIMASTER MM 700 1.7 Q **GROUTING RENEWAL**



SUPPLIED

5 Cutter blades, straight (form 117) 6 390 31 17 01 5, 1 Cutter blade, straight, long (form 116) 6 390 31 16 01 1, 1 Cutter blade, mushroom shaped 6 390 31 28 01 2, 1 handle, 1 protective cover for tool changes, 1 sharpening stone (63719010014), 1 plastic tool case (L-BOXX 238)

For accessories, see page 241

Our best Multitool specially for grouting renewal with durable 12-star receptacle and 7 blades for cutting out elastic joints.

Input	W	450
Output	W	250
Oscillations	rpm	10,000 - 19,500
Tool Holder		12-sided
Tool change		QuickIN
Amplitude		2 x 1,7°
Cable with plug	m	5
Weight according to EPTA	kg	1,65

Part number	7 229 70 66 00 0
EAN	4014586898940

- Precision Multitools get into hard-to-reach places. Thanks to vibration damping, they work quietly and
- Versatility blade lengths up to 98 mm allow even very deep joints to be cut. The diamond-coated cleaning blade cleans mortar flanks before you fill them in again.
- Safety and simplicity Multitools work precisely and safely in the joint. Blades don't break and the power tool is protected against overload and overheating. Misuse is almost impossible.
- QuicklN: tool changes in less than 3 seconds thanks to the patented tool-free FEIN rapid clamping system. 12-sided holder for optimum torque transfer.
- 450 W FEIN high-power motor: high-power motor with a high copper content, which is suited to continuous use and overload for maximum cutting speed and the most rapid work progress.
- Tacho generator: constant speeds even under load and infinitely variable electronic speed control.
- Hetal gearbox: ability to withstand high loading and outstanding service life because all the gearbox parts are made from metal.
- Industrial cable: large working radius thanks to finely
- stranded 5 metre rubber cable of industrial quality. Ideally equipped for every form of use. Mobile working with the L-BOXX system.



9 12-SIDED FITTING ACCESSORIES

REMOVE GROUTS



CARBIDE SAW BLADE

In comparison with the diamond version, the price is lower and the service life shorter.

Extra thin version, cutting line approx. 1.2 mm, not suited to very hard epoxy resin or cement joints. Also suited to reworking deck joints.

Ø	No. in pack	
mm	pcs	Part number
80	1	6 35 02 155 01 0



Stepped, cutting line approx. 2.2 mm, standard for all marble, epoxy resin and concrete trass joints.

Ø	No. in pack	
mm	pcs	Part number
80	1	6 35 02 156 01 0



CARBIDE SEGMENT BLADE

In comparison with the diamond version, the price is lower and the service life shorter.

For corners and radii and for working without overcutting, cutting line approx. 2.2 mm for all marble and epoxy resin joints.

No. in pack	
pcs	Part number
1	6 39 03 225 01 0
5	6 39 03 225 02 0



DIAMOND-COATED SAW BLADE

Cutting line approx. 2.2 mm, standard design for all marble, epoxy resins and cement trass mortar.

Ø	No. in pack	
mm	pcs	Part number
80	1	6 35 02 115 01 1
80	5	6 35 02 115 03 0



Cutting line approx. 1.2 mm for extremely thin marble mortar joints. Not suitable for epoxy resin and cement trass mortar.

Ø	No. in pack	
mm	pcs	Part number
80	1	6 35 02 116 01 4
80	5	6 35 02 116 02 0



SEGMENT BLADE

Diamond-coated, also for corners and radii and for working without overcutting.

Cutting line approx. 2.2 mm, standard design for all marble,

Cutting line approx. 2.2 mm, standard design for all marble epoxy resins and cement trass mortar.

No. in pack	
pcs	Part number
1	6 39 03 162 01 7
5	6 39 03 162 03 0



Cutting line approx. 1,2 mm, for extremely narrow marble joints. Cutting depth max. 10 mm. Not suitable for epoxy resin or trass cement joints.

No. in pack	
pcs	Part number
1	6 39 03 196 01 3
5	6 39 03 196 02 0



XXL 98 MM BLADE, PACK OF 5

XXL cutter blade, straight. Universal bade for expansion joints. Cutting length 98 mm.

Total length		Cut length	
mm	Tool Holder	mm	Part number
105	12-sided	97	6 39 03 270 03 0



XXL 73 MM BLADE, PACK OF 2

XXL cutter blade, straight. Z bend, cutting length 78 mm.

Total length		Cut length		
mm	Tool Holder	mm	Part number	
134	12-sided	73	6 39 03 271 02 0	



CLEANING BLOCK

Rhombus for cleaning the carbide tools and diamond-coated tools.

	Part number
26.60	6 37 19 007 01 0



CUTTING BLADE

Straight shape. Universal blade for almost all expansion sealants. Pack of 5

	Part number
27,40	6 39 03 117 01 5



STRAIGHT FORM

suitable for round grooves in plastics. toothed, 2-pack.

Total length	Cut length	
mm	mm	Part number
56	35	6 39 03 073 01 1



STRAIGHT FORM

Suitable for removal of chassis attachment parts. Z-bend, toothed, 2-pack.

Total length	Cut length	
mm	mm	Part number
120	60	6 39 03 081 01 3



CUTTING BLADE

Straight, long, for very deep joints, pack of 5

F		
		Part number
	87,80	6 39 03 116 01 1



SEGMENT BLADE

Segment form for V-cut from outside and for cuts in corners, 2-pack

Total length	Cut length	
mm	mm	Part number
73	30	6 39 03 132 01 0

CUTTING



CUTTING BLADE

Mushroom-shaped, pack of 5, For cutting elastic silicon or acrylic connecting joints.

		Part number
19,	80	6 39 03 128 01 2

SCRAPING



SCRAPER BLADE

for removing floor covering remains, underseal and residual bonding material, etc., pack of 2

Length	No. in pack	
mm	pcs	Part number
64	2	6 39 03 206 01 8
72	2	6 39 03 227 01 0

AUTOMOTIVE WORKSHOP ACCESSORIES



STRAIGHT FORM

curved, Z-bend, as subsequent order for removal device 9 06 07 001 01 6, 2-pack.

Part number 101,53 6 39 03 197 01 7



SAW BLADES

HSS, with fine teeth for precise cutting. Universal use on sheet metal of up to approx. 1 mm, can be doubled in plastics.

Ø	No. in pack	
mm	pcs	Part number
63	2	6 35 02 102 01 6
63	5	6 35 02 102 07 0
80	2	6 35 02 103 01 0
80	5	6 35 02 103 05 0



E-CUT UNIVERSAL SAW BLADES

Bi-metal teeth, cranked, also suitable for radii, high speed cut, sheet metal (400 N/mm²) up to about 2 mm and plastics, aluminium profiles, copper pipes, wood, plasterboard, and almost all plastics.

Length 60 mm, form 147

Width	No. in pack	
mm	pcs	Part number
28	1	6 35 02 147 01 5
28	5	6 35 02 147 02 1



Length 60 mm, form 148

Width	No. in pack	
mm	pcs	Part number
44	1	6 35 02 148 01 3
44	5	6 35 02 148 02 9



STRAIGHT FORM

suitable for round grooves in plastics. toothed, 2-pack.

Total length	Cut length	
mm	mm	Part number
56	35	6 39 03 073 01 1



STRAIGHT FORM

Suitable for removal of chassis attachment parts. Z-bend, toothed, 2-pack.

Total length	Cut length	
mm	mm	Part number
120	60	6 39 03 081 01 3



SCRAPER BLADE

for removing floor covering remains, underseal and residual bonding material, etc., pack of 2

Length	No. in pack	
mm	pcs	Part number
64	2	6 39 03 206 01 8
72	2	6 39 03 227 01 0



CUTTING BLADE

Mushroom-shaped, pack of 5, For cutting elastic silicon or acrylic connecting joints.

Part number 19,80 6 39 03 128 01 2

FEIN ACCESSORIES FOR REMOVING RESIDUAL **BONDING BEADS**



SCRAPER KNIFE

Spade-shaped, with scratch-protective coating, 2-pack.

Total length	Cut length	
mm	mm	Part number
64	12	6 39 03 129 05 0
65	18	6 39 03 146 01 8
64	25	6 39 03 105 01 9



SCRAPER KNIFE

with cross cutter and scratch protective coating on front limit stop, 2-pack.



Cutting width

mm	Part number
13	6 39 03 113 01 6
25	6 39 03 131 01 7



SCRAPER KNIFE

with cross cutter, 2-pack.

Cutting width	
mm	Part number
13	6 39 03 144 01 1



SCRAPER KNIFE SET

consisting of: 1 each of spade-shaped scraper knife, with scratch-protective coating (forms 129/105).



Part number

81,40 6 39 03 129 01 6



SCRAPER KNIFE SET

consisting of: 1 each of scraper knife with cross cutter and scratch protective coating on front limit stop (form 113/131).

	Part number
81,40	6 39 03 113 02 2

9 12-SIDED FITTING ACCESSORIES

VEHICLE GLAZING ACCESSORIES



U-SHAPED

Ideal for removing glass from under the bonnet. short side, 2-pack

Cut length	
mm	Part number
16	6 39 03 095 01 1
16	6 39 03 108 01 4
18	6 39 03 087 01 9
19,5	6 39 03 118 01 3
22	6 39 03 115 01 8
24	6 39 03 076 01 6
28	6 39 03 163 01 1
32	6 39 03 147 01 2
36	6 39 03 079 01 2
40	6 39 03 110 01 0
60	6 39 03 101 01 0
70	6 39 03 155 01 4
	,



Ideal for removing glass from under the bonnet. long side, 2-pack

Cut length	
mm	Part number
32	6 39 03 114 01 4
32	6 39 03 191 01 1
45	6 39 03 154 01 0
52	6 39 03 153 01 2
60	6 39 03 107 01 6



U-SHAPED

Ideal for removing glass from under the bonnet. reinforced design, 2-pack

Cut length	
mm	Part number
60	6 39 03 157 01 1
95	6 39 03 111 01 9



Ideal for removing glass from under the bonnet. reinforced design, toothed, 2-pack.



Cut length

mm	Part number
19	6 39 03 210 01 6
22,5	6 39 03 211 01 5
38	6 39 03 212 01 8



L-SHAPED

toothed, 2-pack.

Cut length mm	Part number
19	6 39 03 208 01 0
25,4	6 39 03 207 01 2
38	6 39 03 209 01 4



STRAIGHT FORM



Cut length	
mm	Part number
26	6 39 03 121 01 8
40	6 39 03 176 01 5
35	6 39 03 194 01 6
	mm 26 40



STRAIGHT FORM

Z-bend, 2-pack.

Total length	Cut length	
mm	mm	Part number
68	19	6 39 03 122 01 1
84	18	6 39 03 181 01 2
65	23	6 39 03 173 01 0
65	25	6 39 03 124 01 3
85	27	6 39 03 174 01 8
110	32	6 39 03 123 01 5
120	70	6 39 03 171 01 3



STRAIGHT FORM

curved, 2-pack

Total length mm	Cut length mm	Part number
65	14	6 39 03 120 01 9
75	16	6 39 03 104 01 5
75	35	6 39 03 103 01 7
75	35	6 39 03 109 01 8
75	35	6 39 03 172 01 6



STRAIGHT FORM

curved, Z-bend, 2-pack

Total length mm	Cut length mm	Part number
120	45	6 39 03 168 01 8
120	70	6 39 03 125 01 7



STRAIGHT FORM

Z-bend, with rigid depth stop, 2-pack.

Total length	Cut length		
mm	mm	Part number	
120	16	6 39 03 099 01 0	
125	58	6 39 03 097 01 8	



STRAIGHT FORMZ-bend, with adjustable depth stop, 2-pack



Total length	Cut length		
mm	mm	Part number	
100	16-43	6 39 03 143 01 3	
100	18-39	6 39 03 170 01 4	
100	20-35	6 39 03 198 01 5	
100	60-76	6 39 03 169 01 2	



STRAIGHT FORM

flat, with adjustable depth stop, 2-pack.

Total length	Cut length	
mm	mm	Part number
145	42-60	6 39 03 182 01 5



STRAIGHT FORM

Z-bend, bent with rigid depth stop, 2-pack.

Total length	Cut length	
mm	mm	Part number
120	54	6 39 03 160 01 5



CURVED FORM

Z-bend, with rigid depth stop, 2-pack.

Total length	Cut length	
mm	mm	Part number
80	14	6 39 03 082 01 6
80	16	6 39 03 133 01 4
85	39	6 39 03 152 01 8



CURVED FORM

Z-bend, with adjustable depth stop, 2-pack

Total length	Cut length	
mm	mm	Part number
110	32-46	6 39 03 195 01 0

CARGO ACCESSORIES



L-SHAPED

toothed, 2-pack.

Part number	
6 39 03 207 01 2	
6 39 03 209 01 4	



STRAIGHT FORM

suitable for round grooves in plastics. toothed, 2-pack.

Total length Cut length mm Part number mm 35 6 39 03 073 01 1



STRAIGHT FORM

Suitable for removal of chassis attachment parts. Z-bend, toothed, 2-pack.

Total length	Cut length		
mm	mm	Part number	
120	60	6 39 03 081 01 3	



STRAIGHT FORM

Z-bend, 2-pack.

Total length	Cut length		
mm	mm	Part number	
120	60	6 39 03 216 01 7	



STRAIGHT FORM

Angle cutter, 2-pack.

Total length	Cut length		
mm	mm	Part number	
85	65/8	6 39 03 177 01 9	
83	35/20	6 39 03 203 01 3	



CURVED FORM

Z-bend, 2-pack.

Total length	Cut length	Part number
mm 80		6 39 03 072 01 7



U-SHAPED

with elongated traverse, 2-pack.

Cut length

mm	Part number	
40	6 39 03 156 01 7	



HOOK-SHAPED

toothed, 2-pack.

Cut length	
mm	Part number
38	6 39 03 217 01 1



SEGMENT BLADE

Segment form for V-cut from outside and for cuts in corners, 2-pack

Total length	Cut length	
mm	mm	Part number
73	30	6 39 03 132 01 0

SAWING



SAW BLADES

HSS, with fine teeth for precise cutting. Universal use on sheet metal of up to approx. $1\,\text{mm}$, can be doubled in plastics.

Ø	No. in pack	
mm	pcs	Part number
63	2	6 35 02 102 01 6
63	5	6 35 02 102 07 0
80	2	6 35 02 103 01 0
80	5	6 35 02 103 05 0



SAW BLADES

HSS, cranked, countersunk clamping screw for flush working.

Ø	No. in pack		
mm	pcs	Part number	
85	1	6 35 02 177 01 0	
85	5	6 35 02 177 05 0	
100	1	6 35 02 178 01 0	
100	5	6 35 02 178 05 0	



SEGMENT SAW BLADE

HSS, cranked, countersunk clamping screw for flush working.

Ø	No. in pack		
mm	pcs	Part number	
100	1	6 35 02 196 01 0	
100	5	6 35 02 196 05 0	



BEST OF E-CUT ACCESSORY SET

Includes 6 different E-Cut saw blades. Content: E-Cut Universal (1x 28 mm and 1x 44 mm wide), 2x E-Cut Long-Life $35\ \mathrm{mm}$ wide, $2x\ \mathrm{E-Cut}$ Long-Life $65\ \mathrm{mm}$ wide, in practical plastic storage box.

Part number
6 35 02 147 12 0

12-SIDED FITTING ACCESSORIES



E-CUT LONG-LIFE SAW BLADES

Bi-metallic teeth, stepped, high cutting speed. Extremely durable and robust. For hardwood, softwood and all other wooden materials - including those with nails. Also perfectly suited to plastics and plasterboard.

Length 78 mm, form 162

Width	No. in pack	
mm	pcs	Part number
32	1	6 35 02 162 01 0
32	5	6 35 02 162 02 0
32	25	6 35 02 162 03 0



Length 78 mm, form 163

Width	No. in pack	
mm	pcs	Part number
42	1	6 35 02 163 01 0
42	5	6 35 02 163 02 0
42	25	6 35 02 163 03 0



Length 50 mm, form 164

Width	No. in pack	
mm	pcs	Part number
35	1	6 35 02 164 01 0
35	5	6 35 02 164 02 0
35	25	6 35 02 164 03 0



Length 50 mm, form 165

Width	No. in pack		
mm	pcs	Part number	
65	1	6 35 02 165 01 0	
65	5	6 35 02 165 02 0	
65	25	6 35 02 165 03 0	



E-CUT STANDARD SAW BLADES

Crossed toothing for all wood, plasterboard, and plastics jobs. Length 78 mm, form 123

No. in pack	
pcs	Part number
1	6 35 02 123 01 8
5	6 35 02 123 04 6
25	6 35 02 123 03 0
	pcs 1 5



Length 78 mm, form 124

Width	No. in pack		
mm	pcs	Part number	
42	1	6 35 02 124 01 6	
42	5	6 35 02 124 04 4	
42	25	6 35 02 124 03 8	



Length 50 mm, form 135

Width	No. in pack	
mm	pcs	Part number
35	1	6 35 02 135 01 9
35	5	6 35 02 135 03 1
35	25	6 35 02 135 02 5



Length 50 mm, form 136

Width	No. in pack	
mm	pcs	Part number
65	1	6 35 02 136 01 2
65	5	6 35 02 136 03 4
65	25	6 35 02 136 02 8



E-CUT PRECISION SAW BLADES

Double-row original Japan toothing, for top-precision cuts, and clean cutting edges even freely by hand Length 50 mm, form 119

Width	No. in pack	
mm	pcs	Part number
35	1	6 35 02 119 01 0
35	5	6 35 02 119 04 8
35	25	6 35 02 119 03 2



E-CUT PRECISION SAW BLADE

Double-row original Japan toothing, for top-precision cuts, and clean cutting edges even freely by hand Length 50 mm, form 235

Width	No. in pack	
mm	pcs	Part number
50	1	6 35 02 235 01 0
50	5	6 35 02 235 02 0
50	25	6 35 02 235 03 0



Length 50 mm, form 122

Width	No. in pack		
mm	pcs	Part number	
65	1	6 35 02 122 01 4	
65	5	6 35 02 122 04 2	
65	25	6 35 02 122 03 6	



E-CUT PRECISION BIM SAW BLADE

Bimetal with double-row Japan teeth for all wooden materials, plasterboard and soft plastics. Improved tool life and robustness. The fastest cutting speed and maximum precision. Length 50 mm, form 209

Width	No. in pack		
mm	pcs	Part number	
35	1	6 35 02 209 01 0	
35	5	6 35 02 209 02 0	
35	25	6 35 02 209 03 0	



Length 50 mm, form 210

Width	No. in pack		
mm	pcs	Part number	
50	1	6 35 02 234 01 0	
50	5	6 35 02 234 02 0	
50	25	6 35 02 234 03 0	



Length 50 mm, form 212

Width	No. in pack	
mm	pcs	Part number
65	1	6 35 02 212 01 0
65	5	6 35 02 212 02 0
65	25	6 35 02 212 03 0



E-CUT UNIVERSAL SAW BLADES

Bi-metal teeth, cranked, also suitable for radii, high speed cut, sheet metal (400 N/mm²) up to about 2 mm and plastics, aluminium profiles, copper pipes, wood, plasterboard, and almost all plastics. Length 60 mm, form 147

	3	
Width	No. in pack	
mm	pcs	Part number
28	1	6 35 02 147 01 5
28	5	6 35 02 147 02 1
28	25	6 35 02 147 03 7



Length 60 mm, form 148

Width	No. in pack	
mm	pcs	Part number
44	1	6 35 02 148 01 3
44	5	6 35 02 148 02 9
44	25	6 35 02 148 03 5



HSS SAW BLADE WOOD

Ideal for long, straight cuts and for cutting out laid parquet or laminate flooring. Without depth stop

Width	No. in pack	
mm	pcs	Part number
100	1	6 35 02 179 01 0



HSS SAW BLADE WOOD

Ideal for long, straight cuts and for cutting out laid parquet or laminate flooring. With depth stop

Width	No. in pack	
mm	pcs	Part number
100	1	6 35 02 179 02 0



DEPTH STOP

Depth stop for all saw blades. For accurate working at depth Effective protection for blade and workpiece. Contents: 1 adapter for attachment to the machine. 1 depth stop, 1 depth-adjustable guide block. Can only be used with (A)MM 500 / 700.

> Part number 3 21 27 069 01 0



CARBIDE SAW BLADE WITH OPEN TEETH

For perfect, clean cut edges in carbon fibre-reinforced plastic/ fibreglass-reinforced plastic materials without delamination. Distortion-free, long, straight cuts at high cutting speed. Can also be used with depth stop.

Ø	Cutting width	
mm	mm	Part number
105	1.2	6 35 02 189 01 0



DIAMOND SEGMENT SAW BLADE WITH OPEN TEETH

For perfect, clean cut edges in carbon fibre-reinforced plastic/ fibreglass-reinforced plastic materials without delamination. Distortion-free, long, straight cuts at very high cutting speed. Diamond coating for outstanding service life. Can also be used with depth stop.

Ø	Cutting width		
mm	mm	Part number	
105	1,2	6 35 02 190 01 0	



Gentle sawing with perfect, clean cut edges in carbon fibrereinforced plastic/fibreglass-reinforced plastic materials without delamination. Particularly well suited to precise cut-outs and short cuts. Diamond coating for outstanding service life. Precise working into the corners and on edges Can also be used with depth stop.

Width	Length	
mm	mm	Part number
42	60	6 35 02 195 01 0



SEGMENT SAW BLADE

depressed, for removing panes of insulating glass installed on a putty bed, pack of 2

Part number
6 39 03 166 01 6

ACCESSORY SETS



ACCESSORY SET FOR CARGO

Subsequent order to Professional set Cargo consisting of: 2 straight cutter blades, toothed (form 073), 1 straight cutter blade, Z-bend, toothed (form 081), 1 hook-shaped cutter blade, toothed (form 217), 1 curved cutter blade, Z-bend, (form 072), 1 each of L-shaped cutter blade, toothed (forms 207 and 209), 1 spade-shaped scraper knife, with scratch-protective coating (form 105), 1 traction cable, 1 depth stop

> Part number 6 39 03 167 32 0



AUTOMOBILE WORKSHOP ACCESSORIES SET

Consisting of: 2 U-shaped cutter blades, short side (form 076), 2 U-shaped cutter blades, short side (1x form 079 and 1x form 101), 2 L-shaped cutter blades, toothed (form 207), 1 L-shaped cutter blade, toothed (form 208), 1 U-shaped cutter blade, reinforced (form 157), 1 straight cutter blade, Z-bend, with adjustable stop roller (form 143), 1 shovel-shaped scraper blade, with scrape protection coating (form 129), 1 stopper knife, 1 HSS saw blade (Ø 80 mm).

> Part number 6 39 03 167 25 7



AUTOMOBILE GLAZIER ACCESSORY SET

Consisting of: 3 L-shaped cutter blades, toothed (form 207), 2 L-shaped cutter blades, toothed (form 208), 1 L-shaped cutter blade, toothed (form 209), 1 each of U-shaped cutter blade, reinforced version (form 157 and 111), 2 U-shaped cutter blades, reinforced version, toothed (form 212), 1 straight cutter blade. 7-bend with adjustable stop roller (form 143), 1 straight cutter blade, Z-bend, toothed (form 081).

> Part number 6 39 03 167 38 3



ACCESSORY SET FOR INTERIOR CONSTRUCTION WORK WITH WOOD

Additional purchase for professional set for interior construction work with wood, consisting of: 1 HSS saw blade for wood (form 153), 4 E-Cut long-life saw blades (form 162, 163 and 164, 165), 4 E-Cut precision saw blades (form 119, 120 and 121, 122), 2 E-Cut universal saw blades (form 147, 148), 1 depth stop, 1 sanding pad, 5 each of sanding sheets, grain 80, 120, 180, 1 adapter and 2 tensioning elements

Part number 6 39 03 167 66 0



ACCESSORY SET FOR REPAIRING/REPLACING WINDOWS

Additional purchase for professional set for repairing/replacing windows, consisting of: 1 HSS saw blade, stepped (form 137), 1 HSS saw blade for wood (form 153), 1 E-Cut long-life saw blade (form 163), 2 E-Cut universal saw blades (form 147, 148), 1 segment saw blade (form 166), 1 cutter blade, mushroom-shaped (form 128), 1 depth stop, 1 sanding pad, 5 each of sanding sheets, grain 80, 120, 180, 1 adapter and 2 tensioning elements

> Part number 6 39 03 167 67 0

GENERAL ACCESSORIES



SHARPENING STONE

For sharpening blades before use to produce an optimum cut.

Part number 6 37 19 010 01 4



PROTECTIVE COVER

For safe tool changes for SuperCut with QuickIN when opening and closing the clamping lever.

> Part number 3 21 74 011 00 0



GRIT GHB HAND-GUIDED **BELT GRINDER**

The belt grinding system for various applications, can be used for mobile and stationary jobs.



250

GRIT GX 253 **BASIC BELT GRINDER** FOR MANUAL TRADES

Stationary belt grinders for use in trade and small-scale volume production.



255 **GRIT GX** ADD-ON MODULES **FOR MANUAL TRADES**



256 **GRIT GI BASIC BELT GRINDER FOR INDUSTRY**

Stationary belt grinders for use in industry and volume production.





GRIT GI ADD-ON MODULES **FOR INDUSTRY**

259

GRIT GKS COMPACT 263 BELT GRINDER

The space-saving and economical solution for the workshop.





10 GRIT GHB HAND-GUIDED BELT GRINDER

GRIT GHB 15-50



SUPPLIED

1 grinding belt 50 x 1,000 mm (K 36)

For accessories, see page 252

Powerful handheld belt grinder for flexible on-site use.

Input	kW	1,5
Current/Voltages		1 x 230 V
Speed, no load	rpm	8,500
Belt size	mm	50 x 1,000
Cable with plug	m	4
Weight according to EPTA	kg	6

Part number	7 245 01 60 00 0
EAN	4014586894331

FEIN BENEFITS

- Hand-guided alternative for angle grinders.
- Stationary use possible with table holder.
- POWERtronic for enormous power, power reserve and exceptional speed stability under load.
- Patented tool-free belt clamping system.
- anti-vibration handle.
- + Very short tooling time for stationary belt grinding.+ Height-adjustable table for flat grinding.

GRIT GHB 15-50 INOX

Universal handheld belt grinder for on-site problem-solving, ideal for stainless steel processing.

560 x 240 x 230



SUPPLIED

1 grinding belt 50 x 1,000 mm (K 36)

For accessories, see page 252

Input	kW	1,5
Current/Voltages		1 x 230 V
Speed, no load	rpm	2,500 - 7,900
Belt size	mm	50 x 1,000
Cable with plug	m	4
Weight according to EPTA	kg	6

Part number	7 245 02 60 00 0
EAN	4014586894362

FEIN BENEFITS

- + Hand-guided alternative for angle grinders.
- Stationary use possible with table holder.
- POWERtronic for enormous power, power reserve and exceptional speed stability under load.
- + Patented tool-free belt clamping system.
- anti-vibration handle.

 Very short tooling time for stationary belt grinding.
- + Height-adjustable table for flat grinding.

GRIT GHBD



SUPPLIED

1 GHBD module

For accessories, see page 252

Module for stationary belt grinding.

Dimensions LxWxH

Belt size	mm	50 x 1,000
Weight	kg	5,8
Part number		9 90 01 012 00 0
EAN		4014586880488

mm

- + Transforms hand-guided GHB into a stationary belt
- Perfect chamfering thanks to adjustable grinding table.
- Process profiles & pipes on the grinding table.
- Designed for heavy-duty use.

GRIT GHB HAND-GUIDED BELT GRINDER 10

GRIT GHBR



Module for stationary pipe notching.

Pipes up to Ø	mm	16 - 42.4
Dimensions LxWxH	mm	700 x 240 x 207
Belt size	mm	50 x 1,150
Weight	kg	13

Part number	9 90 01 012 02 0
EAN	4014586887005

FEIN BENEFITS

- + Can also be used on site.
 + Easily process pipes with different diameters.
 + Exact radii in one work step.
 + For accurately grinding out radii (with a diameter of 16 to 42,40 mm) on pipes and profiles.

 + Contact rollers for different pipe diameters.

 + Use only with GHB15-50 INOX.

SUPPLIED

Supplied without contact roller or grinding belt

For accessories, see page 252

GRIT GHBM



For accessories, see page 252

Module for mobile surface processing.

Dimensions LxWxH	mm	430 x 252 x 166
Belt size	mm	50 x 1,000
Weight	kg	5

Part number	9 90 01 012 01 0
EAN	4014586886992

- + Minimal effort required when grinding long welded seams thanks to roller guide.

 + Convert to a different application in under 45 seconds.
- + Homogeneous surfaces in one work step.
- + Low-fatigue machining of large areas.

10 GRIT GHB HAND-GUIDED BELT GRINDER

GRINDING BELTS

3M™ CUBITRON™ II

Precision grinding belt with ceramic grain guarantees maximum performance and service life. The evenly shaped ceramic grains produce a uniquely accurate feel during machining. The result is cool grinding without tarnishing and better surface quality. 50 x 1,000 mm

Grain	No. in pack pcs	Part number
36	10	6 99 03 126 00 0
60	10	6 99 03 127 00 0
80	10	6 99 03 128 00 0

3M™ CUBITRON™ II

Precision grinding belt with ceramic grain guarantees maximum performance and service life. The evenly shaped ceramic grains produce a uniquely accurate feel during machining. The result is cool grinding without tarnishing and better surface quality.

50 x 1150 mm, for pipe notching with GRIT GHBR module.

	No. in pack	
Grain	pcs	Part number
36	10	6 99 03 157 00 0

GRINDING MATERIAL Z

It's the all-rounder for grinding and deburring steel and non-ferrous metals which also satisfies the most stringent requirements. Developed in collaboration with professional users, this grinding material features an impressively long service life and high performance and is cost-effective to use Heavy polyester fabric, fully bonded with artificial resins, with zirconium corundum.

50 x 1,000 mm

	No. in pack	
Grain	pcs	Part number
36	10	6 99 03 130 00 0
60	10	6 99 03 131 00 0
80	10	6 99 03 132 00 0
120	10	6 99 03 133 00 0

GRINDING MATERIAL Z

It's the all-rounder for grinding and deburring steel and non-ferrous metals which also satisfies the most stringent requirements. Developed in collaboration with professional users, this grinding material features an impressively long service life and high performance and is cost-effective to use. Heavy polyester fabric, fully bonded with artificial resins, with zirconium corundum.

50 x 1150 mm, for pipe notching with GRIT GHBR module.

	No. in pack	
Grain	pcs	Part number
36	10	6 99 03 159 00 0

GRINDING MATERIAL A

Grinding belts with fine grit for fine grinding of metals to final finish. For the best surface results. Heavy cotton fabric, fully bonded with artificial resins, with corundum. 50 x 1,000 mm

	No. in pack		
Grain	pcs	Part number	
220	10	6 99 03 134 00 0	
320	10	6 99 03 135 00 0	
420	10	6 99 03 136 00 0	

GRINDING MATERIAL R

It's the top grinding belt on the market, featuring superior service life and performance for considerably shorter working times. Especially recommended for machining stainless and high-alloy steel. Extra heavy polyester fabric, fully bonded with artificial resins, with zirconium corundum. Additional top layer for cooling during grinding. 50 x 1.000 mm

Grain	No. in pack pcs	Part number
36	10	6 99 03 137 00 0
60	10	6 99 03 138 00 0
80	10	6 99 03 139 00 0
120	10	6 99 03 140 00 0



GRINDING MATERIAL R

It's the top grinding belt on the market, featuring superior service life and performance for considerably shorter working times. Especially recommended for machining stainless and high-alloy steel. Extra heavy polyester fabric, fully bonded with artificial resins, with zirconium corundum. Additional top layer for cooling during grinding. 50 x 1150 mm, for pipe notching with GRIT GHBR module.

	No. in pack		
Grain	pcs	Part number	
36	10	6 99 03 158 00 0	

FLEECE STRIPS



FLEECE BELT

Reliable for everything from covering up minor mistakes to a perfect finish. Long service lives make for cost-effective 50 x 1,000 mm

	No. in pack	
Model	pcs	Part number
medium	3	6 99 03 143 00 0

ACCESSORIES FOR GHBR



CONTACT ROLLER

Long service lives, low roll resistance thanks to high-quality ball bearings, easy to interchange

Ø	Width	
mm	mm	Part number
16	50	6 99 02 000 40 9
18	50	6 99 02 000 41 0
19	50	6 99 02 000 41 1
20	50	6 99 02 000 41 2
21	50	6 99 02 000 41 3
21,3	50	6 99 02 000 41 4
22	50	6 99 02 000 41 5
25	50	6 99 02 000 41 6
25,4	50	6 99 02 000 41 7
26	50	6 99 02 000 41 8
26,9	50	6 99 02 000 41 9
27	50	6 99 02 000 42 0
28	50	6 99 02 000 42 1
28,8	50	6 99 02 000 42 2
30	50	6 99 02 000 42 3
31,7	50	6 99 02 000 42 4
33	50	6 99 02 000 42 6
33,7	50	6 99 02 000 42 7
34	50	6 99 02 000 42 8
35	50	6 99 02 000 42 9
38	50	6 99 02 000 43 0
38,1	50	6 99 02 000 43 1
38,3	50	6 99 02 000 43 2
40	50	6 99 02 000 43 3
42	50	6 99 02 000 43 4
12,4	50	6 99 02 000 43 5

OTHER ACCESSORIES FOR GRIT GHB

STAINLESS STEEL SANDING SUPPORT

GRIT GHB 15-50 Inox


Part number
3 90 00 008 10 6


GRIT GX BASIC BELT GRINDER FOR MANUAL TRADES 10

GRIT GX basic belt grinder for manual trades

GRIT GX is based on the modular principle. In other words, you start with a high-value belt grinder - and additional modules can be added if necessary to extend the range of performance. This saves times, money and space.

This flexible design makes the GX range ideally suited to frequent use in manual trades. The GRIT GX range also provides impressive levels of maximum performance, reliability and excellent cost-effectiveness.





10 GRIT GX BASIC BELT GRINDER FOR MANUAL TRADES

GRIT GX 75



Powerful belt grinder, modular expandable, for manual trades and for small series.

Input	kW	3
Current/Voltages		3 x 400/440 V 50/60Hz
Speed, no load	rpm	3,000
Belt size	mm	75 x 2,000
Weight	kg	75

Part number	7 901 31 00 40 3
EAN	4014586872018

FEIN BENEFITS

- Expandable because of additional modules.

 Speeds optimal for metal working at 3 000 rpm.
- Height-adjustable plane grinding table for linear plane grinding.
 - Detachable swarf collector.
- Connection for extraction option available.
 Work level is individually adjustable.
 Patented belt-tensioning system.
 Robust three-phase AC motor.

- Low vibrations.

SUPPLIED

1 CEE plug (16 A), 1 grinding belt 75 x 2 000 mm (K 36 R)

For accessories, see page 266

GRIT GX 75 2H

Powerful belt grinder, modular expandable, for manual trades and for small series, ideal for machining stainless steel



Input	kW	1.5 / 2
Current/Voltages		3 x 400/440 V 50/60Hz
Speed, no load	rpm	1,500 / 3,000
Belt size	mm	75 x 2,000
Weight	kg	75

7 901 32 00 40 3 Part number EAN 4014586872063

FEIN BENEFITS

- Expandable because of additional modules.
 Speeds optimal for metal and stainless steel working at 1500/3 000 rpm.
- Height-adjustable plane grinding table for linear plane grinding.
- Detachable swarf collector.
- Connection for extraction option available. Work level is individually adjustable. Patented belt-tensioning system.

- Robust three-phase AC motor.
- Low vibrations.

SUPPLIED

1 grinding belt 75 x 2 000 mm (K 36 R), 1 CEE plug (16 A)

For accessories, see page 266

GRIT GXE



SUPPLIED

1 CEE plug (16 A), Supplied without steel brush

For accessories, see page 266

Highly effective deburring machine for manual trades and for small series.

Input	kW	2,2
Current/Voltages		3 x 400/440 V 50/60Hz
Speed, no load	rpm	1,500
Tool dimensions max. Ø x width	mm	250 x 60
Weight	kg	32

Part number	7 901 05 00 40 3
EAN	4014586857879

FEIN BENEFITS

- + Modular extendable with sturdy machine base also with integrated extraction.
- + Robust AC motor provides deburring with steady speed.
- For deburring of metal pipes, profiles, and flat materials up to a workpiece width of 75 mm.
- + Connection for extraction option available.
 + Broad range of wire brushes available.
- Effective deburring.
- + Motor protection switch.

GRIT GXC



SUPPLIED

1 guide rail, nylon, 1 guide rail, brass, 1 CEE plug (16 A)

For accessories, see page 266

Cylindrical grinding module for perfect surfaces of metal and stainless steel pipes and shafts.

Input	kW	0,18
Current/Voltages		3 x 400/440 V 50/60Hz
Pipes up to Ø	mm	10 - 100
Belt size	mm	75 x 2,000
Weight	kg	48

Part number	7 901 23 00 44 3
EAN	4014586871936

FEIN BENEFITS

- + Automatic feed is individually adjustable.
- High process speed at highest surface quality.
- For grinding of pipes and shafts of diameters ranging from Ø 10 - 100 mm.
- Combination possibilities with belt grinders GX 75 (2H).
- Wet grinding in possible combination with GXW.

GRIT GXW



SUPPLIED

1 litre cooling lubricant emulsion

For accessories, see page 266

Cooling lubricant module for a professional wet grinding.

Input	kW	0,12
Current/Voltages		3 x 400/440 V 50/60Hz
Weight	kg	8,6
Part number		7 901 24 00 44 3
EAN		1011596973115

FEIN BENEFITS

- Perfect surface results due to effective cooling lubricant supply
- Reduces the temperature of the workpiece.
- Binds the swarf.
- Closed circuit.
- Combination possibilities with belt grinders GX 75 (2H) and GI 75 (2H) and GI 150 (2H).
- + Increases service life of the grinding belts.

GRIT GXR



Radii-grinding module for precision fitting of pipes, profiles, and flat materials.

Pipes up to Ø	mm	16 - 75
Belt size	mm	75 x 2,250
Dimension profiles / flat material max.	mm	75 x 75
Weight	kg	54

Part number	9 90 01 001 00 1
EAN	4014586871974

FEIN BENEFITS

- + For accurately grinding out radii (with a diameter of 16 to 90 mm) on pipes and profiles.
- Contact rollers are optionally available in standard dimensions.
- Optional length stop for series application. Integrated depth stop.
- Combination possibilities with belt grinders GX 75 (2H).
- Angle setting, individually possible up to 90°.

SUPPLIED

1 contact roller Ø 42.4 mm, 1 contact roller Ø 48,3 mm, 1 grinding belt 75 x 2 250 (K 36 R)


For accessories, see page 266


10 GRIT GI BASIC BELT GRINDER FOR INDUSTRY


GRIT GI basic belt grinder for industry

The GRIT GI range is perfectly coordinated to all grinding applications, materials and formats in the metal industry. Thanks to the modular system, you can assemble the machine to suit your requirements – even for steps that have already been partly automated. The high quality,

robustness and outstanding power of the tools guarantee maximum efficiency and mean that the tools pay for themselves quickly, as they offer complete reliability, even in continuous use.







GRIT GI 75



SUPPLIED

1 CEE plug (16 A), 1 grinding belt 75 x 2 000 mm (K 36 R)

EAN

For accessories, see page 266

High-performance belt grinder, modular expandable, for industrial and series applications.

Input	kW	4
Current/Voltages		3 x 400/440 V 50/60Hz
Speed, no load	rpm	3,000
Belt size	mm	75 x 2,000
Weight	kg	65
Part number		7 902 01 00 40 3

FEIN BENEFITS

- + Quite robust AC motor provides grinding with steady speed.
- Speeds optimal for metal working at 3 000 rpm.
- Detachable swarf collector.
- Connection for extraction option available.
- Drive disk with polyurethane coating
- Work level is individually adjustable.
- Patented belt-tensioning system.
- Robust three-phase AC motor.
- Low vibrations.

GRIT GI 75 2H

High-performance belt grinder, modular expandable, for industrial and series applications, ideal for machining stainless steel.

4014586858913



SUPPLIED

1 CEE plug (16 A), 1 grinding belt 75 x 2 000 mm (K 36 R)

For accessories, see page 266

Input	kW	2.6 / 3.1
Current/Voltages		3 x 400/440 V 50/60Hz
Speed, no load	rpm	1,500 / 3,000
Belt size	mm	75 x 2,000
Weight	kg	65

Part number	7 902 02 00 40 3
EAN	4014586858944

FEIN BENEFITS

- + Quite robust AC motor provides grinding with steady speed.
- Speeds optimal for metal and stainless steel working at 1500/3 000 rpm.
- Detachable swarf collector.
- + Connection for extraction option available.
- + Drive disk with polyurethane coating
- Work level is individually adjustable.
- Exceedingly robust three-phase AC motor
- Patented belt-tensioning system.
- Low vibrations.

GRIT GI 100 EF

Powerful belt grinder in small format: for universal application on small workpieces



SUPPLIED

1 grinding belt 100 x 1 000 (K 60 Z)

For accessories, see page 266

Input	kW	1,1
Current/Voltages		1 x 230 V
Speed, no load	rpm	3,000
Belt size	mm	100 x 1,000
Weight	kg	29,8

Part number	7 902 23 00 23 2
EAN	4014586887043

FEIN BENEFITS

- + Universally applicable belt grinder for smaller workpieces
- Modular extendable with sturdy machine base also with integrated extraction.
- Can be used as a table machine
- Single-phase, alternating current version 230 V / 50Hz
- Suited also for mobile employment in workshop or assembly vehicles
- Patented belt-tensioning system.


GRIT GI 100

SUPPLIED

1 grinding belt 100 x 1 000 (K 60 Z)

For accessories, see page 266

Powerful belt grinder in small format: for universal application on small workpieces



Part number	7 902 23 00 40 3
EAN	4014586887067

- Universally applicable belt grinder for smaller workpieces
- Modular extendable with sturdy machine base also with integrated extraction.
- Can be used as a table machine
- Three-phase AC motor 1 500 W.
- Suited also for mobile employment in workshop or assembly vehicles
- Patented belt-tensioning system.

10 GRIT GI BASIC BELT GRINDER FOR INDUSTRY

GRIT GI 150



SUPPLIED

1 CEE plug (16 A), 1 grinding belt 150 x 2,000 mm (K 36 R)

For accessories, see page 266

High-performance belt grinder, modular expandable, for industrial and series applications.

Input	kW	4
Current/Voltages		3 x 400/440 V 50/60Hz
Speed, no load	rpm	3,000
Belt size	mm	150 x 2,000
Weight	kg	82
Part number		7 902 04 00 40 3
EAN		4014586858999

FEIN BENEFITS

- Expandable because of additional modules.
- Quite robust AC motor provides grinding with steady
- Speeds optimal for metal working at 3 000 rpm.
- Detachable swarf collector.
- Connection for extraction option available.
- Drive disk with polyurethane coating
- Work level is individually adjustable.
- Patented belt-tensioning system.
- Robust three-phase AC motor.
- Low vibrations.

GRIT GI 150 2H

High-performance belt grinder, modular expandable, for industrial and series applications, ideal for machining stainless steel.



SUPPLIED

1 CEE plug (16 A), 1 grinding belt 150 x 2,000 mm (K 36 R)

For accessories, see page 266

Input	kW	2.6 / 3.1
Current/Voltages		3 x 400/440 V 50/60Hz
Speed, no load	rpm	1,500 / 3,000
Belt size	mm	150 x 2,000
Weight	kg	82
Part number		7 902 05 00 40 3
EAN		4014586859019

FEIN BENEFITS

- Expandable because of additional modules.
- Quite robust AC motor provides grinding with steady
- Speeds optimal for metal and stainless steel working at 1500/3 000 rpm.
- Detachable swarf collector.
- Connection for extraction option available.
- Drive disk with polyurethane coating
- Work level is individually adjustable.
- Patented belt-tensioning system.
- Low vibrations.

GRIT GIS 75

High-performance grinder for standard grinding tasks.



EAN

Input	KVV	4
Current/Voltages		3 x 400/440 V 50/60Hz
Speed, no load	rpm	3,000
Idle speed at 50 Hz	rpm	3,000
Idle speed at 60 Hz	rpm	3,450
Belt size	mm	75 x 2,000
Weight	kg	74
Part number		7 902 29 50 44 3

LAAA

FEIN BENEFITS

- High-performance belt grinder with sturdy machine
- Constant speed at high grinding performance thanks to robust 4-kW motor
- + Very good price-performance ratio+ Detachable swarf collector.
- Patented belt-tensioning system. Low-vibration thanks to robust design

SUPPLIED

1 CEE plug (16 A), 1 grinding belt 75 x 2 000 mm (K 36 R)

For accessories, see page 266

GRIT GIS 150

High-performance grinder for standard grinding applications for extra-wide workpieces.



SUPPLIED

1 CEE plug (16 A), 1 grinding belt 150 x 2,000 mm (K 36 R)

For accessories, see page 266

4014586878126

- Input 3 x 400/440 V Current/Voltages 50/60Hz Speed, no load 3.000 rpm Idle speed at 50 Hz 3.000 rpm Idle speed at 60 Hz 3,450 rpm Relt size 150 x 2,000 mm Weight kg 93
- 7 902 30 50 44 3 Part number EAN 4014586878225

- High-performance belt grinder with sturdy machine
- Constant speed at high grinding performance thanks to robust 4-kW motor
- Very good price-performance ratio
- Detachable swarf collector.
- Patented belt-tensioning system.
- Low-vibration thanks to robust design

GRIT GI ADD-ON MODULES FOR INDUSTRY 10

GRIT GIE



SUPPLIED

1 CEE plug (16 A), Supplied without steel brush

For accessories, see page 266

Highly effective deburring machine for industrial deburring in series.

Input	kW	1.5 / 2.0
Current/Voltages		3 x 400/440 V 50/60Hz
Speed, no load	rpm	1,500 / 3,000
Tool dimensions max. Ø x width	mm	250 x 60/120
Weight	kg	34

Part number	7 902 07 00 40 3
EAN	4014586859057

FEIN BENEFITS

- + Speeds optimal for metal and stainless steel working at 1500/3 000 rpm.
- Modular extendable with sturdy machine base also with integrated extraction.
- Robust AC motor provides deburring with steady speed.
- + Connection for extraction option available.
 + Broad range of wire brushes available.
- Effective deburring.
- Motor protection switch.

GRIT GIC



SUPPLIED

- 1 guide rail, nylon, 1 guide rail, brass,
- 1 CEE plug (16 A)

For accessories, see page 266

Centreless grinding module for industrial centreless grinding in volume production

Input	kW	0,18
Current/Voltages		3 x 400/440 V 50/60Hz
Pipes up to Ø	mm	10 - 130
Belt size	mm	75/150 x 2,000
Variable Feed	m/min	0 - 2
Weight	kg	65
Part number		7 902 12 00 44 3
EAN		4014586867656

FEIN BENEFITS

- + For industrial centreless grinding of pipes up to 6 m long with optional pipe guide.
- Flexible when machining pipe diameters of between 10 and 130 mm.
- + Cool surfaces and a long grinding belt service life thanks to wet grinding in conjunction with the cooling lubricant module GXW.
- Combination possibility with belt grinder GI 150 (2H)
- Quick fastener for simple retooling without the need for tools.
- + Infinitely variable feed speed from 0 to 2 m/min.

GRIT GIMS 75



For accessories, see page 266

Mobile carriage for effective grinding "on site" at the floor.

Input	kW	4
Current/Voltages		3 x 400/440 V 50/60Hz
Speed, no load	rpm	3,000
Belt size	mm	75 x 2,000
Weight	kg	100

Part number	7 902 13 00 40 3
EAN	4014586872599

FEIN BENEFITS

- + Comfortable work handling thanks to standing work
- Highly effective grinding and polishing of weld seams on the floor
- Grinding over and descaling of steel parts
- Towing bar position can be adjusted infinitely variable
- Minimum wall clearance
- + Depth stop

GRIT GIMS 150



For accessories, see page 266

Mobile carriage for effective grinding "on site" at the floor.

Input	kW	4
Current/Voltages		3 x 400/440 V 50/60Hz
Speed, no load	rpm	3,000
Belt size	mm	150 x 2,000
Weight	kg	110

Part number	7 902 14 00 40 3
EAN	4014586872643

- + Comfortable work handling thanks to standing work position
- Highly effective grinding and polishing of weld seams on the floor
- + Grinding over and descaling of steel parts
- Towing bar position can be adjusted infinitely variable
- Minimum wall clearance
- + Depth stop

10 GRIT GI ADD-ON MODULES FOR INDUSTRY

EAN

GIMS 75 2H

Mobile carriage for effective grinding "on site" at the floor.



For accessories, see page 266

Input	kW	2.6 / 3.1
Current/Voltages		3 x 400/440 V 50/60Hz
Speed, no load	rpm	1,500 / 3,000
Belt size	mm	75 x 2,000
Weight	kg	103
Part number		7 902 16 00 40 3

FEIN BENEFITS

- + Comfortable work handling thanks to standing work position
- Highly effective grinding and polishing of weld seams on the floor
- Grinding over and descaling of steel parts
- Speeds optimal for metal and stainless steel working at 1500/3 000 rpm.
- Towing bar position can be adjusted infinitely variable
- Minimum wall clearance
- Depth stop

4014586878614

GIMS 150 2H

Mobile carriage for effective grinding "on site" at the floor.



For accessories, see page 266

Input	kW	2.6 / 3.1
Current/Voltages		3 x 400/440 V 50/60Hz
Speed, no load	rpm	1,500 / 3,000
Belt size	mm	150 x 2,000
Weight	kg	114

Part number	7 902 17 00 40 3
EAN	4014586878621

FEIN BENEFITS

- + Comfortable work handling thanks to standing work
- Highly effective grinding and polishing of weld seams on the floor
- Grinding over and descaling of steel parts
- Speeds optimal for metal and stainless steel working at 1500/3 000 rpm.
- Towing bar position can be adjusted infinitely variable
- Minimum wall clearance
- Depth stop

GIMS 75-6

Mobile carriage for effective grinding "on site" at the floor.



For accessories, see page 266

Input	kW	6
Current/Voltages		3 x 400/440 V 50/60Hz
Speed, no load	rpm	3,000
Belt size	mm	75 x 2,000
Weight	kg	121

Part number	7 902 18 00 40 3
EAN	4014586878645

FEIN BENEFITS

- + Highly effective grinding and polishing of weld seams on the floor
- Grinding over and descaling of steel parts
- Comfortable work handling thanks to standing work position Minimum wall clearance
- Towing bar position can be adjusted infinitely variable
- Depth stop

GIMS 150-6



For accessories, see page 266

Mobile carriage for effective grinding "on site" at the floor.

Input	kW	6
Current/Voltages		3 x 400/440 V 50/60Hz
Speed, no load	rpm	3,000
Belt size	mm	150 x 2,000
Weight	kg	131

Part number	7 902 19 00 40 3
FAN	4014586878683

- + Highly effective grinding and polishing of weld seams on the floor
- Grinding over and descaling of steel parts
- + Comfortable work handling thanks to standing work position Minimum wall clearance
- Towing bar position can be adjusted infinitely variable
- Depth stop

GRIT GILSGIB



SUPPLIED

1 CEE plug (16 A), 1 grinding belt 150 x 2,000 mm (K 120 R)

For accessories, see page 266

Surface grinder for perfect longitudinal grinding of square pipes, profiles and flat materials in automatic processes.

Input	kW	2.6 / 3.1
Current/Voltages		3 x 400/440 V 50/60Hz
Speed, no load	rpm	1,500 / 3,000
Belt size	mm	150 x 2,000
Dimension profiles / flat material max.	mm	100 x 100
Weight	kg	189

Part number	7 902 35 00 40 3
EAN	4014586880921

without dust extraction

FEIN BENEFITS

- + High operating speed because of automatic feed+ Perfect finishing results up to the finish
- Flat material can also be ground "upright".
- Consistent belt dimensions 150 x 2 000 mm. Belt grinder can be used for contact grinding even though module is mounted.
- + For angled workpieces
 + Space-saving employment because of optional swivel plate possible.

GRIT GIL



For accessories, see page 266

Plane grinding module for perfect longitudinal grinding of square pipes, profiles and flat materials.

Input	kW	0,18
Current/Voltages		3 x 400/440 V 50/60Hz
Belt size	mm	150 x 2,000
Dimension profiles / flat material max.	mm	100 x 100
Weight	kg	64

Part number	7 902 48 00 40 3
EAN	4014586880945

FEIN BENEFITS

- + High operating speed because of automatic feed+ Perfect finishing results up to the finish
- Flat material can also be ground "upright".
- Consistent belt dimensions 150 x 2 000 mm.
- Belt grinder can be used for contact grinding even though module is mounted.
- + For angled workpieces
- Combination possibility with belt grinder GI 150 (2H)
- Space-saving employment because of optional swivel plate possible.

GRIT GILS



SUPPLIED

1 grinding belt 150 x 2,000 mm (K 120 R), 1 CEE plug (16 A)

For accessories, see page 266

Surface grinder for perfect longitudinal grinding of square pipes, profiles and flat materials in automatic processes.

Input	kW	2.6 / 3.1
Current/Voltages		3 x 400/440 V 50/60Hz
Speed, no load	rpm	1,500 / 3,000
Belt size	mm	150 x 2,000
Dimension profiles / flat material max.	mm	100 x 100
Weight	kg	206

Part number	7 902 51 00 40 3
EAN	4014586880976

with dust extraction

FEIN BENEFITS

- High operating speed because of automatic feed
- Perfect finishing results up to the finish
- + Flat material can also be ground "upright".
- + Consistent belt dimensions 150 x 2 000 mm.
- + Belt grinder can be used for contact grinding even though module is mounted.
- For angled workpieces
- Space-saving employment because of optional swivel plate possible.

GRIT GIB



For accessories, see page 266

Exceedingly sturdy machine base

Weight	kg	17
Part number		9 90 01 003 00 0
EAN		4014586859064

- Work height can be adjusted conveniently by gas compression spring without effort
- Low-vibration thanks to robust design
- Combination possibilities with belt grinder GI 75 (2H) and GI 150 (2H)
- Powder coating
- + Robust welded construction

10 GRIT GI ADD-ON MODULES FOR INDUSTRY

GRIT GIBE



SUPPLIED

2 hoses, 4 tensioning belts

For accessories, see page 266

Exceedingly sturdy machine base with integrated double extraction.

Input	kW	0,35
Current/Voltages		220/230 & 400/440 V
Air flow	l/min	13,300
Max. vacuum	hPa	4
Weight	kg	55

Part number	9 90 01 004 00 0
EAN	4014586859071

FEIN BENEFITS

- Integrated metal swarf collector, resistant against hot
- Robust welded construction
- Flexible, heat-resistant steel hoses
- Cassette filter for effective filtering
- Combination possibilities with belt grinder GI 75 (2H) and GI 150 (2H)
- Powder coating

GRIT GIR



SUPPLIED

1 contact roller Ø 42.4 mm, 1 grinding belt 150 x 2,250 mm (K 36 R), 1 dust container

For accessories, see page 266

Radii-grinding module for precision fitting of pipes, profiles and flat materials in series application.

mm	20 - 150
mm	150 x 2,250
mm	120 x 150
kg	109
	mm mm

Part number	9 90 01 007 00 1
EAN	4014586878263

- For accurately grinding out radii (with a diameter of 20 to 193.7 mm) on pipes and profiles.
- Contact rollers are optionally available in standard dimensions.
- Integrated depth stop for the series application
- Combination possibility with belt grinder GI 150 (2H)
- Angle setting, individually possible up to 90°.

GRIT GIXBE



SUPPLIED

1 hose, 1 tensioning belt, 1 CEE plug (16 A)

For accessories, see page 266

Integrated motor for effective suction.

Input	kW	0,37
Current/Voltages		3 x 400/440 V 50/60Hz
Air flow	l/min	8,170
Speed, no load	rpm	1,500 / 3,000
Max. vacuum	hPa	2,65
Dimensions LxWxH	mm	305 x 575 x 700
Weight	kg	58

Part number	9 90 01 009 00 0
EAN	4014586859125

FEIN BENEFITS

- Great steadiness because of bolting to the floor
- Connection to integrated extraction possible.
- Combination possibility with belt grinder GI 100 (EF) and deburring machines GXE, GIE Powder coating

GRIT GIXS



For accessories, see page 266

Sturdy machine base made of powder coated steel plate.

Dimensions LxWxH	mm	304 x 356 x 769
Weight	kg	18
Part number		9 90 01 002 00 0
EAN		4014586858340

- Great steadiness because of bolting to the floor
- Combination possibility with belt grinder GI 100 (EF) and deburring machines GXE, GIE
- Powder coating
- Steel plate model











		GRIT GKS 75	GRIT GKS 75	GRIT GKS 75	GRIT GKS 75	GRIT GKS 75 2H
		Compact belt grinder for	metalwork. The economic	cal solution for the worksh	ор.	
PAGE		264	264	264	265	265
Input	kW	4	1,1	1,5	3	1.5 / 2
Current/Voltages		3 x 400/440 V 50/60Hz	1 x 230 V	3 x 400/440 V 50/60Hz	3 x 400/440 V 50/60Hz	3 x 400/440 V 50/60Hz
Belt size	mm	75 x 2,000	75 x 2,000	75 x 2,000	75 x 2,000	75 x 2,000

10 GRIT GKS COMPACT BELT GRINDER

EAN

GRIT GKS 75



SUPPLIED

1 grinding belt 75 x 2 000 mm (K 36 R)

For accessories, see page 266

Compact belt grinder for metalwork. The economical solution for the workshop.

Input	kW	4
Current/Voltages		3 x 400/440 V 50/60Hz
Speed, no load	rpm	3,000
Belt size	mm	75 x 2,000
Weight	kg	50
Dant acceptant		7,005,01,00,40,7

Part number 7 905 01 00 40 3 EAN 4014586888255

FEIN BENEFITS

- Very economical to buy as it offers optimum value for money.
- + Takes up 2/3 less space than standard tools thanks to its minimalistic design concept.
- + Can be used straight away. No assembly or installation work needed.
- + Short setup times grinding belts can be rapidly exchanged.
- Controlled sparking ensures maximum work safety.
- Powerful motor for high sanding capacity.

GRIT GKS 75



SUPPLIED

1 grinding belt 75 x 2 000 mm (K 36 R)

For accessories, see page 266

Compact belt grinder for metalwork. The economical solution for the workshop.

4014586888262

Input	kW	1,1
Current/Voltages		1 x 230 V
Speed, no load	rpm	3,000
Belt size	mm	75 x 2,000
Weight	kg	45
Part number		7 905 02 00 23 2

FEIN BENEFITS

- + Very economical to buy as it offers optimum value for money.
- + Takes up 2/3 less space than standard tools thanks to its minimalistic design concept.
- + Can be used straight away. No assembly or installation work needed.
- + Short setup times grinding belts can be rapidly exchanged.
- + Controlled sparking ensures maximum work safety.

GRIT GKS 75



SUPPLIED

1 grinding belt 75 x 2 000 mm (K 36 R)

For accessories, see page 266

 $Compact \ belt \ grinder \ for \ metalwork. \ The \ economical \ solution \ for \ the \ workshop.$

Input	kW	1,5
Current/Voltages		3 x 400/440 V 50/60Hz
Speed, no load	rpm	3,000
Belt size	mm	75 x 2,000
Weight	kg	45
Part number		7 905 02 00 40 3
EAN		4014586888279

- Very economical to buy as it offers optimum value for money.
- + Takes up 2/3 less space than standard tools thanks to its minimalistic design concept.
- Can be used straight away. No assembly or installation work needed.
- + Short setup times grinding belts can be rapidly exchanged.
- + Controlled sparking ensures maximum work safety.

GRIT GKS 75



SUPPLIED

1 grinding belt 75 x 2 000 mm (K 36 R)

EAN

For accessories, see page 266

Compact belt grinder for metalwork. The economical solution for the workshop.

Input	kW	3
Current/Voltages		3 x 400/440 V 50/60Hz
Speed, no load	rpm	3,000
Belt size	mm	75 x 2,000
Weight	kg	50
Part number		7 905 03 00 40 3

- + Very economical to buy as it offers optimum value for
- money. + Takes up 2/3 less space than standard tools thanks to its minimalistic design concept.
- Can be used straight away. No assembly or installation work needed.
- + Short setup times grinding belts can be rapidly
- exchanged.

 + Controlled sparking ensures maximum work safety.

 + Powerful motor for high sanding capacity.

GRIT GKS 75 2H



SUPPLIED

1 grinding belt 75 x 2 000 mm (K 36 R)

For accessories, see page 266

Compact belt grinder for metalwork. The economical solution for the workshop.

4014586888293

Input	kW	1.5 / 2
Current/Voltages		3 x 400/440 V 50/60Hz
Speed, no load	rpm	1,500 / 3,000
Belt size	mm	75 x 2,000
Weight	kg	45

Part number	7 905 04 00 40 3
EAN	4014586888309

- + Very economical to buy as it offers optimum value for
- Takes up 2/3 less space than standard tools thanks to its minimalistic design concept.

 + Can be used straight away. No assembly or installation
- work needed.
- + Two speed settings deliver optimum speeds for metalworking and stainless steel processing.
- + Short setup times grinding belts can be rapidly
- exchanged.

 + Controlled sparking ensures maximum work safety.

 + Powerful motor for high sanding capacity.

10 BELT GRINDERS

GRINDING BELTS

3M™ CUBITRON™ II

Precision grinding belt with ceramic grain guarantees maximum performance and service life. The evenly shaped ceramic grains produce a uniquely accurate feel during machining. The result is cool grinding without tarnishing and better surface quality. $150 \times 2,000 \ \text{mm}$

	No. in pack	
Grain	pcs	Part number
60	10	6 99 03 149 00 0
80	10	6 99 03 150 00 0



3M™ CUBITRON™ II

Precision grinding belt with ceramic grain guarantees maximum performance and service life. The evenly shaped ceramic grains produce a uniquely accurate feel during machining. The result is cool grinding without tarnishing and better surface quality.

150 x 2250 mm, for pipe notching with GRIT GIR module.

	No. in pack	
Grain	pcs	Part number
36	10	6 99 03 154 00 0
60	10	6 99 03 155 00 0



GRINDING MATERIAL R

It's the top grinding belt on the market, featuring superior service life and performance for considerably shorter working times. Especially recommended for machining stainless and high-alloy steel. Extra heavy polyester fabric, fully bonded with artificial resins, with zirconium corundum. Additional top layer for cooling during grinding.

75 x 2,000 mm

	No. in pack	
Grain	pcs	Part number
24	10	6 99 03 000 00 0
36	10	6 99 03 002 00 0
40	10	6 99 03 004 00 0
60	10	6 99 03 007 00 0
80	10	6 99 03 009 00 0
120	10	6 99 03 013 00 0



GRINDING MATERIAL R

It's the top grinding belt on the market, featuring superior service life and performance for considerably shorter working times. Especially recommended for machining stainless and high-alloy steel. Extra heavy polyester fabric, fully bonded with artificial resins, with zirconium corundum. Additional top layer for cooling during grinding.

75 x 2250 mm, for pipe notching with GRIT GXR module.

Grain	pcs	Part number
36	10	6 99 03 020 00 0



GRINDING MATERIAL R

It's the top grinding belt on the market, featuring superior service life and performance for considerably shorter working times. Especially recommended for machining stainless and high-alloy steel. Extra heavy polyester fabric, fully bonded with artificial resins, with zirconium corundum. Additional top layer for cooling during grinding.

for cooling during grinding. 75 x 2300 mm, for pipe notching with GRIT GXR module for contact rollers with diameter > 80 mm.

	No. in pack	
Grain	pcs	Part number
36	10	6 99 03 122 00 0



GRINDING MATERIAL R

It's the top grinding belt on the market, featuring superior service life and performance for considerably shorter working times. Especially recommended for machining stainless and high-alloy steel. Extra heavy polyester fabric, fully bonded with artificial resins, with zirconium corundum. Additional top layer for cooling during grinding. $150 \times 2,000 \text{ mm}$

Grain	No. in pack	Do at an area la car
Grain	pcs	Part number
24	10	6 99 03 039 00 0
36	10	6 99 03 040 00 0
40	10	6 99 03 042 00 0
60	10	6 99 03 044 00 0
80	10	6 99 03 046 00 0
120	10	6 99 03 048 00 0



GRINDING MATERIAL R

It's the top grinding belt on the market, featuring superior service life and performance for considerably shorter working times. Especially recommended for machining stainless and high-alloy steel. Extra heavy polyester fabric, fully bonded with artificial resins, with zirconium corundum. Additional top layer for cooling during grinding.

150 x 2250 mm, for pipe notching with GRIT GIR module.

	No. in pack	
Grain	pcs	Part number
36	10	6 99 03 053 00 0



GRINDING MATERIAL R

It's the top grinding belt on the market, featuring superior service life and performance for considerably shorter working times. Especially recommended for machining stainless and high-alloy steel. Extra heavy polyester fabric, fully bonded with artificial resins, with zirconium corundum. Additional top layer for cooling during grinding.

150 x 2400 mm, for pipe notching with GRIT GIR module for contact rollers with diameter > 170 mm.

	No. in pack	
Grain	pcs	Part number
36	10	6 99 03 111 00 0



GRINDING MATERIAL Z

It's the all-rounder for grinding and deburring steel and non-ferrous metals which also satisfies the most stringent requirements. Developed in collaboration with professional users, this grinding material features an impressively long service life and high performance and is cost-effective to use. Heavy polyester fabric, fully bonded with artificial resins, with zirconium corundum.

75 x 2,000 mm

Grain	No. in pack	
	pcs	Part number
36	10	6 99 03 003 00 0
40	10	6 99 03 005 00 0
60	10	6 99 03 008 00 0
80	10	6 99 03 010 00 0
120	10	6 99 03 014 00 0



GRINDING MATERIAL Z

It's the all-rounder for grinding and deburring steel and non-ferrous metals which also satisfies the most stringent requirements. Developed in collaboration with professional users, this grinding material features an impressively long service life and high performance and is cost-effective to use. Heavy polyester fabric, fully bonded with artificial resins, with zirconium corundum.

75 x 2250 mm, for pipe notching with GRIT GXR module.

	No. in pack	
Grain	pcs	Part number
36	10	6 99 03 021 00 0



GRINDING MATERIAL Z

It's the all-rounder for grinding and deburring steel and non-ferrous metals which also satisfies the most stringent requirements. Developed in collaboration with professional users, this grinding material features an impressively long service life and high performance and is cost-effective to use. Heavy polyester fabric, fully bonded with artificial resins, with zirconium corundum.

100 x 1,000 mm

Grain	No. in pack pcs	Part number
36	10	6 99 03 034 00 0
40	10	6 99 03 035 00 0
60	10	6 99 03 036 00 0
80	10	6 99 03 037 00 0
120	10	6 99 03 038 00 0



GRINDING MATERIAL Z

It's the all-rounder for grinding and deburring steel and non-ferrous metals which also satisfies the most stringent requirements. Developed in collaboration with professional users, this grinding material features an impressively long service life and high performance and is cost-effective to use. Heavy polyester fabric, fully bonded with artificial resins, with zirconium corundum.

150 x 2,000 mm

pcs	Part number
10	6 99 03 041 00 0
10	6 99 03 043 00 0
10	6 99 03 045 00 0
10	6 99 03 047 00 0
10	6 99 03 049 00 0
	10 10 10



GRINDING MATERIAL Z

It's the all-rounder for grinding and deburring steel and non-ferrous metals which also satisfies the most stringent requirements. Developed in collaboration with professional users, this grinding material features an impressively long service life and high performance and is cost-effective to use. Heavy polyester fabric, fully bonded with artificial resins, with zirconium corundum.

 $150\ x\ 2250\ mm,$ for pipe notching with GRIT GIR module.

	No. in pack	
Grain	pcs	Part number
36	10	6 99 03 054 00 0



GRINDING MATERIAL Z

It's the all-rounder for grinding and deburring steel and non-ferrous metals which also satisfies the most stringent requirements. Developed in collaboration with professional users, this grinding material features an impressively long service life and high performance and is cost-effective to use. Heavy polyester fabric, fully bonded with artificial resins, with zirconium corundum.

 150×2400 mm, for pipe notching with GRIT GIR module for contact rollers with diameter > 170 mm.

Grain	pcs	Part number
36	10	6 99 03 112 00 0



GRINDING MATERIAL A

Grinding belts with fine grit for fine grinding of metals to final finish. For the best surface results. Heavy cotton fabric, fully bonded with artificial resins, with corundum. $75 \times 2,000 \text{ mm}$

	No. in pack		
Grain	pcs	Part number	
220	10	6 99 03 017 00 0	
320	10	6 99 03 018 00 0	
400	10	6 99 03 019 00 0	



GRINDING MATERIAL A

Grinding belts with fine grit for fine grinding of metals to final finish. For the best surface results. Heavy cotton fabric, fully bonded with artificial resins, with corundum. $150 \times 2,000 \text{ mm}$

	No. in pack	
Grain	pcs	Part number
220	10	6 99 03 050 00 0
320	10	6 99 03 051 00 0
400	10	6 99 03 052 00 0

FLEECE STRIPS



FLEECE BELT

Reliable for everything from covering up minor mistakes to a perfect finish. Long service lives make for cost-effective working.

75 x 2,000 mm

	No. in pack	
Model	pcs	Part number
very fine	3	6 99 03 121 01 0
medium	3	6 99 03 119 01 0
coarse	3	6 99 03 117 01 0



FLEECE BELT

Reliable for everything from covering up minor mistakes to a perfect finish. Long service lives make for cost-effective working. 150 x 2,000 mm

	No. in pack	
Model	pcs	Part number
very fine	3	6 99 03 120 01 0
medium	3	6 99 03 118 01 0
coarse	3	6 99 03 116 01 0

ACCESSORIES FOR GRIT GX 75 / GX 75 2H



STAINLESS STEEL SANDING SUPPORT

GX 75

Part number 167,80 6 99 02 338 00 0



GRAPHITE PAD

As sliding base for surface grinding

No. in pack

pocs Part number 5 3 90 00 000 0 1



EYE PROTECTION

Acrylic screen for protection against sparks

No. in pack pcs

pcs	Part number
3	3 90 00 000 00 4



SPARK BOX

with interfaces to extraction unit.

Part number 109,50 6 99 02 343 00 0

10 BELT GRINDERS

ACCESSORIES GRIT GXR

STAINLESS STEEL JAWS

Interchangeable, for vice when machining stainless steel.

6 99 02 004 00 0



LENGTH STOP

 $1000\ \mathrm{mm}$ long, continuously variable, easy to fit

Part number 6 99 02 001 00 0



CONTACT ROLLER

Long service lives, low roll resistance thanks to high-quality ball bearings, easy to interchange

0	AAC 101	
Ø mm	Width mm	Part number
15	75	6 99 02 304 00 0
16	75	6 99 02 020 00 0
17	75	6 99 02 021 00 0
17,2	75	6 99 02 022 00 0
18	75	6 99 02 023 00 0
19	75	6 99 02 024 00 0
20	75	6 99 02 025 00 0
21	75	6 99 02 026 00 0
21,3	75	6 99 02 027 00 0
22	75	6 99 02 028 00 0
22,2	75	6 99 02 029 00 0
22,5	75	6 99 02 030 00 0
23	75	6 99 02 031 00 0
23,1	75	6 99 02 032 00 0
24	75	6 99 02 033 00 0
24,5	75	6 99 02 034 00 0
25	75	6 99 02 035 00 0
25,4	75	6 99 02 036 00 0
25,9	75	6 99 02 037 00 0
26	75	6 99 02 038 00 0
26,4	75	6 99 02 039 00 0
26,9	75	6 99 02 040 00 0
27	75	6 99 02 041 00 0
28	75	6 99 02 042 00 0
28,6	75	6 99 02 043 00 0
28,8	75	6 99 02 044 00 0
29	75	6 99 02 045 00 0
30	75	6 99 02 046 00 0
31	75	6 99 02 323 00 0
31,7	75	6 99 02 047 00 0
32	75	6 99 02 048 00 0
33	75	6 99 02 049 00 0
33,7	75	6 99 02 050 00 0
34	75	6 99 02 051 00 0
35	75	6 99 02 052 00 0
36	75	6 99 02 053 00 0
37,5	75	6 99 02 054 00 0
38	75	6 99 02 055 00 0
38,1	75	6 99 02 056 00 0
38,3	75	6 99 02 057 00 0
40	75	6 99 02 058 00 0
41	75	6 99 02 059 00 0
41,2	75	6 99 02 060 00 0
42	75	6 99 02 061 00 0
42,4	75	6 99 02 062 00 0
42,6	75	6 99 02 063 00 0
43	75	6 99 02 064 00 0
43,3	75	6 99 02 065 00 0

Ø	Width	
mm	mm	Part number
44	75	6 99 02 066 00 0
44,5	75	6 99 02 067 00 0
45	75	6 99 02 068 00 0
46	75	6 99 02 069 00 0
48	75	6 99 02 070 00 0
48,3	75	6 99 02 071 00 0
49	75	6 99 02 072 00 0
50	75	6 99 02 073 00 0
50,8	75	6 99 02 074 00 0
51	75	6 99 02 075 00 0
53	75	6 99 02 076 00 0
53,7	75	6 99 02 077 00 0
54	75	6 99 02 078 00 0
55	75	6 99 02 079 00 0
57	75	6 99 02 080 00 0
57,5	75	6 99 02 324 00 0
58	75	6 99 02 081 00 0
59	75	6 99 02 082 00 0
60	75	6 99 02 083 00 0
60,3	75	6 99 02 084 00 0
63	75	6 99 02 085 00 0
63,5	75	6 99 02 086 00 0
65	75	6 99 02 087 00 0
67	75	6 99 02 088 00 0
68	75	6 99 02 326 00 0
69	75	6 99 02 089 00 0
70	75	6 99 02 090 00 0
73	75	6 99 02 091 00 0
75	75	6 99 02 092 00 0
76	75	6 99 02 093 00 0
76,1	75	6 99 02 094 00 0
76,2	75	6 99 02 095 00 0
80	75	6 99 02 096 00 0
82,5	75	6 99 02 097 00 0
84	75	6 99 02 327 00 0
88,9	75	6 99 02 098 00 0
90	75	6 99 02 099 00 0



EYE PROTECTION GU75/GR/GXR (3 PIECES)

Part number 3 90 00 000 00 7



DUST CONTAINER

Plastic, to douse sparks, with handles on the sides, capacity about 15 l

Part number 3 90 00 000 38 5

ACCESSORIES FOR MACHINES GXC



Part number 6 99 02 179 60 0



PIPE SUPPORT

 \emptyset 10-160 mm Can be combined with one another depending on the pipe length desired.

max.	pipe	length
------	------	--------

mm	Part number
1,000	6 99 02 180 60 0



PIPE SUPPORT

 \emptyset 10-160 mm Can be combined with one another depending on the pipe length desired.

max. pipe length

mm	Part number
1,500	6 99 02 181 60 0



GUIDE RAIL, BRASS

For dry grinding and course material surfaces

Part number 3 90 00 000 49 6



NYLON GLIDE SUPPORT

For high surface quality

Part number
3 90 00 000 49 7

ACCESSORIES GRIT GXE



STAINLESS STEEL SANDING SUPPORT

GXE

Part numbe
6 99 02 344 00 (



STEEL WIRE BRUSH

 \emptyset 250 mm x 60 mm, with very high wire drawing strength for highly efficient use, mounting hole \emptyset 51 mm. 0.2 mm thick wire for thin-walled pipes and profiles. 0.35 mm-thick wire for universal use. 0.5 mm thick wire for thick-walled pipes and profiles and great deburring results. Steel version

Wire thickness

mm	Part number
0,2	6 99 02 006 00 0
0,35	6 99 02 007 00 0
0,5	6 99 02 008 00 0



STEEL WIRE BRUSH

 \emptyset 250 mm x 60 mm, with very high wire drawing strength for highly efficient use, mounting hole \emptyset 51 mm. 0.2 mm thick wire for thin-walled pipes and profiles. 0.35 mm-thick wire for universal use. 0.5 mm thick wire for thick-walled pipes and profiles and great deburring results. Stainless steel version

Wire thickness

mm	Part number
0,2	6 99 02 009 00 0
0,35	6 99 02 010 00 0



EYE PROTECTION

Acrylic screen for protection against sparks

No. in pack

pcs	Part number
3	3 90 00 000 00 4

ACCESSORIES GRIT GXW



GRINDING/COOLING EMULSION

Concentrate, 10 l, mixing ratio 1:30, yields 300 l of ready-to-use cooling lubricant.

Part number 6 99 02 100 00 0

OTHER GRIT GX ACCESSORIES



HOSE

Flexible, for swarf extraction, 90 mm in diameter, 1 m long, steel, high level of heat resistance.

Part number 3 90 00 000 00 2



TUBE CLAMPS

For securing the flexible hose.

Part number 3 90 00 000 00 3



DUST CONTAINER

For extinguishing sparks, metal lid for hose connection, plastic, handles on the sides, capacity approx. 20 l.

Part number 6 99 02 000 00 0

10 BELT GRINDERS

ACCESSORIES FOR GRIT GI 75 / GI 75 2H

-

GRAPHITE PAD

As sliding base for surface grinding.

No. in pack

pcs	Part number
5	3 90 00 000 00 1



EYE PROTECTION GU75/GR/GXR (3 PIECES)

Part number 3 90 00 000 00 7



MITRE JOINT UNIT FOR PREPARATION OF WELDED SEAMS

Fixture for chamfering workpieces to prepare welded seams. GI/GIS 75

Part number 6 99 02 000 15 0



STAINLESS STEEL SANDING SUPPORT GI/GIS 75

Part number 6 99 02 000 14 8

ACCESSORIES FOR GRIT GI 150 / GI 150 2H



GRAPHITE COATING

 No. in pack
 Part number

 3
 3 90 00 000 05 6



MITRE JOINT UNIT FOR PREPARATION OF WELDED

SEAMS

Fixture for chamfering workpieces to prepare welded seams. GI/GIS 150

> Part number 6 99 02 000 15 1



STAINLESS STEEL SANDING SUPPORT

GI/GIS 150

Part number 6 99 02 000 14 9



EYE PROTECTION

 No. in pack
 Part number

 3
 3 90 00 000 18 4

ACCESSORIES FOR GRIT GIR



CONTACT ROLLER

Long service lives, low roll resistance thanks to high-quality ball bearings, easy to interchange

Ø	Width	
mm	mm	Part number
16	150	6 99 02 188 00 0
18	150	6 99 02 189 00 0
19	150	6 99 02 190 00 0
19,1	150	6 99 02 191 00 0
20	150	6 99 02 101 00 0
21	150	6 99 02 192 00 0
21,3	150	6 99 02 193 00 0
22	150	6 99 02 102 00 0
22,3	150	6 99 02 194 00 0
23	150	6 99 02 195 00 0
23,2	150	6 99 02 196 00 0
24,3	150	6 99 02 197 00 0
25	150	6 99 02 103 00 0
25,4	150	6 99 02 104 00 0
26,1	150	6 99 02 198 00 0
26,7	150	6 99 02 199 00 0
26,9	150	6 99 02 105 00 0
27	150	6 99 02 200 00 0
28	150	6 99 02 106 00 0
28,3	150	6 99 02 201 00 0
-	150	6 99 02 202 00 0
28,6	150	6 99 02 202 00 0
29,2 30	150	6 99 02 203 00 0
31,1	150	6 99 02 204 00 0
31,5	150	6 99 02 205 00 0
31,8	150	6 99 02 206 00 0
32	150	6 99 02 108 00 0
33	150	6 99 02 207 00 0
33,4	150	6 99 02 208 00 0
33,7	150	6 99 02 109 00 0
34	150	6 99 02 209 00 0
35	150	6 99 02 110 00 0
37,4	150	6 99 02 210 00 0
38	150	6 99 02 111 00 0
38,1	150	6 99 02 112 00 0
38,3	150	6 99 02 113 00 0
39,8	150	6 99 02 211 00 0
40	150	6 99 02 114 00 0
40,1	150	6 99 02 212 00 0
41,3	150	6 99 02 213 00 0
42	150	6 99 02 214 00 0
42,1	150	6 99 02 215 00 0
42,2	150	6 99 02 216 00 0
42,4	150	6 99 02 115 00 0
43	150	6 99 02 217 00 0
44,5	150	6 99 02 116 00 0
45	150	6 99 02 218 00 0
45,7	150	6 99 02 219 00 0
47,4	150	6 99 02 221 00 0
48	150	6 99 02 222 00 0
48,3	150	6 99 02 117 00 0
49	150	6 99 02 223 00 0
50	150	6 99 02 118 00 0
50,1	150	6 99 02 224 00 0
50,8	150	6 99 02 119 00 0
51	150	6 99 02 225 00 0
		0 33 02 223 00 0

Ø	Width	
mm	mm	Part number
53	150	6 99 02 226 00 0
54	150	6 99 02 229 00 0
55	150	6 99 02 230 00 0
57	150	6 99 02 231 00 0
57,8	150	6 99 02 232 00 0
58	150	6 99 02 233 00 0
59,5	150	6 99 02 234 00 0
60	150	6 99 02 120 00 0
60,3	150	6 99 02 121 00 0
62	150	6 99 02 235 00 0
63	150	6 99 02 236 00 0
63,5	150	6 99 02 122 00 0
64,2	150	6 99 02 237 00 0
65	150	6 99 02 238 00 0
66	150	6 99 02 239 00 0
66,3	150	6 99 02 240 00 0
66,7	150	6 99 02 241 00 0
67,1	150	6 99 02 242 00 0
68,9	150	6 99 02 332 00 0
69	150	6 99 02 123 00 0
69,9	150	6 99 02 243 00 0
70	150	6 99 02 244 00 0
73	150	6 99 02 245 00 0
73,8	150	6 99 02 246 00 0
75	150	6 99 02 247 00 0
75,1	150	6 99 02 248 00 0
76	150	6 99 02 249 00 0
76,2	150	6 99 02 125 00 0
78	150	6 99 02 250 00 0
79,4	150	
		6 99 02 251 00 0
79,8	150	6 99 02 252 00 0
80	150	6 99 02 253 00 0
81	150	6 99 02 255 00 0
82	150	6 99 02 256 00 0
82,1	150	6 99 02 257 00 0
82,5	150	6 99 02 258 00 0
83	150	6 99 02 259 00 0
84	150	6 99 02 126 00 0
84,1	150	6 99 02 260 00 0
85	150	6 99 02 261 00 0
86,7	150	6 99 02 262 00 0
87	150	6 99 02 263 00 0
88	150	6 99 02 264 00 0
88,9	150	6 99 02 127 00 0
89	150	6 99 02 265 00 0
89,3	150	6 99 02 266 00 0
89,9	150	6 99 02 267 00 0
90	150	6 99 02 268 00 0
92	150	6 99 02 269 00 0
93,2	150	6 99 02 227 00 0
100	150	6 99 02 271 00 0
100,5	150	6 99 02 272 00 0
101	150	6 99 02 273 00 0
101,3	150	6 99 02 274 00 0
101,6	150	6 99 02 128 00 0
102	150	6 99 02 275 00 0
102,5	150	6 99 02 276 00 0
102,6	150	6 99 02 277 00 0
104	150	6 99 02 129 00 0
105	150	6 99 02 278 00 0
106,7	150	6 99 02 279 00 0
107	150	6 99 02 228 00 0
10/	100	3 33 02 220 00 0

mm mm Part number 108 150 6 99 02 130 00 0 114 150 6 99 02 282 00 0 114,3 150 6 99 02 131 00 0 115 150 6 99 02 283 00 0 117 150 6 99 02 285 00 0 118 150 6 99 02 286 00 0 118.2 150 6 99 02 286 00 0 120 150 6 99 02 288 00 0 121 150 6 99 02 288 00 0 122 150 6 99 02 289 00 0 124 150 6 99 02 299 00 0 125 150 6 99 02 291 00 0 127 150 6 99 02 292 00 0 127,5 150 6 99 02 292 00 0 127,5 150 6 99 02 295 00 0 128 150 6 99 02 295 00 0 129 150 6 99 02 295 00 0 130 150 6 99 02 295 00 0 133 150 6 99 02 295 00 0 134 150 6 99 02 295 00 0 138 150 <th>Ø</th> <th>Width</th> <th></th>	Ø	Width	
114 150 6 99 02 282 00 0 114,3 150 6 99 02 131 00 0 115 150 6 99 02 283 00 0 117 150 6 99 02 284 00 0 118 150 6 99 02 285 00 0 118.2 150 6 99 02 286 00 0 120 150 6 99 02 287 00 0 121 150 6 99 02 288 00 0 122 150 6 99 02 289 00 0 124 150 6 99 02 291 00 0 125 150 6 99 02 291 00 0 127 150 6 99 02 291 00 0 127,5 150 6 99 02 293 00 0 128 150 6 99 02 293 00 0 129 150 6 99 02 295 00 0 130 150 6 99 02 295 00 0 133 150 6 99 02 295 00 0 133 150 6 99 02 299 00 0 134 150 6 99 02 299 00 0 135 150 6 99 02 299 00 0 138 150 6 99 02 230 00 0 144,3 <td< td=""><td>-</td><td></td><td>Part number</td></td<>	-		Part number
114,3 150 6 99 02 131 00 0 115 150 6 99 02 283 00 0 117 150 6 99 02 284 00 0 118 150 6 99 02 285 00 0 118,2 150 6 99 02 286 00 0 120 150 6 99 02 287 00 0 121 150 6 99 02 289 00 0 122 150 6 99 02 289 00 0 124 150 6 99 02 290 00 0 125 150 6 99 02 291 00 0 127 150 6 99 02 292 00 0 127,5 150 6 99 02 293 00 0 128 150 6 99 02 293 00 0 129 150 6 99 02 295 00 0 130 150 6 99 02 295 00 0 133 150 6 99 02 295 00 0 134 150 6 99 02 295 00 0 135 150 6 99 02 299 00 0 137 150 6 99 02 299 00 0 139 150 6 99 02 299 00 0 139,7 150 6 99 02 300 00 0 141,3 <	108	150	6 99 02 130 00 0
115 150 6 99 02 283 00 0 117 150 6 99 02 284 00 0 118 150 6 99 02 285 00 0 118,2 150 6 99 02 286 00 0 120 150 6 99 02 287 00 0 121 150 6 99 02 288 00 0 122 150 6 99 02 289 00 0 124 150 6 99 02 290 00 0 125 150 6 99 02 292 00 0 127 150 6 99 02 293 00 0 128 150 6 99 02 293 00 0 129 150 6 99 02 295 00 0 130 150 6 99 02 295 00 0 133 150 6 99 02 296 00 0 133 150 6 99 02 299 00 0 134 150 6 99 02 299 00 0 135 150 6 99 02 299 00 0 139 150 6 99 02 299 00 0 1397 150 6 99 02 299 00 0 140 150 6 99 02 300 00 0 141,3 150 6 99 02 300 00 0 144,2	114	150	6 99 02 282 00 0
117 150 6 99 02 284 00 0 118 150 6 99 02 285 00 0 118.2 150 6 99 02 286 00 0 120 150 6 99 02 287 00 0 121 150 6 99 02 288 00 0 122 150 6 99 02 289 00 0 124 150 6 99 02 291 00 0 125 150 6 99 02 292 00 0 127 150 6 99 02 293 00 0 128 150 6 99 02 293 00 0 129 150 6 99 02 295 00 0 130 150 6 99 02 295 00 0 133 150 6 99 02 296 00 0 133 150 6 99 02 299 00 0 138 150 6 99 02 299 00 0 138 150 6 99 02 299 00 0 139 150 6 99 02 299 00 0 140 150 6 99 02 299 00 0 141,3 150 6 99 02 300 00 0 144,2 150 6 99 02 300 00 0 152 150 6 99 02 305 00 0 154 150 6 99 02 305 00 0 152 150 6 99 02 300 0	114,3	150	6 99 02 131 00 0
118 150 6 99 02 285 00 0 118,2 150 6 99 02 286 00 0 120 150 6 99 02 287 00 0 121 150 6 99 02 288 00 0 122 150 6 99 02 289 00 0 124 150 6 99 02 291 00 0 125 150 6 99 02 291 00 0 127 150 6 99 02 292 00 0 127,5 150 6 99 02 293 00 0 128 150 6 99 02 295 00 0 129 150 6 99 02 295 00 0 130 150 6 99 02 295 00 0 133 150 6 99 02 296 00 0 133 150 6 99 02 297 00 0 138 150 6 99 02 299 00 0 139 150 6 99 02 299 00 0 140 150 6 99 02 299 00 0 141,3 150 6 99 02 300 00 0 141,3 150 6 99 02 300 00 0 144,2 150 6 99 02 300 00 0 152 150 6 99 02 300 00 0 154 <	115	150	6 99 02 283 00 0
118,2 150 6 99 02 286 00 0 120 150 6 99 02 287 00 0 121 150 6 99 02 288 00 0 122 150 6 99 02 289 00 0 124 150 6 99 02 290 00 0 125 150 6 99 02 291 00 0 127 150 6 99 02 292 00 0 127,5 150 6 99 02 293 00 0 128 150 6 99 02 294 00 0 129 150 6 99 02 295 00 0 130 150 6 99 02 295 00 0 133 150 6 99 02 296 00 0 133 150 6 99 02 297 00 0 138 150 6 99 02 297 00 0 138 150 6 99 02 299 00 0 139 150 6 99 02 299 00 0 139,7 150 6 99 02 299 00 0 141,3 150 6 99 02 300 00 0 141,9 150 6 99 02 300 00 0 144,2 150 6 99 02 305 00 0 150 6 99 02 305 00 0 152 150 6 99 02 305 00 0 154 150 6 99 02 300 00 0	117	150	6 99 02 284 00 0
120 150 6 99 02 287 00 0 121 150 6 99 02 288 00 0 122 150 6 99 02 289 00 0 124 150 6 99 02 290 00 0 125 150 6 99 02 291 00 0 127 150 6 99 02 292 00 0 127,5 150 6 99 02 293 00 0 128 150 6 99 02 294 00 0 129 150 6 99 02 295 00 0 130 150 6 99 02 296 00 0 133 150 6 99 02 296 00 0 135 150 6 99 02 297 00 0 138 150 6 99 02 297 00 0 139 150 6 99 02 299 00 0 139,7 150 6 99 02 299 00 0 140 150 6 99 02 133 00 0 141,3 150 6 99 02 300 00 0 144,2 150 6 99 02 300 00 0 150 6 99 02 305 00 0 152 150 6 99 02 305 00 0 154 150 6 99 02 308 00 0 152 150 6 99 02 308 00 0 154 150 6 99 02 308 00 0 <td>118</td> <td>150</td> <td>6 99 02 285 00 0</td>	118	150	6 99 02 285 00 0
121 150 6 99 02 288 00 0 122 150 6 99 02 289 00 0 124 150 6 99 02 290 00 0 125 150 6 99 02 291 00 0 127 150 6 99 02 292 00 0 127,5 150 6 99 02 293 00 0 128 150 6 99 02 294 00 0 129 150 6 99 02 295 00 0 130 150 6 99 02 132 00 0 133 150 6 99 02 132 00 0 138 150 6 99 02 298 00 0 139 150 6 99 02 299 00 0 139,7 150 6 99 02 299 00 0 141,3 150 6 99 02 133 00 0 141,3 150 6 99 02 300 00 0 144,2 150 6 99 02 305 00 0 150 150 6 99 02 305 00 0 152 150 6 99 02 305 00 0 154 150 6 99 02 305 00 0 152,4 150 6 99 02 308 00 0 159 150 6 99 02 300 00 0 165 150 6 99 02 310 00 0 165 150 6 99 02	118,2	150	6 99 02 286 00 0
122 150 6 99 02 289 00 0 124 150 6 99 02 290 00 0 125 150 6 99 02 291 00 0 127 150 6 99 02 293 00 0 127,5 150 6 99 02 294 00 0 128 150 6 99 02 294 00 0 129 150 6 99 02 295 00 0 130 150 6 99 02 132 00 0 133 150 6 99 02 132 00 0 138 150 6 99 02 297 00 0 139 150 6 99 02 299 00 0 139,7 150 6 99 02 133 00 0 140 150 6 99 02 300 00 0 141,3 150 6 99 02 300 00 0 144,2 150 6 99 02 300 00 0 144,2 150 6 99 02 305 00 0 152 150 6 99 02 305 00 0 152,4 150 6 99 02 308 00 0 159 150 6 99 02 310 00 0 165 150 6 99 02 310 00 0 165 150 6 99 02 310 00 0 165 150 6 99 02 310 00 0 166 150 6 99 02	120	150	6 99 02 287 00 0
124 150 6 99 02 290 00 0 125 150 6 99 02 291 00 0 127 150 6 99 02 292 00 0 127,5 150 6 99 02 294 00 0 128 150 6 99 02 294 00 0 129 150 6 99 02 295 00 0 130 150 6 99 02 132 00 0 133 150 6 99 02 132 00 0 138 150 6 99 02 297 00 0 138 150 6 99 02 299 00 0 139,7 150 6 99 02 299 00 0 140 150 6 99 02 133 00 0 141,3 150 6 99 02 300 00 0 144,2 150 6 99 02 300 00 0 144,2 150 6 99 02 305 00 0 152 150 6 99 02 305 00 0 152,4 150 6 99 02 308 00 0 159 150 6 99 02 310 00 0 165 150 6 99 02 310 00 0 165 150 6 99 02 310 00 0 166 150 6 99 02 310 00 0 168 150 6 99 02 310 00 0 168 150 6 99 02	121	150	6 99 02 288 00 0
125 150 6 99 02 291 00 0 127 150 6 99 02 292 00 0 127,5 150 6 99 02 293 00 0 128 150 6 99 02 294 00 0 129 150 6 99 02 295 00 0 130 150 6 99 02 296 00 0 133 150 6 99 02 132 00 0 138 150 6 99 02 297 00 0 139 150 6 99 02 299 00 0 139,7 150 6 99 02 133 00 0 140 150 6 99 02 300 00 0 141,3 150 6 99 02 300 00 0 141,9 150 6 99 02 300 00 0 144,2 150 6 99 02 305 00 0 152 150 6 99 02 305 00 0 152 150 6 99 02 308 00 0 152,4 150 6 99 02 308 00 0 159 150 6 99 02 310 00 0 160 150 6 99 02 310 00 0 165 150 6 99 02 310 00 0 165 150 6 99 02 310 00 0 165	122	150	6 99 02 289 00 0
127 150 6 99 02 292 00 0 127,5 150 6 99 02 293 00 0 128 150 6 99 02 294 00 0 129 150 6 99 02 296 00 0 130 150 6 99 02 296 00 0 133 150 6 99 02 132 00 0 138 150 6 99 02 298 00 0 139 150 6 99 02 299 00 0 139,7 150 6 99 02 133 00 0 140 150 6 99 02 300 00 0 141,3 150 6 99 02 300 00 0 141,9 150 6 99 02 302 00 0 144,2 150 6 99 02 305 00 0 152 150 6 99 02 305 00 0 152,4 150 6 99 02 308 00 0 159 150 6 99 02 308 00 0 159 150 6 99 02 310 00 0 165 150 6 99 02 310 00 0 165 150 6 99 02 310 00 0 166 150 6 99 02 310 00 0 167 150 6 99 02 310 00 0 168	124	150	6 99 02 290 00 0
127,5 150 6 99 02 293 00 0 128 150 6 99 02 294 00 0 129 150 6 99 02 296 00 0 130 150 6 99 02 296 00 0 133 150 6 99 02 132 00 0 135 150 6 99 02 297 00 0 138 150 6 99 02 299 00 0 139 150 6 99 02 299 00 0 139,7 150 6 99 02 133 00 0 140 150 6 99 02 300 00 0 141,3 150 6 99 02 300 00 0 141,9 150 6 99 02 302 00 0 144,2 150 6 99 02 303 00 0 150 6 99 02 305 00 0 152,4 150 6 99 02 306 00 0 152,4 150 6 99 02 308 00 0 159 150 6 99 02 309 00 0 160 150 6 99 02 310 00 0 165 150 6 99 02 310 00 0 165 150 6 99 02 310 00 0 165 150 6 99 02 310 00 0 166 99 02 312 00 0	125	150	6 99 02 291 00 0
128 150 6 99 02 294 00 0 129 150 6 99 02 295 00 0 130 150 6 99 02 296 00 0 133 150 6 99 02 132 00 0 135 150 6 99 02 297 00 0 138 150 6 99 02 298 00 0 139 150 6 99 02 299 00 0 139,7 150 6 99 02 133 00 0 140 150 6 99 02 300 00 0 141,3 150 6 99 02 301 00 0 141,9 150 6 99 02 302 00 0 144,2 150 6 99 02 303 00 0 150 6 99 02 305 00 0 152 150 6 99 02 305 00 0 152,4 150 6 99 02 306 00 0 152,4 150 6 99 02 309 00 0 159 150 6 99 02 309 00 0 160 150 6 99 02 310 00 0 165 150 6 99 02 310 00 0 165 150 6 99 02 310 00 0 168 150 6 99 02 314 00 0 168,3 150 6 99 02 314 00 0	127	150	6 99 02 292 00 0
129 150 6 99 02 295 00 0 130 150 6 99 02 296 00 0 133 150 6 99 02 132 00 0 135 150 6 99 02 297 00 0 138 150 6 99 02 298 00 0 139 150 6 99 02 299 00 0 139,7 150 6 99 02 133 00 0 140 150 6 99 02 300 00 0 141,3 150 6 99 02 301 00 0 141,9 150 6 99 02 302 00 0 144,2 150 6 99 02 303 00 0 150 6 99 02 305 00 0 152 150 6 99 02 305 00 0 152,4 150 6 99 02 306 00 0 154 150 6 99 02 308 00 0 159 150 6 99 02 309 00 0 160 150 6 99 02 310 00 0 165 150 6 99 02 310 00 0 165 150 6 99 02 312 00 0 168 150 6 99 02 314 00 0 168,3 150 6 99 02 314 00 0	127,5	150	6 99 02 293 00 0
130 150 6 99 02 296 00 0 133 150 6 99 02 132 00 0 135 150 6 99 02 297 00 0 138 150 6 99 02 298 00 0 139 150 6 99 02 299 00 0 139,7 150 6 99 02 133 00 0 140 150 6 99 02 300 00 0 141,3 150 6 99 02 301 00 0 141,9 150 6 99 02 302 00 0 144,2 150 6 99 02 303 00 0 150 6 99 02 305 00 0 152 150 6 99 02 305 00 0 152,4 150 6 99 02 306 00 0 154 150 6 99 02 308 00 0 159 150 6 99 02 309 00 0 160 150 6 99 02 310 00 0 165 150 6 99 02 310 00 0 165 150 6 99 02 312 00 0 165,1 150 6 99 02 314 00 0 168 150 6 99 02 314 00 0	128	150	6 99 02 294 00 0
133 150 6 99 02 132 00 0 135 150 6 99 02 297 00 0 138 150 6 99 02 299 00 0 139 150 6 99 02 299 00 0 139,7 150 6 99 02 133 00 0 140 150 6 99 02 300 00 0 141,3 150 6 99 02 301 00 0 141,9 150 6 99 02 302 00 0 144,2 150 6 99 02 303 00 0 150 150 6 99 02 305 00 0 152 150 6 99 02 306 00 0 152,4 150 6 99 02 306 00 0 154 150 6 99 02 308 00 0 159 150 6 99 02 309 00 0 160 150 6 99 02 310 00 0 165 150 6 99 02 310 00 0 165 150 6 99 02 312 00 0 165,1 150 6 99 02 314 00 0 168 150 6 99 02 314 00 0 168,3 150 6 99 02 134 00 0	129	150	6 99 02 295 00 0
135 150 6 99 02 297 00 0 138 150 6 99 02 298 00 0 139 150 6 99 02 299 00 0 139,7 150 6 99 02 133 00 0 140 150 6 99 02 300 00 0 141,3 150 6 99 02 301 00 0 141,9 150 6 99 02 302 00 0 144,2 150 6 99 02 303 00 0 150 150 6 99 02 305 00 0 152 150 6 99 02 306 00 0 152,4 150 6 99 02 306 00 0 154 150 6 99 02 308 00 0 159 150 6 99 02 309 00 0 160 150 6 99 02 310 00 0 165 150 6 99 02 310 00 0 165 150 6 99 02 312 00 0 165,1 150 6 99 02 314 00 0 168 150 6 99 02 314 00 0 168,3 150 6 99 02 134 00 0	130	150	6 99 02 296 00 0
138 150 6 99 02 298 00 0 139 150 6 99 02 299 00 0 139,7 150 6 99 02 133 00 0 140 150 6 99 02 300 00 0 141,3 150 6 99 02 301 00 0 141,9 150 6 99 02 302 00 0 144,2 150 6 99 02 303 00 0 150 150 6 99 02 305 00 0 152 150 6 99 02 306 00 0 152,4 150 6 99 02 306 00 0 154 150 6 99 02 308 00 0 159 150 6 99 02 309 00 0 160 150 6 99 02 310 00 0 165 150 6 99 02 312 00 0 165,1 150 6 99 02 313 00 0 168 150 6 99 02 314 00 0 168,3 150 6 99 02 134 00 0	133	150	6 99 02 132 00 0
139 150 6 99 02 299 00 0 139,7 150 6 99 02 133 00 0 140 150 6 99 02 300 00 0 141,3 150 6 99 02 301 00 0 141,9 150 6 99 02 302 00 0 144,2 150 6 99 02 303 00 0 150 150 6 99 02 305 00 0 152 150 6 99 02 306 00 0 152,4 150 6 99 02 155 00 0 154 150 6 99 02 308 00 0 159 150 6 99 02 309 00 0 160 150 6 99 02 310 00 0 165 150 6 99 02 312 00 0 165,1 150 6 99 02 313 00 0 168 150 6 99 02 314 00 0 168,3 150 6 99 02 134 00 0	135	150	6 99 02 297 00 0
139,7 150 6 99 02 133 00 0 140 150 6 99 02 300 00 0 141,3 150 6 99 02 301 00 0 141,9 150 6 99 02 302 00 0 144,2 150 6 99 02 303 00 0 150 150 6 99 02 305 00 0 152 150 6 99 02 306 00 0 152,4 150 6 99 02 155 00 0 154 150 6 99 02 308 00 0 159 150 6 99 02 309 00 0 160 150 6 99 02 310 00 0 165 150 6 99 02 312 00 0 165,1 150 6 99 02 314 00 0 168 150 6 99 02 314 00 0	138	150	6 99 02 298 00 0
140 150 6 99 02 300 00 0 141,3 150 6 99 02 301 00 0 141,9 150 6 99 02 302 00 0 144,2 150 6 99 02 303 00 0 150 150 6 99 02 305 00 0 152 150 6 99 02 306 00 0 152,4 150 6 99 02 155 00 0 154 150 6 99 02 308 00 0 159 150 6 99 02 309 00 0 160 150 6 99 02 310 00 0 165 150 6 99 02 312 00 0 165,1 150 6 99 02 313 00 0 168 150 6 99 02 314 00 0 168,3 150 6 99 02 134 00 0	139	150	6 99 02 299 00 0
141,3 150 6 99 02 301 00 0 141,9 150 6 99 02 302 00 0 144,2 150 6 99 02 303 00 0 150 150 6 99 02 305 00 0 152 150 6 99 02 306 00 0 152,4 150 6 99 02 155 00 0 154 150 6 99 02 308 00 0 159 150 6 99 02 309 00 0 160 150 6 99 02 310 00 0 165 150 6 99 02 312 00 0 165,1 150 6 99 02 313 00 0 168 150 6 99 02 314 00 0 168,3 150 6 99 02 134 00 0	139,7	150	6 99 02 133 00 0
141,9 150 6 99 02 302 00 0 144,2 150 6 99 02 303 00 0 150 150 6 99 02 305 00 0 152 150 6 99 02 306 00 0 152,4 150 6 99 02 155 00 0 154 150 6 99 02 308 00 0 159 150 6 99 02 309 00 0 160 150 6 99 02 310 00 0 165 150 6 99 02 312 00 0 165,1 150 6 99 02 313 00 0 168 150 6 99 02 314 00 0 168,3 150 6 99 02 134 00 0	140	150	6 99 02 300 00 0
144,2 150 6 99 02 303 00 0 150 150 6 99 02 305 00 0 152 150 6 99 02 306 00 0 152,4 150 6 99 02 155 00 0 154 150 6 99 02 308 00 0 159 150 6 99 02 309 00 0 160 150 6 99 02 310 00 0 165 150 6 99 02 312 00 0 165,1 150 6 99 02 313 00 0 168 150 6 99 02 314 00 0 168,3 150 6 99 02 134 00 0	141,3	150	6 99 02 301 00 0
150 150 6 99 02 305 00 0 152 150 6 99 02 306 00 0 152,4 150 6 99 02 155 00 0 154 150 6 99 02 308 00 0 159 150 6 99 02 309 00 0 160 150 6 99 02 310 00 0 165 150 6 99 02 312 00 0 165,1 150 6 99 02 313 00 0 168 150 6 99 02 314 00 0 168,3 150 6 99 02 134 00 0	141,9	150	6 99 02 302 00 0
152 150 6 99 02 306 00 0 152,4 150 6 99 02 155 00 0 154 150 6 99 02 308 00 0 159 150 6 99 02 309 00 0 160 150 6 99 02 310 00 0 165 150 6 99 02 312 00 0 165,1 150 6 99 02 313 00 0 168 150 6 99 02 314 00 0 168,3 150 6 99 02 134 00 0	144,2	150	6 99 02 303 00 0
152,4 150 6 99 02 155 00 0 154 150 6 99 02 308 00 0 159 150 6 99 02 309 00 0 160 150 6 99 02 310 00 0 165 150 6 99 02 312 00 0 165,1 150 6 99 02 313 00 0 168 150 6 99 02 314 00 0 168,3 150 6 99 02 134 00 0	150	150	6 99 02 305 00 0
154 150 6 99 02 308 00 0 159 150 6 99 02 309 00 0 160 150 6 99 02 310 00 0 165 150 6 99 02 312 00 0 165,1 150 6 99 02 313 00 0 168 150 6 99 02 314 00 0 168,3 150 6 99 02 134 00 0	152	150	6 99 02 306 00 0
159 150 6 99 02 309 00 0 160 150 6 99 02 310 00 0 165 150 6 99 02 312 00 0 165,1 150 6 99 02 313 00 0 168 150 6 99 02 314 00 0 168,3 150 6 99 02 134 00 0	152,4	150	6 99 02 155 00 0
160 150 6 99 02 310 00 0 165 150 6 99 02 312 00 0 165,1 150 6 99 02 313 00 0 168 150 6 99 02 314 00 0 168,3 150 6 99 02 134 00 0	154	150	6 99 02 308 00 0
165 150 6 99 02 312 00 0 165,1 150 6 99 02 313 00 0 168 150 6 99 02 314 00 0 168,3 150 6 99 02 134 00 0	159	150	6 99 02 309 00 0
165,1 150 6 99 02 313 00 0 168 150 6 99 02 314 00 0 168,3 150 6 99 02 134 00 0	160	150	6 99 02 310 00 0
168 150 6 99 02 314 00 0 168,3 150 6 99 02 134 00 0	165	150	6 99 02 312 00 0
168,3 150 6 99 02 134 00 0	165,1	150	6 99 02 313 00 0
	168	150	6 99 02 314 00 0
193,7 150 6 99 02 000 18 7	168,3	150	6 99 02 134 00 0
	193,7	150	6 99 02 000 18 7

EYE PROTECTION



No. in pack pcs Part number 3 90 00 000 18 4



ADAPTORFor optimum extraction, for connection to the machine base GRIT GIBE with double extraction.

Part number 6 99 02 182 00 0

10 BELT GRINDERS

ACCESSORIES FOR GRIT GIE



STEEL WIRE BRUSH

 \emptyset 250 mm x 60 mm, with very high wire drawing strength for highly efficient use, mounting hole \emptyset 51 mm. 0.2 mm thick wire for thin-walled pipes and profiles. 0.35 mm-thick wire for universal use. 0.5 mm thick wire for thick-walled pipes and profiles and great deburring results. Steel version

Wire	thic	kness

mm	Part number
0,2	6 99 02 006 00 0
0,35	6 99 02 007 00 0
0,5	6 99 02 008 00 0



STEEL WIRE BRUSH

Ø 250 mm x 60 mm, with very high wire drawing strength for highly efficient use, mounting hole Ø 51 mm. 0.2 mm thick wire for thin-walled pipes and profiles. 0.35 mm-thick wire for universal use. 0.5 mm thick wire for thick-walled pipes and profiles and great deburring results. Stainless steel version

Wire	thic	kness
VVIIC	CITIC	KIICSS

111111	T di Cildilibei
0,2	6 99 02 009 00 0
0,35	6 99 02 010 00 0



EYE PROTECTION GU75/GR/GXR (3 PIECES)

Part number 3 90 00 000 00 7



CASSETTE FILTER

Suitable for GRIT GIBE.

Part number 3 90 00 000 97 6



METAL FILTER

Suitable for GRIT GIBE.

Part number 3 90 00 000 10 0



STAINLESS STEEL SANDING SUPPORT

GIE

Part number 3 90 00 009 92 3

GRIT GIC ACCESSORIES



PIPE SUPPORT

Ø 10-160 mm

Can be combined with one another depending on the pipe length desired.

max. pipe length

 mm
 Part number

 1,000
 6 99 02 180 60 0



PIPE SUPPORT

Ø 10-160 mm

Can be combined with one another depending on the pipe length desired.

-49	K.	
max.	pipe	lenath

Part number 6 99 02 181 60 0

1,500

mm

PIPE CLEANING UNIT

For a clean and dry working environment. The coolant is wiped off the pipe surface without the pipe being scratched. For pipes with a diameter of between 10 and 130 mm. Easy to fit on GIC.

Part number

6 99 02 000 14 6



GUIDE RAIL, BRASS

For dry grinding and course material surfaces

Part number 3 90 00 000 49 6



NYLON GLIDE SUPPORT

For high surface quality

Part number 3 90 00 000 49 7



GRINDING/COOLING EMULSION

Concentrate, 10 l, mixing ratio 1:30, yields 300 l of ready-to-use cooling lubricant.

Part number 6 99 02 100 00 0

GRIT GIL ACCESSORIES



GRAPHITE PAD

As sliding base for surface grinding.

No. in pack

pcs Part number 4 3 90 00 004 76 0

OTHER ACCESSORIES GRIT GI



Flexible, for swarf extraction, 90 mm in diameter, 1 m long, steel, high level of heat resistance.

Part number

3 90 00 000 00 2



TUBE CLAMPSFor securing the flexible hose.

3 90 00 000 00 3



DUST CONTAINER

Plastic, to douse sparks, with handles on the sides, capacity about 15 l

Part number

3 90 00 000 38 5



DUST CONTAINER

For extinguishing sparks, metal lid for hose connection, plastic, handles on the sides, capacity approx. 20 l.

Part number

6 99 02 000 00 0

DRIVE WHEEL PULLER

Part number

6 99 02 410 00 0



SWIVEL JOINT GIT

For adapting working area to tight spaces, continuously variable swivel range of up to 90°.

Part number

6 99 02 176 00 0



PLUGBOX 2 X 7 POLES

Part number

6 99 02 183 00 0

GRIT GI 100 ACCESSORIES



GRAPHITE COATING

Part number 3 90 00 000 18 3



EYE PROTECTION

Acrylic screen for protection against sparks

No. in pack

Part number pcs 3 90 00 000 19 0









11 AMPShare BATTERIES



ProCORE 18 V 4.0 AH AS BATTERY PACK

ProCORE Li-Ion battery with high-power cells, charge status indicator and "Electronic Cell Protection" (ECP). ECP protects against overload, overheating and total discharge. The COOLPACK 2.0 technology ensures a 135 % longer battery life compared with batteries without COOLPACK technology and therefore makes long operating periods possible. Compatible with all 18 V cordless devices with AMPShare or Bosch Professional 18 V battery interface.

Current/Voltages	Capacity	Weight	
V	Ah	kg	Part number
18	4	0,52	9 26 04 341 02 0



ProCORE 18 V 8.0 AH AS BATTERY PACK

ProCORE Li-Ion battery with high-power cells, charge status indicator and "Electronic Cell Protection" (ECP). ECP protects against overload, overheating and total discharge. The COOLPACK 2.0 technology ensures a 135 % longer battery life compared with batteries without COOLPACK technology and therefore makes long operating periods possible. Compatible with all 18 V cordless devices with AMPShare or Bosch Professional 18 V battery interface.

Current/Voltages	Capacity	Weight	
V	Ah	kg	Part number
18	8	0,95	9 26 04 342 02 0



ProCORE 18 V 12.0 AH AS BATTERY PACK

ProCORE Li-lon battery with high-power cells, charge status indicator and "Electronic Cell Protection" (ECP). ECP protects against overload, overheating and total discharge. The COOLPACK 2.0 technology ensures a 135 % longer battery life compared with batteries without COOLPACK technology and therefore makes long operating periods possible. Compatible with all 18 V cordless devices with AMPShare or Bosch Professional 18 V battery interface.

Current/Voltages	Capacity	Weight	
V	Ah	kg	Part number
18	12	1,35	9 26 04 343 02 0



GBA 18 V 2.0 AH AS BATTERY PACK

Li-lon battery with charge status indicator and "Electronic Cell Protection" (ECP). ECP protects against overload, overheating and total discharge. The COOLPACK 1.0 technology ensures a longer battery life compared with batteries without COOLPACK technology and therefore makes long operating periods possible. Compatible with all 18 V cordless devices with AMPShare or Bosch Professional 18 V battery interface.

Current/Voltages	Capacity	Weight	
V	Ah	kg	Part number
18	2	0,35	9 26 04 344 02 0



GBA 18 V 4.0 AH AS BATTERY PACK

Li-lon battery with charge status indicator and "Electronic Cell Protection" (ECP). ECP protects against overload, overheating and total discharge. The COOLPACK 1.0 technology ensures a longer battery life compared with batteries without COOLPACK technology and therefore makes long operating periods possible. Compatible with all 18 V cordless devices with AMPShare or Bosch Professional 18 V battery interface.

Current/Voltages	Capacity	Weight	
V	Ah	kg	Part number
18	4	0,6	9 26 04 345 02 0



GBA 18 V 5.0 AH AS BATTERY PACK

Li-Ion battery with charge status indicator and "Electronic Cell Protection" (ECP). ECP protects against overload, overheating and total discharge. The COOLPACK 1.0 technology ensures a longer battery life compared with batteries without COOLPACK technology and therefore makes long operating periods possible. Compatible with all 18 V cordless devices with AMPShare or Bosch Professional 18 V battery interface.

Current/Voltages	Capacity	Weight	Part number
V	Ah	kg	
18	5	0,62	9 26 04 346 02 0



GBA 18 V 2.0 AH AS BATTERY STARTER SET

2 x Li-Ion batteries with GAL 1880 CV rapid charger. Short charge times thanks to the high charge current of 8 A, active air cooling and process-controlled charge management. User-friendly and space-saving thanks to fixture for coiling the mains cable. For all battery packs with AMPShare or Bosch Professional 18 V battery interface. Charge times (80 % of max. capacity): GBA 18 V 2.0 Ah: 15 min., GBA 18 V 4.0 Ah: 25 min., ProCORE 18 V 4.0 Ah: 32 min., ProCORE 18 V 8.0 Ah: 68 min., ProCORE 18 V 12.0 Ah: 113 min.

Current/Voltages	Capacity	
V	Ah	Part number
18	2	9 26 04 244 01 0



GBA 18 V 5.0 AH AS BATTERY STARTER SET

2 x Li-Ion batteries with GAL 1880 CV rapid charger. Short charge times thanks to the high charge current of 8 A, active air cooling and process-controlled charge management. User-friendly and space-saving thanks to fixture for coiling the mains cable. For all battery packs with AMPShare or Bosch Professional 18 V battery interface. Charge times (80 % of max. capacity): GBA 18 V 2.0 Ah: 15 min., GBA 18 V 4.0 Ah: 25 min., ProCORE 18 V 4.0 Ah: 32 min., ProCORE 18 V 8.0 Ah: 68 min., ProCORE 18 V 12.0 Ah: 113 min.

Current/Voltages	Capacity	5
V	An	Part number
18	5	9 26 04 246 01 0



ProCORE 18 V 4.0 AH AS BATTERY STARTER SET

2 x ProCORE Li-Ion batteries with high-power cells with GAL 1880 CV rapid charger. Short charge times thanks to the high charge current of 8 A, active air cooling and process-controlled charge management. User-friendly and space-saving thanks to fixture for coiling the mains cable. For all battery packs with AMPShare or Bosch Professional 18 V battery interface. Charge times (80 % of max. capacity): GBA 18 V 2.0 Ah: 15 min., GBA 18 V 4.0 Ah: 25 min., GBA 18 V 5.0 Ah: 35 min., ProCORE 18 V 4.0 Ah: 32 min., ProCORE 18 V 12.0 Ah: 113 min.

Current/Voltages	Capacity	
V	Ah	Part number
18	4	9 26 04 228 01 0



Procore 18 V 8.0 AH AS BATTERY STARTER SET

2 x ProCORE Li-Ion batteries with high-power cells with GAL 18 V-160 rapid charger. Short charge times thanks to the high charge current of 16 A, Power Boost charge mode, active air cooling and process-controlled charge management. With charge status indicator and fixture for mounting on wall. For all battery packs with AMPShare or Bosch Professional 18 V battery interface. Charge times (80 % of max. capacity): GBA 18 V 2.0 Ah: 15 min., GBA 18 V 4.0 Ah: 16 min., GBA 18 V 5.0 Ah: 20 min., ProCORE 18 V 4.0 Ah: 32 min., ProCORE 18 V 12.0 Ah: 36 min.

Current/Voltages	Capacity			
V	Ah	Part number		
18	8	9 26 04 229 01 0		



ProCORE 18 V 12.0 AH AS BATTERY STARTER SET

2 x ProCORE Li-Ion batteries with high-power cells with GAL 18 V-160 rapid charger. Short charge times thanks to the high charge current of 16 A, Power Boost charge mode, active air cooling and process-controlled charge management. With charge status indicator and fixture for mounting on wall. For all battery packs with AMPShare or Bosch Professional 18 V battery interface. Charge times (80 % of max. capacity): GBA 18 V 2.0 Ah: 15 min., GBA 18 V 4.0 Ah: 16 min., GBA 18 V 5.0 Ah: 20 min., ProCORE 18 V 4.0 Ah: 32 min., ProCORE 18 V 12.0 Ah: 36 min.

Current/Voltages	Capacity	
V	Ah	Part number
18	12	9 26 04 241 01 0



GAL 18 V-160 AS RAPID CHARGER

Short charge times thanks to the high charge current of 16 A, Power Boost charge mode, active air cooling and process-controlled charge management. With charge status indicator and fixture for mounting on wall. For all battery packs with AMPShare or Bosch Professional 18 V battery interface. Charge times (80 % of max. capacity): GBA 18 V 2.0 Ah: 15 min., GBA 18 V 4.0 Ah: 16 min., GBA 18 V 5.0 Ah: 20 min., ProCORE 18 V 4.0 Ah: 32 min., ProCORE 18 V 12.0 Ah: 36 min.

Part number

9 26 04 339 01 0



GAL 1880 CV AS RAPID CHARGER

Short charge times thanks to the high charge current of 8 A, active air cooling and process-controlled charge management. User-friendly and space-saving thanks to fixture for coiling the mains cable. For all battery packs with AMPShare or Bosch Professional 18 V battery interface. Charge times (80 % of max. capacity): GBA 18 V 2.0 Ah: 15 min., GBA 18 V 4.0 Ah: 25 min., GBA 18 V 5.0 Ah: 35 min., ProCORE 18 V 4.0 Ah: 32 min., ProCORE 18 V 8.0 Ah: 113 min.

Part number

9 26 04 335 01 0





280

Ideally equipped for every form of use. Mobile working with the L-BOXX system.



L-BOXX®

L-BOXX

BALANCERS

282

Balancers increase operating comfort and safety. For loads of 0.5 kg - 60 kg.



285

OTHER PRODUCTS



L-BOXX 136 FEIN L-BOXX 238 FEIN XL-BOXX FEIN i-BOXX 72 FEIN









The tool case with a modular concept. One system – countless possibilities.

Width	mm	445	445	607	367
Depth	mm	358	358	395	316
Height	mm	152	254	179	64
Tank volume	l	13	25,5	30	5,9
Weight	kg	2,2	2,8	3,2	0,9

FEIN BENEFITS

- Store tool and accessories tidily.
 Safe transport of tool and accessories.
 Patented click connection.
 Integration into the in-vehicle equipment systems of well-known manufacturers.

Part number	3 39 01 680 00 0	3 39 01 690 00 0	3 39 01 740 00 0	3 39 01 789 00 0
EAN	4014586464022	4014586464039	4014586466934	4014586473024

For accessories, see page 281

ACCESSORIES L-BOXX



FEIN i-BOXX RACK LID

Mobile shelving system. Compatible with the L-BOXX system.

Width	Depth	Height	Weight	
mm	mm	mm	kg	Part number
442	342	50	1	3 39 01 791 00 0



FEIN i-BOXX RACK, SINGLE

The rack is an individual shelf-like fitting for an i-BOXX or a drawer, which can be combined and extended in virtually any way imaginable.

Width	Depth	Height	Weight	
mm	mm	mm	kg	Part number
442	342	101	1,1	3 39 01 790 00 0



FEIN L-BOXX LID INSERT

Lid insert made from EPP rigid foam for FEIN L-BOXX 136,

238 etc.
Protects the content of the inset boxes or trays for small parts from being mixed up during transport.

Width	Depth	Height	Weight	
mm	mm	mm	kg	Part number
405	321	21	0,07	3 39 06 420 00 0



FEIN XL-BOXX LID INSERT

Lid insert made from EPP rigid foam for FEIN XL-BOXX Protects the content of the trays for small parts from being mixed up during transport.

Width	Depth	Height	Weight	
mm	mm	mm	kg	Part number
596	361	17	0,14	3 39 06 428 00 0



FEIN L-BOXX ROLLER

Mobile platform with 4 guide wheels, 2 of which can be locked using the integrated brake. All L-BOXXs in the system can be easily stacked with the roller.

Width	Depth	Height	Weight	
mm	mm	mm	kg	Part number
646	492	184	3,8	3 39 10 136 00 0

12 BALANCERS

BALANCER UP TO 1.5 KG



BALANCER UP TO 2.5 KG



Safe suspension of device and power line in "weightless" state.

Variable load	kg	0.5 - 1.5	1.5 - 2.5
Factory setting	kg	1	2
max. stroke	m	0,9	0,9
Model		Stable nylon cable	Stable nylon cable
Weight	kg	0,35	0,35

FEIN BENEFITS

- + Small size.

- + Small size.
 + Constant traction.
 + Easily adjustable.
 + Stable nylon cable.
 + Spiral cordset available as accessory

Part number	9 08 01 012 00 8	9 08 01 023 00 1
EAN	4014586835075	4014586835099

For accessories, see page 284

BALANCER UP TO 1.5 KG



BALANCER UP TO 2.5 KG



Safe suspension of device and power line in "weightless" state.

Variable load	kg	0.5 - 1.5	1.5 - 2.5
Factory setting	kg	1	2
max. stroke	m	0,9	0,9
Model		Wire cable	Wire cable
Weight	kg	0,35	0,35

FEIN BENEFITS

- + Constant traction.
- + Tear-resistant steel cable.
 + Spiral cordset available as accessory

Part number	9 08 01 052 00 4	9 08 01 037 00 9
EAN	4014586854052	4014586835228

For accessories, see page 284

BALANCER UP TO 3 KG BALANCER UP TO 5 KG BALANCER UP TO 6.5 KG



Safe suspension of device and power line in "weightless" state.

Variable load	kg	1 - 3	2.5 - 5	3.5 - 6.5	
Factory setting	kg	2	3,5	5	
max. stroke	m	2	2	2	
Model		Wire cable	Wire cable	Wire cable	
Weight	kg	3,2	3,2	3,2	


FEIN BENEFITS

- + Constant traction.
- + Tear-resistant steel cable.
- + Spiral cordset available as accessory

4014586835150

Part number	9 08 01 024 00 9	9 08 01 025 00 3	9 08 01 026 00 6
EAN	4014586835105	4014586835136	4014586835143

For accessories, see page 284



4014586835167

4014586835174

For accessories, see page 284

4014586835181

12 BALANCERS

BALANCER UP TO 25 KG



BALANCER UP TO 45 KG



BALANCER UP TO 60 KG



Safe suspension of device and power line in "weightless" state.

		·				
Variable load	kg	13 - 25	22 - 32	30 - 45	45 - 60	
Factory setting	kg	15	25	40	50	
max. stroke	m	1,9	1,9	1,9	1,9	
Model		Wire cable	Wire cable	Wire cable	Wire cable	
Weight	kg	11,2	11,5	12	12,4	

BALANCER

FEIN BENEFITS

- + Constant traction. + Tear-resistant steel cable.
- + Spiral cordset available as accessory

Part number	9 08 01 055 00 0	9 08 01 056 00 0	9 08 01 057 00 0	9 08 01 058 00 0
EAN	4014586880693	4014586880709	4014586880716	4014586880723

For accessories, see page 284

GENERAL ACCESSORIES



SPIRAL CORDSET

for electric tools with mains connection cables of quality HO 5 RN-F 2 \times 1.

Part number 3 07 07 157 03 5

BALANCER UP TO 60 KG



LOCKING DEVICE for locking the extended cable. eases the exchange of the hooked on tool.

Part number

3 02 40 239 01 4



SWIVEL HOOK

to hook on the rope eye. Prevents the rope from twisting.

Part number

3 02 32 044 01 0

AKP 18-600 AS

AMP Share



Powerful and flexible cordless sealant gun for rapid and precise application of sealing materials and adhesives of various viscosities and for filling gaps.

Battery voltage	V	18
Battery compatibility		Li-ion/ProCORE Li-ion
Battery interface		18 V AMPShare
Maximum compressive force	N	3 500
Capacity, cartridge	ml	310, 400
Capacity, foil pouch	ml	300, 400, 600
Feed speed	mm/sek	7
Width	mm	255
Length	mm	635
Height	mm	80
Weight without storage battery	kg	2,2

Part number	7 146 01 61 00 0
EAN	4014586897271

FEIN BENEFITS

- + With a maximum compressive force of 3500 N and a no-load feed of up to 7 mm/s, the powerful motor guarantees rapid work progress - even when working with particularly viscous materials.
- + It's never been so easy to work accurately: thanks to 9 speed settings, a manual trigger and a continuously variable ejection speed, the material flow can be regulated ideally in no time at all.
- The automatic return function (no drip function) allows the pressure to drop when the trigger is released and the gear rack to retract, thereby preventing the used material from dripping or escaping. Quick, tool-free switch between cartridges and plastic
- bags.
- Optimum utilisation of material as it is virtually all pressed out.
- Constant flow of sealant and reduced bubble formation.
- + Electronic Cell Protection (ECP): ECP protects against overload, overheating and total discharge.
- The COOLPACK technology ensures a longer battery life and therefore makes long operating periods
- The battery charge can be read off the battery.
- Compatible with AMPShare/Bosch Professional 18 V batteries.

GROUTING RENEWERS

AKP 18-600 AS SET FOR The perfect set for grouting renewers. Our powerful and flexible cordless sealant gun coupled with our best oscillating cordless MULTIMASTER together with a jumbo pack of universal cutter blades for virtually all expansion joints.



Battery voltage	V	18
Battery compatibility		Li-ion/ProCORE Li-ion
Battery interface		18 V AMPShare

Part number	7 190 22 60 00 0
FAN	4014586898636

For technical data relating to the cordless MULTIMASTER AMM 700 1.7 Q AS, see page 232

FEIN BENEFITS

- + 50 universal cutter blades with straight shape for virtually all expansion joints.
- Unbeatable saving on set compared with buying separately.

Cordless sealant gun AKP 18-600 AS:

- With a maximum compressive force of 3500 N and a no-load feed of up to 7 mm/s, the powerful motor guarantees rapid work progress - even when working with particularly viscous materials.
- It's never been so easy to work accurately: thanks to 9 speed settings, a manual trigger and a continuously variable ejection speed, the material flow can be regulated ideally in no time at all.
- The automatic return function (no drip function) allows the pressure to drop when the trigger is released and the gear rack to retract, thereby preventing the used material from dripping or escaping.

Cordless MULTIMASTER AMM 700 1.7 Q AS:

- Designed for cutting out windows and work on the car body.
- + Anti-vibration system: continuously safe and pleasant working thanks to minimal vibrations and outstanding noise insulation.
- QuickIN: tool changes in less than 3 seconds thanks to the patented tool-free FEIN rapid clamping system.

SUPPLIED

1 cordless MULTIMASTER AMM 700 1.7 Q AS, 1 cordless sealant gun AKP 18-600 AS, 50 cutter blades, 1 protective cover for tool changes

12 CORDLESS SEALANT GUN

AKP 18-600 AS TOP SET The perfect set for grouting renewers. Our powerful and flexible cordless sealant gun coupled with our best oscillating cordless **FOR GROUTING RENEWERS**



Battery voltage 18 Ah Battery capacity Li-ion/ProCORE Li-ion Battery compatibility Battery interface 18 V AMPShare

Part number	7 190 23 60 00 0
EAN	4014586898643

For technical data relating to the cordless MULTIMASTER AMM 700 1.7 Q AS, see page 232

included mean you can get started straight away.

FEIN BENEFITS

MULTIMASTER together with a jumbo pack of universal cutter blades for virtually all expansion joints. The batteries and charger

- 50 universal cutter blades with straight shape for virtually all expansion joints.
- Unbeatable saving on set compared with buying separately

Cordless sealant gun AKP 18-600 AS:

- With a maximum compressive force of 3500 N and a no-load feed of up to 7 mm/s, the powerful motor guarantees rapid work progress – even when working with particularly viscous materials.
- It's never been so easy to work accurately: thanks to 9 speed settings, a manual trigger and a continuously variable ejection speed, the material flow can be regulated ideally in no time at all.
- The automatic return function (no drip function) allows the pressure to drop when the trigger is released and the gear rack to retract, thereby preventing the used material from dripping or escaping.

 Cordless MULTIMASTER AMM 700 1.7 Q AS:

- Designed for cutting out windows and work on the car body.
- Anti-vibration system: continuously safe and pleasant working thanks to minimal vibrations and outstanding noise insulation.
- QuickIN: tool changes in less than 3 seconds thanks to the patented tool-free FEIN rapid clamping system.

SUPPLIED

1 cordless MULTIMASTER AMM 700 1.7 Q AS, 1 cordless sealant gun AKP 18-600 AS, 2 battery pack GBA 18 V 4.0 AH AS, 1 rapid charger GAL 1880 CV AS, 50 cutter blades, 1 protective cover for tool changes

VEHICLE GLAZIERS

AKP 18-600 AS SET FOR The perfect set for vehicle glaziers. Our powerful and flexible cordless sealant gun coupled with our best oscillating cordless MULTIMASTER for the automotive sector including an extensive set of accessories extensive for cutting out windows and work on the car body in a jumbo pack.



Battery voltage	V	18
Battery compatibility		Li-ion/ProCORE Li-ion
Battery interface		18 V AMPShare

Part number	7 190 24 60 00 0
EAN	4014586898681

For technical data relating to the cordless MULTIMASTER AMM 700 1.7 Q AS, see page 232

FEIN BENEFITS

Unbeatable saving on set compared with buying Cordless sealant gun AKP 18-600 AS:

- With a maximum compressive force of 3500 N and a no-load feed of up to 7 mm/s, the powerful motor guarantees rapid work progress - even when working with particularly viscous materials.
- It's never been so easy to work accurately: thanks to 9 speed settings, a manual trigger and a continuously variable ejection speed, the material flow can be regulated ideally in no time at all.
- The automatic return function (no drip function) allows the pressure to drop when the trigger is released and the gear rack to retract, thereby preventing the used material from dripping or escaping.

CORDLESS MULTIMASTER AMM 700 1.7 Q AUTOGLAS AS:

- Designed for cutting out windows and work on the car body.
- Anti-vibration system: continuously safe and pleasant working thanks to minimal vibrations and outstanding noise insulation.
- QuickIN: tool changes in less than 3 seconds thanks to the patented tool-free FEIN rapid clamping system.

SUPPLIED

1 cordless MULTIMASTER AMM 700 1.7 Q AS, 1 cordless sealant gun AKP 18-600 AS, 2 vehicle glazing accessory sets, 1 protective cover for tool changes

AKP 18-600 AS TOP SET The perfect set for vehicle glaziers. Our powerful and flexible cordless sealant gun coupled with our best oscillating cordless FOR VEHICLE GLAZIERS MULTIMASTER for the automotive sector including an extensive set of accessories extensive for cutting out windows and work on the car body in a jumbo pack. The batteries and charger included mean you can get started straight away.



Battery voltage	V	18
Battery capacity	Ah	4
Battery compatibility		Li-ion/ProCORE Li-ion
Battery interface		18 V AMPShare

Part number	7 190 25 60 00 0
EAN	4014586898698

For technical data relating to the cordless MULTIMASTER AMM 700 1.7 Q AS, see page 232

FEIN BENEFITS

+ Unbeatable saving on set compared with buying separately.

Cordless sealant gun AKP 18-600 AS:

- + With a maximum compressive force of 3500 N and a no-load feed of up to 7 mm/s, the powerful motor guarantees rapid work progress - even when working with particularly viscous materials.
- + It's never been so easy to work accurately: thanks to 9 speed settings, a manual trigger and a continuously variable ejection speed, the material flow can be regulated ideally in no time at all.
- + The automatic return function (no drip function) allows the pressure to drop when the trigger is released and the gear rack to retract, thereby preventing the used material from dripping or escaping.

CORDLESS MULTIMASTER AMM 700 1.7 Q AUTOGLAS AS:

- + Designed for cutting out windows and work on the car body.
- + Anti-vibration system: continuously safe and pleasant working thanks to minimal vibrations and outstanding noise insulation.
- + QuickIN: tool changes in less than 3 seconds thanks to the patented tool-free FEIN rapid clamping system.

SUPPLIED

1 cordless MULTIMASTER AMM 700 1.7 Q AS, 1 cordless sealant gun AKP 18-600 AS, 2 battery pack GBA 18 V 4.0 AH AS, 1 rapid charger GAL 1880 CV AS, 2 vehicle glazing accessory sets, 1 protective cover for tool changes

12 CORDLESS RADIO

ARAD 18 BC AS

AMP Share



SUPPLIED

1 power supply unit, 1 aux cable, 1 3 V CR2032 lithium button cell battery

Robust and mobile digital construction site radio with clear, unique sound and extreme flexibility to make work more enjoyable even in rough conditions.

No. of preset FM stations		8
No. of preset DAB+ stations		8
Battery voltage	V	18
Battery compatibility		Li-ion/ProCORE Li-ion
Battery interface		18 V AMPShare
Weight without storage battery	kg	2,5

Part number	9 26 04 204 01 0
EAN	4014586897288

FEIN BENEFITS

- Two 15 W loudspeakers with extra passive radiators ensure a clear, unique sound – and an optimum listening experience.
- Sounds good no matter where you are: four sources (DAB+, Bluetooth®, FM and AUX), operated using a battery or the mains power supply as well as fixtures for vertical and horizontal positioning ensure universal potential uses and allow for a good sound quality in every work location.
- Thanks to the robust and compact housing with IP 54 protection, impact, dirt, dust and moisture aren't an issue – and you are perfectly set up for use in extreme conditions, such as on the building site.
- Handle and hook for vertical and horizontal positioning.
- USB charging option.
- A smartphone can be used to connect two radios for stereo sound.
- ProCORE Li-lon battery with high-power cells, charge status indicator and "Electronic Cell Protection" (ECP). ECP protects against overload, overheating and total discharge. The COOLPACK 2.0 technology ensures a 135 % longer battery life compared with batteries without COOLPACK technology and therefore makes long operating periods possible. Compatible with all 18 V cordless devices with AMPShare or Bosch Professional 18 V battery interface.



BATTERY COVER

for protecting the work piece surface from mechanical damages for Li-Ion battery 18 V 3 Ah

Current/Voltages	Capacity	
V	Ah	Part number
18	3	3 21 74 020 01 0



BATTERY COVER

for protecting the work piece surface from mechanical damages

for Li-Ion battery 18 V 6 Ah

Current/Voltages V	Capacity Ah	Part number
18	6	3 21 74 019 01 0



PLASTIC BOX

Box insert with lockable lid for small parts and accessories, suitable for tool box 3 39 01 118 01 0, max 5 items/box.

Part number

3 39 01 119 00 0



CUTTING PASTE

Lubricating agents for working on sheet metals.

Part number
3 21 32 046 00 0



MAGBRUSH

Practical tool with high magnetic force for quick and easy collection of magnetic metal swarf.

Part number
6 42 01 005 01 0



WORK GLOVES

Vibration-attenuating, certified according to EN 388/420, EN ISO 10819, EEC No. 0200, No. in pack 1 pair.

Size	Part number
9 L	3 21 73 003 00 3
10 XL	3 21 73 004 00 1
11 XXL	3 21 73 005 00 5

18 V BATTERY



HIGHPOWER BATTERY PACK

HighPower Li-ion battery with cells capable of handling high currents, charge status indicator and FEIN SafetyCell technology. Continually high power output with 75 % higher current rating than a Li-ion battery. Recommended for FEIN cordless magnetic core drills and cordless angle grinders. Can be used with all FEIN 18 V cordless tools.

Current/Voltages	Capacity	Weight	
/	Ah	kg	Part number
18	5,2	0,75	9 26 04 179 02 0



BATTERY PACK

Li-ion battery with charge status indicator and FEIN SafetyCell technology. Protects the battery and tool from overload, overheating and total discharge. Can be used with all FEIN 18 V cordless tools.

Current/ Voltages V	Capacity Ah	No. in pack	Weight kg	Part number
18	3	12	0,45	9 26 04 182 03 0
18	3	1	0,45	9 26 04 182 02 0
18	6	1	0,7	9 26 04 175 02 0



BATTERY STARTER SET

 $2 \times \text{Li-ion}$ batteries with ALG 80 rapid charger. The high charge current of 8 amps and process-controlled charge management make for short charge times. Large LED with charge state indicator and USB port for the mobile charging of small electronic devices, such as smartphones or tablets. Charge times (80 % of max. capacity): 12 and 18 V / 3 Ah: 31 min., 12 and 18 V / 6 Ah: 38 min.

Current/Voltages	Capacity	
V	Ah	Part number
18	6	9 26 04 314 01 0
18	3	9 26 04 315 01 0



QUICK CHARGER ALG 80

The high charge current of 8 amps and process-controlled charge management make for short charge times. Large LED with charge state indicator and USB port for the mobile charging of small electronic devices, such as smartphones or tablets. For all FEIN Li-ion batteries. Charge times (80 % of max. capacity): 12 and 18 V / 3 Ah: 31 min., 12 and 18 V / 6 Ah: 38 min., 18 V / 5.2 Ah: 33 min.

No. in	pack
--------	------

pcs	Part number
1	9 26 04 180 01 0
25	9 26 04 180 02 0

NUMERICAL PART

ACCESSORIES IN **297 NUMERICAL ORDER**

VIBRATION AND NOISE EMISSION VALUES

346

Part number	EAN	Description	PC	Page
3 21 72 050 02 0	4014586461311	FEIN VersaMAG	01	190
3 39 01 680 00 0	4014586464022	L-BOXX 136 FEIN	02	280
3 39 01 680 01 0	4014586460956	L-BOXX 136 FEIN	02	
3 39 01 690 00 0	4014586464039	L-BOXX 238 FEIN	02	280
3 39 01 789 00 0	4014586473024	i-BOXX 72 FEIN	02	280
7 112 62 60 00 0	4014586883830	ASW 18-30 PC	05	95
7 112 63 60 00 0	4014586883847	ASW 18-45 PC	05	95
7 112 64 60 00 0	4014586883854	ASW 18-60 PC	05	95
7 112 66 60 00 0	4014586887920	ASW 18-6 PC	05	94
7 112 68 60 00 0	4014586887968	ASW 18-12 PC	05	94
7 112 70 60 00 0	4014586888002	ASW 18-18 PC	05	94
7 112 77 60 00 0	4014586891422	ASM 18-3 PC	05	93
7 112 78 60 00 0	4014586891446	ASM 18-8 PC	05	93
7 112 79 60 00 0	4014586891460	ASM 18-12 PC	05	93
7 113 11 63 00 0	4014586881461	ASCS 6.3 Select	01	97
7 113 22 64 00 0	4014586887203	ABS 18 Q Select	18	86
7 113 23 64 00 0	4014586887265	ASB 18 Q Select	18	86
7 115 06 64 00 0	4014586887425	ASCD 18-300 W2 Select	18	91
7 115 07 64 00 0	4014586887449	ASCD 18-200 W4 Select	18	91
7 115 08 64 00 0	4014586891651	ASCD 18-1000 W34 Select	18	91
7 116 11 64 00 0	4014586887340	ASCM 18 QM Select	18	85
7 116 12 64 00 0	4014586889900	ASCM 18 QSW Select	18	85
7 122 01 61 00 0	4014586898155	CCG 18-115-10 AS	01	114
7 122 02 61 00 0	4014586898162	CCG 18-125-10 AS	01	115
7 122 03 61 00 0	4014586898179	CCG 18-115-10 PD AS	01	114
7 122 04 61 00 0	4014586898186	CCG 18-125-10 PD AS	01	115
7 122 05 61 00 0	4014586896991	CCG 18-125-10 PD-SEC AS	01	113
7 122 05 62 00 0	4014586897011	CCG 18-125-10 PD-SEC Set 8 Ah ProCORE AS	01	113
7 122 06 61 00 0	4014586897059	CCG 18-115-10 PD-SEC AS	01	112
7 122 06 62 00 0	4014586897073	CCG 18-115-10 PD-SEC Set 8 Ah ProCORE AS	01	112
7 122 07 61 00 0	4014586897202	CCG 18-125-7 AS	01	106
7 122 09 61 00 0	4014586897226	CCG 18-125-15 AS	01	106
7 123 04 61 00 0	4014586897158	AGSZ 18-280 BL AS	01	122
7 123 05 61 00 0	4014586897165	AGSZ 18-280 LBL AS	01	122
7 123 06 61 00 0	4014586897172	AGSZ 18-90 LBL AS	01	122
7 129 36 61 00 0	4014586895277	Cordless MULTIMASTER AMM 700 Max Top 4.0 Ah AS	03	212
7 129 36 62 00 0	4014586895284	Cordless MULTIMASTER AMM 700 Max AS	03	213
7 129 36 63 00 0	4014586895291	Cordless MULTIMASTER AMM 700 Max Top AS	03	212
7 129 37 61 00 0	4014586895307	Cordless MULTIMASTER AMM 700 1.7 Q AS	03	232
7 129 37 62 00 0	4014586895314	Cordless MULTIMASTER AMM 700 1.7 Q Autoglas AS	03	232
7 129 37 63 00 0	4014586898926	MULTIMASTER AMM 700 1.7 Q Joint Renovation	03	238
7 129 37 64 00 0	4014586898933	MULTIMASTER AMM 700 1.7 Q Joint Renovation	03	238
7 129 38 61 00 0	4014586895321	Cordless MULTIMASTER AMM 500 Plus Top 4.0 Ah AS	03	213
7 129 38 62 00 0	4014586895338	Cordless MULTIMASTER AMM 500 Plus AS	03	214
7 129 38 63 00 0	4014586895345	Cordless MULTIMASTER AMM 500 Plus Top AS	03	214
7 130 05 61 00 0	4014586898599	ABSS 18 1.6 E AS	01	165
7 130 05 62 00 0	4014586899169	ABSS 18 1.6 E AS Set	01	165
7 130 05 63 00 0	4014586899176	ABSS 18 1.6 E AS Set 1x 5 Ah	01	165
7 130 05 64 00 0	4014586899183	ABSS 18 1.6 E AS Set 2x 5 Ah	01	165
7 130 06 61 00 0	4014586898605	ABLS 18 1.6 E AS	01	161
7 130 06 62 00 0	4014586899190	ABLS 18 1.6 E AS	01	161
7 130 06 63 00 0	4014586899206	ABLS 18 1.6 E AS Set 1x 5 Ah	01	161
7 130 06 64 00 0	4014586899213	ABLS 18 1.6 E AS Set 2x 5 Ah	01	161
7 132 10 61 00 0	4014586898612	ABLK 18 1.3 CSE AS	01	150
7 132 10 62 00 0	4014586899220	ABLK 18 1.3 CSE AS Set	01	150
7 132 10 63 00 0	4014586899237	ABLK 18 1.3 CSE AS Set 1x 5 Ah	01	150
7 132 10 64 00 0	4014586899244	ABLK 18 1.3 CSE AS Set 2x 5 Ah	01	150
7 132 11 61 00 0	4014586898568	ABLK 18 1.6 E AS	01	151
7 132 11 62 00 0	4014586899251	ABLK 18 1.6 E AS Set	01	151
7 132 11 63 00 0	4014586899268	ABLK 18 1.6 E AS Set 1x 5 Ah	01	151
7 132 11 64 00 0	4014586899275	ABLK 18 1.6 E AS Set 2x 5 Ah	01	151

Part number	EAN	Description	PC	Page
7 138 02 62 00 0	4014586898209	AKFH 18-5 AS	01	178
7 138 05 61 00 0	4014586898247	AKFH 18-5 AS basic chamfer set	01	178
7 138 05 62 00 0	4014586898254	AKFH 18-5 AS basic chamfer set with 1x 8 Ah ProCORE battery	01	178
7 138 05 63 00 0	4014586898261	AKFH 18-5 AS basic chamfer set with 2x 8 Ah ProCORE battery	01	178
7 140 01 64 00 0	4014586889214	ABH 18	01	74
7 146 01 61 00 0	4014586897271	AKP 18-600 AS	01	285
7 170 03 61 00 0	4014586898285	AKBU 35 PMQ AS	01	36
7 170 04 61 00 0	4014586898292	AKBU 35 PMQW AS	01	36
7 170 04 62 00 0	4014586899596	AKBU 35 PMQW AS CONSTRUCTION SITE set 3/4" Weldon / HSS NOVA 50	01	38
7 170 04 62 00 0	4014586899596	AKBU 35 PMQW AS CONSTRUCTION SITE set 3/4" Weldon / HSS NOVA 50	01	38
7 170 04 63 00 0	4014586899602	AKBU 35 PMQW 18 V AS SET 1x 12 Ah	01	37
7 170 04 64 00 0	4014586899633	AKBU 35 PMQW 18 V AS set 2x 8 Ah	01	37
7 170 04 65 00 0	4014586899688	AKBU 35 PMQW 18 V AS CONSTRUCTION SITE 1x 12 Ah set 3/4" Weldon / HSS NOVA 50	01	38
7 170 04 66 00 0	4014586899718	AKBU 35 PMQW 18 V AS CONSTRUCTION SITE 2x 8 Ah set 3/4" Weldon / HSS NOVA 50	01	39
7 190 22 60 00 0	4014586898636 4014586898643	AKP 18-600 AS set for grouting renewers	01	239
7 190 23 60 00 0	4014586898681	AKP 18-600 AS TOP set for grouting renewers AKP 18-600 AS set for vehicle glaziers	01	233
7 190 24 60 00 0	4014586898698	AKP 18-600 AS TOP set for vehicle glaziers	01	233
7 202 51 60 00 0	4014586889849	BOZ 32-4 M	01	72
7 205 47 60 00 0	4014586874463	BOS 16	01	72
7 205 49 60 00 0	4014586876443	BOS 16-2	01	71
7 205 51 60 00 0	4014586878843	WBP 10	01	75
7 205 52 60 00 0	4014586882413	BOP 6	01	67
7 205 52 61 00 0	4014586881973	BOP 6 set	01	67
7 205 53 60 00 0	4014586882468	BOP 10	01	68
7 205 53 61 00 0	4014586881980	BOP 10 set	01	68
7 205 54 60 00 0	4014586882512	BOP 10-2	01	69
7 205 54 61 00 0	4014586881997	BOP 10-2 set	01	69
7 205 55 60 00 0	4014586882567	BOP 13-2	01	70
7 205 55 61 00 0	4014586882017	BOP 13-2 set	01	70
7 209 38 60 00 0	4014586881256	GWP 10	01	76
7 221 48 00 23 0	4014586862699	WPO 14-15 E	01	139
7 221 48 50 01 0	4014586862712	WPO 14-15 E marine polishing set	01	140
7 221 48 51 01 0	4014586867069	WPO 14-15 E Set	01	139
7 221 48 60 00 0	4014586872216	WPO 14-15 E marine polishing set	01	139
7 221 49 00 23 0	4014586862729	WPO 14-25 E	01	128
7 221 49 50 01 0	4014586862743	WPO 14-25 E - Stainless steel start set	01	128
7 221 49 51 01 0	4014586867113	WPO 14-25 E	01	140
7 221 63 00 23 0	4014586866055	WPO 10-25 E	01	141
7 221 63 51 01 0	4014586867199	WPO 10-25 E Set	01	141
7 221 67 60 00 0	4014586868936	KS 10-38 E set	01	129
7 221 98 60 00 0	4014586885506	WSG 7-115	19	107
7 222 65 60 00 0	4014586891477	WSG 7-125	19	107
7 222 67 60 00 0	4014586895802	CG 15-125 BL	19	116
7 222 67 62 00 0	4014586898308	CG 15-125 BL Set Heavy Duty	19	118
7 222 75 60 00 0	4014586895864	RS 17-70 E	01	128
7 222 75 61 00 0	4014586895871	RS 17-70 E set	01	129
7 222 76 60 00 0	4014586895895	CG 15-125 BLP	19	117
7 222 77 60 00 0	4014586895956	CG 15-150 BLP	19	116
7 222 78 60 00 0	4014586896014	CG 15-150 BL	19	117
7 222 79 60 00 0	4014586894980 4014586895000	CG 10-125 CG 13-125 V	19 19	107
7 222 80 60 00 0	4014586895000	CG 17-125 V	19	108
7 222 82 60 00 0	4014586895017	CG 17-125	19	109
7 222 83 60 00 0	4014586895024	CG 17-123 IIIOX	19	109
7 222 85 60 00 0	4014586896076	CG 15-125 BLP Inox	19	117
7 222 86 60 00 0	4014586896137	CG 15-125 BL Inox	19	116
7 223 16 60 00 0	4014586879505	GSZ 8-280 P	01	124
7 223 17 60 00 0	4014586879437	GSZ 8-280 PE	01	124
7 223 19 60 00 0	4014586879444	GSZ 8-280 PEL	01	125
7 223 20 60 00 0	4014586879451	GSZ 8-90 PEL	01	125

Part number	EAN	Description	PC	Page
7 223 22 60 00 0	4014586880501	GSZ 11-320 PERL	01	126
7 223 23 60 00 0	4014586880525	GSZ 11-90 PERL	01	126
7 223 24 60 00 0	4014586880594	GSZ 4-280 EL	01	123
7 223 25 60 00 0	4014586880648	GSZ 4-90 EL	01	123
7 228 05 50 00 0	4014586867250	BF 10-280 E	01	129
7 228 05 51 00 0	4014586867267	BF 10-280 E Start-Set	01	130
7 229 67 69 00 0	4014586897769	MULTIMASTER MM 500 Plus	03	216
7 229 67 70 00 0	4014586897813	MULTIMASTER MM 500 Plus Top	03	216
7 229 68 63 00 0	4014586897868	MULTIMASTER MM 700 Max	03	215
7 229 68 64 00 0	4014586897912	MULTIMASTER MM 700 Max Top	03	215
7 229 69 62 00 0	4014586897967	MULTIMASTER MM 700 1.7 Basic	03	235
7 229 69 63 00 0	4014586897998	MULTIMASTER MM 700 1.7 Q Basic	03	235
7 229 70 64 00 0	4014586898049	MULTIMASTER MM 700 1.7 Q Bus & Truck	03	234
7 229 70 65 00 0	4014586898063	MULTIMASTER MM 700 1.7 Q Autoglas	03	234
7 229 70 66 00 0	4014586898940	MULTIMASTER MM 700 1.7 Q Grouting Renewal	03	240
7 229 72 64 00 0	4014586898094	MULTIMASTER MM 300 Plus Start	03	216
7 230 31 61 00 0	4014586874661	BSS 1.6 E	01	166
7 230 31 62 00 0	4014586899992	BSS 1.6 E Set	01	166
7 230 32 61 00 0	4014586874739	BSS 1.6 CE	01	167
7 230 32 62 00 0	4014586900001	BSS 1.6 CE Set	01	167
7 230 33 61 00 0	4014586874807	BSS 2.0 E	01	168
7 230 33 62 00 0	4014586900018	BSS 2.0 E set	01	168
7 230 34 61 00 0	4014586874876	BLS 1.6 E	01	162
7 230 34 62 00 0	4014586900025	BLS 1.6 E set	01	162
7 230 35 61 00 0	4014586874944	BLS 2.5 E	01	163
7 230 35 62 00 0	4014586900032	BLS 2.5 E set	01	163
7 232 38 60 00 0	4014586869858	BLK 1.6 E	01	154
7 232 38 61 00 0	4014586900049	BLK 1.6 E Set	01	154
7 232 39 60 00 0	4014586869926	BLK 1.6 LE	01	155
7 232 40 60 00 0	4014586869995	BLK 2.0 E	01	156
7 232 40 61 00 0	4014586900056	BLK 2.0 E Set	01	156
7 232 41 60 00 0	4014586870069	BLK 1.3 TE	01	153
7 232 41 61 00 0	4014586900063	BLK 1.3 TE Set	01	153
7 232 42 60 00 0	4014586870137	BLK 1.3 CSE	01	152
7 232 42 61 00 0	4014586900070	BLK 1.3 CSE Set	01	152
7 232 46 61 00 0	4014586897677	BLK 3.5 E	01	157
7 232 47 61 00 0	4014586897714	BLK 5.0 E	01	157
7 234 23 00 23 0	4014586858500	AStxe 649-1	01	174
7 236 54 60 00 0	4014586894447	MKAS 355	01	172
7 238 16 61 00 0	4014586892696	KFH 17-8 R	01	179
7 238 18 61 00 0	4014586892733		01	179
7 245 01 60 00 0		KFH 17-15 R		
	4014586894331	GRIT GHB 15-50	01	250 250
7 245 02 60 00 0	4014586894362	GRIT GHB 15-50 Inox	01	
7 270 40 61 00 0	4014586872995	KBM 50 U	01	46
7 270 41 61 00 0	4014586872834	KBM 50 Q	01	45
7 270 42 61 00 0	4014586874272	KBM 50 auto	01	50
7 270 43 61 00 0	4014586872902	KBM 65 U	01	47
7 270 51 60 00 0	4014586881645	KBE 50-2	01	24
7 270 53 61 00 0	4014586886039	KBU 35 Q	01	40
7 270 54 61 00 0	4014586886763	KBU 35 QW	01	40
7 270 54 63 00 0	4014586897295	KBU 35 QW Structural Steel-Set 3/4" Weldon	01	41
7 270 54 64 00 0	4014586897325	KBU 35 QW Fabricator M12 Tapping-Set 3/4" Weldon	01	41
7 270 55 61 00 0	4014586886053	KBU 35 MQ	01	43
7 270 56 61 00 0	4014586886770	KBU 35 MQW	01	43
7 270 57 61 00 0	4014586886077	KBU 35-2 Q	01	44
7 270 58 61 00 0	4014586886787	KBU 35-2 QW	01	44
7 270 60 61 00 0	4014586889740	KBU 110-4 M	01	48
7 270 71 61 00 0	4014586890524	KBU 35 PQ	01	42
	1011300030321			
7 270 72 61 00 0	4014586890548	KBU 35 PQW	01	42
			01 01	23

Part number	EAN	Description	PC	Page
7 273 23 62 00 0	4014586897356	KBC 36 MAGFORCE (230 V)	01	26
7 273 23 63 00 0	4014586897424	KBC 36 MAGFORCE Machinery-Set 3/4" Weldon (230 V)	01	27
7 273 23 64 00 0	4014586897462	KBC 36 MAGFORCE Structural Steel-Set 3/4" Weldon / HSS NOVA 25	01	26
7 273 23 65 00 0	4014586897509	KBC 36 MAGFORCE Truckframe-Set 3/4" Weldon / HSS SPECIAL 25	01	27
7 273 24 61 00 0	4014586898551	KBE 36 MAGSPEED	01	23
7 273 25 61 00 0	4014586897608	KBM 50 UQW	01	46
7 273 26 61 00 0	4014586897622	KBM 65 UQW	01	47
7 273 27 61 00 0	4014586897646	KBM 50 auto QW	01	50
7 273 28 61 00 0	4014586899794	KBE 36 QW MAGSPEED	01	24
7 273 28 62 00 0	4014586899664	KBE 36 QW MAGSPEED Fabrication Set	01	24
7 534 08 00 00 0	4014586855639	STS 325 R	01	174
7 536 03 00 01 0	4014586861906	MOtlx 6-25	03	236
7 901 05 00 40 3	4014586857879	GRIT GXE	13	255
7 901 23 00 44 3	4014586871936	GRIT GXC	13	255
7 901 24 00 44 3	4014586873145	GRIT GXW	13	255
7 901 31 00 40 3	4014586872018	GRIT GX 75	13	254
7 901 32 00 40 3	4014586872063	GRIT GX 75 2H	13	254
7 902 01 00 40 3	4014586858913	GRIT GI 75	13	257
7 902 02 00 40 3	4014586858944	GRIT GI 75 2H	13	257
7 902 04 00 40 3	4014586858999	GRIT GI 150	13	258
7 902 05 00 40 3	4014586859019	GRIT GI 150 2H	13	258
7 902 07 00 40 3	4014586859057	GRIT GIE	13	259
7 902 12 00 44 3	4014586867656	GRIT GIC	13	259
7 902 13 00 40 3	4014586872599	GRIT GIMS 75	13	259
7 902 14 00 40 3	4014586872643	GRIT GIMS 150	13	259
7 902 16 00 40 3	4014586878614	GIMS 75 2H	13	260
7 902 17 00 40 3	4014586878621	GIMS 150 2H	13	260
7 902 18 00 40 3	4014586878645	GIMS 75-6	13	260
7 902 19 00 40 3	4014586878683	GIMS 150-6	13	260
7 902 23 00 23 2	4014586887043	GRIT GI 100 EF	13	257
7 902 23 00 40 3	4014586887067	GRIT GI 100	13	257
7 902 29 50 44 3	4014586878126	GRIT GIS 75	13	258
7 902 30 50 44 3	4014586878225	GRIT GIS 150	13	258
7 902 35 00 40 3	4014586880921	GRIT GILSGIB	13	261
7 902 48 00 40 3	4014586880945	GRIT GIL	13	261
7 902 51 00 40 3	4014586880976	GRIT GILS	13	261
7 905 01 00 40 3	4014586888255	GRIT GKS 75	13	264
7 905 02 00 23 2	4014586888262	GRIT GKS 75	13	264
7 905 02 00 40 3	4014586888279	GRIT GKS 75	13	264
7 905 03 00 40 3	4014586888293	GRIT GKS 75	13	265
7 905 04 00 40 3	4014586888309	GRIT GKS 75 2H	13	265
9 03 16 223 00 8	4014586847924 4014586878515	MBS 32 F	01	80
9 03 20 223 00 0		IBS 16	01	79
9 03 21 223 00 0	4014586895475	MBS 16 X	01	79
9 03 22 223 00 0	4014586895482	MBS 25 F	01	100
9 07 01 003 02 0	4014586896564	FEIN VersaMAG vise set FEIN VersaMAG core drilling SET MK3	01	190
9 07 01 007 00 0	4014586899749		01	190
9 08 01 012 00 8	4014586835075	Balancer up to 1.5 kg	01	282
9 08 01 023 00 1	4014586835099	Balancer up to 2,5 kg	01	282
9 08 01 024 00 9	4014586835105	Balancer up to 3 kg	01	283
9 08 01 025 00 3	4014586835136	Balancer up to 5 kg	01	283
9 08 01 026 00 6	4014586835143	Balancer up to 6,5 kg	01	283
9 08 01 027 00 0	4014586835150	Balancer up to 9 kg	01	283
9 08 01 028 00 8	4014586835167	Balancer up to 11 kg	01	283
9 08 01 029 00 2	4014586835174	Balancer up to 14 kg	01	283
9 08 01 030 00 4	4014586835181	Balancer up to 17 kg	01	283
9 08 01 037 00 9	4014586835228	Balancer up to 2,5 kg	01	282
9 08 01 052 00 4	4014586854052	Balancer up to 1.5 kg	01	282
9 08 01 055 00 0	4014586880693	Balancer up to 25 kg	01	284
9 08 01 056 00 0	4014586880709	Balancer up to 32 kg	01	284
9 08 01 057 00 0	4014586880716	Balancer up to 45 kg	01	284

Part number	EAN	Description	PC	Page
9 08 01 058 00 0	4014586880723	Balancer up to 60 kg	01	284
9 20 29 060 00 0	4014586882956	FEIN Dustex 35 LX	01	199
9 20 30 060 00 0	4014586882994	FEIN Dustex 35 LX AC	01	199
9 20 31 060 00 0	4014586883052	FEIN Dustex 35 MX	01	198
9 20 32 060 00 0	4014586883069	FEIN Dustex 35 MX AC	01	198
9 20 35 060 00 0	4014586891828	FEIN Dustex 25 L set	01	201
9 20 35 223 00 0	4014586891866	FEIN Dustex 25 L	01	201
9 20 36 060 00 0	4014586891903	FEIN Dustex 35 L set	01	200
9 20 36 223 00 0	4014586891941	FEIN Dustex 35 L	01	200
9 26 04 203 01 0	4014586895734	ASBS 18-10 AS	01	194
9 26 04 204 01 0	4014586897288	ARAD 18 BC AS	01	288
9 90 01 001 00 1	4014586871974	GRIT GXR	13	255
9 90 01 002 00 0	4014586858340	GRIT GIXS	13	262
9 90 01 003 00 0	4014586859064	GRIT GIB	13	261
9 90 01 004 00 0	4014586859071	GRIT GIBE	13	262
9 90 01 007 00 1	4014586878263	GRIT GIR	13	262
9 90 01 009 00 0	4014586859125	GRIT GIXBE	13	262
9 90 01 012 00 0	4014586880488	GRIT GHBD	01	250
9 90 01 012 01 0	4014586886992	GRIT GHBM	01	251
9 90 01 012 02 0	4014586887005	GRIT GHBR	01	251

Part number	EAN	Description	PC	Page
3 01 09 128 01 8	4014586198071	adapter	04	-
3 01 09 141 00 3	4014586224060	Die, No. in pack 1 pcs	02	158
3 01 09 141 02 0	4014586318134	Die, No. in pack 2 pcs	02	158
3 01 09 141 03 0	4014586318141	Die, No. in pack 5 pcs	02	158
3 01 09 154 00 7	4014586246598	Die holder	02	158
3 01 09 169 00 9	4014586265056	Die, No. in pack 1 pcs	02	158
3 01 09 169 03 0	4014586275024	Punches and dies in a set	02	158
3 01 09 169 04 0	4014586318158	Die, No. in pack 2 pcs	02	158
3 01 09 170 00 1	4014586265063	Die, No. in pack 1 pcs	02	158
3 01 09 170 03 0	4014586275031	Punches and dies in a set	02	158
3 01 09 170 04 0	4014586318165	Die, No. in pack 2 pcs	02	158
3 01 09 203 00 0	4014586351230	Adapter wedge	02	_
3 02 16 130 00 4	4014586010427	Bolts	02	_
3 02 17 337 00 2	4014586245225	Centering pin, L 125 mm	02	_
3 02 17 338 00 0	4014586251271	Centering pin, L 85 mm	02	_
3 02 17 359 00 0	4014586341958	Centering pin, L 80 mm, Ø 6.35 mm	02	_
3 02 17 362 01 0	4014586425184	Centering pin, L 184 mm, Ø 7.98 mm	02	58
3 02 17 366 01 0	4014586471266	Centering pin, L 158 mm, Ø 6.35 mm	02	58
3 02 29 216 00 5	4014586012155	Safety guard	02	137
3 02 29 347 01 0	4014586354330	Metal skewers	02	
3 02 31 003 00 3	4014586012414	Chain clamps	02	
3 02 31 008 00 0	4014586012421	Chain clamps	02	
3 02 31 013 02 7	4014586012483	ROLLER CHAIN	08	
3 02 31 029 00 2	4014586224183	ROLLER CHAIN	08	
3 02 31 034 01 0	4014586422145	Chain piece	08	
3 02 31 035 01 0	4014586422169	Chain piece	08	
3 02 31 036 01 0	4014586422176	Chain piece	08	
3 02 32 044 01 0	4014586232591	Swivel hook	02	284
3 02 32 046 00 8	4014586259604	Suspension Device	06	73
3 02 34 022 00 9	4014586012865	Clamping collar	08	_
3 02 40 239 01 4	4014586232584	Locking device	02	284
3 02 40 247 00 2	4014586253510	Bottle holder	02	_
3 02 40 308 01 0	4014586353111	Vacuum ring set	02	
3 02 40 395 00 0	4014586444321	Securing pin	02	92
3 02 40 396 00 0	4014586444338	Circlip	02	92
3 02 40 396 01 0	4014586444345	Locking set	02	92
3 05 01 242 00 1	4014586014272	Spacer sleeve	02	_
3 05 01 345 01 0	4014586272993	Coding sleeves, Colour black, No. in pack 10 pcs	06	_
3 05 01 345 02 0	4014586273006	Coding sleeves, Colour Colour mix, No. in pack 7 pcs	06	-
3 05 01 346 01 0	4014586273013	Coding sleeves, Colour grey, No. in pack 10 pcs	06	
3 05 01 347 01 0	4014586273020	Coding sleeves, Colour green, No. in pack 10 pcs	06	
3 05 01 348 01 0	4014586273037	Coding sleeves, Colour blue, No. in pack 10 pcs	06	_
3 05 01 349 01 0	4014586273044	Coding sleeves, Colour red, No. in pack 10 pcs	06	_
3 05 01 350 01 0	4014586273051	Coding sleeves, Colour orange, No. in pack 10 pcs	06	_
3 05 01 351 01 0	4014586274898	Coding sleeves, Colour yellow, No. in pack 10 pcs	06	
3 05 01 352 01 0	4014586317106	Coding sleeves, Colour black, No. in pack 10 pcs	06	95
3 05 01 352 02 0	4014586317113	Coding sleeves, Colour Colour mix, No. in pack 7 pcs	06	95
3 05 01 353 01 0	4014586317120	Coding sleeves, Colour grey, No. in pack 10 pcs	06	95
3 05 01 354 01 0	4014586317137	Coding sleeves, Colour green, No. in pack 10 pcs	06	95
3 05 01 355 01 0	4014586317144	Coding sleeves, Colour blue, No. in pack 10 pcs	06	95
3 05 01 356 01 0	4014586317151	Coding sleeves, Colour red, No. in pack 10 pcs	06	95
3 05 01 357 01 0	4014586317168	Coding sleeves, Colour orange, No. in pack 10 pcs	06	95
3 05 01 358 01 0	4014586317175	Coding sleeves, Colour yellow, No. in pack 10 pcs	06	95
3 05 05 066 01 5	4014586235271	Stop sleeve	02	
3 05 05 068 01 7	4014586248769	Stop sleeve	02	
3 05 05 069 01 1	4014586258928	Stop sleeve	02	
3 05 17 028 00 7	4014586016931	Hose sleeve, Ø 32 mm	02	
3 05 17 029 00 1	4014586016948	Hose sleeve, Ø 27 mm	02	
3 06 05 109 00 6	4014586224503	Adapter hose	02	
3 06 05 110 00 8	4014586224510	Adapter hose	02	
		to the second se		

Part number	EAN	Description	PC	Page
3 07 06 268 00 6	4014586022260	Spiral cordset	02	_
3 07 07 157 03 5	4014586321035	Spiral cordset	06	284
3 07 28 123 00 7	4014586030104	Male connector	02	
3 07 28 124 00 5	4014586030111	Male connector	02	
3 07 28 130 00 0	4014586030173	Sleeve plug	02	
3 07 28 131 00 9	4014586030180	Sleeve plug	02	
3 07 28 137 00 5	4014586030241	Wall socket	02	
3 07 28 138 00 3	4014586030258	Wall socket	02	
3 07 28 141 00 8	4014586030289	Assembly socket	02	
3 07 28 432 00 0	4014586410388	EU-GB plug adapter	02	
3 07 28 452 00 0	4014586424507	EU-GB plug adapter	02	
3 07 49 065 00 9	4014586031927	Device combination	10	
3 07 49 067 00 6	4014586031941	Device combination	10	
3 07 49 068 00 4	4014586031965	Device combination	10	
3 07 49 069 00 8	4014586031972	Device combination	10	
3 07 49 070 00 0	4014586031989	Device combination	10	
3 07 49 073 00 6	4014586032016	Device combination	10	
3 07 49 086 00 0	4014586032108	Device combination	10	
3 07 49 099 00 5	4014586032221	Device combination	10	
3 07 49 100 00 6	4014586326375	Device combination	10	
3 07 51 144 00 3	4014586032993	Motor protection switch	02	
3 07 56 017 00 6	4014586033358	Motor protection plug	02	
3 07 56 084 00 8	4014586264189	Motor protection plug	02	
3 07 56 085 00 2	4014586264196	Motor protection plug, Model 16 A	02	
3 07 56 086 00 5	4014586264202	Motor protection plug	02	
3 07 56 087 00 9	4014586264219	Motor protection plug, Model 16 A	02	
3 07 56 088 00 7	4014586264226	Motor protection plug, Model 16 A	02	
3 07 56 089 00 1	4014586264233	Motor protection plug, Model 16 A	02	
3 07 56 090 00 3	4014586264240	Motor protection plug, Model 16 A	02	_
3 07 56 093 00 9	4014586264271	Motor protection plug, Model 32 A	02	_
3 07 56 094 00 7	4014586264288	Motor protection plug	02	_
3 07 56 095 00 1	4014586264295	Motor protection plug, Model 32 A	02	-
3 07 56 096 00 4	4014586264301	Motor protection plug, Model 32 A	02	_
3 07 56 097 00 8	4014586264318	Motor protection plug, Model 32 A	02	_
3 07 56 098 00 6	4014586264325	Motor protection plug, Model 32 A	02	_
3 07 98 592 77 0	4014586622040	Cable	02	_
3 12 07 103 01 3	4014586044910	Eccentric head	06	134
3 13 08 072 00 0	4014586048123	Plunger blade and fixed blade, Plate thickness 1 mm	02	163
3 13 08 092 00 8	4014586210803	Fixed blade	02	_
3 13 08 096 00 7	4014586210810	Plunger blade, Plate thickness 4.2 mm	02	-
3 13 08 098 00 9	4014586213477	Plunger blade, Plate thickness 2 mm	02	_
3 13 08 111 00 2	4014586229829	Blade pin	02	169
3 13 08 113 00 9	4014586229836	Cutting bars	02	169
3 13 08 123 00 8	4014586229867	Cutting blade, Plate thickness 1.3 mm	02	169
3 13 08 136 00 2	4014586229805	Fixed blade, Plate thickness 3.5 mm	02	
3 13 08 143 00 6	4014586230092	Fixed blade, Plate thickness 2 mm	02	
3 13 08 146 00 1	4014586232911	Plunger blade, Plate thickness 3.5 mm	02	_
3 13 08 147 00 5	4014586232928	Plunger blade, Plate thickness 2 mm	02	
3 13 08 150 00 9	4014586239583	Cutting blade, Plate thickness 1.6 mm	02	169
3 13 08 151 00 8	4014586239590	Blade for curves, Plate thickness 1 mm	02	169
3 13 08 152 00 1	4014586239606	Cutting blade, Plate thickness 0.8 mm	02	169
3 13 08 153 01 4	4014586239613	Cutting bars	02	169
3 13 08 153 02 0	4014586239620	Cutting bars	02	169
3 13 09 039 00 0	4014586048543	Supporting pin	02	
3 13 09 040 00 2	4014586048550	Die	02	159
3 13 09 093 00 3	4014586199931	Die	02	159
3 13 09 094 00 1	4014586199948	Die	02	159
3 13 09 097 00 2	4014586199955	Punch	02	159
3 13 09 098 00 0	4014586199962	Punch	02	159
3 13 09 100 01 4	4014586199986	Spacer sleeve	02	159

Part number	EAN	Description	PC	Page
3 13 09 107 00 0	4014586210742	Die	02	159
3 13 09 108 00 8	4014586210759	Die	02	159
3 13 09 109 00 2	4014586210766	Die	02	159
3 13 09 114 00 8	4014586210780	Chips bag	02	
3 13 09 121 00 2	4014586209876	Wearing plate	02	159
3 13 09 122 00 5	4014586209883	Die, No. in pack 1 pcs	02	159
3 13 09 122 02 0	4014586318172	Die, No. in pack 2 pcs	02	159
3 13 09 122 03 0	4014586318189	Die, No. in pack 5 pcs	02	159
3 13 09 141 00 0	4014586465548	Punch	02	159
3 13 09 141 01 0	4014586465555	Punches and dies in a set	02	159
3 13 09 142 00 0	4014586465562	Punch	02	159
3 13 09 142 01 0	4014586465579	Punches and dies in a set	02	159
3 13 22 169 00 5	4014586053202	Hose sleeve	02	
3 13 22 757 01 6	4014586261386	Filter bag, Model Dustex II, 25	02	
3 13 22 765 00 9	4014586261454	Filter cartridge	02	
3 13 22 767 01 5	4014586261478	Suction hose	02	
3 13 22 771 00 9	4014586261492	Connecting piece	02	134
3 13 22 772 00 2	4014586261508	Stepped collar	02	
3 13 22 810 01 0	4014586307718	Filter bag, Model Dustex 40	02	
3 13 22 811 01 0	4014586307725	Filter bag, Model Dustex 40	02	
3 13 24 000 10 1	4014586457550	Wheel guard, Ø 125 mm	06	119
3 13 24 000 10 2	4014586457567	Wheel guard, Ø 150 mm	06	119
3 13 24 000 11 1	4014586457635	anti-vibration handle	06	119
3 13 24 000 14 2	4014586457864	Safety hood for cutting work, Ø 125 mm	02	119
3 13 24 000 14 3	4014586457871	Safety hood for cutting work, Ø 150 mm	02	119
3 13 24 000 14 4	4014586457888	Dust protection filter Table dealers	02	119
3 13 24 000 18 7	4014586463452	Tool adapter Suption book	02	195
3 13 24 000 18 8	4014586463469	Suction hose Elbow	02	195 195
3 13 24 000 18 9 3 13 24 000 19 0	4014586463476 4014586463483	Suction tube	02	195
3 13 24 000 19 0		Crevice nozzle	02	195
3 13 24 000 19 1	4014586463490 4014586463506	Fluted filter	02	195
3 13 24 000 19 3	4014586463513	Floor nozzle	02	195
3 13 24 000 19 4	4014586463520	Set of rollers	02	195
3 13 27 064 00 8	4014586199580	Protective steel jaws	02	176
3 13 27 068 00 7	4014586199627	STRAINING SCREW	02	
3 13 33 090 00 0	4014586368375	Drill chuck	02	
3 13 33 118 00 0	4014586368382	Drill chuck	02	
3 13 35 017 01 1	4014586262390	Rotating roller	02	130
3 13 45 012 01 0	4014586366197	Flat-fold filter	02	202
3 13 45 059 01 0	4014586366210	Flat-fold filter	02	202
3 13 45 060 01 0	4014586366227	Flat-fold filter	02	202
3 13 45 061 01 0	4014586366234	Fleece filter bag, Model Dustex 25 L, No. in pack 5 pcs	02	203
3 13 45 062 01 0	4014586366241	Fleece filter bag, Model Dustex 35 L, No. in pack 5 pcs	02	203
3 13 45 063 01 0	4014586366258	Disposal bag, No. in pack 5 pcs	02	203
3 13 45 064 01 0	4014586366265	Permanent filter	02	203
3 13 45 065 01 0	4014586366272	Suction hose, Ø 27 mm, L 4 m	02	202
3 13 45 066 01 0	4014586366289	Suction hose, Ø 35 mm, L 4 m	02	202
3 13 45 067 01 0	4014586366296	Extension hose, Ø 27 mm, L 2.5 m	02	202
3 13 45 068 01 0	4014586366302	Extension hose, Ø 35 mm, L 2.5 m	02	202
3 13 45 069 01 0	4014586366319	Repair set	02	202
3 13 45 070 01 0	4014586366326	Elbow	02	202
3 13 45 071 01 0	4014586366333	Suction tube	02	202
3 13 45 071 02 0	4014586368528	Accessory set	02	203
3 13 45 072 01 0	4014586366340	Floor nozzle	02	202
3 13 45 073 01 0	4014586366357	Combination nozzle	02	202
3 13 45 074 01 0	4014586366364	Crevice nozzle	02	202
3 13 45 075 01 0	4014586366371	Upholstery nozzle	02	202
3 13 45 076 01 0	4014586366388	Suction brush	02	202
3 13 45 077 01 0	4014586366395	Intake brush	02	202

Part number	EAN	Description	PC	Page
3 13 45 079 01 0	4014586366418	Stepped collar	02	202
3 13 45 119 01 0	4014586370187	Cable holder, No. in pack 5 pcs	02	203
3 13 45 120 01 0	4014586386119	Antistatic suction hose, Ø 35 mm, L 4 m	02	202
3 13 45 121 01 0	4014586392059	Antistatic suction hose, Ø 27 mm, L 4 m	02	202
3 13 45 123 01 0	4014586378596	Antistatic tool collar	02	202
3 13 45 130 01 0	4014586379449	HEPA filter bag, No. in pack 3 pcs	02	203
3 13 45 133 02 0	4014586386126	Accessory set, Ø 40 mm	02	203
3 13 45 138 01 0	4014586387819	Brush strips	02	
3 13 45 251 01 0	4014586392691	Premium fleece filter bag, Model Dustex 35 L, No. in pack 5 pcs	02	203
3 13 45 263 01 0	4014586394459	Elbow, Ø 35 mm	02	202
3 13 45 267 01 0	4014586400013	Brush strips	02	
3 13 45 268 01 0	4014586400020	Rubber lip	02	
3 13 45 270 01 0	4014586400037	Brush strips	02	
3 13 45 271 01 0	4014586400044	Rubber lip	02	
3 13 45 273 01 0	4014586409955	Premium fleece filter bag, Model Dustex 25 L, No. in pack 5 pcs	02	203
3 13 45 300 01 0	4014586439341	Antistatic tool collar	02	202
3 13 48 073 01 0	4014586385839	Wheel guard, Ø 115 mm	06	119
3 13 48 134 01 0	4014586436029	Wheel guard, Ø 125 mm	06	119
3 13 48 135 01 0	4014586436180	Safety hood for cutting work, Ø 125 mm	02	119
3 13 50 075 00 0	4014586441320	KX clamping screw, No. in pack 10 pcs	02	183
3 13 50 076 00 0	4014586441337	SX clamping screw, No. in pack 10 pcs	02	182
3 14 14 004 00 3	4014586060026	Hose	08	
3 14 14 054 00 8	4014586208916	Replacement hose	02	33
3 14 14 055 00 2	4014586227290	Hose	08	
3 14 14 055 01 1	4014586252421	Hose	08	
3 14 14 070 01 0	4014586356433	Flex-jointed hose, L 340 mm	02	62
3 14 14 078 01 0	4014586428901	Flex-jointed hose, L 500 mm	02	62
3 14 15 020 00 8	4014586060392	Anti vibration mounts	02	
3 14 15 081 00 1	4014586207865	Anti vibration mounts	02	
3 14 20 120 01 0	4014586376677	Protection for AccuTec ASM, Model ASM 14	02	
3 14 26 030 00 5	4014586061641	Hook and loop fastener, Ø 150 mm	02	134
3 14 26 067 01 6	4014586236797	Anti-slip mat	02	
3 14 28 102 01 6	4014586195957	Anti-chipping protector, No. in pack 5 pcs	02	
3 14 28 156 00 0	4014586272047	Plastic cover	02	
3 18 01 010 01 2	4014586069210	Support	02	
3 18 10 071 01 5	4014586069739	Wheel guard	02	
3 18 10 171 00 5	4014586070124	Protective suction hood	02	
3 18 10 240 01 4	4014586228945	Protect.suction hood	06	134
3 18 10 247 01 9	4014586241906	Contact and swarf protection	02	
3 18 10 264 01 0	4014586307343	Protect.suction hood	02	134
3 18 10 277 00 0	4014586326238	Wheel guard	02	
3 18 10 299 00 0	4014586394107	Wheel guard, Ø 115 mm	06	119
3 18 10 300 00 0	4014586394114	Wheel guard, Ø 125 mm	06	119
3 18 10 301 00 0	4014586394121	Wheel guard, Ø 150 mm	06	119
3 18 10 305 00 0	4014586407852	Wheel guard	02	
3 18 10 319 00 0	4014586452326	Safety hood for cutting work, Ø 125 mm	02	119
3 21 09 061 01 6	4014586074542	Clamping unit	02	
3 21 19 032 00 2	4014586074689	Side handle	02	
3 21 19 047 00 4	4014586074801	Handle	02	
3 21 19 078 02 4	4014586074962	Handle	02	
3 21 19 107 01 6	4014586222882	Handle	02	
3 21 19 113 01 6	4014586235264	Handle	02	
3 21 19 117 01 5	4014586268125	anti-vibration handle	02	
3 21 19 118 01 3	4014586268132	anti-vibration handle	02	
3 21 19 119 01 7	4014586268149	anti-vibration handle	02	
3 21 19 124 01 0	4014586334783	anti-vibration handle	02	118
3 21 19 127 03 0	4014586351971	Starter awl	02	
3 21 19 148 02 0	4014586404790	Additional handle	04	229
3 21 19 150 01 0	4014586404523	Handle Fytonsion for tube bondle	02	96
3 21 20 025 00 6	4014586075105	Extension for tube handle	02	

Part number	EAN	Description	PC	Page
3 21 22 007 01 7	4014586075198	Crank	08	-
3 21 23 002 00 6	4014586270906	Adjustment spanner - torque	02	95
3 21 25 043 00 4	4014586075341	Bow	02	-
3 21 25 050 00 7	4014586075396	Suspension Device	02	73
3 21 26 012 01 0	4014586410210	Tool holder	02	95
3 21 27 003 03 5	4014586075594	Depth stop	02	-
3 21 27 005 00 6	4014586075600	Depth stop	02	73
3 21 27 021 03 6	4014586075761	Stop sleeve	02	-
3 21 27 021 06 1	4014586075792	Stop sleeve	02	-
3 21 27 021 11 3	4014586250724	Stop sleeve	02	-
3 21 27 021 12 9	4014586258669	Stop sleeve	02	-
3 21 27 021 13 5	4014586262406	Stop sleeve	02	-
3 21 27 021 14 1	4014586270531	Depth stop	02	-
3 21 27 043 00 0	4014586075983	Stop sleeve	02	-
3 21 27 057 00 8	4014586208831	Stop sleeve	02	-
3 21 27 065 01 9	4014586266077	Depth stop	02	-
3 21 27 069 01 0	4014586351674	Depth stop	04	218
3 21 31 038 02 0	4014586451794	Coolant tank	02	33
3 21 32 022 00 7	4014586076713	Pump	02	33
3 21 32 039 00 0	4014586418087	BIOCUT 3000 lubricant, Contents 1 l	08	_
3 21 32 040 00 0	4014586418094	BIOCUT 3000 lubricant, Contents 5 l	08	_
3 21 32 042 00 0	4014586422879	Lubricant with resistance to the cold, Contents 1 l	08	_
3 21 32 043 00 0	4014586422886	Lubricant with resistance to the cold, Contents 5 l	08	_
3 21 32 046 00 0	4014586470924	Cutting paste	02	158
3 21 33 021 01 0	4014586404745	Device for dust extract	04	_
3 21 33 035 00 0	4014586465920	1/2* ratchet	02	_
3 21 33 036 00 0	4014586465937	Extension	02	_
3 21 73 003 00 3	4014586265568	Work gloves, Size 9 L	04	289
3 21 73 004 00 1	4014586265575	Work gloves, Size 10 XL	04	289
3 21 73 005 00 5	4014586265582	Work gloves, Size 11 XXL	04	289
3 21 74 003 00 0	4014586077215	Protective cage	02	_
3 21 74 006 00 5	4014586199641	Ratchet buckle w/ strap	02	_
3 21 74 007 00 9	4014586214740	Ratchet buckle w/ strap	02	_
3 21 74 008 00 7	4014586241890	STRAP, SAFETY	02	_
3 21 74 009 00 1	4014586321813	Wrist strap	08	_
3 21 74 010 00 3	4014586321820	Wrist strap	08	_
3 21 74 011 00 0	4014586319056	Protective cover	04	247
3 21 74 013 01 0	4014586335773	Swarf cup	02	
3 21 74 014 01 0	4014586376691	AccuTec ASW protective cover, Model ASW 14	02	_
3 21 74 015 01 0	4014586376707	Battery cover, Current/Voltages 14.4 V, Capacity 2.5 Ah	02	
3 21 74 016 01 0	4014586376714	Battery cover, Current/Voltages 14.4 V, Capacity 5 Ah	02	
3 21 74 019 01 0	4014586404905	Battery cover, Current/Voltages 18 V, Capacity 6 Ah	02	289
	101 1000 10 1500	Battery Cover, Carrent, Foliages 10-1, Supuloty Crist		
3 21 74 020 01 0	4014586404912	Rattery cover Current/Voltages 18 V. Canacity 3 Ah	02	289
3 21 74 020 01 0	4014586404912	Battery cover, Current/Voltages 18 V, Capacity 3 Ah Plastic cover, Model < 60 Nm	02	
3 21 74 021 01 0	4014586404929	Plastic cover, Model <60 Nm	02	96
3 21 74 021 01 0 3 21 74 022 01 0	4014586404929 4014586404936	Plastic cover, Model <60 Nm Plastic cover, Model <45 Nm	02 02	96 96
3 21 74 021 01 0 3 21 74 022 01 0 3 21 74 023 01 0	4014586404929 4014586404936 4014586414003	Plastic cover, Model <60 Nm Plastic cover, Model <45 Nm Plastic cover, Model <14 Nm	02 02 02	96 96 96
3 21 74 021 01 0 3 21 74 022 01 0 3 21 74 023 01 0 3 21 74 024 01 0	4014586404929 4014586404936 4014586414003 4014586404943	Plastic cover, Model <60 Nm Plastic cover, Model <45 Nm Plastic cover, Model <14 Nm AccuTec ASW protective cover, Model ASW 18	02 02 02 02	96 96 96
3 21 74 021 01 0 3 21 74 022 01 0 3 21 74 023 01 0 3 21 74 024 01 0 3 21 74 025 01 0	4014586404929 4014586404936 4014586414003 4014586404943 4014586415499	Plastic cover, Model <60 Nm Plastic cover, Model <45 Nm Plastic cover, Model <14 Nm AccuTec ASW protective cover, Model ASW 18 Battery cover, Current/Voltages 12 V, Capacity 3 Ah	02 02 02 02 02	96 96 96 95
3 21 74 021 01 0 3 21 74 022 01 0 3 21 74 023 01 0 3 21 74 024 01 0 3 21 74 025 01 0 3 21 74 028 01 0	4014586404929 4014586404936 4014586414003 4014586404943 4014586415499 4014586434018	Plastic cover, Model <60 Nm Plastic cover, Model <45 Nm Plastic cover, Model <14 Nm AccuTec ASW protective cover, Model ASW 18 Battery cover, Current/Voltages 12 V, Capacity 3 Ah Protection for AccuTec ASM, Model ASM 18	02 02 02 02 02 02	96 96 96 95
3 21 74 021 01 0 3 21 74 022 01 0 3 21 74 023 01 0 3 21 74 024 01 0 3 21 74 025 01 0 3 21 74 028 01 0 3 21 74 029 01 0	4014586404929 4014586404936 4014586414003 4014586404943 4014586415499 4014586435268	Plastic cover, Model <60 Nm Plastic cover, Model <45 Nm Plastic cover, Model <14 Nm AccuTec ASW protective cover, Model ASW 18 Battery cover, Current/Voltages 12 V, Capacity 3 Ah Protection for AccuTec ASM, Model ASM 18 Battery cover, Current/Voltages 12 V	02 02 02 02 02 02 02	96 96 96 95
3 21 74 021 01 0 3 21 74 022 01 0 3 21 74 023 01 0 3 21 74 024 01 0 3 21 74 025 01 0 3 21 74 025 01 0 3 21 74 029 01 0 3 24 22 346 01 0	4014586404929 4014586404936 4014586414003 4014586404943 4014586415499 4014586434018 4014586435268 4014586431093	Plastic cover, Model <60 Nm Plastic cover, Model <45 Nm Plastic cover, Model <14 Nm AccuTec ASW protective cover, Model ASW 18 Battery cover, Current/Voltages 12 V, Capacity 3 Ah Protection for AccuTec ASM, Model ASM 18 Battery cover, Current/Voltages 12 V Spacer	02 02 02 02 02 02 02 02 08	96 96 96 95 - 95 -
3 21 74 021 01 0 3 21 74 022 01 0 3 21 74 023 01 0 3 21 74 024 01 0 3 21 74 025 01 0 3 21 74 025 01 0 3 21 74 028 01 0 3 21 74 029 01 0 3 24 22 346 01 0 3 24 22 420 01 0	4014586404929 4014586404936 4014586414003 4014586404943 4014586415499 4014586434018 4014586435268 4014586431093 4014586461335	Plastic cover, Model <60 Nm Plastic cover, Model <45 Nm Plastic cover, Model <14 Nm AccuTec ASW protective cover, Model ASW 18 Battery cover, Current/Voltages 12 V, Capacity 3 Ah Protection for AccuTec ASM, Model ASM 18 Battery cover, Current/Voltages 12 V Spacer 60 mm oversize jaws (VersaMAG)	02 02 02 02 02 02 02 02 02 08	96 96 96 95 - 95 -
3 21 74 021 01 0 3 21 74 022 01 0 3 21 74 023 01 0 3 21 74 024 01 0 3 21 74 025 01 0 3 21 74 025 01 0 3 21 74 028 01 0 3 21 74 029 01 0 3 24 22 346 01 0 3 24 22 420 01 0 3 24 33 027 01 7	4014586404929 4014586404936 4014586414003 4014586404943 4014586415499 4014586434018 4014586435268 4014586431093 4014586461335 4014586210469	Plastic cover, Model <60 Nm Plastic cover, Model <45 Nm Plastic cover, Model <14 Nm AccuTec ASW protective cover, Model ASW 18 Battery cover, Current/Voltages 12 V, Capacity 3 Ah Protection for AccuTec ASM, Model ASM 18 Battery cover, Current/Voltages 12 V Spacer 60 mm oversize jaws (VersaMAG) Plate	02 02 02 02 02 02 02 02 08 02	96 96 96 95 - 95 - - 191
3 21 74 021 01 0 3 21 74 022 01 0 3 21 74 023 01 0 3 21 74 024 01 0 3 21 74 025 01 0 3 21 74 025 01 0 3 21 74 029 01 0 3 21 74 029 01 0 3 24 22 346 01 0 3 24 33 027 01 7 3 26 23 009 00 6	4014586404929 4014586404936 4014586414003 4014586404943 4014586415499 4014586435268 4014586431093 4014586461335 4014586210469 4014586200699	Plastic cover, Model <60 Nm Plastic cover, Model <45 Nm Plastic cover, Model <14 Nm AccuTec ASW protective cover, Model ASW 18 Battery cover, Current/Voltages 12 V, Capacity 3 Ah Protection for AccuTec ASM, Model ASM 18 Battery cover, Current/Voltages 12 V Spacer 60 mm oversize jaws (VersaMAG) Plate Reducing rings, Ø 53 / 43 mm	02 02 02 02 02 02 02 02 08 02	96 96 96 95 - 95 - - 191 - 81
3 21 74 021 01 0 3 21 74 022 01 0 3 21 74 023 01 0 3 21 74 024 01 0 3 21 74 025 01 0 3 21 74 025 01 0 3 21 74 029 01 0 3 21 74 029 01 0 3 24 22 346 01 0 3 24 22 420 01 0 3 24 33 027 01 7 3 26 23 009 00 6 3 26 23 010 00 8	4014586404929 4014586404936 4014586414003 4014586404943 4014586415499 4014586434018 4014586431093 4014586461335 4014586210469 4014586200699 4014586200422	Plastic cover, Model <60 Nm Plastic cover, Model <45 Nm Plastic cover, Model <14 Nm AccuTec ASW protective cover, Model ASW 18 Battery cover, Current/Voltages 12 V, Capacity 3 Ah Protection for AccuTec ASM, Model ASM 18 Battery cover, Current/Voltages 12 V Spacer 60 mm oversize jaws (VersaMAG) Plate Reducing rings, Ø 53 / 43 mm Reducing rings, Ø 53 / 38 mm	02 02 02 02 02 02 02 02 08 02 08	96 96 95 - 95 - 191 - 81
3 21 74 021 01 0 3 21 74 022 01 0 3 21 74 023 01 0 3 21 74 024 01 0 3 21 74 025 01 0 3 21 74 025 01 0 3 21 74 029 01 0 3 21 74 029 01 0 3 24 22 346 01 0 3 24 22 420 01 0 3 24 33 027 01 7 3 26 23 009 00 6 3 26 23 010 00 8 3 26 23 012 01 9	4014586404929 4014586404936 4014586414003 4014586404943 4014586415499 4014586434018 4014586435268 4014586431093 4014586210469 4014586200699 4014586200422 4014586248776	Plastic cover, Model <60 Nm Plastic cover, Model <45 Nm Plastic cover, Model <14 Nm AccuTec ASW protective cover, Model ASW 18 Battery cover, Current/Voltages 12 V, Capacity 3 Ah Protection for AccuTec ASM, Model ASM 18 Battery cover, Current/Voltages 12 V Spacer 60 mm oversize jaws (VersaMAG) Plate Reducing rings, Ø 53 / 43 mm Reducing rings, Ø 43 / 33 mm Reducing rings, Ø 43 / 33 mm	02 02 02 02 02 02 02 02 08 02 08	96 96 95 - 95 - 191 - 81 81
3 21 74 021 01 0 3 21 74 022 01 0 3 21 74 023 01 0 3 21 74 024 01 0 3 21 74 025 01 0 3 21 74 025 01 0 3 21 74 029 01 0 3 24 22 346 01 0 3 24 22 346 01 0 3 24 33 027 01 7 3 26 23 010 00 8 3 26 23 012 01 9 3 26 23 013 00 4	4014586404929 4014586404936 4014586414003 4014586404943 4014586434018 4014586435268 4014586431093 4014586431093 4014586210469 4014586200699 4014586200422 4014586248776 4014586248783	Plastic cover, Model <60 Nm Plastic cover, Model <45 Nm Plastic cover, Model <14 Nm AccuTec ASW protective cover, Model ASW 18 Battery cover, Current/Voltages 12 V, Capacity 3 Ah Protection for AccuTec ASM, Model ASM 18 Battery cover, Current/Voltages 12 V Spacer 60 mm oversize jaws (VersaMAG) Plate Reducing rings, Ø 53 / 43 mm Reducing rings, Ø 43 / 33 mm Reducing rings, Ø 43 / 38 mm Reducing rings, Ø 43 / 38 mm	02 02 02 02 02 02 02 08 02 08 02 02 02	96 96 95 - 95 - - 191 - 81 81 81
3 21 74 021 01 0 3 21 74 022 01 0 3 21 74 023 01 0 3 21 74 024 01 0 3 21 74 025 01 0 3 21 74 025 01 0 3 21 74 029 01 0 3 21 22 346 01 0 3 24 22 346 01 0 3 24 33 027 01 7 3 26 23 010 00 8 3 26 23 012 01 9 3 26 23 013 00 4 3 26 23 014 01 0	4014586404929 4014586404936 4014586414003 4014586404943 4014586434018 4014586435268 4014586431093 4014586461335 4014586210469 4014586200699 4014586248776 4014586248776 4014586248783 4014586369853	Plastic cover, Model <60 Nm Plastic cover, Model <45 Nm Plastic cover, Model <14 Nm AccuTec ASW protective cover, Model ASW 18 Battery cover, Current/Voltages 12 V, Capacity 3 Ah Protection for AccuTec ASM, Model ASM 18 Battery cover, Current/Voltages 12 V Spacer 60 mm oversize jaws (VersaMAG) Plate Reducing rings, Ø 53 / 43 mm Reducing rings, Ø 43 / 33 mm Reducing rings, Ø 43 / 38 mm Reducing rings, Ø 43 / 38 mm Reducing rings, Ø 55 / 43 mm	02 02 02 02 02 02 02 08 02 08 02 02 02 02	96 96 95 - 95 - - 191 - 81 81 81
3 21 74 021 01 0 3 21 74 022 01 0 3 21 74 023 01 0 3 21 74 024 01 0 3 21 74 025 01 0 3 21 74 025 01 0 3 21 74 029 01 0 3 24 22 346 01 0 3 24 22 346 01 0 3 24 33 027 01 7 3 26 23 010 00 8 3 26 23 012 01 9 3 26 23 013 00 4	4014586404929 4014586404936 4014586414003 4014586404943 4014586434018 4014586435268 4014586431093 4014586431093 4014586210469 4014586200699 4014586200422 4014586248776 4014586248783	Plastic cover, Model <60 Nm Plastic cover, Model <45 Nm Plastic cover, Model <14 Nm AccuTec ASW protective cover, Model ASW 18 Battery cover, Current/Voltages 12 V, Capacity 3 Ah Protection for AccuTec ASM, Model ASM 18 Battery cover, Current/Voltages 12 V Spacer 60 mm oversize jaws (VersaMAG) Plate Reducing rings, Ø 53 / 43 mm Reducing rings, Ø 43 / 33 mm Reducing rings, Ø 43 / 38 mm Reducing rings, Ø 43 / 38 mm	02 02 02 02 02 02 02 08 02 08 02 02 02	289 96 96 96 95 - 95 - 191 - 81 81 81 81 - 81

Part number	EAN	Description	PC	Page
3 27 14 088 00 7	4014586200750	Chipping protector	02	
3 34 01 116 02 0	4014586472331	3/4" Weldon mounting shaft, Taper MT 2, Cutting depth 75 mm, Bore Ø 12 - 35 mm	02	60
3 34 01 117 02 0	4014586472348	3/4" Weldon mounting shaft, Taper MK 3, Cutting depth 75 mm, Bore Ø 12 - 65 mm	02	60
3 34 01 118 02 0	4014586472355	3/4" Weldon mounting shaft, Taper MK 3, Cutting depth 75 mm, Bore Ø 12 - 35 mm	02	60
3 34 01 119 02 0	4014586472362	3/4" Weldon mounting shaft, Taper MK 3, Cutting depth 50 mm, Bore Ø 12 - 35 mm	02	60
3 34 01 120 02 0	4014586472379	3/4" Weldon mounting shaft, Taper MT 2, Cutting depth 75 mm, Bore Ø 12 - 35 mm	02	60
3 34 01 121 02 0	4014586472386	3/4" Weldon mounting shaft, Taper MT 2, Cutting depth 50 mm, Bore Ø 12 - 35 mm	02	60
3 39 01 031 00 1	4014586110233	Tool case	08	
3 39 01 096 01 6	4014586242095	Tool case	02	
3 39 01 114 00 7	4014586266732	Transport box	08	
3 39 01 118 01 0	4014586285474	Tool case	02	
3 39 01 118 20 0	4014586302775	Tool case	04	
3 39 01 118 48 0	4014586317618	Tool case	02	
3 39 01 119 00 0	4014586285498	Plastic box	02	289
3 39 01 122 01 0	4014586308791	Tool case	02	142
3 39 01 122 06 0	4014586321165	Tool case	02	
3 39 01 122 12 0	4014586336732	Tool case	02	_
3 39 01 122 19 0	4014586405759	Tool case	02	
3 39 01 126 02 0	4014586332406	Tool box ass.	02	
3 39 01 127 02 0	4014586325859	Tool box ass.	02	_
3 39 01 130 05 0	4014586333250	Tool case	02	_
3 39 01 131 03 0	4014586348957	Tool case	02	_
3 39 01 131 08 0	4014586348650	Tool case	02	_
3 39 01 131 92 0	4014586376325	Plastic tool cases	02	_
3 39 01 131 94 0	4014586379630	Tool case	02	_
3 39 01 131 98 0	4014586376332	Carrying case unfilled	04	_
3 39 01 132 03 0	4014586340449	Tool box ass.	02	_
3 39 01 133 05 0	4014586351247	Tool case	02	_
3 39 01 134 04 0	4014586340456	Tool box ass.	02	_
3 39 01 140 99 0	4014586356310	Tool case	02	_
3 39 01 141 01 0	4014586365244	Plastic tool cases	02	_
3 39 01 142 14 0	4014586356921	Case	02	_
3 39 01 143 06 0	4014586356938	Case	02	_
3 39 01 146 00 0	4014586380025	Systainer Sys 1	02	_
3 39 01 146 19 0	4014586430836	Tool case	02	_
3 39 01 146 22 0	4014586416946	Systainer Starlock Plus	04	_
3 39 01 147 00 0	4014586380032	Systainer Sys 2	02	_
3 39 01 152 00 0	4014586398396	Plastic tool cases	02	_
3 39 01 152 05 0	4014586407654	Plastic tool cases	04	_
3 39 01 152 39 0	4014586420080	Plastic tool cases	02	_
3 39 01 152 88 0	4014586465609	Case	02	_
3 39 01 154 03 0	4014586411903	Plastic tool cases	04	_
3 39 01 154 05 0	4014586403786	Plastic tool cases	04	_
3 39 01 155 02 0	4014586379647	Tool box ass.	02	_
3 39 01 157 32 0	4014586410593	Tool case	02	_
3 39 01 174 06 0	4014586403809	Tool box ass.	02	_
3 39 01 175 04 0	4014586403816	Tool box ass.	02	_
3 39 01 182 02 0	4014586420097	Plastic tool cases	02	_
3 39 01 189 10 0	4014586441672	Tool case	02	
3 39 01 190 01 0	4014586457772	Case	02	
3 39 01 191 01 0	4014586457857	Case	02	
3 39 01 604 02 0	4014586422893	Case	02	
3 39 01 605 02 0	4014586425849	Case	02	
3 39 01 680 39 0	4014586465432	Structural Steel-Set 3/4" Weldon / HSS NOVA 50	02	63
3 39 01 680 40 0	4014586465449	Fabricator M12 Tapping-Set 3/4" Weldon	02	63
3 39 01 680 41 0	4014586465456	Machinery-Set 3/4" Weldon	02	33
3 39 01 680 42 0	4014586465463	Structural Steel-Set 3/4" Weldon / HSS NOVA 25	02	33
3 39 01 680 43 0	4014586465470	KBC 36 MAGFORCE Truckframe-Set 3/4" Weldon / HSS SPECIAL 25	02	33
3 39 01 680 52 0	4014586472249	Construction Site Set 3/4" Weldon / HSS NOVA 50	02	63
3 39 01 740 00 0	4014586466934	XL-BOXX FEIN	02	280
3 3 3 3 1 7 7 0 0 0 0	101 1000700504	AL SOME LIN		

Part number	EAN	Description	PC	Page
3 39 01 790 00 0	4014586473031	FEIN i-BOXX Rack, single, Depth 342 mm, Width 442 mm, Height 101 mm	02	281
3 39 01 791 00 0	4014586473048	FEIN i-BOXX Rack lid, Depth 342 mm, Width 442 mm, Height 50 mm	02	281
3 39 06 420 00 0	4014586464480	FEIN L-BOXX lid insert, Depth 321 mm, Width 405 mm, Height 21 mm	02	281
3 39 06 428 00 0	4014586466910	FEIN XL-BOXX lid insert, Depth 361 mm, Width 596 mm, Height 17 mm	02	281
3 39 10 136 00 0	4014586473086	FEIN L-BOXX roller, Depth 492 mm, Width 646 mm, Height 184 mm	02	281
3 39 98 140 02 2	4014586622231	Plastic tool cases	02	
3 39 98 140 08 2	4014586662039	Case	02	
3 43 00 000 00 1	4014586402796	Contact guard	04	218
3 52 22 927 05 0	4014586392455	Adapter for FEIN oscillator (up to 2004)	04	
3 52 22 946 06 0	4014586397498	Composite set of accessories, Mount SLM	04	
3 52 22 952 01 0	4014586392516	HSS saw blade set, Ø 100 mm, Mount SLP	04	218
3 52 22 952 03 0	4014586392530	E-Cut-Combo, Mount SLP	04	
3 52 22 952 10 0	4014586404721	Set of sanding sheets, Edge length 130 mm	04	225
3 52 22 952 11 0	4014586404479	Sanding sheet set, zirconium, Edge length 130 mm	04	
3 52 22 952 30 0	4014586415635	Best of E-Cut accessory set, Mount SL	04	
3 52 22 967 01 0	4014586440378	Best of E-Cut Starlock WOOD & METAL, Mount SL	04	218
3 52 22 967 02 0	4014586440385	Best of Starlock METAL, Mount SL	04	222
3 52 22 967 03 0	4014586440392	Best of E-Cut StarlockPlus WOOD & METAL, Mount SLP	04	218
3 52 22 967 04 0	4014586440408	Best of Starlock SANDING, Mount SL	04	223
3 52 22 967 05 0	4014586440415	Best of E-Cut StarlockMax WOOD & METAL, Mount SLM	04	218
3 52 22 967 06 0	4014586440507	Best of Starlock RENOVATION, Mount SL	04	222
3 52 22 967 07 0	4014586440422	Starlock TILE WORKING combo, Mount SL	04	227
3 52 22 967 08 0	4014586440439	Starlock WOOD E-Cut combo, Mount SL	04	219
3 52 22 967 09 0	4014586440446	Starlock MINI CUT combo, Mount SL	04	219
3 52 22 967 10 0	4014586440453	Starlock WOOD & METAL E-Cut combo, Mount SL	04	219
3 52 22 967 11 0	4014586440460	Starlock RENOVATION combo, Mount SL	04	222
3 52 22 967 12 0	4014586440477	StarlockMax INTERIOR WORK professional set, Mount SLM	04	222
3 52 22 967 13 0	4014586440484	StarlockMax GROUT RENEWAL professional set, Mount SLM	04	228
3 52 22 967 14 0	4014586440491	StarlockMax HEATING/SANITARY professional set, Mount SLM	04	227
3 52 22 967 26 0	4014586444253	Professional marine set, Mount SLP	04	222
3 90 00 000 00 1	4014586280028	Graphite pad, No. in pack 5 pcs	06	267
3 90 00 000 00 2	4014586280035	Hose	06	269
3 90 00 000 00 3	4014586280042	Tube clamps	06	269
3 90 00 000 00 4	4014586280059	Eye protection, No. in pack 3 pcs	06	267
3 90 00 000 00 7	4014586280080	Eye protection GU75/GR/GXR (3 pieces)	06	268
3 90 00 000 05 6	4014586283517	Graphite coating, No. in pack 3 pcs	06	270
3 90 00 000 10 0	4014586294162	Metal filter	06	272
3 90 00 000 18 3	4014586283500	Graphite coating	06	273
3 90 00 000 18 4	4014586283494	Eye protection, No. in pack 3 pcs	06	270
3 90 00 000 19 0	4014586283487	Eye protection, No. in pack 3 pcs	06	273
3 90 00 000 49 6	4014586280325	Guide rail, brass	06	269
3 90 00 000 49 7	4014586280332	Nylon glide support	06	269
3 90 00 000 97 6	4014586286303	Cassette filter	06	272
3 90 00 001 00 2	4014586353739	Brake wheel	06	
3 90 00 004 76 0	4014586380933	Graphite pad, No. in pack 4 pcs	06	272
3 90 00 008 10 6	4014586389837	Stainless steel sanding support	02	252
3 90 00 009 92 3	4014586434919	Stainless steel sanding support	13	272
4 06 11 009 01 9	4014586126760	Set of sealing rings	02	
4 11 14 001 00 8	4014586128030	Nipple	08	
4 11 35 007 00 2	4014586128177	Clutch part	08	_
4 11 36 005 00 0	4014586128269	Coupling sleeve	08	_
4 11 36 005 01 9	4014586128276	Coupling sleeve	08	
4 11 36 006 00 3	4014586128283	Coupling sleeve	08	
4 11 40 004 00 7	4014586128399	Hose coupling	02	176
4 30 33 087 06 5	4014586225173	Set of clamping screws	04	
6 01 10 008 01 7	4014586165790	Tool holder Ø 7 mm with external flat	02	
6 05 03 306 00 8	4014586262772	Bit, 1/4" hexagon head	02	
6 05 05 015 00 1	4014586258713	Bits 1/4" for hexagon socket screws	02	
6 05 10 011 00 9	4014586235141	Tool holder 1/4" external hexagon, Ø 15 mm, L 51 mm	02	97
6 05 10 215 00 3	4014586258812	Tool holder 1/4" external hexagon, Ø 10.6 mm, L 45 mm	02	97
2 22 10 113 00 3	.01.000200012			

Part number	EAN	Description	PC	Page
6 05 10 222 01 0	4014586404820	Bit holder, Accessory interface QuickIN	02	87
6 20 05 019 01 0	4014586420141	Impact socket with protective cover, Tool Holder 1/4" Outer square, wrench size 7 mm	02	
6 20 05 020 01 0	4014586420158	Impact socket with protective cover, Tool Holder 1/4" Outer square, wrench size 8 mm	02	
6 20 05 021 01 0	4014586420165	Impact socket with protective cover, Tool Holder 1/4" Outer square, wrench size 10 mm	02	
6 20 05 023 01 0	4014586420172	Impact socket with protective cover, Tool Holder 1/4" Outer square, wrench size 13 mm	02	
6 20 05 024 01 0	4014586420189	Impact socket with protective cover, Tool Holder 1/4" Outer square, wrench size 16 mm	02	
6 21 05 017 01 0	4014586420196	Impact socket with protective cover, Tool Holder 3/8" Outer square, wrench size 8 mm	02	
6 21 05 018 01 0	4014586420202	Impact socket with protective cover, Tool Holder 3/8" Outer square, wrench size 10 mm	02	
6 21 05 019 01 0	4014586420219	Impact socket with protective cover, Tool Holder 3/8" Outer square, wrench size 13 mm	02	
6 21 05 020 01 0	4014586420226	Impact socket with protective cover, Tool Holder 3/8" Outer square, wrench size 16 mm	02	
6 22 05 023 01 0	4014586420233	Impact socket with protective cover, Tool Holder 1/2" Outer square, wrench size 16 mm	02	
6 22 05 024 01 0	4014586420240	Impact socket with protective cover, Tool Holder 1/2" Outer square, wrench size 18 mm	02	
6 22 05 025 01 0	4014586420257	Impact socket with protective cover, Tool Holder 1/2" Outer square, wrench size 21 mm	02	
6 22 05 026 01 0	4014586420264	Impact socket with protective cover, Tool Holder 1/2" Outer square, wrench size 24 mm	02	
6 22 19 002 07 9	4014586168012	Socket for stay bolts	02	
6 22 19 002 09 1	4014586168036	Socket for stay bolts	02	
6 22 19 002 10 6	4014586168043	Socket for stay bolts	02	
6 22 19 002 14 3	4014586168074	Socket for stay bolts	02	
6 24 05 323 01 0	4014586442006	Impact socket, wrench size 24 mm	02	92
6 24 05 323 02 0	4014586442075	Set of impact sockets	02	92
6 24 05 324 01 0	4014586442013	Impact socket, wrench size 27 mm	02	92
6 24 05 325 01 0	4014586442020	Impact socket, wrench size 30 mm	02	92
6 24 05 326 01 0	4014586442037	Impact socket, wrench size 32 mm	02	92
6 24 05 327 01 0	4014586442044	Impact socket, wrench size 34 mm	02	92
6 24 05 328 01 0	4014586442051	Impact socket, wrench size 36 mm	02	92
6 24 05 329 01 0	4014586442068	Impact socket, wrench size 41 mm	02	92
6 24 15 002 01 0	4014586440118	Reduction adapter	02	92
6 27 12 109 03 4	4014586169637	Bit, 1/4" hexagon head, Size 2, L 25 mm	02	_
6 29 01 002 00 4	4014586172071	Jaw spanner SW8	02	_
6 29 01 003 00 8	4014586172088	Jaw spanner SW9	02	
6 29 01 004 00 6	4014586172095	Single head wrench	02	
6 29 01 007 00 7	4014586172125	Jaw spanner SW13	02	_
6 29 03 002 00 9	4014586172255	Jaw spanner SW17	02	73
6 29 03 010 00 6	4014586172309	Single head wrench	08	_
6 29 03 011 00 5	4014586172316	Jaw spanner SW17	02	
6 29 04 003 00 0	4014586172347	Jaw spanner SW19	02	
6 29 06 009 00 7	4014586172415	Socket spanner SW 8	02	
6 29 06 014 00 0	4014586419534	Pipe socket wrench	08	
6 29 07 004 00 5	4014586172446	Allen key SW6	02	
6 29 07 006 00 2	4014586172453	Allen key SW8	02	
6 29 07 010 00 0	4014586172477	Allen key SW4	02	
6 29 07 011 00 9	4014586172484	Allen key SW5	02	_
6 29 07 013 00 6	4014586172491	Allen key SW3	02	
6 29 07 015 00 8	4014586172514	Allen key SW2.5	02	
6 29 07 017 00 5	4014586172521	Allen key, WAF 4.5	02	
6 29 07 023 00 5	4014586172545	Allen key SW4	02	
6 29 07 029 00 6	4014586172590	Allen key SW2	02	
6 29 07 030 00 8	4014586172606	Allen key SW8	02	
6 29 07 037 00 3	4014586249728	Allen key	02	
6 29 08 013 00 3	4014586172675	Sickle spanner	02	
6 29 08 015 00 0	4014586419541	Sickle spanner	02	
6 29 10 022 00 2	4014586172736	Bidirectional nut spanner	02	
6 29 10 023 00 6	4014586172743	Bi-directional nut spanner	02	_
6 29 10 031 00 8	4014586172811	Bi-directional nut spanner	04	
6 29 11 010 00 0	4014586220772	Ring spanner 17 x 19	08	_
6 29 12 001 00 4	4014586266107	Screwdriver	02	_
6 29 12 002 01 0	4014586441375	Socket head wrench, WAF 4	02	
6 29 12 003 01 0	4014586441382	Socket head wrench, WAF 5	02	
6 29 12 004 01 0	4014586441399	T15 torx wrench	02	
6 29 12 005 00 0	4014586458540	Allen key	02	

Part number	EAN	Description	PC	Page
6 29 13 004 00 0	4014586172859	Retaining pin	02	_
6 29 13 020 00 4	4014586172927	Retaining pin	02	_
6 29 14 002 00 5	4014586172941	Chuck key	02	_
6 29 14 004 00 7	4014586172958	Chuck key	02	_
6 29 14 005 00 1	4014586172965	Chuck key	02	_
6 29 14 011 00 1	4014586173016	Chuck key	02	_
6 31 06 016 01 0	4014586271767	Extension	02	59
6 31 06 017 01 0	4014586335063	Extension	02	_
6 31 06 022 98 0	4014586720180	Extension	02	59
6 31 10 019 01 0	4014586415680	Tapping drill for through holes, Thread M 6, Ø 6 mm, Square 4.9 mm	02	32
6 31 10 019 02 0	4014586416069	Tapping drill set for through holes, Thread M 6	02	32
6 31 10 019 03 0	4014586416076	Tapping drill for through holes with adapter with 3/4" Weldon fitting, Thread M 6	02	32
6 31 10 020 01 0	4014586415697	Tapping drill for through holes, Thread M 8, Ø 6 mm, Square 4.9 mm	02	32
6 31 10 020 02 0	4014586416083	Tapping drill set for through holes, Thread M 8	02	32
6 31 10 020 03 0	4014586416090	Tapping drill for through holes with adapter with 3/4" Weldon fitting, Thread M 8	02	32
6 31 10 021 01 0	4014586415703	Tapping drill for through holes, Thread M 10, Ø 7 mm, Square 5.5 mm	02	32
6 31 10 021 02 0	4014586416106	Tapping drill set for through holes, Thread M 10	02	32
6 31 10 021 03 0	4014586416113	Tapping drill for through holes with adapter with 3/4" Weldon fitting, Thread M 10	02	32
6 31 10 022 01 0	4014586415710	Tapping drill for through holes, Thread M 12, Ø 9 mm, Square 7 mm	02	32
6 31 10 022 02 0	4014586416120	Tapping drill set for through holes, Thread M 12	02	32
6 31 10 022 03 0	4014586416137	Tapping drill for through holes with adapter with 3/4" Weldon fitting, Thread M 12	02	32
6 31 10 023 01 0	4014586465487	Tapping drill for through holes, Thread M 8, Ø 8 mm, Square 6.2 mm	02	61
6 31 10 023 02 0	4014586465494	Tappers for blind holes, Thread M 8, Ø 8 mm, Square 7 mm	02	61
6 31 10 024 01 0	4014586465500	Tapping drill for through holes, Thread M 10, Ø 10 mm, Square 8 mm	02	61
6 31 10 024 02 0	4014586465517	Tappers for blind holes, Thread M 10, Ø 10 mm, Square 8 mm	02	61
6 31 10 025 01 0	4014586465524	Tapping drill for through holes, Thread M 12, Ø 9 mm, Square 7 mm	02	61
6 31 10 025 02 0	4014586465531	Tappers for blind holes, Thread M 12, Ø 9 mm, Square 6.2 mm	02	61
6 31 11 009 01 0	4014586326597	HSS spiral drill with QuickIN fitting, Bore Ø 10 mm	02	59
6 31 11 010 01 0	4014586326603	HSS spiral drill with QuickIN fitting, Bore Ø 10.2 mm	02	59
6 31 11 011 01 0	4014586326610	HSS spiral drill with QuickIN fitting, Bore Ø 11 mm	02	59
6 31 11 012 01 0	4014586326627	HSS spiral drill with QuickIN fitting, Bore Ø 12 mm	02	59
6 31 11 013 01 0	4014586326634	HSS spiral drill with QuickIN fitting, Bore Ø 13 mm	02	59
6 31 11 014 01 0	4014586326641	HSS spiral drill with QuickIN fitting, Bore Ø 14 mm	02	59
6 31 11 015 01 0	4014586326658	HSS spiral drill with QuickIN fitting, Bore Ø 15 mm	02	59
6 31 11 016 01 0	4014586326665	HSS spiral drill with QuickIN fitting, Bore Ø 15.5 mm	02	59
6 31 11 018 01 0	4014586409085	HSS twist drill with 3/4" Weldon fitting, Bore Ø 6 mm	02	31
6 31 11 018 02 0	4014586416144	HSS twist drill set with 3/4" Weldon fitting	02	31
6 31 11 019 01 0	4014586409092	HSS twist drill with 3/4" Weldon fitting, Bore Ø 7 mm	02	31
6 31 11 020 01 0	4014586409108	HSS twist drill with 3/4" Weldon fitting, Bore Ø 8 mm	02	31
6 31 11 021 01 0	4014586409115	HSS twist drill with 3/4" Weldon fitting, Bore Ø 9 mm	02	31
6 31 11 022 01 0	4014586409122	HSS twist drill with 3/4" Weldon fitting, Bore Ø 10 mm	02	31
6 31 11 023 01 0	4014586409139	HSS twist drill with 3/4" Weldon fitting, Bore Ø 11 mm	02	31
6 31 11 024 01 0	4014586409146	HSS twist drill with 3/4" Weldon fitting, Bore Ø 12 mm	02	31
6 31 11 025 01 0	4014586409153	HSS twist drill with 3/4" Weldon fitting, Bore Ø 13 mm	02	31
6 31 11 026 01 0	4014586409160	HSS twist drill with 3/4" Weldon fitting, Bore Ø 14 mm	02	31
6 31 11 027 01 0	4014586409177	HSS twist drill with 3/4" Weldon fitting, Bore Ø 15 mm	02	31
6 31 11 028 01 0	4014586409184	HSS twist drill with 3/4" Weldon fitting, Bore Ø 16 mm	02	31
6 31 11 034 01 0	4014586409658	HSS twist drill with 3/4" Weldon fitting, Bore Ø 6.8 mm	02	31
6 31 11 035 01 0	4014586409665	HSS twist drill with 3/4" Weldon fitting, Bore Ø 8.5 mm	02	31
6 31 11 036 01 0	4014586415109		02	31
		HSS twist drill with 3/4" Weldon fitting, Bore Ø 5 mm	02	31
6 31 11 037 01 0	4014586415116 4014586415727	HSS twist drill with 3/4" Weldon fitting, Bore Ø 10.2 mm HSS 90° countersink bit, Ø 16.5 mm	02	32
6 31 11 038 01 0		HSS 90° countersink bit, Ø 16.5 mm HSS 90° countersink bit with adapter with 3/4" Weldon fitting, Ø 16.5 mm	02	32
	4014586416168			89
6 31 14 038 01 0	4014586331027	Centring drill bit, No. in pack 1 pcs	02	
6 31 14 038 02 0	4014586332796	Centring drill bit, No. in pack 5 pcs TCT Little 50 core bit with EEIN thread M 18 v 6 B 1 5 Pore Ø 19 mm. Cutting don'th 50 mm.	02	89
6 31 27 001 01 5	4014586176130	TCT Ultra 50 core bit with FEIN thread M 18 x 6 P 1.5, Bore Ø 18 mm, Cutting depth 50 mm	20	53
6 31 27 002 01 8	4014586176147	TCT Ultra 50 core bit with FEIN thread M 18 x 6 P 1.5, Bore Ø 20 mm, Cutting depth 50 mm	20	53
6 31 27 003 01 2	4014586176154	TCT Ultra 50 core bit with FEIN thread M 18 x 6 P 1.5, Bore Ø 22 mm, Cutting depth 50 mm	20	53
6 31 27 004 01 0	4014586176161	TCT Ultra 50 core bit with FEIN thread M 18 x 6 P 1.5, Bore Ø 25 mm, Cutting depth 50 mm	20	53
6 31 27 005 01 4	4014586176178	TCT Ultra 50 core bit with FEIN thread M 18 x 6 P 1.5, Bore Ø 26 mm, Cutting depth 50 mm	20	53

Part number	EAN	Description	PC	Page
6 31 27 006 01 7	4014586176185	TCT Ultra 50 core bit with FEIN thread M 18 x 6 P 1.5, Bore Ø 28 mm, Cutting depth 50 mm	20	53
6 31 27 007 01 1	4014586176192	TCT Ultra 50 core bit with FEIN thread M 18 x 6 P 1.5, Bore Ø 30 mm, Cutting depth 50 mm	20	53
6 31 27 008 01 9	4014586176208	TCT Ultra 50 core bit with FEIN thread M 18 x 6 P 1.5, Bore Ø 32 mm, Cutting depth 50 mm	20	53
6 31 27 009 01 3	4014586176215	TCT Ultra 50 core bit with FEIN thread M 18 x 6 P 1.5, Bore Ø 34 mm, Cutting depth 50 mm	20	53
6 31 27 010 01 5	4014586176222	TCT Ultra 50 core bit with FEIN thread M 18 x 6 P 1.5, Bore Ø 35 mm, Cutting depth 50 mm	20	53
6 31 27 011 01 4	4014586176239 4014586176246	TCT Ultra 50 core bit with FEIN thread M 18 x 6 P 1.5, Bore Ø 38 mm, Cutting depth 50 mm TCT Ultra 50 core bit with FEIN thread M 18 x 6 P 1.5, Bore Ø 40 mm, Cutting depth 50 mm	20	53
6 31 27 012 01 7	4014586176246	TCT Ultra 50 core bit with FEIN thread M 18 x 6 P 1.5, Bore Ø 42 mm, Cutting depth 50 mm	20	53
6 31 27 013 01 1	4014586176260	TCT Ultra 50 core bit with FEIN thread M 18 x 6 P 1.5, Bore Ø 43 mm, Cutting depth 50 mm	20	53
6 31 27 015 01 3	4014586176277	TCT Ultra 50 core bit with FEIN thread M 18 x 6 P 1.5, Bore Ø 45 mm, Cutting depth 50 mm	20	53
6 31 27 016 01 6	4014586176284	TCT Ultra 50 core bit with FEIN thread M 18 x 6 P 1.5, Bore Ø 48 mm, Cutting depth 50 mm	20	53
6 31 27 017 01 0	4014586176291	TCT Ultra 50 core bit with FEIN thread M 18 x 6 P 1.5, Bore Ø 50 mm, Cutting depth 50 mm	20	53
6 31 27 018 01 8	4014586176307	TCT Ultra 50 core bit with FEIN thread M 18 x 6 P 1.5, Bore Ø 52 mm, Cutting depth 50 mm	20	53
6 31 27 019 01 2	4014586176314	TCT Ultra 50 core bit with FEIN thread M 18 x 6 P 1.5, Bore Ø 19 mm, Cutting depth 50 mm	20	53
6 31 27 020 01 4	4014586176321	TCT Ultra 50 core bit with FEIN thread M 18 x 6 P 1.5, Bore Ø 21 mm, Cutting depth 50 mm	20	53
6 31 27 021 01 3	4014586176338	TCT Ultra 50 core bit with FEIN thread M 18 x 6 P 1.5, Bore Ø 23 mm, Cutting depth 50 mm	20	53
6 31 27 022 01 6	4014586176345	TCT Ultra 50 core bit with FEIN thread M 18 x 6 P 1.5, Bore Ø 24 mm, Cutting depth 50 mm	20	53
6 31 27 023 01 0	4014586176352	TCT Ultra 50 core bit with FEIN thread M 18 x 6 P 1.5, Bore Ø 27 mm, Cutting depth 50 mm	20	53
6 31 27 024 01 8	4014586176369	TCT Ultra 50 core bit with FEIN thread M 18 x 6 P 1.5, Bore Ø 29 mm, Cutting depth 50 mm	20	53
6 31 27 025 01 2	4014586176376	TCT Ultra 50 core bit with FEIN thread M 18 x 6 P 1.5, Bore Ø 31 mm, Cutting depth 50 mm	20	53
6 31 27 026 01 5	4014586176383	TCT Ultra 50 core bit with FEIN thread M 18 x 6 P 1.5, Bore Ø 33 mm, Cutting depth 50 mm	20	53
6 31 27 027 01 9	4014586176390	TCT Ultra 50 core bit with FEIN thread M 18 x 6 P 1.5, Bore Ø 36 mm, Cutting depth 50 mm	20	53
6 31 27 028 01 7	4014586176406	TCT Ultra 50 core bit with FEIN thread M 18 x 6 P 1.5, Bore Ø 37 mm, Cutting depth 50 mm	20	53
6 31 27 029 01 1	4014586176413	TCT Ultra 50 core bit with FEIN thread M 18 x 6 P 1.5, Bore Ø 39 mm, Cutting depth 50 mm	20	53
6 31 27 030 01 3	4014586176420	TCT Ultra 50 core bit with FEIN thread M 18 x 6 P 1.5, Bore Ø 41 mm, Cutting depth 50 mm	20	53
6 31 27 031 01 2	4014586176437	TCT Ultra 50 core bit with FEIN thread M 18 x 6 P 1.5, Bore Ø 44 mm, Cutting depth 50 mm	20	53
6 31 27 032 01 3	4014586176444 4014586176451	TCT Ultra 50 core bit with FEIN thread M 18 x 6 P 1.5, Bore Ø 46 mm, Cutting depth 50 mm TCT Ultra 50 core bit with FEIN thread M 18 x 6 P 1.5, Bore Ø 47 mm, Cutting depth 50 mm	20	53
6 31 27 034 01 7	4014586176468	TCT Ultra 50 core bit with FEIN thread M 18 x 6 P 1.5, Bore Ø 49 mm, Cutting depth 50 mm	20	53
6 31 27 035 01 1	4014586176475	TCT Ultra 50 core bit with FEIN thread M 18 x 6 P 1.5, Bore Ø 51 mm, Cutting depth 50 mm	20	53
6 31 27 036 01 4	4014586192369	TCT Ultra 50 core bit with FEIN thread M 18 x 6 P 1.5, Bore Ø 53 mm, Cutting depth 50 mm	20	53
6 31 27 037 01 8	4014586192376	TCT Ultra 50 core bit with FEIN thread M 18 x 6 P 1.5, Bore Ø 54 mm, Cutting depth 50 mm	20	53
6 31 27 038 01 6	4014586192383	TCT Ultra 50 core bit with FEIN thread M 18 x 6 P 1.5, Bore Ø 55 mm, Cutting depth 50 mm	20	53
6 31 27 039 01 0	4014586192390	TCT Ultra 50 core bit with FEIN thread M 18 x 6 P 1.5, Bore Ø 56 mm, Cutting depth 50 mm	20	53
6 31 27 040 01 2	4014586192406	TCT Ultra 50 core bit with FEIN thread M 18 x 6 P 1.5, Bore Ø 57 mm, Cutting depth 50 mm	20	53
6 31 27 041 01 1	4014586192413	TCT Ultra 50 core bit with FEIN thread M 18 x 6 P 1.5, Bore Ø 58 mm, Cutting depth 50 mm	20	53
6 31 27 042 01 4	4014586200941	TCT Ultra 50 core bit with FEIN thread M 18 x 6 P 1.5, Bore Ø 12 mm, Cutting depth 50 mm	20	53
6 31 27 043 01 8	4014586200958	TCT Ultra 50 core bit with FEIN thread M 18 x 6 P 1.5, Bore Ø 13 mm, Cutting depth 50 mm	20	53
6 31 27 044 01 6	4014586200965	TCT Ultra 50 core bit with FEIN thread M 18 x 6 P 1.5, Bore Ø 14 mm, Cutting depth 50 mm	20	53
6 31 27 045 01 0	4014586200972	TCT Ultra 50 core bit with FEIN thread M 18 x 6 P 1.5, Bore Ø 15 mm, Cutting depth 50 mm	20	53
6 31 27 046 01 3	4014586200989	TCT Ultra 50 core bit with FEIN thread M 18 x 6 P 1.5, Bore Ø 16 mm, Cutting depth 50 mm	20	53
6 31 27 047 01 7	4014586200996	TCT Ultra 50 core bit with FEIN thread M 18 x 6 P 1.5, Bore Ø 17 mm, Cutting depth 50 mm	20	53
6 31 27 049 01 9	4014586223179	TCT Ultra 50 core bit with FEIN thread M 18 x 6 P 1.5, Bore Ø 59 mm, Cutting depth 50 mm	20	53
6 31 27 050 01 1	4014586223186	TCT Ultra 50 core bit with FEIN thread M 18 x 6 P 1.5, Bore Ø 60 mm, Cutting depth 50 mm	20	53
6 31 27 051 01 0	4014586223193	TCT Ultra 50 core bit with FEIN thread M 18 x 6 P 1.5, Bore Ø 61 mm, Cutting depth 50 mm	20	53
6 31 27 052 01 3	4014586223209 4014586223216	TCT Ultra 50 core bit with FEIN thread M 18 x 6 P 1.5, Bore Ø 62 mm, Cutting depth 50 mm TCT Ultra 50 core bit with FEIN thread M 18 x 6 P 1.5, Bore Ø 63 mm, Cutting depth 50 mm	20	53
6 31 27 054 01 5	4014586223223	TCT Ultra 50 core bit with FEIN thread M 18 x 6 P 1.5, Bore Ø 64 mm, Cutting depth 50 mm	20	53
6 31 27 055 01 9	4014586223230	TCT Ultra 50 core bit with FEIN thread M 18 x 6 P 1.5, Bore Ø 65 mm, Cutting depth 50 mm	20	53
6 31 27 086 01 9	4014586239996	TCT Ultra 35 core bit with QuickIN holder, Bore Ø 12 mm, Cutting depth 35 mm	20	51
6 31 27 086 04 0	4014586375533	Best of core bits QuickIN	20	51
6 31 27 087 01 3	4014586240008	TCT Ultra 35 core bit with QuickIN holder, Bore Ø 13 mm, Cutting depth 35 mm	20	51
6 31 27 088 01 1	4014586240015	TCT Ultra 35 core bit with QuickIN holder, Bore Ø 14 mm, Cutting depth 35 mm	20	51
6 31 27 089 01 5	4014586240022	TCT Ultra 35 core bit with QuickIN holder, Bore Ø 15 mm, Cutting depth 35 mm	20	51
6 31 27 090 01 7	4014586240039	TCT Ultra 35 core bit with QuickIN holder, Bore Ø 16 mm, Cutting depth 35 mm	20	51
6 31 27 091 01 6	4014586240046	TCT Ultra 35 core bit with QuickIN holder, Bore Ø 17 mm, Cutting depth 35 mm	20	51
6 31 27 092 01 9	4014586240053	TCT Ultra 35 core bit with QuickIN holder, Bore Ø 18 mm, Cutting depth 35 mm	20	51
6 31 27 093 01 3	4014586240060	TCT Ultra 35 core bit with QuickIN holder, Bore Ø 19 mm, Cutting depth 35 mm	20	51
6 31 27 094 01 1	4014586240077	TCT Ultra 35 core bit with QuickIN holder, Bore Ø 20 mm, Cutting depth 35 mm	20	51
6 31 27 095 01 5	4014586240084	TCT Ultra 35 core bit with QuickIN holder, Bore Ø 21 mm, Cutting depth 35 mm	20	51

Part number	EAN	Description	PC	Page
6 31 27 096 01 8	4014586240091	TCT Ultra 35 core bit with QuickIN holder, Bore Ø 22 mm, Cutting depth 35 mm	20	51
6 31 27 097 01 2	4014586240091	TCT Ultra 35 core bit with QuickIN holder, Bore Ø 23 mm, Cutting depth 35 mm	20	51 51
6 31 27 098 01 0	4014586240114	TCT Ultra 35 core bit with QuickIN holder, Bore Ø 24 mm, Cutting depth 35 mm	20	51 51
6 31 27 099 01 4	4014586240121	TCT Ultra 35 core bit with QuickIN holder, Bore Ø 25 mm, Cutting depth 35 mm	20	51
6 31 27 100 01 5	4014586240138	TCT Ultra 35 core bit with QuickIN holder, Bore Ø 26 mm, Cutting depth 35 mm	20	51
6 31 27 101 01 4	4014586240145	TCT Ultra 35 core bit with QuickIN holder, Bore Ø 27 mm, Cutting depth 35 mm	20	51
6 31 27 102 01 7	4014586240152	TCT Ultra 35 core bit with QuickIN holder, Bore Ø 28 mm, Cutting depth 35 mm	20	51
6 31 27 103 01 1	4014586240169	TCT Ultra 35 core bit with QuickIN holder, Bore Ø 29 mm, Cutting depth 35 mm	20	51
6 31 27 104 01 9	4014586240176	TCT Ultra 35 core bit with QuickIN holder, Bore Ø 30 mm, Cutting depth 35 mm	20	51
6 31 27 105 01 3	4014586240183	TCT Ultra 35 core bit with QuickIN holder, Bore Ø 31 mm, Cutting depth 35 mm	20	51
6 31 27 106 01 6	4014586240190	TCT Ultra 35 core bit with QuickIN holder, Bore Ø 32 mm, Cutting depth 35 mm	20	51
6 31 27 107 01 0	4014586240206	TCT Ultra 35 core bit with QuickIN holder, Bore Ø 33 mm, Cutting depth 35 mm	20	51
6 31 27 108 01 8	4014586240213	TCT Ultra 35 core bit with QuickIN holder, Bore Ø 34 mm, Cutting depth 35 mm	20	51
6 31 27 109 01 2	4014586240220	TCT Ultra 35 core bit with QuickIN holder, Bore Ø 35 mm, Cutting depth 35 mm	20	51
6 31 27 110 01 4	4014586240237	TCT Ultra 35 core bit with QuickIN holder, Bore Ø 36 mm, Cutting depth 35 mm	20	51
6 31 27 111 01 3	4014586240244	TCT Ultra 35 core bit with QuickIN holder, Bore Ø 37 mm, Cutting depth 35 mm	20	51
6 31 27 112 01 6	4014586240251	TCT Ultra 35 core bit with QuickIN holder, Bore Ø 38 mm, Cutting depth 35 mm	20	51
6 31 27 113 01 0	4014586240268	TCT Ultra 35 core bit with QuickIN holder, Bore Ø 39 mm, Cutting depth 35 mm	20	51
6 31 27 114 01 8	4014586240275	TCT Ultra 35 core bit with QuickIN holder, Bore Ø 40 mm, Cutting depth 35 mm	20	51
6 31 27 115 01 2	4014586240282	TCT Ultra 35 core bit with QuickIN holder, Bore Ø 41 mm, Cutting depth 35 mm	20	51
6 31 27 116 01 5	4014586240299	TCT Ultra 35 core bit with QuickIN holder, Bore Ø 42 mm, Cutting depth 35 mm	20	51
6 31 27 117 01 9	4014586240305	TCT Ultra 35 core bit with QuickIN holder, Bore Ø 43 mm, Cutting depth 35 mm	20	51
6 31 27 118 01 7	4014586240312	TCT Ultra 35 core bit with QuickIN holder, Bore Ø 44 mm, Cutting depth 35 mm	20	51
6 31 27 119 01 1	4014586240329	TCT Ultra 35 core bit with QuickIN holder, Bore Ø 45 mm, Cutting depth 35 mm	20	51
6 31 27 120 01 3	4014586240336	TCT Ultra 35 core bit with QuickIN holder, Bore Ø 46 mm, Cutting depth 35 mm	20	51
6 31 27 121 01 2	4014586240343	TCT Ultra 35 core bit with QuickIN holder, Bore Ø 47 mm, Cutting depth 35 mm	20	51
6 31 27 122 01 5	4014586240350	TCT Ultra 35 core bit with QuickIN holder, Bore Ø 48 mm, Cutting depth 35 mm	20	51
6 31 27 123 01 9	4014586240367	TCT Ultra 35 core bit with QuickIN holder, Bore Ø 49 mm, Cutting depth 35 mm	20	51
6 31 27 124 01 7	4014586240374	TCT Ultra 35 core bit with QuickIN holder, Bore Ø 50 mm, Cutting depth 35 mm	20	51
6 31 27 125 01 1	4014586240381	TCT Ultra 35 core bit with QuickIN holder, Bore Ø 51 mm, Cutting depth 35 mm	20	51
6 31 27 126 01 4	4014586240398	TCT Ultra 35 core bit with QuickIN holder, Bore Ø 52 mm, Cutting depth 35 mm	20	51
6 31 27 127 01 8	4014586240404	TCT Ultra 35 core bit with QuickIN holder, Bore Ø 53 mm, Cutting depth 35 mm	20	51
6 31 27 128 01 6	4014586240411	TCT Ultra 35 core bit with QuickIN holder, Bore Ø 54 mm, Cutting depth 35 mm	20	51
6 31 27 129 01 0	4014586240428	TCT Ultra 35 core bit with QuickIN holder, Bore Ø 55 mm, Cutting depth 35 mm	20	51
6 31 27 130 01 2	4014586240435	TCT Ultra 35 core bit with QuickIN holder, Bore Ø 56 mm, Cutting depth 35 mm	20	 51
6 31 27 131 01 1	4014586240442	TCT Ultra 35 core bit with QuickIN holder, Bore Ø 57 mm, Cutting depth 35 mm	20	51
6 31 27 132 01 4	4014586240459	TCT Ultra 35 core bit with QuickIN holder, Bore Ø 58 mm, Cutting depth 35 mm	20	51
6 31 27 133 01 8	4014586240466	TCT Ultra 35 core bit with QuickIN holder, Bore Ø 59 mm, Cutting depth 35 mm	20	51
6 31 27 134 01 6	4014586240473	TCT Ultra 35 core bit with QuickIN holder, Bore Ø 60 mm, Cutting depth 35 mm	20	51
6 31 27 135 01 0	4014586240480	TCT Ultra 35 core bit with QuickIN holder, Bore Ø 61 mm, Cutting depth 35 mm	20	51
6 31 27 136 01 3	4014586240497	TCT Ultra 35 core bit with QuickIN holder, Bore Ø 62 mm, Cutting depth 35 mm	20	51
6 31 27 137 01 7	4014586240503	TCT Ultra 35 core bit with QuickIN holder, Bore Ø 63 mm, Cutting depth 35 mm	20	51
6 31 27 138 01 5	4014586240510	TCT Ultra 35 core bit with QuickIN holder, Bore Ø 64 mm, Cutting depth 35 mm	20	51
6 31 27 139 01 9	4014586240527	TCT Ultra 35 core bit with QuickIN holder, Bore Ø 65 mm, Cutting depth 35 mm	20	51
6 31 27 238 01 1	4014586252469	TCT Ultra 35 core bit with QuickIN holder, Bore Ø 15.5 mm, Cutting depth 35 mm	20	51
6 31 27 239 01 5	4014586252476	TCT Ultra 35 core bit with QuickIN holder, Bore Ø 17.5 mm, Cutting depth 35 mm	20	51
6 31 27 240 01 7	4014586252483	TCT Ultra 35 core bit with QuickIN holder, Bore Ø 19.5 mm, Cutting depth 35 mm	20	51
6 31 27 241 01 6	4014586252490	TCT Ultra 35 core bit with QuickIN holder, Bore Ø 26.5 mm, Cutting depth 35 mm	20	51
6 31 27 276 01 0	4014586272122	TCT Ultra 50 core bit with 3/4" Weldon holder, Bore Ø 12 mm, Cutting depth 50 mm	20	28
6 31 27 276 02 0	4014586375540	Best of core bits 3/4" Weldon	20	28
6 31 27 277 01 0	4014586272139	TCT Ultra 50 core bit with 3/4" Weldon holder, Bore Ø 13 mm, Cutting depth 50 mm	20	28
6 31 27 278 01 0	4014586272146	TCT Ultra 50 core bit with 3/4" Weldon holder, Bore Ø 14 mm, Cutting depth 50 mm	20	28
6 31 27 279 01 0	4014586272153	TCT Ultra 50 core bit with 3/4" Weldon holder, Bore Ø 15 mm, Cutting depth 50 mm	20	28
6 31 27 280 01 0	4014586272160	TCT Ultra 50 core bit with 3/4" Weldon holder, Bore Ø 16 mm, Cutting depth 50 mm	20	28
6 31 27 281 01 0	4014586272177	TCT Ultra 50 core bit with 3/4" Weldon holder, Bore Ø 17 mm, Cutting depth 50 mm	20	28
6 31 27 282 01 0	4014586272184	TCT Ultra 50 core bit with 3/4" Weldon holder, Bore Ø 18 mm, Cutting depth 50 mm	20	28
6 31 27 283 01 0	4014586272191	TCT Ultra 50 core bit with 3/4" Weldon holder, Bore Ø 19 mm, Cutting depth 50 mm	20	28
6 31 27 284 01 0	4014586272207	TCT Ultra 50 core bit with 3/4" Weldon holder, Bore Ø 20 mm, Cutting depth 50 mm	20	28
6 31 27 285 01 0	4014586272214	TCT Ultra 50 core bit with 3/4" Weldon holder, Bore Ø 21 mm, Cutting depth 50 mm	20	28
6 31 27 286 01 0	4014586272221	TCT Ultra 50 core bit with 3/4" Weldon holder, Bore Ø 22 mm, Cutting depth 50 mm	20	28

Part number	EAN	Description	PC	Page
6 31 27 287 01 0	4014586272238	TCT Ultra 50 core bit with 3/4" Weldon holder, Bore Ø 23 mm, Cutting depth 50 mm	20	28
6 31 27 288 01 0	4014586272245	TCT Ultra 50 core bit with 3/4" Weldon holder, Bore Ø 24 mm, Cutting depth 50 mm	20	28
6 31 27 289 01 0	4014586272252	TCT Ultra 50 core bit with 3/4" Weldon holder, Bore Ø 25 mm, Cutting depth 50 mm	20	28
6 31 27 290 01 0	4014586272269	TCT Ultra 50 core bit with 3/4" Weldon holder, Bore Ø 26 mm, Cutting depth 50 mm	20	28
6 31 27 291 01 0	4014586272276	TCT Ultra 50 core bit with 3/4" Weldon holder, Bore Ø 27 mm, Cutting depth 50 mm	20	28
6 31 27 292 01 0	4014586272283	TCT Ultra 50 core bit with 3/4" Weldon holder, Bore Ø 28 mm, Cutting depth 50 mm	20	28
6 31 27 293 01 0	4014586272290 4014586272306	TCT Ultra 50 core bit with 3/4" Weldon holder, Bore Ø 29 mm, Cutting depth 50 mm TCT Ultra 50 core bit with 3/4" Weldon holder, Bore Ø 30 mm, Cutting depth 50 mm	20	28 28
6 31 27 295 01 0	4014586272313	TCT Ultra 50 core bit with 3/4" Weldon holder, Bore Ø 31 mm, Cutting depth 50 mm	20	28
6 31 27 296 01 0	4014586272320	TCT Ultra 50 core bit with 3/4" Weldon holder, Bore Ø 32 mm, Cutting depth 50 mm	20	28
6 31 27 297 01 0	4014586272337	TCT Ultra 50 core bit with 3/4" Weldon holder, Bore Ø 33 mm, Cutting depth 50 mm	20	28
6 31 27 298 01 0	4014586272344	TCT Ultra 50 core bit with 3/4" Weldon holder, Bore Ø 34 mm, Cutting depth 50 mm	20	28
6 31 27 299 01 0	4014586272351	TCT Ultra 50 core bit with 3/4" Weldon holder, Bore Ø 35 mm, Cutting depth 50 mm	20	28
6 31 27 300 01 0	4014586272368	TCT Ultra 50 core bit with 3/4" Weldon holder, Bore Ø 36 mm, Cutting depth 50 mm	20	28
6 31 27 301 01 0	4014586272375	TCT Ultra 50 core bit with 3/4" Weldon holder, Bore Ø 37 mm, Cutting depth 50 mm	20	28
6 31 27 302 01 0	4014586272382	TCT Ultra 50 core bit with 3/4" Weldon holder, Bore Ø 38 mm, Cutting depth 50 mm	20	28
6 31 27 303 01 0	4014586272399	TCT Ultra 50 core bit with 3/4" Weldon holder, Bore Ø 39 mm, Cutting depth 50 mm	20	28
6 31 27 304 01 0	4014586272405	TCT Ultra 50 core bit with 3/4" Weldon holder, Bore Ø 40 mm, Cutting depth 50 mm	20	28
6 31 27 305 01 0	4014586272412	TCT Ultra 50 core bit with 3/4" Weldon holder, Bore Ø 41 mm, Cutting depth 50 mm	20	28
6 31 27 306 01 0	4014586272429	TCT Ultra 50 core bit with 3/4" Weldon holder, Bore Ø 42 mm, Cutting depth 50 mm	20	28
6 31 27 307 01 0	4014586272436	TCT Ultra 50 core bit with 3/4" Weldon holder, Bore Ø 43 mm, Cutting depth 50 mm	20	28
6 31 27 308 01 0	4014586272443	TCT Ultra 50 core bit with 3/4" Weldon holder, Bore Ø 44 mm, Cutting depth 50 mm	20	28
6 31 27 309 01 0	4014586272450	TCT Ultra 50 core bit with 3/4" Weldon holder, Bore Ø 45 mm, Cutting depth 50 mm	20	28
6 31 27 310 01 0	4014586272467	TCT Ultra 50 core bit with 3/4" Weldon holder, Bore Ø 46 mm, Cutting depth 50 mm	20	28
6 31 27 311 01 0	4014586272474	TCT Ultra 50 core bit with 3/4" Weldon holder, Bore Ø 47 mm, Cutting depth 50 mm	20	28 28
6 31 27 312 01 0	4014586272481 4014586272498	TCT Ultra 50 core bit with 3/4" Weldon holder, Bore Ø 48 mm, Cutting depth 50 mm TCT Ultra 50 core bit with 3/4" Weldon holder, Bore Ø 49 mm, Cutting depth 50 mm	20	28
6 31 27 314 01 0	4014586272504	TCT Ultra 50 core bit with 3/4" Weldon holder, Bore Ø 50 mm, Cutting depth 50 mm	20	28
6 31 27 315 01 0	4014586272511	TCT Ultra 50 core bit with 3/4" Weldon holder, Bore Ø 51 mm, Cutting depth 50 mm	20	52
6 31 27 316 01 0	4014586272528	TCT Ultra 50 core bit with 3/4" Weldon holder, Bore Ø 52 mm, Cutting depth 50 mm	20	52
6 31 27 317 01 0	4014586272535	TCT Ultra 50 core bit with 3/4" Weldon holder, Bore Ø 53 mm, Cutting depth 50 mm	20	52
6 31 27 318 01 0	4014586272542	TCT Ultra 50 core bit with 3/4" Weldon holder, Bore Ø 54 mm, Cutting depth 50 mm	20	52
6 31 27 319 01 0	4014586272559	TCT Ultra 50 core bit with 3/4" Weldon holder, Bore Ø 55 mm, Cutting depth 50 mm	20	52
6 31 27 320 01 0	4014586272566	TCT Ultra 50 core bit with 3/4" Weldon holder, Bore Ø 56 mm, Cutting depth 50 mm	20	52
6 31 27 321 01 0	4014586272573	TCT Ultra 50 core bit with 3/4" Weldon holder, Bore Ø 57 mm, Cutting depth 50 mm	20	52
6 31 27 322 01 0	4014586272580	TCT Ultra 50 core bit with 3/4" Weldon holder, Bore Ø 58 mm, Cutting depth 50 mm	20	52
6 31 27 323 01 0	4014586272597	TCT Ultra 50 core bit with 3/4" Weldon holder, Bore Ø 59 mm, Cutting depth 50 mm	20	52
6 31 27 324 01 0	4014586272603	TCT Ultra 50 core bit with 3/4" Weldon holder, Bore Ø 60 mm, Cutting depth 50 mm	20	52
6 31 27 325 01 0	4014586272610	TCT Ultra 50 core bit with 3/4" Weldon holder, Bore Ø 61 mm, Cutting depth 50 mm	20	52
6 31 27 326 01 0	4014586272627	TCT Ultra 50 core bit with 3/4" Weldon holder, Bore Ø 62 mm, Cutting depth 50 mm	20	52
6 31 27 327 01 0	4014586272634	TCT Ultra 50 core bit with 3/4" Weldon holder, Bore Ø 63 mm, Cutting depth 50 mm	20	52
6 31 27 328 01 0	4014586272641	TCT Ultra 50 core bit with 3/4" Weldon holder, Bore Ø 64 mm, Cutting depth 50 mm	20	52
6 31 27 329 01 0	4014586272658	TCT Ultra 50 core bit with 3/4" Weldon holder, Bore Ø 65 mm, Cutting depth 50 mm	20	52
6 31 27 330 01 0	4014586279732 4014586279749	HM Ultra 50 core drill bit with QuickIN MAX/Weldon 32 fitting, Bore Ø 50 mm, Cutting depth 50 mm	20	53
6 31 27 331 01 0	4014586279756	HM Ultra 50 core drill bit with QuickIN MAX/Weldon 32 fitting, Bore Ø 51 mm, Cutting depth 50 mm HM Ultra 50 core drill bit with QuickIN MAX/Weldon 32 fitting, Bore Ø 52 mm, Cutting depth 50 mm	20	53
6 31 27 333 01 0	4014586279763	HM Ultra 50 core drill bit with QuickIN MAX/Weldon 32 fitting, Bore Ø 53 mm, Cutting depth 50 mm	20	53
6 31 27 334 01 0	4014586279770	HM Ultra 50 core drill bit with QuickIN MAX/Weldon 32 fitting, Bore Ø 54 mm, Cutting depth 50 mm	20	53
6 31 27 335 01 0	4014586279787	HM Ultra 50 core drill bit with QuickIN MAX/Weldon 32 fitting, Bore Ø 55 mm, Cutting depth 50 mm	20	53
6 31 27 336 01 0	4014586279794	HM Ultra 50 core drill bit with QuickIN MAX/Weldon 32 fitting, Bore Ø 56 mm, Cutting depth 50 mm	20	53
6 31 27 337 01 0	4014586279800	HM Ultra 50 core drill bit with QuickIN MAX/Weldon 32 fitting, Bore Ø 57 mm, Cutting depth 50 mm	20	53
6 31 27 338 01 0	4014586279817	HM Ultra 50 core drill bit with QuickIN MAX/Weldon 32 fitting, Bore Ø 58 mm, Cutting depth 50 mm	20	53
6 31 27 339 01 0	4014586279824	HM Ultra 50 core drill bit with QuickIN MAX/Weldon 32 fitting, Bore Ø 59 mm, Cutting depth 50 mm	20	53
6 31 27 340 01 0	4014586279831	HM Ultra 50 core drill bit with QuickIN MAX/Weldon 32 fitting, Bore Ø 60 mm, Cutting depth 50 mm	20	53
6 31 27 341 01 0	4014586279848	HM Ultra 50 core drill bit with QuickIN MAX/Weldon 32 fitting, Bore Ø 61 mm, Cutting depth 50 mm	20	53
6 31 27 342 01 0	4014586279855	HM Ultra 50 core drill bit with QuickIN MAX/Weldon 32 fitting, Bore Ø 62 mm, Cutting depth 50 mm	20	53
6 31 27 343 01 0	4014586279862	HM Ultra 50 core drill bit with QuickIN MAX/Weldon 32 fitting, Bore Ø 63 mm, Cutting depth 50 mm	20	53
6 31 27 344 01 0	4014586279879	HM Ultra 50 core drill bit with QuickIN MAX/Weldon 32 fitting, Bore Ø 64 mm, Cutting depth 50 mm	20	53
6 31 27 345 01 0	4014586279886	HM Ultra 50 core drill bit with QuickIN MAX/Weldon 32 fitting, Bore Ø 65 mm, Cutting depth 50 mm	20	53
6 31 27 346 01 0	4014586279893	HM Ultra 50 core drill bit with QuickIN MAX/Weldon 32 fitting, Bore Ø 66 mm, Cutting depth 50 mm	20	53

Part number	EAN	Description	PC	Page
6 31 27 347 01 0	4014586279909	HM Ultra 50 core drill bit with QuickIN MAX/Weldon 32 fitting, Bore Ø 67 mm, Cutting depth 50 mm	20	53
6 31 27 348 01 0	4014586279916	HM Ultra 50 core drill bit with QuickIN MAX/Weldon 32 fitting, Bore Ø 68 mm, Cutting depth 50 mm	20	53
6 31 27 349 01 0	4014586279923	HM Ultra 50 core drill bit with QuickIN MAX/Weldon 32 fitting, Bore Ø 69 mm, Cutting depth 50 mm	20	53
6 31 27 350 01 0	4014586279930	HM Ultra 50 core drill bit with QuickIN MAX/Weldon 32 fitting, Bore Ø 70 mm, Cutting depth 50 mm	20	53
6 31 27 351 01 0	4014586279947	HM Ultra 50 core drill bit with QuickIN MAX/Weldon 32 fitting, Bore Ø 71 mm, Cutting depth 50 mm	20	53
6 31 27 352 01 0	4014586279954	HM Ultra 50 core drill bit with QuickIN MAX/Weldon 32 fitting, Bore Ø 72 mm, Cutting depth 50 mm	20	53
6 31 27 353 01 0	4014586279961	HM Ultra 50 core drill bit with QuickIN MAX/Weldon 32 fitting, Bore Ø 73 mm, Cutting depth 50 mm	20	53
6 31 27 354 01 0	4014586279978	HM Ultra 50 core drill bit with QuickIN MAX/Weldon 32 fitting, Bore Ø 74 mm, Cutting depth 50 mm	20	53
6 31 27 355 01 0	4014586279985	HM Ultra 50 core drill bit with QuickIN MAX/Weldon 32 fitting, Bore Ø 75 mm, Cutting depth 50 mm	20	53
6 31 27 456 01 0	4014586304083	HM Ultra 50 core drill bit with QuickIN MAX/Weldon 32 fitting, Bore Ø 76 mm, Cutting depth 50 mm	20	53
6 31 27 457 01 0	4014586304090	HM Ultra 50 core drill bit with QuickIN MAX/Weldon 32 fitting, Bore Ø 77 mm, Cutting depth 50 mm	20	53
6 31 27 458 01 0	4014586304106	HM Ultra 50 core drill bit with QuickIN MAX/Weldon 32 fitting, Bore Ø 78 mm, Cutting depth 50 mm	20	53
6 31 27 459 01 0	4014586304113	HM Ultra 50 core drill bit with QuickIN MAX/Weldon 32 fitting, Bore Ø 79 mm, Cutting depth 50 mm	20	53
6 31 27 460 01 0	4014586304120	HM Ultra 50 core drill bit with QuickIN MAX/Weldon 32 fitting, Bore Ø 80 mm, Cutting depth 50 mm	20	53
6 31 27 714 01 0	4014586346632	TCT Ultra 35 core bit with 3/4" Weldon holder, Bore Ø 12 mm, Cutting depth 35 mm	20	28
6 31 27 714 02 0	4014586375557	Best of core bits 3/4" Weldon	20	28
6 31 27 715 01 0	4014586346649	TCT Ultra 35 core bit with 3/4" Weldon holder, Bore Ø 13 mm, Cutting depth 35 mm	20	28
6 31 27 716 01 0	4014586346656	TCT Ultra 35 core bit with 3/4" Weldon holder, Bore Ø 14 mm, Cutting depth 35 mm	20	28
6 31 27 717 01 0	4014586346663	TCT Ultra 35 core bit with 3/4" Weldon holder, Bore Ø 15 mm, Cutting depth 35 mm	20	28
6 31 27 718 01 0	4014586346670	TCT Ultra 35 core bit with 3/4" Weldon holder, Bore Ø 16 mm, Cutting depth 35 mm	20	28
6 31 27 719 01 0	4014586346687	TCT Ultra 35 core bit with 3/4" Weldon holder, Bore Ø 17 mm, Cutting depth 35 mm	20	28
6 31 27 720 01 0	4014586346694	TCT Ultra 35 core bit with 3/4" Weldon holder, Bore Ø 18 mm, Cutting depth 35 mm	20	28
6 31 27 721 01 0	4014586346700	TCT Ultra 35 core bit with 3/4" Weldon holder, Bore Ø 19 mm, Cutting depth 35 mm	20	28
6 31 27 722 01 0	4014586346717	TCT Ultra 35 core bit with 3/4" Weldon holder, Bore Ø 20 mm, Cutting depth 35 mm	20	28
6 31 27 723 01 0	4014586346724	TCT Ultra 35 core bit with 3/4" Weldon holder, Bore Ø 21 mm, Cutting depth 35 mm	20	28
6 31 27 724 01 0	4014586346731	TCT Ultra 35 core bit with 3/4" Weldon holder, Bore Ø 22 mm, Cutting depth 35 mm	20	28
6 31 27 725 01 0	4014586346748	TCT Ultra 35 core bit with 3/4" Weldon holder, Bore Ø 23 mm, Cutting depth 35 mm	20	28
6 31 27 726 01 0	4014586346755	TCT Ultra 35 core bit with 3/4" Weldon holder, Bore Ø 24 mm, Cutting depth 35 mm	20	28
6 31 27 727 01 0	4014586346762	TCT Ultra 35 core bit with 3/4" Weldon holder, Bore Ø 25 mm, Cutting depth 35 mm	20	28
6 31 27 728 01 0	4014586346779	TCT Ultra 35 core bit with 3/4" Weldon holder, Bore Ø 26 mm, Cutting depth 35 mm	20	28
6 31 27 729 01 0	4014586346786	TCT Ultra 35 core bit with 3/4" Weldon holder, Bore Ø 27 mm, Cutting depth 35 mm	20	28
6 31 27 730 01 0	4014586346793	TCT Ultra 35 core bit with 3/4" Weldon holder, Bore Ø 28 mm, Cutting depth 35 mm	20	28
6 31 27 731 01 0	4014586346809	TCT Ultra 35 core bit with 3/4" Weldon holder, Bore Ø 29 mm, Cutting depth 35 mm	20	28
6 31 27 732 01 0	4014586346816	TCT Ultra 35 core bit with 3/4" Weldon holder, Bore Ø 30 mm, Cutting depth 35 mm	20	28
6 31 27 733 01 0	4014586346823	TCT Ultra 35 core bit with 3/4" Weldon holder, Bore Ø 31 mm, Cutting depth 35 mm	20	28
6 31 27 734 01 0	4014586346830	TCT Ultra 35 core bit with 3/4" Weldon holder, Bore Ø 32 mm, Cutting depth 35 mm	20	28
6 31 27 735 01 0	4014586346847	TCT Ultra 35 core bit with 3/4" Weldon holder, Bore Ø 33 mm, Cutting depth 35 mm	20	28
6 31 27 736 01 0	4014586346854	TCT Ultra 35 core bit with 3/4" Weldon holder, Bore Ø 34 mm, Cutting depth 35 mm	20	28
6 31 27 737 01 0	4014586346861	TCT Ultra 35 core bit with 3/4" Weldon holder, Bore Ø 35 mm, Cutting depth 35 mm	20	28
6 31 27 738 01 0	4014586346878	TCT Ultra 35 core bit with 3/4" Weldon holder, Bore Ø 36 mm, Cutting depth 35 mm	20	28
6 31 27 739 01 0	4014586346885	TCT Ultra 35 core bit with 3/4" Weldon holder, Bore Ø 37 mm, Cutting depth 35 mm	20	28
6 31 27 740 01 0	4014586346892	TCT Ultra 35 core bit with 3/4" Weldon holder, Bore Ø 38 mm, Cutting depth 35 mm	20	28
6 31 27 741 01 0	4014586346908	TCT Ultra 35 core bit with 3/4" Weldon holder, Bore Ø 39 mm, Cutting depth 35 mm	20	28
6 31 27 742 01 0	4014586346915	TCT Ultra 35 core bit with 3/4" Weldon holder, Bore Ø 40 mm, Cutting depth 35 mm	20	28
6 31 27 743 01 0	4014586346922	TCT Ultra 35 core bit with 3/4" Weldon holder, Bore Ø 41 mm, Cutting depth 35 mm	20	28
6 31 27 744 01 0	4014586346939	TCT Ultra 35 core bit with 3/4" Weldon holder, Bore Ø 42 mm, Cutting depth 35 mm	20	28
6 31 27 745 01 0	4014586346946	TCT Ultra 35 core bit with 3/4" Weldon holder, Bore Ø 43 mm, Cutting depth 35 mm	20	28
6 31 27 746 01 0	4014586346953	TCT Ultra 35 core bit with 3/4" Weldon holder, Bore Ø 44 mm, Cutting depth 35 mm	20	28
6 31 27 747 01 0	4014586346960	TCT Ultra 35 core bit with 3/4" Weldon holder, Bore Ø 45 mm, Cutting depth 35 mm	20	28
6 31 27 748 01 0	4014586346977	TCT Ultra 35 core bit with 3/4" Weldon holder, Bore Ø 46 mm, Cutting depth 35 mm	20	28
6 31 27 749 01 0	4014586346984	TCT Ultra 35 core bit with 3/4" Weldon holder, Bore Ø 47 mm, Cutting depth 35 mm	20	28
6 31 27 750 01 0	4014586346991	TCT Ultra 35 core bit with 3/4" Weldon holder, Bore Ø 48 mm, Cutting depth 35 mm	20	28
6 31 27 751 01 0	4014586347004	TCT Ultra 35 core bit with 3/4" Weldon holder, Bore Ø 49 mm, Cutting depth 35 mm	20	28
6 31 27 752 01 0	4014586347011	TCT Ultra 35 core bit with 3/4" Weldon holder, Bore Ø 50 mm, Cutting depth 35 mm	20	28
6 31 27 753 01 0	4014586347028	TCT Ultra 35 core bit with 3/4" Weldon holder, Bore Ø 51 mm, Cutting depth 35 mm	20	52 52
6 31 27 754 01 0	4014586347035 4014586347042	TCT Ultra 35 core bit with 3/4" Weldon holder, Bore Ø 52 mm, Cutting depth 35 mm TCT Ultra 35 core bit with 3/4" Weldon holder, Bore Ø 53 mm, Cutting depth 35 mm	20	52
6 31 27 756 01 0	4014586347042	TCT Ultra 35 core bit with 3/4" Weldon holder, Bore Ø 53 mm, Cutting depth 35 mm TCT Ultra 35 core bit with 3/4" Weldon holder, Bore Ø 54 mm, Cutting depth 35 mm	20	52
6 31 27 757 01 0	4014586347059	TCT Ultra 35 core bit with 3/4" Weldon holder, Bore Ø 54 mm, Cutting depth 35 mm	20	52
6 31 27 758 01 0	4014586347073	TCT Ultra 35 core bit with 3/4" Weldon holder, Bore Ø 55 mm, Cutting depth 35 mm	20	52
2215/120010	TOT-10001/0/3	TO TORKE 30 COTE DICENTITY A MELECOTTHORIES, DOTE SO 30 HIRT, CARRING REPORT 33 HIRT		

Part number	EAN	Description	PC	Page
6 31 27 759 01 0	4014586347080	TCT Ultra 35 core bit with 3/4" Weldon holder, Bore \varnothing 57 mm, Cutting depth 35 mm	20	52
6 31 27 760 01 0	4014586347097	TCT Ultra 35 core bit with 3/4" Weldon holder, Bore Ø 58 mm, Cutting depth 35 mm	20	52
6 31 27 761 01 0	4014586347103	TCT Ultra 35 core bit with 3/4" Weldon holder, Bore Ø 59 mm, Cutting depth 35 mm	20	52
6 31 27 762 01 0	4014586347110	TCT Ultra 35 core bit with 3/4" Weldon holder, Bore Ø 60 mm, Cutting depth 35 mm	20	52
6 31 27 763 01 0	4014586353265	TCT Ultra 75 core bit with QuickIN holder, Bore Ø 18 mm, Cutting depth 75 mm	20	51
6 31 27 764 01 0	4014586353272	TCT Ultra 75 core bit with QuickIN holder, Bore Ø 19 mm, Cutting depth 75 mm	20	51
6 31 27 765 01 0	4014586353289	TCT Ultra 75 core bit with QuickIN holder, Bore Ø 20 mm, Cutting depth 75 mm	20	51
6 31 27 766 01 0	4014586353296	TCT Ultra 75 core bit with QuickIN holder, Bore Ø 21 mm, Cutting depth 75 mm	20	51
6 31 27 767 01 0	4014586353302 4014586353319	TCT Ultra 75 core bit with QuickIN holder, Bore Ø 22 mm, Cutting depth 75 mm	20	51 51
6 31 27 768 01 0	4014586353319	TCT Ultra 75 core bit with QuickIN holder, Bore Ø 23 mm, Cutting depth 75 mm TCT Ultra 75 core bit with QuickIN holder, Bore Ø 24 mm, Cutting depth 75 mm	20	51
6 31 27 770 01 0	4014586353333	TCT Ultra 75 core bit with QuickIN Holder, Bore Ø 25 mm, Cutting depth 75 mm	20	51
6 31 27 771 01 0	40145863533340	TCT Ultra 75 core bit with QuickIN holder, Bore Ø 26 mm, Cutting depth 75 mm	20	51
6 31 27 772 01 0	4014586353357	TCT Ultra 75 core bit with QuickIN holder, Bore Ø 27 mm, Cutting depth 75 mm	20	51
6 31 27 773 01 0	4014586353364	TCT Ultra 75 core bit with QuickIN holder, Bore Ø 28 mm, Cutting depth 75 mm	20	51
6 31 27 774 01 0	4014586353371	TCT Ultra 75 core bit with QuickIN holder, Bore Ø 29 mm, Cutting depth 75 mm	20	51
6 31 27 775 01 0	4014586353388	TCT Ultra 75 core bit with QuickIN holder, Bore Ø 30 mm, Cutting depth 75 mm	20	51
6 31 27 776 01 0	4014586353395	TCT Ultra 75 core bit with QuickIN holder, Bore Ø 32 mm, Cutting depth 75 mm	20	51
6 31 27 777 01 0	4014586353401	TCT Ultra 75 core bit with QuickIN holder, Bore Ø 35 mm, Cutting depth 75 mm	20	51
6 31 27 778 01 0	4014586353418	TCT Ultra 75 core bit with QuickIN holder, Bore Ø 36 mm, Cutting depth 75 mm	20	51
6 31 27 779 01 0	4014586353425	TCT Ultra 75 core bit with QuickIN holder, Bore Ø 40 mm, Cutting depth 75 mm	20	51
6 31 27 780 01 0	4014586353432	TCT Ultra 75 core bit with QuickIN holder, Bore Ø 45 mm, Cutting depth 75 mm	20	51
6 31 27 781 01 0	4014586353449	TCT Ultra 75 core bit with QuickIN holder, Bore Ø 50 mm, Cutting depth 75 mm	20	51
6 31 27 782 01 0	4014586353456	TCT Ultra 75 core bit with QuickIN holder, Bore Ø 55 mm, Cutting depth 75 mm	20	51
6 31 27 783 01 0	4014586353463	TCT Ultra 75 core bit with QuickIN holder, Bore Ø 60 mm, Cutting depth 75 mm	20	51
6 31 27 784 01 0	4014586353470	TCT Ultra 75 core bit with QuickIN holder, Bore Ø 65 mm, Cutting depth 75 mm	20	51
6 31 27 785 01 0	4014586353487	TCT Ultra 75 core bit with 3/4" Weldon holder, Bore Ø 18 mm, Cutting depth 75 mm	20	53
6 31 27 786 01 0	4014586353494	TCT Ultra 75 core bit with 3/4" Weldon holder, Bore Ø 19 mm, Cutting depth 75 mm	20	53
6 31 27 787 01 0	4014586353500	TCT Ultra 75 core bit with 3/4" Weldon holder, Bore Ø 20 mm, Cutting depth 75 mm	20	53
6 31 27 788 01 0	4014586353517	TCT Ultra 75 core bit with 3/4" Weldon holder, Bore Ø 21 mm, Cutting depth 75 mm	20	53
6 31 27 789 01 0	4014586353524	TCT Ultra 75 core bit with 3/4" Weldon holder, Bore Ø 22 mm, Cutting depth 75 mm	20	53
6 31 27 790 01 0	4014586353531	TCT Ultra 75 core bit with 3/4" Weldon holder, Bore \varnothing 23 mm, Cutting depth 75 mm	20	53
6 31 27 791 01 0	4014586353548	TCT Ultra 75 core bit with 3/4" Weldon holder, Bore Ø 24 mm, Cutting depth 75 mm	20	53
6 31 27 792 01 0	4014586353555	TCT Ultra 75 core bit with 3/4" Weldon holder, Bore Ø 25 mm, Cutting depth 75 mm	20	53
6 31 27 793 01 0	4014586353562	TCT Ultra 75 core bit with 3/4" Weldon holder, Bore Ø 26 mm, Cutting depth 75 mm	20	53
6 31 27 794 01 0	4014586353579	TCT Ultra 75 core bit with 3/4" Weldon holder, Bore Ø 27 mm, Cutting depth 75 mm	20	53
6 31 27 795 01 0	4014586353586	TCT Ultra 75 core bit with 3/4" Weldon holder, Bore Ø 28 mm, Cutting depth 75 mm	20	53
6 31 27 796 01 0	4014586353593	TCT Ultra 75 core bit with 3/4" Weldon holder, Bore Ø 29 mm, Cutting depth 75 mm	20	53
6 31 27 797 01 0	4014586353609	TCT Ultra 75 core bit with 3/4" Weldon holder, Bore Ø 30 mm, Cutting depth 75 mm	20	53
6 31 27 798 01 0	4014586353616	TCT Ultra 75 core bit with 3/4" Weldon holder, Bore Ø 32 mm, Cutting depth 75 mm	20	53
6 31 27 799 01 0	4014586353623	TCT Ultra 75 core bit with 3/4" Weldon holder, Bore Ø 35 mm, Cutting depth 75 mm	20	53
6 31 27 800 01 0	4014586353630	TCT Ultra 75 core bit with 3/4" Weldon holder, Bore Ø 36 mm, Cutting depth 75 mm	20	53
6 31 27 801 01 0	4014586353647	TCT Ultra 75 core bit with 3/4" Weldon holder, Bore Ø 40 mm, Cutting depth 75 mm	20	53
6 31 27 802 01 0	4014586353654	TCT Ultra 75 core bit with 3/4" Weldon holder, Bore Ø 45 mm, Cutting depth 75 mm	20	53
6 31 27 803 01 0	4014586353661	TCT Ultra 75 core bit with 3/4" Weldon holder, Bore Ø 50 mm, Cutting depth 75 mm	20	53
6 31 27 804 01 0	4014586353678	TCT Ultra 75 core bit with 3/4" Weldon holder, Bore Ø 55 mm, Cutting depth 75 mm	20	53
6 31 27 805 01 0	4014586353685	TCT Ultra 75 core bit with 3/4" Weldon holder, Bore Ø 60 mm, Cutting depth 75 mm	20	53
6 31 27 806 01 0	4014586353692	TCT Ultra 75 core bit with 3/4" Weldon holder, Bore Ø 65 mm, Cutting depth 75 mm	20	53
6 31 27 807 01 0	4014586424972	HM Ultra 50 core drill bit with QuickIN MAX/Weldon 32 fitting, Bore Ø 85 mm, Cutting depth 50 mm	20	53
6 31 27 808 01 0	4014586424989 4014586424996	HM Ultra 50 core drill bit with QuickIN MAX/Weldon 32 fitting, Bore Ø 90 mm, Cutting depth 50 mm	20	53
6 31 27 810 01 0	4014586424996	HM Ultra 50 core drill bit with QuickIN MAX/Weldon 32 fitting, Bore Ø 95 mm, Cutting depth 50 mm HM Ultra 50 core drill bit with QuickIN MAX/Weldon 32 fitting, Bore Ø 100 mm, Cutting depth 50 mm	20	53
6 31 27 810 01 0	4014586425009	HM Ultra 100 core drill bit with Weldon 32 fitting, Bore Ø 50 mm, Cutting depth 100 mm	20	53 54
6 31 27 812 01 0	4014586425016	HM Ultra 100 core drill bit with Weldon 32 fitting, Bore Ø 55 mm, Cutting depth 100 mm	20	54
6 31 27 813 01 0	4014586425030	HM Ultra 100 core drill bit with Weldon 32 fitting, Bore Ø 60 mm, Cutting depth 100 mm	20	54
6 31 27 814 01 0	4014586425047	HM Ultra 100 core drill bit with Weldon 32 fitting, Bore Ø 65 mm, Cutting depth 100 mm	20	54
6 31 27 815 01 0	4014586425054	HM Ultra 100 core drill bit with Weldon 32 fitting, Bore Ø 70 mm, Cutting depth 100 mm	20	54
6 31 27 816 01 0	4014586425061	HM Ultra 100 core drill bit with Weldon 32 fitting, Bore Ø 75 mm, Cutting depth 100 mm	20	54
6 31 27 817 01 0	4014586425078	HM Ultra 100 core drill bit with Weldon 32 fitting, Bore Ø 80 mm, Cutting depth 100 mm	20	54
6 31 27 818 01 0	4014586425085	HM Ultra 100 core drill bit with Weldon 32 fitting, Bore Ø 85 mm, Cutting depth 100 mm	20	54

Part number	EAN	Description	PC	Page
6 31 27 819 01 0	4014586425092	HM Ultra 100 core drill bit with Weldon 32 fitting, Bore Ø 90 mm, Cutting depth 100 mm	20	54
6 31 27 820 01 0	4014586425108	HM Ultra 100 core drill bit with Weldon 32 fitting, Bore \varnothing 95 mm, Cutting depth 100 mm	20	54
6 31 27 821 01 0	4014586425115	HM Ultra 100 core drill bit with Weldon 32 fitting, Bore Ø 100 mm, Cutting depth 100 mm	20	54
6 31 27 822 01 0	4014586425962	HM Ultra 50 core drill bit with QuickIN MAX/Weldon 32 fitting, Bore \varnothing 105 mm, Cutting depth 50 mm	20	53
6 31 27 823 01 0	4014586425979	HM Ultra 50 core drill bit with QuickIN MAX/Weldon 32 fitting, Bore Ø 110 mm, Cutting depth 50 mm	20	53
6 31 27 824 01 0	4014586425771	HM Ultra 100 core drill bit with Weldon 32 fitting, Bore Ø 105 mm, Cutting depth 100 mm	20	54
6 31 27 825 01 0	4014586425788	HM Ultra 100 core drill bit with Weldon 32 fitting, Bore Ø 110 mm, Cutting depth 100 mm	20	54
6 31 27 826 01 0	4014586437811	HM Ultra 100 core drill bit with Weldon 32 fitting, Bore Ø 74 mm, Cutting depth 100 mm	20	54
6 31 27 827 01 0	4014586437828	HM Ultra 100 core drill bit with Weldon 32 fitting, Bore Ø 82 mm, Cutting depth 100 mm	20	54
6 31 27 828 01 0	4014586445137	TCT Ultra 50 core bit with 3/4" Weldon holder, Bore Ø 15.5 mm, Cutting depth 50 mm	20	28
6 31 27 829 01 0	4014586445144	TCT Ultra 50 core bit with 3/4" Weldon holder, Bore Ø 17.5 mm, Cutting depth 50 mm	20	28
6 31 27 830 01 0	4014586445151	TCT Ultra 50 core bit with 3/4" Weldon holder, Bore Ø 19.5 mm, Cutting depth 50 mm	20	28
6 31 27 831 01 0	4014586445168	TCT Ultra 50 core bit with 3/4" Weldon holder, Bore Ø 26.5 mm, Cutting depth 50 mm	20	28
6 31 27 838 00 3	4014586469034	TCT Ultra 35 core bit with 3/4" Weldon holder, Bore Ø 14 mm, Cutting depth 35 mm	20	29
6 31 27 838 00 4	4014586469041	TCT Ultra 35 core bit with 3/4" Weldon holder, Bore Ø 16 mm, Cutting depth 35 mm	20	29
6 31 27 838 00 5	4014586469058	TCT Ultra 35 core bit with 3/4" Weldon holder, Bore Ø 17.5 mm, Cutting depth 35 mm	20	29
6 31 27 838 00 6	4014586469065	TCT Ultra 35 core bit with 3/4" Weldon holder, Bore Ø 18 mm, Cutting depth 35 mm	20	29
6 31 27 838 00 7	4014586469072	TCT Ultra 35 core bit with 3/4" Weldon holder, Bore Ø 20 mm, Cutting depth 35 mm	20	29
6 31 27 838 00 8	4014586469089	TCT Ultra 35 core bit with 3/4" Weldon holder, Bore Ø 21 mm, Cutting depth 35 mm	20	29
6 31 27 838 00 9	4014586469096	TCT Ultra 35 core bit with 3/4" Weldon holder, Bore Ø 22 mm, Cutting depth 35 mm	20	29
6 31 27 838 01 1	4014586469102	TCT Ultra 35 core bit with 3/4" Weldon holder, Bore Ø 24 mm, Cutting depth 35 mm	20	29
6 31 27 838 01 2	4014586469119	TCT Ultra 35 core bit with 3/4" Weldon holder, Bore Ø 25 mm, Cutting depth 35 mm	20	29
6 31 27 838 01 3	4014586469126	TCT Ultra 35 core bit with 3/4" Weldon holder, Bore Ø 26 mm, Cutting depth 35 mm	20	29
6 31 27 838 01 4	4014586469133	TCT Ultra 35 core bit with 3/4" Weldon holder, Bore Ø 26.5 mm, Cutting depth 35 mm	20	29
6 31 27 838 01 5	4014586469140	TCT Ultra 35 core bit with 3/4" Weldon holder, Bore Ø 28 mm, Cutting depth 35 mm	20	29
6 31 27 838 01 6	4014586469157	TCT Ultra 35 core bit with 3/4" Weldon holder, Bore Ø 30 mm, Cutting depth 35 mm	20	29
6 31 27 838 01 7	4014586469164	TCT Ultra 35 core bit with 3/4" Weldon holder, Bore Ø 32 mm, Cutting depth 35 mm	20	29
6 31 27 838 01 8	4014586469171	TCT Ultra 35 core bit with 3/4" Weldon holder, Bore Ø 33 mm, Cutting depth 35 mm	20	29
6 31 27 838 01 9	4014586469188	TCT Ultra 35 core bit with 3/4" Weldon holder, Bore Ø 34 mm, Cutting depth 35 mm	20	29
6 31 27 838 02 0	4014586469195	TCT Ultra 35 core bit with 3/4" Weldon holder, Bore Ø 35 mm, Cutting depth 35 mm	20	29
6 31 27 838 02 1	4014586469201	TCT Ultra 35 core bit with 3/4" Weldon holder, Bore Ø 36 mm, Cutting depth 35 mm	20	29
6 31 27 838 11 0	4014586470689	Accessory set for best of core drilling carbide coated 3/4" Weldon	20	28
6 31 30 014 01 0	4014586331034	Carbide core drill bit with QuickIN PLUS holder, Bore Ø 14 mm, Cutting depth 20 mm	20	89
6 31 30 015 01 0	4014586331041	Carbide core drill bit with QuickIN PLUS holder, Bore Ø 15 mm, Cutting depth 20 mm	20	89
6 31 30 016 01 0	4014586331058	Carbide core drill bit with QuickIN PLUS holder, Bore Ø 16 mm, Cutting depth 20 mm	20	89
6 31 30 017 01 0	4014586331065	Carbide core drill bit with QuickIN PLUS holder, Bore Ø 17 mm, Cutting depth 20 mm	20	89
6 31 30 018 01 0	4014586331072	Carbide core drill bit with QuickIN PLUS holder, Bore Ø 18 mm, Cutting depth 20 mm	20	89
6 31 30 019 01 0	4014586331089	Carbide core drill bit with QuickIN PLUS holder, Bore Ø 19 mm, Cutting depth 20 mm	20	89
6 31 30 020 01 0	4014586331096	Carbide core drill bit with QuickIN PLUS holder, Bore Ø 20 mm, Cutting depth 20 mm	20	89
6 31 30 021 01 0	4014586331102	Carbide core drill bit with QuickIN PLUS holder, Bore Ø 21 mm, Cutting depth 20 mm	20	89
6 31 30 022 01 0	4014586331119	Carbide core drill bit with QuickIN PLUS holder, Bore Ø 22 mm, Cutting depth 20 mm	20	89
6 31 30 023 01 0	4014586331126	Carbide core drill bit with QuickIN PLUS holder, Bore Ø 23 mm, Cutting depth 20 mm	20	89
6 31 30 024 01 0	4014586331133	Carbide core drill bit with QuickIN PLUS holder, Bore Ø 24 mm, Cutting depth 20 mm	20	89
6 31 30 025 01 0	4014586331140	Carbide core drill bit with QuickIN PLUS holder, Bore Ø 25 mm, Cutting depth 20 mm	20	89
6 31 30 026 01 0	4014586331157	Carbide core drill bit with QuickIN PLUS holder, Bore Ø 26 mm, Cutting depth 20 mm	20	89
6 31 30 027 01 0	4014586331164	Carbide core drill bit with QuickIN PLUS holder, Bore Ø 27 mm, Cutting depth 20 mm	20	89
6 31 30 028 01 0	4014586331171	Carbide core drill bit with QuickIN PLUS holder, Bore Ø 28 mm, Cutting depth 20 mm	20	89
6 31 30 029 01 0	4014586331188	Carbide core drill bit with QuickIN PLUS holder, Bore Ø 29 mm, Cutting depth 20 mm	20	89
6 31 30 030 01 0	4014586331195	Carbide core drill bit with QuickIN PLUS holder, Bore Ø 30 mm, Cutting depth 20 mm	20	89
6 31 30 115 51 0	4014586368986	Carbide core drill bit with TiAIN coating and QuickIN PLUS holder, Bore Ø 15.5 mm, Cutting depth 20 mm	20	_
6 31 30 117 51 0	4014586368993	Carbide core drill bit with TiAIN coating and QuickIN PLUS holder, Bore Ø 17.5 mm, Cutting depth 20 mm	20	
6 31 30 119 51 0	4014586369006	Carbide core drill bit with TiAIN coating and QuickIN PLUS holder, Bore Ø 19.5 mm, Cutting depth 20 mm	20	
		Carbide hole saw with QuickIN PLUS holder, Bore Ø 14 mm, Cutting depth 4 mm	20	88
6 31 31 014 01 0	4014586333274	Carbide note saw with Quickin FLOS house, bore & 14 min, Cutting depth 4 min		
6 31 31 014 01 0 6 31 31 015 01 0	4014586333274 4014586333281	Carbide hole saw with QuickIN PLUS holder, Bore Ø 15 mm, Cutting depth 4 mm	20	88
			20 20	
6 31 31 015 01 0	4014586333281	Carbide hole saw with QuickIN PLUS holder, Bore Ø 15 mm, Cutting depth 4 mm		88
6 31 31 015 01 0 6 31 31 016 01 0	4014586333281 4014586333298	Carbide hole saw with QuickIN PLUS holder, Bore Ø 15 mm, Cutting depth 4 mm Carbide hole saw with QuickIN PLUS holder, Bore Ø 16 mm, Cutting depth 4 mm	20	88 88
6 31 31 015 01 0 6 31 31 016 01 0 6 31 31 017 01 0	4014586333281 4014586333298 4014586333304	Carbide hole saw with QuickIN PLUS holder, Bore Ø 15 mm, Cutting depth 4 mm Carbide hole saw with QuickIN PLUS holder, Bore Ø 16 mm, Cutting depth 4 mm Carbide hole saw with QuickIN PLUS holder, Bore Ø 17 mm, Cutting depth 4 mm	20 20	88 88 88 88
6 31 31 015 01 0 6 31 31 016 01 0 6 31 31 017 01 0 6 31 31 018 01 0	4014586333281 4014586333298 4014586333304 40145863333311	Carbide hole saw with QuickIN PLUS holder, Bore Ø 15 mm, Cutting depth 4 mm Carbide hole saw with QuickIN PLUS holder, Bore Ø 16 mm, Cutting depth 4 mm Carbide hole saw with QuickIN PLUS holder, Bore Ø 17 mm, Cutting depth 4 mm Carbide hole saw with QuickIN PLUS holder, Bore Ø 18 mm, Cutting depth 4 mm	20 20 20	88 88 88

Part number	EAN	Description	PC	Page
6 31 31 022 01 0	4014586333342	Carbide hole saw with QuickIN PLUS holder, Bore Ø 22 mm, Cutting depth 4 mm	20	88
6 31 31 023 01 0	4014586333939	Carbide hole saw with QuickIN PLUS holder, Bore Ø 23 mm, Cutting depth 4 mm	20	88
6 31 31 024 01 0	4014586333359	Carbide hole saw with QuickIN PLUS holder, Bore Ø 24 mm, Cutting depth 4 mm	20	88
6 31 31 025 01 0	4014586333366	Carbide hole saw with QuickIN PLUS holder, Bore Ø 25 mm, Cutting depth 4 mm	20	88
6 31 31 026 01 0	4014586333373	Carbide hole saw with QuickIN PLUS holder, Bore Ø 26 mm, Cutting depth 4 mm	20	88
6 31 31 027 01 0	4014586333380	Carbide hole saw with QuickIN PLUS holder, Bore Ø 27 mm, Cutting depth 4 mm	20	88
6 31 31 028 01 0	4014586333946	Carbide hole saw with QuickIN PLUS holder, Bore Ø 28 mm, Cutting depth 4 mm	20	88
6 31 31 029 01 0	4014586333397	Carbide hole saw with QuickIN PLUS holder, Bore Ø 29 mm, Cutting depth 4 mm	20	88
6 31 31 030 01 0	4014586333403 4014586333953	Carbide hole saw with QuickIN PLUS holder, Bore Ø 30 mm, Cutting depth 4 mm	20	88
6 31 31 032 01 0	4014586333410	Carbide hole saw with QuickIN PLUS holder, Bore Ø 31 mm, Cutting depth 4 mm Carbide hole saw with QuickIN PLUS holder, Bore Ø 32 mm, Cutting depth 4 mm	20	88
6 31 31 033 01 0	4014586333427	Carbide hole saw with QuickIN PLUS holder, Bore Ø 33 mm, Cutting depth 4 mm	20	88
6 31 31 034 01 0	4014586333960	Carbide hole saw with QuickIN PLUS holder, Bore Ø 34 mm, Cutting depth 4 mm	20	88
6 31 31 035 01 0	4014586333434	Carbide hole saw with QuickIN PLUS holder, Bore Ø 35 mm, Cutting depth 4 mm	20	88
6 31 31 036 01 0	4014586333977	Carbide hole saw with QuickIN PLUS holder, Bore Ø 36 mm, Cutting depth 4 mm	20	88
6 31 31 037 01 0	4014586333441	Carbide hole saw with QuickIN PLUS holder, Bore Ø 37 mm, Cutting depth 4 mm	20	88
6 31 31 038 01 0	4014586333458	Carbide hole saw with QuickIN PLUS holder, Bore Ø 38 mm, Cutting depth 4 mm	20	88
6 31 31 039 01 0	4014586333984	Carbide hole saw with QuickIN PLUS holder, Bore Ø 39 mm, Cutting depth 4 mm	20	88
6 31 31 040 01 0	4014586333465	Carbide hole saw with QuickIN PLUS holder, Bore Ø 40 mm, Cutting depth 4 mm	20	88
6 31 31 041 01 0	4014586333991	Carbide hole saw with QuickIN PLUS holder, Bore Ø 41 mm, Cutting depth 4 mm	20	88
6 31 31 042 01 0	4014586333472	Carbide hole saw with QuickIN PLUS holder, Bore Ø 42 mm, Cutting depth 4 mm	20	88
6 31 31 043 01 0	4014586334004	Carbide hole saw with QuickIN PLUS holder, Bore Ø 43 mm, Cutting depth 4 mm	20	88
6 31 31 044 01 0	4014586333489	Carbide hole saw with QuickIN PLUS holder, Bore Ø 44 mm, Cutting depth 4 mm	20	88
6 31 31 045 01 0	4014586334011	Carbide hole saw with QuickIN PLUS holder, Bore Ø 45 mm, Cutting depth 4 mm	20	88
6 31 31 046 01 0	4014586334028	Carbide hole saw with QuickIN PLUS holder, Bore Ø 46 mm, Cutting depth 4 mm	20	88
6 31 31 047 01 0	4014586334035	Carbide hole saw with QuickIN PLUS holder, Bore Ø 47 mm, Cutting depth 4 mm	20	88
6 31 31 048 01 0	4014586334042	Carbide hole saw with QuickIN PLUS holder, Bore Ø 48 mm, Cutting depth 4 mm	20	88
6 31 31 049 01 0	4014586334059	Carbide hole saw with QuickIN PLUS holder, Bore Ø 49 mm, Cutting depth 4 mm	20	88
6 31 31 050 01 0	4014586333496	Carbide hole saw with QuickIN PLUS holder, Bore Ø 50 mm, Cutting depth 4 mm	20	88
6 31 31 051 01 0	4014586333502	Carbide hole saw with QuickIN PLUS holder, Bore Ø 51 mm, Cutting depth 4 mm	20	88
6 31 31 052 01 0	4014586334066	Carbide hole saw with QuickIN PLUS holder, Bore Ø 52 mm, Cutting depth 4 mm	20	88
6 31 31 053 01 0	4014586334073	Carbide hole saw with QuickIN PLUS holder, Bore Ø 53 mm, Cutting depth 4 mm	20	88
6 31 31 054 01 0	4014586333519	Carbide hole saw with QuickIN PLUS holder, Bore Ø 54 mm, Cutting depth 4 mm	20	88
6 31 31 055 01 0	4014586366470	Carbide hole saw with QuickIN PLUS holder, Bore Ø 55 mm, Cutting depth 4 mm	20	88
6 31 31 056 01 0	4014586366487	Carbide hole saw with QuickIN PLUS holder, Bore Ø 56 mm, Cutting depth 4 mm	20	88
6 31 31 057 01 0	4014586366494	Carbide hole saw with QuickIN PLUS holder, Bore Ø 57 mm, Cutting depth 4 mm	20	88
6 31 31 058 01 0	4014586366500	Carbide hole saw with QuickIN PLUS holder, Bore Ø 58 mm, Cutting depth 4 mm	20	88
6 31 31 059 01 0	4014586366517	Carbide hole saw with QuickIN PLUS holder, Bore Ø 59 mm, Cutting depth 4 mm	20	88
6 31 31 060 01 0	4014586366524	Carbide hole saw with QuickIN PLUS holder, Bore Ø 60 mm, Cutting depth 4 mm	20	88
6 31 31 065 01 0	4014586366531	Carbide hole saw with QuickIN PLUS holder, Bore Ø 65 mm, Cutting depth 4 mm	20	88
6 31 31 068 01 0	4014586366548	Carbide hole saw with QuickIN PLUS holder, Bore Ø 68 mm, Cutting depth 4 mm	20	88
6 31 31 070 01 0	4014586366555	Carbide hole saw with QuickIN PLUS holder, Bore Ø 70 mm, Cutting depth 4 mm	20	88
6 31 31 075 01 0	4014586366562	Carbide hole saw with QuickIN PLUS holder, Bore Ø 75 mm, Cutting depth 4 mm	20	88 88
	40145863366579 4014586333526	Carbide hole saw with QuickIN PLUS holder, Bore Ø 80 mm, Cutting depth 4 mm	20	88
6 31 31 421 01 0	4014586334349	Carbide hole saw for pipes with QuickIN PLUS holder, Bore Ø 21 mm, Cutting depth 4 mm Carbide hole saw for pipes with QuickIN PLUS holder, Bore Ø 22 mm, Cutting depth 4 mm	20	88
6 31 31 423 01 0	4014586334356	Carbide hole saw for pipes with QuickIN PLUS holder, Bore Ø 23 mm, Cutting depth 4 mm	20	88
6 31 31 424 01 0	4014586334363	Carbide hole saw for pipes with QuickIN PLUS holder, Bore Ø 24 mm, Cutting depth 4 mm	20	88
6 31 31 425 01 0	4014586333533	Carbide hole saw for pipes with QuickIN PLUS holder, Bore Ø 25 mm, Cutting depth 4 mm	20	88
6 31 31 426 01 0	4014586334370	Carbide hole saw for pipes with QuickIN PLUS holder, Bore Ø 26 mm, Cutting depth 4 mm	20	88
6 31 31 427 01 0	4014586333540	Carbide hole saw for pipes with QuickIN PLUS holder, Bore Ø 27 mm, Cutting depth 4 mm	20	88
6 31 31 428 01 0	4014586333557	Carbide hole saw for pipes with QuickIN PLUS holder, Bore Ø 28 mm, Cutting depth 4 mm	20	88
6 31 31 429 01 0	4014586334387	Carbide hole saw for pipes with QuickIN PLUS holder, Bore Ø 29 mm, Cutting depth 4 mm	20	88
6 31 31 430 01 0	4014586333564	Carbide hole saw for pipes with QuickIN PLUS holder, Bore Ø 30 mm, Cutting depth 4 mm	20	88
6 31 31 431 01 0	4014586334394	Carbide hole saw for pipes with QuickIN PLUS holder, Bore Ø 31 mm, Cutting depth 4 mm	20	88
6 31 31 432 01 0	4014586334400	Carbide hole saw for pipes with QuickIN PLUS holder, Bore Ø 32 mm, Cutting depth 4 mm	20	88
6 31 31 433 01 0	4014586333571	Carbide hole saw for pipes with QuickIN PLUS holder, Bore Ø 33 mm, Cutting depth 4 mm	20	88
6 31 31 434 01 0	4014586334417	Carbide hole saw for pipes with QuickIN PLUS holder, Bore Ø 34 mm, Cutting depth 4 mm	20	88
6 31 31 435 01 0	4014586333588	Carbide hole saw for pipes with QuickIN PLUS holder, Bore Ø 35 mm, Cutting depth 4 mm	20	88
6 31 31 436 01 0	4014586334424	Carbide hole saw for pipes with QuickIN PLUS holder, Bore Ø 36 mm, Cutting depth 4 mm	20	88

Part number	EAN	Description	PC	Page
6 31 31 437 01 0	4014586334431	Carbide hole saw for pipes with QuickIN PLUS holder, Bore Ø 37 mm, Cutting depth 4 mm	20	88
6 31 31 438 01 0	4014586334448	Carbide hole saw for pipes with QuickIN PLUS holder, Bore Ø 38 mm, Cutting depth 4 mm	20	88
6 31 31 439 01 0	4014586334455	Carbide hole saw for pipes with QuickIN PLUS holder, Bore Ø 39 mm, Cutting depth 4 mm	20	88
6 31 31 440 01 0	4014586333595	Carbide hole saw for pipes with QuickIN PLUS holder, Bore Ø 40 mm, Cutting depth 4 mm	20	88
6 31 31 441 01 0	4014586334462	Carbide hole saw for pipes with QuickIN PLUS holder, Bore Ø 41 mm, Cutting depth 4 mm	20	88
6 31 31 442 01 0	4014586333601	Carbide hole saw for pipes with QuickIN PLUS holder, Bore Ø 42 mm, Cutting depth 4 mm	20	88
6 31 31 443 01 0	4014586334479	Carbide hole saw for pipes with QuickIN PLUS holder, Bore Ø 43 mm, Cutting depth 4 mm	20	88
6 31 31 444 01 0	4014586334486	Carbide hole saw for pipes with QuickIN PLUS holder, Bore Ø 44 mm, Cutting depth 4 mm	20	88
6 31 31 445 01 0	4014586334493	Carbide hole saw for pipes with QuickIN PLUS holder, Bore Ø 45 mm, Cutting depth 4 mm	20	88
6 31 31 446 01 0	4014586334509	Carbide hole saw for pipes with QuickIN PLUS holder, Bore Ø 46 mm, Cutting depth 4 mm	20	88
6 31 31 447 01 0	4014586334516	Carbide hole saw for pipes with QuickIN PLUS holder, Bore Ø 47 mm, Cutting depth 4 mm	20	88
6 31 31 448 01 0	4014586333618	Carbide hole saw for pipes with QuickIN PLUS holder, Bore Ø 48 mm, Cutting depth 4 mm	20	88
6 31 31 449 01 0	4014586334523	Carbide hole saw for pipes with QuickIN PLUS holder, Bore Ø 49 mm, Cutting depth 4 mm	20	88
6 31 31 450 01 0	4014586333625	Carbide hole saw for pipes with QuickIN PLUS holder, Bore Ø 50 mm, Cutting depth 4 mm	20	88
6 31 31 451 01 0	4014586333632	Carbide hole saw for pipes with QuickIN PLUS holder, Bore Ø 51 mm, Cutting depth 4 mm	20	88
6 31 31 452 01 0	4014586334530	Carbide hole saw for pipes with QuickIN PLUS holder, Bore Ø 52 mm, Cutting depth 4 mm	20	88
6 31 31 453 01 0	4014586334547	Carbide hole saw for pipes with QuickIN PLUS holder, Bore Ø 53 mm, Cutting depth 4 mm	20	88
6 31 31 454 01 0	4014586333649	Carbide hole saw for pipes with QuickIN PLUS holder, Bore Ø 54 mm, Cutting depth 4 mm	20	88
6 31 31 455 01 0	4014586366678	Carbide hole saw for pipes with QuickIN PLUS holder, Bore Ø 55 mm, Cutting depth 4 mm	20	88
6 31 31 456 01 0	4014586366685	Carbide hole saw for pipes with QuickIN PLUS holder, Bore Ø 56 mm, Cutting depth 4 mm	20	88
6 31 31 457 01 0	4014586366692 4014586366708	Carbide hole saw for pipes with QuickIN PLUS holder, Bore Ø 57 mm, Cutting depth 4 mm	20	88
6 31 31 458 01 0		Carbide hole saw for pipes with QuickIN PLUS holder, Bore Ø 58 mm, Cutting depth 4 mm	20	88
6 31 31 459 01 0	4014586366715 4014586366722	Carbide hole saw for pipes with QuickIN PLUS holder, Bore Ø 59 mm, Cutting depth 4 mm	20	88 88
6 31 31 465 01 0	4014586366739	Carbide hole saw for pipes with QuickIN PLUS holder, Bore Ø 60 mm, Cutting depth 4 mm Carbide hole saw for pipes with QuickIN PLUS holder, Bore Ø 65 mm, Cutting depth 4 mm	20	88
6 31 31 468 01 0	4014586366746	Carbide hole saw for pipes with QuickIN PLUS holder, Bore Ø 68 mm, Cutting depth 4 mm	20	88
6 31 33 119 05 1	4014586611471	HSS Nova 25 core bit with QuickIN holder, Bore Ø 12 mm, Cutting depth 4 mm	20	54
6 31 33 119 05 2	4014586611501	HSS Nova 50 core bit with QuickIN holder, Bore Ø 12 mm, Cutting depth 50 mm	20	55
6 31 33 120 06 7	4014586615578	HSS Dura 25 core bit with QuickIN holder, Bore Ø 12 mm, Cutting depth 25 mm	20	57
6 31 33 120 06 8	4014586615639	HSS Dura 50 core bit with QuickIN holder, Bore Ø 12 mm, Cutting depth 50 mm	20	57
6 31 33 129 05 1	4014586611815	HSS Nova 25 core bit with QuickIN holder, Bore Ø 13 mm, Cutting depth 25 mm	20	54
6 31 33 129 05 2	4014586611853	HSS Nova 50 core bit with QuickIN holder, Bore Ø 13 mm, Cutting depth 50 mm	20	55
6 31 33 130 06 7	4014586611822	HSS Dura 25 core bit with QuickIN holder, Bore Ø 13 mm, Cutting depth 25 mm	20	57
6 31 33 130 06 8	4014586611860	HSS Dura 50 core bit with QuickIN holder, Bore Ø 13 mm, Cutting depth 50 mm	20	57
6 31 33 140 05 1	4014586611891	HSS Nova 25 core bit with QuickIN holder, Bore Ø 14 mm, Cutting depth 25 mm	20	54
6 31 33 140 05 2	4014586611938	HSS Nova 50 core bit with QuickIN holder, Bore Ø 14 mm, Cutting depth 50 mm	20	55
6 31 33 140 06 7	4014586611907	HSS Dura 25 core bit with QuickIN holder, Bore Ø 14 mm, Cutting depth 25 mm	20	57
6 31 33 140 06 8	4014586611945	HSS Dura 50 core bit with QuickIN holder, Bore Ø 14 mm, Cutting depth 50 mm	20	57
6 31 33 150 05 1	4014586612188	HSS Nova 25 core bit with QuickIN holder, Bore Ø 15 mm, Cutting depth 25 mm	20	54
6 31 33 150 05 2	4014586612225	HSS Nova 50 core bit with QuickIN holder, Bore Ø 15 mm, Cutting depth 50 mm	20	55
6 31 33 150 06 7	4014586612195	HSS Dura 25 core bit with QuickIN holder, Bore Ø 15 mm, Cutting depth 25 mm	20	57
6 31 33 150 06 8	4014586612232	HSS Dura 50 core bit with QuickIN holder, Bore Ø 15 mm, Cutting depth 50 mm	20	57
6 31 33 159 05 1	4014586612263	HSS Nova 25 core bit with QuickIN holder, Bore Ø 16 mm, Cutting depth 25 mm	20	54
6 31 33 159 05 2	4014586612300	HSS Nova 50 core bit with QuickIN holder, Bore Ø 16 mm, Cutting depth 50 mm	20	55
6 31 33 160 06 7	4014586612270	HSS Dura 25 core bit with QuickIN holder, Bore \emptyset 16 mm, Cutting depth 25 mm	20	57
6 31 33 160 06 8	4014586612317	HSS Dura 50 core bit with QuickIN holder, Bore Ø 16 mm, Cutting depth 50 mm	20	57
6 31 33 170 05 1	4014586612485	HSS Nova 25 core bit with QuickIN holder, Bore Ø 17 mm, Cutting depth 25 mm	20	54
6 31 33 170 05 2	4014586612522	HSS Nova 50 core bit with QuickIN holder, Bore Ø 17 mm, Cutting depth 50 mm	20	55
6 31 33 170 06 7	4014586612492	HSS Dura 25 core bit with QuickIN holder, Bore Ø 17 mm, Cutting depth 25 mm	20	57
6 31 33 170 06 8	4014586612539	HSS Dura 50 core bit with QuickIN holder, Bore Ø 17 mm, Cutting depth 50 mm	20	57
6 31 33 180 05 1	4014586612560	HSS Nova 25 core bit with QuickIN holder, Bore Ø 18 mm, Cutting depth 25 mm	20	54
6 31 33 180 05 2	4014586612607	HSS Nova 50 core bit with QuickIN holder, Bore Ø 18 mm, Cutting depth 50 mm	20	55
6 31 33 180 06 7	4014586612577	HSS Dura 25 core bit with QuickIN holder, Bore Ø 18 mm, Cutting depth 25 mm	20	57
6 31 33 180 06 8	4014586612614	HSS Dura 50 core bit with QuickIN holder, Bore Ø 18 mm, Cutting depth 50 mm	20	57
6 31 33 189 05 1	4014586612713	HSS Nova 25 core bit with QuickIN holder, Bore Ø 19 mm, Cutting depth 25 mm	20	54
6 31 33 189 05 2	4014586612751	HSS Nova 50 core bit with QuickIN holder, Bore Ø 19 mm, Cutting depth 50 mm	20	55
6 31 33 190 06 7	4014586612720	HSS Dura 25 core bit with QuickIN holder, Bore Ø 19 mm, Cutting depth 25 mm	20	57
6 31 33 190 06 8	4014586612768	HSS Dura 50 core bit with QuickIN holder, Bore Ø 19 mm, Cutting depth 50 mm	20	57
6 31 33 199 05 2	4014586612904	HSS Nova 50 core bit with QuickIN holder, Bore Ø 20 mm, Cutting depth 50 mm	20	55
6 31 33 199 06 3	4014586612874	HSS Nova 25 core bit with QuickIN holder, Bore Ø 20 mm, Cutting depth 25 mm	20	54

Part number	EAN	Description	PC	Page
6 31 33 200 06 7	4014586612867	HSS Dura 25 core bit with QuickIN holder, Bore Ø 20 mm, Cutting depth 25 mm	20	57
6 31 33 200 06 8	4014586612911	HSS Dura 50 core bit with QuickIN holder, Bore Ø 20 mm, Cutting depth 50 mm	20	57
6 31 33 210 05 1	4014586613123	HSS Nova 25 core bit with QuickIN holder, Bore Ø 21 mm, Cutting depth 25 mm	20	54
6 31 33 210 05 2	4014586613161	HSS Nova 50 core bit with QuickIN holder, Bore Ø 21 mm, Cutting depth 50 mm	20	55
6 31 33 210 06 7	4014586613130	HSS Dura 25 core bit with QuickIN holder, Bore Ø 21 mm, Cutting depth 25 mm	20	57
6 31 33 210 06 8	4014586613178	HSS Dura 50 core bit with QuickIN holder, Bore Ø 21 mm, Cutting depth 50 mm	20	57
6 31 33 219 05 1	4014586613215	HSS Nova 25 core bit with QuickIN holder, Bore Ø 22 mm, Cutting depth 25 mm	20	54
6 31 33 219 05 2	4014586613253 4014586613222	HSS Nova 50 core bit with QuickIN holder, Bore Ø 22 mm, Cutting depth 50 mm	20	55
6 31 33 220 06 7	4014586613222	HSS Dura 25 core bit with QuickIN holder, Bore Ø 22 mm, Cutting depth 25 mm HSS Dura 50 core bit with QuickIN holder, Bore Ø 22 mm, Cutting depth 50 mm	20	57 57
6 31 33 229 05 1	4014586613406	HSS Nova 25 core bit with QuickIN holder, Bore Ø 23 mm, Cutting depth 35 mm	20	5 <i>7</i>
6 31 33 229 05 2	4014586613444	HSS Nova 50 core bit with QuickIN holder, Bore Ø 23 mm, Cutting depth 50 mm	20	55
6 31 33 230 06 7	4014586613413	HSS Dura 25 core bit with QuickIN holder, Bore Ø 23 mm, Cutting depth 25 mm	20	57
6 31 33 230 06 8	4014586613451	HSS Dura 50 core bit with QuickIN holder, Bore Ø 23 mm, Cutting depth 50 mm	20	57
6 31 33 240 05 1	4014586613499	HSS Nova 25 core bit with QuickIN holder, Bore Ø 24 mm, Cutting depth 25 mm	20	54
6 31 33 240 05 2	4014586613536	HSS Nova 50 core bit with QuickIN holder, Bore Ø 24 mm, Cutting depth 50 mm	20	55
6 31 33 240 06 7	4014586613505	HSS Dura 25 core bit with QuickIN holder, Bore Ø 24 mm, Cutting depth 25 mm	20	57
6 31 33 240 06 8	4014586613543	HSS Dura 50 core bit with QuickIN holder, Bore Ø 24 mm, Cutting depth 50 mm	20	57
6 31 33 250 05 1	4014586613635	HSS Nova 25 core bit with QuickIN holder, Bore Ø 25 mm, Cutting depth 25 mm	20	54
6 31 33 250 05 2	4014586613673	HSS Nova 50 core bit with QuickIN holder, Bore Ø 25 mm, Cutting depth 50 mm	20	55
6 31 33 250 06 7	4014586613642	HSS Dura 25 core bit with QuickIN holder, Bore Ø 25 mm, Cutting depth 25 mm	20	57
6 31 33 250 06 8	4014586613680	HSS Dura 50 core bit with QuickIN holder, Bore Ø 25 mm, Cutting depth 50 mm	20	57
6 31 33 259 05 1	4014586613727	HSS Nova 25 core bit with QuickIN holder, Bore Ø 26 mm, Cutting depth 25 mm	20	54
6 31 33 259 05 2	4014586613765	HSS Nova 50 core bit with QuickIN holder, Bore Ø 26 mm, Cutting depth 50 mm	20	55
6 31 33 260 06 7	4014586613734	HSS Dura 25 core bit with QuickIN holder, Bore Ø 26 mm, Cutting depth 25 mm	20	57
6 31 33 260 06 8	4014586613772	HSS Dura 50 core bit with QuickIN holder, Bore Ø 26 mm, Cutting depth 50 mm	20	57
6 31 33 270 05 1	4014586613819	HSS Nova 25 core bit with QuickIN holder, Bore Ø 27 mm, Cutting depth 25 mm	20	54
6 31 33 270 05 2	4014586613857	HSS Nova 50 core bit with QuickIN holder, Bore Ø 27 mm, Cutting depth 50 mm	20	55
6 31 33 270 06 7	4014586613826	HSS Dura 25 core bit with QuickIN holder, Bore Ø 27 mm, Cutting depth 25 mm	20	57
6 31 33 270 06 8	4014586613864	HSS Dura 50 core bit with QuickIN holder, Bore Ø 27 mm, Cutting depth 50 mm	20	57
6 31 33 279 05 1	4014586613901	HSS Nova 25 core bit with QuickIN holder, Bore Ø 28 mm, Cutting depth 25 mm	20	54
6 31 33 279 05 2	4014586613949	HSS Nova 50 core bit with QuickIN holder, Bore Ø 28 mm, Cutting depth 50 mm	20	55
6 31 33 280 06 7	4014586613918	HSS Dura 25 core bit with QuickIN holder, Bore Ø 28 mm, Cutting depth 25 mm	20	57
6 31 33 280 06 8	4014586613956	HSS Dura 50 core bit with QuickIN holder, Bore Ø 28 mm, Cutting depth 50 mm	20	57
6 31 33 289 05 1	4014586613994	HSS Nova 25 core bit with QuickIN holder, Bore Ø 29 mm, Cutting depth 25 mm	20	54
6 31 33 289 05 2	4014586614038	HSS Nova 50 core bit with QuickIN holder, Bore Ø 29 mm, Cutting depth 50 mm	20	55
6 31 33 290 06 7	4014586614007	HSS Dura 25 core bit with QuickIN holder, Bore Ø 29 mm, Cutting depth 25 mm	20	57
6 31 33 290 06 8	4014586614045	HSS Dura 50 core bit with QuickIN holder, Bore Ø 29 mm, Cutting depth 50 mm	20	57
6 31 33 299 05 1	4014586614229	HSS Nova 25 core bit with QuickIN holder, Bore Ø 30 mm, Cutting depth 25 mm	20	54
6 31 33 299 05 2	4014586614267	HSS Nova 50 core bit with QuickIN holder, Bore Ø 30 mm, Cutting depth 50 mm	20	55
6 31 33 300 06 7	4014586614236	HSS Dura 25 core bit with QuickIN holder, Bore Ø 30 mm, Cutting depth 25 mm	20	57
6 31 33 300 06 8	4014586614274	HSS Dura 50 core bit with QuickIN holder, Bore Ø 30 mm, Cutting depth 50 mm	20	57
6 31 33 309 05 1	4014586614311 4014586614359	HSS Nova 25 core bit with QuickIN holder, Bore Ø 31 mm, Cutting depth 25 mm	20	54 55
6 31 33 309 05 2	4014586614328	HSS Nova 50 core bit with QuickIN holder, Bore Ø 31 mm, Cutting depth 50 mm HSS Dura 25 core bit with QuickIN holder, Bore Ø 31 mm, Cutting depth 25 mm	20	57
6 31 33 310 06 8	4014586614366	HSS Dura 50 core bit with QuickIN holder, Bore Ø 31 mm, Cutting depth 50 mm	20	57
6 31 33 319 05 1	4014586614397	HSS Nova 25 core bit with QuickIN holder, Bore Ø 32 mm, Cutting depth 25 mm	20	54
6 31 33 319 05 2	4014586614434	HSS Nova 50 core bit with QuickIN holder, Bore Ø 32 mm, Cutting depth 50 mm	20	55
6 31 33 320 06 7	4014586614403	HSS Dura 25 core bit with QuickIN holder, Bore Ø 32 mm, Cutting depth 25 mm	20	57
6 31 33 320 06 8	4014586614441	HSS Dura 50 core bit with QuickIN holder, Bore Ø 32 mm, Cutting depth 50 mm	20	57
6 31 33 329 05 1	4014586614489	HSS Nova 25 core bit with QuickIN holder, Bore Ø 33 mm, Cutting depth 25 mm	20	54
6 31 33 329 05 2	4014586614526	HSS Nova 50 core bit with QuickIN holder, Bore Ø 33 mm, Cutting depth 50 mm	20	55
6 31 33 330 06 8	4014586614533	HSS Dura 50 core bit with QuickIN holder, Bore Ø 33 mm, Cutting depth 50 mm	20	57
6 31 33 339 05 1	4014586614564	HSS Nova 25 core bit with QuickIN holder, Bore Ø 34 mm, Cutting depth 25 mm	20	54
6 31 33 339 05 2	4014586614601	HSS Nova 50 core bit with QuickIN holder, Bore Ø 34 mm, Cutting depth 50 mm	20	55
6 31 33 340 06 7	4014586614571	HSS Dura 25 core bit with QuickIN holder, Bore Ø 34 mm, Cutting depth 25 mm	20	57
6 31 33 340 06 8	4014586614618	HSS Dura 50 core bit with QuickIN holder, Bore Ø 34 mm, Cutting depth 50 mm	20	57
6 31 33 350 05 1	4014586614649	HSS Nova 25 core bit with QuickIN holder, Bore Ø 35 mm, Cutting depth 25 mm	20	54
6 31 33 350 05 2	4014586614687	HSS Nova 50 core bit with QuickIN holder, Bore Ø 35 mm, Cutting depth 50 mm	20	55
6 31 33 350 06 8	4014586614694	HSS Dura 50 core bit with QuickIN holder, Bore Ø 35 mm, Cutting depth 50 mm	20	57

Part number	EAN	Description	PC	Page
6 31 33 359 05 1	4014586614731	HSS Nova 25 core bit with QuickIN holder, Bore Ø 36 mm, Cutting depth 25 mm	20	54
6 31 33 359 05 2	4014586614779	HSS Nova 50 core bit with QuickIN holder, Bore Ø 36 mm, Cutting depth 50 mm	20	55
6 31 33 360 06 8	4014586614786	HSS Dura 50 core bit with QuickIN holder, Bore Ø 36 mm, Cutting depth 50 mm	20	57
6 31 33 369 05 1	4014586614823	HSS Nova 25 core bit with QuickIN holder, Bore Ø 37 mm, Cutting depth 25 mm	20	54
6 31 33 369 05 2	4014586614861	HSS Nova 50 core bit with QuickIN holder, Bore Ø 37 mm, Cutting depth 50 mm	20	55
6 31 33 370 06 7	4014586614830	HSS Dura 25 core bit with QuickIN holder, Bore Ø 37 mm, Cutting depth 25 mm	20	57
6 31 33 370 06 8	4014586614878	HSS Dura 50 core bit with QuickIN holder, Bore Ø 37 mm, Cutting depth 50 mm	20	57
6 31 33 379 05 1	4014586614908	HSS Nova 25 core bit with QuickIN holder, Bore Ø 38 mm, Cutting depth 25 mm	20	54
6 31 33 379 05 2	4014586614946	HSS Nova 50 core bit with QuickIN holder, Bore Ø 38 mm, Cutting depth 50 mm	20	55
6 31 33 380 06 8	4014586614953	HSS Dura 50 core bit with QuickIN holder, Bore Ø 38 mm, Cutting depth 50 mm	20	57
6 31 33 389 05 1	4014586614984	HSS Nova 25 core bit with QuickIN holder, Bore Ø 39 mm, Cutting depth 25 mm	20	54
6 31 33 389 05 2	4014586615028	HSS Nova 50 core bit with QuickIN holder, Bore Ø 39 mm, Cutting depth 50 mm	20	55
6 31 33 390 06 8	4014586615035	HSS Dura 50 core bit with QuickIN holder, Bore Ø 39 mm, Cutting depth 50 mm	20	57
6 31 33 399 05 1	4014586615066	HSS Nova 25 core bit with QuickIN holder, Bore Ø 40 mm, Cutting depth 25 mm	20	54
6 31 33 399 05 1		<u> </u>		
	4014586615103	HSS Nova 50 core bit with QuickIN holder, Bore Ø 40 mm, Cutting depth 50 mm	20	55
6 31 33 400 06 8	4014586615110	HSS Dura 50 core bit with QuickIN holder, Bore Ø 40 mm, Cutting depth 50 mm	20	57
6 31 33 409 05 1	4014586615158	HSS Nova 25 core bit with QuickIN holder, Bore Ø 41 mm, Cutting depth 25 mm	20	54
6 31 33 409 05 2	4014586615196	HSS Nova 50 core bit with QuickIN holder, Bore Ø 41 mm, Cutting depth 50 mm	20	55
6 31 33 410 06 8	4014586615202	HSS Dura 50 core bit with QuickIN holder, Bore Ø 41 mm, Cutting depth 50 mm	20	57
6 31 33 420 05 1	4014586615233	HSS Nova 25 core bit with QuickIN holder, Bore Ø 42 mm, Cutting depth 25 mm	20	54
6 31 33 420 05 2	4014586615271	HSS Nova 50 core bit with QuickIN holder, Bore Ø 42 mm, Cutting depth 50 mm	20	55
6 31 33 420 06 8	4014586615288	HSS Dura 50 core bit with QuickIN holder, Bore Ø 42 mm, Cutting depth 50 mm	20	57
6 31 33 429 05 1	4014586615318	HSS Nova 25 core bit with QuickIN holder, Bore Ø 43 mm, Cutting depth 25 mm	20	54
6 31 33 429 05 2	4014586615356	HSS Nova 50 core bit with QuickIN holder, Bore Ø 43 mm, Cutting depth 50 mm	20	55
6 31 33 430 06 7	4014586615325	HSS Dura 25 core bit with QuickIN holder, Bore Ø 43 mm, Cutting depth 25 mm	20	57
6 31 33 430 06 8	4014586615363	HSS Dura 50 core bit with QuickIN holder, Bore Ø 43 mm, Cutting depth 50 mm	20	57
6 31 33 439 05 1	4014586615394	HSS Nova 25 core bit with QuickIN holder, Bore Ø 44 mm, Cutting depth 25 mm	20	54
6 31 33 439 05 2	4014586615431	HSS Nova 50 core bit with QuickIN holder, Bore Ø 44 mm, Cutting depth 50 mm	20	55
6 31 33 440 06 7	4014586615400	HSS Dura 25 core bit with QuickIN holder, Bore Ø 44 mm, Cutting depth 25 mm	20	57
6 31 33 440 06 8	4014586615448	HSS Dura 50 core bit with QuickIN holder, Bore Ø 44 mm, Cutting depth 50 mm	20	57
6 31 33 449 05 1	4014586615479	HSS Nova 25 core bit with QuickIN holder, Bore Ø 45 mm, Cutting depth 25 mm	20	54
6 31 33 449 05 2	4014586615516	HSS Nova 50 core bit with QuickIN holder, Bore Ø 45 mm, Cutting depth 50 mm	20	55
6 31 33 450 06 7	4014586615486	HSS Dura 25 core bit with QuickIN holder, Bore Ø 45 mm, Cutting depth 25 mm	20	57
6 31 33 450 06 8	4014586615523	HSS Dura 50 core bit with QuickIN holder, Bore Ø 45 mm, Cutting depth 50 mm	20	57
6 31 33 459 05 1	4014586615561	HSS Nova 25 core bit with QuicklN holder, Bore Ø 46 mm, Cutting depth 25 mm	20	54
6 31 33 459 05 2	4014586615622	HSS Nova 50 core bit with QuickIN holder, Bore Ø 46 mm, Cutting depth 50 mm	20	55
6 31 33 460 06 7	4014586615585	HSS Dura 25 core bit with QuickIN holder, Bore Ø 46 mm, Cutting depth 25 mm	20	57
6 31 33 460 06 8		HSS Dura 50 core bit with QuickIN holder, Bore Ø 46 mm, Cutting depth 50 mm		57
	4014586615646		20	
6 31 33 469 05 1	4014586615684	HSS Nova 25 core bit with QuickIN holder, Bore Ø 47 mm, Cutting depth 25 mm	20	54
6 31 33 469 05 2	4014586615721	HSS Nova 50 core bit with QuickIN holder, Bore Ø 47 mm, Cutting depth 50 mm	20	55
6 31 33 470 06 7	4014586615691	HSS Dura 25 core bit with QuickIN holder, Bore Ø 47 mm, Cutting depth 25 mm	20	57
6 31 33 470 06 8	4014586615738	HSS Dura 50 core bit with QuickIN holder, Bore Ø 47 mm, Cutting depth 50 mm	20	57
6 31 33 479 05 1	4014586615769	HSS Nova 25 core bit with QuickIN holder, Bore Ø 48 mm, Cutting depth 25 mm	20	54
6 31 33 479 05 2	4014586615806	HSS Nova 50 core bit with QuickIN holder, Bore Ø 48 mm, Cutting depth 50 mm	20	55
6 31 33 480 06 7	4014586615776	HSS Dura 25 core bit with QuickIN holder, Bore Ø 48 mm, Cutting depth 25 mm	20	57
6 31 33 480 06 8	4014586615813	HSS Dura 50 core bit with QuickIN holder, Bore Ø 48 mm, Cutting depth 50 mm	20	57
6 31 33 489 05 1	4014586615844	HSS Nova 25 core bit with QuickIN holder, Bore Ø 49 mm, Cutting depth 25 mm	20	54
6 31 33 489 05 2	4014586615882	HSS Nova 50 core bit with QuickIN holder, Bore Ø 49 mm, Cutting depth 50 mm	20	55
6 31 33 490 06 7	4014586615851	HSS Dura 25 core bit with QuickIN holder, Bore Ø 49 mm, Cutting depth 25 mm	20	57
6 31 33 490 06 8	4014586615899	HSS Dura 50 core bit with QuickIN holder, Bore Ø 49 mm, Cutting depth 50 mm	20	57
6 31 33 499 05 1	4014586615981	HSS Nova 25 core bit with QuickIN holder, Bore Ø 50 mm, Cutting depth 25 mm	20	54
6 31 33 499 05 2	4014586616018	HSS Nova 50 core bit with QuickIN holder, Bore Ø 50 mm, Cutting depth 50 mm	20	55
6 31 33 500 06 7	4014586615592	HSS Dura 25 core bit with QuickIN holder, Bore Ø 50 mm, Cutting depth 25 mm	20	57
6 31 33 500 06 8	4014586615653	HSS Dura 50 core bit with QuickIN holder, Bore Ø 50 mm, Cutting depth 50 mm	20	57
6 31 33 999 01 0	4014586375571	Best of core bits QuickIN	20	54
6 31 34 120 05 1	4014586611457	HSS Nova 25 core bit with 3/4" Weldon holder, Bore Ø 12 mm, Cutting depth 25 mm	20	29
6 31 34 120 05 2	4014586611488	HSS Nova 50 core bit with 3/4" Weldon holder, Bore Ø 12 mm, Cutting depth 50 mm	20	30
6 31 34 120 07 5	4014586611464	HSS Dura 25 core bit with 3/4" Weldon holder, Bore Ø 12 mm, Cutting depth 25 mm	20	31
6 31 34 120 07 6	4014586611495	HSS Dura 50 core bit with 3/4" Weldon holder, Bore Ø 12 mm, Cutting depth 50 mm	20	31
6 31 34 120 07 0	4014586635064		20	30
0.01.04.150.20.1	4014700072004	HSS SPECIAL 25 core bit with 3/4" Weldon fitting, Bore Ø 12 mm, Cutting depth 25 mm	20	

Part number	EAN	Description	PC	Page
6 31 34 120 30 2	4014586470825	HSS SPECIAL 50 core drill bit with 3/4" Weldon fitting, Bore Ø 12 mm, Cutting depth 50 mm	20	30
6 31 34 130 05 1	4014586611792	HSS Nova 25 core bit with 3/4" Weldon holder, Bore Ø 13 mm, Cutting depth 25 mm	20	29
6 31 34 130 05 2	4014586611839	HSS Nova 50 core bit with 3/4" Weldon holder, Bore Ø 13 mm, Cutting depth 50 mm	20	30
6 31 34 130 07 5	4014586611808	HSS Dura 25 core bit with 3/4" Weldon holder, Bore Ø 13 mm, Cutting depth 25 mm	20	31
6 31 34 130 07 6	4014586611846	HSS Dura 50 core bit with 3/4" Weldon holder, Bore Ø 13 mm, Cutting depth 50 mm	20	31
6 31 34 130 30 1	4014586635071	HSS SPECIAL 25 core bit with 3/4" Weldon fitting, Bore Ø 13 mm, Cutting depth 25 mm	20	30
6 31 34 130 30 2	4014586469522	HSS SPECIAL 50 core drill bit with 3/4" Weldon fitting, Bore Ø 13 mm, Cutting depth 50 mm	20	30 29
6 31 34 140 05 1	4014586611877 4014586611914	HSS Nova 25 core bit with 3/4" Weldon holder, Bore Ø 14 mm, Cutting depth 25 mm HSS Nova 50 core bit with 3/4" Weldon holder, Bore Ø 14 mm, Cutting depth 50 mm	20	30
6 31 34 140 07 5	4014586611884	HSS Dura 25 core bit with 3/4" Weldon holder, Bore Ø 14 mm, Cutting depth 35 mm	20	31
6 31 34 140 07 6	4014586611921	HSS Dura 50 core bit with 3/4" Weldon holder, Bore Ø 14 mm, Cutting depth 50 mm	20	31
6 31 34 140 30 1	4014586635088	HSS SPECIAL 25 core bit with 3/4" Weldon fitting, Bore Ø 14 mm, Cutting depth 25 mm	20	30
6 31 34 140 30 2	4014586469539	HSS SPECIAL 50 core drill bit with 3/4" Weldon fitting, Bore Ø 14 mm, Cutting depth 50 mm	20	30
6 31 34 143 30 1	4014586635354	HSS SPECIAL 25 core bit with 3/4" Weldon fitting, Bore Ø 14.3 mm, Cutting depth 25 mm	20	30
6 31 34 150 05 1	4014586612164	HSS Nova 25 core bit with 3/4" Weldon holder, Bore Ø 15 mm, Cutting depth 25 mm	20	29
6 31 34 150 05 2	4014586612201	HSS Nova 50 core bit with 3/4" Weldon holder, Bore Ø 15 mm, Cutting depth 50 mm	20	30
6 31 34 150 07 5	4014586612171	HSS Dura 25 core bit with 3/4" Weldon holder, Bore Ø 15 mm, Cutting depth 25 mm	20	31
6 31 34 150 07 6	4014586612218	HSS Dura 50 core bit with 3/4" Weldon holder, Bore Ø 15 mm, Cutting depth 50 mm	20	31
6 31 34 150 30 1	4014586635095	HSS SPECIAL 25 core bit with 3/4" Weldon fitting, Bore Ø 15 mm, Cutting depth 25 mm	20	30
6 31 34 150 30 2	4014586469546	HSS SPECIAL 50 core drill bit with 3/4" Weldon fitting, Bore Ø 15 mm, Cutting depth 50 mm	20	30
6 31 34 160 05 1	4014586612249	HSS Nova 25 core bit with 3/4" Weldon holder, Bore Ø 16 mm, Cutting depth 25 mm	20	29
6 31 34 160 05 2	4014586612287	HSS Nova 50 core bit with 3/4" Weldon holder, Bore Ø 16 mm, Cutting depth 50 mm	20	30
6 31 34 160 07 5	4014586612256	HSS Dura 25 core bit with 3/4" Weldon holder, Bore Ø 16 mm, Cutting depth 25 mm	20	31
6 31 34 160 07 6	4014586612294	HSS Dura 50 core bit with 3/4" Weldon holder, Bore Ø 16 mm, Cutting depth 50 mm	20	31
6 31 34 160 30 1	4014586635101	HSS SPECIAL 25 core bit with 3/4" Weldon fitting, Bore Ø 16 mm, Cutting depth 25 mm	20	30
6 31 34 160 30 2	4014586469553	HSS SPECIAL 50 core drill bit with 3/4" Weldon fitting, Bore Ø 16 mm, Cutting depth 50 mm	20	30
6 31 34 170 05 1	4014586612461	HSS Nova 25 core bit with 3/4" Weldon holder, Bore Ø 17 mm, Cutting depth 25 mm	20	29
6 31 34 170 05 2	4014586612508	HSS Nova 50 core bit with 3/4" Weldon holder, Bore Ø 17 mm, Cutting depth 50 mm	20	30
6 31 34 170 07 5	4014586612478	HSS Dura 25 core bit with 3/4" Weldon holder, Bore Ø 17 mm, Cutting depth 25 mm	20	31
6 31 34 170 07 6	4014586612515	HSS Dura 50 core bit with 3/4" Weldon holder, Bore Ø 17 mm, Cutting depth 50 mm	20	31
6 31 34 170 30 1	4014586635118	HSS SPECIAL 25 core bit with 3/4" Weldon fitting, Bore Ø 17 mm, Cutting depth 25 mm	20	30
6 31 34 170 30 2	4014586469560	HSS SPECIAL 50 core drill bit with 3/4" Weldon fitting, Bore Ø 17 mm, Cutting depth 50 mm	20	30
6 31 34 180 05 1	4014586612546	HSS Nova 25 core bit with 3/4" Weldon holder, Bore Ø 18 mm, Cutting depth 25 mm	20	29
6 31 34 180 05 2	4014586612584	HSS Nova 50 core bit with 3/4" Weldon holder, Bore Ø 18 mm, Cutting depth 50 mm	20	30
6 31 34 180 07 5	4014586612553	HSS Dura 25 core bit with 3/4" Weldon holder, Bore Ø 18 mm, Cutting depth 25 mm	20	31
6 31 34 180 07 6	4014586612591	HSS Dura 50 core bit with 3/4" Weldon holder, Bore Ø 18 mm, Cutting depth 50 mm	20	31
6 31 34 180 30 1	4014586635125	HSS SPECIAL 25 core bit with 3/4" Weldon fitting, Bore Ø 18 mm, Cutting depth 25 mm	20	30
6 31 34 180 30 2	4014586469577	HSS SPECIAL 50 core drill bit with 3/4" Weldon fitting, Bore Ø 18 mm, Cutting depth 50 mm	20	30
6 31 34 190 05 1	4014586612690	HSS Nova 25 core bit with 3/4" Weldon holder, Bore Ø 19 mm, Cutting depth 25 mm	20	29
6 31 34 190 05 2	4014586612737	HSS Nova 50 core bit with 3/4" Weldon holder, Bore Ø 19 mm, Cutting depth 50 mm	20	30
6 31 34 190 05 3	4014586612775	HSS Nova 75 core bit with 3/4" Weldon holder, Bore Ø 19 mm, Cutting depth 75 mm	20	56
6 31 34 190 07 5	4014586612706 4014586612744	HSS Dura 25 core bit with 3/4" Weldon holder, Bore Ø 19 mm, Cutting depth 25 mm	20	31
6 31 34 200 05 1	4014586612843	HSS Dura 50 core bit with 3/4" Weldon holder, Bore Ø 19 mm, Cutting depth 50 mm HSS Nova 25 core bit with 3/4" Weldon holder, Bore Ø 20 mm, Cutting depth 25 mm	20	29
6 31 34 200 05 2	4014586612881	HSS Nova 50 core bit with 3/4" Weldon holder, Bore Ø 20 mm, Cutting depth 50 mm	20	30
6 31 34 200 05 3	4014586612928	HSS Nova 75 core bit with 3/4" Weldon holder, Bore Ø 20 mm, Cutting depth 75 mm	20	56
6 31 34 200 07 5	4014586612850	HSS Dura 25 core bit with 3/4" Weldon holder, Bore Ø 20 mm, Cutting depth 25 mm	20	31
6 31 34 200 07 6	4014586612898	HSS Dura 50 core bit with 3/4" Weldon holder, Bore Ø 20 mm, Cutting depth 50 mm	20	31
6 31 34 200 30 1	4014586635132	HSS SPECIAL 25 core bit with 3/4" Weldon fitting, Bore Ø 20 mm, Cutting depth 25 mm	20	30
6 31 34 200 30 2	4014586469584	HSS SPECIAL 50 core drill bit with 3/4" Weldon fitting, Bore Ø 20 mm, Cutting depth 50 mm	20	30
6 31 34 210 05 1	4014586613109	HSS Nova 25 core bit with 3/4" Weldon holder, Bore Ø 21 mm, Cutting depth 25 mm	20	29
6 31 34 210 05 2	4014586613147	HSS Nova 50 core bit with 3/4" Weldon holder, Bore Ø 21 mm, Cutting depth 50 mm	20	30
6 31 34 210 05 3	4014586613185	HSS Nova 75 core bit with 3/4" Weldon holder, Bore Ø 21 mm, Cutting depth 75 mm	20	56
6 31 34 210 05 4	4014586470832	HSS NOVA 100 core drill bit with 3/4" Weldon fitting, Bore Ø 21 mm, Cutting depth 100 mm	20	56
6 31 34 210 07 5	4014586613116	HSS Dura 25 core bit with 3/4" Weldon holder, Bore Ø 21 mm, Cutting depth 25 mm	20	31
6 31 34 210 07 6	4014586613154	HSS Dura 50 core bit with 3/4" Weldon holder, Bore Ø 21 mm, Cutting depth 50 mm	20	31
6 31 34 220 05 1	4014586613192	HSS Nova 25 core bit with 3/4" Weldon holder, Bore Ø 22 mm, Cutting depth 25 mm	20	29
6 31 34 220 05 2	4014586613239	HSS Nova 50 core bit with 3/4" Weldon holder, Bore Ø 22 mm, Cutting depth 50 mm	20	30
6 31 34 220 05 3	4014586613277	HSS Nova 75 core bit with 3/4" Weldon holder, Bore Ø 22 mm, Cutting depth 75 mm	20	56
6 31 34 220 05 4	4014586469591	Bore Ø 22 mm, Cutting depth 100 mm	20	56

Part number	EAN	Description	PC	Page
6 31 34 220 07 5	4014586613208	HSS Dura 25 core bit with 3/4" Weldon holder, Bore \varnothing 22 mm, Cutting depth 25 mm	20	31
6 31 34 220 07 6	4014586613246	HSS Dura 50 core bit with 3/4" Weldon holder, Bore Ø 22 mm, Cutting depth 50 mm	20	31
6 31 34 220 30 1	4014586635149	HSS SPECIAL 25 core bit with 3/4" Weldon fitting, Bore Ø 22 mm, Cutting depth 25 mm	20	30
6 31 34 220 30 2	4014586469607	HSS SPECIAL 50 core drill bit with 3/4" Weldon fitting, Bore Ø 22 mm, Cutting depth 50 mm	20	30
6 31 34 230 05 1	4014586613383	HSS Nova 25 core bit with 3/4" Weldon holder, Bore Ø 23 mm, Cutting depth 25 mm	20	29
6 31 34 230 05 2	4014586613420	HSS Nova 50 core bit with 3/4" Weldon holder, Bore Ø 23 mm, Cutting depth 50 mm	20	30
6 31 34 230 05 3	4014586613468	HSS Nova 75 core bit with 3/4" Weldon holder, Bore Ø 23 mm, Cutting depth 75 mm	20	56
6 31 34 230 05 4	4014586469614	HSS NOVA 100 core drill bit with 3/4" Weldon fitting, Bore Ø 23 mm, Cutting depth 100 mm	20	56
6 31 34 230 07 5	4014586613390	HSS Dura 25 core bit with 3/4" Weldon holder, Bore Ø 23 mm, Cutting depth 25 mm	20	31
6 31 34 230 07 6	4014586613437	HSS Dura 50 core bit with 3/4" Weldon holder, Bore Ø 23 mm, Cutting depth 50 mm	20	31
6 31 34 240 05 1	4014586613475	HSS Nova 25 core bit with 3/4" Weldon holder, Bore Ø 24 mm, Cutting depth 25 mm	20	29
6 31 34 240 05 2	4014586613512	HSS Nova 50 core bit with 3/4" Weldon holder, Bore Ø 24 mm, Cutting depth 50 mm	20	30
6 31 34 240 05 3	4014586613550	HSS Nova 75 core bit with 3/4" Weldon holder, Bore Ø 24 mm, Cutting depth 75 mm	20	56
6 31 34 240 05 4	4014586469621 4014586613482	HSS NOVA 100 core drill bit with 3/4" Weldon fitting, Bore Ø 24 mm, Cutting depth 100 mm HSS Dura 25 core bit with 3/4" Weldon holder, Bore Ø 24 mm, Cutting depth 25 mm	20	56
6 31 34 240 07 6	4014586613482	HSS Dura 50 core bit with 3/4" Weldon holder, Bore Ø 24 mm, Cutting depth 23 mm	20	31 31
6 31 34 240 07 0	4014586635156	HSS SPECIAL 25 core bit with 3/4" Weldon fitting, Bore Ø 24 mm, Cutting depth 30 mm	20	30
6 31 34 240 30 1	4014586469638	HSS SPECIAL 23 core bit with 3/4" Weldon fitting, Bore Ø 24 mm, Cutting depth 23 mm	02	30
6 31 34 250 05 1	4014586613611	HSS Nova 25 core bit with 3/4" Weldon holder, Bore Ø 25 mm, Cutting depth 30 mm	20	
6 31 34 250 05 2	4014586613659	HSS Nova 50 core bit with 3/4" Weldon holder, Bore Ø 25 mm, Cutting depth 50 mm	20	30
6 31 34 250 05 3	4014586613697	HSS Nova 75 core bit with 3/4" Weldon holder, Bore Ø 25 mm, Cutting depth 75 mm	20	56
6 31 34 250 05 4	4014586469645	HSS NOVA 100 core drill bit with 3/4" Weldon fitting, Bore Ø 25 mm, Cutting depth 100 mm	20	 56
6 31 34 250 07 5	4014586613628	HSS Dura 25 core bit with 3/4" Weldon holder, Bore Ø 25 mm, Cutting depth 25 mm	20	31
6 31 34 250 07 6	4014586613666	HSS Dura 50 core bit with 3/4" Weldon holder, Bore Ø 25 mm, Cutting depth 50 mm	20	31
6 31 34 260 05 1	4014586613703	HSS Nova 25 core bit with 3/4" Weldon holder, Bore Ø 26 mm, Cutting depth 25 mm	20	29
6 31 34 260 05 2	4014586613741	HSS Nova 50 core bit with 3/4" Weldon holder, Bore Ø 26 mm, Cutting depth 50 mm	20	30
6 31 34 260 05 3	4014586613789	HSS Nova 75 core bit with 3/4" Weldon holder, Bore Ø 26 mm, Cutting depth 75 mm	20	56
6 31 34 260 05 4	4014586469652	HSS NOVA 100 core drill bit with 3/4" Weldon fitting, Bore Ø 26 mm, Cutting depth 100 mm	20	56
6 31 34 260 07 5	4014586613710	HSS Dura 25 core bit with 3/4" Weldon holder, Bore Ø 26 mm, Cutting depth 25 mm	20	31
6 31 34 260 07 6	4014586613758	HSS Dura 50 core bit with 3/4" Weldon holder, Bore Ø 26 mm, Cutting depth 50 mm	20	31
6 31 34 260 30 1	4014586635163	HSS SPECIAL 25 core bit with 3/4" Weldon fitting, Bore Ø 26 mm, Cutting depth 25 mm	20	30
6 31 34 260 30 2	4014586469669	HSS SPECIAL 50 core drill bit with 3/4" Weldon fitting, Bore Ø 26 mm, Cutting depth 50 mm	20	30
6 31 34 270 05 1	4014586613796	HSS Nova 25 core bit with 3/4" Weldon holder, Bore Ø 27 mm, Cutting depth 25 mm	20	29
6 31 34 270 05 2	4014586613833	HSS Nova 50 core bit with 3/4" Weldon holder, Bore Ø 27 mm, Cutting depth 50 mm	20	30
6 31 34 270 05 3	4014586613871	HSS Nova 75 core bit with 3/4" Weldon holder, Bore Ø 27 mm, Cutting depth 75 mm	20	56
6 31 34 270 05 4	4014586469676	HSS NOVA 100 core drill bit with 3/4" Weldon fitting, Bore Ø 27 mm, Cutting depth 100 mm	20	56
6 31 34 270 07 5	4014586613802	HSS Dura 25 core bit with 3/4" Weldon holder, Bore Ø 27 mm, Cutting depth 25 mm		31
6 31 34 270 07 6	4014586613840	HSS Dura 50 core bit with 3/4" Weldon holder, Bore Ø 27 mm, Cutting depth 50 mm	20	
6 31 34 280 05 1		1133 Dura 30 core bit with 3/4 Wetdorfflotder, bore \$27 film, Cutting depth 30 film	20	31
	4014586613888	HSS Nova 25 core bit with 3/4" Weldon holder, Bore Ø 28 mm, Cutting depth 30 mm		31 29
6 31 34 280 05 2	4014586613888 4014586613925		20	
6 31 34 280 05 2 6 31 34 280 05 3		HSS Nova 25 core bit with 3/4" Weldon holder, Bore Ø 28 mm, Cutting depth 25 mm	20 20	29
	4014586613925	HSS Nova 25 core bit with 3/4" Weldon holder, Bore Ø 28 mm, Cutting depth 25 mm HSS Nova 50 core bit with 3/4" Weldon holder, Bore Ø 28 mm, Cutting depth 50 mm	20 20 20	29 30
6 31 34 280 05 3 6 31 34 280 05 4 6 31 34 280 07 5	4014586613925 4014586613963 4014586469683 4014586613895	HSS Nova 25 core bit with 3/4" Weldon holder, Bore Ø 28 mm, Cutting depth 25 mm HSS Nova 50 core bit with 3/4" Weldon holder, Bore Ø 28 mm, Cutting depth 50 mm HSS Nova 75 core bit with 3/4" Weldon holder, Bore Ø 28 mm, Cutting depth 75 mm	20 20 20 20 20 20 20	29 30 56
6 31 34 280 05 3 6 31 34 280 05 4 6 31 34 280 07 5 6 31 34 280 07 6	4014586613925 4014586613963 4014586469683 4014586613895 4014586613932	HSS Nova 25 core bit with 3/4" Weldon holder, Bore Ø 28 mm, Cutting depth 25 mm HSS Nova 50 core bit with 3/4" Weldon holder, Bore Ø 28 mm, Cutting depth 50 mm HSS Nova 75 core bit with 3/4" Weldon holder, Bore Ø 28 mm, Cutting depth 75 mm HSS NOVA 100 core drill bit with 3/4" Weldon fitting, Bore Ø 28 mm, Cutting depth 100 mm	20 20 20 20 20 20 20 20	29 30 56 56 31 31
6 31 34 280 05 3 6 31 34 280 05 4 6 31 34 280 07 5 6 31 34 280 07 6 6 31 34 280 30 1	4014586613925 4014586613963 4014586469683 4014586613895 4014586613932 4014586635170	HSS Nova 25 core bit with 3/4" Weldon holder, Bore Ø 28 mm, Cutting depth 25 mm HSS Nova 50 core bit with 3/4" Weldon holder, Bore Ø 28 mm, Cutting depth 50 mm HSS Nova 75 core bit with 3/4" Weldon holder, Bore Ø 28 mm, Cutting depth 75 mm HSS NOVA 100 core drill bit with 3/4" Weldon fitting, Bore Ø 28 mm, Cutting depth 100 mm HSS Dura 25 core bit with 3/4" Weldon holder, Bore Ø 28 mm, Cutting depth 25 mm HSS Dura 50 core bit with 3/4" Weldon holder, Bore Ø 28 mm, Cutting depth 50 mm HSS SPECIAL 25 core bit with 3/4" Weldon fitting, Bore Ø 28 mm, Cutting depth 25 mm	20 20 20 20 20 20 20 20 20	29 30 56 56 31 31 30
6 31 34 280 05 3 6 31 34 280 05 4 6 31 34 280 07 5 6 31 34 280 07 6 6 31 34 280 30 1 6 31 34 280 30 2	4014586613925 4014586613963 4014586469683 4014586613895 4014586613932 4014586635170 4014586469690	HSS Nova 25 core bit with 3/4" Weldon holder, Bore Ø 28 mm, Cutting depth 25 mm HSS Nova 50 core bit with 3/4" Weldon holder, Bore Ø 28 mm, Cutting depth 50 mm HSS Nova 75 core bit with 3/4" Weldon holder, Bore Ø 28 mm, Cutting depth 75 mm HSS NOVA 100 core drill bit with 3/4" Weldon fitting, Bore Ø 28 mm, Cutting depth 100 mm HSS Dura 25 core bit with 3/4" Weldon holder, Bore Ø 28 mm, Cutting depth 25 mm HSS Dura 50 core bit with 3/4" Weldon holder, Bore Ø 28 mm, Cutting depth 50 mm HSS SPECIAL 25 core bit with 3/4" Weldon fitting, Bore Ø 28 mm, Cutting depth 25 mm HSS SPECIAL 50 core drill bit with 3/4" Weldon fitting, Bore Ø 28 mm, Cutting depth 50 mm	20 20 20 20 20 20 20 20 20 20	29 30 56 56 31 31 30 30
6 31 34 280 05 3 6 31 34 280 05 4 6 31 34 280 07 5 6 31 34 280 07 6 6 31 34 280 30 1 6 31 34 280 30 2 6 31 34 290 05 1	4014586613925 4014586613963 4014586469683 4014586613895 4014586613932 4014586635170 4014586613970	HSS Nova 25 core bit with 3/4" Weldon holder, Bore Ø 28 mm, Cutting depth 25 mm HSS Nova 50 core bit with 3/4" Weldon holder, Bore Ø 28 mm, Cutting depth 50 mm HSS Nova 75 core bit with 3/4" Weldon holder, Bore Ø 28 mm, Cutting depth 75 mm HSS NOVA 100 core drill bit with 3/4" Weldon fitting, Bore Ø 28 mm, Cutting depth 100 mm HSS Dura 25 core bit with 3/4" Weldon holder, Bore Ø 28 mm, Cutting depth 25 mm HSS Dura 50 core bit with 3/4" Weldon holder, Bore Ø 28 mm, Cutting depth 50 mm HSS SPECIAL 25 core bit with 3/4" Weldon fitting, Bore Ø 28 mm, Cutting depth 25 mm HSS SPECIAL 50 core drill bit with 3/4" Weldon fitting, Bore Ø 28 mm, Cutting depth 50 mm HSS Nova 25 core bit with 3/4" Weldon holder, Bore Ø 29 mm, Cutting depth 25 mm	20 20 20 20 20 20 20 20 20 20 20	29 30 56 56 31 31 30 30
6 31 34 280 05 3 6 31 34 280 05 4 6 31 34 280 07 5 6 31 34 280 07 6 6 31 34 280 30 1 6 31 34 280 30 2 6 31 34 290 05 1 6 31 34 290 05 2	4014586613925 4014586613963 4014586469683 4014586613895 4014586613932 4014586635170 4014586613970 4014586614014	HSS Nova 25 core bit with 3/4" Weldon holder, Bore Ø 28 mm, Cutting depth 25 mm HSS Nova 50 core bit with 3/4" Weldon holder, Bore Ø 28 mm, Cutting depth 50 mm HSS Nova 75 core bit with 3/4" Weldon holder, Bore Ø 28 mm, Cutting depth 75 mm HSS NOVA 100 core drill bit with 3/4" Weldon fitting, Bore Ø 28 mm, Cutting depth 100 mm HSS Dura 25 core bit with 3/4" Weldon holder, Bore Ø 28 mm, Cutting depth 25 mm HSS Dura 50 core bit with 3/4" Weldon holder, Bore Ø 28 mm, Cutting depth 50 mm HSS SPECIAL 25 core bit with 3/4" Weldon fitting, Bore Ø 28 mm, Cutting depth 25 mm HSS SPECIAL 50 core drill bit with 3/4" Weldon fitting, Bore Ø 28 mm, Cutting depth 50 mm HSS Nova 25 core bit with 3/4" Weldon holder, Bore Ø 29 mm, Cutting depth 25 mm HSS Nova 50 core bit with 3/4" Weldon holder, Bore Ø 29 mm, Cutting depth 50 mm	20 20 20 20 20 20 20 20 20 20 20	29 30 56 56 31 31 30 30 29 30
6 31 34 280 05 3 6 31 34 280 05 4 6 31 34 280 07 5 6 31 34 280 07 6 6 31 34 280 30 1 6 31 34 280 30 2 6 31 34 290 05 1 6 31 34 290 05 2 6 31 34 290 05 3	4014586613925 4014586613963 4014586469683 4014586613895 4014586613932 4014586635170 4014586613970 4014586614014 4014586614052	HSS Nova 25 core bit with 3/4" Weldon holder, Bore Ø 28 mm, Cutting depth 25 mm HSS Nova 50 core bit with 3/4" Weldon holder, Bore Ø 28 mm, Cutting depth 50 mm HSS Nova 75 core bit with 3/4" Weldon holder, Bore Ø 28 mm, Cutting depth 75 mm HSS NOVA 100 core drill bit with 3/4" Weldon fitting, Bore Ø 28 mm, Cutting depth 100 mm HSS Dura 25 core bit with 3/4" Weldon holder, Bore Ø 28 mm, Cutting depth 25 mm HSS Dura 50 core bit with 3/4" Weldon holder, Bore Ø 28 mm, Cutting depth 50 mm HSS SPECIAL 25 core bit with 3/4" Weldon fitting, Bore Ø 28 mm, Cutting depth 25 mm HSS SPECIAL 50 core drill bit with 3/4" Weldon fitting, Bore Ø 28 mm, Cutting depth 50 mm HSS Nova 25 core bit with 3/4" Weldon holder, Bore Ø 29 mm, Cutting depth 25 mm HSS Nova 50 core bit with 3/4" Weldon holder, Bore Ø 29 mm, Cutting depth 50 mm HSS Nova 75 core bit with 3/4" Weldon holder, Bore Ø 29 mm, Cutting depth 75 mm	20 20 20 20 20 20 20 20 20 20 20 20	29 30 56 56 31 31 30 30 29 30
6 31 34 280 05 3 6 31 34 280 05 4 6 31 34 280 07 5 6 31 34 280 07 6 6 31 34 280 30 1 6 31 34 280 30 2 6 31 34 290 05 1 6 31 34 290 05 3 6 31 34 290 05 3	4014586613925 4014586613963 4014586469683 4014586613895 4014586613932 4014586635170 4014586613970 4014586614014 4014586614052 4014586469706	HSS Nova 25 core bit with 3/4" Weldon holder, Bore Ø 28 mm, Cutting depth 25 mm HSS Nova 50 core bit with 3/4" Weldon holder, Bore Ø 28 mm, Cutting depth 50 mm HSS Nova 75 core bit with 3/4" Weldon holder, Bore Ø 28 mm, Cutting depth 75 mm HSS NOVA 100 core drill bit with 3/4" Weldon fitting, Bore Ø 28 mm, Cutting depth 100 mm HSS Dura 25 core bit with 3/4" Weldon holder, Bore Ø 28 mm, Cutting depth 25 mm HSS Dura 50 core bit with 3/4" Weldon holder, Bore Ø 28 mm, Cutting depth 50 mm HSS SPECIAL 25 core bit with 3/4" Weldon fitting, Bore Ø 28 mm, Cutting depth 25 mm HSS SPECIAL 50 core drill bit with 3/4" Weldon fitting, Bore Ø 28 mm, Cutting depth 50 mm HSS Nova 25 core bit with 3/4" Weldon holder, Bore Ø 29 mm, Cutting depth 25 mm HSS Nova 50 core bit with 3/4" Weldon holder, Bore Ø 29 mm, Cutting depth 50 mm HSS Nova 75 core bit with 3/4" Weldon holder, Bore Ø 29 mm, Cutting depth 75 mm HSS NOVA 100 core drill bit with 3/4" Weldon fitting, Bore Ø 29 mm, Cutting depth 100 mm	20 20 20 20 20 20 20 20 20 20 20 20 20	29 30 56 56 31 31 30 30 29 30 56 56
6 31 34 280 05 3 6 31 34 280 07 5 6 31 34 280 07 6 6 31 34 280 07 6 6 31 34 280 30 1 6 31 34 280 30 2 6 31 34 290 05 1 6 31 34 290 05 3 6 31 34 290 05 4 6 31 34 290 07 5	4014586613925 4014586613963 4014586469683 4014586613895 4014586613932 4014586635170 4014586613970 4014586614014 4014586614052 4014586469706 4014586613987	HSS Nova 25 core bit with 3/4" Weldon holder, Bore Ø 28 mm, Cutting depth 25 mm HSS Nova 50 core bit with 3/4" Weldon holder, Bore Ø 28 mm, Cutting depth 50 mm HSS Nova 75 core bit with 3/4" Weldon holder, Bore Ø 28 mm, Cutting depth 75 mm HSS NOVA 100 core drill bit with 3/4" Weldon fitting, Bore Ø 28 mm, Cutting depth 100 mm HSS Dura 25 core bit with 3/4" Weldon holder, Bore Ø 28 mm, Cutting depth 25 mm HSS Dura 50 core bit with 3/4" Weldon holder, Bore Ø 28 mm, Cutting depth 50 mm HSS SPECIAL 25 core bit with 3/4" Weldon fitting, Bore Ø 28 mm, Cutting depth 25 mm HSS SPECIAL 50 core drill bit with 3/4" Weldon fitting, Bore Ø 28 mm, Cutting depth 50 mm HSS Nova 25 core bit with 3/4" Weldon holder, Bore Ø 29 mm, Cutting depth 50 mm HSS Nova 50 core bit with 3/4" Weldon holder, Bore Ø 29 mm, Cutting depth 50 mm HSS Nova 75 core bit with 3/4" Weldon holder, Bore Ø 29 mm, Cutting depth 75 mm HSS NOVA 100 core drill bit with 3/4" Weldon holder, Bore Ø 29 mm, Cutting depth 100 mm HSS Dura 25 core bit with 3/4" Weldon holder, Bore Ø 29 mm, Cutting depth 100 mm	20 20 20 20 20 20 20 20 20 20 20 20 20 2	29 30 56 56 31 31 30 30 29 30 56 56 31
6 31 34 280 05 3 6 31 34 280 07 5 6 31 34 280 07 6 6 31 34 280 07 6 6 31 34 280 30 1 6 31 34 280 30 2 6 31 34 290 05 1 6 31 34 290 05 2 6 31 34 290 05 3 6 31 34 290 07 5 6 31 34 290 07 6	4014586613925 4014586613963 4014586469683 4014586613895 4014586613932 4014586635170 4014586613970 4014586614014 4014586614052 4014586613987 4014586614021	HSS Nova 25 core bit with 3/4" Weldon holder, Bore Ø 28 mm, Cutting depth 25 mm HSS Nova 50 core bit with 3/4" Weldon holder, Bore Ø 28 mm, Cutting depth 50 mm HSS Nova 75 core bit with 3/4" Weldon holder, Bore Ø 28 mm, Cutting depth 75 mm HSS NOVA 100 core drill bit with 3/4" Weldon fitting, Bore Ø 28 mm, Cutting depth 100 mm HSS Dura 25 core bit with 3/4" Weldon holder, Bore Ø 28 mm, Cutting depth 25 mm HSS Dura 50 core bit with 3/4" Weldon holder, Bore Ø 28 mm, Cutting depth 50 mm HSS SPECIAL 25 core bit with 3/4" Weldon fitting, Bore Ø 28 mm, Cutting depth 25 mm HSS SPECIAL 50 core drill bit with 3/4" Weldon fitting, Bore Ø 28 mm, Cutting depth 50 mm HSS Nova 25 core bit with 3/4" Weldon holder, Bore Ø 29 mm, Cutting depth 25 mm HSS Nova 50 core bit with 3/4" Weldon holder, Bore Ø 29 mm, Cutting depth 50 mm HSS Nova 75 core bit with 3/4" Weldon holder, Bore Ø 29 mm, Cutting depth 75 mm HSS NOVA 100 core drill bit with 3/4" Weldon fitting, Bore Ø 29 mm, Cutting depth 100 mm HSS Dura 25 core bit with 3/4" Weldon holder, Bore Ø 29 mm, Cutting depth 25 mm HSS Dura 25 core bit with 3/4" Weldon holder, Bore Ø 29 mm, Cutting depth 50 mm	20 20 20 20 20 20 20 20 20 20 20 20 20 2	29 30 56 56 31 31 30 30 29 30 56 56 56 31 31 31 31 31 30 30 31 31 31 31 31 31 31 31 31 31
6 31 34 280 05 3 6 31 34 280 07 5 6 31 34 280 07 6 6 31 34 280 07 6 6 31 34 280 30 1 6 31 34 280 30 2 6 31 34 290 05 1 6 31 34 290 05 2 6 31 34 290 05 3 6 31 34 290 07 5 6 31 34 290 07 6 6 31 34 300 05 1	4014586613925 4014586613963 4014586613895 4014586613932 4014586635170 4014586635170 4014586613970 4014586614014 4014586614052 4014586613987 4014586614021 4014586614021 4014586614205	HSS Nova 25 core bit with 3/4" Weldon holder, Bore Ø 28 mm, Cutting depth 25 mm HSS Nova 50 core bit with 3/4" Weldon holder, Bore Ø 28 mm, Cutting depth 50 mm HSS Nova 75 core bit with 3/4" Weldon holder, Bore Ø 28 mm, Cutting depth 75 mm HSS NOVA 100 core drill bit with 3/4" Weldon fitting, Bore Ø 28 mm, Cutting depth 100 mm HSS Dura 25 core bit with 3/4" Weldon holder, Bore Ø 28 mm, Cutting depth 25 mm HSS Dura 50 core bit with 3/4" Weldon holder, Bore Ø 28 mm, Cutting depth 50 mm HSS SPECIAL 25 core bit with 3/4" Weldon fitting, Bore Ø 28 mm, Cutting depth 25 mm HSS SPECIAL 50 core drill bit with 3/4" Weldon fitting, Bore Ø 28 mm, Cutting depth 50 mm HSS Nova 25 core bit with 3/4" Weldon holder, Bore Ø 29 mm, Cutting depth 50 mm HSS Nova 50 core bit with 3/4" Weldon holder, Bore Ø 29 mm, Cutting depth 50 mm HSS Nova 75 core bit with 3/4" Weldon holder, Bore Ø 29 mm, Cutting depth 75 mm HSS NOVA 100 core drill bit with 3/4" Weldon fitting, Bore Ø 29 mm, Cutting depth 100 mm HSS Dura 25 core bit with 3/4" Weldon holder, Bore Ø 29 mm, Cutting depth 25 mm HSS Dura 25 core bit with 3/4" Weldon holder, Bore Ø 29 mm, Cutting depth 50 mm HSS Dura 50 core bit with 3/4" Weldon holder, Bore Ø 29 mm, Cutting depth 50 mm	20 20 20 20 20 20 20 20 20 20 20 20 20 2	29 30 56 56 31 31 30 29 30 56 56 31 31 29
6 31 34 280 05 3 6 31 34 280 07 5 6 31 34 280 07 6 6 31 34 280 30 1 6 31 34 280 30 2 6 31 34 280 30 2 6 31 34 290 05 1 6 31 34 290 05 3 6 31 34 290 07 5 6 31 34 290 07 6 6 31 34 300 05 1 6 31 34 300 05 2	4014586613925 4014586613963 4014586613895 4014586613895 4014586613932 4014586635170 4014586613970 4014586614014 4014586614052 4014586613987 4014586614021 4014586614205 4014586614243	HSS Nova 25 core bit with 3/4" Weldon holder, Bore Ø 28 mm, Cutting depth 25 mm HSS Nova 50 core bit with 3/4" Weldon holder, Bore Ø 28 mm, Cutting depth 50 mm HSS Nova 75 core bit with 3/4" Weldon holder, Bore Ø 28 mm, Cutting depth 75 mm HSS NOVA 100 core drill bit with 3/4" Weldon fitting, Bore Ø 28 mm, Cutting depth 100 mm HSS Dura 25 core bit with 3/4" Weldon holder, Bore Ø 28 mm, Cutting depth 25 mm HSS Dura 50 core bit with 3/4" Weldon holder, Bore Ø 28 mm, Cutting depth 50 mm HSS SPECIAL 25 core bit with 3/4" Weldon fitting, Bore Ø 28 mm, Cutting depth 25 mm HSS SPECIAL 50 core drill bit with 3/4" Weldon fitting, Bore Ø 28 mm, Cutting depth 50 mm HSS Nova 25 core bit with 3/4" Weldon holder, Bore Ø 29 mm, Cutting depth 25 mm HSS Nova 50 core bit with 3/4" Weldon holder, Bore Ø 29 mm, Cutting depth 50 mm HSS NOVA 100 core drill bit with 3/4" Weldon fitting, Bore Ø 29 mm, Cutting depth 100 mm HSS Dura 25 core bit with 3/4" Weldon holder, Bore Ø 29 mm, Cutting depth 25 mm HSS Dura 50 core bit with 3/4" Weldon holder, Bore Ø 29 mm, Cutting depth 50 mm HSS Dura 50 core bit with 3/4" Weldon holder, Bore Ø 29 mm, Cutting depth 50 mm HSS Nova 25 core bit with 3/4" Weldon holder, Bore Ø 29 mm, Cutting depth 50 mm HSS Nova 25 core bit with 3/4" Weldon holder, Bore Ø 30 mm, Cutting depth 50 mm HSS Nova 25 core bit with 3/4" Weldon holder, Bore Ø 30 mm, Cutting depth 50 mm	20 20 20 20 20 20 20 20 20 20 20 20 20 2	29 30 56 56 31 31 30 29 30 56 56 31 31 30 29 30 56 56 31 30 30 30 30 30 30 30 30 30 30
6 31 34 280 05 3 6 31 34 280 05 4 6 31 34 280 07 5 6 31 34 280 07 6 6 31 34 280 30 1 6 31 34 280 30 2 6 31 34 290 05 1 6 31 34 290 05 3 6 31 34 290 05 3 6 31 34 290 07 5 6 31 34 290 07 6 6 31 34 300 05 1 6 31 34 300 05 3	4014586613925 4014586613963 4014586613963 4014586613895 4014586613932 4014586635170 4014586613970 4014586614014 4014586614052 4014586614052 4014586614021 4014586614021 4014586614205 4014586614243 4014586614281	HSS Nova 25 core bit with 3/4" Weldon holder, Bore Ø 28 mm, Cutting depth 25 mm HSS Nova 50 core bit with 3/4" Weldon holder, Bore Ø 28 mm, Cutting depth 50 mm HSS Nova 75 core bit with 3/4" Weldon holder, Bore Ø 28 mm, Cutting depth 75 mm HSS NOVA 100 core drill bit with 3/4" Weldon fitting, Bore Ø 28 mm, Cutting depth 100 mm HSS Dura 25 core bit with 3/4" Weldon holder, Bore Ø 28 mm, Cutting depth 25 mm HSS Dura 50 core bit with 3/4" Weldon holder, Bore Ø 28 mm, Cutting depth 50 mm HSS SPECIAL 25 core bit with 3/4" Weldon fitting, Bore Ø 28 mm, Cutting depth 25 mm HSS Nova 25 core bit with 3/4" Weldon fitting, Bore Ø 28 mm, Cutting depth 50 mm HSS Nova 50 core bit with 3/4" Weldon holder, Bore Ø 29 mm, Cutting depth 50 mm HSS Nova 75 core bit with 3/4" Weldon holder, Bore Ø 29 mm, Cutting depth 50 mm HSS NOVA 100 core drill bit with 3/4" Weldon fitting, Bore Ø 29 mm, Cutting depth 100 mm HSS Dura 25 core bit with 3/4" Weldon holder, Bore Ø 29 mm, Cutting depth 25 mm HSS Dura 25 core bit with 3/4" Weldon holder, Bore Ø 29 mm, Cutting depth 50 mm HSS Dura 25 core bit with 3/4" Weldon holder, Bore Ø 29 mm, Cutting depth 50 mm HSS Nova 25 core bit with 3/4" Weldon holder, Bore Ø 30 mm, Cutting depth 50 mm HSS Nova 25 core bit with 3/4" Weldon holder, Bore Ø 30 mm, Cutting depth 50 mm HSS Nova 25 core bit with 3/4" Weldon holder, Bore Ø 30 mm, Cutting depth 50 mm HSS Nova 50 core bit with 3/4" Weldon holder, Bore Ø 30 mm, Cutting depth 50 mm	20 20 20 20 20 20 20 20 20 20 20 20 20 2	29 30 56 56 31 31 30 29 30 56 56 31 31 29 30 56
6 31 34 280 05 3 6 31 34 280 05 4 6 31 34 280 07 5 6 31 34 280 07 6 6 31 34 280 30 1 6 31 34 280 30 2 6 31 34 290 05 1 6 31 34 290 05 3 6 31 34 290 05 3 6 31 34 290 07 5 6 31 34 290 07 6 6 31 34 300 05 1 6 31 34 300 05 3	4014586613925 4014586613963 4014586613895 4014586613895 4014586613932 4014586635170 4014586613970 4014586614014 4014586614052 4014586614052 4014586614021 4014586614281 4014586614281 4014586614281 4014586614281	HSS Nova 25 core bit with 3/4" Weldon holder, Bore Ø 28 mm, Cutting depth 25 mm HSS Nova 50 core bit with 3/4" Weldon holder, Bore Ø 28 mm, Cutting depth 50 mm HSS Nova 75 core bit with 3/4" Weldon holder, Bore Ø 28 mm, Cutting depth 75 mm HSS NOVA 100 core drill bit with 3/4" Weldon fitting, Bore Ø 28 mm, Cutting depth 100 mm HSS Dura 25 core bit with 3/4" Weldon holder, Bore Ø 28 mm, Cutting depth 25 mm HSS Dura 50 core bit with 3/4" Weldon holder, Bore Ø 28 mm, Cutting depth 50 mm HSS SPECIAL 25 core bit with 3/4" Weldon fitting, Bore Ø 28 mm, Cutting depth 25 mm HSS Nova 25 core bit with 3/4" Weldon fitting, Bore Ø 28 mm, Cutting depth 50 mm HSS Nova 25 core bit with 3/4" Weldon holder, Bore Ø 29 mm, Cutting depth 50 mm HSS Nova 75 core bit with 3/4" Weldon holder, Bore Ø 29 mm, Cutting depth 50 mm HSS NOVA 100 core drill bit with 3/4" Weldon fitting, Bore Ø 29 mm, Cutting depth 75 mm HSS Dura 25 core bit with 3/4" Weldon holder, Bore Ø 29 mm, Cutting depth 100 mm HSS Dura 25 core bit with 3/4" Weldon holder, Bore Ø 29 mm, Cutting depth 25 mm HSS Nova 25 core bit with 3/4" Weldon holder, Bore Ø 29 mm, Cutting depth 50 mm HSS Nova 25 core bit with 3/4" Weldon holder, Bore Ø 30 mm, Cutting depth 50 mm HSS Nova 25 core bit with 3/4" Weldon holder, Bore Ø 30 mm, Cutting depth 50 mm HSS Nova 50 core bit with 3/4" Weldon holder, Bore Ø 30 mm, Cutting depth 50 mm HSS Nova 75 core bit with 3/4" Weldon holder, Bore Ø 30 mm, Cutting depth 50 mm HSS Nova 75 core bit with 3/4" Weldon holder, Bore Ø 30 mm, Cutting depth 50 mm	20 20 20 20 20 20 20 20 20 20 20 20 20 2	29 30 56 56 31 31 30 30 29 30 56 56 31 31 29 30 56 56 56 56 56 56 56 56 56 56
6 31 34 280 05 3 6 31 34 280 05 4 6 31 34 280 07 5 6 31 34 280 07 6 6 31 34 280 30 1 6 31 34 280 30 2 6 31 34 290 05 1 6 31 34 290 05 3 6 31 34 290 05 4 6 31 34 290 07 6 6 31 34 290 07 6 6 31 34 300 05 1 6 31 34 300 05 2 6 31 34 300 05 3	4014586613925 4014586613963 4014586613895 4014586613895 4014586613932 4014586635170 4014586613970 4014586614014 4014586614052 4014586614052 4014586614021 4014586614021 4014586614205 4014586614281 4014586614281 4014586614212	HSS Nova 25 core bit with 3/4" Weldon holder, Bore Ø 28 mm, Cutting depth 25 mm HSS Nova 50 core bit with 3/4" Weldon holder, Bore Ø 28 mm, Cutting depth 50 mm HSS Nova 75 core bit with 3/4" Weldon holder, Bore Ø 28 mm, Cutting depth 75 mm HSS NOVA 100 core drill bit with 3/4" Weldon fitting, Bore Ø 28 mm, Cutting depth 100 mm HSS Dura 25 core bit with 3/4" Weldon holder, Bore Ø 28 mm, Cutting depth 25 mm HSS Dura 50 core bit with 3/4" Weldon holder, Bore Ø 28 mm, Cutting depth 50 mm HSS SPECIAL 25 core bit with 3/4" Weldon fitting, Bore Ø 28 mm, Cutting depth 25 mm HSS Nova 25 core bit with 3/4" Weldon fitting, Bore Ø 28 mm, Cutting depth 50 mm HSS Nova 25 core bit with 3/4" Weldon holder, Bore Ø 29 mm, Cutting depth 50 mm HSS Nova 75 core bit with 3/4" Weldon holder, Bore Ø 29 mm, Cutting depth 75 mm HSS NOVA 100 core drill bit with 3/4" Weldon fitting, Bore Ø 29 mm, Cutting depth 100 mm HSS Dura 25 core bit with 3/4" Weldon holder, Bore Ø 29 mm, Cutting depth 25 mm HSS Nova 50 core bit with 3/4" Weldon holder, Bore Ø 29 mm, Cutting depth 50 mm HSS Nova 50 core bit with 3/4" Weldon holder, Bore Ø 29 mm, Cutting depth 50 mm HSS Nova 50 core bit with 3/4" Weldon holder, Bore Ø 30 mm, Cutting depth 50 mm HSS Nova 50 core bit with 3/4" Weldon holder, Bore Ø 30 mm, Cutting depth 55 mm HSS Nova 50 core bit with 3/4" Weldon holder, Bore Ø 30 mm, Cutting depth 50 mm HSS Nova 75 core bit with 3/4" Weldon holder, Bore Ø 30 mm, Cutting depth 50 mm HSS Nova 75 core bit with 3/4" Weldon holder, Bore Ø 30 mm, Cutting depth 50 mm HSS Nova 75 core bit with 3/4" Weldon holder, Bore Ø 30 mm, Cutting depth 50 mm HSS Nova 75 core bit with 3/4" Weldon holder, Bore Ø 30 mm, Cutting depth 50 mm	20 20 20 20 20 20 20 20 20 20 20 20 20 2	29 30 56 56 31 31 30 30 29 30 56 56 31 31 29 30 56 56 31 31 31 30 30 30 50 50 50 50 50 50 50 50 50 5
6 31 34 280 05 3 6 31 34 280 05 4 6 31 34 280 07 5 6 31 34 280 07 6 6 31 34 280 30 1 6 31 34 280 30 2 6 31 34 290 05 1 6 31 34 290 05 3 6 31 34 290 07 5 6 31 34 290 07 6 6 31 34 290 07 6 6 31 34 300 05 1 6 31 34 300 05 2 6 31 34 300 05 3	4014586613925 4014586613963 4014586613895 4014586613895 4014586613932 4014586635170 4014586613970 4014586614014 4014586614052 4014586614052 4014586614021 4014586614215 4014586614215 4014586614212 4014586614212 4014586614250	HSS Nova 25 core bit with 3/4" Weldon holder, Bore Ø 28 mm, Cutting depth 25 mm HSS Nova 50 core bit with 3/4" Weldon holder, Bore Ø 28 mm, Cutting depth 50 mm HSS Nova 75 core bit with 3/4" Weldon holder, Bore Ø 28 mm, Cutting depth 75 mm HSS NOVA 100 core drill bit with 3/4" Weldon fitting, Bore Ø 28 mm, Cutting depth 100 mm HSS Dura 25 core bit with 3/4" Weldon holder, Bore Ø 28 mm, Cutting depth 25 mm HSS Dura 50 core bit with 3/4" Weldon holder, Bore Ø 28 mm, Cutting depth 50 mm HSS SPECIAL 25 core bit with 3/4" Weldon fitting, Bore Ø 28 mm, Cutting depth 25 mm HSS Nova 25 core bit with 3/4" Weldon fitting, Bore Ø 28 mm, Cutting depth 50 mm HSS Nova 25 core bit with 3/4" Weldon holder, Bore Ø 29 mm, Cutting depth 25 mm HSS Nova 50 core bit with 3/4" Weldon holder, Bore Ø 29 mm, Cutting depth 50 mm HSS Nova 75 core bit with 3/4" Weldon holder, Bore Ø 29 mm, Cutting depth 75 mm HSS NOVA 100 core drill bit with 3/4" Weldon fitting, Bore Ø 29 mm, Cutting depth 100 mm HSS Dura 25 core bit with 3/4" Weldon holder, Bore Ø 29 mm, Cutting depth 25 mm HSS Nova 25 core bit with 3/4" Weldon holder, Bore Ø 29 mm, Cutting depth 50 mm HSS Nova 25 core bit with 3/4" Weldon holder, Bore Ø 30 mm, Cutting depth 55 mm HSS Nova 50 core bit with 3/4" Weldon holder, Bore Ø 30 mm, Cutting depth 50 mm HSS Nova 75 core bit with 3/4" Weldon holder, Bore Ø 30 mm, Cutting depth 50 mm HSS Nova 75 core bit with 3/4" Weldon holder, Bore Ø 30 mm, Cutting depth 50 mm HSS Nova 75 core bit with 3/4" Weldon holder, Bore Ø 30 mm, Cutting depth 50 mm HSS Nova 75 core bit with 3/4" Weldon holder, Bore Ø 30 mm, Cutting depth 50 mm HSS Nova 75 core bit with 3/4" Weldon holder, Bore Ø 30 mm, Cutting depth 50 mm HSS Nova 75 core bit with 3/4" Weldon holder, Bore Ø 30 mm, Cutting depth 50 mm	20 20 20 20 20 20 20 20 20 20 20 20 20 2	29 30 56 56 31 31 30 30 29 30 56 56 31 31 29 30 56 56 31 31 31 30 30 56 56 31 31 30 30 30 50 50 50 50 50 50 50 50 50 5
6 31 34 280 05 3 6 31 34 280 05 4 6 31 34 280 07 5 6 31 34 280 07 6 6 31 34 280 30 1 6 31 34 280 30 2 6 31 34 290 05 1 6 31 34 290 05 3 6 31 34 290 05 4 6 31 34 290 07 6 6 31 34 290 07 6 6 31 34 300 05 1 6 31 34 300 05 2 6 31 34 300 05 3	4014586613925 4014586613963 4014586613895 4014586613895 4014586613932 4014586635170 4014586613970 4014586614014 4014586614052 4014586614052 4014586614021 4014586614021 4014586614205 4014586614281 4014586614281 4014586614212	HSS Nova 25 core bit with 3/4" Weldon holder, Bore Ø 28 mm, Cutting depth 25 mm HSS Nova 50 core bit with 3/4" Weldon holder, Bore Ø 28 mm, Cutting depth 50 mm HSS Nova 75 core bit with 3/4" Weldon holder, Bore Ø 28 mm, Cutting depth 75 mm HSS NOVA 100 core drill bit with 3/4" Weldon fitting, Bore Ø 28 mm, Cutting depth 100 mm HSS Dura 25 core bit with 3/4" Weldon holder, Bore Ø 28 mm, Cutting depth 25 mm HSS Dura 50 core bit with 3/4" Weldon holder, Bore Ø 28 mm, Cutting depth 50 mm HSS SPECIAL 25 core bit with 3/4" Weldon fitting, Bore Ø 28 mm, Cutting depth 25 mm HSS Nova 25 core bit with 3/4" Weldon fitting, Bore Ø 28 mm, Cutting depth 50 mm HSS Nova 25 core bit with 3/4" Weldon holder, Bore Ø 29 mm, Cutting depth 50 mm HSS Nova 75 core bit with 3/4" Weldon holder, Bore Ø 29 mm, Cutting depth 75 mm HSS NOVA 100 core drill bit with 3/4" Weldon fitting, Bore Ø 29 mm, Cutting depth 100 mm HSS Dura 25 core bit with 3/4" Weldon holder, Bore Ø 29 mm, Cutting depth 25 mm HSS Nova 50 core bit with 3/4" Weldon holder, Bore Ø 29 mm, Cutting depth 50 mm HSS Nova 50 core bit with 3/4" Weldon holder, Bore Ø 29 mm, Cutting depth 50 mm HSS Nova 50 core bit with 3/4" Weldon holder, Bore Ø 30 mm, Cutting depth 50 mm HSS Nova 50 core bit with 3/4" Weldon holder, Bore Ø 30 mm, Cutting depth 55 mm HSS Nova 50 core bit with 3/4" Weldon holder, Bore Ø 30 mm, Cutting depth 50 mm HSS Nova 75 core bit with 3/4" Weldon holder, Bore Ø 30 mm, Cutting depth 50 mm HSS Nova 75 core bit with 3/4" Weldon holder, Bore Ø 30 mm, Cutting depth 50 mm HSS Nova 75 core bit with 3/4" Weldon holder, Bore Ø 30 mm, Cutting depth 50 mm HSS Nova 75 core bit with 3/4" Weldon holder, Bore Ø 30 mm, Cutting depth 50 mm	20 20 20 20 20 20 20 20 20 20 20 20 20 2	29 30 56 56 31 31 30 30 29 30 56 56 31 31 29 30 56 56 31 31 31 30 30 30 50 50 50 50 50 50 50 50 50 5

Part number	EAN	Description	PC	Page
6 31 34 310 05 1	4014586614298	HSS Nova 25 core bit with 3/4" Weldon holder, Bore Ø 31 mm, Cutting depth 25 mm	20	29
6 31 34 310 05 2	4014586614335	HSS Nova 50 core bit with 3/4" Weldon holder, Bore Ø 31 mm, Cutting depth 50 mm	20	30
6 31 34 310 07 5	4014586614304	HSS Dura 25 core bit with 3/4" Weldon holder, Bore Ø 31 mm, Cutting depth 25 mm	20	31
6 31 34 310 07 6	4014586614342	HSS Dura 50 core bit with 3/4" Weldon holder, Bore Ø 31 mm, Cutting depth 50 mm	20	31
6 31 34 320 05 1	4014586614373	HSS Nova 25 core bit with 3/4" Weldon holder, Bore Ø 32 mm, Cutting depth 25 mm	20	29
6 31 34 320 05 2	4014586614410	HSS Nova 50 core bit with 3/4" Weldon holder, Bore Ø 32 mm, Cutting depth 50 mm	20	30
6 31 34 320 05 3	4014586614458	HSS Nova 75 core bit with 3/4" Weldon holder, Bore Ø 32 mm, Cutting depth 75 mm	20	56
6 31 34 320 05 4	4014586469737	HSS NOVA 100 core drill bit with 3/4" Weldon fitting, Bore Ø 32 mm, Cutting depth 100 mm	20	56
6 31 34 320 07 5	4014586614380 4014586614427	HSS Dura 25 core bit with 3/4" Weldon holder, Bore Ø 32 mm, Cutting depth 25 mm	20	31
6 31 34 320 07 6	4014586635194	HSS Dura 50 core bit with 3/4" Weldon holder, Bore Ø 32 mm, Cutting depth 50 mm HSS SPECIAL 25 core bit with 3/4" Weldon fitting, Bore Ø 32 mm, Cutting depth 25 mm	20	30
6 31 34 320 30 2	4014586469744	HSS SPECIAL 50 core drill bit with 3/4" Weldon fitting, Bore Ø 32 mm, Cutting depth 50 mm	20	30
6 31 34 330 05 1	4014586614465	HSS Nova 25 core bit with 3/4" Weldon holder, Bore Ø 33 mm, Cutting depth 25 mm	20	29
6 31 34 330 05 2	4014586614502	HSS Nova 50 core bit with 3/4" Weldon holder, Bore Ø 33 mm, Cutting depth 50 mm	20	30
6 31 34 330 07 5	4014586614472	HSS Dura 25 core bit with 3/4" Weldon holder, Bore Ø 33 mm, Cutting depth 25 mm	20	31
6 31 34 330 07 6	4014586614519	HSS Dura 50 core bit with 3/4" Weldon holder, Bore Ø 33 mm, Cutting depth 50 mm	20	31
6 31 34 340 05 1	4014586614540	HSS Nova 25 core bit with 3/4" Weldon holder, Bore Ø 34 mm, Cutting depth 25 mm	20	29
6 31 34 340 05 2	4014586614588	HSS Nova 50 core bit with 3/4" Weldon holder, Bore Ø 34 mm, Cutting depth 50 mm	20	30
6 31 34 340 07 5	4014586614557	HSS Dura 25 core bit with 3/4" Weldon holder, Bore Ø 34 mm, Cutting depth 25 mm	20	31
6 31 34 340 07 6	4014586614595	HSS Dura 50 core bit with 3/4" Weldon holder, Bore Ø 34 mm, Cutting depth 50 mm	20	31
6 31 34 350 05 1	4014586614625	HSS Nova 25 core bit with 3/4" Weldon holder, Bore Ø 35 mm, Cutting depth 25 mm	20	29
6 31 34 350 05 2	4014586614663	HSS Nova 50 core bit with 3/4" Weldon holder, Bore Ø 35 mm, Cutting depth 50 mm	20	30
6 31 34 350 05 3	4014586614700	HSS Nova 75 core bit with 3/4" Weldon holder, Bore Ø 35 mm, Cutting depth 75 mm	20	56
6 31 34 350 05 4	4014586469751	HSS NOVA 100 core drill bit with 3/4" Weldon fitting, Bore Ø 35 mm, Cutting depth 100 mm	20	56
6 31 34 350 07 5	4014586614632	HSS Dura 25 core bit with 3/4" Weldon holder, Bore Ø 35 mm, Cutting depth 25 mm	20	31
6 31 34 350 07 6	4014586614670	HSS Dura 50 core bit with 3/4" Weldon holder, Bore Ø 35 mm, Cutting depth 50 mm	20	31
6 31 34 350 30 1	4014586635200	HSS SPECIAL 25 core bit with 3/4" Weldon fitting, Bore Ø 35 mm, Cutting depth 25 mm	20	30
6 31 34 350 30 2	4014586469768	HSS SPECIAL 50 core drill bit with 3/4" Weldon fitting, Bore Ø 35 mm, Cutting depth 50 mm	20	30
6 31 34 360 05 1	4014586614717	HSS Nova 25 core bit with 3/4" Weldon holder, Bore Ø 36 mm, Cutting depth 25 mm	20	29
6 31 34 360 05 2	4014586614755	HSS Nova 50 core bit with 3/4" Weldon holder, Bore Ø 36 mm, Cutting depth 50 mm	20	30
6 31 34 360 05 3	4014586614793	HSS Nova 75 core bit with 3/4" Weldon holder, Bore \varnothing 36 mm, Cutting depth 75 mm	20	56
6 31 34 360 05 4	4014586469775	HSS NOVA 100 core drill bit with 3/4" Weldon fitting, Bore Ø 36 mm, Cutting depth 100 mm	20	56
6 31 34 360 07 5	4014586614724	HSS Dura 25 core bit with 3/4" Weldon holder, Bore Ø 36 mm, Cutting depth 25 mm	20	31
6 31 34 360 07 6	4014586614762	HSS Dura 50 core bit with 3/4" Weldon holder, Bore Ø 36 mm, Cutting depth 50 mm	20	31
6 31 34 360 30 2	4014586469782	HSS SPECIAL 50 core drill bit with 3/4" Weldon fitting, Bore Ø 36 mm, Cutting depth 50 mm	20	30
6 31 34 370 05 1	4014586614809	HSS Nova 25 core bit with 3/4" Weldon holder, Bore Ø 37 mm, Cutting depth 25 mm	20	29
6 31 34 370 05 2	4014586614847	HSS Nova 50 core bit with 3/4" Weldon holder, Bore Ø 37 mm, Cutting depth 50 mm	20	30
6 31 34 370 07 5	4014586614816	HSS Dura 25 core bit with 3/4" Weldon holder, Bore Ø 37 mm, Cutting depth 25 mm	20	31
6 31 34 370 07 6	4014586614854	HSS Dura 50 core bit with 3/4" Weldon holder, Bore Ø 37 mm, Cutting depth 50 mm	20	31
6 31 34 380 05 1	4014586614885	HSS Nova 25 core bit with 3/4" Weldon holder, Bore Ø 38 mm, Cutting depth 25 mm	20	29
6 31 34 380 05 2	4014586614922	HSS Nova 50 core bit with 3/4" Weldon holder, Bore Ø 38 mm, Cutting depth 50 mm	20	30
6 31 34 380 07 5	4014586614892	HSS Dura 25 core bit with 3/4" Weldon holder, Bore Ø 38 mm, Cutting depth 25 mm	20	31
6 31 34 380 07 6	4014586614939	HSS Dura 50 core bit with 3/4" Weldon holder, Bore Ø 38 mm, Cutting depth 50 mm	20	31
6 31 34 390 05 1	4014586614960 4014586615004	HSS Nova 25 core bit with 3/4" Weldon holder, Bore Ø 39 mm, Cutting depth 25 mm HSS Nova 50 core bit with 3/4" Weldon holder, Bore Ø 39 mm, Cutting depth 50 mm	20	29 30
6 31 34 390 07 5	4014586614977	HSS Dura 25 core bit with 3/4" Weldon holder, Bore Ø 39 mm, Cutting depth 25 mm	20	31
6 31 34 390 07 6	4014586615011	HSS Dura 50 core bit with 3/4" Weldon holder, Bore Ø 39 mm, Cutting depth 50 mm	20	31
6 31 34 400 05 1	4014586615042	HSS Nova 25 core bit with 3/4" Weldon holder, Bore Ø 40 mm, Cutting depth 25 mm	20	29
6 31 34 400 05 2	4014586615080	HSS Nova 50 core bit with 3/4" Weldon holder, Bore Ø 40 mm, Cutting depth 50 mm	20	30
6 31 34 400 05 3	4014586615127	HSS Nova 75 core bit with 3/4" Weldon holder, Bore Ø 40 mm, Cutting depth 75 mm	20	56
6 31 34 400 05 4	4014586469799	HSS NOVA 100 core drill bit with 3/4" Weldon fitting, Bore Ø 40 mm, Cutting depth 100 mm	20	56
6 31 34 400 07 5	4014586615059	HSS Dura 25 core bit with 3/4" Weldon holder, Bore Ø 40 mm, Cutting depth 25 mm	20	31
6 31 34 400 07 6	4014586615097	HSS Dura 50 core bit with 3/4" Weldon holder, Bore Ø 40 mm, Cutting depth 50 mm	20	31
6 31 34 400 30 2	4014586469805	HSS SPECIAL 50 core drill bit with 3/4" Weldon fitting, Bore Ø 40 mm, Cutting depth 50 mm	20	30
6 31 34 410 05 1	4014586615134	HSS Nova 25 core bit with 3/4" Weldon holder, Bore Ø 41 mm, Cutting depth 25 mm	20	29
6 31 34 410 05 2	4014586615172	HSS Nova 50 core bit with 3/4" Weldon holder, Bore Ø 41 mm, Cutting depth 50 mm	20	30
6 31 34 410 07 5	4014586615141	HSS Dura 25 core bit with 3/4" Weldon holder, Bore Ø 41 mm, Cutting depth 25 mm	20	31
6 31 34 410 07 6	4014586615189	HSS Dura 50 core bit with 3/4" Weldon holder, Bore Ø 41 mm, Cutting depth 50 mm	20	31
6 31 34 420 05 1	4014586615219	HSS Nova 25 core bit with 3/4" Weldon holder, Bore Ø 42 mm, Cutting depth 25 mm	20	29
6 31 34 420 05 2	4014586615257	HSS Nova 50 core bit with 3/4" Weldon holder, Bore Ø 42 mm, Cutting depth 50 mm	20	30

Part number	EAN	Description	PC	Page
6 31 34 420 07 5	4014586615226	HSS Dura 25 core bit with 3/4" Weldon holder, Bore Ø 42 mm, Cutting depth 25 mm	20	31
6 31 34 420 07 6	4014586615264	HSS Dura 50 core bit with 3/4" Weldon holder, Bore Ø 42 mm, Cutting depth 50 mm	20	31
6 31 34 430 05 1	4014586615295	HSS Nova 25 core bit with 3/4" Weldon holder, Bore Ø 43 mm, Cutting depth 25 mm	20	29
6 31 34 430 05 2	4014586615332	HSS Nova 50 core bit with 3/4" Weldon holder, Bore Ø 43 mm, Cutting depth 50 mm	20	30
6 31 34 430 07 5	4014586615301	HSS Dura 25 core bit with 3/4" Weldon holder, Bore Ø 43 mm, Cutting depth 25 mm	20	31
6 31 34 430 07 6	4014586615349	HSS Dura 50 core bit with 3/4" Weldon holder, Bore Ø 43 mm, Cutting depth 50 mm	20	31
6 31 34 440 05 1	4014586615370	HSS Nova 25 core bit with 3/4" Weldon holder, Bore Ø 44 mm, Cutting depth 25 mm	20	29
6 31 34 440 05 2	4014586615417	HSS Nova 50 core bit with 3/4" Weldon holder, Bore Ø 44 mm, Cutting depth 50 mm	20	30
6 31 34 440 07 5	4014586615387	HSS Dura 25 core bit with 3/4" Weldon holder, Bore Ø 44 mm, Cutting depth 25 mm	20	31
6 31 34 440 07 6	4014586615424	HSS Dura 50 core bit with 3/4" Weldon holder, Bore Ø 44 mm, Cutting depth 50 mm	20	31
6 31 34 450 05 1	4014586615455	HSS Nova 25 core bit with 3/4" Weldon holder, Bore Ø 45 mm, Cutting depth 25 mm	20	29
6 31 34 450 05 2	4014586615493	HSS Nova 50 core bit with 3/4" Weldon holder, Bore Ø 45 mm, Cutting depth 50 mm	20	30
6 31 34 450 05 3	4014586615530	HSS Nova 75 core bit with 3/4" Weldon holder, Bore Ø 45 mm, Cutting depth 75 mm	20	56
6 31 34 450 05 4	4014586469812	HSS NOVA 100 core drill bit with 3/4" Weldon fitting, Bore Ø 45 mm, Cutting depth 100 mm	20	56
6 31 34 450 07 5	4014586615462	HSS Dura 25 core bit with 3/4" Weldon holder, Bore Ø 45 mm, Cutting depth 25 mm	20	31
6 31 34 450 07 6	4014586615509	HSS Dura 50 core bit with 3/4" Weldon holder, Bore Ø 45 mm, Cutting depth 50 mm	20	31
6 31 34 450 30 2	4014586469829	HSS SPECIAL 50 core drill bit with 3/4" Weldon fitting, Bore Ø 45 mm, Cutting depth 50 mm	20	30
6 31 34 460 05 1	4014586615547	HSS Nova 25 core bit with 3/4" Weldon holder, Bore Ø 46 mm, Cutting depth 25 mm	20	29
6 31 34 460 05 2	4014586615608	HSS Nova 50 core bit with 3/4" Weldon holder, Bore Ø 46 mm, Cutting depth 50 mm	20	30
6 31 34 460 07 5	4014586615554	HSS Dura 25 core bit with 3/4" Weldon holder, Bore Ø 46 mm, Cutting depth 25 mm	20	31
6 31 34 460 07 6	4014586615615	HSS Dura 50 core bit with 3/4" Weldon holder, Bore Ø 46 mm, Cutting depth 50 mm	20	31
6 31 34 470 05 1	4014586615660	HSS Nova 25 core bit with 3/4" Weldon holder, Bore Ø 47 mm, Cutting depth 25 mm	20	29
6 31 34 470 05 2	4014586615707	HSS Nova 50 core bit with 3/4" Weldon holder, Bore Ø 47 mm, Cutting depth 50 mm	20	30
6 31 34 470 07 5	4014586615677	HSS Dura 25 core bit with 3/4" Weldon holder, Bore Ø 47 mm, Cutting depth 25 mm	20	31
6 31 34 470 07 6	4014586615714	HSS Dura 50 core bit with 3/4" Weldon holder, Bore Ø 47 mm, Cutting depth 50 mm	20	31
6 31 34 480 05 1	4014586615745	HSS Nova 25 core bit with 3/4" Weldon holder, Bore Ø 48 mm, Cutting depth 25 mm	20	29
6 31 34 480 05 2	4014586615783	HSS Nova 50 core bit with 3/4" Weldon holder, Bore Ø 48 mm, Cutting depth 50 mm	20	30
6 31 34 480 07 5	4014586615752	HSS Dura 25 core bit with 3/4" Weldon holder, Bore Ø 48 mm, Cutting depth 25 mm	20	31
6 31 34 480 07 6	4014586615790 4014586615820	HSS Dura 50 core bit with 3/4" Weldon holder, Bore Ø 48 mm, Cutting depth 50 mm	20	31 29
6 31 34 490 05 1	4014586615820	HSS Nova 25 core bit with 3/4" Weldon holder, Bore Ø 49 mm, Cutting depth 25 mm HSS Nova 50 core bit with 3/4" Weldon holder, Bore Ø 49 mm, Cutting depth 50 mm	20	30
6 31 34 490 07 5	4014586615837	HSS Dura 25 core bit with 3/4" Weldon holder, Bore Ø 49 mm, Cutting depth 25 mm	20	31
6 31 34 490 07 6	4014586615875	HSS Dura 50 core bit with 3/4" Weldon holder, Bore Ø 49 mm, Cutting depth 50 mm	20	31
6 31 34 500 05 1	4014586615967	HSS Nova 25 core bit with 3/4" Weldon holder, Bore Ø 50 mm, Cutting depth 25 mm	20	29
6 31 34 500 05 2	4014586615998	HSS Nova 50 core bit with 3/4" Weldon holder, Bore Ø 50 mm, Cutting depth 50 mm	20	30
6 31 34 500 05 3	4014586616025	HSS Nova 75 core bit with 3/4" Weldon holder, Bore Ø 50 mm, Cutting depth 75 mm	20	56
6 31 34 500 05 4	4014586469836	HSS NOVA 100 core drill bit with 3/4" Weldon fitting, Bore Ø 50 mm, Cutting depth 100 mm	20	56
6 31 34 500 07 5	4014586615974	HSS Dura 25 core bit with 3/4" Weldon holder, Bore Ø 50 mm, Cutting depth 25 mm	20	31
6 31 34 500 07 6	4014586616001	HSS Dura 50 core bit with 3/4" Weldon holder, Bore Ø 50 mm, Cutting depth 50 mm	20	31
6 31 34 500 30 2	4014586469843	HSS SPECIAL 50 core drill bit with 3/4" Weldon fitting, Bore Ø 50 mm, Cutting depth 50 mm	20	30
6 31 34 510 05 1	4014586616032	HSS Nova 25 core bit with 3/4" Weldon holder, Bore Ø 51 mm, Cutting depth 25 mm	20	55
6 31 34 510 05 2	4014586616056	HSS Nova 50 core bit with 3/4" Weldon holder, Bore Ø 51 mm, Cutting depth 50 mm	20	56
6 31 34 510 07 5	4014586616049	HSS Dura 25 core bit with 3/4" Weldon holder, Bore Ø 51 mm, Cutting depth 25 mm	20	57
6 31 34 510 07 6	4014586616063	HSS Dura 50 core bit with 3/4" Weldon holder, Bore Ø 51 mm, Cutting depth 50 mm	20	58
6 31 34 520 05 1	4014586616070	HSS Nova 25 core bit with 3/4" Weldon holder, Bore Ø 52 mm, Cutting depth 25 mm	20	55
6 31 34 520 05 2	4014586616094	HSS Nova 50 core bit with 3/4" Weldon holder, Bore Ø 52 mm, Cutting depth 50 mm	20	56
6 31 34 520 07 5	4014586616087	HSS Dura 25 core bit with 3/4" Weldon holder, Bore Ø 52 mm, Cutting depth 25 mm	20	57
6 31 34 520 07 6	4014586616100	HSS Dura 50 core bit with 3/4" Weldon holder, Bore Ø 52 mm, Cutting depth 50 mm	20	58
6 31 34 530 05 1	4014586616117	HSS Nova 25 core bit with 3/4" Weldon holder, Bore Ø 53 mm, Cutting depth 25 mm	20	55
6 31 34 530 05 2	4014586616131	HSS Nova 50 core bit with 3/4" Weldon holder, Bore Ø 53 mm, Cutting depth 50 mm	20	56
6 31 34 530 07 5	4014586616124	HSS Dura 25 core bit with 3/4" Weldon holder, Bore Ø 53 mm, Cutting depth 25 mm	20	57
6 31 34 530 07 6	4014586616148	HSS Dura 50 core bit with 3/4" Weldon holder, Bore Ø 53 mm, Cutting depth 50 mm	20	58
6 31 34 540 05 1	4014586616155	HSS Nova 25 core bit with 3/4" Weldon holder, Bore Ø 54 mm, Cutting depth 25 mm	20	55
6 31 34 540 05 2	4014586616179	HSS Nova 50 core bit with 3/4" Weldon holder, Bore Ø 54 mm, Cutting depth 50 mm	20	56
6 31 34 540 07 5	4014586616162	HSS Dura 25 core bit with 3/4" Weldon holder, Bore Ø 54 mm, Cutting depth 25 mm	20	57
6 31 34 540 07 6	4014586616186	HSS Dura 50 core bit with 3/4" Weldon holder, Bore Ø 54 mm, Cutting depth 50 mm	20	58
6 31 34 550 05 1	4014586616193	HSS Nova 25 core bit with 3/4" Weldon holder, Bore Ø 55 mm, Cutting depth 25 mm	20	55
6 31 34 550 05 2	4014586616216	HSS Nova 50 core bit with 3/4" Weldon holder, Bore Ø 55 mm, Cutting depth 50 mm	20	56
6 31 34 550 05 3	4014586616230	HSS Nova 75 core bit with 3/4" Weldon holder, Bore Ø 55 mm, Cutting depth 75 mm	20	
6 31 34 550 07 5	4014586616209	HSS Dura 25 core bit with 3/4" Weldon holder, Bore Ø 55 mm, Cutting depth 25 mm	20	57

Part number	EAN	Description	PC	Page
6 31 34 550 07 6	4014586616223	HSS Dura 50 core bit with 3/4" Weldon holder, Bore Ø 55 mm, Cutting depth 50 mm	20	58
6 31 34 555 05 1	4014586613284	HSS Nova 1 in core bit with Weldon holder	20	
6 31 34 555 05 3	4014586613321	HSS Nova 3 in core bit with Weldon holder	20	
6 31 34 560 05 1	4014586616247	HSS Nova 25 core bit with 3/4" Weldon holder, Bore Ø 56 mm, Cutting depth 25 mm	20	55
6 31 34 560 05 2	4014586616261	HSS Nova 50 core bit with 3/4" Weldon holder, Bore Ø 56 mm, Cutting depth 50 mm	20	56
6 31 34 560 07 5	4014586616254	HSS Dura 25 core bit with 3/4" Weldon holder, Bore Ø 56 mm, Cutting depth 25 mm	20	57
6 31 34 560 07 6	4014586616278	HSS Dura 50 core bit with 3/4" Weldon holder, Bore Ø 56 mm, Cutting depth 50 mm	20	58
6 31 34 570 05 1	4014586616285	HSS Nova 25 core bit with 3/4" Weldon holder, Bore Ø 57 mm, Cutting depth 25 mm	20	55
6 31 34 570 05 2	4014586616308	HSS Nova 50 core bit with 3/4" Weldon holder, Bore Ø 57 mm, Cutting depth 50 mm	20	56
6 31 34 570 07 5	4014586616292	HSS Dura 25 core bit with 3/4" Weldon holder, Bore Ø 57 mm, Cutting depth 25 mm	20	57
6 31 34 570 07 6	4014586616315	HSS Dura 50 core bit with 3/4" Weldon holder, Bore Ø 57 mm, Cutting depth 50 mm	20	58
6 31 34 580 05 1	4014586616322	HSS Nova 25 core bit with 3/4" Weldon holder, Bore Ø 58 mm, Cutting depth 25 mm	20	55
6 31 34 580 05 2	4014586616346	HSS Nova 50 core bit with 3/4" Weldon holder, Bore Ø 58 mm, Cutting depth 50 mm	20	56
6 31 34 580 07 5	4014586616339	HSS Dura 25 core bit with 3/4" Weldon holder, Bore Ø 58 mm, Cutting depth 25 mm	20	57
6 31 34 580 07 6	4014586616353	HSS Dura 50 core bit with 3/4" Weldon holder, Bore Ø 58 mm, Cutting depth 50 mm	20	58
6 31 34 590 05 1	4014586616360	HSS Nova 25 core bit with 3/4" Weldon holder, Bore Ø 59 mm, Cutting depth 25 mm	20	55
6 31 34 590 05 2	4014586616384	HSS Nova 50 core bit with 3/4" Weldon holder, Bore Ø 59 mm, Cutting depth 50 mm	20	56
6 31 34 590 07 5	4014586616377	HSS Dura 25 core bit with 3/4" Weldon holder, Bore Ø 59 mm, Cutting depth 25 mm	20	57
6 31 34 590 07 6	4014586616391	HSS Dura 50 core bit with 3/4" Weldon holder, Bore Ø 59 mm, Cutting depth 50 mm	20	58
6 31 34 600 05 1	4014586616407	HSS Nova 25 core bit with 3/4" Weldon holder, Bore Ø 60 mm, Cutting depth 25 mm	20	55
6 31 34 600 05 2	4014586616421	HSS Nova 50 core bit with 3/4" Weldon holder, Bore Ø 60 mm, Cutting depth 50 mm	20	56
6 31 34 600 05 3	4014586616445	HSS Nova 75 core bit with 3/4" Weldon holder, Bore Ø 60 mm, Cutting depth 75 mm	20	56
6 31 34 600 07 5	4014586616414	HSS Dura 25 core bit with 3/4" Weldon holder, Bore Ø 60 mm, Cutting depth 25 mm	20	57
6 31 34 600 07 6	4014586616438	HSS Dura 50 core bit with 3/4" Weldon holder, Bore Ø 60 mm, Cutting depth 50 mm	20	58
6 31 34 998 30 0	4014586629926	Centering pin, L 82 mm, Ø 6.35 mm	02	31
6 31 34 998 31 0	4014586629940	Centering pin, L 100 mm, Ø 6.35 mm	02	31
6 31 34 998 31 5	4014586629957	Centering pin, L 100 mm, Ø 4.75 mm	02	
6 31 34 998 33 0	4014586629971	Centering pin, L 125 mm, Ø 6.35 mm	02	58
6 31 34 998 33 5	4014586633084	Centering pin, L 135 mm, Ø 6.35 mm	02	58
6 31 34 999 06 1	4014586375588	Best of core bits 3/4" Weldon	20	28
6 31 34 999 06 2	4014586375595	Best of core bits 3/4" Weldon	20	28
6 31 34 999 06 3	4014586375601	Best of core bits 3/4" Weldon	20	28
6 31 34 999 06 4	4014586375618	Best of core bits 3/4" Weldon	20	28
6 32 02 003 01 4	4014586176925	Key-type drill chucks	02	
6 32 02 028 01 9	4014586176963	Key-type drill chucks	02	
6 32 02 030 01 5	4014586176987	Key-type drill chucks, Chuck opening 1.5-13 mm	02	73
6 32 02 037 01 0	4014586177007	Key-type drill chucks, Chuck opening 3-16 mm	02	73
6 32 02 043 01 0	4014586177038	Key-type drill chucks, Chuck opening 0.5-8 mm	02	77
6 32 02 044 01 8	4014586223674	Key-type drill chucks, Chuck opening 0.8-10 mm	02	77
6 32 03 034 01 0	4014586177052	Key-type drill chucks, Chuck opening 1-10 mm	02	73
6 32 03 041 01 4	4014586177083	Key-type drill chucks, Chuck opening 1.5-13 mm	02	73
6 32 03 050 01 4	4014586204291	Key-type drill chucks	02	
6 32 04 025 00 3	4014586177250	Quick-action chucks Quick-action chucks, Chuck opening 3-16 mm	02	73
6 32 04 028 00 8	4014586177281 4014586177311		02	
6 32 04 030 00 4	4014586177335	Quick-action chucks Quick-action chucks	02	<u>_</u>
	4014586177359	Quick-action chucks, Chuck opening 1-13 mm	02	73
6 32 04 032 00 6			02	
	4014586472270	Quick-clamping drill chuck and chucking force safety device with 3/4" Weldon fitting, Chuck opening 1 - 13 mm		
6 32 05 032 01 6	4014586256795	Quick-action chuck	02	
6 32 05 033 01 0	4014586266084	Quick-action chucks, Chuck opening 1-13 mm		73
6 32 05 035 01 0	4014586321721 4014586321738	Quick-action chucks, Chuck opening 1.5-13 mm Quick-action chucks, Chuck opening 0.5 - 10 mm	02	73
			02	
6 32 05 037 02 0	4014586365091	Ouisk-action shucks Chuck opening 3-16 mm	02	
6 32 05 038 01 0	4014586368870	Quick-action chucks, Chuck opening 3-16 mm		73
6 32 06 018 00 5	4014586177410	Jaw chuck	02	
6 32 06 018 01 0	4014586336459	Jaw chuck	02	77
6 32 06 019 00 9	4014586177427	Jaw chuck Floating investurely	02	77
6 32 06 040 00 9	4014586177441	Floating jaw chuck	02	
6 32 06 041 00 8	4014586177458	Floating jaw chuck	02	77
6 32 06 061 02 1	4014586177465	Floating collet chuck	UZ	

Part number	EAN	Description	PC	Page
6 32 06 063 01 2	4014586177489	Collet chuck	02	77
6 32 06 064 00 1	4014586177496	Collets, Ø 3.5 mm, Square 2.7 mm	02	77
6 32 06 065 00 5	4014586177502	Collets, Ø 4.5 mm, Square 3.4 mm	02	77
6 32 06 066 00 8	4014586177519	Collets, Ø 6 mm, Square 4.9 mm	02	77
6 32 06 067 01 1	4014586177526	Collet chuck	02	_
6 32 06 067 02 0	4014586336749	Collet chuck	02	
6 32 06 070 00 6	4014586177533	Collets, Ø 7 mm, Square 5.5 mm	02	77
6 32 06 075 00 4	4014586177588	Collets, Ø 9 mm, Square 7 mm	02	77
6 32 06 076 02 2	4014586177595	Floating collet chuck	02	77
6 32 06 077 00 1	4014586177601	Collets, Ø 2.8 mm, Square 2.1 mm	02	77
6 32 06 078 00 9	4014586177618	Collets, Ø 8 mm, Square 6.2 mm	02	77
6 32 06 079 00 3	4014586177625	Collets, Ø 10 mm, Square 8 mm	02	77
6 32 06 095 01 1	4014586224350	Tapping Inserts, Thread M 6, Ø 6 mm, Square 4.9 mm	02	60
6 32 06 096 01 4	4014586224367	Tapping Inserts, Thread M 10, Ø 7 mm, Square 5.5 mm	02	60
6 32 06 097 01 8	4014586224374	Tapping Inserts, Thread M 12, Ø 9 mm, Square 7 mm	02	60
6 32 06 098 01 6	4014586224381	Tapping Inserts, Thread M 14, Ø 11 mm, Square 9 mm	02	60
6 32 06 099 01 0	4014586224398	Tapping Inserts, Thread M 16, Ø 12 mm, Square 9 mm	02	60
6 32 06 100 01 1	4014586224404	Tapping Inserts, Thread M 18, Ø 14 mm, Square 11 mm	02	60
6 32 06 101 01 0	4014586224411	Tapping Inserts, Thread M 20, Ø 16 mm, Square 12 mm	02	60
6 32 06 102 01 3	4014586229294	Tapping Inserts, Thread M 8, Ø 6 mm, Square 4.9 mm	02	61
6 32 06 103 01 7	4014586229300	Tapping Inserts, Thread M 10, Ø 7 mm, Square 5.5 mm	02	61
6 32 06 104 01 5	4014586229317	Tapping Inserts, Thread M 12, Ø 9 mm, Square 7 mm	02	61
6 32 06 105 01 9	4014586229324	Tapping Inserts, Thread M 14, Ø 11 mm, Square 9 mm	02	61
6 32 06 106 01 2	4014586229331	Tapping Inserts, Thread M 16, Ø 12 mm, Square 9 mm	02	61
6 32 06 107 01 6	4014586229348	Tapping Inserts, Thread M 18, Ø 14 mm, Square 11 mm	02	61
6 32 06 108 01 4	4014586229355	Tapping Inserts, Thread M 20, Ø 16 mm, Square 12 mm	02	61
6 32 06 117 01 5	4014586253459	Tapping Inserts, Thread M 6, Ø 4.5 mm, Square 3.4 mm	02	60
6 32 06 118 01 3	4014586253466	Tapping Inserts, Thread M 6, Ø 6 mm, Square 4.9 mm	02	61
6 32 06 119 01 0	4014586298689	Tapping Inserts, Thread M22/M24, Ø 18 mm, Square 14.5 mm	02	61
6 32 06 120 01 0	4014586298696	Tapping Inserts, Thread M 27, Ø 20 mm, Square 16 mm	02	61
6 32 06 121 01 0	4014586298702	Tapping Inserts, Thread M 30, Ø 22 mm, Square 18 mm	02	61
6 32 06 122 01 0	4014586298719	Tapping Inserts, Thread M22/M24, Ø 18 mm, Square 14.5 mm	02	61
6 32 06 123 01 0	4014586298726	Tapping Inserts, Thread M 27, Ø 20 mm, Square 16 mm	02	61
6 32 06 124 01 0	4014586298733	Tapping Inserts, Thread M 30, Ø 22 mm, Square 18 mm	02	61
6 32 06 125 01 0	4014586298740	Interchangeable reducing insert (size 3 to size 2)	02	61
6 32 06 138 01 0	4014586354446	Tapping Inserts, Thread M 8, Ø 8 mm, Square 6.2 mm	02	60
6 32 06 139 01 0	4014586354453	Tapping Inserts, Thread M 10, Ø 10 mm, Square 8 mm	02	60
6 32 06 140 01 0	4014586354460	Tapping Inserts, Thread M 8, Ø 8 mm, Square 6.2 mm	02	61
6 32 06 141 01 0	4014586354477	Tapping Inserts, Thread M 10, Ø 10 mm, Square 8 mm	02	61
6 32 06 146 01 0	4014586633435	Adapter with 3/4" Weldon fitting, Ø 6 mm, Square 4.9 mm	02	32
6 32 06 147 01 0	4014586633442	Adapter with 3/4" Weldon fitting, Ø 7 mm, Square 5.5 mm	02	32
6 32 06 148 01 0	4014586633459	Adapter with 3/4" Weldon fitting	02	32
6 32 06 149 01 0	4014586634562	Adapter with 3/4" Weldon fitting, Ø 9 mm, Square 7 mm	02	32
6 32 06 155 01 0	4014586425450	Tapping Inserts, Thread M 33, Ø 25 mm, Square 20 mm	02	61
6 32 06 156 01 0	4014586425467	Tapping Inserts, Thread M 36, Ø 28 mm, Square 22 mm	02	61
6 32 06 157 01 0	4014586425474	Tapping Inserts, Thread M 33, Ø 25 mm, Square 20 mm	02	61
6 32 06 158 01 0	4014586425481	Tapping Inserts, Thread M 36, Ø 28 mm, Square 22 mm	02	61
6 32 07 059 00 6	4014586177786	Collets, Ø 6 mm	02	
6 32 07 069 00 5	4014586177793	Collets, Ø 8 mm	02	
6 32 07 087 00 1	4014586177809	Collets, Ø 3 mm	02	
6 32 07 088 00 9	4014586177816	Collets, Ø 1/4"	02	
6 32 07 097 00 0	4014586177861	Collets, Ø 3 mm	02	
6 32 07 103 00 9	4014586177922	Collets, Ø 6 mm	02	
6 32 07 128 00 0	4014586375922	Collets, Ø 6 mm	02	126
6 32 07 129 00 0	4014586375939	Collets, Ø 8 mm	02	126
6 32 07 130 00 0	4014586375946	Collets, Ø 3 mm	02	126
6 32 07 131 00 0	4014586375953	Collets, Ø 1/4"	02	126
6 32 07 132 00 0	4014586375960	Collets Inox, Ø 3 mm	02	126
6 32 07 133 00 0	4014586375977	Collets Inox, Ø 6 mm	02	126
6 32 07 134 00 0	4014586375984	Collets Inox, Ø 8 mm	02	126

Part number	EAN	Description	PC	Page
6 32 07 135 00 0	4014586375991	Collets Inox, Ø 1/4"	02	126
6 32 08 001 02 0	4014586368153	Drill chuck	02	
6 32 08 002 01 0	4014586392080	Drill chuck, Accessory interface QuickIN	02	87
6 32 08 005 01 0	4014586404837	Drill chuck, Accessory interface QuickIN	02	87
6 33 01 006 00 5	4014586178103	Morse taper arbors	02	
6 33 01 008 00 7	4014586178110	Morse taper arbors	02	
6 33 01 012 00 5	4014586178141	Morse taper arbors, Mount MT 3/B 16	02	59 59
6 33 01 014 00 7	4014586178165 4014586178172	Morse taper arbors, Mount MT 3/B 22 Morse taper arbors, Mount MT 4/B 22	02	59
6 33 01 021 00 1	4014586223704	Morse taper arbors	02	
6 33 02 002 00 0	4014586178189	Reducing sleeves	02	
6 33 02 003 00 4	4014586178196	Reducing sleeves	02	73
6 33 02 004 00 2	4014586178202	Reducing sleeves, Mount MT 4/MT 3	02	59
6 33 04 003 00 2	4014586178226	Enlargement tapers	02	
6 33 04 005 00 0	4014586312996	Enlargement tapers, Mount MT 3/MT 3	02	59
6 33 05 003 00 3	4014586178257	Drift keys, Mount MT 1/MT 2, Length 140 mm	02	73
6 33 05 004 00 1	4014586178264	Drift keys, Mount MT 3/MT 4, Length 190 mm	02	73
6 33 05 006 00 8	4014586178288	Splitter wedge	02	176
6 33 05 009 01 3	4014586230627	Drifts, Mount B 12, Length 125 mm	02	77
6 33 05 010 01 5	4014586230634	Drifts	02	_
6 33 05 013 00 2	4014586178318	Wedge	08	
6 34 02 027 00 0	4014586199672	Ratchet with square drive	02	_
6 35 02 022 00 6	4014586178417	Circular saw blades, form 1, Width 4 mm, Teeth 50, Ø 160 mm	08	_
6 35 02 037 00 8	4014586178448	Circular saw blades, form 1, Width 4 mm, Teeth 60, Ø 180 mm	08	_
6 35 02 041 00 1	4014586178455	Circular saw blades, form 1, Width 5 mm, Teeth 70, Ø 220 mm	08	_
6 35 02 053 00 7	4014586178479	Circular saw blades, form 1, Width 4 mm, Teeth 64, Ø 200 mm	08	_
6 35 02 061 00 9	4014586178493	Circular saw blades, form 3, Width 4 mm, Teeth 44, Ø 180 mm	08	_
6 35 02 080 00 8	4014586178585	Circular saw blades, form 3, Width 4 mm, Teeth 40, Ø 160 mm	08	_
6 35 02 084 00 2	4014586178608	Circular saw blades, form 3, Width 4 mm, Teeth 50, Ø 200 mm	08	_
6 35 02 097 21 0	4014586389431	HSS saw blade, Ø 85 mm, No. in pack 1 pcs, Mount SL	04	218
6 35 02 097 22 0	4014586389448	HSS saw blade, Ø 85 mm, No. in pack 2 pcs, Mount SL	04	218
6 35 02 097 23 0	4014586389455	HSS saw blade, Ø 85 mm, No. in pack 5 pcs, Mount SL	04	218
6 35 02 102 01 6	4014586178783	Saw blades, Ø 63 mm, No. in pack 2 pcs	04	243
6 35 02 102 07 0	4014586291703	Saw blades, Ø 63 mm, No. in pack 5 pcs	04	243
6 35 02 103 01 0	4014586178806	Saw blades, Ø 80 mm, No. in pack 2 pcs	04	243
6 35 02 103 05 0	4014586291710	Saw blades, Ø 80 mm, No. in pack 5 pcs	04	243
6 35 02 106 21 0	4014586389462	HSS saw blade, Ø 85 mm, No. in pack 1 pcs, Mount SL	04	218
6 35 02 106 22 0	4014586389479	HSS saw blade, Ø 85 mm, No. in pack 2 pcs, Mount SL	04	218
6 35 02 106 23 0	4014586389486	HSS saw blade, Ø 85 mm, No. in pack 5 pcs, Mount SL	04	218
6 35 02 113 21 0	4014586390222	Saw blade, Ø 85 mm, Mount SL	04	218
6 35 02 114 21 0	4014586390239	Diamond-coated saw blade, Ø 75 mm, No. in pack 1 pcs, Mount SL	04	226
6 35 02 114 23 0	4014586390246	Diamond-coated saw blade, Ø 75 mm, No. in pack 5 pcs, Mount SL	04	226
6 35 02 115 01 1	4014586231914	Diamond-coated saw blade, Ø 80 mm, No. in pack 1 pcs	04	242
6 35 02 115 03 0	4014586315058 4014586231921	Diamond-coated saw blade, Ø 80 mm, No. in pack 5 pcs Diamond-coated saw blade, Ø 80 mm, No. in pack 1 pcs	04	242
6 35 02 116 02 0	4014586315065	Diamond-coated saw blade, Ø 80 mm, No. in pack 5 pcs	04	242
6 35 02 118 21 0	4014586389493	Carbide saw blade, Ø 75 mm, No. in pack 1 pcs, Mount SL	04	226
6 35 02 118 23 0	4014586389509	Carbide saw blade, Ø 75 mm, No. in pack 1 pcs, Mount SL	04	226
6 35 02 119 01 0	4014586232348	E-Cut precision saw blades, Width 35 mm, No. in pack 1 pcs	04	246
6 35 02 119 03 2	4014586258829	E-Cut precision saw blades, Width 35 mm, No. in pack 25 pcs	04	246
6 35 02 119 04 8	4014586264561	E-Cut precision saw blades, Width 35 mm, No. in pack 5 pcs	04	246
6 35 02 122 01 4	4014586232379	E-Cut precision saw blades, Width 65 mm, No. in pack 1 pcs	04	246
6 35 02 122 03 6	4014586258850	E-Cut precision saw blades, Width 65 mm, No. in pack 25 pcs	04	246
6 35 02 122 04 2	4014586264592	E-Cut precision saw blades, Width 65 mm, No. in pack 5 pcs	04	246
6 35 02 123 01 8	4014586232386	E-Cut standard saw blades, Width 32 mm, No. in pack 1 pcs	04	246
6 35 02 123 03 0	4014586250793	E-Cut standard saw blades, Width 32 mm, No. in pack 25 pcs	04	246
6 35 02 123 04 6	4014586264608	E-Cut standard saw blades, Width 32 mm, No. in pack 5 pcs	04	246
6 35 02 124 01 6	4014586232393	E-Cut standard saw blades, Width 42 mm, No. in pack 1 pcs	04	246
6 35 02 124 03 8	4014586250809	E-Cut standard saw blades, Width 42 mm, No. in pack 25 pcs	04	246
6 35 02 124 04 4	4014586264615	E-Cut standard saw blades, Width 42 mm, No. in pack 5 pcs	04	246

Part number	EAN	Description	PC	Page
6 35 02 125 21 0	4014586389516	Carbide saw blade, Ø 75 mm, No. in pack 1 pcs, Mount SL	04	226
6 35 02 125 23 0	4014586389523	Carbide saw blade, Ø 75 mm, No. in pack 5 pcs, Mount SL	04	226
6 35 02 126 21 0	4014586386157	E-Cut precision saw blade, Length 50 mm, Width 35 mm, No. in pack 1 pcs, Mount SL	04	220
6 35 02 126 22 0	4014586386164	E-Cut precision saw blade, Length 50 mm, Width 35 mm, No. in pack 3 pcs, Mount SL	04	220
6 35 02 126 23 0	4014586386171	E-Cut precision saw blade, Length 50 mm, Width 35 mm, No. in pack 5 pcs, Mount SL	04	220
6 35 02 126 24 0	4014586386188	E-Cut precision saw blade, Length 50 mm, Width 35 mm, No. in pack 10 pcs, Mount SL	04	220
6 35 02 126 25 0	4014586390260	E-Cut precision saw blade, Length 50 mm, Width 35 mm, No. in pack 50 pcs, Mount SL	04	220
6 35 02 127 21 0	4014586386232	E-Cut precision saw blade, Length 50 mm, Width 65 mm, No. in pack 1 pcs, Mount SLP	04	221
6 35 02 127 22 0	4014586386249	E-Cut precision saw blade, Length 50 mm, Width 65 mm, No. in pack 3 pcs, Mount SLP	04	221
6 35 02 127 23 0	4014586386256	E-Cut precision saw blade, Length 50 mm, Width 65 mm, No. in pack 5 pcs, Mount SLP	04	221
6 35 02 127 24 0	4014586386263	E-Cut precision saw blade, Length 50 mm, Width 65 mm, No. in pack 10 pcs, Mount SLP	04	221
6 35 02 127 25 0	4014586390291	E-Cut precision saw blade, Length 50 mm, Width 65 mm, No. in pack 50 pcs, Mount SLP	04	221
6 35 02 129 01 9	4014586248400	MiniCut HSS saw blade	04	_
6 35 02 130 01 1	4014586248417	MiniCut HSS saw blade	04	_
6 35 02 133 21 0	4014586386317	E-Cut standard saw blade, Length 50 mm, Width 35 mm, No. in pack 1 pcs, Mount SL	04	220
6 35 02 133 22 0	4014586386324	E-Cut standard saw blade, Length 50 mm, Width 35 mm, No. in pack 1 pcs, Mount SL	04	220
6 35 02 133 23 0	4014586386331	E-Cut standard saw blade, Length 50 mm, Width 35 mm, No. in pack 5 pcs, Mount SL	04	220
6 35 02 133 24 0			04	
	4014586386348	E-Cut standard saw blade, Length 50 mm, Width 35 mm, No. in pack 10 pcs, Mount SL		220
6 35 02 133 25 0	4014586390321	E-Cut standard saw blade, Length 50 mm, Width 35 mm, No. in pack 50 pcs, Mount SL	04	220
6 35 02 134 21 0	4014586386393	E-Cut standard saw blade, Length 50 mm, Width 65 mm, No. in pack 1 pcs, Mount SLP	04	220
6 35 02 134 22 0	4014586386409	E-Cut standard saw blade, Length 50 mm, Width 65 mm, No. in pack 3 pcs, Mount SLP	04	220
6 35 02 134 23 0	4014586386416	E-Cut standard saw blade, Length 50 mm, Width 65 mm, No. in pack 5 pcs, Mount SLP	04	220
6 35 02 134 24 0	4014586386423	E-Cut standard saw blade, Length 50 mm, Width 65 mm, No. in pack 10 pcs, Mount SLP	04	220
6 35 02 134 25 0	4014586390352	E-Cut standard saw blade, Length 50 mm, Width 65 mm, No. in pack 50 pcs, Mount SLP	04	220
6 35 02 135 01 9	4014586248486	E-Cut standard saw blades, Width 35 mm, No. in pack 1 pcs	04	246
6 35 02 135 02 5	4014586258867	E-Cut standard saw blades, Width 35 mm, No. in pack 25 pcs	04	246
6 35 02 135 03 1	4014586264622	E-Cut standard saw blades, Width 35 mm, No. in pack 5 pcs	04	246
6 35 02 136 01 2	4014586248493	E-Cut standard saw blades, Width 65 mm, No. in pack 1 pcs	04	246
6 35 02 136 02 8	4014586258874	E-Cut standard saw blades, Width 65 mm, No. in pack 25 pcs	04	246
6 35 02 136 03 4	4014586264639	E-Cut standard saw blades, Width 65 mm, No. in pack 5 pcs	04	246
6 35 02 147 01 5	4014586262321	E-Cut universal saw blades, Width 28 mm, No. in pack 1 pcs	04	243
6 35 02 147 02 1	4014586264646	E-Cut universal saw blades, Width 28 mm, No. in pack 5 pcs	04	243
6 35 02 147 03 7	4014586264721	E-Cut universal saw blades, Width 28 mm, No. in pack 25 pcs	04	246
6 35 02 147 12 0	4014586369655	Best of E-Cut accessory set	04	245
6 35 02 148 01 3	4014586262338	E-Cut universal saw blades, Width 44 mm, No. in pack 1 pcs	04	243
6 35 02 148 02 9	4014586264653	E-Cut universal saw blades, Width 44 mm, No. in pack 5 pcs	04	243
6 35 02 148 03 5	4014586264738	E-Cut universal saw blades, Width 44 mm, No. in pack 25 pcs	04	247
6 35 02 151 21 0	4014586386461	E-Cut universal saw blade, Length 60 mm, Width 28 mm, No. in pack 1 pcs, Mount SLP	04	221
6 35 02 151 22 0	4014586386478	E-Cut universal saw blade, Length 60 mm, Width 28 mm, No. in pack 1 pes, Mount SLP	04	221
6 35 02 151 23 0	4014586386485	E-Cut universal saw blade, Length 60 mm, Width 28 mm, No. in pack 5 pcs, Mount SLP	04	221
6 35 02 151 24 0	4014586386492	E-Cut universal saw blade, Length 60 mm, Width 28 mm, No. in pack 3 pcs, Mount SLP	04	221
		E-Cut universal saw blade, Length 60 mm, Width 28 mm, No. in pack 10 pcs, Mount SLP	04	221
6 35 02 151 25 0	4014586390390			
	4014586386539	E-Cut universal saw blade, Length 60 mm, Width 44 mm, No. in pack 1 pcs, Mount SLP	04	221
6 35 02 152 22 0	4014586386546	E-Cut universal saw blade, Length 60 mm, Width 44 mm, No. in pack 3 pcs, Mount SLP	04	221
6 35 02 152 23 0	4014586386553	E-Cut universal saw blade, Length 60 mm, Width 44 mm, No. in pack 5 pcs, Mount SLP	04	221
6 35 02 152 24 0	4014586386560	E-Cut universal saw blade, Length 60 mm, Width 44 mm, No. in pack 10 pcs, Mount SLP	04	221
6 35 02 152 25 0	4014586390437	E-Cut universal saw blade, Length 60 mm, Width 44 mm, No. in pack 50 pcs, Mount SLP	04	221
6 35 02 155 01 0	4014586291956	Carbide saw blade, Ø 80 mm, No. in pack 1 pcs	04	242
6 35 02 156 01 0	4014586291963	Carbide saw blade, Ø 80 mm, No. in pack 1 pcs	04	242
6 35 02 157 21 0	4014586386614	E-Cut fine saw blade, Length 50 mm, Width 30 mm, No. in pack 1 pcs, Mount SL	04	221
6 35 02 157 22 0	4014586386621	E-Cut fine saw blade, Length 50 mm, Width 30 mm, No. in pack 3 pcs, Mount SL	04	221
6 35 02 157 23 0	4014586386638	E-Cut fine saw blade, Length 50 mm, Width 30 mm, No. in pack 5 pcs, Mount SL	04	221
6 35 02 157 24 0	4014586386645	E-Cut fine saw blade, Length 50 mm, Width 30 mm, No. in pack 10 pcs, Mount SL	04	221
6 35 02 157 25 0	4014586390451	E-Cut fine saw blade, Length 50 mm, Width 30 mm, No. in pack 50 pcs, Mount SL	04	221
6 35 02 160 21 0	4014586386690	E-Cut long-life saw blade, Length 50 mm, Width 35 mm, No. in pack 1 pcs, Mount SL	04	219
6 35 02 160 22 0	4014586386706	E-Cut long-life saw blade, Length 50 mm, Width 35 mm, No. in pack 3 pcs, Mount SL	04	219
6 35 02 160 23 0	4014586386713	E-Cut long-life saw blade, Length 50 mm, Width 35 mm, No. in pack 5 pcs, Mount SL	04	219
6 35 02 160 24 0	4014586386720	E-Cut long-life saw blade, Length 50 mm, Width 35 mm, No. in pack 10 pcs, Mount SL	04	219
6 35 02 160 25 0	4014586390482	E-Cut long-life saw blade, Length 50 mm, Width 35 mm, No. in pack 50 pcs, Mount SL	04	219
6 35 02 161 21 0	4014586386775	E-Cut long-life saw blade, Length 50 mm, Width 65 mm, No. in pack 1 pcs, Mount SLP	04	219
		<u> </u>		

Part number	EAN	Description	PC	Page
6 35 02 161 22 0	4014586386782	E-Cut long-life saw blade, Length 50 mm, Width 65 mm, No. in pack 3 pcs, Mount SLP	04	219
6 35 02 161 23 0	4014586386799	E-Cut long-life saw blade, Length 50 mm, Width 65 mm, No. in pack 5 pcs, Mount SLP	04	219
6 35 02 161 24 0	4014586386805	E-Cut long-life saw blade, Length 50 mm, Width 65 mm, No. in pack 10 pcs, Mount SLP	04	219
6 35 02 161 25 0	4014586390512	E-Cut long-life saw blade, Length 50 mm, Width 65 mm, No. in pack 50 pcs, Mount SLP	04	219
6 35 02 162 01 0	4014586336008	E-Cut long-life saw blades, Width 32 mm, No. in pack 1 pcs	04	246
6 35 02 162 02 0	4014586336015	E-Cut long-life saw blades, Width 32 mm, No. in pack 5 pcs	04	246
6 35 02 162 03 0	4014586336022	E-Cut long-life saw blades, Width 32 mm, No. in pack 25 pcs	04	246
6 35 02 163 01 0	4014586336039 4014586336046	E-Cut long-life saw blades, Width 42 mm, No. in pack 1 pcs	04	246
6 35 02 163 02 0	4014586336046	E-Cut long-life saw blades, Width 42 mm, No. in pack 5 pcs	04	246
6 35 02 164 01 0	4014586336060	E-Cut long-life saw blades, Width 42 mm, No. in pack 25 pcs E-Cut long-life saw blades, Width 35 mm, No. in pack 1 pcs	04	246
6 35 02 164 02 0	4014586336000	E-Cut long-life saw blades, Width 35 mm, No. in pack 1 pcs	04	246
6 35 02 164 03 0	4014586336084	E-Cut long-life saw blades, Width 35 mm, No. in pack 25 pcs	04	246
6 35 02 165 01 0	4014586336091	E-Cut long-life saw blades, Width 65 mm, No. in pack 1 pcs	04	246
6 35 02 165 02 0	4014586336107	E-Cut long-life saw blades, Width 65 mm, No. in pack 5 pcs	04	246
6 35 02 165 03 0	4014586336114	E-Cut long-life saw blades, Width 65 mm, No. in pack 25 pcs	04	246
6 35 02 166 21 0	4014586390536	Diamond-coated saw blade, Ø 90 mm, No. in pack 1 pcs, Mount SL	04	227
6 35 02 166 23 0	4014586390543	Diamond-coated saw blade, Ø 90 mm, No. in pack 5 pcs, Mount SL	04	227
6 35 02 167 01 0	4014586342023	Diamond-coated saw blade, Ø 105 mm, No. in pack 1 pcs	04	
6 35 02 168 01 0	4014586342047	Diamond-coated saw blade, Ø 105 mm, No. in pack 1 pcs	04	
6 35 02 168 02 0	4014586342054	Diamond-coated saw blade, Ø 105 mm, No. in pack 5 pcs	04	
6 35 02 169 21 0	4014586390550	Carbide saw blade, Ø 90 mm, No. in pack 1 pcs, Mount SLP	04	226
6 35 02 169 23 0	4014586390567	Carbide saw blade, Ø 90 mm, No. in pack 5 pcs, Mount SLP	04	226
6 35 02 170 21 0	4014586390574	Carbide saw blade, Ø 90 mm, No. in pack 1 pcs, Mount SLP	04	226
6 35 02 170 23 0	4014586390581	Carbide saw blade, Ø 90 mm, No. in pack 5 pcs, Mount SLP	04	226
6 35 02 172 01 0	4014586347691	Carbide saw blade, Ø 105 mm, No. in pack 1 pcs	04	
6 35 02 172 02 0	4014586347707	Carbide saw blade, Ø 105 mm, No. in pack 5 pcs	04	_
6 35 02 173 01 0	4014586347714	Carbide saw blade, Ø 105 mm, No. in pack 1 pcs	04	_
6 35 02 174 21 0	4014586389530	HSS saw blade, Ø 85 mm, No. in pack 1 pcs, Mount SL	04	218
6 35 02 174 23 0	4014586389547	HSS saw blade, Ø 85 mm, No. in pack 5 pcs, Mount SL	04	218
6 35 02 175 21 0	4014586389554	HSS saw blade, Ø 100 mm, No. in pack 1 pcs, Mount SLP	04	218
6 35 02 175 23 0	4014586389561	HSS saw blade, Ø 100 mm, No. in pack 5 pcs, Mount SLP	04	218
6 35 02 176 21 0	4014586389578	HSS saw blade, Ø 100 mm, No. in pack 1 pcs, Mount SLP	04	218
6 35 02 177 01 0	4014586379494	Saw blades, Ø 85 mm, No. in pack 1 pcs	04	245
6 35 02 177 05 0	4014586379500	Saw blades, Ø 85 mm, No. in pack 5 pcs	04	245
6 35 02 178 01 0	4014586379517	Saw blades, Ø 100 mm, No. in pack 1 pcs	04	245
6 35 02 178 05 0	4014586379524	Saw blades, Ø 100 mm, No. in pack 5 pcs	04	245
6 35 02 179 01 0	4014586379272	HSS saw blade wood, Width 100 mm, No. in pack 1 pcs	04	247
6 35 02 179 02 0	4014586379289	HSS saw blade wood, Width 100 mm, No. in pack 1 pcs	04	247
6 35 02 181 00 0	4014586354606	Circular saw blade	08	
6 35 02 183 21 0	4014586386850	E-Cut long-life saw blade, Length 34 mm, Width 20 mm, No. in pack 1 pcs, Mount SL	04	219
6 35 02 183 22 0	4014586386867	E-Cut long-life saw blade, Length 34 mm, Width 20 mm, No. in pack 3 pcs, Mount SL	04	219
6 35 02 183 23 0	4014586386874	E-Cut long-life saw blade, Length 34 mm, Width 20 mm, No. in pack 5 pcs, Mount SL	04	219
6 35 02 183 24 0	4014586386881 4014586390604	E-Cut long-life saw blade, Length 34 mm, Width 20 mm, No. in pack 10 pcs, Mount SL E-Cut long-life saw blade, Length 34 mm, Width 20 mm, No. in pack 50 pcs, Mount SL	04	219
6 35 02 184 21 0	4014586386935	E-Cut long-life saw blade, Length 34 mm, Width 10 mm, No. in pack 30 pcs, Mount SL	04	219
6 35 02 184 22 0	4014586386942	E-Cut long-life saw blade, Length 30 mm, Width 10 mm, No. in pack 3 pcs, Mount SL	04	219
6 35 02 184 23 0	4014586386959	E-Cut long-life saw blade, Length 30 mm, Width 10 mm, No. in pack 5 pcs, Mount SL	04	219
6 35 02 184 24 0	4014586386966	E-Cut long-life saw blade, Length 30 mm, Width 10 mm, No. in pack 10 pcs, Mount SL	04	219
6 35 02 184 25 0	4014586390635	E-Cut long-life saw blade, Length 30 mm, Width 10 mm, No. in pack 50 pcs, Mount SL	04	219
6 35 02 185 03 0	4014586369747	E-Cut long-life saw blades, Width 20 mm, No. in pack 25 pcs	04	
6 35 02 187 21 0	4014586390659	Carbide saw blade, Ø 90 mm, Mount SLP	04	222
6 35 02 188 21 0	4014586390666	Diamond-coated saw blade, Ø 90 mm, Mount SLP	04	222
6 35 02 189 01 0	4014586377537	Carbide saw blade with open teeth, Ø 105 mm, Cutting width 1.2 mm	04	247
6 35 02 190 01 0	4014586377544	Diamond segment saw blade with open teeth, Ø 105 mm, Cutting width 1.2 mm	04	247
6 35 02 191 21 0	4014586389585	E-Cut carbide saw blade, Length 50 mm, Width 35 mm, Mount SLP	04	222
6 35 02 193 21 0	4014586389592	E-Cut diamond saw blade, Length 50 mm, Width 35 mm, Mount SLP	04	222
6 35 02 195 01 0	4014586378183	E-Cut diamond saw blade, Length 60 mm, Width 42 mm	04	247
6 35 02 196 01 0	4014586379531	Segment saw blade, Ø 100 mm, No. in pack 1 pcs	04	245
6 35 02 196 05 0	4014586379548	Segment saw blade, Ø 100 mm, No. in pack 5 pcs	04	245
			-	

Part number	EAN	Description	PC	Page
6 35 02 196 21 0	4014586389608	HSS saw blade, Ø 100 mm, No. in pack 1 pcs, Mount SL	04	218
6 35 02 196 23 0	4014586389615	HSS saw blade, Ø 100 mm, No. in pack 5 pcs, Mount SL	04	218
6 35 02 200 21 0	4014586387178	E-Cut standard saw blade, Length 78 mm, Width 32 mm, No. in pack 1 pcs, Mount SLM	04	220
6 35 02 200 22 0	4014586387185	E-Cut standard saw blade, Length 78 mm, Width 32 mm, No. in pack 3 pcs, Mount SLM	04	220
6 35 02 200 23 0	4014586387192	E-Cut standard saw blade, Length 78 mm, Width 32 mm, No. in pack 5 pcs, Mount SLM	04	220
6 35 02 200 24 0	4014586387208	E-Cut standard saw blade, Length 78 mm, Width 32 mm, No. in pack 10 pcs, Mount SLM	04	220
6 35 02 200 25 0	4014586390710	E-Cut standard saw blade, Length 78 mm, Width 32 mm, No. in pack 50 pcs, Mount SLM	04	220
6 35 02 201 21 0	4014586387253	E-Cut long-life saw blade, Length 78 mm, Width 32 mm, No. in pack 1 pcs, Mount SLM	04	219
6 35 02 201 22 0	4014586387260	E-Cut long-life saw blade, Length 78 mm, Width 32 mm, No. in pack 3 pcs, Mount SLM	04	219
6 35 02 201 23 0	4014586387277	E-Cut long-life saw blade, Length 78 mm, Width 32 mm, No. in pack 5 pcs, Mount SLM	04	219
6 35 02 201 24 0	4014586387284	E-Cut long-life saw blade, Length 78 mm, Width 32 mm, No. in pack 10 pcs, Mount SLM	04	219
6 35 02 201 25 0	4014586390734	E-Cut long-life saw blade, Length 78 mm, Width 32 mm, No. in pack 50 pcs, Mount SLM	04	219
6 35 02 202 21 0	4014586387338	E-Cut standard saw blade, Length 78 mm, Width 42 mm, No. in pack 1 pcs, Mount SLM	04	220
6 35 02 202 22 0	4014586387345	E-Cut standard saw blade, Length 78 mm, Width 42 mm, No. in pack 3 pcs, Mount SLM	04	220
6 35 02 202 23 0	4014586387352	E-Cut standard saw blade, Length 78 mm, Width 42 mm, No. in pack 5 pcs, Mount SLM	04	220
6 35 02 202 24 0	4014586387369	E-Cut standard saw blade, Length 78 mm, Width 42 mm, No. in pack 10 pcs, Mount SLM	04	220
6 35 02 202 25 0	4014586390802	E-Cut standard saw blade, Length 78 mm, Width 42 mm, No. in pack 50 pcs, Mount SLM	04	220
6 35 02 203 21 0	4014586387413	E-Cut long-life saw blade, Length 78 mm, Width 42 mm, No. in pack 1 pcs, Mount SLM	04	219
6 35 02 203 22 0	4014586387420	E-Cut long-life saw blade, Length 78 mm, Width 42 mm, No. in pack 3 pcs, Mount SLM	04	219
6 35 02 203 23 0	4014586387437	E-Cut long-life saw blade, Length 78 mm, Width 42 mm, No. in pack 5 pcs, Mount SLM	04	219
6 35 02 203 24 0	4014586387444	E-Cut long-life saw blade, Length 78 mm, Width 42 mm, No. in pack 10 pcs, Mount SLM	04	219
6 35 02 203 25 0	4014586390826	E-Cut long-life saw blade, Length 78 mm, Width 42 mm, No. in pack 50 pcs, Mount SLM	04	219
6 35 02 204 21 0	4014586389622	E-Cut diamond saw blade, Length 60 mm, Width 44 mm, Mount SLM	04	222
6 35 02 205 21 0	4014586387499	E-Cut precision BIM saw blade, Length 50 mm, Width 35 mm, No. in pack 1 pcs, Mount SL	04	220
6 35 02 205 22 0	4014586387505	E-Cut precision BIM saw blade, Length 50 mm, Width 35 mm, No. in pack 3 pcs, Mount SL	04	220
6 35 02 205 23 0	4014586387512	E-Cut precision BIM saw blade, Length 50 mm, Width 35 mm, No. in pack 5 pcs, Mount SL	04	220
6 35 02 205 24 0	4014586387529	E-Cut precision BIM saw blade, Length 50 mm, Width 35 mm, No. in pack 10 pcs, Mount SL	04	220
6 35 02 205 25 0	4014586390840	E-Cut precision BIM saw blade, Length 50 mm, Width 35 mm, No. in pack 50 pcs, Mount SL	04	220
6 35 02 208 21 0	4014586387734	E-Cut precision BIM saw blade, Length 50 mm, Width 65 mm, No. in pack 1 pcs, Mount SLP	04	220
6 35 02 208 22 0	4014586387741	E-Cut precision BIM saw blade, Length 50 mm, Width 65 mm, No. in pack 3 pcs, Mount SLP	04	220
6 35 02 208 23 0	4014586387758	E-Cut precision BIM saw blade, Length 50 mm, Width 65 mm, No. in pack 5 pcs, Mount SLP	04	220
6 35 02 208 24 0	4014586387765	E-Cut precision BIM saw blade, Length 50 mm, Width 65 mm, No. in pack 10 pcs, Mount SLP	04	220
6 35 02 208 25 0	4014586390901	E-Cut precision BIM saw blade, Length 50 mm, Width 65 mm, No. in pack 50 pcs, Mount SLP	04	220
6 35 02 209 01 0	4014586381602	E-Cut precision BIM saw blade, Width 35 mm, No. in pack 1 pcs	04	246
6 35 02 209 02 0	4014586381619	E-Cut precision BIM saw blade, Width 35 mm, No. in pack 5 pcs	04	246
6 35 02 209 03 0	4014586381626	E-Cut precision BIM saw blade, Width 35 mm, No. in pack 25 pcs	04	246
6 35 02 212 01 0	4014586381695	E-Cut precision BIM saw blade, Width 65 mm, No. in pack 1 pcs	04	246
6 35 02 212 02 0	4014586381701	E-Cut precision BIM saw blade, Width 65 mm, No. in pack 5 pcs	04	246
6 35 02 212 03 0	4014586381718	E-Cut precision BIM saw blade, Width 65 mm, No. in pack 25 pcs	04	246
6 35 02 213 23 0	4014586390932	Carbide saw blade, Ø 105 mm, No. in pack 5 pcs, Mount SLM	04	
6 35 02 216 21 0	4014586390970	Diamond-coated saw blade, Ø 75 mm, No. in pack 1 pcs, Mount SL	04	226
6 35 02 216 23 0	4014586390987	Diamond-coated saw blade, Ø 75 mm, No. in pack 5 pcs, Mount SL	04	226
6 35 02 217 21 0	4014586390994	Diamond-coated saw blade, Ø 90 mm, No. in pack 1 pcs, Mount SLP	04	226
6 35 02 217 23 0	4014586391007	Diamond-coated saw blade, Ø 90 mm, No. in pack 5 pcs, Mount SLP	04	226
6 35 02 220 21 0	4014586391052	Diamond-coated saw blade, Ø 105 mm, Mount SLM	04	222
6 35 02 221 21 0	4014586400402	E-Cut long-life saw blade, Length 50 mm, Width 50 mm, No. in pack 1 pcs, Mount SL	04	219
6 35 02 221 22 0	4014586400419	E-Cut long-life saw blade, Length 50 mm, Width 50 mm, No. in pack 3 pcs, Mount SL	04	219
6 35 02 221 23 0	4014586400426	E-Cut long-life saw blade, Length 50 mm, Width 50 mm, No. in pack 5 pcs, Mount SL	04	219
6 35 02 221 24 0	4014586400433	E-Cut long-life saw blade, Length 50 mm, Width 50 mm, No. in pack 10 pcs, Mount SL	04	219
6 35 02 221 25 0	4014586400440	E-Cut long-life saw blade, Length 50 mm, Width 50 mm, No. in pack 50 pcs, Mount SL	04	219
6 35 02 222 21 0	4014586400457	E-Cut universal saw blade, Length 55 mm, Width 28 mm, No. in pack 1 pcs, Mount SL	04	221
6 35 02 222 22 0	4014586400464	E-Cut universal saw blade, Length 55 mm, Width 28 mm, No. in pack 3 pcs, Mount SL	04	221
6 35 02 222 23 0	4014586400471	E-Cut universal saw blade, Length 55 mm, Width 28 mm, No. in pack 5 pcs, Mount SL	04	221
6 35 02 222 24 0	4014586400488	E-Cut universal saw blade, Length 55 mm, Width 28 mm, No. in pack 10 pcs, Mount SL	04	221
6 35 02 222 25 0	4014586400495	E-Cut universal saw blade, Length 55 mm, Width 28 mm, No. in pack 50 pcs, Mount SL	04	221
6 35 02 223 21 0	4014586400501	E-Cut universal saw blade, Length 55 mm, Width 44 mm, No. in pack 1 pcs, Mount SL	04	221
6 35 02 223 22 0	4014586400518	E-Cut universal saw blade, Length 55 mm, Width 44 mm, No. in pack 3 pcs, Mount SL	04	221
6 35 02 223 23 0	4014586400525	E-Cut universal saw blade, Length 55 mm, Width 44 mm, No. in pack 5 pcs, Mount SL	04	221
6 35 02 223 24 0	4014586400532	E-Cut universal saw blade, Length 55 mm, Width 44 mm, No. in pack 10 pcs, Mount SL	04	221
6 35 02 223 25 0	4014586400549	E-Cut universal saw blade, Length 55 mm, Width 44 mm, No. in pack 50 pcs, Mount SL	04	221

Part number	EAN	Description	PC	Page
6 35 02 224 21 0	4014586408170	E-Cut long-life saw blade, Length 90 mm, Width 32 mm, No. in pack 1 pcs, Mount SLM	04	219
6 35 02 224 22 0	4014586408187	E-Cut long-life saw blade, Length 90 mm, Width 32 mm, No. in pack 3 pcs, Mount SLM	04	219
6 35 02 224 23 0	4014586408194	E-Cut long-life saw blade, Length 90 mm, Width 32 mm, No. in pack 5 pcs, Mount SLM	04	219
6 35 02 224 24 0	4014586408200	E-Cut long-life saw blade, Length 90 mm, Width 32 mm, No. in pack 10 pcs, Mount SLM	04	219
6 35 02 224 25 0	4014586408217	E-Cut long-life saw blade, Length 90 mm, Width 32 mm, No. in pack 50 pcs, Mount SLM	04	219
6 35 02 225 21 0	4014586408262	E-Cut standard saw blade curved, Length 50 mm, Width 65 mm, No. in pack 1 pcs, Mount SL	04	220
6 35 02 225 22 0	4014586408279	E-Cut standard saw blade curved, Length 50 mm, Width 65 mm, No. in pack 3 pcs, Mount SL	04	220
6 35 02 225 23 0	4014586408286	E-Cut standard saw blade curved, Length 50 mm, Width 65 mm, No. in pack 5 pcs, Mount SL	04	220
6 35 02 225 24 0	4014586408293 4014586408309	E-Cut standard saw blade curved, Length 50 mm, Width 65 mm, No. in pack 10 pcs, Mount SL	04	220
6 35 02 226 21 0	4014586408354	E-Cut standard saw blade curved, Length 50 mm, Width 65 mm, No. in pack 50 pcs, Mount SL E-Cut standard saw blade curved, Length 50 mm, Width 50 mm, No. in pack 1 pcs, Mount SL	04	220
6 35 02 226 22 0	4014586408361	E-Cut standard saw blade curved, Length 50 mm, Width 50 mm, No. in pack 3 pcs, Mount SL	04	220
6 35 02 226 23 0	4014586408378	E-Cut standard saw blade curved, Length 50 mm, Width 50 mm, No. in pack 5 pcs, Mount SL	04	220
6 35 02 226 24 0	4014586408385	E-Cut standard saw blade curved, Length 50 mm, Width 50 mm, No. in pack 10 pcs, Mount SL	04	220
6 35 02 226 25 0	4014586408392	E-Cut standard saw blade curved, Length 50 mm, Width 50 mm, No. in pack 50 pcs, Mount SL	04	220
6 35 02 227 21 0	4014586408446	E-Cut standard saw blade curved, Length 55 mm, Width 35 mm, No. in pack 1 pcs, Mount SL	04	220
6 35 02 227 22 0	4014586408453	E-Cut standard saw blade curved, Length 55 mm, Width 35 mm, No. in pack 3 pcs, Mount SL	04	220
6 35 02 227 23 0	4014586408460	E-Cut standard saw blade curved, Length 55 mm, Width 35 mm, No. in pack 5 pcs, Mount SL	04	220
6 35 02 227 24 0	4014586408477	E-Cut standard saw blade curved, Length 55 mm, Width 35 mm, No. in pack 10 pcs, Mount SL	04	220
6 35 02 227 25 0	4014586408484	E-Cut standard saw blade curved, Length 55 mm, Width 35 mm, No. in pack 50 pcs, Mount SL	04	220
6 35 02 228 21 0	4014586408538	E-Cut long-life saw blade, Length 50 mm, Width 65 mm, No. in pack 1 pcs, Mount SL	04	219
6 35 02 228 22 0	4014586408545	E-Cut long-life saw blade, Length 50 mm, Width 65 mm, No. in pack 3 pcs, Mount SL	04	219
6 35 02 228 23 0	4014586408552	E-Cut long-life saw blade, Length 50 mm, Width 65 mm, No. in pack 5 pcs, Mount SL	04	219
6 35 02 228 24 0	4014586408569	E-Cut long-life saw blade, Length 50 mm, Width 65 mm, No. in pack 10 pcs, Mount SL	04	219
6 35 02 228 25 0	4014586408576	E-Cut long-life saw blade, Length 50 mm, Width 65 mm, No. in pack 50 pcs, Mount SL	04	219
6 35 02 229 21 0	4014586408620	E-Cut precision BIM saw blade, Length 50 mm, Width 65 mm, No. in pack 1 pcs, Mount SL	04	220
6 35 02 229 22 0	4014586408637	E-Cut precision BIM saw blade, Length 50 mm, Width 65 mm, No. in pack 3 pcs, Mount SL	04	220
6 35 02 229 23 0	4014586408644	E-Cut precision BIM saw blade, Length 50 mm, Width 65 mm, No. in pack 5 pcs, Mount SL	04	220
6 35 02 229 24 0	4014586408651	E-Cut precision BIM saw blade, Length 50 mm, Width 65 mm, No. in pack 10 pcs, Mount SL	04	220
6 35 02 229 25 0	4014586408668	E-Cut precision BIM saw blade, Length 50 mm, Width 65 mm, No. in pack 50 pcs, Mount SL	04	220
6 35 02 230 21 0	4014586408712	E-Cut precision saw blade, Length 50 mm, Width 65 mm, No. in pack 1 pcs, Mount SL	04	221
6 35 02 230 22 0	4014586408729	E-Cut precision saw blade, Length 50 mm, Width 65 mm, No. in pack 3 pcs, Mount SL	04	221
6 35 02 230 23 0	4014586408736	E-Cut precision saw blade, Length 50 mm, Width 65 mm, No. in pack 5 pcs, Mount SL	04	221
6 35 02 230 24 0	4014586408743	E-Cut precision saw blade, Length 50 mm, Width 65 mm, No. in pack 10 pcs, Mount SL	04	221
6 35 02 230 25 0	4014586408750	E-Cut precision saw blade, Length 50 mm, Width 65 mm, No. in pack 50 pcs, Mount SL	04	221
6 35 02 232 21 0	4014586417295	E-Cut precision BIM saw blade, Length 50 mm, Width 50 mm, No. in pack 1 pcs, Mount SL	04	220
6 35 02 232 22 0	4014586417301	E-Cut precision BIM saw blade, Length 50 mm, Width 50 mm, No. in pack 3 pcs, Mount SL	04	220
6 35 02 232 23 0	4014586417318	E-Cut precision BIM saw blade, Length 50 mm, Width 50 mm, No. in pack 5 pcs, Mount SL	04	220
6 35 02 232 24 0	4014586417325	E-Cut precision BIM saw blade, Length 50 mm, Width 50 mm, No. in pack 10 pcs, Mount SL	04	220
6 35 02 232 25 0	4014586417332	E-Cut precision BIM saw blade, Length 50 mm, Width 50 mm, No. in pack 50 pcs, Mount SL	04	220
6 35 02 233 21 0	4014586417387	E-Cut precision saw blade, Length 50 mm, Width 50 mm, No. in pack 1 pcs, Mount SL	04	221
6 35 02 233 22 0	4014586417394	E-Cut precision saw blade, Length 50 mm, Width 50 mm, No. in pack 3 pcs, Mount SL	04	221
6 35 02 233 23 0	4014586417400	E-Cut precision saw blade, Length 50 mm, Width 50 mm, No. in pack 5 pcs, Mount SL	04	221
6 35 02 233 24 0	4014586417417	E-Cut precision saw blade, Length 50 mm, Width 50 mm, No. in pack 10 pcs, Mount SL	04	221
6 35 02 233 25 0	4014586417424	E-Cut precision saw blade, Length 50 mm, Width 50 mm, No. in pack 50 pcs, Mount SL	04	221
6 35 02 234 01 0	4014586417479	E-Cut precision BIM saw blade, Width 50 mm, No. in pack 1 pcs	04	246
6 35 02 234 02 0	4014586417486	E-Cut precision BIM saw blade, Width 50 mm, No. in pack 5 pcs	04	246
6 35 02 234 03 0	4014586421049	E-Cut precision BIM saw blade, Width 50 mm, No. in pack 25 pcs	04	246
6 35 02 235 01 0	4014586417493	E-Cut precision saw blade, Width 50 mm, No. in pack 1 pcs	04	246
6 35 02 235 02 0	4014586417509	E-Cut precision saw blade, Width 50 mm, No. in pack 5 pcs	04	246
6 35 02 235 03 0	4014586421056 4014586427799	E-Cut precision saw blade, Width 50 mm, No. in pack 25 pcs E-Cut Carbide Pro, Length 40 mm, Width 32 mm, No. in pack 1 pcs, Mount SL	04	246
6 35 02 236 21 0	4014586427799	E-Cut Carbide Pro, Length 40 mm, Width 32 mm, No. in pack 1 pcs, Mount SL E-Cut Carbide Pro, Length 40 mm, Width 32 mm, No. in pack 3 pcs, Mount SL	04	221
6 35 02 236 22 0	4014586427805	E-Cut Carbide Pro, Length 40 mm, Width 32 mm, No. in pack 5 pcs, Mount SL E-Cut Carbide Pro, Length 40 mm, Width 32 mm, No. in pack 5 pcs, Mount SL	04	221
6 35 02 236 24 0	4014586427829	E-Cut Carbide Pro, Length 40 mm, Width 32 mm, No. in pack 3 pcs, Mount SL	04	221
6 35 02 236 25 0	4014586427836	E-Cut Carbide Pro, Length 40 mm, Width 32 mm, No. in pack 50 pcs, Mount SL	04	221
6 35 02 237 21 0	4014586427874	E-Cut Carbide Pro, Length 60 mm, Width 32 mm, No. in pack 30 pcs, Mount SLP	04	221
6 35 02 237 22 0	4014586427881	E-Cut Carbide Pro, Length 60 mm, Width 32 mm, No. in pack 3 pcs, Mount SLP	04	221
6 35 02 237 23 0	4014586427898	E-Cut Carbide Pro, Length 60 mm, Width 32 mm, No. in pack 5 pcs, Mount SLP	04	221
6 35 02 237 24 0	4014586427904	E-Cut Carbide Pro, Length 60 mm, Width 32 mm, No. in pack 10 pcs, Mount SLP	04	221
		The second secon		

Part number	EAN	Description	PC	Page
6 35 02 237 25 0	4014586427911	E-Cut Carbide Pro, Length 60 mm, Width 32 mm, No. in pack 50 pcs, Mount SLP	04	221
6 35 02 238 21 0	4014586427959	E-Cut Carbide Pro, Length 75 mm, Width 32 mm, No. in pack 1 pcs, Mount SLM	04	221
6 35 02 238 22 0	4014586427966	E-Cut Carbide Pro, Length 75 mm, Width 32 mm, No. in pack 3 pcs, Mount SLM	04	221
6 35 02 238 23 0	4014586427973	E-Cut Carbide Pro, Length 75 mm, Width 32 mm, No. in pack 5 pcs, Mount SLM	04	221
6 35 02 238 24 0	4014586427980	E-Cut Carbide Pro, Length 75 mm, Width 32 mm, No. in pack 10 pcs, Mount SLM	04	221
6 35 02 238 25 0	4014586446639	E-Cut Carbide Pro, Length 75 mm, Width 32 mm, No. in pack 50 pcs, Mount SLM	04	-
6 35 02 301 00 0	4014586450803	Saw blade	02	172
6 35 02 302 00 0	4014586450810	Saw blade	02	172
6 35 02 303 00 0	4014586450827	Saw blade	02	172
6 35 02 304 00 0	4014586450834	Saw blade	02	172
6 35 03 037 01 8	4014586178936	Saw blade, Length 88 mm	02	_
6 35 03 038 01 6	4014586178943	Saw blade, Length 88 mm	02	_
6 35 03 039 01 0	4014586178950	Saw blade, Length 88 mm	02	_
6 35 03 040 00 3	4014586178967	Saw blade, Length 530 mm, Tooth spacing 6.3 mm, Thickness 1.5 mm	02	175
6 35 03 043 01 8	4014586179001	Saw blades, No. in pack 3 pcs	02	
6 35 03 047 01 7	4014586179049	Saw blades, No. in pack 3 pcs	02	_
6 35 03 051 01 0	4014586179087	Saw blades, No. in pack 3 pcs	02	_
6 35 03 058 01 4	4014586179148		02	
		Saw blades, No. in pack 3 pcs	02	
6 35 03 059 01 8	4014586179155	Saw blades, No. in pack 3 pcs		
6 35 03 060 01 0	4014586179162	Saw blade, Length 77 mm	02	
6 35 03 061 01 9	4014586179186	Saw blade, Length 77 mm	02	-
6 35 03 063 00 7	4014586179209	Saw blade, Length 300 mm, Tooth spacing 1.6 mm, Thickness 1.5 mm	02	175
6 35 03 064 00 5	4014586179216	Saw blade, Length 400 mm, Tooth spacing 1.6 mm, Thickness 1.5 mm	02	175
6 35 03 065 00 9	4014586179223	Saw blade, Length 200 mm, Tooth spacing 3.2 mm, Thickness 1.5 mm	02	175
6 35 03 066 00 2	4014586179230	Saw blade, Length 200 mm, Tooth spacing 1.6 mm, Thickness 1.5 mm	02	175
6 35 03 067 00 6	4014586179247	Saw blade, Length 200 mm, Tooth spacing 1 mm, Thickness 1.5 mm	02	175
6 35 03 068 00 4	4014586179254	Saw blade, Length 400 mm, Tooth spacing 3.2 mm, Thickness 1.5 mm	02	175
6 35 03 069 00 8	4014586179261	Saw blade, Length 530 mm, Tooth spacing 2.1 mm, Thickness 1.5 mm	02	175
6 35 03 070 00 0	4014586179278	Saw blade, Length 300 mm, Tooth spacing 2.1 mm, Thickness 1.5 mm	02	175
6 35 03 071 00 9	4014586179285	Saw blade, Length 300 mm, Tooth spacing 6.3 mm, Thickness 1.5 mm	02	175
6 35 03 072 00 2	4014586179292	Saw blade, Length 500 mm, Tooth spacing 1.8 mm, Thickness 2 mm	02	175
6 35 03 073 00 6	4014586179308	Saw blade, Length 600 mm, Tooth spacing 1.8 mm, Thickness 2 mm	02	175
6 35 03 076 01 0	4014586179339	Saw blade, Length 100 mm	02	-
6 35 03 077 01 4	4014586179346	Saw blade, Length 120 mm	02	-
6 35 03 082 01 0	4014586179360	Saw blade, Length 100 mm	02	-
6 35 03 088 01 1	4014586179407	Saw blade, Length 100 mm	02	-
6 35 03 093 00 4	4014586200774	HD saw blades, Length 300 mm, Tooth spacing 1.6 mm, Thickness 2 mm	02	175
6 35 03 094 00 2	4014586200781	HD saw blades, Length 400 mm, Tooth spacing 2.1 mm, Thickness 2 mm	02	175
6 35 03 095 00 6	4014586200798	HD saw blades, Length 400 mm, Tooth spacing 3.2 mm, Thickness 2 mm	02	175
6 35 03 096 01 8	4014586202921	TD saw blades, Length 320 mm, Thickness 2.2 mm	02	175
6 35 03 097 01 2	4014586202938	TD saw blades, Length 490 mm, Thickness 2.9 mm	02	175
6 35 03 098 00 1	4014586212548	HD saw blades, Length 600 mm, Tooth spacing 1.8 mm, Thickness 2 mm	02	175
6 35 03 099 00 5	4014586212555	HD saw blades, Length 500 mm, Tooth spacing 1.8 mm, Thickness 2 mm	02	175
6 35 03 100 00 6	4014586212562	HD saw blades, Length 530 mm, Tooth spacing 2.1 mm, Thickness 1.6 mm	02	175
6 35 03 112 01 0	4014586305370	Saw blade, Length 88 mm	02	
6 35 03 113 01 0	4014586305387	Saw blade, Length 88 mm	02	_
6 35 03 115 01 0	4014586305417	Saw blade, No. in pack 3 pcs	02	
6 35 08 056 00 4	4014586179506	Form cutter, V-form 30°, Ø 125 mm, Width 25 mm, Teeth 32	08	
6 35 08 081 00 9	4014586179513	Form cutter, V-form 30°, Ø 160 mm, Width 30 mm, Teeth 36	08	
6 35 08 081 00 9			08	
	4014586179520	Form cutter, V-form 30°, Ø 180 mm, Width 42 mm, Teeth 36		
6 35 08 093 00 0	4014586340395	Form cutter, V-form 37.5°, Ø 160 mm, Width 30 mm, Teeth 36	08	
6 35 08 094 00 0	4014586340401	Form cutter, V-form 37.5°, Ø 180 mm, Width 42 mm, Teeth 36	08	
6 35 08 098 00 0	4014586354613	Angled milling cutter, right	08	
6 35 08 099 00 0	4014586354620	Angled milling cutter, left	08	
6 36 01 101 00 9	4014586179766	Plunger blade and fixed blade, Plate thickness 1.6 mm	02	163
6 36 02 048 00 4	4014586224053	Punch, No. in pack 1 pcs	02	158
6 36 02 048 01 3	4014586246260	Punches and dies	02	158
6 36 02 048 04 0	4014586317984	Punch, No. in pack 5 pcs	02	158
6 36 02 048 05 0	4014586317991	Punch, No. in pack 10 pcs	02	158
6 36 02 049 00 8	4014586246611	Punch, No. in pack 1 pcs	02	158

Part number	EAN	Description	PC	Page
6 36 02 049 01 7	4014586246628	Punches and dies	02	158
6 36 02 049 04 0	4014586318004	Punch, No. in pack 2 pcs	02	158
6 36 02 049 05 0	4014586318011	Punch, No. in pack 5 pcs	02	158
6 36 02 050 00 0	4014586264370	Punch, Plate thickness 1.3 mm, No. in pack 1 pcs	02	158
6 36 02 050 01 0	4014586269511	Punch, Plate thickness 1.3 mm, No. in pack 10 pcs	02	158
6 36 02 050 03 0	4014586318028	Punch, Plate thickness 1.3 mm, No. in pack 5 pcs	02	158
6 36 02 051 00 9	4014586262987	Punch	02	159
6 36 02 051 01 8	4014586264356	Punches and dies in a set	02	159
6 37 03 005 01 0	4014586450094	Grinding disc, Ø 125 mm, Thickness 6 mm	02	118
6 37 06 012 02 4	4014586260884	Diamond file	04	_
6 37 06 019 21 0	4014586389639	Carbide file, Length 30 mm, Width 10 mm, Mount SL	04	227
6 37 09 013 01 0	4014586450100	Cutting disc, Ø 125 mm, Thickness 1 mm	02	118
6 37 09 014 01 0	4014586450117	Cutting disc, Ø 125 mm, Thickness 2.5 mm	02	119
6 37 13 007 00 9	4014586180717	Grinding wheel	02	
6 37 13 008 00 7	4014586180724	Grinding wheel	02	
6 37 13 009 00 1	4014586180731	Grinding wheel	02	
6 37 13 010 00 3	4014586180748	Grinding wheel	02	
6 37 13 011 00 2	4014586180755	Polishing wheel	02	
6 37 13 013 01 8	4014586226811	Polishing wheel	02	136
6 37 13 015 01 0	4014586226835	Polishing wheel	02	137
6 37 13 016 01 3	4014586226842	Polishing wheel	02	137
6 37 14 004 00 5	4014586180779	Linen sanding belt, Grain 40, Width 30 mm	02	
6 37 14 006 00 2	4014586180793	Linen sanding belt, Grain 80, Width 30 mm	02	
6 37 14 008 00 4	4014586180816	Linen sanding belt, Grain 180, Width 30 mm	02	
6 37 14 014 00 4	4014586180878	Linen sanding belt, Grain 120, Width 50 mm	02	
6 37 14 015 00 8	4014586180885	Linen sanding belt, Grain 180, Width 50 mm	02	
6 37 14 044 01 0	4014586246406	Grinding belts, Grain 60, No. in pack 10 pcs	02	136
6 37 14 045 01 4	4014586246413	Grinding belts, Grain 120, No. in pack 10 pcs	02	136
6 37 14 046 01 7	4014586246420	Grinding belts, Grain 240, No. in pack 10 pcs	02	136
6 37 14 047 01 1	4014586246437	Fleece strips, Model coarse	02	136
6 37 14 048 01 9	4014586246444	Fleece strips, Model medium	02	136
6 37 14 049 01 3	4014586246451	Fleece strips, Model fine	02	136
6 37 14 050 01 5	4014586259444	Grinding belts, No. in pack 10 pcs, Grain 120	02	130
6 37 14 050 02 1	4014586259451	Basic pipe sander set	02	130
6 37 14 051 01 4	4014586259468	Grinding belts, No. in pack 10 pcs, Grain 180	02	130
6 37 14 052 01 7	4014586259475	Grinding belts, No. in pack 10 pcs, Grain 320	02	130
			02	130
6 37 14 053 01 1	4014586259499	Grinding belts, No. in pack 10 pcs, Grain 400 Grinding belts, No. in pack 10 pcs, Grain 120	02	130
6 37 14 054 01 9	4014586259505 4014586259512			
6 37 14 055 01 3		Grinding belts, No. in pack 10 pcs, Grain 180	02	130
6 37 14 056 01 6	4014586259529	Fleece strips, No. in pack 5 pcs, Grain 80	02	130
6 37 14 057 01 0	4014586259536	Fleece strips, No. in pack 5 pcs, Grain 120	02	130
6 37 14 058 01 8	4014586259543	Fleece strips, No. in pack 5 pcs, Grain 280	02	130
6 37 14 061 01 0	4014586313160	Ceramic grinding belt, Grain 80, Width 3 mm	02	131
6 37 14 062 01 0	4014586313177	Ceramic grinding belt, Grain 120, Width 3 mm	02	131
6 37 14 063 01 0	4014586313184	Ceramic grinding belt, Grain 180, Width 3 mm	02	131
6 37 14 068 01 0	4014586313191	Ceramic grinding belt, Grain 80, Width 6 mm	02	131
6 37 14 069 01 0	4014586313207	Ceramic grinding belt, Grain 120, Width 6 mm	02	131
6 37 14 070 01 0	4014586313214	Ceramic grinding belt, Grain 180, Width 6 mm	02	131
6 37 14 089 01 0	4014586313221	Ceramic grinding belt, Grain 80, Width 20 mm	02	131
6 37 14 090 01 0	4014586313238	Ceramic grinding belt, Grain 120, Width 20 mm	02	131
6 37 14 091 01 0	4014586313245	Ceramic grinding belt, Grain 180, Width 20 mm	02	131
6 37 14 114 01 0	4014586313252	Fleece belt, Width 6 mm, Model coarse	02	131
6 37 14 115 01 0	4014586313269	Fleece belt, Width 6 mm, Model medium	02	131
6 37 14 116 01 0	4014586313276	Fleece belt, Width 6 mm, Model fine	02	131
6 37 14 123 01 0	4014586313283	Fleece belt, Width 20 mm, Model coarse	02	131
6 37 14 124 01 0	4014586313290	Fleece belt, Width 20 mm, Model medium	02	131
6 37 14 125 01 0	4014586313306	Fleece belt, Width 20 mm, Model fine	02	131
6 37 14 130 01 0	4014586300849	Ceramic sanding belts, Dimensions 20 x 815 mm, No. in pack 10 pcs, Grain 80	02	130
6 37 14 131 01 0	4014586300856	Ceramic sanding belts, Dimensions 40 x 815 mm, No. in pack 10 pcs, Grain 80	02	130
6 37 14 132 01 0	4014586305264	Sanding sleeve, Grain 60, No. in pack 5 pcs	02	137

Part number	EAN	Description	PC	Page
6 37 14 133 01 0	4014586305271	Sanding sleeve, Grain 80, No. in pack 5 pcs	02	137
6 37 14 134 01 0	4014586306674	Sanding sleeve, Grain 120, No. in pack 5 pcs	02	137
6 37 14 136 01 0	4014586329512	Grinding belts, Grain 80	02	133
6 37 14 137 01 0	4014586329529	Grinding belts, Grain 120	02	133
6 37 14 138 01 0	4014586329536	Grinding belts, Grain 180	02	133
6 37 14 139 01 0	4014586329543	Grinding belts, Grain 320	02	133
6 37 14 140 01 0	4014586329741	Grinding belts, Grain 400	02	133
6 37 14 143 01 0	4014586329574	Fleece strips, Model fine	02	133
6 37 14 144 01 0	4014586330013	Polishing belts	02	133
6 37 14 145 01 0	4014586409672	Pyramix sanding sleeve, Grain 280, No. in pack 5 pcs	02	137
6 37 14 146 01 0	4014586409689	Pyramix sanding sleeve, Grain 400, No. in pack 5 pcs	02	137
6 37 14 147 01 0	4014586409696	Pyramix sanding sleeve, Grain 600, No. in pack 5 pcs	02	137
6 37 14 148 01 0	4014586409702	Pyramix sanding sleeve, Grain 1 400, No. in pack 5 pcs	02	137
6 37 17 081 01 8	4014586182575	Sanding sheets, Edge length 80 mm	04	223
6 37 17 081 04 6	4014586211114	Sanding sheets, Edge length 80 mm	04	223
6 37 17 082 01 1	4014586182612	Sanding sheets, Edge length 80 mm	04	223
6 37 17 082 03 3	4014586207667	Set of sanding sheets, Edge length 80 mm	04	223
6 37 17 082 04 9	4014586211121	Sanding sheets, Edge length 80 mm	04	223
6 37 17 083 01 5	4014586182643	Sanding sheets, Edge length 80 mm	04	223
6 37 17 083 04 3	4014586211138	Sanding sheets, Edge length 80 mm	04	223
6 37 17 084 01 3	4014586182674	Sanding sheets, Edge length 80 mm	04	223
6 37 17 084 04 1	4014586211145	Sanding sheets, Edge length 80 mm	04	223
6 37 17 085 01 7	4014586182704	Sanding sheets, Edge length 80 mm	04	223
6 37 17 085 04 5	4014586211152	Sanding sheets, Edge length 80 mm	04	223
6 37 17 086 01 0	4014586182728	Sanding sheets, Edge length 80 mm	04	223
6 37 17 086 04 8	4014586211107	Sanding sheets, Edge length 80 mm	04	223
6 37 17 087 01 4	4014586182742	Sanding sheets, Edge length 80 mm	04	223
6 37 17 087 04 2	4014586211169	Sanding sheets, Edge length 80 mm	04	223
6 37 17 088 01 2	4014586182773	Sanding sheets, Edge length 80 mm	04	223
6 37 17 088 04 0	4014586211176	Sanding sheets, Edge length 80 mm	04	223
6 37 17 089 01 6	4014586182797	Sanding sheets, Edge length 80 mm	04	223
6 37 17 089 04 4	4014586211183	Sanding sheets, Edge length 80 mm	04	223
6 37 17 090 01 8	4014586182810	Sanding sheets, Edge length 80 mm	04	223
6 37 17 090 04 6	4014586211190	Sanding sheets, Edge length 80 mm	04	223
6 37 17 107 01 1	4014586182896	Sanding sheets, perforated, Edge length 80 mm	04	224
6 37 17 107 04 9	4014586211237	Sanding sheets, perforated, Edge length 80 mm	04	224
6 37 17 108 01 9	4014586182919	Sanding sheets, perforated, Edge length 80 mm	04	224
6 37 17 108 04 7	4014586211244	Sanding sheets, perforated, Edge length 80 mm	04	224
6 37 17 109 01 3	4014586182933	Sanding sheets, perforated, Edge length 80 mm	04	224
6 37 17 109 03 5	4014586213002	Set of sanding sheets, Edge length 80 mm	04	224
6 37 17 109 04 1	4014586211251	Sanding sheets, perforated, Edge length 80 mm	04	224
6 37 17 110 01 5	4014586182957	Sanding sheets, perforated, Edge length 80 mm	04	224
6 37 17 110 04 3	4014586211268	Sanding sheets, perforated, Edge length 80 mm	04	224
6 37 17 111 01 4	4014586182971	Sanding sheets, perforated, Edge length 80 mm	04	224
6 37 17 111 04 2	4014586211275	Sanding sheets, perforated, Edge length 80 mm	04	224
6 37 17 112 01 7	4014586182995	Sanding sheets, perforated, Edge length 80 mm	04	224
6 37 17 112 04 5	4014586211282	Sanding sheets, perforated, Edge length 80 mm	04	224
6 37 17 113 01 1	4014586183015	Sanding sheets, perforated, Edge length 80 mm	04	224
6 37 17 113 04 9	4014586211299	Sanding sheets, perforated, Edge length 80 mm	04	224
6 37 17 114 01 9	4014586183039	Sanding sheets, perforated, Edge length 80 mm	04	224
6 37 17 114 04 7	4014586211305	Sanding sheets, perforated, Edge length 80 mm	04	224
6 37 17 115 01 3	4014586183053	Sanding sheets, perforated, Edge length 80 mm	04	224
6 37 17 115 04 1	4014586211312	Sanding sheets, perforated, Edge length 80 mm	04	224
6 37 17 116 01 6	4014586183077	Sanding sheets, perforated, Edge length 80 mm	04	224
6 37 17 116 04 4	4014586211329	Sanding sheets, perforated, Edge length 80 mm	04	224
6 37 17 120 01 4	4014586183152	Stone sanding sheets, Edge length 80 mm		224
6 37 17 121 01 3	4014586183176	Stone sanding sheets, Edge length 80 mm	04	224
6 37 17 122 01 6	4014586183190	Stone sanding sheets, Edge length 80 mm	04	224
6 37 17 123 01 0	4014586183213	Stone sanding sheets, Edge length 80 mm	04	224
6 37 17 124 01 8	4014586183237	Stone sanding sheets, Edge length 80 mm	04	

Part number	EAN	Description	PC	Page
6 37 17 125 01 2	4014586183251	Stone sanding sheets, Edge length 80 mm	04	224
6 37 17 126 01 5	4014586183275	Supersoft sanding sheets, Edge length 80 mm	04	223
6 37 17 127 01 9	4014586183299	Supersoft sanding sheets, Edge length 80 mm	04	223
6 37 17 128 01 7	4014586183312	Supersoft sanding sheets, Edge length 80 mm	04	223
6 37 17 175 01 7	4014586183343	Stone sanding sheets, Edge length 80 mm	04	224
6 37 17 179 01 6	4014586201375	Supersoft sanding sheets, Edge length 80 mm	04	223
6 37 17 184 01 2	4014586208473	Sanding sheets for sanding fingers, Grain 40, No. in pack 20 pcs	04	224
6 37 17 185 01 6	4014586208480 4014586208497	Sanding sheets for sanding fingers, Grain 60, No. in pack 20 pcs	04	224
6 37 17 187 01 3	4014586208497	Sanding sheets for sanding fingers, Grain 80, No. in pack 20 pcs Sanding sheets for sanding fingers, Grain 100, No. in pack 20 pcs	04	224
6 37 17 188 01 1	4014586208510	Sanding sheets for sanding fingers, Grain 120, No. in pack 20 pcs	04	224
6 37 17 189 01 5	4014586208527	Sanding sheets for sanding fingers, Grain 150, No. in pack 20 pcs	04	224
6 37 17 190 01 7	4014586208534	Sanding sheets for sanding fingers, Grain 180, No. in pack 20 pcs	04	224
6 37 17 191 01 6	4014586208541	Sanding sheets for sanding fingers, Grain 220, No. in pack 20 pcs	04	224
6 37 17 192 01 9	4014586208558	Sanding sheets for sanding fingers, Grain 240, No. in pack 20 pcs	04	224
6 37 17 217 01 6	4014586260914	Sandpaper for profile sanding set, Grain 80, No. in pack 25 pcs	04	224
6 37 17 218 01 4	4014586260921	Sandpaper for profile sanding set, Grain 120, No. in pack 25 pcs	04	224
6 37 17 219 01 8	4014586260938	Sandpaper for profile sanding set, Grain 180, No. in pack 25 pcs	04	224
6 37 17 221 01 0	4014586282893	Sanding disc	02	142
6 37 17 227 01 0	4014586317182	Set of sanding sheets	04	225
6 37 17 227 02 0	4014586317199	Sanding sheets, Grain 60, No. in pack 16 pcs	04	225
6 37 17 228 02 0	4014586317205	Sanding sheets, Grain 80, No. in pack 16 pcs	04	225
6 37 17 229 01 0	4014586317212	Sanding sheets, Grain 120, No. in pack 16 pcs	04	225
6 37 17 230 02 0	4014586317229	Sanding sheets, Grain 40, No. in pack 16 pcs	04	225
6 37 17 231 02 0	4014586317236	Sanding sheets, Grain 180, No. in pack 16 pcs	04	225
6 37 17 232 01 0	4014586317243	Sanding sheets, Grain 240, No. in pack 16 pcs	04	225
6 37 17 233 01 0	4014586329581	Sanding sheets, zirconium, Grain 40, No. in pack 12 pcs	04	225
6 37 17 233 02 0	4014586329598	Sanding sheet set, zirconium	04	225
6 37 17 234 01 0	4014586329604	Sanding sheets, zirconium, Grain 60, No. in pack 12 pcs	04	225
6 37 17 235 01 0	4014586329611	Sanding sheets, zirconium, Grain 80, No. in pack 12 pcs	04	225
6 37 17 236 01 0	4014586329628	Sanding sheets, zirconium, Edge length 80 mm	04	224
6 37 17 237 01 0	4014586329635	Sanding sheets, zirconium, Edge length 80 mm	04	224
6 37 17 238 01 0	4014586329642	Sanding sheets, zirconium, Edge length 80 mm	04	224
6 37 17 239 01 0	4014586328768	Pyramix sanding sheet, Grain 280, No. in pack 5 pcs	02	132
6 37 17 239 02 0	4014586328775	Pyramix sanding sheet, Grain 280, No. in pack 25 pcs	02	132
6 37 17 240 01 0	4014586328782	Pyramix sanding sheet, Grain 400, No. in pack 5 pcs	02	132
6 37 17 240 02 0	4014586328799	Pyramix sanding sheet, Grain 400, No. in pack 25 pcs	02	132
6 37 17 241 01 0	4014586328805	Pyramix sanding sheet, Grain 800, No. in pack 5 pcs	02	132
6 37 17 241 02 0	4014586328812	Pyramix sanding sheet, Grain 800, No. in pack 25 pcs	02	132
6 37 17 242 01 0	4014586328829	Pyramix sanding sheet, Grain 1 400, No. in pack 5 pcs	02	132
6 37 17 242 02 0	4014586328836	Pyramix sanding sheet, Grain 1 400, No. in pack 25 pcs	02	132
6 37 17 243 01 0	4014586329659	Sanding sheets, zirconium, Edge length 80 mm	04	223
6 37 17 244 01 0	4014586329666	Sanding sheets, zirconium, Edge length 80 mm	04	223
6 37 17 245 01 0	4014586329673 4014586373867	Sanding sheets, zirconium, Edge length 80 mm Sanding sheets, foam backing, Grain 500, No. in pack 5 pcs	04	223
6 37 17 247 01 0	4014586373874	Sanding sheets, foam backing, Grain 1000, No. in pack 5 pcs	04	226
6 37 17 293 02 0	4014586399157	Sanding sheets, perforated, Edge length 130 mm	04	225
6 37 17 294 02 0	4014586399164	Sanding sheets, perforated, Edge length 130 mm	04	225
6 37 17 295 02 0	4014586399171	Sanding sheets, perforated, Edge length 130 mm	04	225
6 37 17 296 02 0	4014586399188	Sanding sheets, perforated, Edge length 130 mm	04	225
6 37 17 297 02 0	4014586399195	Sanding sheets, perforated, Edge length 130 mm	04	225
6 37 17 298 01 0	4014586401430	Sanding sheets, zirconium, Edge length 130 mm	04	225
6 37 17 299 01 0	4014586401447	Sanding sheets, zirconium, Edge length 130 mm	04	225
6 37 17 300 01 0	4014586401454	Sanding sheets, zirconium, Edge length 130 mm	04	225
6 37 17 301 01 0	4014586450124	Fibre sanding disc, Ø 125 mm, No. in pack 25 pcs	02	119
6 37 17 302 01 0	4014586450131	Fibre sanding disc, Ø 125 mm, No. in pack 25 pcs	02	119
6 37 17 303 01 0	4014586450148	Fibre sanding disc, Ø 125 mm, No. in pack 25 pcs	02	119
6 37 18 011 01 0	4014586334998	Felt disc, Ø 150 mm, Thickness 6 mm	02	133
6 37 19 007 01 0	4014586213101	Cleaning block	04	176
6 37 19 010 01 4	4014586213453	Sharpening stone	04	247

Part number	EAN	Description	PC	Page
6 37 19 011 01 0	4014586336466	Profiling stone	02	133
6 37 19 011 22 0	4014586389646	Tile joint cleaner, No. in pack 2 pcs, Mount SLP	04	227
6 37 21 001 00 1	4014586183428	Flap wheel, Ø 200 mm	02	137
6 37 21 003 01 7	4014586226583	Flap wheel	02	135
6 37 21 004 01 5	4014586226590	Flap wheel	02	135
6 37 21 005 01 9	4014586226606	Flap wheel	02	135
6 37 21 006 01 2	4014586246321	Elastic sanding cylinder, Grain 60, Model medium	02	135
6 37 21 006 04 0	4014586306629	Standard stainless steel set for surfaces	02	135
6 37 21 007 01 6	4014586246338	Elastic sanding cylinder, Grain 180, Model fine	02	135
6 37 21 008 01 4	4014586246345	Lamella fleece cylinder, Grain 100, Model medium	02	135
6 37 21 009 01 8	4014586246352	Lamella fleece cylinder, Grain 180, Model fine	02	136
6 37 21 010 01 0	4014586248448	Lamella fleece cylinder, Grain 280, Model very fine	02	136
6 37 21 015 01 0	4014586282329	Lamella fleece cylinder	02	135
6 37 21 050 02 0	4014586306636	Stainless steel set for satin-finishing surfaces	02	135
6 37 21 051 01 0	4014586305288	Sine fleece sanding cylinder, Grain 180, Model fine	02	135
6 37 21 052 01 0	4014586305189	Flap wheel, Grain 120	02	132
6 37 21 054 01 0	4014586328843	Elastic sanding cylinder, Grain 60, Model medium	02	135
6 37 21 054 02 0	4014586328850	Stainless steel set – Satin-finishing profiles	02	135
6 37 21 055 01 0	4014586328874	Elastic sanding cylinder, Grain 180, Model fine	02	135
6 37 21 056 01 0	4014586329062	Sine fleece sanding cylinder, Grain 180, Model fine	02	135
6 37 21 057 01 0	4014586409917	Felt lamella roller, Model soft	02	136
6 37 21 058 01 0	4014586409924	Felt lamella roller, Model medium	02	136
6 37 22 048 01 4	4014586226736	Nylon barrel brush	02	143
6 37 23 003 00 3	4014586183633	Lambskin, Ø 170 mm	02	143
6 37 23 007 00 2	4014586183688	Lambskin, Ø 120 mm	02	142
6 37 23 008 00 0	4014586216720	Lambskin, Ø 125 mm	02	135
6 37 23 009 00 4	4014586216737	Lambskin, Ø 150 mm	02	134
6 37 23 010 00 6	4014586216744	Lambskin, Ø 200 mm	02	134
6 37 23 011 01 4	4014586226637	Polishing rings, Sisal, cloth, ∅ 150 mm	02	136
6 37 23 012 01 7	4014586226644	Polishing rings, Sisal, cloth, ∅ 200 mm	02	136
6 37 23 013 01 1	4014586226651	Polishing rings, hard cloth, Ø 150 mm	02	136
6 37 23 014 01 9	4014586226668	Polishing rings, soft cloth, Ø 150 mm	02	136
6 37 23 015 01 3	4014586226675	Polishing rings, hard cloth, Ø 200 mm	02	136
6 37 23 016 01 6	4014586226682	Polishing rings, soft cloth, Ø 200 mm	02	136
6 37 23 017 01 0	4014586232829	Polishing sponge, Ø 125 mm, Model medium	02	142
6 37 23 018 01 8	4014586232836	Polishing sponge, Ø 150 mm, Model medium	02	
6 37 23 019 01 2	4014586233710	Polishing rings, fleece, extra soft, Ø 150 mm	02	136
6 37 23 020 01 4	4014586233727	Polishing rings, fleece, extra soft, Ø 200 mm	02	136
6 37 23 021 01 3	4014586233734	Sanding fleece, Ø 150 mm	02	136
6 37 23 022 01 6	4014586233741	Sanding fleece, Ø 200 mm	02	136
6 37 23 023 01 0	4014586233918	Polishing sponge, Ø 100 mm, Model hard	02	142
6 37 23 024 01 8	4014586233925	Polishing sponge, Ø 100 mm, Model soft	02	142
6 37 23 025 01 2	4014586233932	Polishing sponge, Ø 160 mm, Model hard	02	143
6 37 23 026 01 5	4014586233949	Polishing sponge, Ø 160 mm, Model soft	02	143
6 37 23 028 01 0	4014586282909	Polishing sponge orange 150 mm	02	142
6 37 23 029 01 0	4014586282930	Waffled sponge	02	142
6 37 23 029 01 0	4014586304939	Bristle fleece, No. in pack 2 pcs, Edge length 80 mm	02	225
6 37 23 032 01 0			04	226
	4014586304946	Felt polishing pad, No. in pack 5 pcs, Edge length 80 mm	02	
6 37 23 033 01 0	4014586304953	Bristle fleece, Ø 195 mm		142
6 37 23 034 01 0	4014586304960	Polishing sponge, Ø 195 mm	02	142
6 37 23 035 01 0	4014586304977	Lamb's wool, dome shape, Ø 230 mm	02	143
6 37 23 036 01 0	4014586335001	Felt polishing pad, No. in pack 5 pcs	04	226
6 37 23 037 01 0	4014586409931	Felt serrated disc, Model soft, Ø 125 mm	02	133
6 37 23 038 01 0	4014586409948	Felt serrated disc, Model medium, Ø 125 mm	02	133
6 37 26 010 01 8	4014586259574	Polishing belts	02	130
6 37 26 016 01 0	4014586313313	Polishing belt, Width 6 mm	02	131
6 37 26 019 01 0	4014586313320	Polishing belt, Width 20 mm	02	131
6 37 28 009 01 4	4014586184500	Sanding sheets, Grain 40, No. in pack 50 pcs	02	134
6 37 28 010 01 6	4014586184524	Sanding sheets, Grain 60, No. in pack 50 pcs	02	134
6 37 28 011 01 5	4014586184548	Sanding sheets	02	

Part number	EAN	Description	PC	Page
6 37 28 012 01 8	4014586184562	Sanding sheets, Grain 150, No. in pack 50 pcs	02	134
6 37 28 013 01 2	4014586184586	Sanding sheets, Grain 180, No. in pack 50 pcs	02	134
6 37 28 015 01 4	4014586184623	Sanding sheets, Grain 240, No. in pack 50 pcs	02	134
6 37 28 022 01 7	4014586184739	Sanding sheets, Grain 60, No. in pack 50 pcs	02	134
6 37 28 054 01 6	4014586185002	Sanding sheets, Grain 100, No. in pack 50 pcs	02	134
6 37 28 056 01 3	4014586185040	Sanding sheets, Grain 80, No. in pack 50 pcs	02	134
6 37 28 073 01 6	4014586185194	Sanding sheets, Grain 60, No. in pack 50 pcs	02	134
6 37 28 074 01 4	4014586185217	Sanding sheets, Grain 80, No. in pack 50 pcs	02	134
6 37 28 084 01 3	4014586185354	Sanding sheets, Grain 120, No. in pack 50 pcs	02	134
6 37 28 096 01 9	4014586215969	Sanding sheets, Grain 80, No. in pack 50 pcs	02	134
6 37 28 135 01 0	4014586329994	Sanding sheets, Grain 80, No. in pack 25 pcs	02	132
6 37 30 019 01 0	4014586409719	Flap wheel, Model soft, Ø 125 mm, No. in pack 5 pcs	02	133
6 37 30 020 01 0	4014586409726	Flap wheel, Model coarse, Ø 125 mm, No. in pack 5 pcs	02	133
6 37 30 021 01 0	4014586410296 4014586450155	Flap wheel, Model medium, Ø 125 mm, No. in pack 5 pcs Flap wheel, Ø 125 mm, No. in pack 10 pcs	02	119
6 37 30 023 01 0	4014586450162	Flap wheel, Ø 125 mm, No. in pack 10 pcs	02	119
6 37 30 024 01 0	4014586450179	Flap wheel, Ø 125 mm, No. in pack 10 pcs	02	119
6 37 31 001 21 0	4014586391069	Carbide rasp, Edge length 80 mm, Mount SL	02	227
6 37 31 001 21 0	4014586391009	Carbide rasp, Mount SLP	04	227
6 37 31 006 21 0	4014586391083	Carbide rasp, Florent SEI Carbide rasp, Edge length 110 mm, Mount SLM	04	227
6 37 32 001 01 8	4014586226781	Fleece sanding discs, Model coarse, No. in pack 10 pcs	02	132
6 37 32 002 01 1	4014586226798	Fleece sanding discs, Model medium, No. in pack 10 pcs	02	132
6 37 32 003 01 5	4014586226804	Fleece sanding discs, Model fine, No. in pack 10 pcs	02	132
6 37 32 004 01 0	4014586305493	Sanding fleece for antifoul, Ø 150 mm, No. in pack 5 pcs	02	143
6 37 32 005 01 0	4014586305202	Finishing disc	02	132
6 37 33 001 01 0	4014586282992	Humidification sponge	02	142
6 37 33 002 01 0	4014586283005	Sanding block	02	142
6 37 33 003 01 0	4014586283012	Microfibre cloth	02	130
6 37 33 006 01 0	4014586307312	Holder	02	137
6 37 33 010 01 0	4014586409733	Stainless steel masking tape, L 5 m	02	130
6 37 34 001 01 0	4014586334868	Fleece disc, Model coarse, Ø 150 mm, Thickness 3 mm	02	133
6 37 34 002 01 0	4014586334875	Fleece disc, Model coarse, Ø 150 mm, Thickness 6 mm	02	133
6 37 34 003 01 0	4014586334882	Fleece disc, Model medium, Ø 150 mm, Thickness 3 mm	02	133
6 37 34 004 01 0	4014586334899	Fleece disc, Model hard, Ø 150 mm, Thickness 6 mm	02	133
6 37 34 005 01 0	4014586334905	Fleece disc, Model fine, Ø 150 mm, Thickness 3 mm	02	133
6 37 34 006 01 0	4014586334912	Fleece disc, Model fine, Ø 150 mm, Thickness 6 mm	02	133
6 37 34 007 01 0	4014586334929	Fleece disc, Model very fine, Ø 150 mm, Thickness 6 mm	02	133
6 37 34 008 01 0	4014586409740	Fleece disc, Model very course, Ø 150 mm, Thickness 7 mm	02	133
6 38 01 079 00 9	4014586185569	Inner flange	02	
6 38 01 096 00 1	4014586185613	Inner flange	02	_
6 38 01 097 00 5	4014586185620	Grinding wheel	02	
6 38 01 098 00 3	4014586185637	Flange	02	
6 38 01 116 00 8	4014586185743	Flange	02	
6 38 01 137 00 0	4014586185842	Flange	02	
6 38 01 154 00 7	4014586185972	Threaded flange	02	118
6 38 01 176 01 1	4014586212517	Flange	02	
6 38 01 178 00 4	4014586259857	adapter	02	
6 38 01 182 01 0	4014586412405	Inner flange	02	118
6 38 02 052 00 0	4014586186115	Threaded flange	02	118
6 38 02 084 00 9	4014586186207	Threaded flange	02	
6 38 02 105 00 0	4014586186252	Threaded flange	02	
6 38 02 106 00 3	4014586186269	Grinding wheel	02	
6 38 02 107 00 7	4014586186276	Flange Clamping unit	02	
6 38 02 178 02 3	4014586212890	Clamping unit	02	
6 38 02 180 02 9 6 38 02 182 00 6	4014586212883 4014586232805	Clamping unit	02	
6 38 02 182 00 6	4014586232805	Flange Clamping unit	02	
6 38 02 183 02 5	4014586233468	Clamping unit Clamping unit	02	
6 38 02 185 03 1	4014586233321	Clamping unit	02	
6 38 02 191 01 0	4014586356266	Quick-clamping nut	02	118
0 30 05 131 01 0	101 1300330200	auton dumping nat		

Part number	EAN	Description	PC	Page
6 38 02 197 00 0	4014586455587	Quick-clamping nut	02	_
6 38 03 027 03 8	4014586228136	Wheel arbor	02	137
6 38 03 066 02 4	4014586226613	Wheel arbor	02	137
6 38 03 067 02 8	4014586226729	Wheel arbor, Length 100 mm	02	137
6 38 03 071 02 0	4014586328898	Wheel arbor, Length 50 mm	02	137
6 38 06 012 00 8	4014586186801	Backing pad, Ø 120 mm	02	142
6 38 06 030 00 4	4014586186832	Backing pad, Ø 170 mm	02	143
6 38 06 034 01 7	4014586186849	Elastic backing pad, Ø 180 mm	02	
6 38 06 076 00 1	4014586187006	Contact disc	02	
6 38 06 077 00 5	4014586187013	Contact disc	02	
6 38 06 087 01 3	4014586187112	Elastic backing pad, Ø 125 mm	02	118
6 38 06 088 02 7	4014586187136	Sanding pad, Model medium	02	134
6 38 06 090 02 3	4014586187174	Sanding pad, Model medium	02	134
6 38 06 095 02 1	4014586187235	Sanding pad, Model medium	02	134
6 38 06 101 02 0	4014586187358	Sanding pad, Model hard	02	134
6 38 06 102 02 3	4014586187372	Sanding pad, Model hard	02	134
6 38 06 103 02 7	4014586187396	Sanding pad, Model hard	02	134
6 38 06 114 02 4	4014586187556	Sanding pad, Model soft	02	134
6 38 06 116 02 1	4014586187594	Sanding pad, Model hard	02	134
6 38 06 117 02 5	4014586187617	Sanding pad, Model soft	02	134
6 38 06 118 02 3	4014586187631	Sanding pad, Model extra soft	02	134
6 38 06 129 22 0	4014586391090	Sanding pad set, unperforated, Edge length 80 mm, Mount SL	04	223
6 38 06 136 22 0	4014586391106	Sanding pad set, perforated, Edge length 80 mm, Mount SL	04	224
6 38 06 138 01 5	4014586213798	Elastic backing pad, ∅ 125 mm	02	-
6 38 06 140 22 0	4014586391113	Felt polishing pad, Edge length 80 mm, Mount SL	04	225
6 38 06 141 22 0	4014586391120	Supersoft sanding pad, Edge length 80 mm, Mount SL	04	223
6 38 06 142 22 0	4014586391137	Sanding pad set, flat, Edge length 80 mm, Mount SL	04	223
6 38 06 143 01 7	4014586212906	Elastic backing pad, Ø 115 mm	02	
6 38 06 159 22 0	4014586391144	Sanding finger, No. in pack 2 pcs, Mount SL	04	224
6 38 06 166 02 6	4014586215990	Sanding pad, Model extra soft	02	134
6 38 06 167 02 0	4014586216003	Sanding pad	02	134
6 38 06 168 01 2	4014586226569	Backing pad, Ø 115 mm	02	132
6 38 06 169 01 6	4014586226743	Backing pad, Ø 125 mm	02	142
6 38 06 170 01 8	4014586226750	Backing pad, Ø 150 mm	02	142
6 38 06 171 01 7	4014586226767	Backing pad, Ø 200 mm	02	143
6 38 06 172 01 0	4014586226774	Backing pad, Ø 115 mm	02	132
6 38 06 174 01 2	4014586233420	Elastic backing pad, ∅ 180 mm	02	
6 38 06 174 02 8	4014586233437	Elastic backing pad, ∅ 180 mm	02	
6 38 06 178 01 1	4014586233994	Backing pad, ∅ 130 mm	02	142
6 38 06 179 01 5	4014586233956	Backing pad, Ø 80 mm	02	142
6 38 06 181 01 6	4014586246383	Sanding strip roll	02	136
6 38 06 181 03 0	4014586306698	Standard stainless steel set for pipes	02	135
6 38 06 184 01 0	4014586282381	Backing pad	02	
6 38 06 186 01 0	4014586299228	Backing pad	02	
6 38 06 187 01 0	4014586304984	Backing pad, Ø 170 mm	02	142
6 38 06 188 01 0	4014586304991	Sanding pad, Ø 150 mm	02	143
6 38 06 192 01 0	4014586305257	Expansion roller Stainless steel set for grinding surfaces	02	137
6 38 06 192 02 0	4014586306704	Stainless steel set for grinding surfaces	02	135
6 38 06 193 01 0	4014586305363	Cool sanding pad, Ø 115 mm Stainless steel set – Preparing to polish surfaces / pipes / profiles	02	132 133
6 38 06 193 04 0	4014586328911		04	225
6 38 06 195 21 0	4014586391151 4014586328935	Sanding set, Ø 115 mm, Mount SLP Cool sanding pad, Ø 75 mm	02	132
6 38 06 196 01 0	4014586328935	Sanding set, Edge length 130 mm, Mount SLP	04	225
6 38 09 004 01 9	4014586246468	Adhesive strip	02	136
6 38 10 026 01 0	4014586313337	Stepped grinding arm, Belt width 3/6 mm	02	131
6 38 10 027 01 0	4014586313337	Straight grinding arm, Belt width 6 mm	02	131
6 38 10 030 01 0	4014586313351	Straight grinding arm, Belt width 20 mm	02	131
6 38 10 031 01 0	4014586392912	Profile sanding set, Mount SLP	04	224
6 38 11 004 01 0	4014586324838	Safety hood for cutting work, Ø 180 mm	02	
6 38 11 005 01 0	4014586324845	Safety hood for cutting work, Ø 230 mm	02	

Part number	EAN	Description	PC	Page
6 38 11 008 01 0	4014586324852	Safety hood for cutting work	02	
6 38 11 009 01 0	4014586324869	Safety hood for cutting work, Ø 180 mm	02	
6 38 11 010 01 0	4014586324876	Safety hood for cutting work, Ø 230 mm	02	
6 38 11 016 01 0	4014586392400	Safety hood for cutting work, Ø 115 mm	02	119
6 38 11 017 01 0	4014586392417	Safety hood for cutting work, Ø 125 mm	02	119
6 38 11 018 01 0	4014586392424	Safety hood for cutting work, Ø 150 mm	02	119
6 39 01 018 01 9	4014586241807	QuickIN-adaptors, Taper MT 2, Cutting depth 50 mm, Bore Ø 12 - 35 mm	02	60
6 39 01 019 01 3	4014586241814	QuickIN-adaptors, Taper MK 3, Cutting depth 50 mm, Bore Ø 12 - 65 mm	02	60
6 39 01 020 00 6	4014586241821	QuickIN-adaptor	02	58
6 39 01 021 01 4	4014586241845	QuickIN-adaptor	02	58
6 39 01 022 00 8	4014586241852	QuickIN-adaptor	02	59
6 39 01 023 00 2	4014586241869	QuickIN-adaptor	02	59
6 39 01 023 01 1	4014586258621	Key-type drill chuck with QuickIN holder, Chuck opening 1 - 16 mm	02	59
6 39 01 023 02 0	4014586317960	Key-type drill chuck with QuickIN holder, Chuck opening 1.5 - 13 mm	02	59
6 39 01 024 01 9	4014586244433	QuickIN-adaptor	02	58
6 39 01 027 01 0	4014586253480	Adapter with 3/4" Weldon fitting	02	59
6 39 01 028 01 8	4014586254685	Retro-fitting kit	02	
6 39 01 030 01 4	4014586262796	High-speed construction screws, Ø 3.9 mm, L 35 mm, No. in pack 1,000 pcs	02	
6 39 01 030 02 0	4014586331928	High-speed construction screws, Ø 3.9 mm, L 35 mm, No. in pack 10,000 pcs	02	
6 39 01 031 01 3	4014586262802 4014586331935	High-speed construction screws, Ø 3.9 mm, L 30 mm, No. in pack 1,000 pcs	02	
6 39 01 031 02 0	4014586351935	High-speed construction screws, Ø 3.9 mm, L 30 mm, No. in pack 10,000 pcs High-speed construction screws, Ø 3.9 mm, L 35 mm, No. in pack 1,000 pcs	02	
6 39 01 032 01 0	4014586262819	High-speed construction screws, Ø 3.9 mm, L 35 mm, No. in pack 1,000 pcs	02	
6 39 01 032 02 0	4014586262826	High-speed construction screws, Ø 3.9 mm, L 45 mm, No. in pack 10,000 pcs	02	
6 39 01 033 02 0	4014586331959	High-speed construction screws, Ø 3.9 mm, L 45 mm, No. in pack 1,000 pcs	02	
6 39 01 033 02 0	4014586262833	High-speed construction screws, Ø 3.9 mm, L 30 mm, No. in pack 10,000 pcs	02	
6 39 01 034 02 0	4014586331966	High-speed construction screws, Ø 3.9 mm, L 30 mm, No. in pack 1,000 pcs	02	
6 39 01 035 02 0	4014586331973	High-speed construction screws, Ø 4.2 mm, L 35 mm, No. in pack 10,000 pcs	02	
6 39 01 036 01 0	4014586274096	Gravity-fed cooling lubricant unit.	02	
6 39 01 037 01 0	4014586274980	Contact and swarf protection	02	
6 39 01 038 02 0	4014586298757	QuickIN MAX output, Taper MK 3, Cutting depth 50 mm, Bore Ø 50 - 80 mm	02	
6 39 01 039 02 0	4014586310299	QuickIN output, Taper MK 3, Cutting depth 50 mm, Bore Ø 12 - 65 mm	02	
6 39 01 040 01 0	4014586296647	Weldon 32 output, Mount Jancy	02	
6 39 01 042 01 0	4014586296685	Weldon 32 output, Mount Hougen	02	
6 39 01 045 01 0	4014586317977	Adapter with QuickIN MAX / Weldon 32 fitting	02	59
6 39 01 047 00 0	4014586336756	QuickIN PLUS adapter on B16	02	
6 39 01 048 02 0	4014586355528	QuickIN-adaptors, Taper MK 3, Cutting depth 50 mm, Bore Ø 12 - 65 mm	02	60
6 39 01 049 02 0	4014586355535	QuickIN-adaptors, Taper MK 3, Cutting depth 75 mm, Bore Ø 12 - 65 mm	02	60
6 39 01 050 02 0	4014586355542	3/4" Weldon mounting shaft, Taper MK 3, Cutting depth 50 mm, Bore Ø 12 - 65 mm	02	
6 39 01 051 02 0	4014586355559	3/4" Weldon mounting shaft, Taper MK 3, Cutting depth 75 mm, Bore Ø 12 - 65 mm	02	_
6 39 01 052 02 0	4014586355566	3/4" Weldon mounting shaft, Taper MK 3, Cutting depth 50 mm, Bore Ø 12 - 65 mm	02	_
6 39 01 053 02 0	4014586355573	3/4" Weldon mounting shaft, Taper MK 3, Cutting depth 75 mm, Bore Ø 12 - 65 mm	02	_
6 39 01 054 00 0	4014586365169	QuickIN Plus adapter for 1/2" -20 UNF	02	_
6 39 01 054 01 0	4014586365176	Quick-action chucks	02	_
6 39 01 055 02 0	4014586371160	QuickIN-adaptors, Taper MK 3, Cutting depth 75 mm, Bore Ø 12 - 65 mm	02	60
6 39 01 057 02 0	4014586371122	QuickIN-adaptors, Taper MT 2, Cutting depth 75 mm, Bore Ø 12 - 35 mm	02	60
6 39 01 061 00 0	4014586369235	Adapter 3/4" Weldon on B16	02	59
6 39 01 061 02 0	4014586425245	Key-type drill chuck with 3/4" Weldon fitting, Chuck opening 1.5 - 13 mm	02	59
6 39 01 063 02 0	4014586403182	3/4" Weldon mounting shaft, Taper MT 2, Cutting depth 50 mm, Bore Ø 12 - 35 mm	02	
6 39 01 064 02 0	4014586403199	3/4" Weldon mounting shaft, Taper MT 2, Cutting depth 75 mm, Bore Ø 12 - 35 mm	02	
6 39 01 065 02 0	4014586403205	QuickIN-adaptors, Taper MT 2, Cutting depth 50 mm, Bore Ø 12 - 35 mm	02	60
6 39 01 066 02 0	4014586403212	QuickIN-adaptors, Taper MT 2, Cutting depth 75 mm, Bore Ø 12 - 35 mm	02	60
6 39 01 070 00 0	4014586407678	Adapter with 3/4" Weldon fitting	02	59
6 39 01 072 02 0	4014586425276	Weldon 32 mounting shaft, Taper MT 4, Cutting depth 50 mm, Bore Ø 50 - 100 mm	02	60
6 39 01 073 02 0	4014586425283	3/4" Weldon mounting shaft, Taper MK 3, Cutting depth 75 mm, Bore Ø 12 - 65 mm	02	60
6 39 01 074 02 0	4014586425290	3/4" Weldon mounting shaft, Taper MK 3, Cutting depth 50 mm, Bore Ø 12 - 65 mm	02	60
6 39 01 075 01 0	4014586425191	Adapter with Weldon 32 fitting	02	59
6 39 01 076 01 0	4014586425207	Adapter with QuickIN MAX / Weldon 32 fitting	02	59
6 39 01 078 01 0	4014586425214	Adapter with 1-1/4" Weldon fitting	02	
6 39 02 002 01 3	4014586188232	Paddle	02	73

6.89 0.0760.1 6. 4.41 4456188052. U-brayed. Cut length 2 form 94 24 6.99 0.081.0 13. 4.01 456818865. Straight form. Cut length 60 mm. Iotal length 120 mm 0.4 24 6.99 0.081.0 13. 4.01 456818865. Straight form. Cut length 60 mm. Iotal length 120 mm 0.4 24 6.99 0.081.0 13. 4.01 456818879. U-brayed. Cut length 16 mm. Install length 150 mm 0.4 24 6.99 0.0801.0 14. 4.01 456818879. U-brayed. Cut length 16 mm. Install length 120 mm 0.4 24 6.99 0.0801.0 14. 4.01 456818879. U-brayed. Cut length 16 mm. Install length 120 mm 0.4 24 8.99 0.1901.0 14. 4.01 456818879. U-brayed. Cut length 16 mm. Install length 120 mm 0.4 24 8.99 0.1901.0 14. 4.01 456818879. U-brayed. Cut length 16 mm. Install length 120 mm 0.4 24 8.99 0.1901.0 14. 4.01 456818879. Straight form. Cut length 15 mm. Total length 75 mm 0.4 24 8.99 0.1901.0 14. 4.01 456818879. Straight form. Cut length 15 mm. Total length 75 mm 0.4 24 8.99 0.1901.0 15. 4.01 4568188939. Straight form. Cut l	Part number	EAN	Description					
6.89 0.0760.1 6. 4.41 4456188052. U-brayed. Cut length 2 form 94 24 6.99 0.081.0 13. 4.01 456818865. Straight form. Cut length 60 mm. Iotal length 120 mm 0.4 24 6.99 0.081.0 13. 4.01 456818865. Straight form. Cut length 60 mm. Iotal length 120 mm 0.4 24 6.99 0.087.0 13. 4.01 456818879. U-brayed. Cut length 16 mm. Iotal length 120 mm 0.4 24 6.99 0.087.0 12. 4.01 456818879. U-brayed. Cut length 16 mm. Iotal length 120 mm 0.4 24 6.99 0.097.0 12. 4.01 456818879. Straight form. Cut length 50 mm. Total length 120 mm 0.4 24 8.99 0.190.1 12. 4.01 456818887. Straight form. Cut length 50 mm. Total length 120 mm 0.4 24 8.99 0.190.1 12. 4.01 45681887. Aut length 50 mm. Cut length 50 mm. Total length 72 mm 0.4 24 8.99 0.190.1 12. 4.01 45681887. Aut length 50 mm. Cut length 50 mm. Total length 72 mm 0.4 24 8.99 0.1 1.0 12. 4.01 45681887. Aut length 50 mm. 0.4 24 8.99 0.1 1.0 12. 4.01 456818889. Straight form. Total length 57 mm. 0.4	6 39 03 072 01 7	4014586188577	urved form, Cut length 45 mm, Total length 80 mm					
6.9910.07.00 / 2.4014666188645 Li Sopper Count Call bength 5 mm. 9.4 2.4014661886855 Curved Form. Cut length 1 fmm. Total length 80 mm. 9.4 2.4014686188655 Curved Form. Cut length 1 fmm. Total length 80 mm. 9.4 2.4014686188655 Curved Form. Cut length 1 fmm. Total length 80 mm. 9.4 2.4014686188655 Curved Form. Cut length 1 fmm. Total length 80 mm. 9.4 2.4014686188659 2.4014686188659 2.4014686188659 2.4014686188659 3.4014686188659	6 39 03 073 01 1	4014586188584	Straight form, Cut length 35 mm, Total length 56 mm	04	242			
6 82 00 00 00 01 01 3 40145662888275 Stroigh Row Culteright 60 mm. Total largin 80 mm 04 254 6 90 00 00 07 01 9 40145662888275 U-shaeed. Cut length 18 mm 04 244 6 90 00 00 07 01 9 40145662888275 U-shaeed. Cut length 18 mm 04 244 6 90 00 00 07 01 9 4014566288279 U-shaeed. Cut length 18 mm 04 244 6 90 00 07 01 01 401456638880 Stroight Form. Cut length 16 mm. Iotal length 120 mm 04 244 6 90 00 07 01 01 401456638880 Stroight Form. Cut length 15 mm. Total length 75 mm 04 244 6 90 00 07 01 01 401456638880 Stroight Form. Cut length 15 mm. Total length 75 mm 04 244 6 90 00 10 01 01 4014566388800 Stroight Form. Cut length 15 mm. Total length 75 mm 04 244 8 90 00 10 01 01 4014566388800 Stroight Form. Cut length 15 mm. Total length 75 mm 04 244 8 90 00 10 01 01 4014566388801 Scrippe Kind. Cut length 15 mm. Total length 75 mm 04 244 8 90 00 10 01 01 4014566388801 Scrippe Kind. Cut length 15 mm. Total length 75 mm 04 244 8 90 00 10 01 01 40 4014566388801 Scrippe Kind. Cut length	6 39 03 076 01 6	4014586188621	U-shaped, Cut length 24 mm	04	244			
6.89 0.00 20 6. M. 240 450658080000 Content mouth length 18 mm. Total length 18 mm. 0.4 0.244 6.89 0.00 20 6.0 1. 4014566180070 U-shaped, Cut length 18 mm. 0.4 0.244 6.89 0.00 20 6.0 1. 4014566180070 U-shaped, Cut length 18 mm. 0.4 0.244 6.89 0.00 20 7.0 1. 4014566180070 U-shaped, Cut length 18 mm. 0.4 0.244 6.89 0.00 10 0. 4014561808070 U-shaped, Cut length 18 mm. Total length 170 mm. 0.4 0.244 6.89 0.00 10 0. 4014561808070 U-shaped, Cut length 16 mm. Total length 170 mm. 0.4 0.244 6.89 0.00 10 0. 4014561808070 U-shaped, Cut length 16 mm. Total length 75 mm. 0.4 0.244 6.89 0.00 10 0. 4014561808070 U-shaped, Cut length 16 mm. Total length 75 mm. 0.4 0.244 6.89 0.00 10 0. 4014561808070 U-shaped, Cut length 16 mm. Total length 75 mm. 0.4 0.244 6.89 0.00 10 0. 4014561808070 U-shaped, Cut length 16 mm. Total length 75 mm. 0.4 0.244 6.89 0.00 10 0. 4014561808070 U-shaped, Cut length 16 mm. 0.4 0.244 6.89 0.00 10 0. 0. 4014561808070 U-shaped, Cut length 55 mm. Total length 75 mm. 0.4 0.244 6.89 0.00 10 0. 0. 0. 4014561808070 U-shaped, Cut length 35 mm. Total length 75 mm. 0.4 0.244 6.89 0.00 10 0. 0. 0. 0. 4014561808070 U-shaped, Cut length 35 mm. Total length 75 mm. 0.4 0.244 6.89 0.00 10 0. 0. 0. 0. 4014561808070 U-shaped, Cut length 35 mm. 0.4 0.2	6 39 03 079 01 2	4014586188645	U-shaped, Cut length 36 mm	04	244			
6.9015.07.01.19 4.01456628872 J. U-shapes. Cut length 18 mm 94 24.015607018 9.015607018 4.01456628802 Snaghr farm. Cut length 15 mm. Total length 125 mm 94 24.015607018 9.015607018 9.01456628802 Snaghr farm. Cut length 15 mm. Total length 125 mm 94 24.015607019 94 24.	6 39 03 081 01 3	4014586188676	Straight form, Cut length 60 mm, Total length 120 mm	04	242			
6.99.00.00.00.00.00.00.00.00.00.00.00.00.	6 39 03 082 01 6	4014586188683	Curved form, Cut length 14 mm, Total length 80 mm	04	245			
6.99.05.07.01.8. 4014566188829. Straight Form, Cut length 16 mm, Total langen 120 mm 40 244 6.99.05.30.10.10.1. 4014566188897. U-thopped, Cut length 16 mm, Total langen 120 mm 40 244 6.99.05.30.10.1.0.3. 4014566188898. Straight Form, Cut length 16 mm, Total length 75 mm 40 244 6.99.05.10.0.1.0.3. 4014566188898. Straight Form, Cut length 32 mm, Total length 75 mm 40 244 6.99.05.10.0.1.0.3. 4014566188891. Scrape Fraidhill, Cut length 25 mm, Total length 75 mm 40 244 6.99.05.10.0.1.0.3. 401456818891. U-shaped, Cut length 25 mm, Total length 64 mm 40 244 6.99.05.10.0.1.0.3. 401456818891. U-shaped, Cut length 32 mm, Total length 75 mm 40 244 6.99.05.10.1.0.1.0.3. 401456818892. U-shaped, Cut length 32 mm 40 244 6.99.05.10.1.0.1.0.3. 401456818893. U-shaped, Cut length 32 mm 40 244 6.99.05.10.1.0.1.0.3. 401456818893. U-shaped, Cut length 32 mm 40 244 6.99.05.10.10.1.0.3. 401456818893. U-shaped, Cut length 32 mm 40	6 39 03 087 01 9	4014586188737	U-shaped, Cut length 18 mm	04	244			
6.939.03.09.01.01 4014565688570 Straight Form, Coat length 150 mm 04 244 6.939.03.10.01.01 4014566188874 U-t-happerd, Cust length 150 mm 04 244 6.939.03.10.01.01 4014566188893 Straight Form, Cust length 150 mm, Total length 150 mm 04 244 6.939.03.10.01.01 4014566188903 Straight Form, Cust length 50 mm, Total length 164 mm 04 244 6.939.03.10.01.01 4014566188903 U-shaped, Cust length 40 mm 04 244 6.939.03.10.01.01 4014566188903 Straight Form, Cust length 40 mm 04 244 6.939.03.10.01.01 4014566188903 Straight Form, Cust length 40 mm 04 244 6.939.03.11.01.01 4014566188903 Straight Form, Cust length 40 mm 04 244 6.939.03.11.01.01 4014566188903 Scape rinkle, Custing width 5 mm 04 244 6.939.03.11.01.01 4014566188903 Scape rinkle, Custing width 5 mm 04 244 6.939.03.11.01.01 4014566188903 Custing Blade 04 244 6.939.03.11.01.01 401456618903 Cus	6 39 03 095 01 1	4014586188799	U-shaped, Cut length 16 mm	04	244			
	6 39 03 097 01 8	4014586188829	Straight form, Cut length 58 mm, Total length 125 mm	04	244			
6.99 10 10 10 17 40.1458 (1.1880)88 Straight form, Cut length 15 mm, Total length 75 mm 0.4 244 6.9 00 10 10 10 19 40.1458 (1.1880)11 Straight form, Cut length 16 mm, Total length 75 mm 0.4 244 6.9 00 10 10 10 19 40.1458 (1.1880)11 Straight form, Cut length 16 mm 0.4 244 6.9 00 10 10 10 19 40.1458 (1.1880)11 U-shaped, Cut length 16 mm 0.4 244 6.9 00 10 10 10 19 40.1458 (1.1880)11 U-shaped, Cut length 16 mm 0.4 244 6.9 00 11 10 19 40.1458 (1.1880)11 U-shaped, Cut length 16 mm 0.4 244 6.9 00 11 10 19 40.1458 (1.1880)11 U-shaped, Cut length 16 mm 0.4 244 6.9 00 11 10 19 40.1458 (1.1880)11 U-shaped, Cut length 15 mm 0.4 244 6.9 00 11 10 10 1 40.1458 (1.1880)11 U-shaped, Cut length 13 mm 0.4 245 6.9 00 11 10 10 1 40.1458 (1.1880)11 U-shaped, Cut length 13 mm 0.4 245 6.9 00 11 10 10 1 40.1458 (1.1880)11 U-shaped, Cut length 12 mm 0.4 245 6.9 00 11 10 10 1	6 39 03 099 01 0	4014586188850	Straight form, Cut length 16 mm, Total length 120 mm	04	244			
6.99 0.0 180 0.1 S 40145861889014 Sznappir form. Cut length 16 mm, Total length 75 mm 0.9 246 6.99 0.0 180 0.1 O 40145861889315 U-shapert, Cut length 60 mm 0.9 245 6.99 0.0 180 0.1 O 40145861889325 U-shapert, Cut length 60 mm 0.9 244 6.99 0.0 180 0.1 O 4014586188942 U-shapert, Cut length 60 mm 0.9 244 6.99 0.0 180 0.1 O 4014586188943 U-shapert, Cut length 60 mm 0.9 244 6.90 0.0 181 0.1 O 4014586188973 U-shapert, Cut length 50 mm 0.9 244 6.90 0.0 181 0.1 O 4014586188977 U-shapert, Cut length 95 mm 0.9 245 6.90 0.0 181 0.1 O 4014586188907 Scraper kinike, Cuttings width 13 mm 0.9 248 6.90 0.0 181 0.1 O 4014586188907 U-shapert, Cut length 22 mm 0.9 0.9 248 6.90 0.0 181 0.1 O 4014586188905 Cutting plated 0.9 249 249 250 251 241 242 250 251 241 242 250 251 241 242	6 39 03 101 01 0	4014586188874	U-shaped, Cut length 60 mm	04	244			
6.93 93 1570 16 40145865189913 Scraper kirelle, Cut length 50 mm 0.4 244 6.39 03 170 16 4014586189932 U-shaped, Cut length 50 mm 0.4 244 6.39 03 170 10 4014586189939 U-shaped, Cut length 36 mm 0.4 244 6.39 03 170 10 401458618993 Straper form, Cut length 35 mm, Total length 75 mm 0.4 244 6.39 03 171 10 19 401458618993 U-shaped, Cut length 30 mm 0.4 244 6.39 03 171 10 19 401458618990 Scraper kinle, Cut length 95 mm 0.4 243 6.39 03 171 10 19 401458618907 Corper kinle, Letting with 13 mm 0.4 243 6.39 03 171 10 19 401458618907 Corper kinle, Letting by 20 mm 0.4 243 6.39 03 171 10 11 401458618908 Cutting blade 0.4 244 6.39 03 171 10 13 401458618908 Cutting blade 0.4 242 6.39 03 171 10 13 4014586189015 Cutting blade 0.4 243 6.39 03 172 10 13 4014586189015 Straiger form, Cut length 13 mm, Total length 56 mm 0.4	6 39 03 103 01 7	4014586188898	Straight form, Cut length 35 mm, Total length 75 mm	04	244			
6390 310 010 6 40145801589055 U-shaped, Cut length 16 mm 0.4 244 639 03 100 013 40145801589959 Snaight form: Cut length 35 mm. Total length 75 mm 0.4 244 639 03 110 010 40145801589969 Snaight form: Cut length 35 mm. Total length 75 mm 0.4 244 639 03 111 010 1 4014580158997 Snapper hinle, Cut length 30 mm 0.4 244 639 03 113 012 2 4014580158907 Scrapper hinle, Cut length 32 mm 0.4 245 639 03 113 012 3 4014580158907 U-shaped, Cut length 22 mm 0.4 245 639 03 113 013 4 4014580158901 U-shaped, Cut length 22 mm 0.4 245 639 03 113 013 4 4014580158901 U-shaped, Cut length 22 mm 0.4 246 639 03 112 013 4 4014580158905 Scraight from. Cut length 195 mm 0.4 242 639 03 112 013 4 4014580158905 Straight from. Cut length 195 mm 0.4 242 639 03 112 013 4 4014580158905 Straight from. Cut length 195 mm 0.4 242 639 03 112 013 4 4014580158905 Straight from.	6 39 03 104 01 5	4014586188904	Straight form, Cut length 16 mm, Total length 75 mm	04	244			
6.99 0.03 10.00 1.4 40.14 8805188942 U-shapped, Cut length 16 mm 0.4 2.44 6.39 0.03 10.00 1.0 40.14 866188950 Surplint form, Cut length 35 mm, Total length 75 mm 0.4 2.44 6.39 0.03 11.00 1.0 40.14 866188950 U-shaped, Cut length 97 mm 0.4 2.44 6.39 0.03 11.00 1.0 40.14 86618890 Scraper kinfe, Cuttlength 97 mm 0.4 2.44 6.39 0.03 11.00 1.0 40.14 86618900 Scraper kinfe set 0.4 2.43 6.39 0.03 11.00 1.0 40.14 86618900 Scraper kinfe set 0.4 2.43 6.39 0.03 11.00 1.0 40.14 86618901 U-shaped, Cut length 32 mm 0.4 2.44 6.39 0.03 11.00 1.0 40.14 86618903 Cutting blade 0.4 2.42 6.39 0.03 11.00 1.0 40.14 86618903 Scraight form, Cut length 1.0 mm 0.4 2.44 6.39 0.03 11.00 1.0 40.14 86618903 Straight form, Cut length 1.0 mm 0.4 2.44 6.39 0.03 11.00 1.0 40.14 86618903 Straight form, Cut length 1.0 mm 0.4 2.44 6.39 0.03 12.00 1.0 40.14 86618903 Straigh	6 39 03 105 01 9	4014586188911	Scraper knife, Cut length 25 mm, Total length 64 mm	04	243			
6.99 03 110 00 18 4014586188999 Straight form, Cut length 35 mm, Total length 75 mm 0.4 244 6.99 03 110 10 1 4014565188966 U-shaped, Cut length 40 mm 0.4 244 6.99 03 113 10 6 4014586188907 U-shaped, Cut length 95 mm 0.4 245 6.99 03 113 01 6 4014586189017 U-shaped, Cut length 32 mm 0.4 245 6.99 03 114 01 4 4014586189017 U-shaped, Cut length 32 mm 0.4 244 6.99 03 115 01 8 4014586189013 U-shaped, Cut length 32 mm 0.4 244 6.99 03 115 01 8 4014586189035 U-shaped, Cut length 22 mm 0.4 242 6.99 03 115 01 8 4014586189035 U-thing blade 0.4 242 6.99 03 112 01 8 4014586189055 U-thing blade 0.4 244 6.99 03 12 01 8 4014586189055 Straight form, Cut length 12 mm, Total length 65 mm 0.4 244 6.99 03 12 01 8 401458618916 Straight form, Cut length 12 mm, Total length 65 mm 0.4 244 6.99 03 12 01 8 4014586189118 Straight form, Cut length 12 mm, Total len	6 39 03 107 01 6	4014586188935	U-shaped, Cut length 60 mm	04	244			
6.999.03.110.01.01 40,145861,889866 U-shapped, Cut length 40 mm 0.4 244 6.99.03.11.10.11.01 40,145861,889973 U-shapped, Cut length 95 mm 0.4 248 6.99.03.11.10.02 40,145861,889973 Scraper Infels. Cutting width 15 mm 0.4 248 6.99.03.11.10.01 40,145861,889013 U-shapped, Cut length 52 mm 0.4 248 6.99.03.11.50.11 40,145861,89013 U-shapped, Cut length 52 mm 0.4 244 6.99.03.11.50.11 40,145861,89014 Cutting blade 0.4 242 6.99.03.11.50.13 40,145861,89014 Cutting blade 0.4 242 6.99.03.11.50.13 40,145861,89003 Stralght form, Cut length 19.5 mm 0.4 242 6.99.03.12.50.11 40,145861,89003 Stralght form, Cut length 19.5 mm 0.4 242 6.99.03.12.50.12 40,145861,89003 Stralght form, Cut length 19.5 mm 0.4 244 6.99.03.12.50.12 40,145861,89003 Stralght form, Cut length 19.5 mm 0.4 244 6.99.03.12.60.17 40,145861,89013 Stralght form, Cut length 19.5 mm	6 39 03 108 01 4		U-shaped, Cut length 16 mm	04	244			
6.39 0.3111.01 p. 4.014896188973 U-shaped. Cut length 95 mm 0.4 2.44 6.39 0.311.01 c. 4.0148961889000 Scraper kinfe: cetting width 15 mm 0.4 2.43 6.39 0.311.01 d. 4.014896189001 U-shaped. Cut length 23 mm 0.4 2.43 6.39 0.311.01 d. 4.014896189017 U-shaped. Cut length 23 mm 0.4 2.44 6.39 0.311.01 d. 4.014896189018 U-shaped. Cut length 22 mm 0.4 2.42 6.39 0.311.01 d. 4.014896189018 Cutting blade 0.4 2.42 6.39 0.312.01 d. 4.014896189068 Straight form. Cut length 19 5 mm 0.4 2.44 6.39 0.312.01 d. 4.014896189086 Straight form. Cut length 19 5 mm 0.4 2.44 6.39 0.312.01 d. 4.014896189019 Straight form. Cut length 56 mm. Total length 16 mm 0.4 2.44 6.39 0.312.01 d. 4.01489618910 Straight form. Cut length 25 mm. Total length 12 mm 0.4 2.44 6.39 0.312.01 d. 4.01489618913 Straight form. Cut length 25 mm. Total length 65 mm 0.4 2.43 6.39 0.312.01 d. 4.01489618913	6 39 03 109 01 8	4014586188959	Straight form, Cut length 35 mm, Total length 75 mm	04	244			
6 5 9 0 3 1 13 0 16 40 14 \$68 1889977 Scraper kmife. Cutting width 13 mm 0.4 24 5 6 3 9 0 3 1 13 0 0 2 40 14 \$68 1899007 U-shaped. Cut length 32 mm 0.4 24 4 6 3 9 0 3 1 15 0 1 8 40 14 \$68 189017 U-shaped. Cut length 32 mm 0.4 24 4 6 3 9 0 3 1 15 0 1 8 40 14 \$68 189031 U-shaped. Cut length 22 mm 0.4 24 4 6 3 9 0 3 1 15 0 1 5 40 14 \$68 189035 Cutting blade 0.4 24 2 6 3 9 0 3 1 10 1 3 40 14 \$68 189035 Cutting blade 0.4 24 2 6 3 9 0 3 1 20 1 1 8 40 14 \$68 189036 U-shaped. Cut length 19 5 mm 0.4 24 4 6 3 9 0 3 1 20 1 1 8 40 14 \$68 189038 Straight form. Cut length 14 mm. Total length 55 mm 0.4 24 4 6 3 9 0 3 1 20 1 1 4 0 14 \$68 189033 Straight form. Cut length 26 mm. Total length 56 mm 0.4 24 4 6 3 9 0 3 1 20 1 1 4 0 14 \$68 189103 Straight form. Cut length 12 mm. Total length 65 mm 0.4 24 4 6 3 9 0 3 1 20 1 1 4 0 14 \$68 18913 Straight form. Cut length 12 mm. Total length 12 mm 0.4 24 4 6 3 9 0 3 1 20 1 1 4 0 14 \$68 18913 </td <td>6 39 03 110 01 0</td> <td>4014586188966</td> <td>U-shaped, Cut length 40 mm</td> <td>04</td> <td>244</td>	6 39 03 110 01 0	4014586188966	U-shaped, Cut length 40 mm	04	244			
6 39 03 113 02 2 4014586189000 Scraper kinife set 0.4 243 6 39 03 114 01.4 4014586189031 U-shaped, Cut length 32 mm 0.4 244 6 39 03 115 01.1 4014586189031 U-shaped, Cut length 22 mm 0.4 244 6 39 03 117 01.5 4014586189008 Cutting blade 0.4 242 6 39 03 117 01.5 40145861890062 U-shaped, Cut length 19 5 mm 0.4 242 6 39 03 120 01.9 40145861890062 U-shaped, Cut length 19 5 mm 0.4 242 6 39 03 120 01.9 4014586189006 Straight form, Cut length 19 5 mm 0.4 244 6 39 03 122 01.1 4014586189109 Straight form, Cut length 19 mm, Total length 65 mm 0.4 244 6 39 03 122 01.1 401458618910 Straight form, Cut length 32 mm, Total length 10 mm 0.4 244 6 39 03 122 01.2 401458618910 Straight form, Cut length 32 mm, Total length 110 mm 0.4 244 6 39 03 122 01.2 401458618910 Straight form, Cut length 52 mm, Total length 110 mm 0.4 243 6 39 03 123 01.5 401458618910 <t< td=""><td>6 39 03 111 01 9</td><td>4014586188973</td><td>U-shaped, Cut length 95 mm</td><td>04</td><td>244</td></t<>	6 39 03 111 01 9	4014586188973	U-shaped, Cut length 95 mm	04	244			
6 39 03 114 01 4 40 14586189017 U-shaped, Cut length 32 mm 04 244 6 39 03 115 01 8 40 14586189031 U-shaped, Cut length 22 mm 04 242 6 39 03 115 01 1 40 14586189035 Cutting blade 04 242 6 39 03 117 01 5 40 14586189055 Cutting blade 04 242 6 39 03 120 01 8 40 14586189052 U-shaped, Cut length 19 5 mm 04 244 6 39 03 120 01 9 40 14586189038 Straight Corm, Cut length 14 mm, Total length 65 mm 04 244 6 39 03 120 01 8 40 14586189039 Straight Corm, Cut length 19 mm, Total length 65 mm 04 244 6 39 03 120 01 8 40 14586189103 Straight form, Cut length 22 mm, Total length 10 mm 04 244 6 39 03 120 01 8 40 14586189103 Straight form, Cut length 22 mm, Total length 10 mm 04 244 6 39 03 120 01 9 40 14586189103 Straight form, Cut length 22 mm, Total length 10 mm 04 244 6 39 03 120 01 9 40 14586189103 Straight form, Cut length 32 mm, Total length 10 mm 04 243 6 39 03 120 01 9	6 39 03 113 01 6	4014586188997	Scraper knife, Cutting width 13 mm	04	243			
63 90 31 15 01 8 4014586189031 U-shaped, Cut length 22 mm 04 244 63 90 31 15 01 1 4014586189048 Cutting blade 04 242 63 90 31 15 01 3 4014586189062 U-shaped, Cut length 19 5 mm 04 244 63 90 31 12 01 3 4014586189062 U-shaped, Cut length 19 5 mm 04 244 63 90 31 22 01 1 4014586189068 Straight form, Cut length 26 mm, Total length 56 mm 04 244 63 90 31 22 01 1 4014586189109 Straight form, Cut length 19 5 mm 04 244 63 90 31 22 01 1 4014586189109 Straight form, Cut length 19 5 mm, Total length 56 mm 04 244 63 90 31 22 01 1 4014586189109 Straight form, Cut length 32 mm, Total length 10 mm 04 244 63 90 31 22 01 3 401458618910 Straight form, Cut length 27 mm, Total length 10 mm 04 244 63 90 31 22 01 4 401458618910 Straight form, Cut length 27 mm, Total length 120 mm 04 243 63 90 31 22 01 5 401458618913 Straight form, Cut length 70 mm, Total length 20 mm 04 243 63 90 31 22 01 4	6 39 03 113 02 2	4014586189000	Scraper knife set	04	243			
63 90 31 16 01 1 401.4586189048 Cutting blade 04 242 63 90 31 17 01 5 401.4586189055 Cutting blade 04 242 63 90 31 18 01 3 401.4586189055 Cutting blade 04 242 63 90 31 18 01 3 401.4586189066 Straight form, Cut length 19 5 mm 04 244 63 90 31 21 01 8 401.4586189093 Straight form, Cut length 26 mm, Total length 56 mm 04 244 63 90 31 22 01 1 401.4586189033 Straight form, Cut length 19 mm, Total length 88 mm 04 244 63 90 31 22 01 3 401.4586189116 Straight form, Cut length 27 mm, Total length 110 mm 04 244 63 90 31 22 01 3 401.4586189116 Straight form, Cut length 27 mm, Total length 120 mm 04 244 63 90 31 22 01 4 401.4586189116 Cutting blade 04 242 63 90 31 22 01 5 401.4586189161 Cutting blade 04 243 63 90 31 24 01 3 401.4586189161 Cutting blade 04 243 63 90 31 25 01 4 401.4586189163 Scraper knife, cutting with 25 mm 04 <td>6 39 03 114 01 4</td> <td>4014586189017</td> <td>U-shaped, Cut length 32 mm</td> <td>04</td> <td>244</td>	6 39 03 114 01 4	4014586189017	U-shaped, Cut length 32 mm	04	244			
6 39 03 117 01 5 4014586189055 Cutting blade 04 242 6 39 03 12 01 3 4014586189062 U-shaped, Cut length 19 5 mm 04 244 6 39 03 12 01 01 4014586189033 Straight form, Cut length 14 mm, Total length 56 mm 04 244 6 39 03 12 01 1 4014586189033 Straight form, Cut length 26 mm, Total length 56 mm 04 244 6 39 03 12 01 3 4014586189109 Straight form, Cut length 32 mm, Total length 68 mm 04 244 6 39 03 12 01 3 4014586189123 Straight form, Cut length 25 mm, Total length 10 mm 04 244 6 39 03 12 01 3 4014586189123 Straight form, Cut length 25 mm, Total length 65 mm 04 244 6 39 03 12 01 4 4014586189133 Straight form, Cut length 70 mm, Total length 65 mm 04 244 6 39 03 12 01 6 4014586189138 Straight form, Cut length 25 mm, Total length 120 mm 04 244 6 39 03 12 01 6 4014586189183 Straight form, Cut length 25 mm, Total length 120 mm 04 243 6 39 03 12 01 6 4014586189183 Straight form, Cut length 32 mm 04 243 <td>6 39 03 115 01 8</td> <td>4014586189031</td> <td>U-shaped, Cut length 22 mm</td> <td>04</td> <td>244</td>	6 39 03 115 01 8	4014586189031	U-shaped, Cut length 22 mm	04	244			
63 90 31 18 01 3 4014586189062 U-shaped, Cut length 19 5 mm 04 244 63 90 31 21 01 9 4014586189086 Straight form, Cut length 14 mm, Total length 65 mm 04 244 63 90 31 21 01 8 4014586189090 Straight form, Cut length 19 mm, Total length 66 mm 04 244 63 90 31 22 01 1 4014586189109 Straight form, Cut length 19 mm, Total length 66 mm 04 244 63 90 31 22 01 3 4014586189116 Straight form, Cut length 32 mm, Total length 65 mm 04 244 63 90 31 22 01 7 4014586189130 Straight form, Cut length 32 mm, Total length 65 mm 04 244 63 90 31 28 01 2 4014586189130 Straight form, Cut length 32 mm, Total length 65 mm 04 243 63 90 31 28 01 2 4014586189130 Straight form, Cut length 32 mm, Total length 65 mm 04 243 63 90 31 28 01 2 4014586189130 Straight form, Cut length 32 mm, Total length 64 mm 04 243 63 90 31 32 01 6 4014586189130 Straight form, Cut length 12 mm, Total length 64 mm 04 243 63 90 31 32 01 6 4014586189314 Straight form, Cut length 12 mm, Total le	6 39 03 116 01 1	4014586189048	Cutting blade	04	242			
63 90 31 20 01 9 4014586189086 Straight form, Cut length 14 mm, Total length 65 mm 04 244 63 90 31 22 01 1 4014586189093 Straight form, Cut length 19 mm, Total length 68 mm 04 244 63 90 31 22 01 1 4014586189109 Straight form, Cut length 19 mm, Total length 68 mm 04 244 63 90 31 23 01 3 4014586189116 Straight form, Cut length 32 mm, Total length 110 mm 04 244 63 90 31 25 01 7 4014586189123 Straight form, Cut length 22 mm, Total length 100 mm 04 244 63 90 31 280 12 4014586189130 Straight form, Cut length 70 mm, Total length 120 mm 04 244 63 90 31 290 16 4014586189161 Cutting blade 04 242 63 90 31 290 16 4014586189161 Scraper knife set 04 243 63 90 31 290 10 4014586189164 Scraper knife, Cuttlength 12 mm, Total length 64 mm 04 243 63 90 31 31 01 7 4014586189215 Scraper knife, Cuttlength 32 mm, Total length 73 mm 04 243 63 90 31 31 01 7 4014586189314 Straight form, Cut length 32 mm, Total length 73 mm 04 24	6 39 03 117 01 5	4014586189055	Cutting blade	04	242			
63 90 31 21 01 8 4014586189093 Straight form, Cut length 26 mm, Total length 56 mm 04 244 63 90 31 22 01 1 4014586189109 Straight form, Cut length 19 mm, Total length 66 mm 04 244 63 90 31 23 01 5 4014586189116 Straight form, Cut length 27 mm, Total length 160 mm 04 244 63 90 31 240 11 4014586189123 Straight form, Cut length 25 mm, Total length 65 mm 04 244 63 90 31 220 11 4014586189130 Straight form, Cut length 70 mm, Total length 120 mm 04 244 63 90 31 29 01 6 4014586189178 Scraper knife set 04 243 63 90 31 29 05 0 4014586189178 Scraper knife, Cut length 120 mm 04 243 63 90 31 31 01 7 4014586210636 Scraper knife, Cut length 32 mm, Total length 64 mm 04 243 63 90 31 31 01 7 4014586189205 Scraper knife, Cuttling width 25 mm 04 243 63 90 31 31 01 3 40145861893215 Scraper knife, Cuttling width 35 mm, Total length 80 mm 04 243 63 90 31 31 01 3 4014586189331 Scraper knife, Cuttling width 13 mm 04 243	6 39 03 118 01 3	4014586189062	U-shaped, Cut length 19.5 mm	04	244			
6 39 03 122 01 1 4014586189109 Straight form, Cut length 19 mm, Total length 68 mm 04 244 6 39 03 123 01 5 4014586189123 Straight form, Cut length 32 mm, Total length 110 mm 04 244 6 39 03 124 01 3 4014586189123 Straight form, Cut length 25 mm, Total length 65 mm 04 244 6 39 03 128 01 2 4014586189130 Straight form, Cut length 70 mm, Total length 120 mm 04 244 6 39 03 129 01 6 4014586189161 Cutting blade 04 243 6 39 03 129 01 6 4014586189178 Scraper knife, Cut length 12 mm, Total length 64 mm 04 243 6 39 03 130 17 4014586189208 Scraper knife, Cut length 15 mm 04 243 6 39 03 133 01 1 4014586189208 Segment blade, Cut length 30 mm, Total length 73 mm 04 243 6 39 03 133 01 4 4014586189312 Scraper knife, Cut length 30 mm, Total length 73 mm 04 243 6 39 03 140 01 8 4014586189314 Straight form, Cut length 30 mm, Total length 80 mm 04 244 6 39 03 140 01 8 4014586189315 Scraper knife, Cut length 16-43 mm, Total length 90 mm 04 </td <td>6 39 03 120 01 9</td> <td>4014586189086</td> <td>Straight form, Cut length 14 mm, Total length 65 mm</td> <td>04</td> <td>244</td>	6 39 03 120 01 9	4014586189086	Straight form, Cut length 14 mm, Total length 65 mm	04	244			
63 93 123 015 4014586189116 Straight form, Cut length 32 mm, Total length 110 mm 04 244 63 90 31 124 013 4014586189123 Straight form, Cut length 25 mm, Total length 65 mm 04 244 63 90 31 125 017 4014586189161 Cutting blade 04 242 63 90 31 129 016 4014586189178 Scraper knife set 04 243 63 90 31 129 016 4014586108016 Scraper knife, Cut length 12 mm, Total length 64 mm 04 243 63 90 31 120 01 4014586108016 Scraper knife, Cut length 12 mm, Total length 64 mm 04 243 63 90 31 310 01 4014586189216 Curved form, Cut length 16 mm, Total length 73 mm 04 243 63 90 31 313 01 4014586189208 Segment blade, Cut length 16 mm, Total length 80 mm 04 243 63 90 31 43 013 4014586189315 Curved form, Cut length 16 mm, Total length 910 mm 04 243 63 90 31 440 01 4014586189312 Scraper knife, Cut length 16 mm, Total length 65 mm 04 243 63 90 31 47 012 4014586189321 Scraper knife, Cut length 32 mm 04 243	6 39 03 121 01 8	4014586189093	Straight form, Cut length 26 mm, Total length 56 mm	04	244			
63 90 31 124 013 4014586189123 Straight form, Cut length 25 mm, Total length 120 mm 04 244 63 90 31 126 017 4014586189130 Straight form, Cut length 70 mm, Total length 120 mm 04 244 63 90 31 28 01 2 4014586189161 Cutting blade 04 243 63 90 31 29 01 6 4014586189178 Scraper knife set 04 243 63 90 31 29 05 0 4014586210636 Scraper knife, Cut length 12 mm, Total length 64 mm 04 243 63 90 31 31 01 7 4014586189128 Segment blade, Cut length 30 mm, Total length 73 mm 04 243 63 90 31 32 010 4014586189208 Segment blade, Cut length 16 mm, Total length 80 mm 04 243 63 90 31 33 01 3 4014586189314 Straight form, Cut length 16 -43 mm, Total length 90 mm 04 245 63 90 31 440 01 4 4014586189314 Straight form, Cut length 13 mm 04 244 63 90 31 450 01 8 4014586189352 Scraper knife, Cut length 18 mm, Total length 65 mm 04 244 63 90 31 50 01 8 4014586189343 Curved form, Cut length 32 mm 04 244	6 39 03 122 01 1	4014586189109	Straight form, Cut length 19 mm, Total length 68 mm	04	244			
639 03 125 017 4014586189130 Straight form, Cut length 70 mm, Total length 120 mm 04 244 639 03 128 01 2 4014586189161 Cutting blade 04 242 639 03 129 01 6 4014586189178 Scraper knife set 04 243 639 03 129 01 0 4014586189178 Scraper knife, Cut length 12 mm, Total length 64 mm 04 243 639 03 130 10 7 4014586189218 Scraper knife, Cut length 30 mm, Total length 73 mm 04 243 639 03 133 01 0 4014586189208 Segment blade, Cut length 30 mm, Total length 73 mm 04 243 639 03 133 01 4 4014586189215 Curved form, Cut length 16 mm, Total length 80 mm 04 243 639 03 140 01 3 4014586189314 Straight form, Cut length 16 mm, Total length 100 mm 04 243 639 03 140 01 1 4014586189352 Scraper knife, Cut length 18 mm, Total length 65 mm 04 243 639 03 152 01 8 4014586189345 Scraper knife, Cut length 32 mm 04 244 639 03 152 01 8 4014586189343 Curlength 32 mm, Total length 85 mm 04 244 639 03 15	6 39 03 123 01 5	4014586189116	Straight form, Cut length 32 mm, Total length 110 mm	04	244			
639 03 128 01 2 4014586189161 Cutting blade 04 242 639 03 129 01 6 4014586189178 Scraper knife set 04 243 639 03 129 05 0 4014586189178 Scraper knife set 04 243 639 03 132 01 0 4014586210635 Scraper knife, Cut length 12 mm, Total length 64 mm 04 243 639 03 132 01 0 4014586189208 Segment blade, Cut length 30 mm, Total length 73 mm 04 242 639 03 133 01 4 4014586189215 Curved form, Cut length 16 mm, Total length 80 mm 04 245 639 03 143 01 3 4014586189321 Straight form, Cut length 13 mm, Total length 100 mm 04 243 639 03 144 01 1 4014586189321 Scraper knife, Cut length 13 mm, Total length 65 mm 04 243 639 03 147 01 2 4014586189352 U-shaped, Cut length 32 mm 04 244 639 03 152 01 8 4014586189413 Curved form, Cut length 33 mm, Total length 65 mm 04 244 639 03 153 01 2 4014586189412 U-shaped, Cut length 52 mm 04 244 639 03 150 01 0 4014586189435	6 39 03 124 01 3	4014586189123	Straight form, Cut length 25 mm, Total length 65 mm	04	244			
63 90 31 29 01 6 4014586189178 Scraper knife set 04 243 63 90 31 29 05 0 4014586210636 Scraper knife, Cut length 12 mm, Total length 64 mm 04 243 63 90 31 31 01 7 4014586210643 Scraper knife, Cuttling width 25 mm 04 243 63 90 31 31 30 1 0 4014586189208 Segment blade, Cut length 30 mm, Total length 73 mm 04 242 63 90 31 33 01 4 4014586189215 Curved form, Cut length 16 mm, Total length 80 mm 04 245 63 90 31 43 01 3 4014586189314 Straight form, Cut length 16 mm, Total length 100 mm 04 244 63 90 31 44 01 1 4014586189314 Straight form, Cut length 31 mm, Total length 65 mm 04 243 63 90 31 46 01 8 4014586189345 Scraper knife, Cut length 13 mm, Total length 65 mm 04 244 63 90 31 52 01 8 4014586189345 U-shaped, Cut length 32 mm 04 244 63 90 31 53 01 2 4014586189352 U-shaped, Cut length 52 mm 04 244 63 90 31 54 01 0 4014586189437 U-shaped, Cut length 52 mm 04 24 63 90 31 55 01	6 39 03 125 01 7	4014586189130	Straight form, Cut length 70 mm, Total length 120 mm	04	244			
63 9 0 3 129 0 5 0 4014586210636 Scraper knife, Cut length 12 mm, Total length 64 mm 04 243 6 3 9 0 3 1 31 0 1 7 4014586210643 Scraper knife, Cutting width 25 mm 04 243 6 3 9 0 3 1 32 0 10 4014586189208 Segment blade, Cut length 30 mm, Total length 73 mm 04 242 6 3 9 0 3 1 33 0 14 4014586189215 Curved form, Cut length 16 mm, Total length 80 mm 04 243 6 3 9 0 3 1 43 0 1 3 4014586189314 Straight form, Cut length 16-43 mm, Total length 100 mm 04 244 6 3 9 0 3 1 44 0 1 1 4014586189321 Scraper knife, Cutting width 13 mm 04 243 6 3 9 0 3 1 46 0 1 8 4014586189352 U-shaped, Cut length 18 mm, Total length 65 mm 04 243 6 3 9 0 3 1 47 0 1 2 4014586189352 U-shaped, Cut length 32 mm 04 244 6 3 9 0 3 1 5 2 0 1 8 4014586189343 Curved form, Cut length 52 mm 04 245 6 3 9 0 3 1 5 0 1 0 4014586189420 U-shaped, Cut length 45 mm 04 244 6 3 9 0 3 1 5 0 1 0 4014586189343 U-shaped, Out length 70 mm 04 244 6 3 9 0 3 1 5 0 0 1 5 4014586189343 U-shaped, Out length	6 39 03 128 01 2	4014586189161	Cutting blade	04	242			
639 03 131 01 7 4014586210643 Scraper knife, Cutting width 25 mm 04 243 639 03 132 01 0 4014586189208 Segment blade, Cut length 30 mm, Total length 73 mm 04 242 639 03 133 01 4 4014586189215 Curved form, Cut length 16 mm, Total length 80 mm 04 245 639 03 143 01 3 4014586189314 Straight form, Cut length 16-43 mm, Total length 100 mm 04 243 639 03 144 01 1 4014586189321 Scraper knife, Cuttling width 13 mm 04 243 639 03 147 01 2 4014586189325 Scraper knife, Cuttlength 18 mm, Total length 65 mm 04 243 639 03 147 01 2 4014586189352 U-shaped, Cut length 32 mm 04 244 639 03 153 01 2 4014586189437 U-shaped, Cut length 52 mm 04 244 639 03 153 01 2 4014586189437 U-shaped, Cut length 45 mm 04 244 639 03 155 01 4 4014586189437 U-shaped, Cut length 40 mm 04 244 639 03 155 01 4 4014586198934 U-shaped, Cut length 60 mm 04 245 639 03 157 01 1 4014586198934	6 39 03 129 01 6	4014586189178	Scraper knife set	04	243			
63 90 31 32 01 0 4014586189208 Segment blade, Cut length 30 mm, Total length 73 mm 04 242 63 90 31 33 01 4 4014586189215 Curved form, Cut length 16 mm, Total length 80 mm 04 245 63 90 31 43 01 3 4014586189314 Straight form, Cut length 16-43 mm, Total length 100 mm 04 244 63 90 31 44 01 1 4014586189321 Scraper knife, Cut length 18 mm, Total length 65 mm 04 243 63 90 31 44 01 2 4014586189352 U-shaped, Cut length 18 mm, Total length 65 mm 04 243 63 90 31 47 01 2 4014586189355 U-shaped, Cut length 32 mm 04 244 63 90 31 52 018 4014586189413 Curved form, Cut length 39 mm, Total length 85 mm 04 244 63 90 31 53 012 4014586189437 U-shaped, Cut length 52 mm 04 244 63 90 31 54 010 4014586189437 U-shaped, Cut length 45 mm 04 244 63 90 31 55 014 4014586189434 U-shaped, No. in pack 1 pcs 04 244 63 90 31 55 014 4014586193939 U-shaped, Cut length 70 mm 04 244 63 90 31 56 017 4014586193935 U-shaped, Cut length 26 mm 04 24 <td>6 39 03 129 05 0</td> <td>4014586210636</td> <td>Scraper knife, Cut length 12 mm, Total length 64 mm</td> <td>04</td> <td>243</td>	6 39 03 129 05 0	4014586210636	Scraper knife, Cut length 12 mm, Total length 64 mm	04	243			
6 39 03 133 01 4 4014586189215 Curved form, Cut length 16 mm, Total length 80 mm 04 245 6 39 03 143 01 3 4014586189314 Straight form, Cut length 16-43 mm, Total length 100 mm 04 244 6 39 03 144 01 1 4014586189321 Scraper knife, Cut length 13 mm 04 243 6 39 03 146 01 8 4014586189345 Scraper knife, Cut length 18 mm, Total length 65 mm 04 243 6 39 03 147 01 2 4014586189352 U-shaped, Cut length 32 mm 04 244 6 39 03 152 01 8 4014586189413 Curved form, Cut length 39 mm, Total length 85 mm 04 244 6 39 03 153 01 2 4014586189420 U-shaped, Cut length 52 mm 04 244 6 39 03 154 01 0 4014586189437 U-shaped, Cut length 45 mm 04 244 6 39 03 155 014 4014586189437 U-shaped, Cut length 70 mm 04 244 6 39 03 155 017 4014586193939 U-shaped, Cut length 70 mm 04 244 6 39 03 155 011 4014586193939 U-shaped, Cut length 60 mm 04 244 6 39 03 150 017 4014586193933 U-shaped, Cut length 91 mm, Total length 120 mm 04 245	6 39 03 131 01 7	4014586210643	Scraper knife, Cutting width 25 mm	04	243			
63 90 31 43 01 3 4014586189314 Straight form, Cut length 16-43 mm, Total length 100 mm 04 244 63 90 31 44 01 1 4014586189321 Scraper knife, Cutting width 13 mm 04 243 63 90 31 46 01 8 4014586189345 Scraper knife, Cut length 18 mm, Total length 65 mm 04 243 63 90 31 47 01 2 4014586189352 U-shaped, Cut length 32 mm 04 244 63 90 31 52 01 8 4014586189413 Curved form, Cut length 32 mm 04 245 63 90 31 53 01 2 4014586189413 Curved form, Cut length 52 mm 04 244 63 90 31 54 01 0 4014586189420 U-shaped, Cut length 52 mm 04 244 63 90 31 54 03 0 4014586189437 U-shaped, Cut length 45 mm 04 244 63 90 31 54 03 0 4014586189444 U-shaped, No. in pack 1 pcs 04 24 63 90 31 55 01 4 4014586189444 U-shaped, Cut length 70 mm 04 24 63 90 31 55 01 7 4014586198933 U-shaped, Cut length 60 mm 04 24 63 90 31 60 01 5 4014586198381 Straight form, Cut length 54 mm, Total length 120 mm 04 24 63 90 31 61 01 4	6 39 03 132 01 0	4014586189208	Segment blade, Cut length 30 mm, Total length 73 mm	04	242			
6 39 03 144 01 1 4014586189321 Scraper knife, Cutting width 13 mm 04 243 6 39 03 146 01 8 4014586189345 Scraper knife, Cut length 18 mm, Total length 65 mm 04 243 6 39 03 147 01 2 4014586189352 U-shaped, Cut length 32 mm 04 244 6 39 03 152 01 8 4014586189413 Curved form, Cut length 39 mm, Total length 85 mm 04 245 6 39 03 153 01 2 4014586189420 U-shaped, Cut length 52 mm 04 244 6 39 03 154 03 0 4014586189437 U-shaped, Cut length 45 mm 04 244 6 39 03 154 03 0 4014586189437 U-shaped, Cut length 45 mm 04 244 6 39 03 155 01 4 4014586189437 U-shaped, Cut length 40 mm 04 244 6 39 03 155 01 4 4014586189339 U-shaped, Cut length 70 mm 04 244 6 39 03 157 01 1 4014586198339 U-shaped, Cut length 60 mm 04 245 6 39 03 160 01 5 4014586198781 Straight form, Cut length 54 mm, Total length 120 mm 04 245 6 39 03 160 01 5 4014586198934 Cleaning blades 04 - 6 39 03 160 01 7 401458	6 39 03 133 01 4	4014586189215	Curved form, Cut length 16 mm, Total length 80 mm	04	245			
6 39 03 146 01 8 4014586189345 Scraper knife, Cut length 18 mm, Total length 65 mm 04 243 6 39 03 147 01 2 4014586189352 U-shaped, Cut length 32 mm 04 244 6 39 03 152 01 8 4014586189413 Curved form, Cut length 39 mm, Total length 85 mm 04 245 6 39 03 153 01 2 4014586189420 U-shaped, Cut length 45 mm 04 244 6 39 03 154 01 0 4014586189437 U-shaped, Cut length 45 mm 04 -4 6 39 03 155 01 4 4014586189444 U-shaped, Cut length 70 mm 04 244 6 39 03 155 01 4 40145861893393 U-shaped, Cut length 40 mm 04 245 6 39 03 157 01 1 4014586195803 U-shaped, Cut length 60 mm 04 245 6 39 03 160 01 5 4014586198781 Straight form, Cut length 54 mm, Total length 120 mm 04 245 6 39 03 161 01 4 4014586198934 Cleaning blades 04 - 6 39 03 162 01 7 4014586198934 Cleaning blades 04 - 6 39 03 162 01 7 4014586198958 Segment blade, No. in pack 1 pcs 04 242 6 39 03 162 01 0 4014586315089	6 39 03 143 01 3	4014586189314	Straight form, Cut length 16-43 mm, Total length 100 mm	04	244			
6 39 03 147 01 2 4014586189352 U-shaped, Cut length 32 mm 04 244 6 39 03 152 01 8 4014586189413 Curved form, Cut length 39 mm, Total length 85 mm 04 245 6 39 03 153 01 2 4014586189420 U-shaped, Cut length 52 mm 04 244 6 39 03 154 01 0 4014586189437 U-shaped, Cut length 45 mm 04 244 6 39 03 155 01 4 4014586189444 U-shaped, No. in pack 1 pcs 04 - 6 39 03 155 01 7 40145861993939 U-shaped, Cut length 70 mm 04 244 6 39 03 157 01 1 4014586195803 U-shaped, Cut length 60 mm 04 245 6 39 03 160 01 5 4014586198781 Straight form, Cut length 54 mm, Total length 120 mm 04 245 6 39 03 161 01 4 4014586198934 Cleaning blades 04 - 6 39 03 160 01 5 4014586315072 Cleaning blades 04 - 6 39 03 160 03 0 4014586315089 Segment blade, No. in pack 1 pcs 04 242 6 39 03 162 01 7 4014586315089 Segment blade, No. in pack 5 pcs 04 242 6 39 03 165 21 0 4014586389653 Flexible Sc	6 39 03 144 01 1	4014586189321	Scraper knife, Cutting width 13 mm	04	243			
6 39 03 152 01 8 4014586189413 Curved form, Cut length 39 mm, Total length 85 mm 04 245 6 39 03 153 01 2 4014586189420 U-shaped, Cut length 52 mm 04 244 6 39 03 154 01 0 4014586189437 U-shaped, Cut length 45 mm 04 244 6 39 03 154 03 0 4014586269016 U-shaped, No. in pack 1 pcs 04 - 6 39 03 155 01 4 4014586189444 U-shaped, Cut length 70 mm 04 244 6 39 03 156 01 7 4014586193939 U-shaped, Cut length 40 mm 04 245 6 39 03 157 01 1 4014586195803 U-shaped, Cut length 60 mm 04 245 6 39 03 160 01 5 4014586198781 Straight form, Cut length 54 mm, Total length 120 mm 04 245 6 39 03 161 01 4 4014586198934 Cleaning blades 04 - 6 39 03 161 03 0 4014586198934 Cleaning blades 04 - 6 39 03 162 01 7 4014586198958 Segment blade, No. in pack 1 pcs 04 242 6 39 03 162 03 0 401458639059 Segment blade, No. in pack 5 pcs 04 242 6 39 03 165 21 0 4014586389653 Flexible Scra	6 39 03 146 01 8	4014586189345	Scraper knife, Cut length 18 mm, Total length 65 mm	04	243			
6 39 03 153 01 2 4014586189420 U-shaped, Cut length 52 mm 04 244 6 39 03 154 01 0 4014586189437 U-shaped, Cut length 45 mm 04 -4 6 39 03 154 03 0 4014586269016 U-shaped, No. in pack 1 pcs 04 6 39 03 155 01 4 4014586189444 U-shaped, Cut length 70 mm 04 244 6 39 03 156 01 7 4014586193939 U-shaped, Cut length 40 mm 04 245 6 39 03 157 01 1 40145861985803 U-shaped, Cut length 60 mm 04 245 6 39 03 160 01 5 4014586198981 Straight form, Cut length 54 mm, Total length 120 mm 04 245 6 39 03 161 01 4 4014586198934 Cleaning blades 04 6 39 03 161 03 0 4014586198958 Segment blade, No. in pack 1 pcs 04 242 6 39 03 162 01 7 4014586198958 Segment blade, No. in pack 5 pcs 04 242 6 39 03 162 03 0 401458629805 Segment blade, No. in pack 5 pcs 04 242 6 39 03 165 21 0 4014586389653 Flexible Scraper Blade, Mount SL 04 247 6 39 03 167 25 7 4014586208862 Segment s	6 39 03 147 01 2	4014586189352	U-shaped, Cut length 32 mm	04	244			
6 39 03 154 01 0 4014586189437 U-shaped, Cut length 45 mm 04 244 6 39 03 154 03 0 4014586269016 U-shaped, No. in pack 1 pcs 04 - 6 39 03 155 01 4 4014586189444 U-shaped, Cut length 70 mm 04 244 6 39 03 156 01 7 4014586193939 U-shaped, Cut length 40 mm 04 245 6 39 03 157 01 1 4014586195803 U-shaped, Cut length 60 mm 04 244 6 39 03 160 01 5 4014586198781 Straight form, Cut length 54 mm, Total length 120 mm 04 245 6 39 03 161 01 4 4014586198934 Cleaning blades 04 - 6 39 03 161 03 0 401458615072 Cleaning blades 04 - 6 39 03 162 01 7 4014586198958 Segment blade, No. in pack 1 pcs 04 242 6 39 03 162 03 0 4014586198958 Segment blade, No. in pack 5 pcs 04 242 6 39 03 162 01 7 4014586198958 Segment blade, No. in pack 5 pcs 04 242 6 39 03 165 21 0 4014586200729 U-shaped, Cut length 28 mm 04 247 6 39 03 165 21 0 401458628862 Segment saw blade <t< td=""><td>6 39 03 152 01 8</td><td>4014586189413</td><td>Curved form, Cut length 39 mm, Total length 85 mm</td><td>04</td><td>245</td></t<>	6 39 03 152 01 8	4014586189413	Curved form, Cut length 39 mm, Total length 85 mm	04	245			
6 39 03 154 03 0 4014586269016 U-shaped, No. in pack 1 pcs 04 - 6 39 03 155 01 4 4014586189444 U-shaped, Cut length 70 mm 04 244 6 39 03 156 01 7 4014586193939 U-shaped, Cut length 40 mm 04 245 6 39 03 157 01 1 4014586195803 U-shaped, Cut length 60 mm 04 244 6 39 03 160 01 5 4014586198781 Straight form, Cut length 54 mm, Total length 120 mm 04 245 6 39 03 161 01 4 4014586198934 Cleaning blades 04 - 6 39 03 161 03 0 4014586315072 Cleaning blades 04 - 6 39 03 162 01 7 4014586198958 Segment blade, No. in pack 1 pcs 04 242 6 39 03 162 03 0 4014586315089 Segment blade, No. in pack 5 pcs 04 242 6 39 03 165 21 0 4014586389653 Flexible Scraper Blade, Mount SL 04 247 6 39 03 166 01 6 4014586208862 Segment saw blade 04 247 6 39 03 167 25 7 4014586240794 Automobile workshop accessories set 04 247 6 39 03 167 32 0 4014586252445 Accessory set for cargo	6 39 03 153 01 2		U-shaped, Cut length 52 mm	04	244			
6 39 03 155 01 4 4014586189444 U-shaped, Cut length 70 mm 04 244 6 39 03 156 01 7 4014586193939 U-shaped, Cut length 40 mm 04 245 6 39 03 157 01 1 4014586195803 U-shaped, Cut length 60 mm 04 244 6 39 03 160 01 5 4014586198781 Straight form, Cut length 54 mm, Total length 120 mm 04 245 6 39 03 161 01 4 4014586198934 Cleaning blades 04 - 6 39 03 161 03 0 4014586315072 Cleaning blades 04 - 6 39 03 162 01 7 4014586198958 Segment blade, No. in pack 1 pcs 04 242 6 39 03 162 03 0 4014586315089 Segment blade, No. in pack 5 pcs 04 242 6 39 03 163 01 1 4014586200729 U-shaped, Cut length 28 mm 04 247 6 39 03 165 21 0 4014586389653 Flexible Scraper Blade, Mount SL 04 247 6 39 03 167 25 7 4014586240794 Automobile workshop accessories set 04 247 6 39 03 167 32 0 4014586252445 Accessory set for cargo 04 247	6 39 03 154 01 0	4014586189437	U-shaped, Cut length 45 mm	04	244			
6 39 03 156 01 7 4014586193939 U-shaped, Cut length 40 mm 04 245 6 39 03 157 01 1 4014586195803 U-shaped, Cut length 60 mm 04 244 6 39 03 160 01 5 4014586198781 Straight form, Cut length 54 mm, Total length 120 mm 04 245 6 39 03 161 01 4 4014586198934 Cleaning blades 04 - 6 39 03 161 03 0 4014586315072 Cleaning blades 04 - 6 39 03 162 01 7 4014586198958 Segment blade, No. in pack 1 pcs 04 242 6 39 03 162 03 0 4014586315089 Segment blade, No. in pack 5 pcs 04 242 6 39 03 163 01 1 4014586200729 U-shaped, Cut length 28 mm 04 244 6 39 03 165 21 0 4014586389653 Flexible Scraper Blade, Mount SL 04 247 6 39 03 167 25 7 4014586240794 Automobile workshop accessories set 04 247 6 39 03 167 32 0 4014586252445 Accessory set for cargo 04 247	6 39 03 154 03 0	4014586269016	U-shaped, No. in pack 1 pcs	04	_			
6 39 03 157 01 1 4014586195803 U-shaped, Cut length 60 mm 04 244 6 39 03 160 01 5 4014586198781 Straight form, Cut length 54 mm, Total length 120 mm 04 245 6 39 03 161 01 4 4014586198934 Cleaning blades 04 - 6 39 03 161 03 0 4014586315072 Cleaning blades 04 - 6 39 03 162 01 7 4014586198958 Segment blade, No. in pack 1 pcs 04 242 6 39 03 162 03 0 4014586315089 Segment blade, No. in pack 5 pcs 04 242 6 39 03 163 01 1 4014586200729 U-shaped, Cut length 28 mm 04 244 6 39 03 165 21 0 4014586389653 Flexible Scraper Blade, Mount SL 04 227 6 39 03 167 25 7 4014586240794 Automobile workshop accessories set 04 247 6 39 03 167 32 0 4014586252445 Accessory set for cargo 04 247	6 39 03 155 01 4	4014586189444	U-shaped, Cut length 70 mm	04	244			
6 39 03 160 01 5 4014586198781 Straight form, Cut length 54 mm, Total length 120 mm 04 245 6 39 03 161 01 4 4014586198934 Cleaning blades 04 - 6 39 03 161 03 0 4014586315072 Cleaning blades 04 - 6 39 03 162 01 7 4014586198958 Segment blade, No. in pack 1 pcs 04 242 6 39 03 162 03 0 4014586315089 Segment blade, No. in pack 5 pcs 04 242 6 39 03 163 01 1 4014586200729 U-shaped, Cut length 28 mm 04 244 6 39 03 165 21 0 4014586389653 Flexible Scraper Blade, Mount SL 04 227 6 39 03 167 25 7 4014586208862 Segment saw blade 04 247 6 39 03 167 25 7 4014586240794 Automobile workshop accessories set 04 247 6 39 03 167 32 0 4014586252445 Accessory set for cargo 04 247	6 39 03 156 01 7	4014586193939	U-shaped, Cut length 40 mm	04	245			
6 39 03 161 01 4 4014586198934 Cleaning blades 04 - 6 39 03 161 03 0 4014586315072 Cleaning blades 04 - 6 39 03 162 01 7 4014586198958 Segment blade, No. in pack 1 pcs 04 242 6 39 03 162 03 0 4014586315089 Segment blade, No. in pack 5 pcs 04 242 6 39 03 163 01 1 4014586200729 U-shaped, Cut length 28 mm 04 244 6 39 03 165 21 0 4014586389653 Flexible Scraper Blade, Mount SL 04 227 6 39 03 167 25 7 4014586208862 Segment saw blade 04 247 6 39 03 167 32 0 4014586252445 Accessory set for cargo 04 247	6 39 03 157 01 1	4014586195803	U-shaped, Cut length 60 mm	04	244			
6 39 03 161 03 0 4014586315072 Cleaning blades 04 - 6 39 03 162 01 7 4014586198958 Segment blade, No. in pack 1 pcs 04 242 6 39 03 162 03 0 4014586315089 Segment blade, No. in pack 5 pcs 04 242 6 39 03 163 01 1 4014586200729 U-shaped, Cut length 28 mm 04 244 6 39 03 165 21 0 4014586389653 Flexible Scraper Blade, Mount SL 04 227 6 39 03 166 01 6 4014586208862 Segment saw blade 04 247 6 39 03 167 25 7 4014586240794 Automobile workshop accessories set 04 247 6 39 03 167 32 0 4014586252445 Accessory set for cargo 04 247	6 39 03 160 01 5	4014586198781	Straight form, Cut length 54 mm, Total length 120 mm	04	245			
6 39 03 162 01 7 4014586198958 Segment blade, No. in pack 1 pcs 04 242 6 39 03 162 03 0 4014586315089 Segment blade, No. in pack 5 pcs 04 242 6 39 03 163 01 1 4014586200729 U-shaped, Cut length 28 mm 04 244 6 39 03 165 21 0 4014586389653 Flexible Scraper Blade, Mount SL 04 227 6 39 03 166 01 6 4014586208862 Segment saw blade 04 247 6 39 03 167 25 7 4014586240794 Automobile workshop accessories set 04 247 6 39 03 167 32 0 4014586252445 Accessory set for cargo 04 247	6 39 03 161 01 4	4014586198934	Cleaning blades	04	-			
6 39 03 162 03 0 4014586315089 Segment blade, No. in pack 5 pcs 04 242 6 39 03 163 01 1 4014586200729 U-shaped, Cut length 28 mm 04 244 6 39 03 165 21 0 4014586389653 Flexible Scraper Blade, Mount SL 04 227 6 39 03 166 01 6 4014586208862 Segment saw blade 04 247 6 39 03 167 25 7 4014586240794 Automobile workshop accessories set 04 247 6 39 03 167 32 0 4014586252445 Accessory set for cargo 04 247	6 39 03 161 03 0	4014586315072	Cleaning blades	04	-			
6 39 03 163 01 1 4014586200729 U-shaped, Cut length 28 mm 04 244 6 39 03 165 21 0 4014586389653 Flexible Scraper Blade, Mount SL 04 227 6 39 03 166 01 6 4014586208862 Segment saw blade 04 247 6 39 03 167 25 7 4014586240794 Automobile workshop accessories set 04 247 6 39 03 167 32 0 4014586252445 Accessory set for cargo 04 247	6 39 03 162 01 7	4014586198958	Segment blade, No. in pack 1 pcs	04	242			
6 39 03 165 21 0 4014586389653 Flexible Scraper Blade, Mount SL 04 227 6 39 03 166 01 6 4014586208862 Segment saw blade 04 247 6 39 03 167 25 7 4014586240794 Automobile workshop accessories set 04 247 6 39 03 167 32 0 4014586252445 Accessory set for cargo 04 247	6 39 03 162 03 0	4014586315089	Segment blade, No. in pack 5 pcs	04	242			
6 39 03 166 01 6 4014586208862 Segment saw blade 04 247 6 39 03 167 25 7 4014586240794 Automobile workshop accessories set 04 247 6 39 03 167 32 0 4014586252445 Accessory set for cargo 04 247	6 39 03 163 01 1	4014586200729			244			
6 39 03 167 25 7 4014586240794 Automobile workshop accessories set 04 247 6 39 03 167 32 0 4014586252445 Accessory set for cargo 04 247	6 39 03 165 21 0	4014586389653	Flexible Scraper Blade, Mount SL	04	227			
6 39 03 167 32 0 4014586252445 Accessory set for cargo 04 247	6 39 03 166 01 6	4014586208862	Segment saw blade	04	247			
	6 39 03 167 25 7	4014586240794	Automobile workshop accessories set	04	247			
6 39 03 167 38 3 4014586265032 Automobile glazier accessory set 04 247	6 39 03 167 32 0	4014586252445	Accessory set for cargo	04	247			
	6 39 03 167 38 3	4014586265032	Automobile glazier accessory set	04	247			

Part number	EAN	Description					
6 39 03 167 66 0	4014586343549	Accessory set for interior construction work with wood	04	247			
6 39 03 167 67 0	4014586343556	Accessory set for repairing/replacing windows	04	247			
6 39 03 168 01 8	4014586210247	Straight form, Cut length 45 mm, Total length 120 mm	04	244			
6 39 03 169 01 2	4014586210261	Straight form, Cut length 60-76 mm, Total length 100 mm	04	244			
6 39 03 170 01 4	4014586210285	Straight form, Cut length 18-39 mm, Total length 100 mm	04	244			
6 39 03 171 01 3	4014586210308	Straight form, Cut length 70 mm, Total length 120 mm	04	244			
6 39 03 172 01 6	4014586211978	Straight form, Cut length 35 mm, Total length 75 mm	04	244			
6 39 03 173 01 0	4014586211985	Straight form, Cut length 23 mm, Total length 65 mm	04	244			
6 39 03 174 01 8	4014586213736	Straight form, Cut length 27 mm, Total length 85 mm	04	244			
6 39 03 176 01 5	4014586214245	Straight form, Cut length 40 mm, Total length 90 mm	04	244			
6 39 03 177 01 9	4014586214252	Straight form, Cut length 65/8 mm, Total length 85 mm	04	245			
6 39 03 181 01 2	4014586215785	Straight form, Cut length 18 mm, Total length 84 mm	04	244			
6 39 03 182 01 5	4014586216010	Straight form, Cut length 42-60 mm, Total length 145 mm	04	244			
6 39 03 183 01 9	4014586216539	Cutting blade, Blade width 3 mm, No. in pack 2 pcs	04				
6 39 03 184 01 7	4014586216546	Cutting blade, Blade width 4 mm, No. in pack 2 pcs	04				
6 39 03 185 01 1	4014586216553	Cutting blade, Blade width 5 mm, No. in pack 2 pcs	04				
6 39 03 186 01 4	4014586216560	Cutting blade, Blade width 6 mm, No. in pack 2 pcs	04				
6 39 03 191 01 1	4014586217376	U-shaped, Cut length 32 mm	04	244			
6 39 03 194 01 6	4014586221878	Straight form, Cut length 35 mm, Total length 145 mm	04	244			
6 39 03 195 01 0	4014586223513	Curved form, Cut length 32-46 mm, Total length 110 mm	04	245			
6 39 03 196 01 3	4014586222974	Segment blade, No. in pack 1 pcs	04	242			
6 39 03 196 02 0	4014586315096	Segment blade, No. in pack 5 pcs	04	242			
6 39 03 197 01 7	4014586223506	Straight form	04	243			
6 39 03 198 01 5	4014586223469	Straight form, Cut length 20-35 mm, Total length 100 mm	04	244			
6 39 03 200 21 0	4014586389660	Cutting blade, Blade width 3 mm, Mount SLP	04	228			
6 39 03 201 21 0	4014586389677	Cutting blade, Blade width 4 mm, Mount SLP	04	228			
6 39 03 202 21 0	4014586389684	Cutting blade, Blade width 5 mm, Mount SLP	04	228			
6 39 03 203 01 3	4014586228488	Straight form, Cut length 35/20 mm, Total length 83 mm	04	245			
6 39 03 206 01 8	4014586240930	Scraper blade, Length 64 mm, No. in pack 2 pcs	04	243			
6 39 03 207 01 2	4014586240947	L-shaped, Cut length 25.4 mm	04	244			
6 39 03 208 01 0	4014586240954	L-shaped, Cut length 19 mm	04	244			
6 39 03 209 01 4	4014586245133	L-shaped, Cut length 38 mm	04	244			
6 39 03 210 01 6	4014586245140	U-shaped, Cut length 19 mm	04	244			
6 39 03 211 01 5	4014586245157	U-shaped, Cut length 22.5 mm	04	244			
6 39 03 212 01 8	4014586245164 4014586258164	U-shaped, Cut length 38 mm Straight form, Cut length 60 mm, Total length 120 mm	04	244			
6 39 03 216 02 0	4014586324302	Straight form, No. in pack 100 pcs	04				
6 39 03 217 01 1	4014586265810	Hook-shaped, Cut length 38 mm	04	245			
6 39 03 225 01 0	4014586294254	Carbide segment blade, No. in pack 1 pcs	04	242			
6 39 03 225 02 0	4014586294261	Carbide segment blade, No. in pack 5 pcs	04	242			
6 39 03 226 21 0	4014586389691	Fixed Scraper Blade, Mount SL	04	227			
6 39 03 227 01 0	4014586342078	Scraper blade, Length 72 mm, No. in pack 2 pcs	04	243			
6 39 03 234 21 0	4014586389714	Fixed Scraper Blade, Mount SLP	04	228			
6 39 03 236 23 0	4014586389776	Cutting blade, No. in pack 5 pcs, Mount SLM	04	228			
6 39 03 237 21 0	4014586391175	Diamond cleaning knife, No. in pack 1 pcs, Mount SLM	04	227			
6 39 03 237 23 0	4014586391182	Diamond cleaning knife, No. in pack 5 pcs, Mount SLM	04	227			
6 39 03 238 21 0	4014586389738	Cutting blade, Mount SLM, No. in pack 1 pcs, Cutting depth 69 mm	04	228			
6 39 03 238 31 0	4014586433363	Cutting blade, Mount SLM, No. in pack 100 pcs, Cutting depth 69 mm	04				
6 39 03 239 23 0	4014586389745	Cutting blade, Mount SLM, No. in pack 5 pcs, Cutting depth 65 mm	04	228			
6 39 03 240 21 0	4014586391199	Carbide saw blade, No. in pack 1 pcs, Mount SLM	04	226			
6 39 03 240 23 0	4014586391205	Carbide saw blade, No. in pack 5 pcs, Mount SLM	04	226			
6 39 03 241 21 0	4014586391212	Carbide saw blade, No. in pack 1 pcs, Mount SLM	04	226			
6 39 03 241 23 0	4014586391229	Carbide saw blade, No. in pack 5 pcs, Mount SLM	04	226			
6 39 03 242 21 0	4014586391236	Diamond-coated saw blade, No. in pack 1 pcs, Mount SLM	04	227			
6 39 03 242 23 0	4014586391243	Diamond-coated saw blade, No. in pack 5 pcs, Mount SLM	04	227			
6 39 03 243 21 0	4014586391250	Diamond-coated saw blade, No. in pack 1 pcs, Mount SLM	04	227			
6 39 03 243 23 0	4014586391267	Diamond-coated saw blade, No. in pack 5 pcs, Mount SLM	04	227			
6 39 03 244 22 0	4014586389783	Segment saw blade, No. in pack 2 pcs, Mount SLM	04	222			
6 39 03 245 23 0	4014586389752	Cutting blade, No. in pack 5 pcs, Mount SL	04	228			
6 39 03 251 21 0	4014586409276	Multi-function knife, No. in pack 1 pcs, Mount SL	04	227			

Part number	EAN	Description	PC	Page
6 39 03 251 23 0	4014586409283	Multi-function knife, No. in pack 5 pcs, Mount SL	04	227
6 39 03 270 03 0	4014586473765	XXL 98 mm blade, pack of 5, Cut length 97 mm, Total length 105 mm	04	242
6 39 03 271 02 0	4014586473772	XXL 73 mm blade, pack of 2, Cut length 73 mm, Total length 134 mm	04	242
6 39 98 611 03 0	4014586621241	PROTECTING LATTICE	02	
6 42 01 001 00 0	4014586307305	Hook f. chip removal	02	
6 42 01 005 01 0	4014586376554	Magbrush	02	158
6 42 03 001 00 0	4014586325118	Holder	02	
6 42 03 002 01 0	4014586404844	Socket adapter, Accessory interface QuickIN	02	87
6 42 03 003 01 0	4014586404851	Tapping adapter, Accessory interface QuickIN	02	87
6 42 03 003 02 0	4014586414546	Tapping adapter, Accessory interface QuickIN	02	87
6 42 03 004 01 0	4014586404547	Extension	02	_
6 42 03 005 01 0	4014586404554	Extension	02	96
6 42 03 006 01 0	4014586420844	Drill chuck SKE, Accessory interface QuickIN	02	87
6 42 03 007 01 0	4014586420851	Hole saw adapter, Accessory interface QuickIN	02	87
6 42 03 008 01 0	4014586422909	Angled head, Accessory interface QuickIN	02	87
6 42 03 009 01 0	4014586422985	Tapping collet, Ø 3.5 mm, Square 2.7 mm, Accessory interface QuickIN	02	87
6 42 03 010 01 0	4014586419961	Tapping collet, Ø 4.5 mm, Square 3.4 mm, Accessory interface QuickIN	02	87
6 42 03 011 01 0	4014586419978	Tapping collet, Ø 6 mm, Square 4.9 mm, Accessory interface QuickIN	02	87
6 42 03 012 01 0	4014586422992	Tapping collet, Ø 7 mm, Square 5.5 mm, Accessory interface QuickIN	02	87
6 42 03 013 01 0	4014586423005	Tapping collet, Ø 8 mm, Square 6.2 mm, Accessory interface QuickIN	02	87
6 42 03 014 01 0	4014586423012	Tapping collet, Ø 9 mm, Square 7 mm, Accessory interface QuickIN	02	87
6 42 03 015 01 0	4014586423029	Tapping collet, Ø 10 mm, Square 8 mm, Accessory interface QuickIN	02	87
6 42 03 016 01 0	4014586423203	Tapping collet, Ø 11 mm, Square 9 mm, Accessory interface QuickIN	02	87
6 42 03 017 02 0	4014586436401	QuickIN set of accessories for metal, Accessory interface QuickIN	02	87
6 42 04 001 01 0	4014586351988	Cutting wire	02	_
6 42 04 002 01 0	4014586354354	Anti-Metal-Cut set	02	-
6 42 04 003 01 0	4014586371177	Extension-set	02	-
6 43 01 001 01 0	4014586440972	Cutter	02	182
6 43 01 002 01 0	4014586440989	Cutter	02	182
6 43 01 003 01 0	4014586440996	Cutter	02	182
6 43 01 004 01 0	4014586441009	Cutter	02	182
6 43 01 005 01 0	4014586444482	Cutter	02	_
6 43 01 006 01 0	4014586444499	Cutter	02	-
6 43 01 007 01 0	4014586447780	Cutter	02	182
6 43 01 008 01 0	4014586447797	Cutter	02	182
6 43 02 001 01 0	4014586441016	SX indexable tip, No. in pack 10 pcs	02	182
6 43 02 002 01 0	4014586441023	SX indexable tip, No. in pack 10 pcs	02	182
6 43 02 003 01 0	4014586441030	KX indexable tip, No. in pack 10 pcs	02	183
6 43 02 004 01 0	4014586441047	KX indexable tip, No. in pack 10 pcs	02	183
6 43 02 005 01 0	4014586441054	KX indexable tip, No. in pack 10 pcs	02	183
6 43 02 006 01 0	4014586441061	KX indexable tip, No. in pack 10 pcs	02	183
6 43 02 007 01 0	4014586447803	SX indexable tip, No. in pack 10 pcs	02	182
6 43 02 008 01 0	4014586447810	SX indexable tip, No. in pack 10 pcs	02	182
6 43 02 009 01 0	4014586447827	SX indexable tip, No. in pack 10 pcs	02	182
6 43 02 010 01 0	4014586447834	SX indexable tip, No. in pack 10 pcs	02	182
6 43 02 011 01 0	4014586447841	KX indexable tip, No. in pack 10 pcs	02	182
6 43 02 012 01 0	4014586447858	KX indexable tip, No. in pack 10 pcs	02	183
6 43 02 013 01 0	4014586447865	KX indexable tip, No. in pack 10 pcs	02	183
6 43 02 014 01 0	4014586447872	KX indexable tip, No. in pack 10 pcs	02	183
6 43 02 015 01 0	4014586447889	KX indexable tip, No. in pack 10 pcs	02	183
6 43 02 016 01 0	4014586447896	KX indexable tip, No. in pack 10 pcs	02	183
6 43 02 017 01 0	4014586447902	KX indexable tip, No. in pack 10 pcs	02	183
6 43 02 018 01 0	4014586447919	KX indexable tip, No. in pack 10 pcs	02	183
6 43 03 001 01 0	4014586441078	Guide roller	02	182
6 43 03 002 01 0	4014586441085	Guide roller	02	183
6 43 03 003 01 0	4014586441092	Guide roller	02	183
6 43 03 004 01 0	4014586441108	Guide roller	02	183
6 43 03 006 01 0	4014586447933	Guide roller	02	182
6 43 03 007 01 0	4014586447940	Guide roller	02	182
6 43 03 008 01 0	4014586447957	Guide roller	02	183

Part number	EAN	Description					
6 43 03 009 01 0	4014586447964	Guide roller	02	183			
6 43 03 010 01 0	4014586447971	Guide roller	02	183			
6 43 03 011 01 0	4014586447988	Guide roller	02	183			
6 99 02 000 00 0	4014586277479	Dust container	13	269			
6 99 02 000 14 6	4014586330693	Pipe cleaning unit	13	272			
6 99 02 000 14 8	4014586369129	Stainless steel sanding support	13	270			
6 99 02 000 14 9	4014586369136	Stainless steel sanding support	13	270			
6 99 02 000 15 0	4014586369143	Mitre joint unit for preparation of welded seams	13	270			
6 99 02 000 15 1	4014586369150	Mitre joint unit for preparation of welded seams	13	270			
6 99 02 000 18 7	4014586372655	Contact roller, Ø 193.7 mm, Width 150.0 mm	13	271			
6 99 02 000 40 9	4014586405292	Contact roller, Ø 16.0 mm, Width 50.0 mm	13	252			
6 99 02 000 41 0	4014586405308	Contact roller, Ø 18.0 mm, Width 50.0 mm	13	252			
6 99 02 000 41 1	4014586405315	Contact roller, Ø 19.0 mm, Width 50.0 mm	13	252			
6 99 02 000 41 2	4014586405322	Contact roller, Ø 20.0 mm, Width 50.0 mm	13	252			
6 99 02 000 41 3	4014586405339	Contact roller, Ø 21.0 mm, Width 50.0 mm	13	252			
6 99 02 000 41 4	4014586405346	Contact roller, Ø 21.3 mm, Width 50.0 mm	13	252			
6 99 02 000 41 5	4014586405353	Contact roller, Ø 22.0 mm, Width 50.0 mm	13	252			
6 99 02 000 41 6	4014586405360	Contact roller, Ø 25.0 mm, Width 50.0 mm	13	252			
6 99 02 000 41 7	4014586405377	Contact roller, Ø 25.4 mm, Width 50.0 mm	13	252			
6 99 02 000 41 8	4014586405384	Contact roller, Ø 26.0 mm, Width 50.0 mm	13	252			
6 99 02 000 41 9	4014586405391	Contact roller, Ø 26.9 mm, Width 50.0 mm	13	252			
6 99 02 000 42 0	4014586405407	Contact roller, Ø 27.0 mm, Width 50.0 mm	13	252			
6 99 02 000 42 1	4014586405414	Contact roller, Ø 28.0 mm, Width 50.0 mm	13	252			
6 99 02 000 42 2	4014586405421	Contact roller, Ø 28.8 mm, Width 50.0 mm	13	252			
6 99 02 000 42 3	4014586405438	Contact roller, Ø 30.0 mm, Width 50.0 mm	13	252			
6 99 02 000 42 4	4014586405445	Contact roller, Ø 31.7 mm, Width 50.0 mm	13	252			
6 99 02 000 42 6	4014586405469	Contact roller, Ø 33.0 mm, Width 50.0 mm	13	252			
6 99 02 000 42 7	4014586405476	Contact roller, Ø 33.7 mm, Width 50.0 mm	13	252			
6 99 02 000 42 8	4014586405483 4014586405490	Contact roller, Ø 34.0 mm, Width 50.0 mm	13	252 252			
6 99 02 000 42 9		Contact roller, Ø 35.0 mm, Width 50.0 mm	13	252			
6 99 02 000 43 0 6 99 02 000 43 1	4014586405506 4014586405513	Contact roller, Ø 38.0 mm, Width 50.0 mm Contact roller, Ø 38.1 mm, Width 50.0 mm	13	252			
6 99 02 000 43 1	4014586405520	Contact roller, Ø 38.3 mm, Width 50.0 mm	13	252			
6 99 02 000 43 3	4014586405537	Contact roller, Ø 40.0 mm, Width 50.0 mm	13	252			
6 99 02 000 43 4	4014586405544	Contact roller, Ø 42.0 mm, Width 50.0 mm	13	252			
6 99 02 000 43 5	4014586405551	Contact roller, Ø 42.4 mm, Width 50.0 mm	13	252			
6 99 02 001 00 0	4014586277486	Length stop	13	268			
6 99 02 002 00 0	4014586277493	Adaptor	02				
6 99 02 004 00 0	4014586277516	Stainless steel jaws	06	268			
6 99 02 006 00 0	4014586277530	Steel wire brush, Wire thickness 0.20 mm	12	269			
6 99 02 007 00 0	4014586277547	Steel wire brush, Wire thickness 0.35 mm	12	269			
6 99 02 008 00 0	4014586277554	Steel wire brush, Wire thickness 0.50 mm	12	269			
6 99 02 009 00 0	4014586277561	Steel wire brush, Wire thickness 0.20 mm	12	269			
6 99 02 010 00 0	4014586277578	Steel wire brush, Wire thickness 0.35 mm	12	269			
6 99 02 020 00 0	4014586277677	Contact roller, Ø 16.0 mm, Width 75.0 mm	13	268			
6 99 02 021 00 0	4014586277684	Contact roller, Ø 17.0 mm, Width 75.0 mm	13	268			
6 99 02 022 00 0	4014586277691	Contact roller, Ø 17.2 mm, Width 75.0 mm	13	268			
6 99 02 023 00 0	4014586277707	Contact roller, Ø 18.0 mm, Width 75.0 mm	13	268			
6 99 02 024 00 0	4014586277714	Contact roller, Ø 19.0 mm, Width 75.0 mm	13	268			
6 99 02 025 00 0	4014586277721	Contact roller, Ø 20.0 mm, Width 75.0 mm	13	268			
6 99 02 026 00 0	4014586277738	Contact roller, Ø 21.0 mm, Width 75.0 mm	13	268			
6 99 02 027 00 0	4014586277745	Contact roller, Ø 21.3 mm, Width 75.0 mm	13	268			
6 99 02 028 00 0	4014586277752	Contact roller, Ø 22.0 mm, Width 75.0 mm	13	268			
6 99 02 029 00 0	4014586277769	Contact roller, Ø 22.2 mm, Width 75.0 mm	13	268			
6 99 02 030 00 0	4014586277776	Contact roller, Ø 22.5 mm, Width 75.0 mm	13	268			
6 99 02 031 00 0	4014586277783	Contact roller, Ø 23.0 mm, Width 75.0 mm	13	268			
6 99 02 032 00 0	4014586277790	Contact roller, Ø 23.1 mm, Width 75.0 mm	13	268			
6 99 02 033 00 0	4014586277806	Contact roller, Ø 24.0 mm, Width 75.0 mm	13	268			
6 99 02 034 00 0	4014586277813	Contact roller, Ø 24.5 mm, Width 75.0 mm	13	268			
6 99 02 035 00 0	4014586277820	Contact roller, Ø 25.0 mm, Width 75.0 mm	13	268			

Part number	EAN	Description					
6 99 02 036 00 0	4014586277837	Contact roller, Ø 25.4 mm, Width 75.0 mm	13	268			
6 99 02 037 00 0	4014586277844	Contact roller, Ø 25.9 mm, Width 75.0 mm	13	268			
6 99 02 038 00 0	4014586277851	Contact roller, Ø 26.0 mm, Width 75.0 mm	13	268			
6 99 02 039 00 0	4014586277868	Contact roller, Ø 26.4 mm, Width 75.0 mm	13	268			
6 99 02 040 00 0	4014586277875	Contact roller, Ø 26.9 mm, Width 75.0 mm	13	268			
6 99 02 041 00 0	4014586277882	Contact roller, Ø 27.0 mm, Width 75.0 mm	13	268			
6 99 02 042 00 0	4014586277899	Contact roller, Ø 28.0 mm, Width 75.0 mm	13	268			
6 99 02 043 00 0	4014586277905	Contact roller, Ø 28.6 mm, Width 75.0 mm	13	268			
6 99 02 044 00 0	4014586277912	Contact roller, Ø 28.8 mm, Width 75.0 mm	13	268			
6 99 02 045 00 0	4014586277929	Contact roller, Ø 29.0 mm, Width 75.0 mm	13	268			
6 99 02 046 00 0	4014586277936	Contact roller, Ø 30.0 mm, Width 75.0 mm	13	268			
6 99 02 047 00 0	4014586277943	Contact roller, Ø 31.7 mm, Width 75.0 mm	13	268			
6 99 02 048 00 0	4014586277950	Contact roller, Ø 32.0 mm, Width 75.0 mm	13	268			
6 99 02 049 00 0	4014586277967	Contact roller, Ø 33.0 mm, Width 75.0 mm	13	268			
6 99 02 050 00 0	4014586277974	Contact roller, Ø 33.7 mm, Width 75.0 mm	13	268			
6 99 02 051 00 0	4014586277981	Contact roller, Ø 34.0 mm, Width 75.0 mm	13	268			
6 99 02 052 00 0	4014586277998	Contact roller, Ø 35.0 mm, Width 75.0 mm	13	268			
6 99 02 053 00 0	4014586278001	Contact roller, Ø 36.0 mm, Width 75.0 mm	13	268			
6 99 02 054 00 0	4014586278018	Contact roller, Ø 37.5 mm, Width 75.0 mm	13	268			
6 99 02 055 00 0	4014586278025	Contact roller, Ø 38.0 mm, Width 75.0 mm	13	268			
6 99 02 056 00 0	4014586278032	Contact roller, Ø 38.1 mm, Width 75.0 mm	13	268			
6 99 02 057 00 0	4014586278049	Contact roller, Ø 38.3 mm, Width 75.0 mm	13	268			
6 99 02 058 00 0	4014586278056	Contact roller, Ø 40.0 mm, Width 75.0 mm	13	268			
6 99 02 059 00 0	4014586278063	Contact roller, Ø 41.0 mm, Width 75.0 mm	13	268			
6 99 02 060 00 0	4014586278070	Contact roller, Ø 41.2 mm, Width 75.0 mm	13	268			
6 99 02 061 00 0	4014586278087	Contact roller, Ø 42.0 mm, Width 75.0 mm	13	268			
6 99 02 062 00 0	4014586278094	Contact roller, Ø 42.4 mm, Width 75.0 mm	13	268			
6 99 02 063 00 0 6 99 02 064 00 0	4014586278100	Contact roller, Ø 42.6 mm, Width 75.0 mm Contact roller, Ø 43.0 mm, Width 75.0 mm	13	268 268			
6 99 02 065 00 0	4014586278117 4014586278124	Contact roller, Ø 43.3 mm, Width 75.0 mm	13	268			
6 99 02 066 00 0	4014586278131	Contact roller, Ø 49.9 mm, Width 75.0 mm	13	268			
6 99 02 067 00 0	4014586278148	Contact roller, Ø 44.5 mm, Width 75.0 mm	13	268			
6 99 02 068 00 0	4014586278155	Contact roller, Ø 45.0 mm, Width 75.0 mm	13	268			
6 99 02 069 00 0	4014586278162	Contact roller, Ø 46.0 mm, Width 75.0 mm	13	268			
6 99 02 070 00 0	4014586278179	Contact roller, Ø 48.0 mm, Width 75.0 mm	13	268			
6 99 02 071 00 0	4014586278186	Contact roller, Ø 48.3 mm, Width 75.0 mm	13	268			
6 99 02 072 00 0	4014586278193	Contact roller, Ø 49.0 mm, Width 75.0 mm	13	268			
6 99 02 073 00 0	4014586278209	Contact roller, Ø 50.0 mm, Width 75.0 mm	13	268			
6 99 02 074 00 0	4014586278216	Contact roller, Ø 50.8 mm, Width 75.0 mm	13	268			
6 99 02 075 00 0	4014586278223	Contact roller, Ø 51.0 mm, Width 75.0 mm	13	268			
6 99 02 076 00 0	4014586278230	Contact roller, Ø 53.0 mm, Width 75.0 mm	13	268			
6 99 02 077 00 0	4014586278247	Contact roller, Ø 53.7 mm, Width 75.0 mm	13	268			
6 99 02 078 00 0	4014586278254	Contact roller, Ø 54.0 mm, Width 75.0 mm	13	268			
6 99 02 079 00 0	4014586278261	Contact roller, Ø 55.0 mm, Width 75.0 mm	13	268			
6 99 02 080 00 0	4014586278278	Contact roller, Ø 57.0 mm, Width 75.0 mm	13	268			
6 99 02 081 00 0	4014586278285	Contact roller, Ø 58.0 mm, Width 75.0 mm	13	268			
6 99 02 082 00 0	4014586278292	Contact roller, Ø 59.0 mm, Width 75.0 mm	13	268			
6 99 02 083 00 0	4014586278308	Contact roller, Ø 60.0 mm, Width 75.0 mm	13	268			
6 99 02 084 00 0	4014586278315	Contact roller, Ø 60.3 mm, Width 75.0 mm	13	268			
6 99 02 085 00 0	4014586278322	Contact roller, Ø 63.0 mm, Width 75.0 mm	13	268			
6 99 02 086 00 0	4014586278339	Contact roller, Ø 63.5 mm, Width 75.0 mm	13	268			
6 99 02 087 00 0	4014586278346	Contact roller, Ø 65.0 mm, Width 75.0 mm	13	268			
6 99 02 088 00 0	4014586278353	Contact roller, Ø 67.0 mm, Width 75.0 mm	13	268			
6 99 02 089 00 0	4014586278360	Contact roller, Ø 69.0 mm, Width 75.0 mm	13	268			
6 99 02 090 00 0	4014586278377	Contact roller, Ø 70.0 mm, Width 75.0 mm	13	268			
6 99 02 091 00 0	4014586278384	Contact roller, Ø 73.0 mm, Width 75.0 mm	13	268			
6 99 02 092 00 0	4014586278391	Contact roller, Ø 75.0 mm, Width 75.0 mm	13	268			
6 99 02 093 00 0	4014586278407	Contact roller, Ø 76.0 mm, Width 75.0 mm	13	268			
6 99 02 094 00 0	4014586278414	Contact roller, Ø 76.1 mm, Width 75.0 mm	13	268			
6 99 02 095 00 0	4014586278421	Contact roller, Ø 76.2 mm, Width 75.0 mm	13	268			

Part number	EAN	Description					
6 99 02 096 00 0	4014586278438	Contact roller, Ø 80.0 mm, Width 75.0 mm	13	268			
6 99 02 097 00 0	4014586278445	Contact roller, Ø 82.5 mm, Width 75.0 mm	13	268			
6 99 02 098 00 0	4014586278452	Contact roller, Ø 88.9 mm, Width 75.0 mm	13	268			
6 99 02 099 00 0	4014586278469	Contact roller, Ø 90.0 mm, Width 75.0 mm	13	268			
6 99 02 100 00 0	4014586278476	Grinding/cooling emulsion	13	269			
6 99 02 101 00 0	4014586283098	Contact roller, Ø 20.0 mm, Width 150.0 mm	13	270			
6 99 02 102 00 0	4014586283104	Contact roller, Ø 22.0 mm, Width 150.0 mm	13	270			
6 99 02 103 00 0	4014586283111	Contact roller, Ø 25.0 mm, Width 150.0 mm	13	270			
6 99 02 104 00 0	4014586283128	Contact roller, Ø 25.4 mm, Width 150.0 mm	13	270			
6 99 02 105 00 0	4014586283135	Contact roller, Ø 26.9 mm, Width 150.0 mm	13	270			
6 99 02 106 00 0	4014586283142	Contact roller, Ø 28.0 mm, Width 150.0 mm	13	270			
6 99 02 107 00 0	4014586283159	Contact roller, Ø 30.0 mm, Width 150.0 mm	13	270			
6 99 02 108 00 0	4014586283166	Contact roller, Ø 32.0 mm, Width 150.0 mm	13	270			
6 99 02 109 00 0	4014586283173	Contact roller, Ø 33.7 mm, Width 150.0 mm	13	270			
6 99 02 110 00 0	4014586283180	Contact roller, Ø 35.0 mm, Width 150.0 mm	13	270			
6 99 02 111 00 0	4014586283197	Contact roller, Ø 38.0 mm, Width 150.0 mm	13	270			
6 99 02 112 00 0	4014586283203	Contact roller, Ø 38.1 mm, Width 150.0 mm	13	270			
6 99 02 113 00 0	4014586283210	Contact roller, Ø 38.3 mm, Width 150.0 mm	13	270			
6 99 02 114 00 0	4014586283227	Contact roller, Ø 40.0 mm, Width 150.0 mm	13	270			
6 99 02 115 00 0	4014586283234	Contact roller, Ø 42.4 mm, Width 150.0 mm	13	270			
6 99 02 116 00 0	4014586283241	Contact roller, Ø 44.5 mm, Width 150.0 mm	13	270			
6 99 02 117 00 0	4014586283258	Contact roller, Ø 48.3 mm, Width 150.0 mm	13	270			
6 99 02 118 00 0	4014586283265	Contact roller, Ø 50.0 mm, Width 150.0 mm	13	270			
6 99 02 119 00 0	4014586283272	Contact roller, Ø 50.8 mm, Width 150.0 mm	13	270			
6 99 02 120 00 0	4014586283289	Contact roller, Ø 60.0 mm, Width 150.0 mm	13	270			
6 99 02 121 00 0	4014586283296	Contact roller, Ø 60.3 mm, Width 150.0 mm	13	270			
6 99 02 122 00 0	4014586283302	Contact roller, Ø 63.5 mm, Width 150.0 mm	13	270			
6 99 02 123 00 0	4014586283319	Contact roller, Ø 69.0 mm, Width 150.0 mm	13	270			
6 99 02 125 00 0	4014586283333	Contact roller, Ø 76.2 mm, Width 150.0 mm	13	271			
6 99 02 126 00 0	4014586283340	Contact roller, Ø 84.0 mm, Width 150.0 mm	13	271			
6 99 02 127 00 0	4014586283357	Contact roller, Ø 88.9 mm, Width 150.0 mm	13	271			
6 99 02 128 00 0	4014586283364	Contact roller, Ø 101.6 mm, Width 150.0 mm	13	271			
6 99 02 129 00 0	4014586283371	Contact roller, Ø 104.0 mm, Width 150.0 mm	13	271			
6 99 02 130 00 0	4014586283388	Contact roller, Ø 108.0 mm, Width 150.0 mm	13	271			
6 99 02 131 00 0 6 99 02 132 00 0	4014586283395	Contact roller, Ø 114.3 mm, Width 150.0 mm	13	271 271			
6 99 02 133 00 0	4014586283401 4014586283418	Contact roller, Ø 133.0 mm, Width 150.0 mm Contact roller, Ø 139.7 mm, Width 150.0 mm	13	271			
6 99 02 134 00 0	4014586283415	Contact roller, Ø 159.7 mm, Width 150.0 mm	13	271			
6 99 02 155 00 0	4014586284835	Contact roller, Ø 152.4 mm, Width 150.0 mm	13	271			
6 99 02 176 00 0	4014586285528	Swivel joint GIT	13	273			
6 99 02 179 60 0	4014586349381	Pipe support	13	269			
6 99 02 180 60 0	4014586351193	Pipe support, max. pipe length 1,000 mm	13	269			
6 99 02 181 60 0	4014586351209	Pipe support, max. pipe length 1,500 mm	13	269			
6 99 02 182 00 0	4014586285580	Adaptor	13	271			
6 99 02 183 00 0	4014586285597	Plugbox 2 x 7 poles	13	273			
6 99 02 188 00 0	4014586290683	Contact roller, Ø 16.0 mm, Width 150.0 mm	13	270			
6 99 02 189 00 0	4014586290706	Contact roller, Ø 18.0 mm, Width 150.0 mm	13	270			
6 99 02 190 00 0	4014586290713	Contact roller, Ø 19.0 mm, Width 150.0 mm	13	270			
6 99 02 191 00 0	4014586290720	Contact roller, Ø 19.1 mm, Width 150.0 mm	13	270			
6 99 02 192 00 0	4014586290737	Contact roller, Ø 21.0 mm, Width 150.0 mm	13	270			
6 99 02 193 00 0	4014586290744	Contact roller, Ø 21.3 mm, Width 150.0 mm	13	270			
6 99 02 194 00 0	4014586290751	Contact roller, Ø 22.3 mm, Width 150.0 mm	13	270			
6 99 02 195 00 0	4014586290768	Contact roller, Ø 23.0 mm, Width 150.0 mm	13	270			
6 99 02 196 00 0	4014586290775	Contact roller, Ø 23.2 mm, Width 150.0 mm	13	270			
6 99 02 197 00 0	4014586290782	Contact roller, Ø 24.3 mm, Width 150.0 mm	13	270			
6 99 02 198 00 0	4014586290799	Contact roller, Ø 26.1 mm, Width 150.0 mm	13	270			
6 99 02 199 00 0	4014586290805	Contact roller, Ø 26.7 mm, Width 150.0 mm	13	270			
6 99 02 200 00 0	4014586290812	Contact roller, Ø 27.0 mm, Width 150.0 mm	13	270			
6 99 02 201 00 0	4014586290829	Contact roller, Ø 28.3 mm, Width 150.0 mm	13	270			
6 99 02 202 00 0	4014586290836	Contact roller, Ø 28.6 mm, Width 150.0 mm	13	270			

Part number	EAN	Description					
6 99 02 203 00 0	4014586290843	Contact roller, Ø 29.2 mm, Width 150.0 mm	13	270			
6 99 02 204 00 0	4014586290850	Contact roller, Ø 31.1 mm, Width 150.0 mm	13	270			
6 99 02 205 00 0	4014586290867	Contact roller, Ø 31.5 mm, Width 150.0 mm	13	270			
6 99 02 206 00 0	4014586290874	Contact roller, Ø 31.8 mm, Width 150.0 mm	13	270			
6 99 02 207 00 0	4014586290881	Contact roller, Ø 33.0 mm, Width 150.0 mm	13	270			
6 99 02 208 00 0	4014586290898	Contact roller, Ø 33.4 mm, Width 150.0 mm	13	270			
6 99 02 209 00 0	4014586290904	Contact roller, Ø 34.0 mm, Width 150.0 mm	13	270			
6 99 02 210 00 0	4014586290911	Contact roller, Ø 37.4 mm, Width 150.0 mm	13	270			
6 99 02 211 00 0	4014586290928	Contact roller, Ø 39.8 mm, Width 150.0 mm	13	270			
6 99 02 212 00 0	4014586290935	Contact roller, Ø 40.1 mm, Width 150.0 mm	13	270			
6 99 02 213 00 0	4014586290942	Contact roller, Ø 41.3 mm, Width 150.0 mm	13	270			
6 99 02 214 00 0	4014586290959	Contact roller, Ø 42.0 mm, Width 150.0 mm	13	270			
6 99 02 215 00 0	4014586290966	Contact roller, Ø 42.1 mm, Width 150.0 mm	13	270			
6 99 02 216 00 0	4014586290973	Contact roller, Ø 42.2 mm, Width 150.0 mm	13	270			
6 99 02 217 00 0	4014586290980	Contact roller, Ø 43.0 mm, Width 150.0 mm	13	270			
6 99 02 218 00 0	4014586290997	Contact roller, Ø 45.0 mm, Width 150.0 mm	13	270			
6 99 02 219 00 0	4014586291000	Contact roller, Ø 45.7 mm, Width 150.0 mm	13	270			
6 99 02 221 00 0	4014586291024	Contact roller, Ø 47.4 mm, Width 150.0 mm	13	270			
6 99 02 222 00 0	4014586291031	Contact roller, Ø 48.0 mm, Width 150.0 mm	13	270			
6 99 02 223 00 0	4014586291048	Contact roller, Ø 49.0 mm, Width 150.0 mm	13	270			
6 99 02 224 00 0	4014586291055	Contact roller, Ø 50.1 mm, Width 150.0 mm	13	270			
6 99 02 225 00 0	4014586291062	Contact roller, Ø 51.0 mm, Width 150.0 mm	13	270			
6 99 02 226 00 0	4014586291086	Contact roller, Ø 53.0 mm, Width 150.0 mm	13	270			
6 99 02 227 00 0	4014586291093	Contact roller, Ø 93.2 mm, Width 150.0 mm	13	271			
6 99 02 228 00 0	4014586291109	Contact roller, Ø 107.0 mm, Width 150.0 mm	13	271			
6 99 02 229 00 0	4014586291116	Contact roller, Ø 54.0 mm, Width 150.0 mm	13	270			
6 99 02 230 00 0	4014586291123	Contact roller, Ø 55.0 mm, Width 150.0 mm	13	270			
6 99 02 231 00 0	4014586291130	Contact roller, Ø 57.0 mm, Width 150.0 mm	13	270			
6 99 02 232 00 0	4014586291147	Contact roller, Ø 57.8 mm, Width 150.0 mm	13	270			
6 99 02 233 00 0	4014586291154	Contact roller, Ø 58.0 mm, Width 150.0 mm	13	270			
6 99 02 234 00 0	4014586291161	Contact roller, Ø 59.5 mm, Width 150.0 mm	13	270			
6 99 02 235 00 0 6 99 02 236 00 0	4014586291178	Contact roller, Ø 62.0 mm, Width 150.0 mm	13	270			
	4014586291185	Contact roller, Ø 63.0 mm, Width 150.0 mm	13	270			
6 99 02 237 00 0 6 99 02 238 00 0	4014586291192 4014586291208	Contact roller, Ø 64.2 mm, Width 150.0 mm Contact roller, Ø 65.0 mm, Width 150.0 mm	13	270			
6 99 02 239 00 0	4014586291208	Contact roller, Ø 65.0 mm, Width 150.0 mm	13	270			
6 99 02 240 00 0	4014586291222	Contact roller, Ø 66.3 mm, Width 150.0 mm	13	270			
6 99 02 241 00 0	4014586291239	Contact roller, Ø 66.7 mm, Width 150.0 mm	13	270			
6 99 02 242 00 0	4014586291246	Contact roller, Ø 67.1 mm, Width 150.0 mm	13	270			
6 99 02 243 00 0	4014586291253	Contact roller, Ø 69.9 mm, Width 150.0 mm	13	270			
6 99 02 244 00 0	4014586291260	Contact roller, Ø 70.0 mm, Width 150.0 mm	13	271			
6 99 02 245 00 0	4014586291277	Contact roller, Ø 73.0 mm, Width 150.0 mm	13	271			
6 99 02 246 00 0	4014586291284	Contact roller, Ø 73.8 mm, Width 150.0 mm	13	271			
6 99 02 247 00 0	4014586291291	Contact roller, Ø 75.0 mm, Width 150.0 mm	13	271			
6 99 02 248 00 0	4014586291307	Contact roller, Ø 75.1 mm, Width 150.0 mm	13	271			
6 99 02 249 00 0	4014586291314	Contact roller, Ø 76.0 mm, Width 150.0 mm	13	271			
6 99 02 250 00 0	4014586291321	Contact roller, Ø 78.0 mm, Width 150.0 mm	13	271			
6 99 02 251 00 0	4014586291338	Contact roller, Ø 79.4 mm, Width 150.0 mm	13	271			
6 99 02 252 00 0	4014586291345	Contact roller, Ø 79.8 mm, Width 150.0 mm	13	271			
6 99 02 253 00 0	4014586291352	Contact roller, Ø 80.0 mm, Width 150.0 mm	13	271			
6 99 02 254 00 0	4014586291369	Contact roller, Ø 80.2 mm, Width 150.0 mm	13	271			
6 99 02 255 00 0	4014586291376	Contact roller, Ø 81.0 mm, Width 150.0 mm	13	271			
6 99 02 256 00 0	4014586291383	Contact roller, Ø 82.0 mm, Width 150.0 mm	13	271			
6 99 02 257 00 0	4014586291390	Contact roller, Ø 82.1 mm, Width 150.0 mm	13	271			
6 99 02 258 00 0	4014586291406	Contact roller, Ø 82.5 mm, Width 150.0 mm	13	271			
6 99 02 259 00 0	4014586291413	Contact roller, Ø 83.0 mm, Width 150.0 mm	13	271			
6 99 02 260 00 0	4014586291420	Contact roller, Ø 84.1 mm, Width 150.0 mm	13	271			
6 99 02 261 00 0	4014586291437	Contact roller, Ø 85.0 mm, Width 150.0 mm	13	271			
6 99 02 262 00 0	4014586291444	Contact roller, Ø 86.7 mm, Width 150.0 mm	13	271			
6 99 02 263 00 0	4014586291451	Contact roller, Ø 87.0 mm, Width 150.0 mm	13	271			

Part number	EAN	Description	PC	Page
6 99 02 264 00 0	4014586291468	Contact roller, Ø 88.0 mm, Width 150.0 mm	13	271
6 99 02 265 00 0	4014586291475	Contact roller, Ø 89.0 mm, Width 150.0 mm	13	271
6 99 02 266 00 0	4014586291482	Contact roller, Ø 89.3 mm, Width 150.0 mm	13	271
6 99 02 267 00 0	4014586291499	Contact roller, Ø 89.9 mm, Width 150.0 mm	13	271
6 99 02 268 00 0	4014586291505	Contact roller, Ø 90.0 mm, Width 150.0 mm	13	271
6 99 02 269 00 0	4014586291512	Contact roller, Ø 92.0 mm, Width 150.0 mm	13	271
6 99 02 271 00 0	4014586291543	Contact roller, Ø 100.0 mm, Width 150.0 mm	13	271
6 99 02 272 00 0	4014586291635	Contact roller, Ø 100.5 mm, Width 150.0 mm	13	271
6 99 02 273 00 0	4014586291642	Contact roller, Ø 101.0 mm, Width 150.0 mm	13	271
6 99 02 274 00 0	4014586291659	Contact roller, Ø 101.3 mm, Width 150.0 mm	13	271
6 99 02 275 00 0	4014586291987	Contact roller, Ø 102.0 mm, Width 150.0 mm	13	271
6 99 02 276 00 0	4014586291994	Contact roller, Ø 102.5 mm, Width 150.0 mm	13	271
6 99 02 277 00 0	4014586292007	Contact roller, Ø 102.6 mm, Width 150.0 mm	13	271
6 99 02 278 00 0	4014586292014	Contact roller, Ø 105.0 mm, Width 150.0 mm	13	271
6 99 02 279 00 0	4014586292021	Contact roller, Ø 106.7 mm, Width 150.0 mm	13	271
6 99 02 281 00 0	4014586292045	Contact roller, Ø 110.0 mm, Width 150.0 mm	13	271
6 99 02 282 00 0	4014586292052	Contact roller, Ø 114.0 mm, Width 150.0 mm	13	271
6 99 02 283 00 0	4014586292069	Contact roller, Ø 115.0 mm, Width 150.0 mm	13	271
6 99 02 284 00 0	4014586292076	Contact roller, Ø 117.0 mm, Width 150.0 mm	13	271
6 99 02 285 00 0	4014586292083	Contact roller, Ø 118.0 mm, Width 150.0 mm	13	271
6 99 02 286 00 0	4014586292090	Contact roller, Ø 118.2 mm, Width 150.0 mm	13	271
6 99 02 287 00 0	4014586292106	Contact roller, Ø 120.0 mm, Width 150.0 mm	13	271
6 99 02 288 00 0	4014586292113	Contact roller, Ø 121.0 mm, Width 150.0 mm	13	271
6 99 02 289 00 0	4014586293080	Contact roller, Ø 122.0 mm, Width 150.0 mm	13	271
6 99 02 290 00 0	4014586292120	Contact roller, Ø 124.0 mm, Width 150.0 mm	13	271
6 99 02 291 00 0	4014586292137	Contact roller, Ø 125.0 mm, Width 150.0 mm	13	271
6 99 02 292 00 0	4014586292144	Contact roller, Ø 127.0 mm, Width 150.0 mm	13	271
6 99 02 293 00 0	4014586292151	Contact roller, Ø 127.5 mm, Width 150.0 mm	13	271
6 99 02 294 00 0	4014586292168 4014586292175	Contact roller, Ø 128.0 mm, Width 150.0 mm Contact roller, Ø 129.0 mm, Width 150.0 mm	13 13	271
6 99 02 296 00 0	4014586292173	Contact roller, Ø 129.0 mm, Width 150.0 mm	13	271
6 99 02 297 00 0	4014586292199	Contact roller, Ø 135.0 mm, Width 150.0 mm	13	271
6 99 02 298 00 0	4014586292205	Contact roller, Ø 138.0 mm, Width 150.0 mm	13	271
6 99 02 299 00 0	4014586292212	Contact roller, Ø 139.0 mm, Width 150.0 mm	13	271
6 99 02 300 00 0	4014586292229	Contact roller, Ø 140.0 mm, Width 150.0 mm	13	271
6 99 02 301 00 0	4014586292236	Contact roller, Ø 141.3 mm, Width 150.0 mm	13	271
6 99 02 302 00 0	4014586292243	Contact roller, Ø 141.9 mm, Width 150.0 mm	13	271
6 99 02 303 00 0	4014586292250	Contact roller, Ø 144.2 mm, Width 150.0 mm	13	271
6 99 02 304 00 0	4014586292267	Contact roller, Ø 15.0 mm, Width 75.0 mm	13	268
6 99 02 305 00 0	4014586292274	Contact roller, Ø 150.0 mm, Width 150.0 mm	13	271
6 99 02 306 00 0	4014586292281	Contact roller, Ø 152.0 mm, Width 150.0 mm	13	271
6 99 02 308 00 0	4014586292304	Contact roller, Ø 154.0 mm, Width 150.0 mm	13	271
6 99 02 309 00 0	4014586292311	Contact roller, Ø 159.0 mm, Width 150.0 mm	13	271
6 99 02 310 00 0	4014586292328	Contact roller, Ø 160.0 mm, Width 150.0 mm	13	271
6 99 02 311 00 0	4014586292335	Contact roller, Ø 163.0 mm, Width 150.0 mm	13	271
6 99 02 312 00 0	4014586292342	Contact roller, Ø 165.0 mm, Width 150.0 mm	13	271
6 99 02 313 00 0	4014586292359	Contact roller, Ø 165.1 mm, Width 150.0 mm	13	271
6 99 02 314 00 0	4014586292366	Contact roller, Ø 168.0 mm, Width 150.0 mm	13	271
6 99 02 315 00 0	4014586292373	Contact roller, Ø 172.2 mm, Width 150.0 mm	13	_
6 99 02 316 00 0	4014586292380	Contact roller, Ø 180.0 mm, Width 150.0 mm	13	-
6 99 02 317 00 0	4014586292397	Contact roller, Ø 188.4 mm, Width 150.0 mm	13	_
6 99 02 318 00 0	4014586292403	Contact roller, Ø 190.0 mm, Width 150.0 mm	13	
6 99 02 319 00 0	4014586292410	Contact roller, Ø 195.0 mm, Width 150.0 mm	13	_
6 99 02 320 00 0	4014586292427	Contact roller, Ø 202.0 mm, Width 150.0 mm	13	
6 99 02 321 00 0	4014586292533	Contact roller, Ø 215.0 mm, Width 150.0 mm	13	
6 99 02 322 00 0	4014586292540	Contact roller, Ø 219.0 mm, Width 150.0 mm	13	
6 99 02 323 00 0	4014586292557	Contact roller, Ø 31.0 mm, Width 75.0 mm	13	268
6 99 02 324 00 0	4014586292564	Contact roller, Ø 57.5 mm, Width 75.0 mm	13	268
6 99 02 326 00 0	4014586292588	Contact roller, Ø 68.0 mm, Width 75.0 mm	13	268
6 99 02 327 00 0	4014586292595	Contact roller, Ø 84.0 mm, Width 75.0 mm	13	268

Part number	EAN	Description	PC	Page
			13	
6 99 02 332 00 0 6 99 02 338 00 0	4014586295435 4014586299488	Contact roller, Ø 68.9 mm, Width 150.0 mm	13	270 267
6 99 02 343 00 0	4014586349398	Stainless steel sanding support Spark box	13	267
6 99 02 344 00 0	4014586349404	Stainless steel sanding support	13	269
6 99 02 410 00 0	4014586299310	Drive wheel puller	07	273
6 99 03 000 00 0	4014586278483	Grinding material R, Grain 24, No. in pack 10 pcs	12	266
6 99 03 002 00 0	4014586278506	Grinding material R, Grain 36, No. in pack 10 pcs	12	266
6 99 03 003 00 0	4014586278513	Grinding material Z, Grain 36, No. in pack 10 pcs	12	266
6 99 03 004 00 0	4014586278520	Grinding material R, Grain 40, No. in pack 10 pcs	12	266
6 99 03 005 00 0	4014586278537	Grinding material Z, Grain 40, No. in pack 10 pcs	12	266
6 99 03 007 00 0	4014586278551	Grinding material R, Grain 60, No. in pack 10 pcs	12	266
6 99 03 008 00 0	4014586278568	Grinding material Z, Grain 60, No. in pack 10 pcs	12	266
6 99 03 009 00 0	4014586278575	Grinding material R, Grain 80, No. in pack 10 pcs	12	266
6 99 03 010 00 0	4014586278582	Grinding material Z, Grain 80, No. in pack 10 pcs	12	266
6 99 03 013 00 0	4014586278612	Grinding material R, Grain 120, No. in pack 10 pcs	12	266
6 99 03 014 00 0	4014586278629	Grinding material Z, Grain 120, No. in pack 10 pcs	12	266
6 99 03 017 00 0	4014586278650	Grinding material A, Grain 220, No. in pack 10 pcs	12	267
6 99 03 018 00 0	4014586278667	Grinding material A, Grain 320, No. in pack 10 pcs	12	267
6 99 03 019 00 0	4014586278674	Grinding material A, Grain 400, No. in pack 10 pcs	12	267
6 99 03 020 00 0	4014586278681	Grinding material R, Grain 36, No. in pack 10 pcs	12	266
6 99 03 021 00 0	4014586278698	Grinding material Z, Grain 36, No. in pack 10 pcs	12	266
6 99 03 034 00 0	4014586283616	Grinding material Z, Grain 36, No. in pack 10 pcs	12	267
6 99 03 035 00 0	4014586283623	Grinding material Z, Grain 40, No. in pack 10 pcs	12	267
6 99 03 036 00 0	4014586283630	Grinding material Z, Grain 60, No. in pack 10 pcs	12	267
6 99 03 037 00 0	4014586283647	Grinding material Z, Grain 80, No. in pack 10 pcs	12	267
6 99 03 038 00 0	4014586283654	Grinding material Z, Grain 120, No. in pack 10 pcs	12	267
6 99 03 039 00 0	4014586283661	Grinding material R, Grain 24, No. in pack 10 pcs	12	266
6 99 03 040 00 0	4014586283678	Grinding material R, Grain 36, No. in pack 10 pcs	12	266
6 99 03 041 00 0	4014586283685	Grinding material Z, Grain 36, No. in pack 10 pcs	12	267
6 99 03 042 00 0	4014586283692	Grinding material R, Grain 40, No. in pack 10 pcs	12	266
6 99 03 043 00 0	4014586283708	Grinding material Z, Grain 40, No. in pack 10 pcs	12	267
6 99 03 044 00 0	4014586283715	Grinding material R, Grain 60, No. in pack 10 pcs	12	266
6 99 03 045 00 0	4014586283722	Grinding material Z, Grain 60, No. in pack 10 pcs	12	267
6 99 03 046 00 0	4014586283739	Grinding material R, Grain 80, No. in pack 10 pcs	12	266
6 99 03 047 00 0	4014586283746	Grinding material Z, Grain 80, No. in pack 10 pcs	12	267
6 99 03 048 00 0	4014586283753	Grinding material R, Grain 120, No. in pack 10 pcs	12	266
6 99 03 049 00 0	4014586283760	Grinding material Z, Grain 120, No. in pack 10 pcs	12	267
6 99 03 050 00 0	4014586283777	Grinding material A, Grain 220, No. in pack 10 pcs	12	267
6 99 03 051 00 0	4014586283784	Grinding material A, Grain 320, No. in pack 10 pcs	12	267
6 99 03 052 00 0	4014586283791	Grinding material A, Grain 400, No. in pack 10 pcs	12	267
6 99 03 053 00 0	4014586283807	Grinding material R, Grain 36, No. in pack 10 pcs	12	266
6 99 03 054 00 0	4014586283814	Grinding material Z, Grain 36, No. in pack 10 pcs	12	267
6 99 03 097 00 0	4014586292915	Grinding material R, Grain 36, No. in pack 10 pcs	12	-
6 99 03 098 00 0	4014586292922	Grinding material R, Grain 60, No. in pack 10 pcs	12	-
6 99 03 099 00 0	4014586292939	Grinding material R, Grain 80, No. in pack 10 pcs	12	-
6 99 03 111 00 0	4014586299235	Grinding material R, Grain 36, No. in pack 10 pcs	12	266
6 99 03 112 00 0	4014586299242	Grinding material Z, Grain 36, No. in pack 10 pcs	12	267
6 99 03 116 01 0	4014586329888	Fleece belt, Model coarse, No. in pack 3 pcs	12	267
6 99 03 117 01 0	4014586329895	Fleece belt, Model coarse, No. in pack 3 pcs	12	267
6 99 03 118 01 0	4014586329901	Fleece belt, Model medium, No. in pack 3 pcs	12	267
6 99 03 119 01 0	4014586329918	Fleece belt, Model medium, No. in pack 3 pcs	12	267
6 99 03 120 01 0	4014586329925	Fleece belt, Model very fine, No. in pack 3 pcs	12	267
6 99 03 121 01 0	4014586329932	Fleece belt, Model very fine, No. in pack 3 pcs	12	267
6 99 03 122 00 0	4014586368054	Grinding material R, Grain 36, No. in pack 10 pcs	12	266
6 99 03 126 00 0	4014586379029	3M™ Cubitron™ II, Grain 36, No. in pack 10 pcs	12	252
6 99 03 127 00 0	4014586379036	3M™ Cubitron™ II, Grain 60, No. in pack 10 pcs	12	252
6 99 03 128 00 0	4014586379043	3M™ Cubitron™ II, Grain 80, No. in pack 10 pcs	12	252
6 99 03 130 00 0	4014586379050	Grinding material Z, Grain 36, No. in pack 10 pcs	12	252
6 99 03 131 00 0	4014586379067	Grinding material Z, Grain 60, No. in pack 10 pcs	12	252
6 99 03 132 00 0	4014586379074	Grinding material Z, Grain 80, No. in pack 10 pcs	12	252

Part number	EAN	Description	PC	Page
6 99 03 133 00 0	4014586379081	Grinding material Z, Grain 120, No. in pack 10 pcs	12	252
6 99 03 134 00 0	4014586379098	Grinding material A, Grain 220, No. in pack 10 pcs	12	252
6 99 03 135 00 0	4014586379104	Grinding material A, Grain 320, No. in pack 10 pcs	12	252
6 99 03 136 00 0	4014586379111	Grinding material A, Grain 420, No. in pack 10 pcs	12	252
6 99 03 137 00 0	4014586379128	Grinding material R, Grain 36, No. in pack 10 pcs	12	252
6 99 03 138 00 0	4014586379135	Grinding material R, Grain 60, No. in pack 10 pcs	12	252
6 99 03 139 00 0	4014586379142	Grinding material R, Grain 80, No. in pack 10 pcs	12	252
6 99 03 140 00 0	4014586379159	Grinding material R, Grain 120, No. in pack 10 pcs	12	252
6 99 03 143 00 0	4014586379173	Fleece belt, Model medium, No. in pack 3 pcs	12	252
6 99 03 149 00 0	4014586385938	3M™ Cubitron™ II, Grain 60, No. in pack 10 pcs	12	266
6 99 03 150 00 0	4014586385945	3M™ Cubitron™ II, Grain 80, No. in pack 10 pcs	12	266
6 99 03 154 00 0	4014586385983	3M™ Cubitron™ II, Grain 36, No. in pack 10 pcs	12	266
6 99 03 155 00 0	4014586385990	3M™ Cubitron™ II, Grain 60, No. in pack 10 pcs	12	266
6 99 03 157 00 0	4014586405063	3M™ Cubitron™ II, Grain 36, No. in pack 10 pcs	12	252
6 99 03 158 00 0	4014586405070	Grinding material R, Grain 36, No. in pack 10 pcs	12	252
6 99 03 159 00 0	4014586405087	Grinding material Z, Grain 36, No. in pack 10 pcs	12	252
9 01 02 014 01 0	4014586882703	Angled head Basic, Tool Holder 1/4" Outer square	05	_
9 01 02 015 02 0	4014586882802	Angled head up to 45 Nm, Tool Holder 3/8" Outer square	05	96
9 01 02 016 02 0	4014586882826	Angled head up to 60 Nm, Tool Holder 1/2" Outer square	05	96
9 01 02 017 02 0	4014586887784	Angled head up to 18 Nm, Tool Holder 3/8" Outer square	05	96
9 01 02 018 02 0	4014586889290	Angled head up to 14 Nm, Tool Holder 3/8" Outer square	05	95
9 01 02 019 02 0	4014586889306	Angled head up to 14 Nm, Tool Holder 1/4" Outer square	05	96
9 01 02 020 02 0	4014586889313	Angled head up to 14 Nm, Tool Holder 1/4" hexagon socket	05	96
9 01 02 021 02 0	4014586889320	Angled head up to 14 Nm, Tool Holder QuickIN 1/4" Hexagon socket	05	96
9 01 04 009 01 0	4014586871622	M55 X magazine	01	
9 01 04 010 01 0	4014586871639	M55 X magazine extension with belt guide	02	
9 01 06 001 02 0	4014586886930	Straight output, Tool Holder QuickIN 1/4" Hexagon socket	05	96
9 01 06 002 02 0	4014586886626	Straight output, Tool Holder 3/8" Outer square	05	96
9 06 04 008 01 3	4014586849805	Protective suction hood	02	
9 06 04 009 01 7	4014586849829	Protective suction hood	02	
9 06 06 002 00 9	4014586834467	Saw blade guide	02	176
9 07 01 003 01 0	4014586896496	Fein Vice (VersaMAG)	02	191
9 07 01 005 02 0	4014586898278	Welding plate, diameter 16 mm (Fein VersaMAG)	02	191
9 07 02 001 00 1	4014586834498	Clamping fixture	02	176
9 07 02 003 00 8	4014586834511	Clamping fixture	02	176
9 07 02 004 00 6	4014586834528	Clamping fixture	02	176
9 07 02 005 00 0	4014586839783	FEIN clamp and feed device	02	176
9 12 01 002 00 4	4014586842868	Compressed air cooling lubrication	08	
9 26 01 022 01 3	4014586846965	Vacuum pump	02	32
9 26 01 023 02 3	4014586847283	Compressor	08	
9 26 02 054 01 6	4014586841342	Suction plate	02	33
9 26 02 055 01 0	4014586841335	Pipe drilling device	02	33
9 26 02 057 01 7	4014586843322	Vacuum plate	02	32
9 26 02 071 01 9	4014586851389	Profile set 160	01	158
9 26 02 075 01 8	4014586855097	Device for dust extract	04	
9 26 02 079 01 0	4014586857152	Size 2 tapping quick-change chuck with QuickIN fitting	02	60
9 26 02 082 01 0	4014586861920	Size 3 tapping quick-change chuck with QuickIN MAX/Weldon 32 fitting	02	61
9 26 02 083 01 0	4014586860152	Table-top and drill jigs support	04	229
9 26 02 085 01 0	4014586867977	Vacuum plate	02	62
9 26 02 089 01 0	4014586878508	Size 2 tapping quick-change chuck with 3/4" Weldon fitting	02	60
9 26 02 091 00 0	4014586882932	Dust extraction set	04	
9 26 02 092 00 0	4014586882949	Dust extraction set	04	
9 26 02 095 00 0	4014586885551	Dust extraction set	04	
9 26 02 101 01 0	4014586889771	Drilling dust nozzle	02	77
9 26 02 102 00 0	4014586892283	Dust extraction set	04	229
9 26 04 096 01 0	4014586863986	Quick charger ALG 30	02	
9 26 04 096 03 0	4014586887128	Quick charger ALG 30, No. in pack 25 pcs	02	
9 26 04 103 01 0	4014586862651	Charging adapter	02	
9 26 04 163 02 0	4014586872681	Programming adapter	02	96
9 26 04 170 02 0	4014586882727	Battery pack, Current/Voltages 14.4 V, Capacity 2.5 Ah	02	
9 26 04 172 02 0	4014586882741	Battery pack, Current/Voltages 14.4 V, Capacity 5 Ah	02	
3 2 3 3 1 1 / 2 0 2 0	.51.500002/71	Tanana parama tanagas I i, supudity a / iii		

Part number	EAN	Description				
9 26 04 175 02 0	4014586890586	Battery pack, Current/Voltages 18 V, Capacity 6 Ah				
9 26 04 175 03 0	4014586890593	Battery pack, Current/Voltages 18 V, Capacity 6 Ah, No. in pack 12 pcs	02			
9 26 04 179 02 0	4014586888224	HighPower battery pack, Current/Voltages 18 V, Capacity 5.2 Ah	02	289		
9 26 04 180 01 0	4014586890630	Quick charger ALG 80	02	289		
9 26 04 180 02 0	4014586892047	Quick charger ALG 80, No. in pack 25 pcs	02	289		
9 26 04 182 02 0	4014586890609	Battery pack, Current/Voltages 18 V, Capacity 3 Ah	02	289		
9 26 04 182 03 0	4014586890616	Battery pack, Current/Voltages 18 V, Capacity 3 Ah, No. in pack 12 pcs	02	289		
9 26 04 183 02 0	4014586891262	Battery pack, Current/Voltages 12 V, Capacity 3 Ah	02	_		
9 26 04 184 02 0	4014586890623	Battery pack, Current/Voltages 12 V, Capacity 6 Ah	02	_		
9 26 04 210 01 0	4014586893921	Quick charger ALG 80 BC	02	_		
9 26 04 228 01 0	4014586895604	ProCORE 18 V 4.0 Ah AS battery starter set, Current/Voltages 18 V, Capacity 4 Ah	02	276		
9 26 04 229 01 0	4014586895611	ProCORE 18 V 8.0 Ah AS battery starter set, Current/Voltages 18 V, Capacity 8 Ah	02	276		
9 26 04 241 01 0	4014586895628	ProCORE 18 V 12.0 Ah AS battery starter set, Current/Voltages 18 V, Capacity 12 Ah	02	276		
9 26 04 244 01 0	4014586895635	GBA 18 V 2.0 Ah AS battery starter set, Current/Voltages 18 V, Capacity 2 Ah	02	276		
9 26 04 246 01 0	4014586895642	GBA 18 V 5.0 Ah AS battery starter set, Current/Voltages 18 V, Capacity 5 Ah		276		
9 26 04 314 01 0	4014586891026	Battery starter set, Current/Voltages 18 V, Capacity 6 Ah	02	289		
9 26 04 315 01 0	4014586891071	Battery starter set, Current/Voltages 18 V, Capacity 3 Ah	02	289		
9 26 04 323 01 0	4014586892788	Battery starter set, Current/Voltages 18 V, Capacity 6 Ah	02	_		
9 26 04 324 01 0	4014586892849	Battery starter set, Current/Voltages 18 V, Capacity 3 Ah	02	_		
9 26 04 325 01 0	4014586892900	HighPower battery starter set, Current/Voltages 18 V, Capacity 5.2 Ah	02	_		
9 26 04 326 01 0	4014586892542	Battery starter set, Current/Voltages 12 V, Capacity 3 Ah	02	_		
9 26 04 327 01 0	4014586892603	Battery starter set, Current/Voltages 12 V, Capacity 6 Ah	02	_		
9 26 04 335 01 0	4014586896212	GAL 1880 CV AS rapid charger	02	277		
9 26 04 339 01 0	4014586896861	GAL 18 V-160 AS rapid charger	02	277		
9 26 04 341 02 0	4014586896229	ProCORE 18 V 4.0 Ah AS battery pack, Current/Voltages 18 V, Capacity 4 Ah	02	276		
9 26 04 342 02 0	4014586896908	ProCORE 18 V 8.0 Ah AS battery pack, Current/Voltages 18 V, Capacity 8 Ah	02	276		
9 26 04 343 02 0	4014586896922	ProCORE 18 V 12.0 Ah AS battery pack, Current/Voltages 18 V, Capacity 12 Ah	02	276		
9 26 04 344 02 0	4014586896236	GBA 18 V 2.0 Ah AS battery pack, Current/Voltages 18 V, Capacity 2 Ah	02	276		
9 26 04 345 02 0	4014586896243	GBA 18 V 4.0 Ah AS battery pack, Current/Voltages 18 V, Capacity 4 Ah	02	276		
9 26 04 346 02 0	4014586896250	GBA 18 V 5.0 Ah AS battery pack, Current/Voltages 18 V, Capacity 5 Ah	02	276		
9 90 01 010 00 1	4014586871417	Machine base GX/GIS	13	_		

VIBRATION AND NOISE EMISSION VALUES

Part number	Sound pressure level LpA (dB)	Uncertainty of measured value KpA (dB)	Sound power level LWA (dB)	Uncertainty of measured value KWA (dB)	Sound peak value LpCpeak (dB)	Uncertainty of measured value KpCpeak (dB)	Vibration value 1 ahv 3-way (m/s²)	Uncertainty of measured value Kα (m/s²)	Vibration value 2 dhv 3-way (m/s²)
7 112 62 60 00 0	81,0	3	92,0	3	95,0	3	<1,8	1,5	
7 112 63 60 00 0	81,0	3	92,0	3	95,0	3	<1,8	1,5	
7 112 64 60 00 0	81,0	3	92,0	3	95,0	3	<1,8	1,5	
7 112 66 60 00 0	81,0	3	92,0	3	95,0	3	<1,8	1,5	
7 112 70 60 00 0	81,0	3	92,0	3	95,0	3	<1,8	1,5	
7 113 11 63 00 0	73	3	84	3	92	3	1	1,5	
7 113 22 64 00 0	76	3	87	3	89	3	αh,D 1,5	1,5	αh 0,6
7 113 23 64 00 0	91	3	102	3	107	3	αh,D 1,5	1,5	αh 0,5
7 115 06 64 00 0	96,1	3	107,1	3	118,2	3	αh 16,1	1,5	
7 115 07 64 00 0	93,8	3	104,8	3	114,5	3	αh 12,9	1,5	
7 115 08 64 00 0	93,6 dB	3 dB	104,6 dB	3 dB	119,5 dB	3 dB	12,9 m/s ²	1,5 m/s ²	
7 116 11 64 00 0	73	3	84	3	86	3	αh,D 1,5	1,5	
7 122 01 61 00 0	86	3	97	3	100	3	αh,AG 4,6	1,5	αh,DS 1,8
7 122 02 61 00 0	86	3	97	3	99	3	4,7	1,5	1,4
7 122 03 61 00 0	86	3	97	3	99	3	4,4	1,5	1,4
7 122 04 61 00 0	86	3	97	3	99	3	4,9	1,5	1,5
7 122 05 61 00 0 7 122 05 62 00 0	80	3	91	3	94	3	8,8	1,5	2,1
7 122 05 62 00 0	80	3	91	3	94	3	7,7	1,5	2,1
7 122 06 61 00 0	80	3	91	3	94	3	7,7	1,5	1,8
7 122 07 61 00 0	79	3	90	3			7,0	1,5	3,5
7 122 09 61 00 0	92	3	81	3			4	1,5	1,5
7 123 04 61 00 0	83	3	94	3	97	3	αh,SG (Ø 50 mm) 9,0	1,5	αh,SG (Ø 25 mm) 4,7
7 123 05 61 00 0	82	3	93	3	96	3	αh,SG (Ø 50 mm) 13,7	1,5	αh,SG (Ø 25 mm) 6,2
7 123 06 61 00 0	83	3	94	3	97	3	αh,SG (Ø 50 mm) 3,2	1,5	αh,SG (Ø 25 mm) 1,2
7 129 37 63 00 0	77,0	3,0	85,0	3,0	90,3	3,0		1,5	
7 129 37 64 00 0	77,0	3,0	85,0	3,0	90,3	3,0		1,5	
7 130 05 61 00 0	74,3	3	85,3	3	87,6	3	αh 4,6	1,5	
7 130 05 62 00 0	74,3	3	85,3	3	87,6	3	αh 4,6	1,5	
7 130 05 63 00 0	74,3	3	85,3	3	87,6	3	αh 4,6	1,5	
7 130 05 64 00 0	74,3	3	85,3	3	87,6	3	αh 4,6	1,5	
7 130 06 61 00 0	74,2	3	85,2	3	86,0	3	αh 5,2	1,5	
7 130 06 62 00 0	74,2	3	85,2	3	86,0	3	αh 5,2	1,5	
7 130 06 63 00 0	74,2	3	85,2	3	86,0	3	αh 5,2	1,5	
7 130 06 64 00 0	74,2	3	85,2	3	86,0	3	αh 5,2	1,5	
7 132 10 61 00 0	82,2	3	93,2	3	103,3	3	αh 3,8	1,5	
7 132 10 62 00 0	82,2	3	93,2	3	103,3	3	αh 3,8	1,5	
7 132 10 63 00 0	82,2	3	93,2	3	103,3	3	αh 3,8	1,5	
7 132 10 64 00 0 7 132 11 61 00 0	82,2 87,8	3	98,8	3	103,3	3	αh 3,8 αh 12,1	1,5	
7 132 11 61 00 0	87,8	3	98,8	3	109,6	3	αh 12,1	1,5	
7 132 11 63 00 0	87,8	3	98,8	3	109,6	3	αh 12,1	1,5	
7 132 11 64 00 0	87,8	3	98,8	3	109,6	3	αh 12,1	1,5	
7 138 02 62 00 0	85	3	96	3	100	3	3,1	1,5	4,5
7 138 05 61 00 0	85	3	96	3	100	3	3,1	1,5	4,5
7 138 05 62 00 0	85	3	96	3	100	3	3,1	1,5	4,5
7 138 05 63 00 0	85	3	96	3	100	3	3,1	1,5	4,5
7 140 01 64 00 0	88,4	3	99,4	3	105,8	3	αh,D 4,2	1,5	αh,D 11,8
7 146 01 61 00 0	70	3	80	3					
7 170 03 61 00 0	82,4	3	93,4	3	97,1	3	αh,D 0,6	1,5	
7 170 04 61 00 0	82,4	3	93,4	3	97,1	3	αh,D 0,6	1,5	
7 170 04 62 00 0	82,4	3	93,4	3	97,1	3	αh,D 0,6	1,5	
7 170 04 63 00 0	82,4	3	93,4	3	97,1	3	αh,D 0,6	1,5	
7 170 04 64 00 0	82,4	3	93,4	3	97,1	3	αh,D 0,6	1,5	
7 170 04 65 00 0	82,4	3	93,4	3	97,1	3	αh,D 0,6	1,5	
7 170 04 66 00 0	82,4	3	93,4	3	97,1	3	αh,D 0,6	1,5	
7 202 51 60 00 0	79,1	3	90,1	3	93,4	3	1,1	1,5	

VIBRATION AND NOISE EMISSION VALUES

Part number	Sound pressure level LpA (dB)	Uncertainty of measured value KpA (dB)	Sound power level LWA (dB)	Uncertainty of measured value KWA (dB)	Sound peak value LpCpeak (dB)	Uncertainty of measured value KpCpeak (dB)	Vibration value 1 ahv 3-way (m/s²)	Uncertainty of measured value Ka (m/s²)	Vibration value 2 chv 3-way (m/s ⁸)
7 205 47 60 00 0	81,1	3	92,1	3	95,2	3	αh,D 2.4	1,5	
7 205 49 60 00 0	82,1	3	93,1	3	95,6	3	αh,D 1.9	1,5	
7 205 51 60 00 0	82	3	93	3	96	3	3	1,5	
7 205 52 60 00 0	82	3	93	3	96	3	αh,D 4,0	1,5	
7 205 52 61 00 0	82	3	93	3	96	3	αh,D 4,0	1,5	
7 205 53 60 00 0	82	3	93	3	96	3	αh,D 3,0	1,5	
7 205 53 61 00 0	82	3	93	3	96	3	αh,D 3,0	1,5	
7 205 54 60 00 0	82	3	93	3	96	3	αh,D 3,0	1,5	
7 205 54 61 00 0	82	3	93	3	96	3	αh,D 3,0	1,5	
7 205 55 60 00 0	82	3	93	3	96	3	αh,D 3,0	1,5	
7 205 55 61 00 0	82	3	93	3	96	3	αh,D 3,0	1,5	
7 209 38 60 00 0	82	3	93	3	96	3	3,0	1,5	
7 221 48 00 23 0	84	3	95	3	100	3	αh,P 2,5	1,5	αh,SG 2,5
7 221 48 50 01 0	84	3	95	3	100	3	αh,P 2,5	1,5	αh,SG 2,5
7 221 48 51 01 0	84	3	95	3	100	3	αh,P 2,5	1,5	αh,SG 2,5
7 221 48 60 00 0	84	3	95	3	100	3	αh,P 2,5	1,5	αh,SG 2,5
7 221 49 00 23 0	84	3	95	3	100	3	αh,P 3,5	1,5	αh,SG 2,5
7 221 49 50 01 0	84	3	95	3	100	3	αh,P 3,5	1,5	αh,SG 2,5
7 221 49 51 01 0	84	3	95	3	100	3	αh,P 3,5	1,5	αh,SG 2,5
7 221 63 00 23 0	84	3	95	3	100	3	αh,P 3,5	1,5	αh,SG 2,5
7 221 63 51 01 0	84	3	95	3	100	3	αh,P 3,5	1,5	αh,SG 2,5
7 221 67 60 00 0	85	3	96	3	101	3	αh,P/T=3 2,5	1,5	αh,P/T=6 5,0
7 221 98 60 00 0	91	3	102	3	105	3	αh,AG 6,5	1,5	αh,DS 3,5
7 222 67 60 00 0	86	3	97	3	102	3	5,1	1,5	1,7
7 222 67 62 00 0	86	3	97	3	102	3	5,1	1,5	1,7
7 222 75 60 00 0	94,1	3	102,3	3	107,9	3	5,9	1,5	
7 222 75 61 00 0	94,1	3	102,3	3	107,9	3	5,9	1,5	
7 222 76 60 00 0	86	3	97	3	102	3	5,1	1,5	1,7
7 222 77 60 00 0	86	3	97	3	101	3	4,2	1,5	1,7
7 222 78 60 00 0	87	3	98	3	106	3	4,2	1,5	2,5
7 222 79 60 00 0	91	3	102	3			8,5	1,5	3
7 222 80 60 00 0	91	3	102	3			6	1,5	2
7 222 81 60 00 0	92	3	103	3			6	1,5	4
7 222 82 60 00 0	92	3	103	3			5	1,5	2
7 222 83 60 00 0	92	3	103	3			7	1,5	2,5
7 222 85 60 00 0	86	3	97	3	101	3	4,2	1,5	2,1
7 222 86 60 00 0	86	3	97	3	101	3	4,2	1,5	2,1
7 223 16 60 00 0	84	3	95	3	97	3	4,7	1,5	
7 223 17 60 00 0	84	3	95	3	97	3	4,7	1,5	7,9
7 223 19 60 00 0	84	3	95	3	97	3	5,3	1,5	11,4
7 223 20 60 00 0	84	3	95	3	97	3	1,9	1,5	2,9
7 223 22 60 00 0	85	3	96	3	98	3	9,7	1,5	
7 223 23 60 00 0	85	3	96	3	98	3	1,5	1,5	4,5
7 223 24 60 00 0	83	3	94	3	95	3	4,8	1,5	
7 223 25 60 00 0	83	3	94	3	95	3	1,0	1,5	
7 228 05 50 00 0	84	3	95	3	99	3	2	1,5	
7 228 05 51 00 0	84	3	95	3	99	3	2		
7 229 67 69 00 0	72	3	83	3	84	3			
7 229 67 70 00 0	72	3	83	3	84	3			
7 229 68 63 00 0	85	3	96	3	97	3			
7 229 68 64 00 0	85	3	96	3	97	3			
7 229 69 62 00 0	82	3	93	3	96	3			
7 229 69 63 00 0	82	3	93	3	96	3			
7 229 70 64 00 0	85,0	3	96,0	3	97,0	3			
7 229 70 65 00 0	85	3	96	3	97	3			
7 229 70 66 00 0	82	3	93	3	96	3			
7 229 72 64 00 0	74	3	85	3	96	3			

VIBRATION AND NOISE EMISSION VALUES

Doub worsth ou	Sound pressure level LpA (dB)	Uncertainty of measured value KpA (dB)	Sound power level LWA (dB)	Uncertainty of measured value KWA (dB)	Sound peak value LpCpeak (dB)	Uncertainty of measured value KpCpeak (dB)	Vibration value 1 dhv 3-way (m/s²)	Uncertainty of measured value Κα (m/s²)	Vibration value 2 dhv 3-way (m/s²)
Part number 7 230 31 61 00 0	81,1	3	92,1	3	93,3	3	5,7	1,5	> N €
7 230 31 62 00 0	81,1	3	92,1	3	93,3	3	5,7	1,5	
7 230 31 62 00 0	81,1	3	92,1	3	93,3	3	5,7	1,5	
7 230 32 61 00 0		3		3		3	5,7		
	81,1	3	92,1		93,3	3		1,5	
7 230 33 61 00 0	76,2		87,2	3	91		10,8	1,5	
7 230 33 62 00 0	76,2	3	87,2	3	91	3	10,8	1,5	
7 230 34 61 00 0	82,5	3	93,5	3	94,9	3	4,1	1,5	
7 230 34 62 00 0	82,5	3	93,5	3	94,9	3	4,1	1,5	
7 230 35 61 00 0	81,7	3	92,7	3	93,8	3	4,8	1,5	
7 230 35 62 00 0	81,7	3	92,7	3	93,8	3	4,8	1,5	<u>-</u>
7 232 38 60 00 0	82	3	93	3	93	3	8,8	1,5	
7 232 38 61 00 0	82	3	93	3	93	3	8,8	1,5	
7 232 39 60 00 0	82	3	93	3	93	3	8,8	1,5	
7 232 40 60 00 0	80	3	91	3	91	3	7,3	1,5	
7 232 40 61 00 0	80	3	91	3	91	3	7,3	1,5	
7 232 41 60 00 0	82	3	93	3	93	3	9,5	1,5	
7 232 41 61 00 0	82	3	93	3	93	3	9,5	1,5	
7 232 42 60 00 0	82	3	93	3	93	3	6,8	1,5	
7 232 42 61 00 0	82	3	93	3	93	3	6,8	1,5	
7 232 46 61 00 0	92,1	3	100,1	3	110,5	3	10,5	1,5	
7 232 47 61 00 0	95,8	3	103,8	3	112,4	3	12,4	1,5	
7 234 23 00 23 0	89	3	100	3	102	3	7	1,5	
7 236 54 60 00 0	95,3	3	106,3	3	110,9	3	$\alpha h = 2.7$	1,5	
7 238 16 61 00 0	90	3	101	3	104	3	αh, 5,4	1,5	αh, 6,2
7 238 18 61 00 0	90	3	101	3	104	3	αh, 3,7	1,5	αh, 4,3
7 245 01 60 00 0	93,1	3,0	104,1	3,0	107,4	3,0			
7 245 02 60 00 0	92,9	3,0	103,9	3,0	107,2	3,0			
7 270 40 61 00 0	82,1	5	93,1	5	96,2	5	< 2,5	1,5	
7 270 41 61 00 0	82,1	5	93,1	5	96,2	5	< 2,5	1,5	
7 270 42 61 00 0	82,1	5	93,1	5	96,2	5	< 2,5	1,5	
7 270 43 61 00 0	81,6	5	92,6	5	95,2	5	< 2,5	1,5	
7 270 51 60 00 0	88,5	3	99,5	3	102,5	3	αh,D <2,5	1,5	
7 270 53 61 00 0	82,3	5	93,3	5	95,9	5	αh,D <2,5	1,5	
7 270 54 61 00 0	82,3	5	93,3	5	95,9	5	αh,D <2,5	1,5	
7 270 54 63 00 0	86,7	3	97,7	3	101,2	3	αh,D <2,5	1,5	
7 270 54 64 00 0	86,7	3	97,7	3	101,2	3	αh,D <2,5	1,5	
7 270 55 61 00 0	82,3	5	93,3	5	95,9	5	αh,D <2,5	1,5	
7 270 56 61 00 0	82,3	5	93,3	5	95,9	5	αh,D <2,5	1,5	
7 270 57 61 00 0	83,2	5	94,2	5	96,8	5	αh,D <2,5	1,5	
7 270 58 61 00 0	83,2	5	94,2	5	96,8	5	αh,D <2,5	1,5	
7 270 60 61 00 0	86,0	5	97,0	5	98,5	5	αh,D = 1,4	1,5	
7 270 71 61 00 0	86,7	3	97,7	3	101,2	3	<2,5	1,5	
7 270 72 61 00 0	86,7	3	97,7	3	101,2	3	<2,5	1,5	
7 273 23 62 00 0	95,3	5	103,3	5	106,3	5	αh,D = <2,5	1,5	
7 273 23 63 00 0	95,3	5	103,3	5	106,3	5	αh,D = <2,5	1,5	
7 273 23 64 00 0	95,3	5	103,3	5	106,3	5	αh,D = <2,5	1,5	
7 273 23 65 00 0	95,3	5	103,3	5	106,3	5	αh,D = <2,5	1,5	
7 273 25 61 00 0	82,1	5	93,1	5	96,2	5	< 2,5	1,5	
7 273 26 61 00 0	81,6	5	92,6	5	95,2	5	< 2,5	1,5	
7 273 27 61 00 0	82,1	5	93,1	5	96,2	5	< 2,5 m/s ²	1,5 m/s ²	
7 534 08 00 00 0	81	3	92	3	102	3	αh,D 7,1	1,5	
7 536 03 00 01 0	82	3	93	3		3			
9 20 29 060 00 0	67,0	3	81,0	3			< 2,5		1,5
9 20 30 060 00 0	67	2	81	2			< 2,5		
9 20 31 060 00 0	67	2	81	2			< 2,5		
9 20 32 060 00 0	67	2	81	2			< 2,5		
-									











	AMM 300 PLUS	AMM 500 PLUS	MM 300 PLUS	MM 500 PLUS
	VC	VC	VC	VC
6 35 02 097	0	0	2	0
6 35 02 106	0	0	2	0
6 35 02 113	0	0	2	0
6 35 02 114	0	0	1	0
6 35 02 118	0	0	2	0
6 35 02 125	0	0	1	0
6 35 02 126	1	1	4	1
6 35 02 127	1	1	5	1
6 35 02 133	1	1	4	1
6 35 02 134	1	1	5	1
6 35 02 151	1	1	4	1
6 35 02 152	1	1	5	1
6 35 02 157	1	1	3	0
6 35 02 160	1	1	4	1
6 35 02 161	1	1	5	1
6 35 02 166	1	1	2	0
6 35 02 169	1	1	3	0
6 35 02 170	1	1	3	0
6 35 02 174	0	0	3	0
6 35 02 175	1	1	3	0
6 35 02 176	1	1	3	0
6 35 02 183	1	1	4	1
6 35 02 184	0	0	3	0
6 35 02 187	1	1	3	0
6 35 02 188	1	1	2	0
6 35 02 191	1	1	4	1
6 35 02 193	1	1	4	1
6 35 02 196	1	1	3	0
6 35 02 198	1	1	4	1
6 35 02 199	1	1	5	1
6 35 02 205	1	1	4	1
6 35 02 206	1	1	4	1
6 35 02 207	1	1	5	1
6 35 02 208	1	1	5	1
6 35 02 214	1	1	3	0
6 35 02 216	0	0	2	0
6 35 02 217	1	1	2	0
6 35 02 219	1	1	3	0
6 35 02 221	1	1	5	1
6 35 02 222	1	1	4	1
6 35 02 223	1	1	4	1
6 35 02 225	1	1	4	1
6 35 02 226	1	1		
			4	1
6 35 02 227	1	1	5	1
6 35 02 228	1	1	5	1
6 35 02 229	1	1	5	1
6 35 02 230	1	1	5	1
6 35 02 231	1	1	5	1
6 35 02 232	1	1	4	1
6 35 02 233	1	1	4	1
6 35 02 236	1	1	4	1
6 35 02 237	1	1	5	1
0 33 02 237	I	<u> </u>	J	I











	AMM 300 PLUS	AMM 500 PLUS	MM 300 PLUS	MM 500 PLUS
	VC	VC	VC	VC
6 37 06 019	0	0	3	0
6 37 19 011	1	1	4	1
6 37 31 001	1	0	2	0
6 37 31 002	1	0	1	0
6 38 06 129	0	0	1	0
6 38 06 136	0	0	1	0
6 38 06 140	0	0	1	0
6 38 06 141	0	0	1	0
6 38 06 142	0	0	1	0
6 38 06 159	0	0	1	0
6 38 06 195	1	3	3	1
6 38 06 204	1	3	3	1
6 38 10 031	2	3	5	1
6 39 03 165	0	0	3	0
6 39 03 200	0	0	2	0
6 39 03 201	0	0	2	0
6 39 03 202	0	0	2	0
6 39 03 226	1	1	4	1
6 39 03 233	0	0	2	0
6 39 03 234	1	2	4	1
6 39 03 235	1	1	3	0
6 39 03 245	0	0	3	0
6 39 03 251	0	1	2	0









	MM 700 MAX	AMM 700 MAX		MM 700 MAX	AMM 700 MAX
	VC	VC		VC	VC
6 35 02 097	0	0	6 35 02 224	1	2
6 35 02 106	0	0	6 35 02 225	1	1
6 35 02 113	0	0	6 35 02 226	1	1
6 35 02 114	0	0	6 35 02 227	1	2
6 35 02 118	0	0	6 35 02 228	1	2
6 35 02 125	0	0	6 35 02 229	1	2
6 35 02 126	1	1	6 35 02 230	1	2
6 35 02 127	1	2	6 35 02 231	1	2
6 35 02 133	1	1	6 35 02 232	1	1
6 35 02 134	1	2	6 35 02 233	1	1
6 35 02 151	1	1	6 35 02 236	1	1
6 35 02 152	1	1	6 35 02 237	1	1
6 35 02 157	1	1	6 35 02 238	1	2
6 35 02 160	1	1	6 37 06 019	0	0
6 35 02 161	1	2	6 37 19 011	1	1
6 35 02 166	0	1	6 37 31 001	0	0
6 35 02 169	0	1	6 37 31 002	0	0
6 35 02 170	0	1	6 37 31 006	1	1
6 35 02 174	0	0	6 38 06 129	0	0
6 35 02 175	0	1	6 38 06 136	0	0
6 35 02 176	0	1	6 38 06 140	0	0
6 35 02 183	1	1	6 38 06 141	0	0
6 35 02 184	0	0	6 38 06 142	0	0
6 35 02 187	0	1	6 38 06 159	0	0
6 35 02 188	0	1	6 38 06 195	0	2
6 35 02 191	1	1	6 38 06 204	0	2
6 35 02 193	1	1	6 38 10 031	1	3
6 35 02 196	1	1	6 39 03 165	0	0
6 35 02 198	1	1	6 39 03 200	0	0
6 35 02 199	1	1	6 39 03 201	0	0
6 35 02 200	1	2	6 39 03 202	0	0
6 35 02 201	1	2	6 39 03 226	1	1
6 35 02 202	1	2	6 39 03 233	0	0
6 35 02 203	1	2	6 39 03 234	1	2
6 35 02 204	1	1	6 39 03 235	0	1
6 35 02 205	1	1	6 39 03 236	2	2
6 35 02 206	1	1	6 39 03 237	1	1
6 35 02 207	1	1	6 39 03 238	1	1
6 35 02 208	1	2	6 39 03 239	2	2
6 35 02 213	0	1	6 39 03 240	1	1
6 35 02 214	0	1	6 39 03 241	1	1
6 35 02 215	0	1	6 39 03 242	1	1
6 35 02 216	0	0	6 39 03 243	1	1
6 35 02 217	0	1	6 39 03 244	1	1
6 35 02 218	0	1	6 39 03 245	0	0
6 35 02 219	0	1	6 39 03 246	3	3
6 35 02 219	0	1	6 39 03 247	3	3
6 35 02 220	1	1	6 39 03 248	3	3
6 35 02 221	1	1	6 39 03 251	0	0
			0 37 03 231	U	U
6 35 02 223	1	1			











	MM 700-1.7 MM 700-1.7Q	AMM 700-1.7Q		MM 700-1.7 MM 700-1.7Q	AMM 700-1.7Q		MM 700-1.7 MM 700-1.7Q	AMM 700-1.7Q
	VC	VC		VC	VC		VC	VC
6 35 02 102	0	0	6 38 06 140	0	1	6 39 03 154	1	1
6 35 02 103	0	1	6 38 06 141	0	1	6 39 03 155	1	1
6 35 02 115	0	1	6 38 06 195	0	1	6 39 03 156	1	1
6 35 02 116	0	1	6 38 06 204	0	1	6 39 03 157	1	1
6 35 02 119	1	0	6 39 03 072	1	0	6 39 03 160	2	2
6 35 02 120	1	1	6 39 03 073	1	0	6 39 03 161	1	1
6 35 02 121	1	1	6 39 03 076	1	0	6 39 03 162	1	1
6 35 02 122	1	1	6 39 03 079	1	0	6 39 03 163	1	0
6 35 02 123	1	1	6 39 03 081	2	2	6 39 03 166	1	1
6 35 02 124	1	1	6 39 03 082	1	1	6 39 03 168	2	2
6 35 02 135	1	1	6 39 03 083	1	0	6 39 03 169	2	2
6 35 02 136	1	1	6 39 03 087	1	0	6 39 03 170	2	2
6 35 02 138	1	1	6 39 03 095	1	0	6 39 03 170	2	2
6 35 02 147	1	1	6 39 03 097	1	1	6 39 03 171	1	0
6 35 02 147	1	1	6 39 03 097	2	2	6 39 03 172	1	0
6 35 02 146	0	1	6 39 03 101	1	1	6 39 03 173	1	1
6 35 02 153	0	_	6 39 03 101	-	-	6 39 03 174	-	
		0		1	0		1	1
6 35 02 162	1	1	6 39 03 104	1	0	6 39 03 179	2	2
6 35 02 163	1	1	6 39 03 105	1	1	6 39 03 181	1	1
6 35 02 164	1	1	6 39 03 107	1	1	6 39 03 182	3	3
6 35 02 165	1	1	6 39 03 108	1	0	6 39 03 183	1	0
6 35 02 167	0	1	6 39 03 109	1	0	6 39 03 184	1	0
6 35 02 168	0	1	6 39 03 110	1	0	6 39 03 185	1	0
6 35 02 172	0	1	6 39 03 111	2	2	6 39 03 186	1	0
6 35 02 173	0	1	6 39 03 113	1	1	6 39 03 189	1	1
6 35 02 177	0	1	6 39 03 114	1	1	6 39 03 190	2	2
6 35 02 178	0	1	6 39 03 115	1	0	6 39 03 191	1	1
6 35 02 179	0	1	6 39 03 116	2	2	6 39 03 194	2	2
6 35 02 183	1	2	6 39 03 117	2	2	6 39 03 195	2	2
6 35 02 185	1	1	6 39 03 118	1	0	6 39 03 196	1	1
6 35 02 186	0	0	6 39 03 120	1	0	6 39 03 198	2	2
6 35 02 189	0	1	6 39 03 121	1	0	6 39 03 206	1	1
6 35 02 190	0	1	6 39 03 122	1	0	6 39 03 207	1	1
6 35 02 192	1	1	6 39 03 123	2	2	6 39 03 208	1	1
6 35 02 194	1	1	6 39 03 124	1	0	6 39 03 209	1	1
6 35 02 195	1	1	6 39 03 125	2	2	6 39 03 210	1	1
6 35 02 196	0	1	6 39 03 127	1	0	6 39 03 211	1	1
6 35 02 209	1	1	6 39 03 128	1	1	6 39 03 212	1	0
6 35 02 210	1	1	6 39 03 129	1	1	6 39 03 217	1	1
6 35 02 211	1	1	6 39 03 131	1	1	6 39 03 221	3	3
6 35 02 212	1	1	6 39 03 132	1	1	6 39 03 222	3	3
6 35 02 234	1	1	6 39 03 133	1	1	6 39 03 223	3	3
6 35 02 235	1	1	6 39 03 143	2	2	6 39 03 227	1	1
6 37 06 018	0	1	6 39 03 144	1	1	6 39 03 228	3	3
6 37 31 001	0	0	6 39 03 146	1	1	6 39 03 229	2	2
6 37 31 002	0	0	6 39 03 147	1	0	6 39 03 230	3	3
6 37 31 005	0	1	6 39 03 152	1	1	6 39 03 231	2	2
6 38 06 129	0	1	6 39 03 153	1	1			
6 38 06 136	0	1						



Imprint:
DE: C. & E. Fein GmbH (District Court Ulm, HRB 702155), Hans-Fein-Straße 81, 73529 Schwäbisch Gmünd-Bargau Managing Director: Dr. Christoph Weiß

Effective from 01/2024 Subject to print errors and modifications concerning technique, shape and layout. St.-Nr. 83085 / 02398, WEEE Reg-Nr. DE 32503249